Learning Long-Term Reward Redistribution via Randomized Return Decomposition

Abstract

Many practical applications of reinforcement learning require agents to learn from sparse and delayed rewards. It highlights a fundamental problem called long-term temporal credit assignment that challenges the ability of agents to tackle delayed environmental feedback. In this paper, we consider the problem formulation of episodic reinforcement learning with trajectory feedback. It refers to an extreme delay of reward signals, in which the agent can only obtain one reward signal at the end of each trajectory. A popular paradigm for this problem setting is learning with a designed auxiliary dense reward function, namely proxy reward, instead of sparse environmental signals. Based on this framework, this paper proposes a novel reward redistribution algorithm, randomized return decomposition (RRD), to learn a proxy reward function for episodic reinforcement learning. We establish a surrogate problem by Monte-Carlo sampling that scales up regression-based reward redistribution to long-horizon problems. We analyze our surrogate loss function by connection with existing methods in the literature, which illustrates the algorithmic properties of our approach. In experiments, we extensively evaluate our proposed method on a variety of benchmark tasks with episodic rewards and demonstrate substantial improvement over baseline algorithms.

1 Introduction

Scaling reinforcement learning (RL) algorithms to practical applications has become the focus of numerous recent studies, including resource management (Mao et al., 2016), industrial control (Hein et al., 2017), drug discovery (Popova et al., 2018), and recommendation systems (Chen et al., 2018). One of the challenges in these real-world problems is the sparse and delayed environmental rewards. For example, in the molecular structure design problem, the target molecule property can only be evaluated after completing the whole sequence of modification operations (Zhou et al., 2019). The sparsity of environmental feedback would complicate the attribution of rewards on agent actions and therefore can hinder the efficiency of learning (Rahmandad et al., 2009). In practice, it is a common choice to formulate the RL objective with a meticulously designed reward function instead of the sparse environmental rewards. The design of such a reward function is crucial to the performance of the learned polices. Most standard RL frameworks, such as temporal difference learning and policy gradient methods, require the reward function to provide instant feedback for every step of environment transitions. Designing such dense reward functions is not a simple problem even with domain knowledge and human supervision. It has been widely observed in prior works that handcrafted heuristic reward functions may lead to unexpected and undesired behaviors (Randløv & Alstrøm, 1998; Bottou et al., 2013; Andrychowicz et al., 2017). The agent may find a shortcut solution that formally optimizes the given objective but deviates from the desired polices (Dewey, 2014; Amodei et al., 2016). The reward designer can hardly anticipate all potential side effects of the designed reward function, which highlights the difficulty of reward engineering.

To avoid the unintended behaviors induced by misspecified reward engineering, a common paradigm is considering the reward design as an online problem within the trial-and-error loop of reinforcement learning (Sorg et al., 2010). This algorithmic framework contains two components, namely reward modeling and policy optimization. The agent first learns a proxy reward function from the experience data and then optimizes its policy based on the learned per-step rewards. By iterating this procedure and interacting with the environment, the agent is able to continuously refine its reward model so that the learned proxy reward function can better approximate the actual objective given

by the environmental feedback. More specifically, we aim to redistribute the sparse and delayed environmental rewards to a dense Markovian reward function without misspecifying the goal of the given task.

In this paper, we propose a novel reward redistribution algorithm built upon a classical mechanism called *return decomposition* (Arjona-Medina et al., 2019). The basic idea of return decomposition is training a regression model that decomposes the trajectory return to the summation of per-step proxy rewards. This paradigm is a promising approach to the long-term credit assignment for redistributing sparse environmental feedback. Our proposed approach, *randomized return decomposition* (RRD), establish a surrogate optimization of return decomposition to improve the scalability in long-horizon tasks. In this surrogate problem, the reward model is trained to predict the episodic return from a random subsequence of the agent trajectory, i.e., we conduct a structural constraint that the learned proxy rewards can approximately reconstruct environmental trajectory return from a small subset of state-action pairs. This design enables us to conduct return decomposition effectively by mini-batch training. Our analysis shows that our surrogate loss function is an upper bound of the original loss of deterministic return decomposition, which gives a theoretical interpretation of this randomized implementation. We also present how the surrogate gap can be controlled and draw connections to another method called uniform credit assignment. In experiments, we demonstrate substantial improvement of our proposed approach over baseline algorithms on a suite of MuJoCo benchmark tasks with episodic rewards.

2 BACKGROUND

2.1 EPISODIC REINFORCEMENT LEARNING WITH TRAJECTORY FEEDBACK

In standard reinforcement learning settings, the environment model is usually formulated by a *Markov decision process* (MDP; Bellman, 1957), defined as a tuple $\mathcal{M} = \langle \mathcal{S}, \mathcal{A}, P, R, \mu \rangle$, where $\mathcal{S}$ and $\mathcal{A}$ denote the spaces of environment states and agent actions. $P(s'|s, a)$ and $R(s, a)$ denote the unknown environment transition and reward functions. μ denotes the initial state distribution. The goal of reinforcement learning is to find a policy $\pi : \mathcal{S} \to \mathcal{A}$ maximizing cumulative rewards. More specifically, a common objective is maximizing infinite-horizon discounted rewards based on a pre-defined discount factor γ as follows:

$$\text{(standard objective)} \quad J(\pi) = \mathbb{E}\left[\sum_{t=0}^{\infty} \gamma^t R(s_t, \pi(s_t)) \ \middle| \ s_0 \sim \mu, \ s_{t+1} \sim P(\cdot \mid s_t, \pi(s_t)) \right]. \quad (1)$$

In this paper, we consider the episodic reinforcement learning setting with trajectory feedback, in which the agent can only obtain one reward feedback at the end of each trajectory. Let τ denote an agent trajectory that contains all experienced states and behaved actions within an episode. We assume all trajectories terminate in finite steps. The episodic reward function $R_{\text{ep}}(\tau)$ is defined on the trajectory space, which represents the overall performance of trajectory τ. The goal of episodic reinforcement learning is to maximize the expected trajectory return:

$$\text{(episodic objective)} \quad J_{\text{ep}}(\pi) = \mathbb{E}\left[R_{\text{ep}}(\tau) \ \middle| \ s_0 \sim \mu, \ a_t = \pi(s_t), \ \tau = \langle s_0, a_0, s_1, \cdots, s_T \rangle \right]. \quad (2)$$

In general, the episodic-reward setting is a particular form of *partially observable Markov decision processes* (POMDPs) where the reward function is non-Markovian. The worst case may require the agent to enumerate the entire exponential-size trajectory space for recovering the episodic reward function. In practical problems, the episodic environmental feedback usually has structured representations. A common structural assumption is the existence of an underlying Markovian reward function $\widehat{R}(s, a)$ that approximates the episodic reward $R_{\text{ep}}(\tau)$ by a sum-form decomposition,

$$\text{(sum-decomposable episodic reward)} \quad R_{\text{ep}}(\tau) \approx \widehat{R}_{\text{ep}}(\tau) = \sum_{t=0}^{T-1} \widehat{R}(s_t, a_t). \quad (3)$$

This structure is commonly considered by both theoretical (Efroni et al., 2021) and empirical studies (Liu et al., 2019; Raposo et al., 2021) on long-term credit assignment. It models the situations where the agent objective is measured by some metric with additivity properties, e.g., the distance of robot running, the time cost of navigation, or the number of products produced in a time interval.

2.2 REWARD REDISTRIBUTION

The goal of *reward redistribution* is constructing a proxy reward function $\widehat{R}(s_t, a_t)$ that transforms the episodic-reward problem stated in Eq. (2) to a standard dense-reward setting. By replacing environmental rewards with such a Markovian proxy reward function $\widehat{R}(s_t, a_t)$, the agent can be trained to optimize the discounted objective in Eq. (1) using any standard RL algorithms. Formally, the proxy rewards $\widehat{R}(s_t, a_t)$ form a sum-decomposable reward function $\widehat{R}_{\text{ep}}(\tau) = \sum_{t=0}^{T-1} \widehat{R}(s_t, a_t)$ that is expected to have high correlation to the environmental reward $R_{\text{ep}}(\tau)$. Here, we introduce two branches of existing reward redistribution methods, *return decomposition* and *uniform credit assignment*, which are the most related to our proposed approach. We defer the discussions of other related work to section 5.

Return Decomposition. The idea of *return decomposition* is training a reward model that predicts the trajectory return with a given state-action sequence (Arjona-Medina et al., 2019). The reward redistribution is given by the learned reward model, i.e., decomposing the environmental episodic reward $R_{\text{ep}}(\tau)$ to a Markovian proxy reward function $\widehat{R}(s, a)$. In practice, the reward modeling is formulated by solving a least-squares problem optimizing the following loss function:

$$\mathcal{L}_{\text{RD}}(\theta) = \mathbb{E}_{\tau \sim \mathcal{D}} \left[\left(R_{\text{ep}}(\tau) - \sum_{t=0}^{T-1} \widehat{R}_\theta(s_t, a_t) \right)^2 \right], \tag{4}$$

where $\widehat{R}_\theta$ denotes the parameterized proxy reward function, and $\mathcal{D}$ denotes the experience dataset collected by the agent. Assuming the sum-decomposable structure stated in Eq. (3), the least-squares estimation $\widehat{R}_\theta(s, a)$ is expected to asymptotically concentrate near the ground-truth underlying rewards $\widehat{R}(s, a)$ when the above loss function is properly optimized (Efroni et al., 2021).

One limitation of the return decomposition method specified by Eq. (4) is its scalability in terms of the computation costs. Note that the trajectory-wise episodic reward is the only environmental supervision for the reward modeling problem. Computing the loss function $\mathcal{L}_{\text{RD}}(\theta)$ with a single episodic reward label requires to enumerate all state-action pairs along the whole trajectory. This computation procedure can be expensive in numerous situations, e.g., when the task horizon T is quite long, or the state space $\mathcal{S}$ is high-dimensional. To address this practical barrier, recent works focus on designing reward redistribution mechanisms that can be easily integrated in complex tasks. We will discuss the implementation subtlety of existing methods in section 4.

Uniform Credit Assignment. To pursue a simple but effective reward redistribution mechanism, Gangwani et al. (2020) considers *uniform credit assignment* (UCA) which assumes all state-action pairs equally contribute to the return value. This method is designed to redistribute rewards in the absence of any prior structure or information. More specifically, the proxy reward $\widehat{R}_{\text{UCA}}(s, a)$ is computed by averaging episodic return values over all experienced trajectories containing (s, a),

$$\widehat{R}_{\text{UCA}}(s, a) = \mathbb{E}_{\tau \sim \mathcal{D}} \left[R_{\text{ep}}(\tau) \mid (s, a) \in \tau \right]. \tag{5}$$

In this paper, we will introduce a novel reward redistribution mechanism that bridges between return decomposition and uniform credit assignment.

3 REWARD REDISTRIBUTION VIA RANDOMIZED RETURN DECOMPOSITION

In this section, we introduce our approach, randomized return decomposition (RRD), which sets up a surrogate optimization problem of return decomposition. The proposed surrogate objective allows us to conduct return decomposition on short subsequences of agent trajectories, which can be easily applied in long-horizon tasks. We provide analyses to characterize the algorithmic property of our surrogate objective function and discuss connections to existing methods.

3.1 RANDOMIZED RETURN DECOMPOSITION WITH MONTE-CARLO RETURN ESTIMATION

One practical barrier to apply return decomposition methods in long-horizon tasks is the computation costs of the regression loss in Eq. (4), i.e., it requires to enumerate all state-action pairs within the

agent trajectory. To resolve this issue, we consider a randomized method that uses a Monte-Carlo estimator to compute the predicted episodic return $\widehat{R}_{\text{ep},\theta}(\tau)$ as follows:

$$\underbrace{\widehat{R}_{\text{ep},\theta}(\tau) = \sum_{t=0}^{T-1} \widehat{R}_\theta(s_t, a_t)}_{\text{Deterministic Computation}} = \underset{\mathcal{I} \sim \rho_T(\cdot)}{\mathbb{E}} \left[\frac{T}{|\mathcal{I}|} \sum_{t \in \mathcal{I}} \widehat{R}_\theta(s_t, a_t) \right] \approx \underbrace{\frac{T}{|\mathcal{I}|} \sum_{t \in \mathcal{I}} \widehat{R}_\theta(s_t, a_t)}_{\text{Monte-Carlo Estimation}} , \quad (6)$$

where $\rho_T(\cdot)$ denotes an unbiased sampling distribution. In this paper, without further specification, $\rho_T(\cdot)$ is constructed by uniformly sampling K distinct indices.

$$\rho_T(\cdot) = \text{Uniform}\left(\{ \mathcal{I} \subseteq \mathbb{Z}_T : |\mathcal{I}| = K \} \right), \quad (7)$$

where K is a hyper-parameter. In this sampling distribution, each timestep t has the same probability to be covered by the sampled subsequence $\mathcal{I} \sim \rho_T(\cdot)$ so that it gives an unbiased Monte-Carlo estimation of the episodic summation $\widehat{R}_{\text{ep},\theta}(\tau)$.

Randomized Return Decomposition. Based on the idea of using Monte-Carlo estimation shown in Eq. (6), we introduce our approach, *randomized return decomposition* (RRD), to improve the scalability of regression-based reward redistribution methods. The objective function of our approach is formulated by the randomized return decomposition loss $\mathcal{L}_{\text{Rand-RD}}(\theta)$ stated in Eq. (8), in which the parameterized proxy reward function $\widehat{R}_\theta$ is trained to predict the episodic return $R_{\text{ep}}(\tau)$ given a random subsequence of the agent trajectory. In other words, we integrate the Monte-Carlo estimator (see Eq. (6)) into the return decomposition loss to obtain the following surrogate loss function:

$$\mathcal{L}_{\text{Rand-RD}}(\theta) = \underset{\tau \sim \mathcal{D}}{\mathbb{E}} \left[\underset{\mathcal{I} \sim \rho_T(\cdot)}{\mathbb{E}} \left[\left(R_{\text{ep}}(\tau) - \frac{T}{|\mathcal{I}|} \sum_{t \in \mathcal{I}} \widehat{R}_\theta(s_t, a_t) \right)^2 \right] \right]. \quad (8)$$

In practice, the loss function $\mathcal{L}_{\text{Rand-RD}}(\theta)$ can be estimated by sampling a mini-batch of trajectory subsequences instead of computing $\widehat{R}_\theta(s_t, a_t)$ for the whole agent trajectory, and thus the implementation of randomized return decomposition is adaptive and flexible in long-horizon tasks.

3.2 ANALYSIS OF RANDOMIZED RETURN DECOMPOSITION

The main purpose of our approach is establishing a surrogate loss function to improve the scalability of regression-based return decomposition in practice. Our proposed method, randomized return decomposition, is a trade-off between the computation complexity and the estimation error induced by the Monte-Carlo estimator. In this section, we show that our approach is an interpolation between between the return decomposition paradigm and uniform credit assignment, which can be controlled by the hyper-parameter K used in the sampling distribution (see Eq. (7)). We present Theorem 1 as a formal characterization of our proposed surrogate objective function.

Theorem 1 (Loss Decomposition). *The surrogate loss function $\mathcal{L}_{\text{Rand-RD}}(\theta)$ can be decomposed to two terms interpolating between return decomposition and uniform credit assignment.*

$$\mathcal{L}_{\text{Rand-RD}}(\theta) = \mathcal{L}_{\text{RD}}(\theta) + \underset{\tau \sim \mathcal{D}}{\mathbb{E}} \left[\underbrace{\underset{\mathcal{I} \sim \rho_T(\cdot)}{\text{Var}} \left[\frac{T}{|\mathcal{I}|} \sum_{t \in \mathcal{I}} \widehat{R}_\theta(s_t, a_t) \right]}_{\text{variance of the Monte-Carlo estimator}} \right] \quad (9)$$

$$= \underbrace{\mathcal{L}_{\text{RD}}(\theta)}_{\text{return decomposition}} + \underset{\tau \sim \mathcal{D}}{\mathbb{E}} \left[T^2 \cdot \underbrace{\underset{(s_t, a_t) \sim \tau}{\text{Var}} \left[\widehat{R}_\theta(s_t, a_t) \right]}_{\text{uniform credit assignment}} \cdot \underbrace{\frac{1}{K} \left(1 - \frac{K-1}{T-1} \right)}_{\text{interpolation weight}} \right], \quad (10)$$

where K denotes the length of sampled subsequences defined in Eq. (7).

The proof of Theorem 1 is based on the bias-variance decomposition formula of mean squared error (Kohavi & Wolpert, 1996). The detailed proofs for statements presented in this section are deferred to Appendix A.

Interpretation as Regularization. As presented in Theorem 1, the randomized decomposition loss can be decomposed to two terms, the deterministic return decomposition loss $\mathcal{L}_{\text{RD}}(\theta)$ and a variance penalty term (see the second term of Eq. (9)). The variance penalty term can be regarded as a regularization that is controlled by hyper-parameter K. In practical problems, the objective of return decomposition is ill-posed, since the number of trajectory labels is dramatically less than the number of transition samples. There may exist solutions of reward redistribution that formally optimize the least-squares regression loss but serve little functionality to guide the policy learning. Regarding this issue, the variance penalty in randomized return decomposition is a regularizer for reward modeling. It searches for smooth proxy rewards that has low variance within the trajectory. This regularization effect is similar to the mechanism of uniform reward redistribution (Gangwani et al., 2020), which achieves state-of-the-art performance in the previous literature. In section 4, our experiments demonstrate that the variance penalty is crucial to the empirical performance of randomized return decomposition.

A Closer Look at Loss Decomposition. In addition to the intuitive interpretation of regularization, we will present a detailed characterization of the loss decomposition shown in Theorem 1. We interpret this loss decomposition as below:

1. Note that the Monte-Carlo estimator used by randomized return decomposition is an unbiased estimation of the proxy episodic return $\widehat{R}_{\text{ep},\theta}(\tau)$ (see Eq. (6)). This unbiased property gives the first component of the loss decomposition, i.e, the original return decomposition loss $\mathcal{L}_{\text{RD}}(\theta)$.

2. Despite the Monte-Carlo estimator is unbiased, its variance would contribute to an additional loss term induced by the mean-square operator, i.e., the second component of loss decomposition presented in Eq. (10). This additional term penalizes the variance of the learned proxy rewards under random sampling. This penalty expresses the same mechanism as uniform reward redistribution (Gangwani et al., 2020) in which the episodic return is uniformly redistributed to the state-action pairs in the trajectory.

Based on the above discussions, we can analyze the algorithmic properties of randomized return decomposition by connecting with previous studies.

3.2.1 Surrogate Optimization of Return Decomposition

Randomized return decomposition conducts a surrogate optimization of the actual return decomposition. Note that the variance penalty term in Eq. (10) is non-negative, our loss function $\mathcal{L}_{\text{Rand-RD}}(\theta)$ serves an upper bound estimation of the original loss $\mathcal{L}_{\text{RD}}(\theta)$ as the following statement.

Proposition 1 (Surrogate Upper Bound). *The randomized return decomposition loss $\mathcal{L}_{Rand\text{-}RD}(\theta)$ is an upper bound of the actual return decomposition loss function $\mathcal{L}_{RD}(\theta)$, i.e., $\mathcal{L}_{Rand\text{-}RD}(\theta) \geq \mathcal{L}_{RD}(\theta)$.*

Proposition 1 suggests that optimizing our surrogate loss $\mathcal{L}_{\text{Rand-RD}}(\theta)$ guarantees to optimize an upper bound of the actual return decomposition loss $\mathcal{L}_{\text{RD}}(\theta)$. According to Theorem 1, the gap between $\mathcal{L}_{\text{Rand-RD}}(\theta)$ and $\mathcal{L}_{\text{RD}}(\theta)$ refers to the variance of subsequence sampling. The magnitude of this gap can be controlled by the hyper-parameter K that refers to the length of sampled subsequences.

Proposition 2 (Objective Gap). *Let $\mathcal{L}_{Rand\text{-}RD}^{(K)}(\theta)$ denote the randomized return decomposition loss that samples subsequences with length K. The gap between $\mathcal{L}_{Rand\text{-}RD}^{(K)}(\theta)$ and $\mathcal{L}_{RD}(\theta)$ can be reduced by using larger values of hyper-parameter K.*

$$\forall \theta, \quad \mathcal{L}_{Rand\text{-}RD}^{(1)}(\theta) \geq \mathcal{L}_{Rand\text{-}RD}^{(2)}(\theta) \geq \cdots \geq \mathcal{L}_{Rand\text{-}RD}^{(T-1)}(\theta) \geq \mathcal{L}_{Rand\text{-}RD}^{(T)}(\theta) = \mathcal{L}_{RD}(\theta). \quad (11)$$

This gap can be eliminated by choosing $K = T$ in the sampling distribution (see Eq. (7)) so that our approach degrades to the original deterministic implementation of return decomposition.

3.2.2 Generalization of Uniform Credit Assignment

The reward redistribution mechanism of randomized return decomposition is a generalization of uniform credit assignment. To serve intuitions, we start the discussions with the simplest case using $K = 1$ in subsequence sampling, in which our approach degrades to the uniform reward redistribution as the following statement.

Proposition 3 (Uniform Reward Redistribution). *Assume all trajectories have the same length and the parameterization space of θ serves universal representation capacity. The optimal solution $\theta^\star$ of minimizing $\mathcal{L}^{(1)}_{Rand\text{-}RD}(\theta)$ is stated as follows:*

$$\widehat{R}_{\theta^\star}(s,a) = \mathbb{E}_{\tau \sim \mathcal{D}} \big[R_{ep}(\tau)/T \mid (s,a) \in \tau \big], \tag{12}$$

where $\mathcal{L}^{(1)}_{Rand\text{-}RD}(\theta)$ denotes the randomized return decomposition loss with $K = 1$.

A minor difference between Eq. (12) and the proxy reward designed by Gangwani et al. (2020) (see Eq. (5)) is a multiplier scalar $1/T$. Gangwani et al. (2020) interprets such a reward redistribution mechanism as a trajectory-space smoothing process or a non-committal credit assignment. Our analysis can give a mathematical characterization to illustrate the objective of uniform reward redistribution. As characterized by Theorem 1, uniform reward redistribution conducts an additional regularizer to penalize the variance of per-step proxy rewards. In the view of randomized return decomposition, the functionality of this regularizer is requiring the reward model to reconstruct episodic return from each single-step transition.

By using larger values of hyper-parameter K, randomized return decomposition is trained to reconstruct the episodic return from a subsequence of agent trajectory instead of the single-step transition used by uniform reward redistribution. This mechanism is a generalization of uniform credit assignment, in which we equally assign credits to subsequences generated by uniformly random sampling. It relies on the concentratability of random sampling, i.e., the average of a sequence can be estimated by a small random subset with sub-linear size. The individual contribution of each transition within the subsequence is further attributed by return decomposition.

3.3 Practical Implementation of Randomized Return Decomposition

In Algorithm 1, we integrate randomized return decomposition with policy optimization. It follows an iterative paradigm that iterates between the rewarding modeling and policy optimization modules.

Algorithm 1 Policy Optimization with Randomized Return Decomposition

---

1: Initialize $\mathcal{D} \leftarrow \emptyset$
2: **for** $\ell = 1, 2, \cdots$ **do**
3:      Collect a rollout trajectory τ using the current policy.
4:      Store trajectory τ and feedback $R_{ep}(\tau)$ into the replay buffer $\mathcal{D} \leftarrow \mathcal{D} \cup \{(\tau, R_{ep}(\tau))\}$.
5:      **for** $i = 1, 2, \cdots$ **do**
6:          Sample M trajectories $\{\tau_j \in \mathcal{D}\}_{j=1}^{M}$ from the replay buffer.
7:          Sample subsequences $\{\mathcal{I}_j \subseteq \mathbb{Z}_{T_j}\}_{j=1}^{M}$ for these trajectories.
8:          Estimate randomized return decomposition loss $\widehat{\mathcal{L}}_{\text{Rand-RD}}(\theta)$,

$$\widehat{\mathcal{L}}_{\text{Rand-RD}}(\theta) = \frac{1}{M} \sum_{j=1}^{M} \left[\left(R_{\text{ep}}(\tau_j) - \frac{T_j}{|\mathcal{I}_j|} \sum_{t \in \mathcal{I}_j} \widehat{R}_\theta(s_{j,t}, a_{j,t}) \right)^2 \right], \tag{13}$$

         where T_j denotes the length of trajectory $\tau_j = \langle s_{j,1}, a_{j,1}, \cdots, s_{j,T_j} \rangle$.
9:          Perform a gradient update on the reward model $\widehat{R}_\theta$,

$$\theta \leftarrow \theta - \alpha \nabla_\theta \widehat{\mathcal{L}}_{\text{Rand-RD}}(\theta), \tag{14}$$

         where α denotes the learning rate.
10:     Perform policy optimization using the learned proxy reward function $\widehat{R}_\theta(s,a)$.

As presented in Eq. (13) and Eq. (14), the optimization of our loss function $\mathcal{L}_{\text{Rand-RD}}(\theta)$ can be easily conducted by mini-batch gradient descent. This surrogate loss function only requires computations on short-length subsequences. It provides a scalable implementation for return decomposition that can be generalized to long-horizon tasks with manageable computation costs. In section 4, we will show that this simple implementation can also achieve state-of-the-art performance in comparison to other existing methods.

4 EXPERIMENTS

In this section, we investigate the empirical performance of our proposed methods by conducting experiments on a suite of MuJoCo benchmark tasks with episodic rewards. We compare our approach with several baseline algorithms in the literature and conduct an ablation study on subsequence sampling that is the core component of our algorithm.

4.1 PERFORMANCE EVALUATION ON MUJOCO BENCHMARK WITH EPISODIC REWARDS

Experiment Setting. We adopt the same experiment setting as Gangwani et al. (2020) to compare the performance of our approach with baseline algorithms. The experiment environments is based on the MuJoCo locomotion benchmark tasks created by OpenAI Gym (Brockman et al., 2016). These tasks are long-horizon with maximum trajectory length $T = 1000$, i.e., the task horizon is definitely longer than the batch size used by the standard implementation of mini-batch gradient estimation. We modify the reward function of these environments to set up an episodic-reward setting. Formally, on non-terminal states, the agent will receive a zero signal instead of the per-step dense rewards. The agent can obtain the episodic feedback $R_{\text{ep}}(\tau)$ at the last step of the rollout trajectory, in which $R_{\text{ep}}(\tau)$ is computed by the summation of per-step instant rewards given by the standard setting. We evaluate the performance of our proposed methods with the same configuration of hyper-parameters in all environments. A detailed description of the experiment setting and implementation details is included in Appendix B.

We evaluate two implementations of randomized return decomposition (RRD):

- **RRD (ours)** denotes the default implementation of our approach. We train a reward model using randomized return decomposition loss $\mathcal{L}_{\text{Rand-RD}}$, in which we sample subsequences with length $K = 64$ in comparison to the task horizon $T = 1000$. The reward model $\widehat{R}_\theta$ is parameterized by a two-layer fully connected network. The policy optimization module is implemented by soft actor-critic (SAC; Haarnoja et al., 2018).

- **RRD-$\mathcal{L}_{\text{RD}}$ (ours)** is an alternative implementation that optimizes $\mathcal{L}_{\text{RD}}$ instead of $\mathcal{L}_{\text{Rand-RD}}$. Note that Theorem 1 gives a closed-form characterization of the gap between $\mathcal{L}_{\text{Rand-RD}}(\theta)$ and $\mathcal{L}_{\text{RD}}(\theta)$, which is represented by the variance of the learned proxy rewards. By subtracting an unbiased variance estimation from loss function $\mathcal{L}_{\text{Rand-RD}}(\theta)$, we can train RRD with loss function $\mathcal{L}_{\text{RD}}(\theta)$. We include this alternative implementation to reveal the functionality of the regularization given by variance penalty. We include a detailed description in Appendix B.2.

We compare with several existing methods for long-term credit assignment:

- **IRCR** (Gangwani et al., 2020) is an implementation of uniform credit assignment. The reward redistribution of IRCR is non-parametric, in which the proxy reward of a transition is set to be the normalized value of corresponding trajectory return. It is equivalent to use a Monte-Carlo estimator of Eq. (5). Due to the ease of implementation, this method achieves state-of-the-art performance in the literature.

- **RUDDER** (Arjona-Medina et al., 2019) is an implementation of return decomposition. It trains a return predictor, and the proxy reward is computed by the prediction difference between two consecutive states. This transform prevents the training computation costs of return decomposition from depending on the task horizon T so that it implementation is adaptive to long-horizon tasks.

- **GASIL** (Guo et al., 2018), generative adversarial self-imitation learning, is a generalization of GAIL (Ho & Ermon, 2016). It formulates an imitation learning framework by imitating best trajectories in the replay buffer. The proxy rewards are given by a discriminator that is trained to classify the agent and expert trajectories.

- **LIRPG** (Zheng et al., 2018) aims to learn an intrinsic reward function from sparse environment feedback. Its policy is trained to optimized the sum of the extrinsic and intrinsic rewards. The parametric intrinsic reward function is updated by meta-gradients to optimize the actual extrinsic rewards achieved by the policy

Figure 1: Learning curves on a suite of MuJoCo benchmark tasks with episodic rewards. All curves presented in this paper are plotted from at least 10 runs with random initializations. The shaded region indicates 60% population around median.

Overall Performance Comparison. As presented in Figure 1, randomized return decomposition generally outperforms baseline algorithms. Our approach can achieve higher sample efficiency and produce better polices after convergence. RUDDER is an implementation of return decomposition that represents single-step rewards by the differences between the return predictions of two consecutive states. This implementation maintains high computation efficiency but long-term return prediction is a hard optimization problem and requires on-policy samples. In comparison, RRD is a more scalable and stable implementation which can better integrate with off-policy learning for improving sample efficiency. The uniform credit assignment considered by IRCR is simple to implement but cannot extract the temporal structure of episodic rewards. Thus the final policy quality produced by RRD is usually better than that of IRCR. GASIL and LIRPG aim to construct auxiliary reward functions that have high correlation to the environmental return. These two methods cannot achieve high sample efficiency since their objectives require on-policy training.

Variance Penalty as Regularization. Figure 1 also compares two implementations of randomized return decomposition. In most testing environments, RRD optimizing $\mathcal{L}_{\text{Rand-RD}}$ outperforms the unbiased implementation RRD-$\mathcal{L}_{\text{RD}}$. We consider RRD using $\mathcal{L}_{\text{Rand-RD}}$ as our default implementation since it performs better and its objective function is simpler to implement. As discussed in section 3.2, the variance penalty conducted by RRD aims to minimize the variance of the Monte-Carlo estimator presented in Eq. (6). It serves as a regularization to restrict the solution space of return decomposition, which gives two potential effects: (1) RRD prefers smooth proxy rewards when the expressiveness capacity of reward network over-parameterizes the dataset. (2) The variance of mini-batch gradient estimation can also be reduced when the variance of Monte-Carlo estimator is small. In practice, this regularization would benefit the training stability. As presented in Figure 1, RRD achieves higher sample efficiency than RRD-$\mathcal{L}_{\text{RD}}$ in most testing environments. The quality of the learned policy of RRD is also better than that of RRD-$\mathcal{L}_{\text{RD}}$. It suggests that the regularized reward redistribution can better approximate the actual environmental objective.

4.2 ABLATION STUDIES

We conduct an ablation study on the hyper-parameter K that represent the length of subsequences used by randomized return decomposition. As discussed in section 3.2, the hyper-parameter K controls the interpolation ratio between return decomposition and uniform reward redistribution. It trades off the accuracy of return reconstruction and variance regularization. In Figure 2, we evaluate RRD with a set of choices of hyper-parameter $K \in \{1, 8, 16, 32, 64, 128\}$. The experiment results show that, although the sensitivity of this hyper-parameter depends on the environment, a relatively large value of K generally achieves better performance, since it can better approximate the environmental objective. In this experiment, we ensure all runs use the same input size for mini-batch training, i.e., using larger value of K leads to less number of subsequences in the mini-batch.

Figure 2: Learning curves of RRD with different choices of hyper-parameter K. The curves with $K = 64$ correspond to the default implementation of RRD presented in Figure 1.

More specifically, in this ablation study, all algorithm instances estimate the loss function $\mathcal{L}_{\text{Rand-RD}}$ using a mini-batch containing 256 transitions. We consider $K = 64$ as our default configuration for the choice of hyper-parameter K, since it balances the weight of variance regularization and the number of subsequences for mini-batch gradient estimation. As presented in Figure 2, larger values give marginal benefits. In some cases, such as `Ant-v2`, we can observe a slight drop in the performance of $K = 128$, which highlights the trade-off.

5 RELATED WORK

Delayed Feedback. Tackling environmental delays is a long-lasting problem in reinforcement learning and control theory (Nilsson et al., 1998; Walsh et al., 2009). In real-world applications, almost all environmental signals have random delays (Schuitema et al., 2010; Hester & Stone, 2013), which is a fundamental challenge for the designs of RL algorithms. A classical method to process delayed signals is stacking recent observations within a small sliding window as the input for decision-making (Katsikopoulos & Engelbrecht, 2003). This simple transformation can establish a Markovian environment formulation, which is widely used to deal with short-term environmental delays (Mnih et al., 2015). Many recent works focus on establishing sample-efficient off-policy RL algorithm that is adaptive to delayed environmental signals (Bouteiller et al., 2021; Han et al., 2021). In this paper, we consider an extreme delay of reward signals, which is a harder problem setting than short-term random delays.

Reward Design. The ability of reinforcement learning agents highly depends on the designs of reward functions. It is widely observed that reward shaping can accelerate learning (Mataric, 1994; Ng et al., 1999; Devlin et al., 2011; Wu & Tian, 2017; Song et al., 2019). Many previous works study how to automatically design auxiliary reward functions for efficient reinforcement learning. A famous paradigm, inverse reinforcement learning (Ng & Russell, 2000; Fu et al., 2018), considers to recover a reward function from expert demonstrations. Another branch of works is learning an intrinsic reward function from experience to guide the agent to maximize extrinsic objective (Sorg et al., 2010; Guo et al., 2016; Zheng et al., 2018; 2020). Reward attribution is also an important problem for multi-agent reinforcement learning (Nguyen et al., 2018; Du et al., 2019; Wang et al., 2020). This paper follows the return decomposition paradigm (Arjona-Medina et al., 2019) that aims to redistribute the trajectory return in temporal horizon.

6 CONCLUSION

In this paper, we propose randomized return decomposition (RRD), a novel reward redistribution algorithm, to tackle the episodic reinforcement learning problem with trajectory feedback. RRD uses a Monte-Carlo estimator to establish a surrogate optimization problem of return decomposition. This surrogate objective implicitly conducts a variance reduction penalty as regularization. We analyze its algorithmic properties by connecting with previous studies in long-term credit assignment. Our experiments demonstrate that RRD outperforms previous methods in terms of both sample efficiency and policy quality. The basic idea of randomized return decomposition can potentially generalize to other related problems with sum-decomposition structure, such as preference-based reward modeling (Lee et al., 2021) and multi-agent value decomposition (Sunehag et al., 2018). It is also promising to consider non-linear decomposition as what is explored in multi-agent value factorization (Rashid et al., 2018). We leave these investigations as our future work.

REFERENCES

Dario Amodei, Chris Olah, Jacob Steinhardt, Paul Christiano, John Schulman, and Dan Mané. Concrete problems in ai safety. *arXiv preprint arXiv:1606.06565*, 2016.

Marcin Andrychowicz, Filip Wolski, Alex Ray, Jonas Schneider, Rachel Fong, Peter Welinder, Bob McGrew, Josh Tobin, Pieter Abbeel, and Wojciech Zaremba. Hindsight experience replay. In *Advances in Neural Information Processing Systems*, pp. 5048–5058, 2017.

András Antos, Csaba Szepesvári, and Rémi Munos. Learning near-optimal policies with bellman-residual minimization based fitted policy iteration and a single sample path. *Machine Learning*, 71(1):89–129, 2008.

Jose A Arjona-Medina, Michael Gillhofer, Michael Widrich, Thomas Unterthiner, Johannes Brandstetter, and Sepp Hochreiter. Rudder: Return decomposition for delayed rewards. In *Advances in Neural Information Processing Systems*, volume 32, 2019.

Richard Bellman. Dynamic programming. *Princeton University Press*, 89:92, 1957.

Léon Bottou, Jonas Peters, Joaquin Quiñonero-Candela, Denis X Charles, D Max Chickering, Elon Portugaly, Dipankar Ray, Patrice Simard, and Ed Snelson. Counterfactual reasoning and learning systems: The example of computational advertising. *Journal of Machine Learning Research*, 14 (11), 2013.

Yann Bouteiller, Simon Ramstedt, Giovanni Beltrame, Christopher Pal, and Jonathan Binas. Reinforcement learning with random delays. In *International Conference on Learning Representations*, 2021.

Greg Brockman, Vicki Cheung, Ludwig Pettersson, Jonas Schneider, John Schulman, Jie Tang, and Wojciech Zaremba. Openai gym. *arXiv preprint arXiv:1606.01540*, 2016.

Shi-Yong Chen, Yang Yu, Qing Da, Jun Tan, Hai-Kuan Huang, and Hai-Hong Tang. Stabilizing reinforcement learning in dynamic environment with application to online recommendation. In *Proceedings of the 24th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining*, pp. 1187–1196, 2018.

Sam Devlin, Daniel Kudenko, and Marek Grześ. An empirical study of potential-based reward shaping and advice in complex, multi-agent systems. *Advances in Complex Systems*, 14(02): 251–278, 2011.

Daniel Dewey. Reinforcement learning and the reward engineering principle. In *2014 AAAI Spring Symposium Series*, 2014.

Yali Du, Lei Han, Meng Fang, Tianhong Dai, Ji Liu, and Dacheng Tao. Liir: learning individual intrinsic reward in multi-agent reinforcement learning. In *Advances in Neural Information Processing Systems*, pp. 4403–4414, 2019.

Yonathan Efroni, Nadav Merlis, and Shie Mannor. Reinforcement learning with trajectory feedback. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 35, pp. 7288–7295, 2021.

Justin Fu, Katie Luo, and Sergey Levine. Learning robust rewards with adverserial inverse reinforcement learning. In *International Conference on Learning Representations*, 2018.

Tanmay Gangwani, Qiang Liu, and Jian Peng. Learning self-imitating diverse policies. In *International Conference on Learning Representations*, 2019.

Tanmay Gangwani, Yuan Zhou, and Jian Peng. Learning guidance rewards with trajectory-space smoothing. In *Advances in Neural Information Processing Systems*, volume 33, pp. 822–832, 2020.

Xiaoxiao Guo, Satinder P Singh, Richard L Lewis, and Honglak Lee. Deep learning for reward design to improve monte carlo tree search in atari games. In *Proceedings of the Twenty-Fifth International Joint Conference on Artificial Intelligence*, pp. 1519–1525, 2016.

Yijie Guo, Junhyuk Oh, Satinder Singh, and Honglak Lee. Generative adversarial self-imitation learning. *arXiv preprint arXiv:1812.00950*, 2018.

Tuomas Haarnoja, Aurick Zhou, Pieter Abbeel, and Sergey Levine. Soft actor-critic: Off-policy maximum entropy deep reinforcement learning with a stochastic actor. In *International conference on machine learning*, pp. 1861–1870. PMLR, 2018.

Beining Han, Zhizhou Ren, Zuofan Wu, Yuan Zhou, and Jian Peng. Off-policy reinforcement learning with delayed rewards. *arXiv preprint arXiv:2106.11854*, 2021.

Daniel Hein, Stefan Depeweg, Michel Tokic, Steffen Udluft, Alexander Hentschel, Thomas A Runkler, and Volkmar Sterzing. A benchmark environment motivated by industrial control problems. In *2017 IEEE Symposium Series on Computational Intelligence (SSCI)*, pp. 1–8. IEEE, 2017.

Todd Hester and Peter Stone. Texplore: real-time sample-efficient reinforcement learning for robots. *Machine learning*, 90(3):385–429, 2013.

Jonathan Ho and Stefano Ermon. Generative adversarial imitation learning. In *Advances in neural information processing systems*, volume 29, pp. 4565–4573, 2016.

Konstantinos V Katsikopoulos and Sascha E Engelbrecht. Markov decision processes with delays and asynchronous cost collection. *IEEE transactions on automatic control*, 48(4):568–574, 2003.

Ron Kohavi and David Wolpert. Bias plus variance decomposition for zero-one loss functions. In *Proceedings of the Thirteenth International Conference on International Conference on Machine Learning*, pp. 275–283, 1996.

Kimin Lee, Laura Smith, and Pieter Abbeel. Pebble: Feedback-efficient interactive reinforcement learning via relabeling experience and unsupervised pre-training. In *International Conference on Machine Learning*, 2021.

Yang Liu, Yunan Luo, Yuanyi Zhong, Xi Chen, Qiang Liu, and Jian Peng. Sequence modeling of temporal credit assignment for episodic reinforcement learning. *arXiv preprint arXiv:1905.13420*, 2019.

Horia Mania, Aurelia Guy, and Benjamin Recht. Simple random search provides a competitive approach to reinforcement learning. *arXiv preprint arXiv:1803.07055*, 2018.

Hongzi Mao, Mohammad Alizadeh, Ishai Menache, and Srikanth Kandula. Resource management with deep reinforcement learning. In *Proceedings of the 15th ACM workshop on hot topics in networks*, pp. 50–56, 2016.

Maja J Mataric. Reward functions for accelerated learning, 1994.

Volodymyr Mnih, Koray Kavukcuoglu, David Silver, Andrei A Rusu, Joel Veness, Marc G Bellemare, Alex Graves, Martin Riedmiller, Andreas K Fidjeland, Georg Ostrovski, et al. Human-level control through deep reinforcement learning. *Nature*, 518(7540):529–533, 2015.

David S Moore. *The basic practice of statistics*, volume 2. 2007.

Andrew Y Ng and Stuart Russell. Algorithms for inverse reinforcement learning. In *Proceedings of the Seventeenth International Conference on Machine Learning*. Citeseer, 2000.

Andrew Y Ng, Daishi Harada, and Stuart J Russell. Policy invariance under reward transformations: Theory and application to reward shaping. In *Proceedings of the Sixteenth International Conference on Machine Learning*, pp. 278–287. Morgan Kaufmann Publishers Inc., 1999.

Duc Thien Nguyen, Akshat Kumar, and Hoong Chuin Lau. Credit assignment for collective multi-agent rl with global rewards. In *Advances in Neural Information Processing Systems*, volume 31, pp. 8102–8113, 2018.

Johan Nilsson, Bo Bernhardsson, and Björn Wittenmark. Stochastic analysis and control of real-time systems with random time delays. *Automatica*, 34(1):57–64, 1998.

Mariya Popova, Olexandr Isayev, and Alexander Tropsha. Deep reinforcement learning for de novo drug design. *Science advances*, 4(7):eaap7885, 2018.

Hazhir Rahmandad, Nelson Repenning, and John Sterman. Effects of feedback delay on learning. *System Dynamics Review*, 25(4):309–338, 2009.

Jette Randløv and Preben Alstrøm. Learning to drive a bicycle using reinforcement learning and shaping. In *International Conference on Machine Learning*, pp. 463–471. Citeseer, 1998.

David Raposo, Sam Ritter, Adam Santoro, Greg Wayne, Theophane Weber, Matt Botvinick, Hado van Hasselt, and Francis Song. Synthetic returns for long-term credit assignment. *arXiv preprint arXiv:2102.12425*, 2021.

Tabish Rashid, Mikayel Samvelyan, Christian Schroeder, Gregory Farquhar, Jakob Foerster, and Shimon Whiteson. Qmix: Monotonic value function factorisation for deep multi-agent reinforcement learning. In *International Conference on Machine Learning*, pp. 4295–4304. PMLR, 2018.

Erik Schuitema, Lucian Buşoniu, Robert Babuška, and Pieter Jonker. Control delay in reinforcement learning for real-time dynamic systems: a memoryless approach. In *2010 IEEE/RSJ International Conference on Intelligent Robots and Systems*, pp. 3226–3231. IEEE, 2010.

Shihong Song, Jiayi Weng, Hang Su, Dong Yan, Haosheng Zou, and Jun Zhu. Playing fps games with environment-aware hierarchical reinforcement learning. pp. 3475–3482, 2019.

Jonathan Sorg, Richard L Lewis, and Satinder Singh. Reward design via online gradient ascent. In *Advances in Neural Information Processing Systems*, volume 23, pp. 2190–2198, 2010.

Peter Sunehag, Guy Lever, Audrunas Gruslys, Wojciech Marian Czarnecki, Vinicius Zambaldi, Max Jaderberg, Marc Lanctot, Nicolas Sonnerat, Joel Z Leibo, Karl Tuyls, et al. Value-decomposition networks for cooperative multi-agent learning based on team reward. In *Proceedings of the 17th International Conference on Autonomous Agents and MultiAgent Systems*, pp. 2085–2087, 2018.

Thomas J Walsh, Ali Nouri, Lihong Li, and Michael L Littman. Learning and planning in environments with delayed feedback. *Autonomous Agents and Multi-Agent Systems*, 18(1):83–105, 2009.

Jianhong Wang, Yuan Zhang, Tae-Kyun Kim, and Yunjie Gu. Shapley q-value: a local reward approach to solve global reward games. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 34, pp. 7285–7292, 2020.

Yuxin Wu and Yuandong Tian. Training agent for first-person shooter game with actor-critic curriculum learning. In *International Conference on Learning Representations*, 2017.

Zeyu Zheng, Junhyuk Oh, and Satinder Singh. On learning intrinsic rewards for policy gradient methods. In *Advances in Neural Information Processing Systems*, volume 31, pp. 4644–4654, 2018.

Zeyu Zheng, Junhyuk Oh, Matteo Hessel, Zhongwen Xu, Manuel Kroiss, Hado Van Hasselt, David Silver, and Satinder Singh. What can learned intrinsic rewards capture? In *International Conference on Machine Learning*, pp. 11436–11446. PMLR, 2020.

Zhenpeng Zhou, Steven Kearnes, Li Li, Richard N Zare, and Patrick Riley. Optimization of molecules via deep reinforcement learning. *Scientific reports*, 9(1):1–10, 2019.

A   OMITTED PROOFS

Theorem 1 (Loss Decomposition). *The surrogate loss function $\mathcal{L}_{Rand\text{-}RD}(\theta)$ can be decomposed to two terms interpolating between return decomposition and uniform credit assignment.*

$$\mathcal{L}_{Rand\text{-}RD}(\theta) = \mathcal{L}_{RD}(\theta) + \underset{\tau \sim \mathcal{D}}{\mathbb{E}} \Bigg[\underbrace{\underset{\mathcal{I} \sim \rho_T(\cdot)}{Var} \Bigg[\frac{T}{|\mathcal{I}|} \sum_{t \in \mathcal{I}} \widehat{R}_\theta(s_t, a_t) \Bigg]}_{\text{variance of the Monte-Carlo estimator}} \Bigg] \tag{9}$$

$$= \underbrace{\mathcal{L}_{RD}(\theta)}_{\text{return decomposition}} + \underset{\tau \sim \mathcal{D}}{\mathbb{E}} \Bigg[T^2 \cdot \underbrace{\underset{(s_t, a_t) \sim \tau}{Var} \Big[\widehat{R}_\theta(s_t, a_t) \Big]}_{\text{uniform credit assignment}} \cdot \underbrace{\frac{1}{K} \Big(1 - \frac{K-1}{T-1} \Big)}_{\text{interpolation weight}} \Bigg], \tag{10}$$

where K denotes the length of sampled subsequences defined in Eq. (7).

Proof. First, we note that random sampling serves an unbiased estimation. i.e.,

$$\underset{\mathcal{I} \sim \rho_T(\cdot)}{\mathbb{E}} \Bigg[\frac{T}{|\mathcal{I}|} \sum_{t \in \mathcal{I}} \widehat{R}_\theta(s_t, a_t) \Bigg] = \sum_{t=0}^{T-1} \widehat{R}_\theta(s_t, a_t) = \widehat{R}_{\text{ep},\theta}(\tau). \tag{15}$$

We can decompose our loss function $\mathcal{L}_{\text{Rand-RD}}(\theta)$ as follows:

$$\mathcal{L}_{\text{Rand-RD}}(\theta) = \underset{\tau \sim \mathcal{D}}{\mathbb{E}} \Bigg[\underset{\mathcal{I} \sim \rho_T(\cdot)}{\mathbb{E}} \Bigg[\Big(R_{\text{ep}}(\tau) - \frac{T}{|\mathcal{I}|} \sum_{t \in \mathcal{I}} \widehat{R}_\theta(s_t, a_t) \Big)^2 \Bigg] \Bigg]$$

$$= \underset{\tau \sim \mathcal{D}}{\mathbb{E}} \Bigg[\underset{\mathcal{I} \sim \rho_T(\cdot)}{\mathbb{E}} \Bigg[\Big(R_{\text{ep}}(\tau) - \widehat{R}_{\text{ep},\theta}(\tau) + \widehat{R}_{\text{ep},\theta}(\tau) - \frac{T}{|\mathcal{I}|} \sum_{t \in \mathcal{I}} \widehat{R}_\theta(s_t, a_t) \Big)^2 \Bigg] \Bigg]$$

$$= \underbrace{\underset{\tau \sim \mathcal{D}}{\mathbb{E}} \Bigg[\underset{\mathcal{I} \sim \rho_T(\cdot)}{\mathbb{E}} \Bigg[\Big(R_{\text{ep}}(\tau) - \widehat{R}_{\text{ep},\theta}(\tau) \Big)^2 \Bigg] \Bigg]}_{=\mathcal{L}_{\text{RD}}(\theta)}$$

$$+ \underset{\tau \sim \mathcal{D}}{\mathbb{E}} \Bigg[2 \big(R_{\text{ep}}(\tau) - \widehat{R}_{\text{ep},\theta}(\tau) \big) \cdot \underbrace{\underset{\mathcal{I} \sim \rho_T(\cdot)}{\mathbb{E}} \Bigg[\Big(\widehat{R}_{\text{ep},\theta}(\tau) - \frac{T}{|\mathcal{I}|} \sum_{t \in \mathcal{I}} \widehat{R}_\theta(s_t, a_t) \Big) \Bigg]}_{=0} \Bigg]$$

$$+ \underset{\tau \sim \mathcal{D}}{\mathbb{E}} \Bigg[\underbrace{\underset{\mathcal{I} \sim \rho_T(\cdot)}{\mathbb{E}} \Bigg[\Big(\widehat{R}_{\text{ep},\theta}(\tau) - \frac{T}{|\mathcal{I}|} \sum_{t \in \mathcal{I}} \widehat{R}_\theta(s_t, a_t) \Big)^2 \Bigg]}_{=\text{Var}\big[(T/|\mathcal{I}|) \cdot \sum_{t \in \mathcal{I}} \widehat{R}_\theta(s_t, a_t) \big]} \Bigg]$$

$$= \mathcal{L}_{\text{RD}}(\theta) + \underset{\tau \sim \mathcal{D}}{\mathbb{E}} \Bigg[\underset{\mathcal{I} \sim \rho_T(\cdot)}{\text{Var}} \Bigg[\frac{T}{|\mathcal{I}|} \sum_{t \in \mathcal{I}} \widehat{R}_\theta(s_t, a_t) \Bigg] \Bigg].$$

Note our sampling distribution defined in Eq. (7) refers to "*sampling without replacement*" (Moore, 2007) whose variance can be further decomposed as follows:

$$\mathcal{L}_{\text{Rand-RD}}(\theta) = \mathcal{L}_{\text{RD}}(\theta) + \underset{\tau \sim \mathcal{D}}{\mathbb{E}} \Bigg[\underset{\mathcal{I} \sim \rho_T(\cdot)}{\text{Var}} \Bigg[\frac{T}{|\mathcal{I}|} \sum_{t \in \mathcal{I}} \widehat{R}_\theta(s_t, a_t) \Bigg] \Bigg]$$

$$= \mathcal{L}_{\text{RD}}(\theta) + \underset{\tau \sim \mathcal{D}}{\mathbb{E}} \Bigg[T^2 \cdot \underset{(s_t, a_t) \sim \tau}{\text{Var}} \Big[\widehat{R}_\theta(s_t, a_t) \Big] \cdot \frac{1}{K} \Big(1 - \frac{K-1}{T-1} \Big) \Bigg].$$

$$\square$$

The proof of Theorem 1 follows a particular form of bias-variance decomposition formula (Kohavi & Wolpert, 1996). Similar decomposition form can also be found in other works in the literature of reinforcement learning (Antos et al., 2008).

Proposition 1 (Surrogate Upper Bound). *The randomized return decomposition loss $\mathcal{L}_{Rand\text{-}RD}(\theta)$ is an upper bound of the actual return decomposition loss function $\mathcal{L}_{RD}(\theta)$, i.e., $\mathcal{L}_{Rand\text{-}RD}(\theta) \geq \mathcal{L}_{RD}(\theta)$.*

Proof. Note that the second term of Eq. (9) in Theorem 1 expresses the variance of a Monte-Carlo estimator which is clearly non-negative. It directly gives $\mathcal{L}_{\text{Rand-RD}}(\theta) \geq \mathcal{L}_{\text{RD}}(\theta)$. $\square$

An alternative proof of Proposition 1 can be directly given by Jensen's inequality.

Proposition 2 (Objective Gap). *Let $\mathcal{L}_{Rand\text{-}RD}^{(K)}(\theta)$ denote the randomized return decomposition loss that samples subsequences with length K. The gap between $\mathcal{L}_{Rand\text{-}RD}^{(K)}(\theta)$ and $\mathcal{L}_{RD}(\theta)$ can be reduced by using larger values of hyper-parameter K.*

$$\forall \theta, \quad \mathcal{L}_{Rand\text{-}RD}^{(1)}(\theta) \geq \mathcal{L}_{Rand\text{-}RD}^{(2)}(\theta) \geq \cdots \geq \mathcal{L}_{Rand\text{-}RD}^{(T-1)}(\theta) \geq \mathcal{L}_{Rand\text{-}RD}^{(T)}(\theta) = \mathcal{L}_{RD}(\theta). \tag{11}$$

Proof. In Eq. (10) of Theorem 1, the last term $\frac{1}{K}\left(1 - \frac{K-1}{T-1}\right)$ monotonically decreases as the hyper-parameter K increases. When $K = T$, this coefficient is equal to zero. It derives Eq. (11) in the given statement. $\square$

Proposition 3 (Uniform Reward Redistribution). *Assume all trajectories have the same length and the parameterization space of θ serves universal representation capacity. The optimal solution $\theta^\star$ of minimizing $\mathcal{L}_{Rand\text{-}RD}^{(1)}(\theta)$ is stated as follows:*

$$\widehat{R}_{\theta^\star}(s, a) = \mathop{\mathbb{E}}_{\tau \sim \mathcal{D}}\left[R_{ep}(\tau)/T \mid (s, a) \in \tau \right], \tag{12}$$

where $\mathcal{L}_{Rand\text{-}RD}^{(1)}(\theta)$ denotes the randomized return decomposition loss with $K = 1$.

Proof. Note that we assume all trajectories have the same length. The optimal solution of this least-squares problem is given by

$$
\begin{aligned}
\widehat{R}_{\theta^\star}(s, a) &= \min_{r \in \mathbb{R}} \mathop{\mathbb{E}}_{\tau \sim \mathcal{D}} \left[(R_{\text{ep}}(\tau) - T \cdot r)^2 \Big| (s, a) \in \tau \right] \\
&= \min_{r \in \mathbb{R}} \mathop{\mathbb{E}}_{\tau \sim \mathcal{D}} \left[\frac{1}{T^2} (R_{\text{ep}}(\tau)/T - r)^2 \Big| (s, a) \in \tau \right] \\
&= \min_{r \in \mathbb{R}} \frac{1}{T^2} \mathop{\mathbb{E}}_{\tau \sim \mathcal{D}} \left[(R_{\text{ep}}(\tau)/T - r)^2 \Big| (s, a) \in \tau \right] \\
&= \min_{r \in \mathbb{R}} \mathop{\mathbb{E}}_{\tau \sim \mathcal{D}} \left[(R_{\text{ep}}(\tau)/T - r)^2 \Big| (s, a) \in \tau \right] \\
&= \mathop{\mathbb{E}}_{\tau \sim \mathcal{D}} \left[R_{\text{ep}}(\tau)/T \mid (s, a) \in \tau \right],
\end{aligned}
$$

which depends on the trajectory distribution in dataset $\mathcal{D}$. $\square$

If we relax the assumption that all trajectories have the same length, the solution of the above least-squares problem would be a weighted expectation as follows:

$$
\begin{aligned}
\widehat{R}_{\theta^\star}(s, a) &= \min_{r \in \mathbb{R}} \mathop{\mathbb{E}}_{\tau \sim \mathcal{D}} \left[(R_{\text{ep}}(\tau) - T_\tau \cdot r)^2 \Big| (s, a) \in \tau \right] \\
&= \min_{r \in \mathbb{R}} \mathop{\mathbb{E}}_{\tau \sim \mathcal{D}} \left[T_\tau^2 \cdot (R_{\text{ep}}(\tau)/T_\tau - r)^2 \Big| (s, a) \in \tau \right] \\
&= \frac{\sum_{\tau \in \mathcal{D}:(s,a) \in \tau} T_\tau \cdot R_{\text{ep}}(\tau)}{\sum_{\tau \in \mathcal{D}:(s,a) \in \tau} T_\tau^2},
\end{aligned}
$$

where T_τ denotes the length of trajectory τ. This solution can still be interpreted as a uniform reward redistribution, in which the dataset distribution is prioritized by the trajectory length.

B   Experiment Settings and Implementation Details

B.1   Experiment Settings

MuJoCo Benchmark with Episodic Rewards.   We adopt the same experiment setting as Gang-wani et al. (2020) and compare our approach with baselines in a suite of MuJoCo locomotion bench-mark tasks with episodic rewards. This experiment setting is commonly used in the literature (Mania et al., 2018; Guo et al., 2018; Liu et al., 2019; Arjona-Medina et al., 2019; Gangwani et al., 2019; 2020). The environment simulator is based on OpenAI Gym (Brockman et al., 2016). These tasks are long-horizon with maximum trajectory length $T = 1000$. We modify the reward function of these environments to set up an episodic-reward setting. Formally, on non-terminal states, the agent will receive a zero signal instead of the per-step dense rewards. The agent can obtain the episodic feedback $R_{\mathrm{ep}}(\tau)$ at the last step of the rollout trajectory, in which $R_{\mathrm{ep}}(\tau)$ is computed by the sum-mation of per-step instant rewards given by the standard setting.

Hyper-Parameter Configuration.   The policy optimization module of our proposed approach, randomized return decomposition (RRD), is implemented based on soft actor-critic (SAC; Haarnoja et al., 2018). We evaluate the performance of our proposed methods with the same configuration of hyper-parameters in all environments. We summarize our default configuration of hyper-parameters as the following table:

Hyper-Parameter	Default Configuration
discount factor γ	0.99
# hidden layers (all networks)	2
# neurons per layer	256
activation	ReLU
optimizer (all losses)	Adam
learning rate	$3 \cdot 10^{-4}$
initial temperature α_{init}	1.0
target entropy	$-\dim(\mathcal{A})$
Polyak-averaging coefficient	0.005
# gradient steps per environment step	1
# gradient steps per target update	1
# transitions in replay buffer	10^6
# transitions in mini-batch for training SAC	256
# transitions in mini-batch for training $\widehat{R}_\theta$	256
# transitions per subsequence (K)	64
# subsequences in mini-batch for training $\widehat{R}_\theta$	4

B.2   An Alternative Implementation of Randomized Return Decomposition

Theorem 1 motivates an unbiased implementation of randomized return decomposition that opti-mizes $\mathcal{L}_{\mathrm{RD}}$ instead of $\mathcal{L}_{\mathrm{Rand\text{-}RD}}$. Note our sampling distribution defined in Eq. (7) refers to "*sampling without replacement*" (Moore, 2007) whose variance can be estimated as follows:

$$\operatorname*{Var}_{\mathcal{I} \sim \rho_T(\cdot)} \left[\frac{T}{|\mathcal{I}|} \sum_{t \in \mathcal{I}} \widehat{R}_\theta(s_t, a_t) \right] = T^2 \cdot \operatorname*{\mathbb{E}}_{\mathcal{I} \sim \rho_T(\cdot)} \left[\frac{T - K}{T} \cdot \frac{\sum_{t \in \mathcal{I}} \left(\widehat{R}_\theta(s_t, a_t) - \bar{R}_\theta(\mathcal{I}; \tau) \right)^2}{K(K-1)} \right],$$

where $\bar{R}_\theta(\mathcal{I}; \tau) = \frac{1}{|\mathcal{I}|} \sum_{t \in \mathcal{I}} \widehat{R}_\theta(s_t, a_t)$. Thus we can estimate this variance penalty by sampling a subsequence $\mathcal{I}$. By subtracting this estimation from $\widehat{\mathcal{L}}_{\mathrm{Rand\text{-}RD}}(\theta)$, we can obtain an unbiased estima-tion of $\mathcal{L}_{\mathrm{RD}(\theta)}$.