Augmented World Models Facilitate Zero-Shot Dynamics Generalization From a Single Offline Environment

Abstract

Reinforcement learning from large-scale offline datasets provides the opportunity to learn policies without potentially unsafe or impractical exploration. Significant progress has been made in the past few years in dealing with the challenge of correcting for differing behavior of the data collection and learned policies. However, little attention has been paid to the potentially changing dynamics when transferring a policy to the online setting, where performance can be up to 90% reduced for existing methods. In this paper we address this problem with *Augmented World Models*: we augment a learned dynamics model with simple transformations that seek to capture potential changes in physical properties of the robot, leading to more robust policies. We not only train our policy in this new setting, but also provide it with the sampled augmentation as context, allowing it to infer potential changes in the environment. At test time we can then *learn the context* in a self-supervised fashion, by approximating the augmentation which leads to the new environment. We show in a series of experiments that this simple approach is able to significantly improve the zero-shot generalization of a recent state-of-the-art baseline, often achieving successful policies where the baseline fails.

1 Introduction

Offline reinforcement learning (RL) describes the problem setting where reinforcement learning agents learn policies solely from previously collected experience without further interaction with the environment (11; 26). This offers the potential to exploit rich datasets of past experience where exploration is either not feasible (i.e., a Mars Rover) or unsafe (i.e., in medical settings).

This work focuses on model-based offline RL, which has achieved state-of-the-art performance through the use of uncertainty penalized updates (42; 20). However, in many cases, simply correcting for the data collection policy is insufficient. Consider the case where a new Mars Rover is learning from data collected from a previous, different model. Even with a very similar design, there will almost certainly be changes in the dynamics of the new robot. As we show in this paper, this can lead to catastrophic decreases in performance. Even with a vast amount of data, training on a single setting cannot generalize to changing dynamics, rendering the offline data obsolete.

A similar issue, known the Sim2Real problem, has been subject to significant interest in the robotics community. Sim2Real considers transferring an agent from a simulated environment to the real world. In recent years there has been a tremendous amount of success in the Sim2Real setting through the use of domain randomization (39; 17), the process of randomizing non-essential regions of the observation space to make agents robust to 'observational overfitting' (38). Indeed, methods seeking to generalize to novel dynamics have also shown promise (31), by randomizing physical properties such as the mass of the agent. However, this requires access to parameters in a simulator, which is not possible when learning from offline data.

We therefore describe our problem setting as follows: an agent must learn to generalize to unseen test-time dynamics whilst having access to offline data from *only a single environment*; we call this problem "dynamics generalization from a single offline environment". In this paper we concentrate on the zero-shot performance of our agents to unseen dynamics, as it may not be practical (or safe) to perform multiple rollouts at test time.

(a) World Model: $\widehat{P}$ (b) Augmented World Model: $\widehat{P}_z$ (c) Test: $P^\star$

Figure 1: An illustration of our approach, each figure shows a transition $P(s, a) \to s'$. In a) we show the World Model dynamics $\widehat{P}$, trained from $\mathcal{D}_{\text{env}}$, a single offline dataset. In b) we show the Augmented World Model, blue represents $\widehat{P}$, while each green agent illustrates an instantiation of augmented dynamics, which is sampled at each timestep: $\widehat{P}_z, z \sim \mathcal{Z}$. The goal is to approximate c) where we show an unseen test environment, with transition dynamics $P^\star$.

To tackle this problem, consider a novel form of data augmentation: rather than augment observations, we focus on *augmenting the dynamics*. We first learn a world model of the environment, and then augment the transition function at policy training time, making the agent train under different imagined dynamics. In addition, our agent is given access to the augmentation itself as part of the observations, allowing it to consider the context of modified transitions.

At test time we propose a simple, yet surprisingly effective, self-supervised approach to learning an agent's augmentation context. Concretely, we learn a linear dynamics model which is then used to approximate the dynamics augmentation induced by the modified environment. This context is then given to the agent, allowing it to adapt on the fly to the new dynamics. We show that our approach is capable of training agents that can vastly outperform existing Offline RL methods on the "dynamics generalization from a single offline environment" problem. We also note that this approach does *not* require access to environment rewards at test time. This facilitates application to Sim2Real problems whereby test time rewards may not be available.

Our contributions are twofold: 1) As far as we are aware, we are the first to propose **dynamics augmentation for model based RL**, allowing us to generalize to changing dynamics despite only training on a single setting. We do this without access to any environment parameters or prior knowledge. 2) We propose a simple **self-supervised context adaptation** reward-free algorithm, which allows our policy to use information from interactions in the environment to vary its behavior, increasing performance. We believe both of these approaches are not only novel but offer significant improvement vs. state-of-the-art methods, improving generalization and providing a promising approach for using offline RL in the real world.

2   RELATED WORK

Online MBRL In this work we focus on Model Based RL (MBRL). A key challenge in MBRL is that an inaccurate model can be exploited by the policy, leading to suboptimal behaviors. As such, a swathe of recent works have made use of model ensembles to improve robustness (23; 7; 9; 5; 18). With increased accuracy, MBRL has recently been shown to be competitive with model free methods in continuous control (12; 18; 7) and games (36; 19). Concretely, we make use of the ensemble of probabilistic dynamics models, first introduced in (7), and subsequently used in (18).

Offline RL The past few years have seen a series of impressive results in offline RL, predominantly focused on the off policy setting (41; 22; 11). In this paper we focus on Model-Based offline RL, where MOPO (42) and MORel (20) have recently demonstrated the effectiveness of learned dynamics models, making use of model uncertainty from an ensemble to constrain policy optimization. We build upon this framework for zero-shot dynamics generalization from offline data. In OPAL (1) a context variable is used to condition a policy when moving from offline to online. However in their case the context variable describes primitives that exist in the offline data set, whilst we seek to condition on contexts that describe dynamics that exist *outside* of the offline data set. Finally, in MBOP (4) considers the problem of goal-conditioned zero-shot transfer from offline datasets. However, their goal-conditioning relies on unchanged dynamics in the test environment, and therefore their controller would plan under a WM having incorrect dynamics in our problem setting.

Dynamics Generalization Sim2Real is the setting whereby an agent trained in a simulator must transfer to the real world. A common approach to solve this problem is through domain randomization (39; 17), whereby parameters in the simulator are varied during training. This has shown to be effective for dynamics generalization (2; 3; 31; 43; 44; 29), yet requires access to parameters in the simulator and thus is not possible with a learned model from offline data.

In online RL, recent work achieved strong dynamics generalization with a learned model (37). However, this required training under varied dynamics, assigning different experiences to models. In addition, this work used MPC whereas we train a policy inside the model, which is significantly faster at deployment time. Also related is (8; 27), where the model is trained to quickly to new dynamics $P(s'|s,a)$, however both these works place more emphasis on model-adaption rather than zero-shot policy performance. Furthermore, access to an underlying task distribution is required to facilitate meta-gradients/contexts, something we do not have in our offline setting. Also similar to our work is the recently proposed Policy Adaptation during Deployment (PAD, (16)) approach. Our approach differs in that we learn a context, whereas PAD uses a auxiliary objective to adapt its features. In addition, PAD considers the *online model free* setting, while our method is *offline and model based*.

Data Augmentation Data augmentation has recently proved to be effective for training RL policies (24; 25; 21; 33), leading to more efficient learning and improved generalization. Thus far, these works have focused on online model free methods, and used data augmentation on the state space, reducing *observational* overfitting (38). By contrast, we focus on offline MBRL and instead augment the *dynamics*. We are not the first to propose data augmentation in the MBRL setting, (32) proposed Counterfactual data augmentation for improving performance in the context of locally factored tasks. Approaches to ensuring adversarial robustness can include data augmentations that assist with out-of-domain generalization, as opposed to observational over-fitting. In (40) this is done without a simulator and from a single source of data, however they only work on supervised learning problems and require an adversary to be learned, adding computational complexity.

3 PRELIMINARIES

We consider a Markov Decision Process (MDP), defined as a tuple $M = (\mathcal{S}, \mathcal{A}, P, R, \rho_0, \gamma)$, where $\mathcal{S}$ and $\mathcal{A}$ denote the state space and action space respectively, $P(s'|s,a)$ the transition dynamics, $R(s,a)$ the reward function, ρ_0 the initial state distribution, and $\gamma \in (0,1)$ the discount factor. The goal in RL is to optimize a policy $\pi(a|s)$ that maximizes the expected discounted return $\mathbb{E}_{\pi,P,\rho_0}[\sum_{t=0}^{\infty} \gamma^t R(s_t, a_t)]$. The value function $V^\pi(s) := \mathbb{E}_{\pi,P}[\sum_{t=0}^{\infty} \gamma^t R(s_t, a_t)|s_0 = s]$ gives the expected discounted return under π when starting from state s. In *offline RL*, the policy is not deployed in the environment until test time. Instead, the algorithm only has access to a static dataset $\mathcal{D}_{env} = \{(s, a, r, s')\}$, collected by one or more behavioral policies π_b. We borrow notation from (42) and refer to the distribution from which $\mathcal{D}_{env}$ was sampled as the *behavioral distribution*.

When training a model, we follow MBPO (18) and MOPO (42) and train an ensemble of N probabilistic dynamics models (28). Each of the models learns to predict both the next state s' and reward r from a state-action pair, using $\mathcal{D}_{env}$ in a supervised fashion. Concretely, each of the N models output a Gaussian $\widehat{P}_i(s_{t+1}, r_t|s_t, a_t) = \mathcal{N}(\mu(s_t, a_t), \Sigma(s_t, a_t))$. The resulting dynamics model $\widehat{P}$ defines a *model MDP* $\widehat{M} = (\mathcal{S}, \mathcal{A}, \widehat{P}, \widehat{R}, \rho_0, \gamma)$, where $\widehat{R}$ refers to the learned reward model.

To train the policy, we use k step rollouts inside $\widehat{M}$, adding experience to a replay buffer $\mathcal{D}_{\widehat{env}}$ to learn an action-value function and a policy, using Soft Actor Critic (SAC (13)). SAC alternates between a soft policy evaluation step, which estimates $Q^\pi(s,a) = \mathbb{E}_\pi[\sum_{t=0}^{\infty} \gamma^t(R(s_t, a_t) + \alpha\mathcal{H}(\pi(\cdot|s_k)))|s_0 = s, a_0 = a]$ using Bellman backups (where α is a temperature parameter for policy entropy $\mathcal{H}$), and a policy improvement which learns a policy by minimizing the expected KL divergence $J_\pi(\phi, \mathcal{D}) = \mathbb{E}_{s_t \sim \mathcal{D}_{\widehat{env}}}[D_{KL}(\pi\|\exp\{\frac{1}{\alpha}\{Q^\pi - V^\pi\}\})]$. Note that the SAC algorithm is unchanged from the model-free setting, aside from the environment being a learned model, and the rollout horizon k being truncated. Perhaps surprisingly, this approach alone produces strong results in the offline setting. However MOPO (42) and MORel (20) show improvement in performance by penalizing rewards in regions of the state space where the ensemble of probabilistic models is less certain. This implicitly reduces reliance on samples which deviate beyond the support of $\mathcal{D}_{env}$.

While MOPO and MORel have addressed the issue of training a policy in $\mathcal{D}_{env}$, and transferring to the true environment M, they only consider where the data in $\mathcal{D}_{env}$ is actually drawn from P. However, sometimes this may not be sufficient for deployment. For example, a robot could fail to walk when learning from data that was collected by a different version of the robot (with different mass), or if the same robot collected data but in a different room to deployment (with varied friction). It is this setting, where dynamics may vary at test-time, that is the focus of our work. To learn successfully we propose a novel approach to training robust context-dependent policies.

4 AUGMENTED WORLD MODELS WITH SELF SUPERVISED POLICY ADAPTATION

Figure 2: Training policies in Augmented World Models. For each state-action pair sampled from the buffer, a new augmentation $z_t \sim \mathcal{Z}$ is sampled to produce an augmentation operator $\mathcal{T}_z$, which is applied to the transition. The policy is then trained with the new tuple of data, with the context concatenated to the state.

Figure 3: Self-supervised policy adaptation via learned context. At each timestep, the state s_t is fed into a linear model (trained online at each timestep) to predict the change in state δ_t, and also passed to the fixed World Model (trained on the offline data) to predict the change in state under $\widehat{P}$, $\widehat{\delta}_t$. The approximate context is then $z_t = \frac{\delta_t}{\widehat{\delta}_t}$, which is concatenated with s_t and passed to the agent to produce an action.

In this section we introduce our approach: Augmented World Models. We first discuss our training procedure (Fig. 2) before moving to our self-supervised approach to learning context online (Fig. 3).

4.1 AUGMENTED WORLD MODELS

Rather than seeking to transfer our policy from $\widehat{M}$ to M, we instead wish to transfer from $\widehat{M}$ to $M^\star$, where $M^\star = (\mathcal{S}, \mathcal{A}, P^\star, R^\star, \rho_0, \gamma)$ is an unseen environment with *different dynamics*. Thus, our emphasis shifts to producing experience inside the world model such that our agent is able to generalize to unseen, out of distribution dynamics. We approach this problem by training our policy in an *Augmented World Model*. Formally, we denote an augmentation as $z_t \sim \mathcal{Z}, z \in \mathbb{R}^{|\mathcal{S}|}$, which is sampled at each timestep to produce an augmentation operator $\mathcal{T}_z$. $\mathcal{T}_z$ is applied to (s, a, r, s') tuples from the dataset $\mathcal{D}$, and when used with tuples sampled from $\mathcal{D}_{\overline{env}}$ indirectly induces an augmented distribution $\widehat{P}_z$. For our augmentations to be successful, we wish to include the true modified environment dynamics $P^\star$ in the support of the distribution of augmented dynamics, i.e.

$$\inf{}_z D(\widehat{P}_z(s,a) \| P^\star(s,a)) \leq \epsilon \tag{1}$$

for all s, a, some small $\epsilon > 0$, and suitable distance/divergence metric D. We consider several augmentations, beginning with existing works before moving to new approaches which specifically target the problem of dynamics generalization. We begin with **Random Amplitude Scaling** as in (24), which we refer to as RAD. RAD scales both s_t and s_{t+1} as follows:

$$\mathcal{T}_z : (s_t, a_t, r_t, s_{t+1}) \mapsto (z \odot s_t, a_t, r_t, z \odot s_{t+1}) \tag{2}$$

for $z \sim \text{Unif}([a,b]^{|\mathcal{S}|})$. Given that our focus is on changing dynamics (vs. observational overfitting), we also propose to scale only the next state, i.e., **Random Amplitude Nextstate Scaling** (RANS):

$$\mathcal{T}_z : (s_t, a_t, r_t, s_{t+1}) \mapsto (s_t, a_t, r_t, z \odot s_{t+1}) \tag{3}$$

for $z \sim \text{Unif}([a,b]^{|\mathcal{S}|})$. Note that while RANS is more focused on augmenting dynamics than RAS, it still suffers from a dependence on the magnitude of s_{t+1}. As such, we further propose a more targeted augmentation, which we call **Dynamics Amplitude Sampling** (DAS). Rather than directly scale the state, DAS scales the *change in the state* which we denote with $\delta_t = s_{t+1} - s_t$, as follows:

$$\mathcal{T}_z : (s_t, a_t, r_t, s_{t+1}) \mapsto (s_t, a_t, r_t, s_t + z \odot \delta_t) \tag{4}$$

for $z \sim \text{Unif}([a,b]^{|\mathcal{S}|})$. The full training procedure is shown in Algorithm 1.

Algorithm 1 Augmented World Models: Training

Input: Offline data $\mathcal{D}_{\mathrm{env}}$, Penalty λ, horizon h, batchsize B, augmentation $\mathcal{Z}$.
Initialize: Ensemble of N dynamics models $\widehat{P}$, policy π. Replay buffer $\mathcal{D}_{\widehat{\mathrm{env}}}$
1. Train $\widehat{P}$ in a supervised fashion using $\mathcal{D}_{\mathrm{env}}$.
for *epoch* $= 1, 2, \ldots$ **do**
    (i) Sample initial states: $\{s_1^1, \ldots, s_1^B\} \sim \mathcal{D}_{\mathrm{env}}$
    (ii) Rollout policy (in parallel), using λ-penalized reward, storing all data in $\mathcal{D}_{\widehat{\mathrm{env}}}$
    (iii) Train policy using $\mathcal{D}_{\mathrm{env}} \cup \mathcal{D}_{\widehat{\mathrm{env}}}$. For each (s, a, r, s'), sample $z \sim \mathcal{Z}$ and apply $\mathcal{T}_z$.
end
Return: Policy π

One crucial addition to our method is the use of context. Concretely, when we are optimizing the policy using a batch of data, we concatenate the next state with the augmentation vector z. This allows our policy to be informed of the specific augmentation that was applied to the environment and thus behave accordingly. We note that similar context based methods have been applied successfully in recent meta-learning works (35; 45). However, at test time we do not know z, so what can we use? Next we propose a solution to this problem, learning the context on the fly.

4.2 Self-Supervised Policy Selection

In the meta learning literature there have been many recent successes making use of a *learned context* to adapt a model at test time to a new environment. However, the context is typically taken to be a black box model. In our setting, during training we explicitly know what the context represents: a linear transformation of s_t, or δ_t. Using this insight, we are able to learn an effective context on the fly. Concretely, we observe that from a state s_t drawn from $M^\star$, we can sample an action $a_t \sim \pi$ and then compute an approximate $\widehat{s}_{t+1}$ using our model $\widehat{P}$. With $\widehat{s}_{t+1}$, we have a sample estimate of the *state change under $\widehat{P}$*, i.e. $\widehat{\delta}_t = \widehat{s}_{t+1} - s_t$. We can make this approximation of the next state without interacting with the environment, but once we do take the action a_t in the environment, we then receive the *true next state* s_{t+1} and can store the true difference $\delta_t = s_{t+1} - s_t$. Using the DAS augmentation, we can approximate z as $\frac{\delta_t}{\widehat{\delta}_t}$.

Algorithm 2 Augmented World Models: Testing

Input: Initial state s_1, horizon H, policy π, world model $\widehat{P}$, initial context $\hat{z} = \mathbf{1}^{|\mathcal{S}|}$
Initialize: Linear model f_ψ, dataset $\mathcal{D} = \emptyset$, return $R_0 = 0$.
for *step* $= 1, 2, \ldots H$ **do**
    Select action: $a_t \sim \pi(s_t, \hat{z}_t)$
    Take action: $s_{t+1} \sim P^\star(s_t, a_t)$
    Update return: $R_{t+1} = R_t + R^\star(s_t, a_t, s_{t+1})$
    Update Dataset: $\mathcal{D} \cup (s_t, \delta_t)$.
    Update Linear model by minimizing $\mathcal{L}_{\mathrm{MSE}}(\psi, \mathcal{D})$.
    Predict new context using $\hat{z}_t = \frac{\delta_t}{\widehat{\delta}_t}$.
end
Return: R_T

This however is retroactive; we can only approximate z having already seen the next state, by which time our agent has already acted. We also believe that under changed dynamics (for example damping), the true z likely depends on s, and thus we cannot use a previous true z for future timesteps. Therefore, we instead try to learn a forward dynamics model using the data collected *during* the test rollout. Note that after h timesteps in the environment, we have the following dataset: $\mathcal{D} = \{(s_1, s_2), \ldots, (s_{h-1}, s_h)\}$. This allows us to learn a simple dynamics model $f_\psi : (s_t) \mapsto \delta_t = s_{t+1} - s_t$, by minimizing the mean squared error $\mathcal{L}_{\mathrm{MSE}}(\psi, \mathcal{D})$. We choose to use a regularized linear model for f, since we want it to be "accurate enough" from only a handful of timesteps. Finally, equipped with f_ψ, we can approximate δ_t, and predict the augmentation as $\hat{z}_t = \frac{\delta_t}{\widehat{\delta}_t}$. We then provide our agent with $\widehat{z}_t$ to compute action a_t. The full procedure is shown in Algorithm 2. We note that linear models have recently achieved success in meta learning (30), and are effective in our case due to their data efficiency, but can be replaced by more flexible models to deal with different augmentations. It is also likely that in the case where we wish to extend to k-shot generalization, and we have a larger dataset of transitions, we may be able to train a more flexible (and potentially more accurate) model.

5 EXPERIMENTS

In our experiments we seek to investigate the effectiveness of our approach for zero-shot dynamics generalization from a single offline dataset. To assess this, we will seek to answer a series of questions, ranging from the need to develop methods for dynamics generalization through to the impact of adaptive contexts. We begin with the former, and ask:

Do we really need to develop methods specifically for dynamics generalization?

To answer this, we train MOPO using offline data from a single environment, and test it under changed dynamics. We consider the HalfCheetah environment from the OpenAI Gym (6), using offline data from D4RL (10). We train a MOPO agent using the mixed dataset, using our own implementation of the algorithm (but using the same hyperparameters as the original authors). To test the trained policy, we vary both the mass of the agent and damping coefficient by a multiplicative factor.[1] In this work we consider a grid of the following values for HalfCheetah: $\{0.25, 0.5, 0.75, 1.0, 1.25, 1.5, 1.75\}$ and $\{0.5, 0.75, 1.0, 1.25, 1.5\}$ for Walker2d, representing a significant out-of-distribution shift.

Figure 4: **Left:** Mean performance for 5 seeds for MOPO on HalfCheetah environments with varying dynamics. Note the central cell (1,1) corresponds to the in-sample data. **Right:** Mean performance for 3 seeds for MBPO with a dynamics oracle on HalfCheetah with $1.5\times$ mass and damping.

The results (Fig. 4, left), show that MOPO performance is highly dependent on the training dynamics being consistent with the in-sample data. We see in the central cell, that performance for our version of MOPO matches the author results (42), and in some cases we even see small gains (for example: mass $= 0.75$, damping $= 1.0$). However, on the top left we see dramatically weaker performance, often below 1k, indicating the robot is failing to achieve locomotion. This shows MOPO is brittle to changing dynamics. Before evaluating Augmented World Models, we first test whether training with the "correct" augmentation improves generalization performance. In short, we ask:

Is augmenting dynamics even worthwhile?

Our approach to answering this question is as follows: we generate 1×10^5 states by training with a model-free SAC in the 'true' environment, and save the visited states from its buffer. We then use these starting states to train a policy in an offline MBPO[2] manner, using augmented world models. However, instead of sampling $z_t \sim \mathcal{Z}$, we provide the true $z = \frac{\delta^\star}{\widehat{\delta}}$ as we have access to the 'true' and 'modified' environments; we refer to this as an *oracle* version of our method, and is simply designed to assess the viability of our approach. Note that we keep $\widehat{R}$ from the 'true' environment, so do not provide any information about augmented rewards. We consider two baselines, MBPO and SAC. We train MBPO until convergence (also using an oracle WM, albeit of the 'true' environment), and SAC for 1×10^5 steps on the 'modified' environment.

As shown in the right of Fig. 4, when provided with the true z, Augmented World Models outperforms MBPO and SAC trained in the 'true' environment. The SAC result is surprising: the baseline agent was trained directly on the 'modified' environment for the same number of steps as the policy that generated our oracle starting states. One explanation is the greater exploration induced by the 'easier' dynamics of the 'true' environment. This validates our approach; as long as we augment the dynamics $\widehat{P}$ from a model correctly, we can generalize to unseen dynamics. Neither the starting states nor rewards need to be generated from the 'modified' environment. Our next question is a simple one:

---

[1]The standard environment (both in Gym and D4RL) corresponds to these factors both being set to 1.0.

[2]Since we have access to the true environment, there is no need for the MOPO penalty

Which augmentation strategy is most effective?

Figure 5: Average performance gains of different World Model augmentations over base MOPO for different levels of damping and mass in the HalfCheetah test environment (5 seeds).

To test this, we train as in Algorithm 1, *without* context, to test the effectiveness of the training process. We use the HalfCheetah mixed dataset and train a MOPO agent, augmenting either both s and s' (RAD), just s' (RANS) or just δ (DAS); the results are shown in Fig. 5. As we see, the RAD augmentation (taken from (24)) fails to improve dynamics generalization, actually leading to worse performance overall. However, we do notice stronger performance (+189 return) if the dynamics are the same as in training; this suggests we may be improving in-domain dynamics generalization, but not *out-of-domain* dynamics generalization, which is our aim. Switching to augment just the next state with RANS does improve performance on unseen dynamics, as we are influencing the *dynamics*, not just the observation. However, DAS clearly provides the strongest performance. As a result, we use DAS for Augmented World Models. Our final algorithm design question is as follows:

Does training with context improve performance?

Figure 6: Average performance gains of adding contexts over base MOPO for different levels of damping and mass in the HalfCheetah test environment (5 seeds).

To answer this question we return to the HalfCheetah mixed setting from Fig. 5, taking the policy trained in the Augmented World Model with DAS. We now train two additional agents: 1) Default Context: at train time the agent is provided with the DAS augmentation z as context, at test time it is provided with a vector of ones, $\mathbf{1}^{|S|}$ and 2) Learned Context: trained the same way as 1) but learning the context online using Algorithm 2. The results for five seeds are shown in in Fig. 6. We observe that training with a context (orange) improves performance on average, while adapting the context on the fly (green) leads to further gains (+80 on average). These methods combine to produce our final Augmented World Models algorithm. Now we are ready for the final question:

Can Augmented World Models improve zero-shot generalization?

Table 1: A high level summary of the performance averaged over all test-time dynamics. Each entry for HalfCheetah corresponds to the mean of 49 different dynamics, while for Walker2d it corrsponds to 25 dynamics. Results show the mean $\pm$1std. $\star$ indicates $p < 0.05$ for Welch's t-test on the gain over MOPO.

Dataset Type	Environment	MOPO	AugWM (Ours)
Random	HalfCheetah	2303 ± 112	$2818 \pm 197 \star$
Random	Walker2d	569 ± 103	706 ± 139
Mixed	HalfCheetah	3447 ± 218	$3948 \pm 122 \star$
Mixed	Walker2d	946 ± 95	$1317 \pm 206 \star$
Medium	HalfCheetah	2954 ± 89	2967 ± 106
Medium	Walker2d	1477 ± 337	1614 ± 440
Med-Expert	HalfCheetah	1590 ± 766	$2885 \pm 432 \star$
Med-Expert	Walker2d	1062 ± 334	$2521 \pm 316 \star$

To answer this question we perform a rigorous analysis, using multiple benchmarks from the D4RL dataset (10). Namely, we consider the random, medium, mixed and med-expert datasets for both

Walker2d and HalfCheetah. In each setting, we compare Augmented World Models against base MOPO on zero-shot performance, training entirely on the data provided, but not seeing the test environment until evaluation. The results are shown as a change vs. MOPO, averaged over one dimension in Fig. 9, and as a total return number averaged over both dimensions in Table 1. For additional implementation details (such as choice of hyperparameters) see the Appendix (Section B). Augmented World Models provides *statistically significant* improvements in zero-shot performance v.s. MOPO in many cases, achieving successful policies where MOPO fails.

Finally, we note that the dynamics may change *during* an episode; consider the case where a robot suffers a motor malfunction, causing it to deliver less power to its joints. It is clear that the underlying dynamics will be different, and it will be challenging to be robust to such changes when only training from a single dataset of offline experience. For a first test of this phenomenon, we consider a 1500 step rollout in the HalfCheetah environment, initially using the offline dynamics (mass = 1, damping = 1), before changing to mass = 0.75 and damping = 0.5 after 500 steps. The performance is shown in Fig.7. As we see, after 500 steps the performance of MOPO dramatically reduces. This is because the agent continues to apply the same force and thus falls forward with lighter mass. For our Augmented World Model agent, performance initially drops, then when the new context is learned we achieve *higher* performance than before, making use of the lighter torso.

Figure 7: Performance under changing dynamics. Left = cumulative returns, Right = rolling average single step reward. Both averaged over twenty seeds, shaded area shows ±1std.

Discussion We believe our experiments provide significant support to the claim that training with Augmented World Models improves zero-shot dynamics generalization. In a broad set of commonly used datasets, and with a wide range of out-of-distribution dynamics, our algorithms learn good policies where the state-of-the-art model based offline RL method fails.[3] The improvement over the baseline is down to a number of novel contributions: 1) using *dynamics augmentation* rather than *observation augmentation*; 2) training and testing with a context-based policy. Regarding limitations, we note that training inside the WM with context generally takes longer to converge (Appendix B). Furthermore, our experiments with dynamics focused on mass or damping, but it remains to be seen if it generalizes to asymmetric changes such as crippled joints.

6 CONCLUSION AND FUTURE WORK

In this paper we proposed Augmented World Models, which we show sufficiently simulates changes in dynamics such that agents can generalize in a zero-shot manner. We believe that we are the first to propose this problem setting, and our results show a significant improvement over existing state-of-the-art methods which ignore this problem.

A promising line of future work we are considering is to see if it is possible to meta-learn a policy over Augmented World Models such that it can adapt in the few-shot setting, quickly achieving optimal test time performance under new dynamics. There is evidence that data augmentation can improve robustness in meta-learning (34), and could extend to strong performance in out-of-distribution tasks. We also wish to consider varying goals at test time, and other potential sources of non-stationarity which may impact policy performance. We can also consider extending our work to the pixel-based RL regime, which has received a great deal of recent attention (15; 14). We believe our transition based augmentations will be applicable to a latent representation, as commonly used in state-of-the-art vision MBRL approaches. Thus we think that extending our work to this setting, while a considerable feat of engineering, should not require significant methodological changes.

---

[3]For videos see: https://sites.google.com/view/augmentedworldmodels/

REFERENCES

[1] A. Ajay, A. Kumar, P. Agrawal, S. Levine, and O. Nachum. OPAL: Offline primitive discovery for accelerating offline reinforcement learning. In *International Conference on Learning Representations*, 2021.

[2] O. M. Andrychowicz, B. Baker, M. Chociej, R. Józefowicz, B. McGrew, J. Pachocki, A. Petron, M. Plappert, G. Powell, A. Ray, J. Schneider, S. Sidor, J. Tobin, P. Welinder, L. Weng, and W. Zaremba. Learning dexterous in-hand manipulation. *The International Journal of Robotics Research*, 39(1):3–20, 2020.

[3] R. Antonova, S. Cruciani, C. Smith, and D. Kragic. Reinforcement learning for pivoting task, 2017.

[4] A. Argenson and G. Dulac-Arnold. Model-based offline planning. In *International Conference on Learning Representations*, 2021.

[5] P. Ball, J. Parker-Holder, A. Pacchiano, K. Choromanski, and S. Roberts. Ready policy one: World building through active learning. In *Proceedings of the 37th International Conference on Machine Learning, ICML.* 2020.

[6] G. Brockman, V. Cheung, L. Pettersson, J. Schneider, J. Schulman, J. Tang, and W. Zaremba. Openai gym. *arXiv preprint arXiv:1606.01540*, 2016.

[7] K. Chua, R. Calandra, R. McAllister, and S. Levine. Deep reinforcement learning in a handful of trials using probabilistic dynamics models. In *Advances in Neural Information Processing Systems 31*, pages 4754–4765. 2018.

[8] I. Clavera, A. Nagabandi, S. Liu, R. S. Fearing, P. Abbeel, S. Levine, and C. Finn. Learning to adapt in dynamic, real-world environments through meta-reinforcement learning. In *International Conference on Learning Representations*, 2019.

[9] I. Clavera, J. Rothfuss, J. Schulman, Y. Fujita, T. Asfour, and P. Abbeel. Model-based reinforcement learning via meta-policy optimization. In *2nd Annual Conference on Robot Learning, CoRL 2018, Zürich, Switzerland, 29-31 October 2018, Proceedings*, volume 87 of *Proceedings of Machine Learning Research*, pages 617–629. PMLR, 2018.

[10] J. Fu, A. Kumar, O. Nachum, G. Tucker, and S. Levine. D4{rl}: Datasets for deep data-driven reinforcement learning, 2021.

[11] S. Fujimoto, D. Meger, and D. Precup. Off-policy deep reinforcement learning without exploration. In *International Conference on Machine Learning*, pages 2052–2062, 2019.

[12] D. Ha and J. Schmidhuber. Recurrent world models facilitate policy evolution. In *Proceedings of the 32Nd International Conference on Neural Information Processing Systems*, NeurIPS'18, pages 2455–2467, 2018.

[13] T. Haarnoja, A. Zhou, K. Hartikainen, G. Tucker, S. Ha, J. Tan, V. Kumar, H. Zhu, A. Gupta, P. Abbeel, and S. Levine. Soft actor-critic algorithms and applications. *CoRR*, abs/1812.05905, 2018.

[14] D. Hafner, T. Lillicrap, J. Ba, and M. Norouzi. Dream to control: Learning behaviors by latent imagination. In *International Conference on Learning Representations*, 2020.

[15] D. Hafner, T. Lillicrap, I. Fischer, R. Villegas, D. Ha, H. Lee, and J. Davidson. Learning latent dynamics for planning from pixels. In K. Chaudhuri and R. Salakhutdinov, editors, *Proceedings of the 36th International Conference on Machine Learning*, pages 2555–2565, 2019.

[16] N. Hansen, R. Jangir, Y. Sun, G. Alenyà, P. Abbeel, A. A. Efros, L. Pinto, and X. Wang. Self-supervised policy adaptation during deployment. In *International Conference on Learning Representations*, 2021.

[17] S. James, A. J. Davison, and E. Johns. Transferring end-to-end visuomotor control from simulation to real world for a multi-stage task. In *1st Conference on Robot Learning.* 2017.

[18] M. Janner, J. Fu, M. Zhang, and S. Levine. When to trust your model: Model-based policy optimization. In *Advances in Neural Information Processing Systems*. 2019.

[19] L. Kaiser, M. Babaeizadeh, P. Milos, B. Osiński, R. H. Campbell, K. Czechowski, D. Erhan, C. Finn, P. Kozakowski, S. Levine, A. Mohiuddin, R. Sepassi, G. Tucker, and H. Michalewski. Model based reinforcement learning for Atari. In *International Conference on Learning Representations*, 2020.

[20] R. Kidambi, A. Rajeswaran, P. Netrapalli, and T. Joachims. Morel : Model-based offline reinforcement learning. In *Advances in Neural Information Processing Systems*. 2020.

[21] I. Kostrikov, D. Yarats, and R. Fergus. Image augmentation is all you need: Regularizing deep reinforcement learning from pixels. In *International Conference on Learning Representations*. 2021.

[22] A. Kumar, A. Zhou, G. Tucker, and S. Levine. Conservative q-learning for offline reinforcement learning. In *Advances in Neural Information Processing Systems*. 2020.

[23] T. Kurutach, I. Clavera, Y. Duan, A. Tamar, and P. Abbeel. Model-ensemble trust-region policy optimization. In *International Conference on Learning Representations*, 2018.

[24] M. Laskin, K. Lee, A. Stooke, L. Pinto, P. Abbeel, and A. Srinivas. Reinforcement learming with augmented data. In *Advances in Neural Information Processing Systems 33*. 2020.

[25] M. Laskin, A. Srinivas, and P. Abbeel. CURL: Contrastive unsupervised representations for reinforcement learning. In *Proceedings of the 37th International Conference on Machine Learning*, 2020.

[26] S. Levine, A. Kumar, G. Tucker, and J. Fu. Offline reinforcement learning: Tutorial, review, and perspectives on open problems, 2020.

[27] A. Nagabandi, C. Finn, and S. Levine. Deep online learning via meta-learning: Continual adaptation for model-based RL. In *International Conference on Learning Representations*, 2019.

[28] D. A. Nix and A. S. Weigend. Estimating the mean and variance of the target probability distribution. In *Proceedings of 1994 IEEE International Conference on Neural Networks (ICNN'94)*, volume 1, pages 55–60 vol.1, 1994.

[29] OpenAI, I. Akkaya, M. Andrychowicz, M. Chociej, M. Litwin, B. McGrew, A. Petron, A. Paino, M. Plappert, G. Powell, R. Ribas, J. Schneider, N. Tezak, J. Tworek, P. Welinder, L. Weng, Q. Yuan, W. Zaremba, and L. Zhang. Solving rubik's cube with a robot hand. *CoRR*, abs/1910.07113, 2019.

[30] M. Peng, B. Zhu, and J. Jiao. Linear representation meta-reinforcement learning for instant adaptation. *CoRR*, 2021.

[31] X. B. Peng, M. Andrychowicz, W. Zaremba, and P. Abbeel. Sim-to-real transfer of robotic control with dynamics randomization. In *IEEE International Conference on Robotics and Automation, ICRA*, 2018.

[32] S. Pitis, E. Creager, and A. Garg. Counterfactual data augmentation using locally factored dynamics. In *Advances in Neural Information Processing Systems*. 2020.

[33] R. Raileanu, M. Goldstein, D. Yarats, I. Kostrikov, and R. Fergus. Automatic data augmentation for generalization in deep reinforcement learning. *CoRR*, abs/2006.12862, 2020.

[34] J. Rajendran, A. Irpan, and E. Jang. Meta-learning requires meta-augmentation. In *Advances in Neural Information Processing Systems*. 2020.

[35] K. Rakelly, A. Zhou, C. Finn, S. Levine, and D. Quillen. Efficient off-policy meta-reinforcement learning via probabilistic context variables. In *Proceedings of the 36th International Conference on Machine Learning, ICML 2019, 9-15 June 2019, Long Beach, California, USA*, volume 97, pages 5331–5340. PMLR, 2019.

[36] J. Schrittwieser, I. Antonoglou, T. Hubert, K. Simonyan, L. Sifre, S. Schmitt, A. Guez, E. Lockhart, D. Hassabis, T. Graepel, T. P. Lillicrap, and D. Silver. Mastering Atari, Go, Chess and Shogi by Planning with a Learned Model. *CoRR*, abs/1911.08265, 2019.

[37] Y. Seo, K. Lee, I. Clavera, T. Kurutach, J. Shin, and P. Abbeel. Trajectory-wise multiple choice learning for dynamics generalization in reinforcement learning. In *Advances in Neural Information Processing Systems*, 2020.

[38] X. Song, Y. Jiang, S. Tu, Y. Du, and B. Neyshabur. Observational overfitting in reinforcement learning. In *International Conference on Learning Representations*, 2020.

[39] J. Tobin, R. Fong, A. Ray, J. Schneider, W. Zaremba, and P. Abbeel. Domain randomization for transferring deep neural networks from simulation to the real world. In *2017 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, pages 23–30, 2017.

[40] R. Volpi, H. Namkoong, O. Sener, J. C. Duchi, V. Murino, and S. Savarese. Generalizing to unseen domains via adversarial data augmentation. In S. Bengio, H. Wallach, H. Larochelle, K. Grauman, N. Cesa-Bianchi, and R. Garnett, editors, *Advances in Neural Information Processing Systems*, volume 31, pages 5334–5344. Curran Associates, Inc., 2018.

[41] Y. Wu, G. Tucker, and O. Nachum. Behavior regularized offline reinforcement learning. In *To Appear: The International Conference on Learning Representations (ICLR)*. 2021.

[42] T. Yu, G. Thomas, L. Yu, S. Ermon, J. Zou, S. Levine, C. Finn, and T. Ma. Mopo: Model-based offline policy optimization. In *Advances in Neural Information Processing Systems*. 2020.

[43] W. Yu, J. Tan, C. K. Liu, and G. Turk. Preparing for the unknown: Learning a universal policy with online system identification. In N. M. Amato, S. S. Srinivasa, N. Ayanian, and S. Kuindersma, editors, *Robotics: Science and Systems XIII*, 2017.

[44] W. Zhou, L. Pinto, and A. Gupta. Environment probing interaction policies. In *International Conference on Learning Representations*, 2019.

[45] L. Zintgraf, K. Shiarlis, M. Igl, S. Schulze, Y. Gal, K. Hofmann, and S. Whiteson. Varibad: A very good method for bayes-adaptive deep rl via meta-learning. In *International Conference on Learning Representations*, 2020.

APPENDIX

A ADDITIONAL EXPERIMENTS

Here we show the more granular experimental results, presented in condensed form in Table 1. In Fig. 9 we show the improvement vs. MOPO for each dimension of mass (green) or damping (blue), for HalfCheetah (top) and Walker2d (bottom).

Figure 8: Mean improvement for Augmented World Models over MOPO for the HalfCheetah environment, averaged over five seeds. Top row (blue) = damping scale, bottom row (green) = mass scale. Dotted line is the mean, the same value for both damping and mass.

Figure 9: Mean improvement for Augmented World Models over MOPO for the Walker2d environment, averaged over five seeds. Top row (blue) = damping scale, bottom row (green) = mass scale. Dotted line is the mean, the same value for both damping and mass.

In this section we show the performance for Augmented World Models with different training ranges for the DAS augmentation (z train in Table 3). We train with adaptive context on the HalfCheetah mixed dataset, and present the results in Fig. 10. As we see, $[0.75, 1.25]$ and $[0.5, 1.5]$ perform the best. Based on this, we use $[0.5, 1.5]$ for our experiments as we believe this helps us sample a wider set of dynamics, helping us generalize better across all environments and data sets.

B IMPLEMENTATION DETAILS

B.1 HYPERPARAMETERS

Our algorithm is based on MOPO (42) with the following values for the rollout length h and penalty coefficient λ:

AWM specific hyperparameters are listed below. For each evaluation rollout, we clear the buffer of stored true modified environment transitions to measure zero-shot performance. We adapt using the context after a set number of steps, k, in the environment to train the linear model. The two ranges used for the context z during training and test time are different. At test time, the estimated context is clipped to remain within the given bounds.

---

[4]We follow the original MOPO hyperparameters for all datasets except for walker2d-mixed where we found (1, 1) worked better for both MOPO and our method than (5, 5).

Figure 10: Performance for Augmented World Models with the DAS augmentation. Each plot shows different values for a and b, the ranges for the sampled noise.

Table 2: Hyperparameters used in the D4RL datasets.

Dataset Type	Environment	MOPO (h, λ)
random	halfcheetah	5, 0.5
random	walker2d	1, 1
medium	halfcheetah	1, 1
medium	walker2d	1, 1
mixed	halfcheetah	5, 1
mixed	walker2d	1, 1 [4]
med-expert	halfcheetah	5, 1
med-expert	walker2d	1, 2

Table 3: AWM Hyperparameters

Parameter	Value
evaluation rollouts	5
MOPO offline epochs	400
AWM offline epochs	900
k, steps for adaptation	300
z train range	[0.5, 1.5]
z test range	[0.93, 1.07]

B.2 D4RL DATASET

We evaluate our method on D4RL (10) datasets based on the MuJoCo continuous control tasks (halfcheetah and walker2d). The four dataset types we evaluate on are:

- **random:** roll out a randomly initialized policy for 1M steps.
- **medium:** partially train a policy using SAC, then roll it out for 1M steps.
- **mixed:** train a policy using SAC until a certain (environment-specific) performance threshold is reached, and take the replay buffer as the batch.
- **medium-expert:** combine 1M samples of rollouts from a fully-trained policy with another 1M samples of rollouts from a partially trained policy or a random policy.

This gives us a total of 8 experiments.