An Efficient Pessimistic-Optimistic Algorithm for Stochastic Linear Bandits with General Constraints

Abstract

This paper considers stochastic linear bandits with general nonlinear constraints. The objective is to maximize the expected cumulative reward over horizon T subject to a set of constraints in each round $\tau \leqslant T$. We propose a pessimistic-optimistic algorithm for this problem, which is efficient in two aspects. First, the algorithm yields $\tilde{\mathcal{O}}\left(\left(\frac{K^{0.75}}{\delta} + d\right)\sqrt{\tau}\right)$ (pseudo) regret in round $\tau \leqslant T$, where K is the number of constraints, d is the dimension of the reward feature space, and δ is a Slater's constant; and *zero* constraint violation in any round $\tau > \tau'$, where τ' is *independent* of horizon T. Second, the algorithm is computationally efficient. Our algorithm is based on the primal-dual approach in optimization and includes two components. The primal component is similar to unconstrained stochastic linear bandits (our algorithm uses the linear upper confidence bound algorithm (LinUCB)). The computational complexity of the dual component depends on the number of constraints, but is independent of the sizes of the contextual space, the action space, and the feature space. Thus, the computational complexity of our algorithm is similar to that of LinUCB for unconstrained stochastic linear bandits.

1 Introduction

Stochastic linear bandits have a broad range of applications in practice, including online recommendations, job assignments in crowdsourcing, and clinical trials in healthcare. Most existing studies on stochastic linear bandits formulated them as unconstrained online optimization problems, limiting their application to problems with operational constraints such as safety, fairness, and budget constraints. In this paper, we consider a stochastic linear bandit with general constraints. As in a standard stochastic linear bandit, at the beginning of each round $t \in [T]$, the learner is given a context $c(t)$ that is randomly sampled from the context set $\mathcal{C}$ (a countable set), and takes an action $A(t) \in [J]$. The learner then receives a reward $R(c(t), A(t)) = r(c(t), A(t)) + \eta(t)$, where $r(c, j) = \langle \theta_*, \phi(c, j) \rangle$, $\phi(c, j) \in \mathbb{R}^d$ is a d-dimensional feature vector for (context, action) pair (c, j), $\theta_* \in \mathbb{R}^d$ is an unknown underlying vector to be learned, and $\eta(t)$ is a zero-mean random variable. For constrained stochastic linear bandits, we further assume when action $A(t)$ is taken on context $c(t)$, it incurs K different types of costs, denoted by $W^{(k)}(c(t), A(t))$. We assume $W^{(k)}(c, j)$ is a random variable with mean $w^{(k)}(c, j)$ that is unknown to the learner. This paper considers general cost functions and does *not* require $w^{(k)}(c, j)$ to have a linear form like $r(c, j)$.

Denote the action taken by policy π in round t by $A^\pi(t)$. The learner's objective is to learn a policy π that maximizes the cumulative rewards over horizon T subject to *anytime cumulative constraints*:

$$\max_\pi \mathbb{E}\left[\sum_{t=1}^{T} R(c(t), A^\pi(t))\right] \quad (1) \qquad \mathbb{E}\left[\sum_{t=1}^{\tau} W^{(k)}(c(t), A^\pi(t))\right] \leqslant 0, \forall\, \tau \in [T], k \in [K]. \quad (2)$$

The constraint (2) above may represent different operational constraints including safety, fairness, and budget constraints.

Anytime cumulative constraints

In the literature, constraints in stochastic bandits have been formulated differently. There are two popular formulations. The first one is a cumulative constraint over horizon T, including knapsack bandits [10, 9, 3, 4, 5, 20, 11] where the process terminates when the total budget has been consumed; fair bandits where the number of times an action can be taken must exceed a threshold at the end of the horizon [13]; and contextual bandits with a cumulative budget constraint [40, 16]. In these settings, the feasible action set in each round depends on the history. In general, the learner has more flexibility in the earlier rounds, close to that in the unconstrained setting. Another formulation is *anytime* constraints, which either require the expected cost of the action taken in each round to be lower than a threshold [6] or the expected cost of the policy in each round is lower than a threshold [32]. We call them *anytime* action constraints and *anytime* policy constraints, respectively.

Our constraint in the form of (2) is an *anytime cumulative constraint*, i.e., it imposes a cumulative constraint in *every* round. This anytime cumulative constraint is most similar to the anytime policy constraint in [32] because the average cost of a policy is close to its mean after the policy has been applied for many rounds and the process converges, so it can be viewed as a cumulative constraint on actions over many rounds (like ours). Furthermore, when our anytime cumulative constraint (2) is satisfied, it is guaranteed that the time-average cost is below a threshold in every round.

Figure 1: A conceptual description of feasible policy sets under different constraint formulations.

In summary, our anytime cumulative constraint is stricter than a cumulative constraint over fixed horizon T but is less restrictive than anytime action constraint in [6]. Figure 1 provides a conceptual description of the relationship between these different forms of constraints.

Main Contributions

This paper presents a pessimistic-optimistic algorithm based on the primal-dual approach in optimization for the problem defined in (1)-(2). The algorithm is efficient in two aspects. First, the algorithm yields $\tilde{\mathcal{O}}\left(\left(\frac{K^{0.75}}{\delta} + d\right)\sqrt{\tau}\right)$ regret in round $\tau \leqslant T$ and achieves *zero* constraint violation in any round $\tau > \tau'$ for a constant τ' independent of horizon T. Second, the algorithm is computationally efficient.

For computational efficiency, the design of our algorithm is based on the primal-dual approach in optimization. The computation of the primary component is similar to unconstrained stochastic linear bandits [17, 33, 28, 1, 14]. The dual component includes a set of Lagrangian multipliers that are updated in a simple manner to keep track of the levels of constraint violations so far in each round; the update depends on the number of constraints, but it is independent of the sizes of the contextual space, the action space, and the feature space. Thus, the overall computational complexity of our algorithm is similar to that of LinUCB in the unconstrained setting. This results in a much more efficient calculation comparing to OPLB proposed in [32]. OPLB needs to construct a safe policy set in each round, hence, its computational complexity is prohibitively high as the authors acknowledged.

For constraint violation, our algorithm guarantees that for any $\tau > \tau'$, the constraint holds with probability one. In other words, after a constant number of rounds, the constraint is always satisfied. This is in contrast to prior works [32, 6], where anytime constraints are proven to hold over horizon T with probability $1 - \chi$ for a constant χ. In other words, the anytime constraints may be violated with probability χ, and it is not clear how often they are violated when it happens. Furthermore, beyond mean cost constraints considered in (2) and in [32, 6], we prove that a sample-path version of constraint (2) holds with probability $1 - O\left(e^{-\frac{\delta\sqrt{\tau}}{50K^{2.5}}}\right)$ in round τ under our algorithm.

To summarize, our algorithm is computationally efficient and provides strong guarantees on both regret and constraint violations. Additionally, our cost function is in a general form and does not need to be linear as those in [32, 6]. An overview of other related work can be found in Appendix A.

Notation. $f(n) = \tilde{\mathcal{O}}(g(n))$ denotes $f(n) = O(g(n)\log^k n)$ with $k > 0$; $[N]$ denotes the set $\{1, 2, \cdots, N\}$; $\langle \cdot, \cdot \rangle$ denotes the inner product; $(\cdot)^\dagger$ denotes the transpose of a vector or a matrix; $||\cdot|| = ||\cdot||_2$, and $||\mathbf{x}||_\Sigma = \sqrt{\mathbf{x}^\dagger \Sigma \mathbf{x}}$. We summarize our notation in Appendix B.

2 A Pessimistic-Optimistic Algorithm

We consider a stochastic linear bandit over horizon T as described in the introduction. The learner's objective is to maximize the cumulative reward over time horizon T subject to K anytime cumulative constraints as defined in (1)-(2). To address the challenges on the *unknown* reward and cost in constraint, as well as the anytime cumulative constraints, we develop a pessimistic-optimistic algorithm based on the primal-dual approach for constrained optimization. We first give out the intuition of the algorithm and then provide the formal statement of the algorithm.

To start, we consider a baseline, deterministic problem that replaces all the random variables with their expectations. Different from the conventional setup, we introduce a "tightness" constant $\epsilon > 0$:

$$\max_{\mathbf{x}} \sum_{c \in \mathcal{C}, j \in [J]} p_c r(c, j) x_{c,j} \tag{3}$$

$$\text{s.t.} \sum_{j \in [J]} x_{c,j} = 1, \ x_{c,j} \geqslant 0, \forall c \in \mathcal{C}, \tag{4}$$

$$\sum_{c \in \mathcal{C}, j \in [J]} p_c w^{(k)}(c, j) x_{c,j} + \epsilon \leqslant 0, \ \forall k \in [K], \tag{5}$$

where $x_{c,j}$ can be viewed as the probability of taking action j on context c, and p_c is the probability that context c is selected in each round. We will discuss in further details the importance of the tightness constant ϵ in Section 4. The Lagrangian of the problem above is

$$\max_{\mathbf{x}: \sum_j x_{c,j}=1, x_{c,j} \geqslant 0} \sum_{c,j} p_c r(c, j) x_{c,j} - \sum_k \lambda^{(k)} \left(\sum_{c \in \mathcal{C}, j \in [J]} p_c w^{(k)}(c, j) x_{c,j} + \epsilon \right), \tag{6}$$

where $\lambda^{(k)}$ is the Lagrange multiplier associated with the kth constraint in (5). Fixing the values of the Lagrange multipliers, solving the optimization problem is equivalent to solving $|\mathcal{C}|$ separate subproblems (7), one for each context c, because the optimization variables $\mathbf{x}$ are coupled through j only:

$$\max_{\mathbf{x}: \sum_j x_{c,j}=1, x_{c,j} \geqslant 0} p_c \left(\sum_j r(c, j) x_{c,j} - \sum_k \lambda^{(k)} \left(\sum_j w^{(k)}(c, j) x_{c,j} \right) \right). \tag{7}$$

Since the problem above is a linear programming, one of the optimal solutions is $x_{c,j} = 1$ for $j = j^*$ and $x_{c,j} = 0$ otherwise, where

$$j^* \in \arg\max_j r(c, j) - \sum_k \lambda^{(k)} w^{(k)}(c, j) \tag{8}$$

and a tie can be broken arbitrarily. If we call $r(c, j) - \sum_k \lambda^{(k)} w^{(k)}(c, j)$ the action-value of context c, then the solution for fixed values of Lagrange multipliers is to choose an action with the highest action-value. We may view the action value here plays a similar role as the Q-value (also called action-value function) in Q-learning [37].

Now the challenges to find a solution according to (8) include: (i) both $r(c, j)$ and $w^{(k)}(c, j)$ are unknown, and (ii) the optimal Lagrange multipliers $\lambda^{(k)}$ are also unknown. To overcome these challenges, we develop a pessimistic-optimistic algorithm that

- Uses LinUCB to estimate $r(c, j)$ based on its linear structure.

118 • Uses observed $W^{(k)}(c(t), j)$ to replace $w^{(k)}(c(t), j)$ at each round t.

119 • Uses the following function to dynamically approximate the Lagrange multipliers ($X_j(t) = 1$ if
120 $A(t) = j$; otherwise $X_j(t) = 0$):

$$Q^{(k)}(t+1) = \left[Q^{(k)}(t) + \sum_{j \in [J]} W^{(k)}(c(t), j) X_j(t) + \epsilon_t \right]^+, \forall k.$$

121 In other words, we increase its value when the current cost exceeds the current "budget," and
122 decrease it otherwise. Therefore, $Q^{(k)}(t)$ keeps track of the cumulative constraint violation by
123 round t.

124 • We further add a scaling parameter $1/V_t$ to $Q^{(k)}(t)$, i.e. $Q^{(k)}(t)/V_t$, to approximate $\lambda^{(k)}$. With a
125 carefully designed V_t, we can control the tradeoff between maximizing reward and minimizing
126 constraint violation in the policy and achieve the regret and constraint violation bounds to be
127 presented in the main theorem.

Next, we formally state our algorithm. This algorithm takes the following information as input at the
beginning of each round t: (i) historical observations

$$\mathcal{F}_{t-1} = \{c(s), A(s), R(c(s), A(s)), W^{(k)}(c(s), A(s))\}_{s \in [t-1], k \in [K]},$$

128 (ii) current observations $c(s)$ and $\{W^{(k)}(c(s), j)\}_{k \in [K], j \in [J]}$, and (iii) system parameters: the feature
129 map $\{\phi(c, j)\}_{c \in \mathcal{C}, j \in [J]}$, time horizon T, and a pre-set constant δ. In the analysis of our algorithm, we
130 will reveal the connection of this constant δ with Slater's condition. The algorithm outputs the action
131 in each round, observes reward $R(c(t), A(t))$, makes updates, and then moves to the next round $t + 1$.

132 **A Pessimistic-Optimistic Algorithm**

---

133 **Initialization:** $Q^{(k)}(1) = 0$, $\mathcal{B}_1 = \{\theta | ||\theta||_{\Sigma_0} \leq \sqrt{\beta_1}\}$, $\Sigma_0 = \mathbf{I}$ and $\sqrt{\beta_1} = m + \sqrt{2 \log T}$.

134 For $t = 1, \cdots, T$,

135 • **Set:** $V_t = \delta K^{0.25} \sqrt{\frac{2t}{3}}$ and $\epsilon_t = K^{0.75} \sqrt{\frac{6}{t}}$.

• **LinUCB (Optimistic):** Use LinUCB to estimate $r(c(t), j)$ for all j :
$$\hat{r}(c(t), j) = \min\{1, \tilde{r}(c(t), j)\} \text{ with } \tilde{r}(c(t), j) = \max_{\theta \in \mathcal{B}_t} \langle \theta, \phi(c(t), j) \rangle.$$

136 • **MaxValue:** Compute *pseudo-action-value* of context $c(t)$ for all action j, and take the action
137 $A(t) = j^*$ with the highest pseudo-action-value, breaking a tie arbitrarily

$$j^* \in \arg \max_j \underbrace{\hat{r}(c(t), j) - \frac{1}{V_t} \sum_k W^{(k)}(c(t), j) Q^{(k)}(t)}_{\text{pseudo action value of } (c(t), j)}.$$

138 • **Dual Update (Pessimistic):** Update the estimates of dual variables $Q^{(k)}(t)$ as follows:

$$Q^{(k)}(t+1) = \left[Q^{(k)}(t) + \sum_j W^{(k)}(c(t), j) X_j(t) + \epsilon_t \right]^+, \forall k. \tag{9}$$

139 • **Confidence Set Update:** Update Σ_t, $\hat{\theta}_t$, β_{t+1} and $\mathcal{B}_{t+1}$ by the received reward $R(c(t), j^*)$:

$$\Sigma_t = \Sigma_{t-1} + \phi(c(t), j^*) \phi^\dagger(c(t), j^*), \quad \hat{\theta}_t = \Sigma_t^{-1} \sum_{s=1}^t \phi(c(s), A(s)) R(c(s), A(s)),$$

$$\sqrt{\beta_{t+1}} = m + \sqrt{2 \log T + d \log \left(\frac{d+t}{d} \right)}, \quad \mathcal{B}_{t+1} = \{\theta \mid ||\theta - \hat{\theta}_t||_{\Sigma_t} \leq \sqrt{\beta_{t+1}}\}.$$

---

140 The complexity of our algorithm is similar to LinUCB. The additional complexity is proportional to
141 the number of constraints (for updating $Q^{(k)}$), and it is much lower than OPLB in [32], where the
142 construction of a safe policy set in each round is a major computational hurdle. Our algorithm is
143 computationally efficient. Additionally, our algorithm does not estimate $w^{(k)}(c, j)$, hence, we do not
144 need to make any specific assumption on $w^{(k)}(c, j)$.

3 Main Results: Regret and Constraint Violation Bounds

To understand the performance of a given policy π, we will analyze both the regret and the constraint violation. For that, we first define the baselines and state the assumptions made for the performance analysis. Then, we present our main results on the regret bound and constraint violations – for the latter, we present both results on expected violation and an additional high probability bound for pathwise constraint violation.

3.1 Baselines and Assumptions

Regret baseline: We consider the following optimization problem:

$$\max_{\mathbf{x}} \sum_{c \in \mathcal{C}, j \in [J]} p_c r(c, j) x_{c,j} \tag{10}$$

$$\text{s.t.} \sum_{j \in [J]} x_{c,j} = 1, \; x_{c,j} \geqslant 0, \forall c \in \mathcal{C}, \tag{11}$$

$$\sum_{c \in \mathcal{C}, j \in [J]} p_c w^{(k)}(c, j) x_{c,j} \leqslant 0, \; \forall k \in [K]. \tag{12}$$

Constraint violation baseline: We choose zero (no violation) as our baseline.

It worth noting the baseline we use in the regret analysis is derived from relaxed cumulative constraints instead of anytime cumulative constraints in the original problem. Since the cumulative constraint is the least restrictive constraint, a learner obtains the highest cumulative rewards in such a setting. In other words, our regret analysis is with respect to the best (the most relaxed) baseline.

We make the following assumptions for all the results present in this paper.

Assumption 1 *The context $c(t)$ are i.i.d. across rounds. The mean reward $r(c, j) = \langle \theta_*, \phi(c, j) \rangle \in [0, 1]$ with $\|\phi(c, j)\| \leqslant 1, \|\theta_*\| \leqslant m$ for any $c \in \mathcal{C}$, $j \in [J]$. $\eta(t)$ is zero-mean 1-subGaussian conditioned on $\{\mathcal{F}_{t-1}, A(t)\}$.*

Assumption 2 *The costs in the constraints satisfy $|W^{(k)}(c, j)| \leqslant 1$. Furthermore, we assume $\{W^{(k)}(c, j)\}_{t=1}^{T}$ are i.i.d. samples for given c and j.*

Assumption 3 (Slater's condition) *There exists $\delta > 0$ such that there exists a feasible solution $\mathbf{x}$ to optimization problem (10)-(12) that guarantees $\sum_{c \in \mathcal{C}, j \in [J]} p_c w^{(k)}(c, j) x_{c,j} \leqslant -\delta, \forall k \in [K]$. We assume $\delta \leqslant 1$ because if the condition holds for $\delta > 1$, it also holds for $\delta = 1$.*

We call δ Slater's constant because it comes from Slater's condition in optimization – this is the constant used as an input of our algorithm. This constant plays a similar role as the cost of a safe action in [6, 32]. In fact, a safe action guarantees the existence of a Slater's constant, and we can estimate the constant by running the safe action for a period of time. However, the existence of a Slater's constant does not require the existence of a safe action. It is also a more relaxed quantity than the safety gap in [6], which is defined under the optimal policy. Slater's constant can be from a feasible solution that is not necessarily optimal.

The next lemma shows that the optimal value of (10)-(12) is an upper bound on that of (1)-(2). The proof of this lemma can be found in Appendix C.

Lemma 1 *Assume $\{c(t)\}$ are i.i.d. across rounds, and $\{R(c, j)\}$ and $\{W^{(k)}(c, j)\}$ are i.i.d. samples given action j and context c. Let π^* be the optimal policy to problem (1)-(2) and $\mathbf{x}^*$ be the solution to (10)-(12) with entries $\{x^*_{c,j}\}_{c \in \mathcal{C}, j \in [J]}$. We have*

$$\mathbb{E}\left[\sum_{t=1}^{T} \sum_{j \in [J]} R(c(t), j) X_j^{\pi^*}(t) \right] \leqslant T \sum_{c \in \mathcal{C}, j \in [J]} p_c r(c, j) x^*_{c,j}.$$

The baseline problem (10)-(12) is the same as the one presented in Section 2 except that the tightness constant $\epsilon = 0$ here. Any feasible solution for the tightened problem in Section 2 is a feasible solution to the baseline problem. Under Slater's condition, when $\epsilon < \delta$, the tightened problem also has feasible solutions.

3.2 Regret and Constraint Violation Bounds

Given the baselines above, we now define regret and constraint violation.

Regret: Given policy π, we define the (pseudo)-regret of the policy to be

$$\mathcal{R}(\tau) = \tau \sum_{c \in \mathcal{C}, j \in [J]} p_c r(c, j) x^*_{c,j} - \mathbb{E}\left[\sum_{t=1}^{\tau} \sum_{j \in [J]} R(c(t), j) X^\pi_j(t)\right]. \tag{13}$$

Constraint violation: The constraint violation in round τ is defined to be

$$\mathcal{V}(\tau) = \sum_{k \in [K]} \left(\mathbb{E}\left[\sum_{t=1}^{\tau} \sum_{j \in [J]} W^{(k)}(c(t), j) X^\pi_j(t)\right]\right)^+. \tag{14}$$

Note that the operator $(\cdot)^+ = \max(\cdot, 0)$ is imposed so that different types of constraint violations will not be canceled out.

Theorem 1 *Under Assumptions 1-3, the pessimistic-optimistic algorithm achieves the following regret and constraint violations bounds for any $\tau \in [T]$:*

$$\mathcal{R}(\tau) \leqslant \frac{60K^3}{\delta^3} + \frac{4\sqrt{6}K^{0.75}\sqrt{\tau}}{\delta} + 2 + \sqrt{8d\tau\beta_\tau(T^{-1})\log\left(\frac{d+\tau}{d}\right)},$$

$$\mathcal{V}(\tau) \leqslant K^{1.5}\left(\frac{48K^2}{\delta}\log\left(\frac{16}{\delta}\right) + \frac{24K^{1.5}}{\delta^2} + \frac{30K^{1.5}}{\delta} + 8K - \sqrt{\tau}\right)^+.$$

where $\sqrt{\beta_\tau(T^{-1})} = m + \sqrt{2\log T + d\log(1 + \tau/d)}$.

We make a few important observations from our theoretical results. First, for the *reward regret*, we observe

$$\mathcal{R}(\tau) = \tilde{\mathcal{O}}\left(\left(\frac{K^{0.75}}{\delta} + d\right)\sqrt{\tau}\right).$$

So the regret is independent of the number of contexts, action space $[J]$ and the dimension of cost functions $W^{(k)}(\cdot, \cdot)$. It grows sub-linearly in τ and the number of constraints K, and linearly in the dimension of reward feature d and the inverse of Slater's constant δ.

Second, for the *constraint violation*, we observe

$$\mathcal{V}(\tau) = \begin{cases} \tilde{\mathcal{O}}\left(\frac{K^{3.5}}{\delta} + \frac{K^3}{\delta^2}\right) & \tau \leqslant \tau' = \tilde{\mathcal{O}}\left(\frac{K^4}{\delta^2} + \frac{K^3}{\delta^4}\right) \\ 0 & \text{otherwise} \end{cases}. \tag{15}$$

That is, the constraint violation is *independent* of horizon T and becomes *zero* when $\tau > \tau'$. The constraint violation, however, has a strong dependence on K and δ when $\tau \leqslant \tau'$. This is not surprising because K defines the number of constraints, and δ represents the tightness of the constraints (or size of the feasible set).

Dependence on Slater's constant. Both the regret and constraint violation increase in δ. To see the intuition, note that δ determines the size of the feasible set for the optimization problem. A larger δ implies a larger feasible set, so it is easier to find a feasible solution, vice versa. Therefore, both regret and constraint violation increase as δ decreases because the problem becomes harder and requires more accurate learning.

Sharpness of the bound. In terms of horizon T, the bounds in Theorem 1 are sharp because the regret bound $\mathcal{R}(T)$ matches the instance-independent regret $\Omega(\sqrt{T})$ in multi-armed bandit problems without constraints [7, 21] up to logarithmic factors. Furthermore, zero constraint violation is the best possible. Therefore, the bounds are sharp up to logarithmic factors in terms of horizon T. It is not clear whether these bounds are sharp in terms of K, d, and δ, which are interesting open questions.

3.3 A High Probability Bound on Constraint Violation

The constraint (2) defined in the original problem and the constraint violation measure defined in (14) are both in terms of expectation. An interesting, related question is what the probability is for a *sample-path version* of the constraints to be satisfied. It turns out that our algorithm provides a high probability guarantee on that as well. The proof can be found in Appendix H.

Corollary 1 *The pessimistic-optimistic algorithm guarantees that for any $\tau \geqslant \frac{\kappa K^5}{\delta^2} \left(\log \left(\frac{K}{\delta} \right) \right)^2$, where κ is a positive constant independent of τ, K, δ and d,*

$$\mathbb{P} \left(\sum_{t=1}^{\tau} \sum_{j \in [J]} W^{(k)}(c(t), j) X_j(t) > 0 \right) = O \left(e^{-\frac{\delta \sqrt{\tau}}{50 K^2}} \right).$$

4 Proof of Theorem 1

We first explain the intuition behind the main result. Recall that the algorithm selects action j^* such that

$$j^* \in \arg \max_j \left(\hat{r}(c(\tau), j) - \frac{1}{V_\tau} \sum_k W^{(k)}(c(\tau), j) Q^{(k)}(\tau) \right),$$

and $V_\tau = O(\sqrt{\tau})$. Therefore, when $Q^{(k)}(\tau) = o(\sqrt{\tau})$, the reward term dominates the cost term, and our algorithm uses LinUCB to maximize the reward. When $Q^{(k)}(\tau) = \omega(\sqrt{\tau})$, the cost term dominates the reward term and our algorithm focuses on reducing $Q^{(k)}$. Slater's condition implies that there exists a policy that can reduce $Q^{(k)}$ by a constant (related to δ) in each round. Therefore, the algorithm takes $\tilde{\mathcal{O}}(\sqrt{\tau})$ rounds to reduce $Q^{(k)}$ to $o(\sqrt{\tau})$, which may add $\tilde{\mathcal{O}}(\sqrt{\tau})$ to the regret during this period. The argument above also implies that $Q^{(k)}(\tau) = O(\sqrt{\tau})$. Then, because

$$\mathbb{E} \left[\sum_{t=1}^{\tau} \sum_{j \in [J]} W^{(k)}(c(t), j) X_j(t) \right] \leqslant \mathbb{E} \left[Q^{(k)}(\tau + 1) \right] - \sum_{t=1}^{\tau} \epsilon_t.$$

we can further bound the constraint violation at time τ to be a constant or even zero via the bound on $\mathbb{E}[Q^{(k)}(\tau + 1)]$ and a proper choice of ϵ_t.

4.1 Regret Bound

Now consider the regret defined in (13) and define $\mathbf{x}^{\epsilon_t, *}$ to be the optimal solution to the tightened problem (3)-(5) with $\epsilon = \epsilon_t$. We obtain the following decomposition by adding and subtracting corresponding terms:

$$\mathcal{R}(\tau) = \tau \sum_{c,j} p_c r(c, j) x_{c,j}^* - \mathbb{E} \left[\sum_{t=1}^{\tau} \sum_j R(c(t), j) X_j(t) \right]$$

$$\overset{(a)}{=} \tau \sum_{c,j} p_c r(c, j) x_{c,j}^* - \mathbb{E} \left[\sum_{t=1}^{\tau} \sum_j r(c(t), j) X_j(t) \right]$$

$$= \underbrace{\sum_{t=1}^{\tau} \sum_{c,j} p_c r(c, j) \left(x_{c,j}^* - x_{c,j}^{\epsilon_t, *} \right)}_{\epsilon_t\text{-tight}} + \underbrace{\mathbb{E} \left[\sum_{t=1}^{\tau} \sum_j \left(r(c(t), j) - \hat{r}(c(t), j) \right) x_{c(t), j}^{\epsilon_t, *} \right]}_{\text{reward mismatch}}$$

$$+ \underbrace{\mathbb{E} \left[\sum_{t=1}^{\tau} \sum_j \left(\hat{r}(c(t), j) x_{c(t), j}^{\epsilon_t, *} - \hat{r}(c(t), j) X_j(t) \right) \right] - \sum_{t=1}^{\tau} \frac{K(1 + \epsilon_t^2)}{V_t}}_{\text{Lyapunov drift}} \qquad (16)$$

$$+ \underbrace{\sum_{t=1}^{\tau} \frac{K(1 + \epsilon_t^2)}{V_t}}_{\text{accumulated tightness}} + \underbrace{\mathbb{E} \left[\sum_{t=1}^{\tau} \sum_j \left(\hat{r}(c(t), j) - r(c(t), j) \right) X_j(t) \right]}_{\text{reward mismatch}}, \qquad (17)$$

227 where (a) holds because the random reward is revealed after action $A(t)$ is taken so the noise is
228 independent of the action. We next present a sequence of lemmas that bounds the terms above. The
229 proofs of these lemmas are presented in Appendices D, E, and F.

First, we establish an upper bound on (16) by using the Lyapunov-drift analysis [31, 34]. We consider
a Lyapunov function $L(t) = \sum_k Q^{(k)}(t)$ and show that maximizing the pseudo action value in our
algorithm (**MaxValue** step) is equivalent to maximizing the following "reward minus Lyapunov drift"

$$V_t \sum_{j \in [J]} \hat{r}(c(t), j) X_j(t) - (L(t+1) - L(t)).$$

230 Therefore, our algorithm outperforms a static policy $x^{\epsilon_t}_{c(t),j}$ and results in the following lower bound

$$V_t \mathbb{E}\left[\sum_{j \in [J]} \hat{r}(c(t), j) X_j(t)\right] - \mathbb{E}[L(t+1) - L(t)] \geqslant V_t \sum_{j \in [J]} \hat{r}(c(t), j) x^{\epsilon_t}_{c(t),j} - K(1 + \epsilon_t^2). \quad (18)$$

231 Apply the telescoping sum on (18) provides an upper bound on (16) in Lemma 2.

232 **Lemma 2** *Under the Pessimistic-Optimistic Algorithm, we have*

$$\mathbb{E}\left[\sum_{t=1}^{\tau} \sum_{j \in [J]} \hat{r}(c(t), j)\left(x^{\epsilon_t}_{c(t),j} - X_j(t)\right) \Big| \mathbf{H}(t) = \mathbf{h}\right] - \sum_{t=1}^{\tau} \frac{K(1 + \epsilon_t^2)}{V_t} \leqslant \sum_{t=1}^{\tau} \frac{Kt(\epsilon_t + \epsilon_t^2)\mathbb{I}(\epsilon_t > \delta)}{V_t}.$$

233 Next, we present Lemma 3 which establishes an upper bound on the ϵ_t-tight term by comparing the
234 optimal solution to the original baseline problem and that to its ϵ_t-tightened version. It is based on
235 the intuition that adding ϵ_t-tightness to the feasible region only incurs $O(\epsilon_t)$ loss in the reward.

Lemma 3 *Under Assumptions 1-3, we can bound the difference between the baseline optimization
problem and its tightened version:*

$$\sum_{t=1}^{\tau} \sum_{c,j} p_c r(c, j)\left(x^*_{c,j} - x^{\epsilon_t,*}_{c,j}\right) \leqslant \sum_{t=1}^{\tau} \frac{\epsilon_t}{\delta}.$$

236 Finally, we present Lemma 4 that provides an upper bound on the reward mismatch terms. The
237 proof is based on "self-normalized bound for vector-valued martingales" in [1] and shows that $\hat{r}(c, j)$
238 over-estimates $r(c, j)$ and converges to $r(c, j)$.

239 **Lemma 4** *Under the Pessimistic-Optimistic Algorithm, LinUCB guarantees that*

$$\mathbb{E}\left[\sum_{t=1}^{\tau} \sum_j (\hat{r}(c(t), j) - r(c(t), j)) X_j(t)\right] \leqslant 1 + \sqrt{8d\tau\beta_\tau(T^{-1}) \log\left(\frac{d+\tau}{d}\right)},$$

$$\mathbb{E}\left[\sum_{t=1}^{\tau} \sum_j (r(c(t), j) - \hat{r}(c(t), j)) x^{\epsilon_t,*}_{c(t),j}\right] \leqslant 1.$$

240 Based on Lemmas 2, 3, and 4, we conclude that

$$\mathcal{R}(\tau) \leqslant \sum_{t=1}^{\tau} \frac{Kt(\epsilon_t + \epsilon_t^2)\mathbb{I}(\epsilon_t > \delta)}{V_t} + \sum_{t=1}^{\tau} \frac{\epsilon_t}{\delta} + \sum_{t=1}^{\tau} \frac{K(1 + \epsilon_t^2)}{V_t} + 2 + \sqrt{8d\tau\beta_\tau(T^{-1}) \log\left(\frac{d+\tau}{d}\right)}.$$

By choosing $\epsilon_t = K^{0.75}\sqrt{\frac{6}{t}}$ and $V_t = \delta K^{0.25}\sqrt{\frac{2t}{3}}$, we have

$$\sum_{t=1}^{\tau} \epsilon_t \leqslant 2K^{0.75}\sqrt{6\tau}, \quad \sum_{t=1}^{\tau} 1/V_t \leqslant \frac{\sqrt{6\tau}}{K^{0.25}}, \quad \text{and} \quad \sum_{t=1}^{\tau} \frac{Kt(\epsilon_t + \epsilon_t^2)\mathbb{I}(\epsilon_t > \delta)}{V_t} \leqslant \frac{60K^3}{\delta^3},$$

241 which yields the regret bound

$$\mathcal{R}(\tau) \leqslant \frac{60K^3}{\delta^3} + \frac{4\sqrt{6}K^{0.75}\sqrt{\tau}}{\delta} + 2 + \sqrt{8d\tau\beta_\tau(T^{-1}) \log\left(\frac{d+\tau}{d}\right)}.$$

4.2 Constraint Violation Bound

According to the dynamic defined in (9), we have

$$Q^{(k)}(\tau + 1) \geqslant \sum_{t=1}^{\tau} \sum_j W^{(k)}(c(t), j) X_j(t) + \sum_{t=1}^{\tau} \epsilon_t,$$

where we used the fact $Q^{(k)}(0) = 0$. This implies the constraint violation can be bounded as follows:

$$\mathcal{V}(\tau) \leqslant \sum_k \left(\mathbb{E}[Q^{(k)}(\tau + 1)] - \sum_{t=1}^{\tau} \epsilon_t \right)^+ . \tag{19}$$

Next, we introduce a lemma on the upper bound of $Q^k(\tau)$. Define τ' the first time such that $\epsilon_{\tau'} \leqslant \delta/2$, that is, $\epsilon_\tau > \delta/2, \forall 1 \leqslant \tau < \tau'$.

Lemma 5 *For any time $\tau \in [T]$ such that $\tau \geqslant \tau'$, i.e., $\epsilon_\tau \leqslant \delta/2$, we have*

$$\mathbb{E}\left[Q^{(k)}(\tau) \right] \leqslant \sqrt{K} \left(\frac{48K^2}{\delta} \log\left(\frac{16K}{\delta} \right) + 2K + \frac{4(V_\tau + K(1 + \epsilon_\tau^2))}{\delta} + \tau' + \sqrt{K} \sum_{t=1}^{\tau'} \epsilon_t \right).$$

Based on our choices of $\epsilon_t = K^{0.75} \sqrt{\frac{6}{t}}$ and $V_t = \delta K^{0.25} \sqrt{\frac{2t}{3}}$, we obtain

$$\tau' = \frac{24K^{1.5}}{\delta^2} \text{ and } \sum_{t=1}^{\tau} \frac{\epsilon_t}{\sqrt{K}} - \frac{4V_{\tau+1}}{\delta} \geqslant \sqrt{\tau} - 6K.$$

Note $\mathcal{V}(\tau) \leqslant K\tau'$ for any $\tau \leqslant \tau'$. Combine Lemma 5 into (19), we conclude

$$\mathcal{V}(\tau) \leqslant K^{1.5} \left(\frac{48K^2}{\delta} \log\left(\frac{16}{\delta} \right) + \frac{24K^{1.5}}{\delta^2} + \frac{30K^{1.5}}{\delta} + 8K - \sqrt{\tau} \right)^+ .$$

5 Conclusions and Extensions

In this paper, we study stochastic linear bandits with general anytime cumulative constraints. We develop a pessimistic-optimistic algorithm that is computationally efficient and has strong guarantees on both regret and constraint violations. We conclude this paper by mentioning an extension on the case where the cost signals $W^{(k)}(c(t), A(t))$ are revealed after action $A(t)$ is taken. However, we assume the costs can be linearly parameterized as in [32].

Linear Cost Functions: In this case, we assume that the costs , $W^{(k)}(c(t), A(t))$, are not available before the action is taken but the costs are linear as in [32]. The learner observes cost *after* taking action $A(t)$,

$$W(c(t), A(t)) = \langle \mu_*, \psi(c, j) \rangle + \xi(t),$$

where $\psi(c, j) \in \mathbb{R}^d$ is a d-dimensional feature vector for (context, action) pair (c, j), $\mu_* \in \mathbb{R}^d$ is an unknown underlying vector to be learned, and $\xi(t)$ is a zero-mean random variable. In this case, we also obtain an estimate $\check{W}(c(t), j)$ of $W(c(t), j)$ with LinUCB and replace $W(c(t), j)$ with $\check{W}(c(t), j)$ in the steps of MaxValue and Dual Update in the Pessimisitic-Optimistic Algorithm. This variation of Pessimisitic-Optimistic Algorithm has a similar computational complexity as our main algorithm, and it can provide similar regret and constraint violation guarantees:

Theorem 2 (Informal) *With linear costs as in [32], a variation of our algorithm achieves $\mathcal{R}(\tau) = \tilde{\mathcal{O}}\left(\frac{d}{\delta} \sqrt{\tau} + \frac{d^4}{\delta^3} \right)$ for any $\tau \in [T]$ and $\mathcal{V}(\tau) = 0$ for $\tau \geqslant \tau'' = O\left(\frac{d^2}{\delta^4} \log^2 T \right)$.*

The formal statement and the detailed analysis are in Appendix I.

References

[1] Yasin Abbasi-yadkori, Dávid Pál, and Csaba Szepesvári. Improved algorithms for linear stochastic bandits. In *Advances in Neural Information Processing Systems 24*. 2011.

[2] Naoki Abe and Philip M. Long. Associative reinforcement learning using linear probabilistic concepts. In *Int. Conf. Machine Learning (ICML)*, 1999.

[3] Shipra Agrawal and Nikhil Devanur. Linear contextual bandits with knapsacks. In *Advances Neural Information Processing Systems (NeurIPS)*, 2016.

[4] Shipra Agrawal and Nikhil R. Devanur. Bandits with concave rewards and convex knapsacks. In *Proceedings of the Fifteenth ACM Conference on Economics and Computation*. Association for Computing Machinery, 2014.

[5] Shipra Agrawal, Nikhil R. Devanur, and Lihong Li. An efficient algorithm for contextual bandits with knapsacks, and an extension to concave objectives. In *Proc. Conf. Learning Theory (COLT)*, 2016.

[6] Sanae Amani, Mahnoosh Alizadeh, and Christos Thrampoulidis. Linear stochastic bandits under safety constraints. In *Advances Neural Information Processing Systems (NeurIPS)*, pages 9256–9266, 2019.

[7] P. Auer, N. Cesa-Bianchi, Y. Freund, and R. E. Schapire. Gambling in a rigged casino: The adversarial multi-armed bandit problem. In *Proceedings of IEEE 36th Annual Foundations of Computer Science*, 1995.

[8] Peter Auer. Using confidence bounds for exploitation-exploration trade-offs. *Journal of Machine Learning Research*, 3:397–422, March 2003.

[9] Ashwinkumar Badanidiyuru, Robert Kleinberg, and Aleksandrs Slivkins. Bandits with knapsacks. *J. ACM*, 2018.

[10] Ashwinkumar Badanidiyuru, John Langford, and Aleksandrs Slivkins. Resourceful contextual bandits. In *Proc. Conf. Learning Theory (COLT)*, 2014.

[11] Semih Cayci, Atilla Eryilmaz, and R Srikant. Budget-constrained bandits over general cost and reward distributions. In *Proceedings of Machine Learning Research*, volume 108, pages 4388–4398, 26–28 Aug 2020.

[12] Nicolo Cesa-Bianchi and Gabor Lugosi. *Prediction, Learning, and Games*. Cambridge University Press, 2006.

[13] Yifang Chen, Alex Cuellar, Haipeng Luo, Jignesh Modi, Heramb Nemlekar, and Stefanos Nikolaidis. Fair contextual multi-armed bandits: Theory and experiments. In *Proceedings of Machine Learning Research*, 2020.

[14] Wei Chu, Lihong Li, Lev Reyzin, and Robert Schapire. Contextual bandits with linear payoff functions. In *Proceedings of the Fourteenth International Conference on Artificial Intelligence and Statistics*, 2011.

[15] Fan Chung and Linyuan Lu. Concentration inequalities and martingale inequalities: A survey. *Internet Mathematics*, 3:127 – 79, 2006.

[16] Richard Combes, Chong Jiang, and Rayadurgam Srikant. Bandits with budgets: Regret lower bounds and optimal algorithms. *Proc. Ann. ACM SIGMETRICS Conf.*, 43(1):245–257, 2015.

[17] Varsha Dani, Thomas Hayes, and Sham Kakade. Stochastic linear optimization under bandit feedback. In *Proc. Conf. Learning Theory (COLT)*, 2008.

[18] Rémy Degenne, Han Shao, and Wouter Koolen. Structure adaptive algorithms for stochastic bandits. In *Proceedings of the 37th International Conference on Machine Learning*, volume 119 of *Proceedings of Machine Learning Research*, pages 2443–2452. PMLR, 13–18 Jul 2020.

[19] Atilla Eryilmaz and R. Srikant. Asymptotically tight steady-state queue length bounds implied by drift conditions. *Queueing Syst.*, 72(3-4):311–359, December 2012.

[20] Kris Johnson Ferreira, David Simchi-Levi, and He Wang. Online network revenue management using Thompson sampling. *Operations Research*, 66(6):1586–1602, 2018.

[21] Sébastien Gerchinovitz and Tor Lattimore. Refined lower bounds for adversarial bandits. In *Advances Neural Information Processing Systems (NeurIPS)*, 2016.

[22] B. Hajek. Hitting-time and occupation-time bounds implied by drift analysis with applications. *Ann. Appl. Prob.*, pages 502–525, 1982.

[23] Johannes Kirschner, Tor Lattimore, Claire Vernade, and Csaba Szepesvári. Asymptotically optimal information-directed sampling. *Arxiv preprint arXiv:2011.05944*, 2021.

[24] T.L Lai and Herbert Robbins. Asymptotically efficient adaptive allocation rules. *Advances in Applied Mathematics*, 1985.

[25] John Langford and Tong Zhang. The epoch-greedy algorithm for multi-armed bandits with side information. In *Advances Neural Information Processing Systems (NeurIPS)*, 2008.

[26] Tor Lattimore and Csaba Szepesvári. *Bandit Algorithms*. Cambridge University Press, 2020.

[27] F. Li, J. Liu, and B. Ji. Combinatorial sleeping bandits with fairness constraints. In *Proc. IEEE Int. Conf. Computer Communications (INFOCOM)*, pages 1702–1710, 2019.

[28] Lihong Li, Wei Chu, John Langford, and Robert E. Schapire. A contextual-bandit approach to personalized news article recommendation. In *Proc. Int. Conf. World Wide Web (WWW)*, page 661–670, 2010.

[29] Mehrdad Mahdavi, Rong Jin, and Tianbao Yang. Trading regret for efficiency: Online convex optimization with long term constraints. *Journal of Machine Learning Research*, 13(81):2503–2528, 2012.

[30] M. J. Neely. Energy-aware wireless scheduling with near-optimal backlog and convergence time tradeoffs. *IEEE/ACM Transactions on Networking*, 24(4):2223–2236, 2016.

[31] Michael J. Neely. Stochastic network optimization with application to communication and queueing systems. *Synthesis Lectures on Communication Networks*, 3(1):1–211, 2010.

[32] Aldo Pacchiano, Mohammad Ghavamzadeh, Peter Bartlett, and Heinrich Jiang. Stochastic bandits with linear constraints. *arXiv preprint arXiv:2006.10185*, 2020.

[33] Paat Rusmevichientong and John N. Tsitsiklis. Linearly parameterized bandits. *Mathematics of Operations Research*, 35(2):395–411, 2010.

[34] R. Srikant and Lei Ying. *Communication Networks: An Optimization, Control and Stochastic Networks Perspective*. Cambridge University Press, 2014.

[35] Andrea Tirinzoni, Matteo Pirotta, Marcello Restelli, and Alessandro Lazaric. An asymptotically optimal primal-dual incremental algorithm for contextual linear bandits. In *nips*, volume 33, pages 1417–1427, 2020.

[36] Ilnura Usmanova, Andreas Krause, and Maryam Kamgarpour. Safe convex learning under uncertain constraints. In *Proceedings of Machine Learning Research*. PMLR, 2019.

[37] Christopher J. C. H. Watkins and Peter Dayan. Q-learning. In *Machine Learning*, pages 279–292, 1992.

[38] Xiaohan Wei, Hao Yu, and Michael J. Neely. Online primal-dual mirror descent under stochastic constraints. *Proc. Ann. ACM SIGMETRICS Conf.*, 4(2), June 2020.

[39] Michael Woodroofe. A one-armed bandit problem with a concomitant variable. *Journal of the American Statistical Association*, 74(368):799–806, 1979.

[40] Huasen Wu, R. Srikant, Xin Liu, and Chong Jiang. Algorithms with logarithmic or sublinear regret for constrained contextual bandits. In *Advances Neural Information Processing Systems (NeurIPS)*, 2015.

[41] Hao Yu and Michael J. Neely. A low complexity algorithm with $o(\sqrt{T})$ regret and $o(1)$ constraint violations for online convex optimization with long term constraints. *Journal of Machine Learning Research*, 21(1):1–24, 2020.

[42] Hao Yu, Michael J. Neely, and Xiaohan Wei. Online convex optimization with stochastic constraints. In *Advances Neural Information Processing Systems (NeurIPS)*, page 1427–1437, 2017.