UViM: A Unified Modeling Approach for Vision with Learned Guiding Codes

Abstract

We introduce UViM, a unified approach capable of modeling a wide range of computer vision tasks. In contrast to previous models, UViM has the same functional form for all tasks; it requires no task-specific modifications which require extensive human expertise. The approach involves two components: (I) a *base model* (feed-forward) which is trained to directly predict raw vision outputs, guided by a learned discrete code and (II) a *language model* (autoregressive) that is trained to generate the guiding code. These components complement each other: the language model is well-suited to modeling structured interdependent data, while the base model is efficient at dealing with high-dimensional outputs. We demonstrate the effectiveness of UViM on three diverse and challenging vision tasks: panoptic segmentation, depth prediction and image colorization, where we achieve competitive and near state-of-the-art results. Our experimental results suggest that UViM is a promising candidate for a unified modeling approach in computer vision.

1 Introduction

Many computer vision tasks require producing high-dimensional structured outputs. Examples include various types of image segmentation, monocular depth estimation, surface normal estimation, colorization, object detection, image super-resolution, etc. By handcrafting architectures and training procedures specific to each task, the structure of those target outputs can be exploited to learn better models. However, this fragmented approach impedes the ability to build a general solution ready to be applied to any task.

For the tasks above, that require predicting high-dimensional structured outputs, direct use of powerful parametric models such as CNNs [26, 43, 16] and Vision Transformers [9], trained with decomposable (e.g. pixel-wise) loss is not sufficient, as this basic approach lacks the ability to model the structure of the output. To address this shortcoming, standard approaches turn to using additional modeling components such as, for example, anchor boxes [36, 29], non-maximal suppression [36, 29], matching losses [2, 5, 6] or conditional random fields [3, 54].

Recently, there have been significant advances in the modeling of complex structured outputs in the context of language generation and (conditional) image generation: autoregressive models [48, 40, 24], GANs [13], VAE [21], VQVAE [50], diffusion models [44, 18]. However, using such techniques to tackle discriminative problems in a unified way remains under-explored.

In this work, we propose a new approach, UViM, capable of modeling many vision tasks, leveraging recent advances in discrete representation learning [50] and language modeling [51]. We show competitive results in three diverse tasks: panoptic segmentation [22], depth prediction [42] and colorization [56]. Crucially, there are no task-specific components required for each task. All of the tasks use the same model and are amenable to transfer learning from standard pre-trained models.

Submitted to 36th Conference on Neural Information Processing Systems (NeurIPS 2022). Do not distribute.

(a) **Stage I** training: we train the base model f, which is guided by the code produced by the *restricted oracle* model Ω. The oracle has access to the ground-truth label, but is only allowed to communicate with f by passing a short discrete sequence, which we call a *guiding code*.

(b) **Stage II** training: we train a *language model* (LM) to output a *guiding code* by learning to mimic the oracle, but using only the image input.

Figure 1: An overview of the UViM learning procedure. Blue blocks depict parts of the model which are being optimized, while black blocks depict frozen components.

2 Unified Modeling Approach for Vision

We first discuss the motivation and inspiration behind our unified modeling approach: UViM. Then we give a high-level overview, followed by an in-depth explanation of its design and technical details[1].

2.1 Motivation

The field of computer vision made a huge leap by transitioning to models based on rich parametric functions (CNNs [26, 43, 47, 16], ViTs [9]). Combined with well-working gradient-based algorithms to train these functions (e.g. Adam [20]), it enables learning of complex feedforward mappings from inputs to outputs $f : X \rightarrow Y$, which we call *base models*.

Despite the ability to train powerful and reusable base models, different vision applications, particularly those involving high-dimensional structured outputs, such as object bounding boxes, per-pixel segmentation masks or 3D point clouds, still rely on highly customized components and techniques listed in the introduction.

The necessity for introducing these non-trivial custom components has the same underlying root cause: the outputs are high-dimensional and structured (interdependent) and modeling complex interactions is a necessary condition for succeeding at a given task. Modeling such data is a long-standing challenge in computer vision (and beyond), with numerous books on the subject [33, 25] and remains a relevant area of research.

In contrast to computer vision, a prominent unified modeling approach has been adopted in NLP. Many NLP tasks can be handled by an autoregressive sequence model [34] parameterized by the Transformer architecture [51]. This approach combines multiple desirable properties: it is theoretically sound, expressive (capable of modeling a joint probability distribution of the outputs) and there are robust techniques for training such models.

Why has the computer vision field not yet adopted a similar unified model? There are papers that demonstrate that the NLP-like approach, based on autoregressive sequence models, is viable for some image tasks [4, 37]. However, it only works for tasks that have compact output representations; the additional challenge in vision is that outputs are often very high-dimensional. NLP models typically model sequences of length up to 10'000 tokens, while in vision, outputs, such as per-pixel image segmentation/instance masks, may contain millions of elements. It is computationally prohibitive to apply autoregressive sequence models directly to such tasks.

---

[1]To facilitate reproducibility, we will provide a link to the code when the anonymity requirements are lifted.

2.2 Unified vision model via learned guiding code

Now we present our unified modeling approach for computer vision. We first give a high-level overview of the proposed model and then describe its components in detail.

We devise a unified vision model as a composition of a standard feedforward *base model* and an autoregressive *language model* of a short sequence. Our decomposition works well even for vision tasks that deal with extremely high dimensional and structured outputs.

Our key insight is to reduce the original task of modeling very high-dimensional structured output (e.g. panoptic segmentation mask) to modeling a short discrete sequence with the language model. For this, we propose an optimization procedure, illustrated in Figure 1. The resulting model during inference is depicted in Figure 2.

Figure 2: The schematic illustration of UViM during inference.

Stage I training: learning with a guiding code. To build a unified vision model we start from a base model $f : \mathcal{X} \rightarrow \mathcal{Y}$, which directly maps task inputs to its outputs. As discussed above, learning such model with simple element-wise loss for a structured label space $\mathcal{Y}$ does not result in a good prediction model, as it is not modeling complex interactions within the output space.

To compensate for this modeling deficiency, we introduce an input $z \in \mathcal{Z}$, called *guiding code*. The assumption is that given x and z, the elements of the output y have fewer dependencies, and can be modelled well by the *base model*. As an illustrative example, consider colorization: given a grayscale image of a car, the pixel colors are highly dependent (most cars are of uniform color). However, given a guiding code with the information "the car is red", such cross-pixel dependencies cease to exist.

The guiding code z has two key properties. First, it is represented as a short discrete sequence of the fixed length n, i.e. $z = (z_1, z_2, \ldots, z_n)$. Second, it is derived from the output y through the special function Ω: $z = \Omega(y)$. We call Ω the *restricted oracle*, because it has access to the target (ground truth) $y \in \mathcal{Y}$, but at the same time is forced to compactly represent the information which will help f to solve the task. Note, the restricted oracle is only used during training, but not at test time.

We train f and Ω jointly and end-to-end by minimizing a reconstruction loss between $f(x, \Omega(y))$ and y. For the reconstruction loss, we use the simplest task-appropriate loss function, e.g. pixel-wise cross-entropy or mean squared error. See stage I training step illustrated in Figure 1(a).

Empirically, we observe that the function $f(x, z)$, "aided" by the guiding code from the restricted oracle, is capable to solve the complex vision tasks very well, as measured by the task-specific standard metrics. Note, that $f(x, z)$ is not a prediction model, as z depends on the ground truth y. Nevertheless, in this stage we have introduced a crucial component, which helps to reduce a high-dimensional structured prediction task to modeling a short sequence of discrete variables z.

Stage II training: learning to model the guiding code. At the second stage, we model the discrete sequence z using the input x. The training data is a collection of input-output pairs $(x, \Omega(y))$, where Ω is the fixed restricted oracle trained from the stage I. Note, that this task is equivalent to many standard NLP problems (except the input is an image) and there is a vast number of research and tools to tackle it. We use a standard encoder-decoder language model [51] LM : $\mathcal{X} \rightarrow \mathcal{Z}$, which processes the image through the encoder and passes it to the autoregressive decoder. Training is performed end-to-end with gradient-based optimization. See Figure 1(b) for illustration of stage II learning step.

Resulting unified vision model. As a result of the two-stage optimization procedure, we obtain a final model $f(x, \text{LM}(x))$, which we call UViM, short for *U*nified *V*ision *M*odel. See Figure 2 for an overview. Later in the experimental section we show that such a model can be successfully trained to model highly structured outputs for very different vision tasks.

2.3 Implementation details

Joint training of base model f and restricted oracle Ω. Stage I training involves training a model that contains a discrete bottleneck $z = \Omega(y)$, which is used to guide the base model $f(x, z) \rightarrow y$. Such discrete bottleneck is problematic for training with gradient-based methods, as it does not have a gradient. To address this, we employ the technique introduced by the seminal VQ-VAE paper [50].

117 The key idea is to map the embeddings to be quantized to the nearest entry in a dictionary of N
118 d-dimensional embeddings. We refer the reader to the paper for a detailed overview.

119 **Addressing embedding dictionary usage.** We observed that during Stage I training the usage of
120 VQ-VAE dictionary may be highly unbalanced and certain entries going unused. To address this,
121 we adapt the classic Linde-Buzo-Gray [31] splitting algorithm to VQ-VAE's dictionary learning
122 procedure. Specifically, if, throughout the training process, we detect an unused embedding, we
123 then take the most frequently used embedding and split it into two new embeddings by applying
124 a tiny noise, and consequently replacing the unused one.

125 **Architectures of functions f, Ω and** LM**.** Throughout our experiments, we strive to use as uniform
126 setup as possible. By default, we use a plain ViT architecture to parameterize all functions. Specif-
127 ically, function f and Ω are modeled by the ViT architecture introduced in [9]. For historical reasons
128 we equip Ω with an additional input x, though it appears not to affect the resulting model. The function
129 LM is a standard encoder-decoder model and consists of two parts: LM_{enc} and LM_{dec}. The encoder,
130 LM_{enc} is also modeled by the ViT backbone. The decoder, LM_{dec} is modeled by the standard
131 transformer decoder, which is identical to the ViT model without initial projection for image patches.

132 **Controlling sequence length of guiding code.** As Ω is parameterized by the ViT model, its output
133 is a collection of vectors arranged as a grid. To disentangle the number of vectors from the guiding
134 code size, we optionally perform a linear spatial resize operation.

135 **Dropout for guiding code.** Empirically, we find that modeling the code z during phase II can
136 be quite challenging. This motivates us to explore a code dropout mechanism to affect the code
137 complexity. For each training example in a batch, we randomly select an integer k from 0 to n, where
138 n is the code length. Then, we set a random subset of k codewords to 0 before inputting it to the
139 model f. As a result, *base model* learns to not rely on any individual code too heavily and the code
140 becomes more robust. Intuitively, we expect that this can help to get better final stage II UViM model.
141 We empirically validate the effect of this approach in Section 4.

142 **Sampling from** LM **at test time.** Running UViM at test time involves evaluating two functions:
143 $\text{LM} : \mathcal{X} \to \mathcal{Z}$ and then $f : \mathcal{X} \times \mathcal{Z} \to \mathcal{Y}$. While evaluating f is straightforward, the function LM is
144 autoregressive and models a joint distribution $p(z|x) = p(z_1, z_2, \ldots, z_n|x)$. Sampling from $p(z|x)$
145 is a known and extensively studied task in NLP literature [7, 46, 51]. In our initial experiments we
146 observed that the the simplest sampling approach seems to work well and more complex sampling
147 techniques, such as beam search are not necessary. Thus, we sample z using the most standard
148 coordinate-wise sequential sampling $z_k \sim p(z_k|z_{k-1} \ldots z_1, x)$. Note, we can optionally vary the
149 temperature T of the conditional distributions. By setting $T = 0$ we can produce the "most likely"
150 sample z, but lose diversity. Contrary, with the default temperature $T = 1$, we can get diverse samples
151 (and consequently diverse predictions), but potentially at the expense of prediction quality.

3   Experiments

153 We apply UViM to three diverse tasks: a general scene understanding panoptic segmentation task,
154 a conditional generative image colorization task and a 3D scene understanding task of the depth
155 prediction. With UViM, we use a unified setup for all three, seemingly different, tasks.

156 **Experimental setup for stage I.** We parameterize the *base model* f and the *restricted oracle* Ω with
157 ViT-B/16 model. For Ω we use 6 layers instead of 12, as in the initial experiments we observed that a
158 relatively small capacity is sufficient. Both models are trained from scratch.

159 The input and output resolution during stage I for all tasks is 512×512. For optimization we use a
160 variant of Adafactor [41] introduced in [55]. Due to differences in dataset size, we tune the learning
161 rate and number of epochs per task, but all other hyperparameters are the same.

162 For the guiding code, $z \in \mathcal{Z}$, produced by the restricted oracle, we use a sequence length of 256 with
163 4096 dictionary entries. To put this choice into perspective, for the panoptic task, the original panoptic
164 mask is encoded as roughly $512 \cdot 512 \cdot 2 \approx 524\,000$ discrete values, each ranging approximately from
165 0 to 100. Thus, z is more than three orders of magnitude more compact than the original label.

166 **Experimental setup for stage II.** The language model consists of the encoder and autoregressive
167 decoder. For the encoder, by default, we use the ViT-L/16 model. We initialize the encoder with the
168 ImageNet-21k [38] pre-trained model from [45]. For the decoder, we use the ViT-B model. Note, that

Table 1: Comparison of presented modeling approach (UViM) and other related works discussed in Section 5 including current state of the art. Note that ours is the only work covering a set of significantly different tasks dominated by different types of approaches. Standard deviations are computed across three independent reruns.

COCO Panoptic [PQ]		NYU Depth v2 [RMSE]		ImageNet Colorization [FID-5k]	
UViM (ours)	45.6 ± 0.1	UViM (ours)	$0.467 \pm 9e{-}3$	UViM (ours)	16.17 ± 0.04
DETR-R101 [2]	45.1	DenseDepth [1]	0.465	COLTRAN [27]	19.37
Mask2Former [5]	**57.8**	BinsFormer [28]	**0.330**	Palette [39]	**15.78**

Figure 3: We demonstrate how UViM performs across three different diverse tasks. Note that when provided with oracle's *guiding code* it achieves near perfect results (3rd row). Predictions of the final UViM model are exemplified in 4th row. They are generally of very high quality and confirm that LM can successfully learn to produce the guiding code from the image input.

there is no initial patch projection, as it uses guiding code z as autoregressive input, this is equivalent to the standard BERT-Base [8] architecture.

As in the stage I, the input and output resolution for all tasks is 512×512, except for the panoptic task, where we use a higher input resolution of 1280×1280. For optimization, we use the same optimizer as in Stage I. For all tasks, we use a base learning rate of 0.001 with cosine decay and, additionally, apply a 10-fold reduction for the pre-trained encoder weights. Due to differences in dataset size, the number of epochs is tuned per task.

For all our experiments we use Google Cloud TPU-v3 hardware. A phase I training run for panoptic segmentation requires 1.9k TPU-v3 hours, while a phase II training run requires 0.9k TPU-v3 hours.

Data augmentations We strive to use the simple and standard augmentations for all tasks. At train time we opt for using an inception crop [47], random horizontal flipping, followed by resize to a square-shaped input. At test time we only squared-shaped resize the inputs to the input resolution.

3.1 Panoptic segmentation

Panoptic segmentation [22] is a general scene understanding task, which requires mapping every image pixel to its semantic class and, if applicable, instance ID. We adopt the raw target representation

Figure 4: UViM outputs for the colorization task. Different samples produced by re-sampling the guiding code from the *language model* LM. Visually, the resulting samples are consistent and diverse.

used in the original paper: a 2-channel mask, where the first channel encodes semantics, and the second channel encodes instance IDs. During training we assign instances IDs in an a raster scan order of object centers.

We train on the COCO panoptic 2017 [30, 22] dataset. It has approximately 118'000 training images and 5'000 official validation images which we use for test. All hyper-parameters were selected on 4'096 images held out from the training data. For evaluation, we use the official metric, called panoptic quality (PQ), which jointly estimates the accuracy of semantic and instance segmentation. We train stage I for 1000 epochs and stage II for 200 epochs.

As the reconstruction loss during stage I, we use the standard cross-entropy categorical loss for each channel independently. At test time, the output mask is first formed by the predicted instance channel. Then each instance is labeled my the majority vote of pixels from the semantic channels. This avoids inconsistencies in which pixels with the same instance id, but different semantic categories are interpreted as different instances. We additionally remove tiny objects that occupy less than 0.1% of all pixels. At test time, we resize the outputs to the target resolution via nearest neighbour.

Table 1 shows that UViM achieves 45.6 PQ, outperforming a recent strong baseline model DETR-R101 [2]. We focus on evaluating the generality of our approach, hence we avoid specialization towards individual tasks, such as commonly-used feature pyramids or scale jitter augmentations. As a result we lag behind the most recent state-of-the-art [5]. We expect that the gap can be bridged by further refining UViM with better understanding of its components and smarter modeling choices.

3.2 Colorization

Colorization requires mapping grayscale pixels of an image to plausible colors. In particular for a given input there are many possible outputs and as so Fréchet Inception Distance (FID) [17] is a common metric. We opt to model this as a mapping from grayscale to RGB and use mean squared error as reconstruction loss during stage I training. For training we use ImageNet [38] training split consisting of 1.2M examples. We follow COLTRAN [27] and report FIDs using the prescribed splits of images for metric computation and resize our model predictions to 256×256. We train stage I for 100 epochs and stage II for 50 epochs.

Figure 4 demonstrates that UViM is capable of producing high-quality and *diverse colorizations* for natural images. Table 1 shows that it achieves an FID of 16.174 on this task. This is slightly below the current state-of-the-art Palette [39] which uses diffusion models to cover a variety of tasks that output natural images. But significantly above COLTRAN [27] which uses a conditional autoregressive transformer to output a low resolution colorization followed by an upsampling model.

3.3 Monocular depth estimation

Depth prediction is a 3D scene understanding task, which requires mapping every pixel to a depth value (distance to the camera). We quantize the depth into buckets using 256 uniformly spaced bins, and use softmax cross entropy as reconstruction loss during stage I.

We train on the NYU Depth V2 [42] dataset consisting of 47'584 training examples captured across 280 indoor scenes, and 654 official validation examples. For hyper-parameter selection we hold out all examples from 14 scenes from the training set. For evaluation, we report the common evaluation metric: root mean squared error (RMSE) on the standard crop of the evaluation images from [10]. At test time, we resize UViM outputs to the crop resolution via nearest neighbour. We train stage I for 200 epochs and stage II for 50 epochs.

Table 2: Effect of ablating various UViM components on the panoptic segmentation task. PQ metric is computed on 4096 examples holdout from the training set. Besides stage II results (second row, black), we also show the results of stage I using the restricted oracle's guiding code (first row gray).

	Default	From Scratch	no Dropout	no Oracle	no Autoreg.	no Image
UViM(stage I)	75.7	75.7	**85.8**	19.6	75.7	66.1
UViM (stage II)	**43.7**	39.8	42.2	N/A	33.3	39.1

Figure 5: Outputs of various models in our ablation. We demonstrate that *base model* alone is not capable of modeling structured outputs, but when supported with compact oracle's guiding code, it achieves near perfect results. For completeness, we also present the result of the final UViM model.

Table 1 shows that UViM achieves an RMSE of 0.467 RMSE on this task. To contextualize this result, this score is comparable to DenseDepth [1] which uses an architecture composed of a pre-trained DenseNet-169 followed by upsampling layers and skip-connections. Our results still lags behind the most recent state-of-the-art model for this task [28] which consists of a mixed classification/regression loss, adaptive bins, auxiliary scene classification task and multi-scale prediction refining. However, UViM has very little task-specific tuning; our depth model is almost identical to out setup for panoptic segmentation, even sharing most hyperparameter values.

4 Ablations

In this section we dive deep into understanding UViM and perform ablations of its key components. We run extensive ablations (summarized in Table 2) on the panoptic segmentation task. For completeness, together with the performance of the final UViM models, we demonstrate the performance of UViM models after stage I training, which use the code from the restricted oracle. Some of our ablations are also illustrated visually in Figure 5.

For the default setting we follow the main experimental setup, but use 512×512 inputs for stage II training. To avoid overfitting to test data, all our ablations are performed using our custom splits, where we hold out 4096 randomly selected images from the training data and use those for evaluation.

Ablating pre-trained weights. UViM is designed to make transfer learning easy, as it uses plain parametric models (without any modifications) that are commonly used for large-scale pre-training [45]. Nevertheless, we ablate the usage of pre-trained weights to understand how UViM will perform in the this scenario. "From Scratch" column in Table 2 shows the results (note as we only use pre-trained weights for the LM, stage I results are not affected). Notably we use a longer training schedule with 500 epochs, which improves from-scratch results due to slower convergence. We observe that the from-scratch trained model performs well and achieves competitive results. Nevertheless, from scratch training is 2.9 PQ points behind the default setup of using pre-trained weights.

Ablating code dropout. The idea of the code dropout procedure, described in section 2.3, is to make the *guiding code* learned during stage I less "strict", so it will be easier to model it with the LM in stage II. Table 2 shows results of ablating this procedure in the "no dropout" column. As expected, ablating dropout results in better stage I results (by approximately 10 PQ points), as the oracle's code is not weakened by the dropout. On the other hand, the final UViM model becomes worse, as the resulting code learned without dropout has much more complex structure. We support our intuition by comparing final training losses of the LM models, trained for code with and without dropout. The losses are measured as average negative log-likelihoods, as are equal to 1.3 and 4.2, confirming that the code that was trained with dropout are much easier to learn.

For the depth estimation task, we observed no difference ablating code dropout, indicating that code dropout is not always necessary, only for tasks where the code can become challenging for the LM to learn.

Ablating restricted oracle model. In this ablation we evaluate the base model $f : \mathcal{X} \mapsto \mathcal{Y}$ trained directly without z. The results in Table 2 confirm our (see 5) qualitative assessment that directly predicting panoptic mask with pixel-wise loss works very poorly in the absence of the oracle model.

Ablating autoregressive structure of LM model. So far we have assumed that the guiding code z needs to predicted by a function capable to model a joint probability distribution, such as an autoregressive LM. We ablate this design choice and train a non-autoregressive LM, which predicts all components of z in a single pass, but otherwise is identical to default LM models that we use.

The results in Table 2 confirm that the autoregressive component for joint probability distribution modeling is crucial. Ablating this component leads to a significant quality drop of 10.4 PQ points. We observe a similar effect on depth estimation, where RMSE drops from 0.47 to 0.55.

Ablating image input at stage I training. One interesting ablation is to hide the image input from the base model f. In this case our whole UViM model can be interpreted from a different, more limited perspective: Ω learns to compress a label into z and, at the same time, f learns to decode it back into the original label. Then the LM learns to solve the task in this new learned compact space.

As shown in column "no image" of Table 2, the model solving the task in the learned space $\mathcal{Z}$ still performs reasonably well, though it lags behind the more general default approach. For depth estimation, the base model with no image obtains a similar performance to the full model (within 0.005 RMSE), indicating that for this task the oracle can compress all of the information required to reconstruct the label into the guiding code.

Varying oracle code length and dictionary size

Finally, we investigate how the size of the code $z \in \mathcal{Z}$ affects performance. In particular, we vary the code length and dictionary size (the total number of discrete values for each component). Intuitively, a longer sequence and a larger dictionary make it easier to learn during stage I training, as the oracle "restriction" becomes weaker. However, it is not clear how the code parameters will affect the stage II training and the final UViM model, as longer sequence and more discrete values are potentially harder to learn for the LM model.

Figure 6: UViM model performance for the panoptic task (measured as PQ points).

To study this trade-off we train nine models: a cross-product of sequence lengths $\{64, 256, 1024\}$ and dictionary sizes $\{1024, 4096, 16384\}$. Figure 6 shows the results. As expected, UViM with oracle stage I model monotonically benefits from longer sequences and bigger dictionary sizes. However, the sweet spot for the final model is the code which is neither too long nor too short.

5 Related work

This paper is related to the vast amount of literature in computer vision, as the proposed modeling approach aims at unifying a wide array of vision tasks. We focus on the most related work that is either pushing in the same direction of model unification or uses highly related modeling techniques.

Generative and autoregressive models. Like in generative modeling, we have a similar goal of modeling high-dimensional structured outputs. A notable work, Pix2Pix [19], uses a conditional GAN model to map arbitrary image input to arbitrary image outputs. Despite going beyond generative tasks, and showing some outputs for semantic segmentation task, this model has not become a competitive approach, likely due to the complexity and instability of GAN training.

Autoregressive models gained a popularity in computer vision as (conditional) image generation tools [49, 48, 40] and later were used for tasks like image colorization [37, 14, 27]. However,

scalability of autoregressive models for very high-dimensional outputs is a big problem, which was necessitating additional complexity, such as hierarchical generation [48, 24] or learning of an additional upsampling model [14, 27]. The idea of modeling a complex structured target by recurrent "autoregressive" invocations of a model was used in a customized implementations for visual relationship prediction [23] and human pose estimation [12].

Closer to our approach is the use of *learned discrete representations* with an autoregressively learned prior [50]. DALL-E [35] showed text conditioned image generation by using a decoder-only transformer to model a sequence of text and image discrete representations. VQGAN [11] show high-quality natural image generation conditioned in arbitrary image inputs by using an adversarial and perceptual loss to learn discrete representations. VIT-VQGAN [53] improved class-conditioned image synthesis with codebook improvements and parameterizing VQGAN with ViT [9]. Similarity NÜWA [52] propose a 3D transformer encoder-decoder, which covers language, image, and video with learned discrete representations. Notably, these works concentrate on the (conditional) generative image tasks and mostly ignore discriminative image tasks.

Scene understanding. There are several fundamental vision tasks that require a model to perform high-level scene parsing, such as object detection, instance or panoptic segmentation. Many standard methods, such as Faster-RCNN [36], Mask-RCNN [15] and RetinaNet [29] produce "dense" predictions for a large number of scored anchor boxes, followed by an ad-hoc non-maximal suppression procedure to eliminate redundant boxes. DETR [2] takes an alternative approach with an end-to-end model using a set-based global loss (via bipartite matching of proposals and ground truth). The DETR model can also be used for panoptic segmentation [22], where initial approaches involved combining models optimized for each sub-part of the task (instance and semantic classification). Maskformer [6] uses a mask loss to guide the set-loss and further claims that the mask classification view of the problem is important for panoptic and also semantic segmentation. Mask2former [5] shows a single architecture *designed around masks* can tackle all semantic, instance and panoptic segmentation tasks. Despite some promising convergence in the scene understanding area, the proposed approaches remain only viable for an important, but relatively narrow range of tasks.

Vision model unification. PIX2SEQ [4] proposes a model highly related to ours. It leverages a plain (sequence) language model for tackling the highly structured task of object detection. However, it is limited to the scenario when an output of a vision task can be manually represented as a short discrete sequence, which is rarely true for vision tasks. In [32] the authors propose a Transframer model, which uses a language model for modeling image outputs represented as sparse discrete cosine transform codes. However, the paper only shows qualitative results for "discriminative" tasks. Moreover, in comparison to our model, the Transframer is less flexible and powerful because it relies on the pre-defined fixed transform, while UViM learns discrete representations using a powerful end-to-end approach.

6 Conclusion and Discussion

UViM is a modeling approach for vision with an ambitious goal of unifying diverse vision tasks with one technique. Our resulting model consists of two components: an autoregressive language model (for modeling complex structured outputs) and a plain feed-forward base model that helps to handle high dimensional outputs efficiently. Empirically, we confirm that UViM is capable of tackling diverse vision tasks in a unified way, while achieving competitive results. Our tasks cover semantic scene understanding (panoptic segmentation), conditional generative image modeling task (colorization) and 3D scene prediction (depth prediction).

Note, that the proposed modeling approach is very general and is not specifically tailored to any particular application. As a result, we do not anticipate any negative *societal* impact of our technique.

We see UViM as a brave new prototype of the general-purpose learning approach for computer vision. As such, it still has many rough edges that need more research. For example, we do not yet fully understand how to learn the optimal *guiding code*. Empirically, we observe that the final result is sensitive to the phase I code learning parameters. For example, code length of 256 seems overall better than 16 and 1024 in our experiments; or adding dropout to the code during its training results in a better final model. We hope future research will come up with better understanding of how to set up learning of the *guiding code*, beyond pure empirical observations. Another aspect is the computational efficiency. As reported in the paper, the training is relatively compute hungry. More research may be needed to find design choices that will lead to much more efficient training procedures.

References

[1] I. Alhashim and P. Wonka. High quality monocular depth estimation via transfer learning. *arXiv preprint arXiv:1812.11941*, 2018.

[2] N. Carion, F. Massa, G. Synnaeve, N. Usunier, A. Kirillov, and S. Zagoruyko. End-to-end object detection with transformers. In *European Conference on Computer Vision*, 2020.

[3] L.-C. Chen, G. Papandreou, I. Kokkinos, K. Murphy, and A. L. Yuille. DeepLab: Semantic image segmentation with deep convolutional nets, atrous convolution, and fully connected CRFs. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 2017.

[4] T. Chen, S. Saxena, L. Li, D. J. Fleet, and G. Hinton. Pix2seq: A language modeling framework for object detection. In *International Conference on Learning Representations*, 2022.

[5] B. Cheng, I. Misra, A. G. Schwing, A. Kirillov, and R. Girdhar. Masked-attention mask transformer for universal image segmentation. *arXiv preprint arXiv:2112.01527*, 2021.

[6] B. Cheng, A. Schwing, and A. Kirillov. Per-pixel classification is not all you need for semantic segmentation. In *Advances in Neural Information Processing Systems*, 2021.

[7] K. Cho, B. van Merriënboer, D. Bahdanau, and Y. Bengio. On the properties of neural machine translation: Encoder–decoder approaches. In *Proceedings of SSST-8, Eighth Workshop on Syntax, Semantics and Structure in Statistical Translation*, 2014.

[8] J. Devlin, M.-W. Chang, K. Lee, and K. Toutanova. BERT: Pre-training of deep bidirectional transformers for language understanding. *arXiv preprint arXiv:1810.04805*, 2018.

[9] A. Dosovitskiy, L. Beyer, A. Kolesnikov, D. Weissenborn, X. Zhai, T. Unterthiner, M. Dehghani, M. Minderer, G. Heigold, S. Gelly, J. Uszkoreit, and N. Houlsby. An image is worth 16x16 words: Transformers for image recognition at scale. In *International Conference on Learning Representations*, 2021.

[10] D. Eigen, C. Puhrsch, and R. Fergus. Depth map prediction from a single image using a multi-scale deep network. In *Advances in Neural Information Processing Systems*, 2014.

[11] P. Esser, R. Rombach, and B. Ommer. Taming transformers for high-resolution image synthesis. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 2021.

[12] G. Gkioxari, A. Toshev, and N. Jaitly. Chained predictions using convolutional neural networks. In *European Conference on Computer Vision*, 2016.

[13] I. Goodfellow, J. Pouget-Abadie, M. Mirza, B. Xu, D. Warde-Farley, S. Ozair, A. Courville, and Y. Bengio. Generative adversarial nets. In *Advances in Neural Information Processing Systems*, 2014.

[14] S. Guadarrama, R. Dahl, D. Bieber, M. Norouzi, J. Shlens, and K. Murphy. PixColor: Pixel recursive colorization. In *British Machine Vision Conference*, 2017.

[15] K. He, G. Gkioxari, P. Dollár, and R. Girshick. Mask R-CNN. In *Proceedings of the IEEE International Conference on Computer Vision*, 2017.

[16] K. He, X. Zhang, S. Ren, and J. Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, 2016.

[17] M. Heusel, H. Ramsauer, T. Unterthiner, B. Nessler, and S. Hochreiter. GANs trained by a two time-scale update rule converge to a local nash equilibrium. In *Advances in Neural Information Processing Systems*, 2017.

[18] J. Ho, A. Jain, and P. Abbeel. Denoising diffusion probabilistic models. In *Advances in Neural Information Processing Systems*, 2020.

[19] P. Isola, J.-Y. Zhu, T. Zhou, and A. A. Efros. Image-to-image translation with conditional adversarial networks. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, 2017.

[20] D. P. Kingma and J. Ba. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014.

[21] D. P. Kingma and M. Welling. Auto-encoding variational Bayes. *arXiv preprint arXiv:1312.6114*, 2013.

[22] A. Kirillov, K. He, R. Girshick, C. Rother, and P. Dollar. Panoptic segmentation. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 2019.

[23] A. Kolesnikov, A. Kuznetsova, C. Lampert, and V. Ferrari. Detecting visual relationships using box attention. In *Proceedings of the IEEE/CVF International Conference on Computer Vision Workshops*, 2019.

[24] A. Kolesnikov and C. H. Lampert. PixelCNN models with auxiliary variables for natural image modeling. In *International Conference on Machine Learning*, 2017.

[25] D. Koller and N. Friedman. *Probabilistic graphical models: principles and techniques*. MIT Press, 2009.

[26] A. Krizhevsky, I. Sutskever, and G. E. Hinton. Imagenet classification with deep convolutional neural networks. In *Advances in Neural Information Processing Systems*, 2012.

[27] M. Kumar, D. Weissenborn, and N. Kalchbrenner. Colorization transformer. In *International Conference on Learning Representations*, 2021.

[28] Z. Li, X. Wang, X. Liu, and J. Jiang. BinsFormer: Revisiting adaptive bins for monocular depth estimation. *arXiv preprint arXiv:2204.00987*, 2022.

[29] T.-Y. Lin, P. Goyal, R. Girshick, K. He, and P. Dollár. Focal loss for dense object detection. In *Proceedings of the IEEE International Conference on Computer Vision*, 2017.

[30] T.-Y. Lin, M. Maire, S. Belongie, J. Hays, P. Perona, D. Ramanan, P. Dollár, and C. L. Zitnick. Microsoft COCO: Common objects in context. In *European Conference on Computer Vision*, 2014.

[31] Y. Linde, A. Buzo, and R. Gray. An algorithm for vector quantizer design. *IEEE Transactions on Communications*, 1980.

[32] C. Nash, J. Carreira, J. Walker, I. Barr, A. Jaegle, M. Malinowski, and P. Battaglia. Transframer: Arbitrary frame prediction with generative models. *arXiv preprint arXiv:2203.09494*, 2022.

[33] S. Nowozin and C. H. Lampert. *Structured learning and prediction in computer vision*. Now publishers Inc, 2011.

[34] C. Raffel, N. Shazeer, A. Roberts, K. Lee, S. Narang, M. Matena, Y. Zhou, W. Li, and P. J. Liu. Exploring the limits of transfer learning with a unified text-to-text transformer. *Journal of Machine Learning Research*, 2020.

[35] A. Ramesh, M. Pavlov, G. Goh, S. Gray, C. Voss, A. Radford, M. Chen, and I. Sutskever. Zero-shot text-to-image generation. In *International Conference on Machine Learning*, 2021.

[36] S. Ren, K. He, R. Girshick, and J. Sun. Faster R-CNN: Towards real-time object detection with region proposal networks. In *Advances in Neural Information Processing Systems*, 2015.

[37] A. Royer, A. Kolesnikov, and C. H. Lampert. Probabilistic image colorization. *arXiv preprint arXiv:1705.04258*, 2017.

[38] O. Russakovsky, J. Deng, H. Su, J. Krause, S. Satheesh, S. Ma, Z. Huang, A. Karpathy, A. Khosla, M. Bernstein, A. C. Berg, and L. Fei-Fei. ImageNet large scale visual recognition challenge. *International Journal of Computer Vision*, 2015.

[39] C. Saharia, W. Chan, H. Chang, C. A. Lee, J. Ho, T. Salimans, D. J. Fleet, and M. Norouzi. Palette: Image-to-image diffusion models. *arXiv preprint arXiv:2111.05826*, 2021.

[40] T. Salimans, A. Karpathy, X. Chen, and D. P. Kingma. PixelCNN++: Improving the PixelCNN with discretized logistic mixture likelihood and other modifications. *arXiv preprint arXiv:1701.05517*, 2017.

[41] N. Shazeer and M. Stern. Adafactor: Adaptive learning rates with sublinear memory cost. In *International Conference on Machine Learning*, 2018.

[42] N. Silberman, D. Hoiem, P. Kohli, and R. Fergus. Indoor segmentation and support inference from RGBD images. In *European Conference on Computer Vision*, 2012.

[43] K. Simonyan and A. Zisserman. Very deep convolutional networks for large-scale image recognition. In *International Conference on Learning Representations*, 2015.

[44] J. Sohl-Dickstein, E. Weiss, N. Maheswaranathan, and S. Ganguli. Deep unsupervised learning using nonequilibrium thermodynamics. In *International Conference on Machine Learning*, 2015.

[45] A. Steiner, A. Kolesnikov, X. Zhai, R. Wightman, J. Uszkoreit, and L. Beyer. How to train your ViT? data, augmentation, and regularization in vision transformers. *arXiv preprint arXiv:2106.10270*, 2021.

[46] I. Sutskever, O. Vinyals, and Q. V. Le. Sequence to sequence learning with neural networks. In *Advances in Neural Information Processing Systems*, 2014.

[47] C. Szegedy, W. Liu, Y. Jia, P. Sermanet, S. Reed, D. Anguelov, D. Erhan, V. Vanhoucke, and A. Rabinovich. Going deeper with convolutions. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, 2015.

[48] A. van den Oord, N. Kalchbrenner, L. Espeholt, K. Kavukcuoglu, O. Vinyals, and A. Graves. Conditional image generation with PixelCNN decoders. In *Advances in Neural Information Processing Systems*, 2016.

[49] A. van den Oord, N. Kalchbrenner, and K. Kavukcuoglu. Pixel recurrent neural networks. In *International Conference on Machine Learning*, 2016.

[50] A. van den Oord, O. Vinyals, and K. Kavukcuoglu. Neural discrete representation learning. In *Advances in Neural Information Processing Systems*, 2017.

[51] A. Vaswani, N. Shazeer, N. Parmar, J. Uszkoreit, L. Jones, A. N. Gomez, Ł. Kaiser, and I. Polosukhin. Attention is all you need. In *Advances in Neural Information Processing Systems*, 2017.

[52] C. Wu, J. Liang, L. Ji, F. Yang, Y. Fang, D. Jiang, and N. Duan. Nüwa: Visual synthesis pre-training for neural visual world creation. *arXiv preprint arXiv:2111.12417*, 2021.

[53] J. Yu, X. Li, J. Y. Koh, H. Zhang, R. Pang, J. Qin, A. Ku, Y. Xu, J. Baldridge, and Y. Wu. Vector-quantized image modeling with improved VQGAN. In *International Conference on Learning Representations*, 2022.

[54] W. Yuan, X. Gu, Z. Dai, S. Zhu, and P. Tan. NeW CRFs: Neural window fully-connected CRFs for monocular depth estimation. *arXiv preprint arXiv:2203.01502*, 2022.

[55] X. Zhai, A. Kolesnikov, N. Houlsby, and L. Beyer. Scaling vision transformers. *arXiv preprint arXiv:2106.04560*, 2021.

[56] R. Zhang, P. Isola, and A. A. Efros. Colorful image colorization. In *European Conference on Computer Vision*, 2016.