Not All Thoughts are Generated Equal: Efficient LLM Reasoning via Synergizing-Oriented Multi-Turn Reinforcement Learning

Abstract

Compressing long chain-of-thought (CoT) from large language models (LLMs) is an emerging strategy to improve reasoning efficiency. Despite its promising benefits, existing studies equally compress all thoughts within a long CoT, hindering more concise and effective reasoning. To this end, we first investigate the importance of different thoughts through automatic long CoT chunking and Monte Carlo rollouts. Building on this, we propose a theoretically bounded metric to jointly measure the effectiveness and efficiency of different thoughts. We then propose **Long⊗Short**, an efficient reasoning framework that enables two LLMs to collaboratively solve problems: a long-thought LLM for effectively generating important thoughts, and a short-thought LLM for efficiently generating remaining thoughts. Specifically, we synthesize cold-start data to fine-tune LLMs for long-thought and short-thought reasoning styles, respectively. Furthermore, we propose synergizing-oriented multi-turn reinforcement learning, focusing on model self-evolution and collaboration between long-thought and short-thought LLMs. Experimental results show that our method outperforms **seven** efficient reasoning methods and enables Qwen2.5-7B to **achieve comparable performance** to DeepSeek-R1-Distill-Qwen-7B, while **reducing token length by over 80%** across five reasoning benchmarks. Our code and data are available at https://anonymous.4open.science/r/Long-otimes-Short-0687/.

1 Introduction

Long Chain-of-Thought (CoT) reasoning achieves test-time scaling (Snell et al., 2024) by increasing the length of CoT (Wei et al., 2022) reasoning. With the advancement of LLMs such as OpenAI o-1 and DeepSeek-R1 (Guo et al., 2025), long CoT reasoning has demonstrated significant improvements on challenging tasks including mathemat-

Figure 1: Thought importance analysis framework. Given a long CoT, we automatically chunk it into multiple thought blocks and perform Monte Carlo rollouts to evaluate how individual thoughts affect reasoning effectiveness and efficiency.

ics (Hendrycks et al., 2021a), coding (Jain et al., 2024), and scientific reasoning (Rein et al., 2024). Despite these advances, the excessive token length (Jin et al., 2024) of long CoT reasoning remains a major bottleneck limiting its practical applicability.

Existing solutions for compressing reasoning tokens can be divided into three categories: *training-free*, *supervised fine-tuning (SFT) based*, and *reinforcement learning (RL) based* methods. Training-free methods prompt LLMs to limit word count or set maximum token-budgets (Han et al., 2024) at inference, *e.g.*, Qwen3 (Team, 2025). SFT-based approaches rely on rejection sampling (Yuan et al., 2023) to select correct but shortest reasoning trajectories for fine-tuning (Kang et al., 2025). RL-based methods employ offline learning (Shen et al., 2025a; Luo et al., 2025) with length preferences or online RL (Team et al., 2025; Yu et al., 2025a) with length-aware reward functions. However, these efforts **equally compress all thoughts within a long CoT** without considering differences in their importance—for example, a "double-verification" thought might be less important than "problem understanding" as it costs more tokens without extra accuracy gains (Figure 1), which hinders more concise and effective reasoning.

To address this, we first investigate thought im-

Table 1: Example of how a long-thought LLM and a short-thought LLM collaboratively answer a question through role switching.

Question: Given that the arithmetic mean of two positive numbers a and b is 4, then the maximum value of the geometric mean of a and b is ?
Ground Truth: 4
Long⊗Short:
`<think>` Ok. So I have a question ... `</think>`
`<answer>` Let's ... Therefore, current approach need to be reconsidered. `</rethink>`
...
`<think>` Wait, ... wait, hold on. maybe i'm overthinking this. perhaps there's a simpler way. `</think>`
`<answer>` Therefore, the answer should be 4. `</answer>`

portance within long CoTs by examining their contributions to reasoning. As illustrated in Figure 1, we: (1) propose automatic long CoT chunking to split reasoning into logical thought blocks; (2) perform Monte Carlo rollouts to approximate each thought's contribution to effectiveness and efficiency; and (3) propose a joint metric with theoretical error bounds for thought measurement. We find that front thoughts tend to yield higher contributions, even enabling Qwen2.5-7B to achieve performance comparable to DeepSeek-R1-Distill-Qwen-7B under zero-shot prompting.

Based on the above thought measurement approach, we propose **Long⊗Short**, an efficient reasoning framework that enables two LLMs to collaboratively solve the problem: a long-thought LLM for more effectively generating important thoughts, while a short-thought LLM for efficiently generating remaining thoughts. Specifically, we first fine-tune LLMs to follow long-thought reasoning and short-thought reasoning format under the supervision of synthesized cold start instructions. Moreover, we propose a *Synergizing-oriented Multi-Turn Reinforcement Learning* scheme to further enhance the efficient collaborative reasoning capability of the proposed framework. Different from existing studies (Shani et al., 2024) that rely on interactions with the environment to obtain reward signals (Zhou et al., 2025), our long-thought and short-thought LLMs engage in a multi-turn conversation to arrive at a final answer reward. Based on asynchronous policy optimization, the collaboration between long-thought and short-thought LLM could become stable, and their own reasoning capability could be improved, naturally emerging the oha moment (Guo et al., 2025) of "Overthinking" (e.g., maybe i'm overthinking this. perhaps there's a simpler way) and "Rethinking" (e.g., current approach need to be reconsidered).

We validate Long⊗Short on five benchmarks, including MATH 500, AIME 2024/2025, AMC 2023, and GPQA Diamond. The experimen-

tal results demonstrate that Long⊗Short enables LLM backbones (e.g., Qwen2.5-7B and Llama3.1-8B) to achieve comparable performance compared to their distillation versions (e.g., DeepSeek-R1-Distill-Qwen-7B and DeepSeek-R1-Distill-Llama-8B), while reducing average token length by over 80%. In addition, Long⊗Short also outperforms seven existing efficient reasoning methods.

In summary, our key contributions are threefold:

- We establish a thought analysis framework, which automatically chunks long CoT into multiple thoughts and quantifies their contributions.
- We propose Long⊗Short, which adopts cold-start and multi-turn RL training to synergize long-thought and short-thought reasoning.
- Extensive experiments and theoretical justification demonstrate the effectiveness of our method, offering a foundation for long CoT compression.

2 Preliminaries

Definition 1. *Thought. A thought is the basic logical block (e.g., problem decomposition, solution verification) in an LLM reasoning process. Given a long CoT response y, it can be structured as an ordered sequence of thoughts: $y = \{y_1, y_2, \ldots, y_n\}$, where n is the total number of thoughts.*

Problem 1. *Long⊗Short Thought Reasoning. A long CoT reasoning process $y = \{y_1, y_2, \ldots, y_n\}$ can be reformulated into a mixture of long and short thoughts: $y = \{l_1, s_1, l_2, s_2, \ldots, l_m, s_k\}$, where l represents an important long thought, s denotes a compressed short thought, and $m + k \leq n$ since multiple thoughts may be compressed into a single short thought.*

This paradigm enables reasoning to dynamically alternate between long-thought and short-thought modes. Long-thought LLM uses `<think>` and `</think>` tokens, while short-thought LLM uses `<answer>` and `</rethink>` (to request rethinking) or `</answer>` (to finalize). Table 1 provides an illustrative example.

Figure 2: **(a) How thoughts affect Pass@1 accuracy and token length on GPQA.** We investigate how long thoughts from DeepSeek-R1-Distill-Qwen-7B affect the accuracy and token length of Qwen2.5-7B. The cyan line represents the effectiveness upper bound with full long thoughts; the orange line indicates the baseline under full short thoughts. **(b) Joint measurement of thought effectiveness and efficiency** as Monte Carlo rollout count increase from 2^3 times to 2^7 times.

3 Understanding Thoughts within Long CoT

To achieve long⊗short thought reasoning, we first investigate thought importance to determine whether a reasoning step should be handled by a long-thought or short-thought LLM.

3.1 Quantitative Analysis by Long CoT Chunking and Thought Rollout

Assumption 1. *Given a question q and the chunked thoughts $y = \{y_1, y_2, \ldots, y_n\}$ from reasoning model π_θ, a thought y_i is important if it helps the base model generate a response $y_{base} = \pi_{\theta_{base}}(q, \{y_1, y_2, \ldots, y_i\})$ that achieves higher accuracy with small response length increase.*

Long CoT Chunking and Thought Rollout. We develop a two-stage framework to analyze thought-level contributions. Unlike prior works relying on static templates or delimiters (Yang et al., 2025a), we prompt an LLM to automatically split the long CoT y into logical blocks $\{y_1, y_2, \ldots, y_n\}$, achieving 89% accuracy based on human-in-the-loop evaluation (details in Appendix A.3). We then perform Monte Carlo rollouts (Snell et al., 2024) on a base model (Qwen2.5-7B) by prefixing it with the top-k thoughts ($k \in [1, n]$) distilled from the DeepSeek-R1-7B.

Empirical Observation. We conduct analysis on the GPQA Diamond dataset (Figure 2a) and summarize two findings:

- **Front thoughts bring more accuracy gain:** The accuracy consistently increases when using top-0 to top-10 thoughts for rollout. Providing only the first 8 thoughts allows the 7B base model to significantly outperform the DeepSeek-R1-Distill-Qwen-7B, suggesting that **"thinking more" does not always equate to "thinking better."**

- **Long thoughts lead to significant length increase:** While early thoughts boost accuracy, they trigger a "length explosion." Even using only the top-1 thought doubles the response length, and many subsequent thoughts contribute marginal accuracy gains with token overhead.

These observations suggest that thought importance should be evaluated by jointly considering accuracy gains and additional length. We thus propose the following joint measurement metric.

3.2 Joint Measurement of Thought Effectiveness and Efficiency

We propose a unified metric to jointly evaluate the effectiveness and efficiency of each thought. This metric considers the accuracy gain from Monte Carlo rollouts alongside factors penalizing excessive length. Let $T_1(i) = \frac{d_y - d_{\{y_1,\ldots,y_i\}}}{d_y}$ and $T_2(i) = \frac{d_y - d_{y_i}}{d_y}$ be the length-based factors; the metric for thought y_i is:

$$\mathcal{M}(y_i) = \log_2\left(1 + T_1(i) \cdot T_2(i) \cdot \left(\frac{N_i^{right}}{N_i^{sum}}\right)\right) - \delta(y_i), \quad (1)$$

where (1) d_y is the total length of all thoughts; (2) $T_2(i) = \frac{d_y - d_{y_i}}{d_y}$ assigns higher scores to shorter thoughts; (3) $T_1(i) = \frac{d_y - d_{\{y_1,\ldots,y_i\}}}{d_y}$ assigns higher scores to thoughts with shorter cumulative context; (4) $\frac{N_i^{right}}{N_i^{sum}}$ is the empirical accuracy from Monte Carlo rollouts $\pi_{\theta_{base}}(q, \{y_1, \ldots, y_i\})$; and (5) $\delta(y_i) \in (0, 1)$ is a conditional decay penalty (set to 0.25), activated when thought y_i does not improve accuracy over y_{i-1}.

Motivation for the log-form design. The $\log_2(1 + x)$ formulation draws on information-theoretic principles: it maps the product of efficiency weights and accuracy into a bounded, concave score that naturally diminishes marginal returns—a thought must contribute proportionally more accuracy to compensate for its additional length. This ensures that the metric penalizes

"diminishing-return" thoughts while remaining numerically stable when accuracy estimates are noisy.

We present measurement results in Figure 2(b). High scores are predominantly associated with front thoughts, while only a few rear thoughts occasionally trigger resurgences. As rollout count increases, the approximate metrics converge to the theoretical curve.

Importantly, this metric is used *solely* for cold-start SFT data construction (Section 4.1). The subsequent RL training stage does not rely on this metric, instead using online reward signals to further refine collaboration.

3.3 Theoretical Justification

Based on the structure of Equation 1, we assume that the optimal measurement accounts for the true probability of success given the thoughts up to y_i, P_i^{true}. We can write the optimal measurement as:

$$\mathcal{M}_{opt}(y_i) = \log_2\left(1 + T_1(i) \cdot T_2(i) \cdot P_i^{true}\right) - \delta(y_i). \quad (2)$$

The error $\mathcal{E}(y_i)$ of our measurement $\mathcal{M}(y_i)$ relative to the theoretical optimum $\mathcal{M}_{opt}(y_i)$ is given by their difference:

$$\begin{aligned}\mathcal{E}(y_i) &= \mathcal{M}(y_i) - \mathcal{M}_{opt}(y_i) \\ &= \log_2\left(\frac{1 + T_1(i)T_2(i)\hat{P}_i}{1 + T_1(i)T_2(i)P_i^{true}}\right),\end{aligned} \quad (3)$$

where $\hat{P}_i = \frac{N_i^{right}}{N_i^{sum}}$ is the Monte Carlo estimate of P_i^{true}. To bound the absolute error $|\mathcal{E}(y_i)|$, we note that it is determined by the term $|\log_2(A) - \log_2(B)|$, where $A = 1 + T_1(i)T_2(i)\hat{P}_i$ and $B = 1 + T_1(i)T_2(i)P_i^{true}$. Applying the Mean Value Theorem (Siegel, 1945), there exists ξ between A and B such that $\log_2(A) - \log_2(B) = (A - B)\frac{1}{\xi \ln 2}$:

$$|\mathcal{E}(y_i)| \le |\log_2(A) - \log_2(B)| = \frac{T_1(i)T_2(i)|\hat{P}_i - P_i^{true}|}{|\xi| \ln 2}. \quad (4)$$

Since thoughts have non-zero length ($d_{y_i} > 0$) and the sequence does not cover the full length before thought n ($d_{\{y_1,...,y_i\}} < d_y$ for $i < n$), we have $T_1(i) \in [0, 1)$ and $T_2(i) \in [0, 1)$. Also, $\hat{P}_i, P_i^{true} \in [0, 1]$. Therefore, $A, B \in [1, 2]$, which implies $\xi \in [1, 2]$ and $|\xi| \ge 1$. $|\hat{P}_i - P_i^{true}| \le \epsilon$ where ϵ decreases with N_i^{sum}. Combining these results, we obtain the following upper bound:

$$|\mathcal{E}(y_i)| \le \frac{\epsilon}{\ln 2}. \quad (5)$$

This bound reveals that the error is mainly due to the probability error ϵ of Monte Carlo rollout, and can be reduced by increasing the rollout sample size. Detailed proof is provided in Appendix A.1.

4 Long⊗Short

Building on this analysis, we propose Long⊗Short, an efficient reasoning framework to incentivize long⊗short thought reasoning capacity (Figure 3).

4.1 Cold Start with Supervised Fine-Tuning

With the automatic long CoT chunking and joint measurement from Section 3.1, we obtain thought-score pairs $\{(y_1, \mathcal{M}(y_1)), \ldots, (y_n, \mathcal{M}(y_n))\}$. As shown in Figure 3, the next step is to construct SFT datasets for fine-tuning long-thought and short-thought LLMs.

Cold Start Data Synthesis. Thoughts with high scores are assigned to the long-thought LLM, and those with lower scores are handled by the short-thought LLM. To achieve this, we adopt a heuristic approach via a sequential scan over the trajectory of thoughts $\{(y_1, \mathcal{M}(y_1)), (y_2, \mathcal{M}(y_2)), \ldots, (y_n, \mathcal{M}(y_n))\}$. The first thought y_1 is always preserved as a long thought. For each subsequent thought y_i ($i > 1$), we compare its joint measurement against the maximum score of all previous thoughts: $\mathcal{M}(y_i) > \max\{\mathcal{M}(y_1), \mathcal{M}(y_2), \ldots, \mathcal{M}(y_{i-1})\}$. If this inequality holds, y_i is deemed sufficiently important and preserved as a long thought. Otherwise, a non-reasoning LLM is prompted to re-complete y_i, and the resulting output serves as a short thought. This procedure produces a structured sequence comprising alternating thought chunks: $\{l_1, s_1, l_2, s_2, \ldots, l_m, s_k\}$, where $m + k \le n$ since multiple thoughts may merge into a single short thought. We provide the prompt template for thought completion in Appendix A.2.3 and quality analysis in Appendix A.3.

Remark on data consistency. When a thought y_i is replaced by a short version s_i, the context for subsequent thoughts changes. We note that: (1) this approximation only affects the cold-start stage; (2) the subsequent RL training with online rollouts naturally corrects distributional mismatches introduced during cold-start; and (3) empirically, the cold-start policy provides a strong initialization that RL further improves (Table 2).

Efficiency-Aware Fine-Tuning. Subsequently, we concatenate reasoning templates and thought context to obtain two SFT datasets D_{long} and D_{short}. Specifically, for D_{long}, the instruction

Figure 3: Overview of the proposed Long⊗Short framework: (a) Cold-start data synthesis via thought importance measurement; (b) SFT cold-start for reasoning style initialization; (c) Synergizing-oriented multi-turn RL for collaborative self-evolution.

input $x = [\Gamma_{long} \parallel q \parallel h]$ is the concatenation of the long-thought reasoning template Γ_{long}, question q, and historical conversation h (e.g., `<think>`...`</think>``<answer>`...`</rethink>`) between the long-thought and short-thought LLM, while the instruction output corresponds to the long-thought reasoning process. For D_{short}, the instruction input $x = [\Gamma_{short} \parallel q \parallel h]$, where the difference lies in the reasoning template and potential historical conversation. Detailed reasoning templates can be found in Appendix A.2. Then, we utilize these datasets to perform full parameter fine-tuning on a base model:

$$\mathcal{L} = - \mathbb{E}_{(x,o) \sim D_{long}/D_{short}} \left[\log \mathcal{P}_{\pi_{\theta_{long}}/\pi_{\theta_{short}}} (o \mid x) \right], \quad (6)$$

where x and o represent the instruction input and output, respectively. Through this fine-tuning process, we derive two specialized models: $\pi_{\theta_{long}}$, tailored for effectively generating long thoughts, and $\pi_{\theta_{short}}$, adapted for producing short thoughts.

4.2 Synergizing-Oriented Multi-Turn RL

After the cold-start stage, the long-thought LLM and short-thought LLM can switch roles to collaboratively solve a question through multi-turn conversations. To facilitate more efficient reasoning, we propose a synergizing-oriented multi-turn reinforcement learning framework (Shani et al., 2024), designed to amplify the effectiveness and efficiency benefits of the long⊗short thought reasoning paradigm.

Asynchronous Policy Optimization. Unlike existing multi-turn RL methods (Zhou et al., 2025) that update the model's policy through direct interaction with the environment, our approach requires the long-thought LLM $\pi_{\theta_{long}}$ and the short-thought LLM $\pi_{\theta_{short}}$ to engage in a multi-turn conversation to derive the final reward for policy update. For the $\pi_{\theta_{long}}$, we formulate the optimization goal with an

external short-thought LLM $\pi_{\theta_{short}}$ as follows:

$$\max_{\pi_{\theta_{long}}} \mathbb{E}_{x \sim \mathcal{D}, o \sim \pi_{\theta_{long}}(\cdot|x;\pi_{\theta_{short}})} [r(x,o)] -$$
$$\beta \mathbb{D}_{\mathrm{KL}} \left[\pi_{\theta_{long}}(y \mid x; \pi_{\theta_{short}}) \parallel \pi_{\mathrm{ref}_{long}}(y \mid x; \pi_{\theta_{short}}) \right], \quad (7)$$

where $x \sim \mathcal{D}$ represents the input, o is the output generated by $\pi_{\theta_{long}}$ given x and the external $\pi_{\theta_{short}}$, $r(x,o)$ is the reward function, $\pi_{\mathrm{ref}_{long}}$ is the reference LLM, and $\mathbb{D}_{\mathrm{KL}}$ denotes the KL-divergence. By explicitly conditioning on an external model during policy learning, it enables more effective collaboration. Symmetrically, when optimizing the short-thought LLM $\pi_{\theta_{short}}$, the $\pi_{\theta_{long}}$ acts as the fixed external LLM:

$$\max_{\pi_{\theta_{short}}} \mathbb{E}_{x \sim \mathcal{D}, o \sim \pi_{\theta_{short}}(\cdot|x;\pi_{\theta_{long}})} [r(x,o)] -$$
$$\beta \mathbb{D}_{\mathrm{KL}} \left[\pi_{\theta_{short}}(y \mid x; \pi_{\theta_{long}}) \parallel \pi_{\mathrm{ref}_{short}}(y \mid x; \pi_{\theta_{long}}) \right]. \quad (8)$$

This alternating optimization ensures that each model updates its own policy in synergy with its counterpart, enabling efficient reasoning. This fundamentally distinguishes our approach from simple model routing methods (Ong et al., 2024) that merely dispatch queries to different models without joint training.

Online Sampling Strategy. To improve policy optimization stability and avoid the need for an additional value function approximation, we use Group Relative Policy Optimization (GRPO) (Shao et al., 2024) to sample a group of outputs $o = \{o_1, o_2, ..., o_G\}$ for the reference model for each input x. The sampling process follows an iterative framework where the system alternates between generating long thoughts (via $\pi_{\theta_{long}}$) and short thoughts (via $\pi_{\theta_{short}}$). This process continues until the short-thought LLM generates a final response, which is enclosed between designated answer tokens, `<answer>` and `</answer>`. Then, the reward is computed via a hybrid reward model.

Hybrid Reward Modeling. We introduce the reward function $r(x,o)$, which is the primary train-

ing signal to guide the optimization process. We design a hybrid reward combining correctness, format following, and response length:

$$r(x, o) = \eta \cdot \text{EM}\left(a_{\text{pred}}, a_{\text{gold}}\right) + \lambda \cdot \text{FM}\left(o\right) + \mu \cdot \text{LM}\left(o\right),$$
$$(9)$$

where a_{pred} is the extracted final answer from output o and a_{gold} is the ground truth answer; $\text{EM}(.)$ is a rule-based exact match function; $\text{FM}(.)$ represents the format reward function, designed to encourage LLMs to follow the predefined training templates specified in Table 6 and 7 in Appendix A.2; $\text{LM}(.)$ is the length reward function from KIMI K1.5 (Team et al., 2025) to guide models to use fewer tokens to achieve the final answer. The coefficients η, λ, and μ act as reward reweighting parameters. We use a curriculum: $\lambda=1.0$ early to stabilize formatting, then reduce to 0.1; $\mu=0$ initially for exploration, gradually increased to 0.5 to compress responses (we provide a detailed analysis in Appendix A.7).

5 Experiments

5.1 Experimental Setup

Benchmarks. We evaluate on five widely used reasoning benchmarks: MATH 500, AIME 2024, AIME 2025, GPQA Diamond, and AMC 2023 (Guo et al., 2025).

Backbone LLMs. We use Llama-3.1-8B, Qwen-2.5-7B, and Qwen3-8B as base non-reasoning models, comparing with their long CoT reasoning versions (DeepSeek-R1-Distill-Llama-8B, DeepSeek-R1-Distill-Qwen-7B, Qwen3-8B-thinking).

Baselines. We compare with existing methods: (1) *Training-free*: CoD (Xu et al., 2025), TALE-EP (Han et al., 2024); (2) *SFT-based*: C3oT (Kang et al., 2025), DAST (Shen et al., 2025a), O1-Pruner (Luo et al., 2025); (3) *RL-based*: SimplePO-DAST, Kimi k1.5 (Team et al., 2025).

Metrics. We employ Pass@1 accuracy, average length, and Accuracy-Efficiency Score (AES) (Luo et al., 2025): $AES = \eta \frac{Length_{base} - Length_{model}}{Length_{base}} + \varsigma \left| \frac{Acc_{model} - Acc_{base}}{Acc_{base}} \right|$, with $\eta=1$, $\varsigma=3$ when $Acc_{model} \geq Acc_{base}$, and $\varsigma=-5$ otherwise.

Implementation Details. We sample 0.1% of OpenMathInstruct (Toshniwal et al., 2024) (1.8K problems) for long CoT distillation from DeepSeek-R1. Qwen2.5-72B-Instruct performs automatic chunking. Monte Carlo rollouts (5 times per thought) on Qwen2.5-7B-Instruct and thought completion via Qwen2.5-72B-Instruct yield 1.4K SFT

samples. For RL, we use MATH-lighteval (7.5K training, 5K validation). Details in Appendix A.4.

Note on fairness. While Long⊗Short uses two 7B models (14B total parameters), at inference time only one model is active at any given step. As shown in Table 5, the throughput overhead from model switching is minimal (∼13 tokens/s reduction), and end-to-end latency remains close to the single base model.

5.2 Main Results

The main results are reported in Tables 2 and 3. We highlight key observations:

Cold-start stage establishes a strong initial policy. As reported in Table 2, to enable the long-thought and short-thought LLMs to switch roles effectively, we perform Monte Carlo rollouts to collect SFT data. After fine-tuning, Qwen2.5-7B achieves significant performance gains: 7.4%, 59.98%, 83.86%, 17.32%, and 58.82% on MATH500, AIME24/25, GPQA Diamond, and AMC23, respectively, with an increase in average response length from 1,623 to 7,323 tokens. The response length increase is expected as the long-thought LLM distills the long CoT reasoning style from DeepSeek-R1. The excessive reasoning tokens can be alleviated by the subsequent RL process.

Multi-turn RL continuously improves reasoning capacity. As reported in Table 2, after 4 rounds of evolution in the long-thought LLM and 2 rounds in the short-thought LLM, Long⊗Short enables Qwen2.5-7B, Qwen3-8B, and Llama3.1-8B to match the performance of DeepSeek-R1-Distill-Qwen-7B and DeepSeek-R1-Distill-Llama-8B, while reducing reasoning token lengths by over 80%. Long-r4⊗Short-r2 achieves the best AES metric (Luo et al., 2025), confirming that iterative RL training process maximizes the efficiency.

Long⊗Short outperforms existing efficient reasoning baselines. As shown in Table 3, we conduct a comprehensive baseline comparison. The experimental results demonstrate that Long⊗Short outperforms existing baselines (such as CoD and DAST) in both reasoning effectiveness and efficiency across five benchmarks. It is worth noting that, despite adopting a two-model collaborative reasoning scheme, our approach outperforms existing single-model methods in both accuracy and efficiency, demonstrating that the collaborative paradigm's benefits outweigh its additional complexity introduced by the two-model design.

Table 2: Long⊗Short across asynchronous evolution rounds. Pass@1 accuracy continually improves while response length significantly decreases. Long-r0⊗Short-r0 denotes the model after cold-start SFT.

Round#	MATH 500 Pass@1 ↑	AIME 2024 Pass@1 ↑	AIME 2025 Pass@1 ↑	GPQA Diamond Pass@1 ↑	AMC 2023 Pass@1 ↑	Avg. Length ↓	Avg. AES ↑
DeepSeek-R1-Distill-Qwen-7B	**93.40**	**53.33**	**36.67**	**48.98**	**95.00**	24,566	0
Base (Qwen2.5-7B)	74.80	16.67	7.25	37.88	42.50	1,623	-1.33
Long-r0⊗Short-r0 w/SFT	80.40	26.67	13.33	44.44	67.50	7,323	-0.75
Long-r1⊗Short-r0	84.60	36.67	23.33	45.45	72.50	2,169	-0.08
Long-r2⊗Short-r0	87.60	43.33	26.67	46.46	85.00	2,331	0.32
Long-r2⊗Short-r1	87.00	33.33	26.67	45.96	82.50	**2,021**	0.12
Long-r3⊗Short-r1	88.60	43.33	30.00	46.96	87.50	2,457	0.43
Long-r3⊗Short-r2	87.80	43.33	26.67	46.96	87.50	2,116	0.38
Long-r4⊗Short-r2	89.80	46.67	33.33	47.97	90.00	2,113	**0.61**
DeepSeek-R1-Distill-Llama-8B	**87.20**	**43.33**	30.00	**49.49**	**90.00**	28,496	0
Base (Llama3.1-8B)	62.80	10.00	6.67	35.86	22.50	3,713	-1.83
Long-r4⊗Short-r2	86.20	40.00	**33.33**	46.96	87.50	**2,402**	**0.81**
Qwen3-8B-thinking	88.20	**53.33**	**50.00**	58.08	77.50	21,158	0
Qwen3-8B-nothinking	81.60	36.67	20.00	53.03	60.00	5,580	-4.20
Long-r4⊗Short-r2	**88.50**	43.00	46.67	**59.09**	**80.50**	3,105	**0.66**

Table 3: Comparison with existing efficient reasoning approaches on Qwen2.5-7B backbone.

Methods		MATH 500 Pass@1 ↑	AIME 2024 Pass@1 ↑	AIME 2025 Pass@1 ↑	GPQA Diamond Pass@1 ↑	AMC 2023 Pass@1 ↑	Avg. Length ↓	Avg. AES ↑
Base (Qwen2.5-7B)		74.80	16.67	7.25	37.88	42.50	1,623	-1.33
Training-free	CoD	82.60	46.67	23.33	35.86	75.00	13,229	-0.51
	TALE-EP	88.20	50.00	**36.67**	41.41	85.00	16,668	-0.08
SFT-based	C3oT	81.00	30.00	26.67	47.47	82.50	12,576	-0.42
	DAST	83.50	33.33	13.33	32.83	77.50	10,235	-0.74
	O1-Pruner	87.55	36.67	26.67	37.87	85.00	13,467	-0.37
RL-based	SimplePO-DAST	82.75	33.33	26.67	43.93	77.50	17,849	-0.69
	Kimi k1.5	84.00	43.33	26.67	37.37	75.00	17,583	- 0.65
Long⊗Short-Qwen2.5-7B		89.80	46.67	33.33	47.97	90.00	**2,113**	**0.61**

5.3 Ablation Study

We evaluate through variants: (1) *SFT w/random*: random scoring replaces thought metric; (2) *Prompt wo/SFT*: directly prompting without fine-tuning; (3) *SFT w/δ(y_i) = 0.1/0.5*: alternative decay penalties; (4) *RL w/only short*: RL only for short-thought LLM; (5) *RL w/only long*: RL only for long-thought LLM.

As reported in Table 4, both direct prompting and random scoring lead to significant accuracy drops and length increases, validating the necessity of the thought-importance-guided cold-start. Training only one model leads to excessive length (long-only) or reduced accuracy (short-only), confirming the collaborative architecture.

5.4 In-Depth Analysis

Model Evolution Analysis. During iterative RL, the long-thought and short-thought LLMs are updated asynchronously (Figure 4). In early training, updating the short-thought LLM degrades performance, highlighting the critical role of the long-thought LLM. As the long-thought LLM evolves to

(a) Pass@1 Accuracy on Qwen2.5-7B   (b) Pass@1 Accuracy on Llama3.1-8B

Figure 4: Pass@1 accuracy evolution during asynchronous policy updates. Red stars indicate selected model checkpoints.

Rounds 3–4, performance stabilizes and improves, demonstrating that effective collaboration emerges through iterative optimization rather than being a simple pipeline.

Runtime Efficiency. As shown in Table 5, switching between two LLMs introduces only small overhead (∼13 tokens/s reduction for Qwen2.5-7B). The average latency (4.98s) is 6× faster than DeepSeek-R1-Distill-Qwen-7B (30.28s), demonstrating practical efficiency gains. Notably, while our framework maintains two 7B models (14B total parameters), only one is active at any inference step, and the total inference cost is dominated by the dramatically reduced output

Table 4: Ablation study on Qwen2.5-7B.

Variant	MATH 500 Pass@1 ↑	AIME 2024 Pass@1 ↑	GPQA Dia. Pass@1 ↑	Avg. Len ↓
Base (Qwen2.5-7B)	74.80	16.67	37.88	1,623
Prompt wo/SFT	71.60	6.67	33.83	5,362
SFT w/random	77.20	16.67	40.91	8,234
SFT w/δ=0.1	78.40	16.67	42.50	5,661
SFT w/δ=0.5	76.20	10.00	35.86	7,724
SFT w/ours (δ=0.25)	80.40	26.67	44.33	7,312
RL w/only short	82.04	33.33	40.90	1,226
RL w/only long	88.26	40.00	46.46	6,056
RL w/ours	89.80	46.67	47.97	2,364

Table 5: Runtime efficiency on MATH 500.

Model	Avg. Latency (s)	Tokens/s
DeepSeek-R1-Distill-Qwen-7B	30.28	355.81
Base (Qwen2.5-7B)	4.06	356.16
Long⊗Short-Qwen2.5-7B	4.98	343.97

length rather than model switching overhead.

Hyperparameter Sensitivity. We analyze sensitivity to rollout sample size n and RL reward weights (details in Appendix A.7). Key findings: (1) accuracy plateaus after n=4–5 rollouts, validating our choice of n=5 as a cost-effective operating point; (2) correctness weight η must remain dominant (η=1.0); reducing it to 0.5 substantially degrades accuracy; (3) format weight λ should be high initially (1.0) to stabilize the structured reasoning format, then reduced after convergence; (4) length penalty μ should be introduced gradually in later rounds to compress responses without sacrificing the task accuracy.

Emergent Aha Moments. We observe that RL training naturally increases the frequency of self-reflective behaviors ("Maybe I'm overthinking this", "Let me reconsider") from <5% after SFT to 16–43% after iterative RL, particularly on challenging benchmarks (AIME, GPQA). This suggests that the collaborative paradigm, combined with multi-turn RL, encourages more reflective reasoning without explicit supervision.

6 Related Work

Reinforcement Learning for LLM Reasoning. Recently, reinforcement learning (RL) like Proximal Policy Optimization (PPO) (Schulman et al., 2017) and DPO (Rafailov et al., 2023) has been widely adopted to improve LLM reasoning capability. More recently, GRPO (Ramesh et al., 2024) further simplifies this pipeline by removing the critic model, instead estimating policy value based on a group of rollout responses. However, these single-turn RL methods cannot interact with environments, limiting multi-step LLM reasoning. To

this end, the multi-turn RL (Shani et al., 2024) is proposed to improve LLM reasoning by enabling collaboration with external tools (Jin et al., 2025) and LLMs. Nevertheless, the application of multi-turn RL for efficient reasoning remains unexplored.

Efficient Chain-of-Thought Reasoning in LLMs. To improve reasoning efficiency (Jin et al., 2024), recent work focuses on reducing chain-of-thought (CoT) length without sacrificing accuracy (Sui et al., 2025), which can be mainly divided into three categories: (1) *Training-free* methods explicitly prompt LLMs to generate limited outputs (Kumar et al., 2025) or enforce hard token limits during inference (Team, 2025). They avoid parameter updates and rely on external constraints to guide brevity (Yu et al., 2025b). (2) *SFT-based* methods first apply rejection sampling to obtain correct but shorter reasoning trajectories. Then, approaches like TOPS (Yang et al., 2025c) and C3oT (Kang et al., 2025) directly use such trajectories for SFT (Ma et al., 2025). This strategy encourages LLM to conduct more concise reasoning (Shen et al., 2025b). (3) *RL-based* methods employ both offline and online learning strategy. Offline methods like DAST (Shen et al., 2025a) construct shorter-longer response pairs (Chen et al., 2024) for CoT-length preference learning, while online methods such as Kimi k1.5 (Team et al., 2025) and DAPO (Yu et al., 2025a) incorporate length rewards to penalize excessive reasoning (Arora and Zanette, 2025). However, these methods equally compress all thoughts within long CoT, limiting more efficient reasoning.

7 Conclusion and Future Work

In this work, we propose a theoretically grounded thought analysis framework that incorporates an automatic chunking method and a Monte Carlo thought rollout process to quantify thought importance. Moreover, we introduce Long⊗Short, a collaborative reasoning framework that sequentially execute SFT for reasoning style cold-start and multi-turn RL for model self-evolution, enabling two LLMs to dynamically switch between long-thought and short-thought reasoning styles. Extensive experiments show that Long⊗Short significantly enhances the performance of base LLMs while maintaining competitive efficiency. Future work includes scaling long⊗short thought reasoning paradigm with size-varying LLMs.

Limitations

Our cold-start stage involves Monte Carlo rollouts and thought completion with an auxiliary LLM, introducing additional training-time computation. Additionally, our evaluation focuses on mathematical and scientific reasoning benchmarks; generalization to other reasoning-intensive domains (e.g., GUI agent) is left for future investigation.

Ethical Statement

We use LLMs for paper polishing and figure plotting, and have carefully verified all outputs for correctness. This work evaluates existing large language models on publicly available datasets and benchmarks. It does not involve user private data, or harmful content. Furthermore, all models used are not deployed for real-world user applications.

References

Daman Arora and Andrea Zanette. 2025. Training language models to reason efficiently. *arXiv preprint arXiv:2502.04463*.

Xingyu Chen, Jiahao Xu, Tian Liang, Zhiwei He, Jianhui Pang, Dian Yu, Linfeng Song, Qiuzhi Liu, Mengfei Zhou, Zhuosheng Zhang, and 1 others. 2024. Do not think that much for 2+ 3=? on the overthinking of o1-like llms. *arXiv preprint arXiv:2412.21187*.

Daya Guo, Dejian Yang, Haowei Zhang, Junxiao Song, Ruoyu Zhang, Runxin Xu, Qihao Zhu, Shirong Ma, Peiyi Wang, Xiao Bi, and 1 others. 2025. Deepseek-r1: Incentivizing reasoning capability in llms via reinforcement learning. *arXiv preprint arXiv:2501.12948*.

Tingxu Han, Zhenting Wang, Chunrong Fang, Shiyu Zhao, Shiqing Ma, and Zhenyu Chen. 2024. Token-budget-aware llm reasoning. *arXiv preprint arXiv:2412.18547*.

Dan Hendrycks, Collin Burns, Saurav Kadavath, Akul Arora, Steven Basart, Eric Tang, Dawn Song, and Jacob Steinhardt. 2021a. Measuring mathematical problem solving with the math dataset. *arXiv preprint arXiv:2103.03874*.

Dan Hendrycks, Collin Burns, Saurav Kadavath, Akul Arora, Steven Basart, Eric Tang, Dawn Song, and Jacob Steinhardt. 2021b. Measuring mathematical problem solving with the math dataset. *arXiv preprint arXiv:2103.03874*.

Naman Jain, King Han, Alex Gu, Wen-Ding Li, Fanjia Yan, Tianjun Zhang, Sida Wang, Armando Solar-Lezama, Koushik Sen, and Ion Stoica. 2024. Livecodebench: Holistic and contamination free evaluation of large language models for code. *arXiv preprint arXiv:2403.07974*.

Bowen Jin, Hansi Zeng, Zhenrui Yue, Jinsung Yoon, Sercan Arik, Dong Wang, Hamed Zamani, and Jiawei Han. 2025. Search-r1: Training llms to reason and leverage search engines with reinforcement learning. *arXiv preprint arXiv:2503.09516*.

Mingyu Jin, Qinkai Yu, Dong Shu, Haiyan Zhao, Wenyue Hua, Yanda Meng, Yongfeng Zhang, and Mengnan Du. 2024. The impact of reasoning step length on large language models. *arXiv preprint arXiv:2401.04925*.

Yu Kang, Xianghui Sun, Liangyu Chen, and Wei Zou. 2025. C3ot: Generating shorter chain-of-thought without compromising effectiveness. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 39, pages 24312–24320.

Abhinav Kumar, Jaechul Roh, Ali Naseh, Marzena Karpinska, Mohit Iyyer, Amir Houmansadr, and Eugene Bagdasarian. 2025. Overthink: Slowdown attacks on reasoning llms. *arXiv e-prints*, pages arXiv–2502.

Zichen Liu, Changyu Chen, Wenjun Li, Penghui Qi, Tianyu Pang, Chao Du, Wee Sun Lee, and Min Lin. 2025. Understanding r1-zero-like training: A critical perspective. *arXiv preprint arXiv:2503.20783*.

Haotian Luo, Li Shen, Haiying He, Yibo Wang, Shiwei Liu, Wei Li, Naiqiang Tan, Xiaochun Cao, and Dacheng Tao. 2025. O1-pruner: Length-harmonizing fine-tuning for o1-like reasoning pruning. *arXiv preprint arXiv:2501.12570*.

Xinyin Ma, Guangnian Wan, Runpeng Yu, Gongfan Fang, and Xinchao Wang. 2025. Cot-valve: Length-compressible chain-of-thought tuning. *arXiv preprint arXiv:2502.09601*.

Isaac Ong, Amjad Almahairi, Vincent Wu, Wei-Lin Chiang, Tianhao Wu, Joseph E Gonzalez, M Waleed Kadous, and Ion Stoica. 2024. Routellm: Learning to route llms with preference data. *arXiv preprint arXiv:2406.18665*.

OpenAI. 2024. Introducing openai o1. *https://openai.com/o1/*.

OpenAI. 2025. gpt-oss-120b & gpt-oss-20b model card. *Preprint*, arXiv:2508.10925.

Rafael Rafailov, Archit Sharma, Eric Mitchell, Christopher D Manning, Stefano Ermon, and Chelsea Finn. 2023. Direct preference optimization: Your language model is secretly a reward model. *Advances in Neural Information Processing Systems*, 36:53728–53741.

Shyam Sundhar Ramesh, Yifan Hu, Iason Chaimalas, Viraj Mehta, Pier Giuseppe Sessa, Haitham Bou Ammar, and Ilija Bogunovic. 2024. Group robust preference optimization in reward-free rlhf. *Advances in*

Neural Information Processing Systems, 37:37100–37137.

David Rein, Betty Li Hou, Asa Cooper Stickland, Jackson Petty, Richard Yuanzhe Pang, Julien Dirani, Julian Michael, and Samuel R Bowman. 2024. Gpqa: A graduate-level google-proof q&a benchmark. In *First Conference on Language Modeling*.

John Schulman, Filip Wolski, Prafulla Dhariwal, Alec Radford, and Oleg Klimov. 2017. Proximal policy optimization algorithms. *arXiv preprint arXiv:1707.06347*.

Lior Shani, Aviv Rosenberg, Asaf Cassel, Oran Lang, Daniele Calandriello, Avital Zipori, Hila Noga, Orgad Keller, Bilal Piot, Idan Szpektor, and 1 others. 2024. Multi-turn reinforcement learning from preference human feedback. *arXiv preprint arXiv:2405.14655*.

Zhihong Shao, Peiyi Wang, Qihao Zhu, Runxin Xu, Junxiao Song, Xiao Bi, Haowei Zhang, Mingchuan Zhang, YK Li, Y Wu, and 1 others. 2024. Deepseek-math: Pushing the limits of mathematical reasoning in open language models. *arXiv preprint arXiv:2402.03300*.

Yi Shen, Jian Zhang, Jieyun Huang, Shuming Shi, Wenjing Zhang, Jiangze Yan, Ning Wang, Kai Wang, and Shiguo Lian. 2025a. Dast: Difficulty-adaptive slow-thinking for large reasoning models. *arXiv preprint arXiv:2503.04472*.

Zhenyi Shen, Hanqi Yan, Linhai Zhang, Zhanghao Hu, Yali Du, and Yulan He. 2025b. Codi: Compressing chain-of-thought into continuous space via self-distillation. *arXiv preprint arXiv:2502.21074*.

Carl Ludwig Siegel. 1945. A mean value theorem in geometry of numbers. *Annals of Mathematics*, 46(2):340–347.

Charlie Snell, Jaehoon Lee, Kelvin Xu, and Aviral Kumar. 2024. Scaling llm test-time compute optimally can be more effective than scaling model parameters. *arXiv preprint arXiv:2408.03314*.

Yang Sui, Yu-Neng Chuang, Guanchu Wang, Jiamu Zhang, Tianyi Zhang, Jiayi Yuan, Hongyi Liu, Andrew Wen, Hanjie Chen, Xia Hu, and 1 others. 2025. Stop overthinking: A survey on efficient reasoning for large language models. *arXiv preprint arXiv:2503.16419*.

Kimi Team, Angang Du, Bofei Gao, Bowei Xing, Changjiu Jiang, Cheng Chen, Cheng Li, Chenjun Xiao, Chenzhuang Du, Chonghua Liao, and 1 others. 2025. Kimi k1. 5: Scaling reinforcement learning with llms. *arXiv preprint arXiv:2501.12599*.

Qwen Team. 2025. Qwen3 technical report. *https://github.com/QwenLM/Qwen3*.

Shubham Toshniwal, Ivan Moshkov, Sean Narenthiran, Daria Gitman, Fei Jia, and Igor Gitman. 2024. Openmathinstruct-1: A 1.8 million math instruction tuning dataset. *Advances in Neural Information Processing Systems*, 37:34737–34774.

Jason Wei, Xuezhi Wang, Dale Schuurmans, Maarten Bosma, Fei Xia, Ed Chi, Quoc V Le, Denny Zhou, and 1 others. 2022. Chain-of-thought prompting elicits reasoning in large language models. *Advances in neural information processing systems*, 35:24824–24837.

Silei Xu, Wenhao Xie, Lingxiao Zhao, and Pengcheng He. 2025. Chain of draft: Thinking faster by writing less. *arXiv preprint arXiv:2502.18600*.

An Yang, Beichen Zhang, Binyuan Hui, Bofei Gao, Bowen Yu, Chengpeng Li, Dayiheng Liu, Jianhong Tu, Jingren Zhou, Junyang Lin, and 1 others. 2024. Qwen2. 5-math technical report: Toward mathematical expert model via self-improvement. *arXiv preprint arXiv:2409.12122*.

Ling Yang, Zhaochen Yu, Bin Cui, and Mengdi Wang. 2025a. Reasonflux: Hierarchical llm reasoning via scaling thought templates. *arXiv preprint arXiv:2502.06772*.

Shu Yang, Junchao Wu, Xin Chen, Yunze Xiao, Xinyi Yang, Derek F Wong, and Di Wang. 2025b. Understanding aha moments: from external observations to internal mechanisms. *arXiv preprint arXiv:2504.02956*.

Wenkai Yang, Shuming Ma, Yankai Lin, and Furu Wei. 2025c. Towards thinking-optimal scaling of test-time compute for llm reasoning. *arXiv preprint arXiv:2502.18080*.

Qiying Yu, Zheng Zhang, Ruofei Zhu, Yufeng Yuan, Xiaochen Zuo, Yu Yue, Tiantian Fan, Gaohong Liu, Lingjun Liu, Xin Liu, and 1 others. 2025a. Dapo: An open-source llm reinforcement learning system at scale. *arXiv preprint arXiv:2503.14476*.

Zishun Yu, Tengyu Xu, Di Jin, Karthik Abinav Sankararaman, Yun He, Wenxuan Zhou, Zhouhao Zeng, Eryk Helenowski, Chen Zhu, Sinong Wang, and 1 others. 2025b. Think smarter not harder: Adaptive reasoning with inference aware optimization. *arXiv preprint arXiv:2501.17974*.

Zheng Yuan, Hongyi Yuan, Chengpeng Li, Guanting Dong, Keming Lu, Chuanqi Tan, Chang Zhou, and Jingren Zhou. 2023. Scaling relationship on learning mathematical reasoning with large language models. *arXiv preprint arXiv:2308.01825*.

Yifei Zhou, Song Jiang, Yuandong Tian, Jason Weston, Sergey Levine, Sainbayar Sukhbaatar, and Xian Li. 2025. Sweet-rl: Training multi-turn llm agents on collaborative reasoning tasks. *arXiv preprint arXiv:2503.15478*.

A Appendix

A.1 Theoretical Justification

We first give the mean value theorem lemma (Siegel, 1945) used for our theoretical justification:

Lemma A.1 (Mean Value Theorem). *Let f : $[a, b] \to \mathbb{R}$ be a continuous function on the closed interval $[a, b]$ and differentiable on the open interval (a, b). Then there exists a point $c \in (a, b)$ such that*

$$f'(c) = \frac{f(b) - f(a)}{b - a}. \tag{10}$$

With the defined lemma, we now analyze the error of our proposed measurement. we first postulate a form for the theoretical optimal measurement $\mathcal{M}_{opt}(y_i)$. Based on the structure of Equation 1, we assume that the optimal measurement accounts for the true probability of success given the thoughts up to y_i, P_i^{true}. Let the length-based factors $T_1(i) = \frac{d_y - d_{\{y_1, ..., y_i\}}}{d_y}$ and $T_2(i) = \frac{d_y - d_{y_i}}{d_y}$, we can write the optimal measurement as:

$$\mathcal{M}_{opt}(y_i) = \log_2 \left(1 + T_1(i) \cdot T_2(i) \cdot P_i^{true} \right) - \delta_{(y_i)}. \tag{11}$$

Then, The error $\mathcal{E}(y_i)$ of our proposed measurement $\mathcal{M}(y_i)$ relative to the theoretical optimum $\mathcal{M}_{opt}(y_i)$ is given by their difference:

$$\begin{aligned} \mathcal{E}(y_i) &= \mathcal{M}(y_i) - \mathcal{M}_{opt}(y_i) \\ &= \log_2 \left(1 + T_1(i) T_2(i) \hat{P}_i \right) \\ &\quad - \log_2 \left(1 + T_1(i) T_2(i) P_i^{true} \right) \\ &= \log_2 \left(\frac{1 + T_1(i) T_2(i) \hat{P}_i}{1 + T_1(i) T_2(i) P_i^{true}} \right). \end{aligned} \tag{12}$$

where $\hat{P}_i = \frac{N_i^{right}}{N_i^{sum}}$ is the Monte Carlo estimate of P_i^{true}. This error expression shows that the total error due to estimating the true probability P_i^{true} via Monte Carlo rollouts. Then, we derive an upper bound for the absolute error $|\mathcal{E}(y_i)|$. Using the triangle inequality, we have:

$$|\mathcal{E}(y_i)| \leq \left| \log_2 \left(\frac{1 + T_1(i) T_2(i) \hat{P}_i}{1 + T_1(i) T_2(i) P_i^{true}} \right) \right|. \tag{13}$$

Let $A = 1 + T_1(i) T_2(i) \hat{P}_i$ and $B = 1 + T_1(i) T_2(i) P_i^{true}$. The first term is $|\log_2(A) - \log_2(B)|$. Applying the Mean Value Theorem (Siegel, 1945) shown in Equation A.1, there exists

ξ between A and B such that $\log_2(A) - \log_2(B) = (A - B) \frac{1}{\xi \ln 2}$. Thus,

$$|\log_2(A) - \log_2(B)| = |A - B| \frac{1}{|\xi| \ln 2}, \tag{14}$$

The difference $|A - B|$ is given by:

$$\begin{aligned} |A - B| &= \left| (1 + T_1(i) T_2(i) \hat{P}_i) \right| \\ &\quad - \left| (1 + T_1(i) T_2(i) P_i^{true}) \right| \\ &= T_1(i) T_2(i) |\hat{P}_i - P_i^{true}|. \end{aligned} \tag{15}$$

Since $T_1(i) = \frac{d_y - d_{\{y_1, ..., y_i\}}}{d_y}$ and $T_2(i) = \frac{d_y - d_{y_i}}{d_y}$ are ratios of lengths within long CoT, and assuming thoughts have non-zero length ($d_{y_i} > 0$) and the sequence does not cover the full length before thought n ($d_{\{y_1, ..., y_i\}} < d_y$ for $i < n$), we have $T_1(i) \in [0, 1)$ and $T_2(i) \in [0, 1)$. Also, $\hat{P}_i, P_i^{true} \in [0, 1]$. Therefore, $A, B \in [1, 2]$, which implies $\xi \in [1, 2]$ and $|\xi| \geq 1$. Substituting these into the inequality for the log term:

$$\begin{aligned} |\log_2(A) - \log_2(B)| &\leq \frac{T_1(i) T_2(i) |\hat{P}_i - P_i^{true}|}{\ln 2} \\ &\leq \frac{|\hat{P}_i - P_i^{true}|}{\ln 2}. \end{aligned} \tag{16}$$

where the term $|\hat{P}_i - P_i^{true}|$ represents the absolute error in the Monte Carlo estimation of the success probability. For a sufficiently large number of rollouts N_i^{sum}, this error is expected to be small and is bounded. By concentration inequalities (e.g., Hoeffding's), w.h.p., $|\hat{P}_i - P_i^{true}| \leq \epsilon$ where ϵ decreases with N_i^{sum}. Combining the bounds for both terms, the total error is bounded by:

$$|\mathcal{E}(y_i)| \leq \frac{|\hat{P}_i - P_i^{true}|}{\ln 2}. \tag{17}$$

Using the trivial bound ϵ for the probability error, we obtain an upper bound for the absolute error:

$$|\mathcal{E}(y_i)| \leq \frac{\epsilon}{\ln 2}. \tag{18}$$

This bound reveals that the error is mainly due to the probability nature of Monte Carlo rollout, and can be effectively reduced by increasing the sample size N_i^{sum}.

A.2 Prompt Template

This section introduces the design of the training template and the prompt used to enable automatic Long CoT chunking and short thought completion.

> **A2.2.2 Prompt for Automatic Long CoT Chunking**
>
> You are a professional math teacher. When solving math problems, you typically begin by understanding the problem, then break down the solution into several major steps, solving each part in sequence, arriving at the final result, and performing a second verification. Next, I will give you a student's solution process to a math problem. Based on this process, you need to reconstruct their general thinking process during problem-solving — for example, first understanding the problem, then decomposing it, and so on.
>
> Specifically, please first read the problem and their solution. Then summarize the student's thinking process into distinct blocks such as "problem understanding" and so on. Record the start and end step index for each block. Return your answer in JSON format, where the key is "block 1", "block 2", etc., and the value includes the fields start, end, and block type. The start and end should refer to the index of each step, and block type should be a broad category (not too specific), such as "problem understanding".
>
> **Problem:**
> {Problem}
>
> **Solution:**
> {Long CoT}
>
> Fill in start and end using step indices, and write block type. Return only the following JSON format without any explanations: 'block 1': 'start': ", 'end': ", 'block type': ", ...

A.2.1 Training Template

As shown in Table 6 and Table 7, we display the training template for long-thought LLM and short-thought LLM in multi-turn RL training process. In general, these training template guide two LLMs follow tailored style to collaboratively reasoning.

A.2.2 Automatic Long Chain-of-Thought Chunking

Table A2.2.2 shows the prompt template used for automatic long CoT chunking. We also provide a chunk example for a mathematical question "Given that $47^{-1} \equiv 51 \pmod{97}$, find $28^{-1} \pmod{97}$, as a residue modulo 97. (Give a number between 0 and 96, inclusive.)". As can be seen the Table A2.2.3, we will first split Long CoT into multiple steps by '\n\n', and then we explicitly prompt LLM the chunk long CoT into multiple thoughts. In general, the chunked thought represent the key logical block in the overall long CoT reasoing process.

A.2.3 Thought Completion

As shown in Table A2.2.4, we present the prompt template used for thought completion, where a sequence of thoughts is completed based on the given thought type. The illustrative example in Table A2.2.5 demonstrates that, during an incomplete solution process, we provide the corresponding thought types for the reasoning steps that need to be completed. Thought chunks that already include the reasoning process are regarded as long-thoughts, as previously discussed. We can see that, after thought completion the solution process will be merged by original long thought and completed short thought. These data will be further used for SFT dataset construction.

A.3 Quality Analysis of Automatic Long Chain-of-Thought Chunking

To assess the reliability of our automatic long Chain-of-Thought (CoT) chunking method, we conduct a quantitative evaluation along two complementary dimensions: (1) rule-based validation of structural and indexing correctness, and (2) LLM-as-Judge assessment of semantic faithfulness to the original reasoning. We report results on the Math500 dataset.

Rule-based Evaluation. We validate the generated chunks against a prescribed JSON schema of the form `{"block 1": {"start": "0", "end": "5", "block type": "Question understanding"}, . . . }`. We measure: (i) **Format Error**, which flags any deviation from the

Table 6: Training template for long thought reasoning model.

A conversation between the User and two Assistants. The User asks a question, and two Assistants collaborate to solve it. The first assistant tackles the hard steps, carefully thinks about the reasoning process in the mind, and then provides the reasoning process. The second assistant follows the provided reasoning process to complete the remaining straightforward steps to arrive at the final answer.

Two assistants switch roles to solve the question. The first assistant uses `<think>` to start its thought, and uses `</think>` to stop the thinking process. The second assistant user `<answer>` to complete the remaining steps, and use `</answer>` to stop the solving process. But if the second assistant finds the reasoning insufficient or encounters an error, they use `</rethink>` to request the first assistant to generate thoughts again.

The process is enclosed within `<think>`...`</think>`, `<answer>`...`</rethink>` and `<answer>`...`</answer>` tags, respectively, e.g., `<think>` the first assistant's reasoning process here `</think>` `<answer>` the second assistant's answer here `</rethink>` `<think>` the first assistant's reasoning process here `</think>` `<answer>` the second assistant's answer here `</answer>`.

You are the first assistant, you return reasoning process starts from `<think>`, and ends with `</think>`.

Table 7: Training template for the short thought reasoning model.

A conversation between the User and two Assistants. The User asks a question, and two Assistants collaborate to solve it. The first assistant tackles the hard steps, carefully thinks about the reasoning process in the mind, and then provides the reasoning process. The second assistant follows the provided reasoning process to complete the remaining straightforward steps to arrive at the final answer.

Two assistants switch roles to solve the question. The first assistant uses `<think>` to start its thought, and uses `</think>` to stop the thinking process. The second assistant user `<answer>` to complete the remaining steps, and use `</answer>` to stop the solving process. But if the second assistant finds the reasoning insufficient or encounters an error, they use `</rethink>` to request the first assistant to generate thoughts again.

The process is enclosed within `<think>`...`</think>`, `<answer>`...`</rethink>` and `<answer>`...`</answer>` tags, respectively, e.g., `<think>` the first assistant's reasoning process here `</think>` `<answer>` the second assistant's answer here `</rethink>` `<think>` the first assistant's reasoning process here `</think>` `<answer>` the second assistant's answer here `</answer>`.

You are the second assistant, you return completed remaining steps: (1) start from `<answer>`, and end with `</rethink>`, or (2) start from `<answer>`, and end with `</answer>`.

Table 8: Quality analysis of automatic long CoT chunking on Math500.

Evaluation Method	Metric	Value
Rule-based	Format Error	8.4%
	Index Error	1.2%
LLM-as-Judge	Faithful (True)	89.8%
	Not Faithful (False)	0.6%

expected JSON structure; and (ii) **Index Error**, which flags overlapping or inconsistent step indices across blocks (e.g., block 1 ends at step 5 while block 2 starts at step 3).

LLM-as-Judge Evaluation. We employ GPT-4o to evaluate whether the chunked thoughts faithfully capture the key logic and reasoning steps of the original long CoT. The judge model is provided with both the original CoT and the chunked representation and prompted to decide whether the latter preserves the original reasoning process: (i) **Faithful**; (ii) **Not Faithful**.

Quality Analysis Table 8 summarizes the quantitative results. We observe that 8.4% of trajectories incur format errors, typically arising in exceedingly long CoTs that stress the output schema. Index errors are rarer (1.2%), indicating that our boundary detection is generally robust. According to the LLM-as-Judge, 89.8% of chunked outputs are judged *Faithful*, whereas only 0.6% are judged *Not Faithful*. The remaining cases are neutral or indeterminate under the judge's criteria. The rule-based errors suggest straightforward avenues for engineering improvements, such as stricter schema validation and adaptive truncation or pagination for extremely long CoTs. The low index error indicates that our automatic boundary detection is reliable in most cases.

A.4 Training Details of Long⊗Short

We report the details of the Long⊗Short training process, including dataset construction, resource and costs and the visualization of RL training process of Long⊗Short. We begin by the dataset statistics, and introduce the detailed information about cold-start stage and multi-turn RL training stage.

A.4.1 Dataset Statistics

We report the dataset statistic in cold start stage and multi-turn RL training stage.

Quantitative Analysis Stage. In the quantitative analysis stage, we utilize chunked thoughts derived from long chains of thought (CoTs), which are distilled using DeepSeek-R1-Distill-Qwen7B and DeepSeek-R1-Distill-Llama8B. To provide a broader understanding of the structure and scale of the chunked data, we report detailed statistics in Table 9, including the minimum, average, and maximum number of thoughts per CoT, as well as the corresponding statistics for thought lengths (measured by token count). In general, the number of thoughts per CoT ranges from 2 to over 200, with average values around 10–16 depending on the dataset and model. Similarly, the length of individual thoughts varies significantly, from short spans of fewer than 10 tokens to long segments exceeding 30,000 tokens, highlighting the diverse granularity and complexity of reasoning captured in our proposed chunking process.

Cold Start Stage. In the cold start stage, we use chunked thoughts obtained from 1.8K long CoTs extracted from the OpenMathInstruct dataset, as detailed in Section 5.1. Table 9 summarizes the key statistics of this chunked data, including the minimum, average, and maximum number of thoughts per CoT and the corresponding lengths of these thoughts. These statistics offer insight into the distribution and scale of reasoning units during the early stage, serving as a foundation for subsequent training or adaptation processes.

Multi-turn RL training Stage. For the multi-turn RL traing, we utilize MATH-ligtheval (Hendrycks et al., 2021b) (7.5K training samples and 5K validation samples in total) to conduct iterative self-evolution reinforcement learning training.

A.4.2 Resources and Costs in Training

Quantitative Analysis Stage. To enable quantitative analysis of reasoning within long chains-of-thought (CoT), we perform 128 rollouts at each intermediate thought step. For the GPQA-Diamond dataset, this rollout process takes approximately 6 hours using 20 NVIDIA A100 GPUs. For the MATH 500 dataset, the same procedure requires around 10 hours on 20 NVIDIA A100 GPUs.

Cold Start Stage. In the SFT cold start stage, we first perform 8 rollouts at each thought step on 1.8K collected long CoTs using Qwen2.5-7B-Instruct, which takes roughly 10 hours on 40 NVIDIA A100 GPUs. Subsequently, we use Qwen2.5-72B-Instruct for thought completion as described in Section 4.1. This step takes approximately 2 hours on 40 NVIDIA A100 GPUs.

Multi-turn RL Training Stage. Each round of reinforcement learning (RL) training takes approx-

Table 9: Statistics of chunked long CoTs

Dataset	# num of thought			# length of thought		
	min	average	max	min	average	max
OpenMath-ThoughtChunk1.8K	2	15.93	211	8	799.3	25,188
Math-500-Thought-DeepSeek-R1-Distill-Qwen7B	2	10.67	133	13	929.26	17,597
GPQA-Dimaond-Thought-DeepSeek-R1-Distill-Qwen7B	4	14.95	132	9	1,484.60	36,842
Math-500-Thought-DeepSeek-R1-Distill-Llama8B	3	12.23	220	13	930.48	15,359
GPQA-Dimaond-Thought-DeepSeek-R1-Distill-Llama8B	4	16.12	130	15	1,630.85	22,751

Table 10: Runtime efficiency on Math500 with a single H800 GPU. We report average response length; average inference latency (s) and average tokens per seconds (Tokens/s).

Model	Average Response Length	Average Inference Latency (s)	Tokens/s
DeepSeek-R1-Distill-Qwen-7B	10,774	30.28	355.81
Base (Qwen2.5-7B)	1,446	4.06	356.16
Long⊗Short-Qwen2.5-7B	1,713	4.98	343.97
DeepSeek-R1-Distill-Llama-8B	12,275	34.32	357.66
Base (Llama3.1-8B)	3,631	10.12	358.70
Long⊗Short-Llama-8B	3,663	10.70	342.36

imately 24 hours on 8 NVIDIA A100 GPUs.

A.5 Inference Efficiency Analysis of Long⊗Short

A key practical consideration for collaborative inference is runtime efficiency when switching between two LLMs during generation. Since modern deployments commonly leverage key–value (KV) caching for speed, maintaining two separate caches and recomputing them at switch points may introduce overhead. To quantify this effect, we report detailed throughput metrics, including average response length, average end-to-end inference latency, and decoding throughput (tokens per second), under a standardized setup.

Setup. We evaluate all 7B/8B models on a single H800 GPU and collect statistics on the Math500 dataset. For each system, we record: (i) average response length (generated tokens), (ii) average inference latency (seconds) measured end-to-end per instance, and (iii) decoding throughput (tokens/s). We compare the proposed Long⊗Short framework against its corresponding base model, as well as strong distillation-based reasoning models of comparable size.

Findings. As reported in Table 10, we observe a small reduction in decoding throughput when employing Long⊗Short, attributable to maintaining two KV caches and recomputing them at switch boundaries. Relative to the base models, throughput decreases by $\sim$13 tokens/s for Qwen2.5-7B ($356.16 \rightarrow 343.97$) and $\sim$16 tokens/s for Llama-

8B ($358.70 \rightarrow 342.36$). Despite this overhead, end-to-end latency remains close to the corresponding base models: 4.06 s vs. 4.98 s for Qwen2.5-7B, and 10.12 s vs. 10.70 s for Llama-8B. Crucially, Long⊗Short delivers substantially lower latency than distillation-based reasoning LLMs of similar size (e.g., 30.28 s $\rightarrow 4.98$ s for Qwen-7B, and 34.32 s $\rightarrow 10.70$ s for Llama-8B) while achieving comparable accuracy.

Implications and trade-offs. These results clarify the practical trade-off introduced by collaborative inference: minor decoding slowdowns from dual-cache management versus significant latency reductions relative to distilled long-reasoning models. In typical deployments where end-to-end latency dominates user experience and cost, Long⊗Short offers a favorable balance—retaining base-model responsiveness with only a small throughput penalty. Future work may further mitigate switching overhead via shared-cache layouts, cross-model KV projection, or adaptive batching that aligns switch points across requests.

A.6 Baseline Comparison of Long⊗Short

A.6.1 Comparison with Existing Efficient Reasoning Baselines

We also present a comprehensive comparison between our proposed method and existing chain-of-thought long-to-short approaches. Specifically, we categorize the baseline approaches into the following groups:

Table 11: Comparison of Long⊗Short with existing efficient reasoning approaches on Llama3.1-8B. We selected the average accuracy and length of DeepSeek-R1-Distill-Llama8B as our baseline for AES metric calculation.

Methods		MATH 500 Pass@1 ↑	AMIE 2024 Pass@1 ↑	AMIE 2025 Pass@1 ↑	GPQA Diamond Pass@1 ↑	AMC 2023 Pass@1 ↑	Avg. Length ↓	Avg. AES ↑
DeepSeek-R1-Distill-Llama-8B		**87.20**	**43.33**	30.00	**49.49**	**90.00**	28,496	0
Base (Llama3.1-8B)		62.80	10.00	6.67	35.86	22.50	3,713	-1.83
Training-free	CoD	85.00	43.33	23.33	48.99	87.50	13,897	0.40
	TALE-EP	79.20	40.00	30.00	41.11	82.50	18,830	-0.11
SFT-based	C3oT	40.20	30.00	3.33	41.41	22.50	10,014	-2.06
	DAST	78.50	26.67	13.33	40.40	78.50	13,443	-0.52
	O1-Pruner	82.50	30.00	23.33	42.93	78.50	14,486	-0.22
RL-based	SimplePO-DAST	82.05	26.67	23.33	37.37	82.50	16,285	-0.37
	Kimi k1.5	76.50	13.33	3.33	30.30	72.50	13,684	-1.21
Long⊗Short-Llama3.1-8B		86.20	40.00	**33.33**	46.96	87.50	**2,402**	**0.81**

- **Training-free methods**: These rely on prompt engineering or inference-time techniques without any parameter updates. We select CoD (Xu et al., 2025) and TALE-EP (Han et al., 2024) as our baselines.

- **SFT-based methods**: These utilize supervised fine-tuning on curated datasets to learn reasoning patterns. We select C3oT (Kang et al., 2025), DAST (Shen et al., 2025a) and O1-Pruner (Luo et al., 2025) as our baselines.

- **RL-based methods**: These leverage reinforcement learning, typically with reward signals derived from task-specific objectives or human feedback, to optimize reasoning performance. We select SimplePO-DAST (Shen et al., 2025a), and Kimi k1.5 (Team et al., 2025) as our baselines.

As shown in Table 3 and Table 11, our method achieves consistent improvements in both reasoning accuracy and efficiency across multiple benchmarks and model backbones. *(1) On the Qwen2.5-7B backbone*, our method outperforms most baselines in terms of average accuracy while significantly reducing the average output length (2,113 tokens vs. 13K–17K for most baselines). Notably, our approach achieves a superior AES score of **+0.61**, indicating that it not only maintains high reasoning performance but also generates more concise outputs compared to the AES baseline (DeepSeek-R1-Distill-Qwen7B). While some training-free and RL-based methods perform competitively on certain benchmarks, they often incur substantial output length and latency overheads. *(2) On the Llama3.1-8B backbone*, our method

again demonstrates strong performance, achieving the highest accuracy on the AMIE 2025 benchmark (33.33%) and the second-best performance on MATH500 (86.20%), while maintaining the lowest average output length (2,402 tokens). Compared to the AES baseline (DeepSeek-R1-Distill-Llama8B), our method yields a notable AES improvement of **+0.81**.

A.6.2 Comparison with Existing Reasoning LLMs

In addition, we compare our proposed models, Long⊗Short-Qwen2.5-7B and Long⊗Short-Llama3.1-8B, with both reasoning and non-reasoning models to comprehensively evaluate their effectiveness and efficiency on reasoning tasks. We also compare our method with recently introduced hybrid-thinking-mode LLMs (e.g., Qwen3 (Team, 2025)). We categorize the baseline LLMs as follows:

- **Non-reasoning models**: These models aim to solve problems quickly without engaging in explicit reasoning. While they offer high speed, the absence of step-by-step reasoning may result in incomplete or less accurate outputs. We select advanced models such as GPT-4-o (OpenAI, 2024), DeepSeek-V3-671B (Guo et al., 2025), Qwen2.5-7B, and Llama3.1-8B as representative examples.

- **Reasoning models**: These models employ extended chain-of-thought capabilities to perform multi-step reasoning across tasks. Although generally more effective, they tend to produce overly lengthy reasoning traces, which can affect efficiency. We include

OpenAI-o1 (OpenAI, 2024), DeepSeek-R1 (Guo et al., 2025), QwQ (Yang et al., 2024), DeepSeek-R1-Distill-Qwen-7B, and DeepSeek-R1-Distill-Llama-8B as representative models.

- **Hybrid reasoning models**: These models are capable of switching between reasoning and non-reasoning modes, allowing for more flexible inference. We choose Qwen3-8B (Team, 2025), Qwen3-32B and gpt-oss-20B (OpenAI, 2025) with low, medium and high reasoning efforts as our comparison models.

As can be seen in Table 12, Long⊗Short demonstrates three key advantages: *(1) Compared with non-reasoning models*, Long⊗Short significantly improves performance across all benchmarks while maintaining similar response lengths. For instance, Long⊗Short-Llama3.1-8B achieves an average of over 20-point gain in most tasks compared to its base Llama3.1-8B with even shorter output length (2,402 vs. 3,713 tokens). *(2) Compared with reasoning models*, except for DeepSeek-R1, Long⊗Short achieves comparable or better performance while dramatically reducing token usage—compressing the average output length by more than 80% (e.g., from 24k–28k tokens down to 2k tokens), thus offering a more efficient solution for reasoning-intensive tasks. *(3) Compared with hybrid models*, Long⊗Short consistently matches or surpasses their performance, while generating significantly shorter responses. For example, Long⊗Short-Qwen2.5-7B achieves 90.00 on AMC 2023, outperforming Qwen3-8B-nothinking (60.00) and closely matching Qwen3-32B-thinking (92.50), with less token length than Qwen3-8B-nothinking.

Furthermore, our method achieves the highest average Pass@1 among all non-reasoning models of similar size, surpassing GPT-4-o, Qwen2.5-7B, Llama3.1-8B, Qwen3-8B-nothinking, and even Qwen3-32B-nothinking. The only exception is DeepSeek-V3-671B, which is more than $80\times$ larger than our models. This highlights the strong trade-off between efficiency and performance achieved by Long⊗Short.

A.7 Hyperparameter Sensitivity Analysis of Long⊗Short

We analyze the sensitivity of Long⊗Short to key hyperparameters used in the SFT cold-start data construction and the subsequent RL stage.

Rollout sample size (n). As theoretically justified in Eq. (5), the estimation accuracy of the joint measurement depends on the rollout sample size n. Increasing n reduces the estimation error ε but raises computational cost. To quantify the trade-off, we construct SFT cold-start datasets with $n \in 1, \ldots, 8$ and report Math500 performance of Qwen2.5-7B-Cold-Start. As reported in Table 13, accuracy improvements plateau after $n=4$–5, whereas computation grows near-linearly. We therefore select $n=5$ as a cost-effective operating point used in all main experiments. While larger n yields marginal gains, we consider adaptive sampling strategies that allocate larger n only to ambiguous instances an interesting direction for future work.

RL reward weights (η, λ, μ). We ablate the weights governing correctness (η), structured-format adherence (λ), and response-length penalty (μ). Our default curriculum keeps the policy focused on correctness while first stabilizing formatting and later compressing length: (i) set $\eta=1.0$ throughout to prioritize accuracy; (ii) set $\lambda=1.0$ for the first 1–2 RL rounds to enforce the structured reasoning format; once format following exceeds ~90(iii) start with $\mu=0$ to permit broad exploration of reasoning strategies, then increase up to 0.5 in later rounds to shorten responses without harming accuracy. We summarize the effects as follows. (1) Correctness weight η: Lowering η from 1.0 to 0.5 substantially degrades accuracy, indicating that correctness must remain the dominant optimization target. (2) Format weight λ: A high λ early stabilizes the structured format and improves overall performance; reducing it too early increases format inconsistency and harms accuracy. After convergence of formatting, a small λ prevents reward hacking. (3) Length penalty μ: Introducing μ too early shortens responses but hurts accuracy. Gradually increasing μ in later rounds compresses outputs while maintaining performance.

Takeaways. Rollout size n: choose $n\approx4$–5 for a strong cost–accuracy trade-off. Rewards: keep $\eta=1.0$; use a high-then-low λ to first enforce and then maintain formatting; introduce μ late to control verbosity without sacrificing accuracy. Future work: adaptive n per-instance and principled, possibly learned, schedules for (η, λ, μ) to enhance efficiency and generalization.

Table 12: Comparison with existing advanced LLMs. We bold the results of models with comparable size to highlight the advantages of our efficient inference model over similarly sized LLMs (e.g. Qwen3-8B).

Methods	MATH 500 Pass@1 ↑	AMIE 2024 Pass@1 ↑	AMIE 2025 Pass@1 ↑	GPQA Diamond Pass@1 ↑	AMC 2023 Pass@1 ↑	Avg. Length ↓	Average Pass@1 ↑
Non-reasoning model							
Llama3.1-8B	62.80	10.00	6.67	35.86	22.50	3,713	27.50
Qwen2.5-7B	74.80	16.67	7.25	37.88	42.50	1,623	35.82
DeepSeek-V3-671B	90.20	39.20	30.00	69.10	90.00	3,287	63.70
GPT-4-o	78.60	20.00	13.33	48.48	50.00	2,840	42.08
Reasoning model							
DeepSeek-R1-Distill-Llama-8B	87.20	43.33	30.00	49.49	90.00	28,496	60.00
DeepSeek-R1-Distill-Qwen-7B	93.40	53.33	36.67	48.98	**95.00**	24,566	65.48
QwQ	94.40	46.67	60.00	46.67	85.00	19,504	66.55
DeepSeek-R1	**95.30**	**69.80**	**70.37**	71.50	**95.00**	26,874	80.39
OpenAI-o1	92.00	50.00	40.00	**72.73**	82.50	-	67.45
Hybrid reasoning model							
Qwen3-8B-thinking	88.20	53.33	50.00	58.08	77.50	21,158	65.42
Qwen3-32B-thinking	94.40	66.67	53.33	63.64	92.50	18,607	74.11
gpt-oss-20B-low	86.60	33.33	10.00	44.94	62.00	5,158	47.37
gpt-oss-20B-medium	85.20	30.00	16.67	48.48	72.50	6,026	50.57
gpt-oss-20B-high	92.20	36.67	46.00	56.56	88.50	14,026	63.99
Qwen3-8B-nothinking	81.60	36.67	20.00	53.03	60.00	5,580	50.26
Qwen3-32B-nothinking	85.40	36.67	20.00	61.62	77.50	4,301	56.24
Long⊗Short-Llama3.1-8B	86.20	40.00	33.33	46.96	87.50	2,402	58.80
Long⊗Short-Qwen2.5-7B	89.80	46.67	33.33	47.97	90.00	2,113	61.55

Table 13: Hyperparameters analysis on rollout sample size (n).

n	1	2	3	4	5	6	7	8
Accuracy (%)	75.26	77.82	77.50	79.24	80.40	80.94	81.02	81.24
Cost (GPU hours)	0.93	2.18	3.14	4.07	5.12	7.48	8.52	10.24

A.8 Case Studies of Long⊗Short

To gain deeper insights into Long⊗Short, we conduct a case study using Long⊗Short-Qwen2.5-7B, comparing its behavior with DeepSeek-R1. We also provide a breakdown of the number of dialog turns involved in this multi-turn collaborative reasoning process. Finally, we analyze the emergence of the "aha" moment phenomenon during the model evolution process.

A.8.1 Comparison Between Long⊗Short and R1

An illustrative example of how Long⊗Short reasoning works is presented. As can be seen, Long⊗Short produces significantly more concise and focused reasoning traces compared to DeepSeek-R1. While R1 generates a long chain of self-reflections—some of which are tangential or redundant—Long⊗Short delivers a more structured and efficient explanation. Moreover, both models ultimately arrive at the correct answer, but their reasoning styles differ: R1 mimics internal dialogue and uncertainty resolution,

whereas Long⊗Short is more deterministic and goal-oriented. This illustrates that Long⊗Short can retain reasoning effectiveness while reducing verbosity, suggesting a better alignment with user expectations in scenarios requiring clarity and precision.

A.8.2 Thought Length and Dialog Turn Anaylsis of Long⊗Short

Table 14 presents a quantitative analysis of the dialog turns and reasoning length under the Long⊗Short paradigm across various math and QA datasets.

Across both Qwen2.5-7B and Llama3.1-8B backbones, we observe that Long⊗Short typically completes reasoning within 2–3 turns, indicating a stable and efficient interaction pattern.

Interestingly, the average length gap between long-thought and short-thought responses suggests the paradigm's ability to modulate verbosity depending on the reasoning role: long-thoughts provide comprehensive problem-solving steps, while short-thoughts summarize or validate the solution.

Table 14: Detailed statistics of Long⊗Short thought reasoning paradigm.

Dataset	# num of turn			# average length of thought	
	min	average	max	long-thought	short-thought
Long⊗Short-Qwen2.5-7B					
Math 500	1	2.16	4	799	498
AIME 2024	1	2.47	5	1,473	653
AIME 2025	1	2.17	3	1,211	620
GPQA Diamond	1	2.13	3	1,425	859
AMC 2023	1	2.17	3	991	544
Long⊗Short-Llama3.1-8B					
Math 500	1	2.17	4	1,350	906
AIME 2024	1	2.25	4	1,340	1,224
AIME 2025	1	2.38	4	1,453	966
GPQA Diamond	1	2.11	3	1,407	859
AMC 2023	1	2.38	4	1,032	937

This supports the effectiveness of the Long⊗Short design in encouraging role-specialized reasoning styles.

A.9 Oha Moment of 'Overthinking' and 'Rethinking'

Another phenomenon is the aha moment of 'Overthinking' and 'Rethinking' emerged in RL training process. Although recent works (Yang et al., 2025b; Liu et al., 2025) reveal that even base model exhibit aha moment, we find that RL can cause the aha moment to occur frequently, accompanied by a reduction in the response length. As shown in the figure, we analyze the emergence of oha moments—self-reflective expressions such as 'Maybe I'm overthinking this' or 'Let me double-check'—across different training stages and datasets shown in the case study.

We summarize three key findings: *(1) Initial SFT Models Rarely Exhibit Oha Moments* In the early stage of training (i.e., SFT-only models, e.g., Long-r0⊗Short-r0 w/SFT), the frequency of oha moments is extremely low, often below 5% across all datasets. This indicates that SFT stage alone can only make LLM to learn the basic reasoning style, but the potential reasoning activity is still underactivated. *(2) Reinforcement Learning Significantly Enhances Oha Moment Emergence.* As the models undergo asynchronous multi-turn reinforcement learning, the frequency of oha moments steadily increases. For example, Long⊗Short-Llama3.1-8B reaches over 40% on AMIE 2024 and 2025 datasets by Round 3 and 4. This suggests that RL not only improves task performance but also encourages the model to engage in more reflective reasoning activity in such collaborative reasoning paradigm. *(3)*

Task Difficulty Correlates with Oha Moment Frequency. We observe that oha moments are more frequent in datasets with higher complexity, such as AMIE 2024/2025 and GPQA Diamond. On these challenging benchmarks, oha moments appear in up to 40–43% of the model responses in later training rounds. In contrast, simpler datasets such as MATH500 show more modest increases, rarely exceeding 20%. This suggests that oha moments are not uniformly distributed but instead tend to occur when the model faces harder reasoning tasks, indicating that oha moments may serve as a proxy for perceived uncertainty or internal conflict during the long⊗short thought reasoning.

In summary, the progressive rise of oha moments through RL training—particularly on complex datasets—highlights the potential of collaborative and hybrid reasoning paradigm. These findings also suggest a promising direction for developing hybrid reasoning.

Table 15: The comparison of Long⊗Short across asynchronous evolution rounds reveals an increasing percentage (100%) of oha moments generated by the model.

Round#	MATH 500	AMIE 2024	AMIE 2025	GPQA Diamond	AMC 2023
Long⊗Short-Qwen2.5-7B					
Long-r0⊗Short-r0 w/SFT	3.33	6.67	3.33	1.20	2.25
Long-r1⊗Short-r0	6.67	13.33	6.67	3.33	5.23
Long-r2⊗Short-r0	15.64	36.67	16.67	9.53	15.53
Long-r2⊗Short-r1	16.67	33.33	11.53	7.65	22.50
Long-r3⊗Short-r1	16.50	40.33	10.54	12.50	25.25
Long-r3⊗Short-r2	14.50	42.33	16.67	14.26	24.47
Long-r4⊗Short-r2	16.60	40.00	20.00	12.62	25.00
Long⊗Short-Llama3.1-8B					
Long-r0⊗Short-r0 w/SFT	3.35	0	0	1.25	0
Long-r1⊗Short-r0	3.35	13.35	15.57	6.67	10.25
Long-r2⊗Short-r0	9.76	37.54	28.50	16.67	25.50
Long-r2⊗Short-r1	16.67	42.50	30.00	17.50	33.33
Long-r3⊗Short-r1	15.20	40.00	31.50	21.55	34.50
Long-r3⊗Short-r2	12.50	42.50	30.00	21.00	35.55
Long-r4⊗Short-r2	14.20	43.33	33.33	22.73	37.50

Problem:
Given that $47^{-1} \equiv 51 \pmod{97}$, find $28^{-1} \pmod{97}$, as a residue modulo 97. (Give a number between 0 and 96, inclusive.)

Solution:
Step 0: So I have this problem here: given that $47^{-1} \equiv 51 \pmod{97}$, I need to find $28^{-1} \pmod{97}$, and it should be a number between 0 and 96, inclusive. Alright, let's see how to approach this.

Step 1: First off, $47^{-1} \pmod{97}$ means the multiplicative inverse of 47 modulo 97, which is a number that, when multiplied by 47, gives a result that's congruent to 1 modulo 97. They've already told me that $47^{-1} \equiv 51 \pmod{97}$, so that's a starting point.

Step 2: Now, I need to find the inverse of 28 modulo 97. That is, find a number x such that $28x \equiv 1 \pmod{97}$. I wonder if there's a way to relate this to the inverse of 47 that's already given.

Step 3: One thing I remember is that in modular arithmetic, if you have inverses of certain numbers, you might be able to combine them in useful ways. Maybe I can express 28 in terms of 47 or something related.

Step 4: Let me think about the relationship between 28 and 47 modulo 97. If I can find some expression that relates them, I might be able to use the known inverse of 47 to find the inverse of 28.

Step 5: Hmm, perhaps I can find a multiple of 47 that is congruent to 28 modulo 97. That is, find some integer k such that $47k \equiv 28 \pmod{97}$. If I can find such a k, then maybe I can manipulate that equation to find the inverse of 28.

Step 6: Let's try to solve $47k \equiv 28 \pmod{97}$. Since I know that $47^{-1} \equiv 51 \pmod{97}$, I can multiply both sides of the equation by 51 to solve for k:

Step 7: $k \equiv 28 \times 51 \pmod{97}$

Step 8: Let me calculate 28×51:

Step 9: $28 \times 50 = 1400$

Step 10: $28 \times 1 = 28$

Step 11: So, $1400 + 28 = 1428$

Step 12: Now, compute $1428 \pmod{97}$. To find this, I'll divide 1428 by 97 and find the remainder.

Step 13: First, $97 \times 10 = 970$, and $97 \times 4 = 388$, so total $970 + 388 = 1358$.

Step 14: Subtracting: $1428 - 1358 = 70$

Step 15: So, $1428 \equiv 70 \pmod{97}$, which means $k \equiv 70 \pmod{97}$.

. . .

Step 144: So, my final answer is that $28^{-1} \equiv 52 \pmod{97}$.

Step 145: Final answer: $\boxed{52}$

Chunked Thought:
{ "block 1": {"start": 0, "end": 5, "block type": "Question understanding"}, "block 2": {"start": 6, "end": 15, "block type": "Preliminary attempt"}, "block 3": {"start": 16, "end": 25, "block type": "Verify preliminary attempt"}, "block 4": {"start": 26, "end": 49, "block type": "Solve using extended Euclidean algorithm"}, "block 5": {"start": 50, "end": 69, "block type": "Try to solve using known inverse"}, "block 6": {"start": 70, "end": 81, "block type": "Verify answer"}, "block 7": {"start": 82, "end": 142, "block type": "Further attempts and verification"}, "block 8": {"start": 143, "end": 145, "block type": "Final conclusion"} }

A2.2.4 Prompt for Thought Completion

Given a problem and its corresponding partially completed solution process, please complete the missing parts of the solution based on the specified thought identifiers. Return only the completed results in JSON format. Do not return the steps that have already been provided.

Problem:
{Problem}

Incompleted solution process:
{Incompleted solution process}

The parts you need to complete are the content fields corresponding to the following thoughts:
{Incompleted thought}

Note that the thought numbers are already specified—you must not split or modify them. Please strictly return the completions according to the given numbering, even if the required content for a single thought involves multiple steps.

You must return your answer in the following JSON format, and do not provide any explanation or content for other thoughts: {"Completed Steps": [{"thought": "string", "content": "string"}]}

Problem:
Given that the arithmetic mean of two positive numbers a and b is 4, then the maximum value of the geometric mean of a and b is () A: 2 B: 4 C: 8 D: 16

Incompleted solution process:
{ "chunk 1": "Ok, so I have a question. This question is about the arithmetic mean and geometric mean. The question says that the arithmetic mean of two positive numbers a and b is 4. We need to find the maximum of their geometric means. The options are a:2, b:4, c:8, d:16.First, I have to recall the definitions of the arithmetic mean and geometric mean. The arithmetic mean is (a + b)/2, and the geometric mean is $\sqrt{ab}$. The question says $(a + b)/2 = 4$, so we can conclude that a + b = 8.", "chunk 2": "Problem decomposition and preliminary solution", "chunk 3": "Wait, wait, I am a little confused, because there are larger numbers in the options, such as 8 and 16. Will there be a larger geometric mean? However, according to the inequality, the arithmetic mean is greater than or equal to the geometric mean, and only when $a = b$, the geometric mean is equal to the arithmetic mean. If a and b are not equal, the geometric mean will be less than the arithmetic mean. Assume that $a \neq b$, for example, $a = 5$, $b = 3$, then $a + b = 8$, the geometric mean is $\sqrt{15} \approx 3.87$, which is indeed less than 4. For another example, if $a = 6$, $b = 2$, the geometric mean is $\sqrt{12} \approx 3.46$, which is still less than 4. It seems that the maximum value of the geometric mean is indeed 4. ", "chunk 4": "Further verification", "chunk 5": "Conclusion" }

The parts you need to complete are the content fields corresponding to the following thoughts:
{"Problem decomposition and preliminary solution", "Further verification", "Conclusion"}

Completed thoughts:
{ "Completed Steps": [{ "thought": "Problem Analysis and Preliminary Solution", "content": "According to the property that the arithmetic mean is greater than or equal to the geometric mean, the geometric mean is equal to the arithmetic mean only when a = b. The condition given in the question is (a + b)/2 = 4, so a + b = 8. If a = b, then a = b = 4, and the geometric mean $\sqrt{ab} = \sqrt{44}$ = 4." }, { "thought": "Further Verification", "content": "Verify whether the geometric mean can be greater than 4 when $a \neq b$. Assuming $a > b$, and given that $a + b = 8$, we can set $a = 8 - b$. Then the geometric mean is $\sqrt{ab} = \sqrt{b(8 - b)}$. Since $b(8 - b)$ is a quadratic function that opens downward, its maximum value occurs when $b = 4$, that is, $a = b = 4$, and the geometric mean is 4. When $b \neq 4$, $b(8 - b)$ will be less than 16, and the geometric mean will also be less than 4. Therefore, the maximum value of the geometric mean is 4." }, { "thought": "Conclusion", "content": "According to the above analysis, the maximum value of the geometric mean is 4, and it can only be achieved when a = b = 4. Therefore, the correct answer is B: 4. " }] }

A.8.1 Case Study 1

Problem: 1+1=?

DeepSeek-R1:
<think>Okay, so the user is asking what 1 plus 1 equals. Let me think. Well, in basic arithmetic, when you add two numbers together, you're combining their values. So if I have one apple and someone gives me another apple, I have two apples. That makes sense. But wait, could there be any other interpretations here? Sometimes people use 1+1 in different contexts, like binary. In binary, 1 plus 1 would be 10, right? But the question doesn't specify the number system. Since it's a simple question without any context, probably the answer is expecting the standard base 10 result. So 1 + 1 should equal 2. But maybe I should double-check. Let me count on my fingers. One finger up, then add another finger. That's two fingers. Yep, that's right. So unless there's some trick or alternative meaning intended, the answer is 2.</think>
<answer>The result of 1 + 1 is **2**. This is a fundamental arithmetic operation in the base-10 number system. If you encounter this in a different context (e.g., binary, modular arithmetic, or symbolic logic), the answer might vary, but in standard mathematics, the answer is **2**.</answer>

Long⊗Short:
<think> Alright, so i've got this problem here: 1+1=? </think> <answer> The problem you've presented is a simple addition problem. When you add 1 and 1 together, the result is 2. So, the answer is 2. </answer>

A.9 Case Study 2

Problem: Consider a rhombohedral crystal, with the interatomic distance of 10 Angstrom and the angles $\alpha = \beta = \gamma = 30^0$. What is the interplanar distance of the (111) plane of the crystal?

Long⊗Short:
<think> Alright, I've got this problem about a rhombohedral crystal. So, a rhombohedron is a type of prism where all six faces are rhombuses, and in this case, the interatomic distance is 10 Angstrom, and all the angles α, β, and γ are 30 degrees. I need to find the interplanar distance of the (111) plane in this crystal. First, I should recall what interplanar distance means. It's the distance between two parallel planes in a crystal lattice. In this case, I'm looking at the (111) plane, which is a specific plane in the rhombohedral lattice. </think> <answer> The interplanar distance in a rhombohedral crystal can be calculated using the formula for the interplanar distance in a lattice, which is

$$d_{hkl} = \frac{a}{\sqrt{h^2 + k^2 + l^2 - 2\cos(\alpha)hk - 2\cos(\beta)kl - 2\cos(\gamma)lh}},$$

where a is the lattice constant (10 Angstrom in this case), and h, k, l are the Miller indices of the plane (111 in this case). The angles α, β, γ are all 30 degrees. Plugging in the values, we get ... However, this does not match any of the given options. I will recheck the calculation. </rethink> <think> Maybe I need to consider the lattice constant differently. Maybe a is not just the interatomic distance, but something else. I need to understand the structure of the rhombohedral lattice. A rhombohedron can be thought of as a cube that's stretched along one axis. In this case, all angles are 30 degrees, which is different from a cube where angles are 90 degrees.... After some calculation, I find that the distance between adjacent atoms along a lattice vector in a rhombohedral lattice with angle 30 degrees is ...This seems incorrect because distance can't be negative. I need to check my signs. After correcting the signs, ... This is close to one of the options, but not exact. I need to verify the calculation. Wait, maybe I'm overthinking on this, the interplanar distance of the (111) plane is 9.54 Angstrom. </think> <answer> After rechecking the calculation, the correct value for the interplanar distance of the (111) plane in the rhombohedral crystal is approximately 9.54 Angstrom. This matches the candidate answer (1) 9.54 Angstrom. Therefore, the interplanar distance of the (111) plane is 9.54 Angstrom. </answer>