Smoothed Embeddings for Certified Few-Shot Learning

Abstract

Randomized smoothing is considered to be the state-of-the-art provable defense against adversarial perturbations. However, it heavily exploits the fact that classifiers map input objects to class probabilities and do not focus on the ones that learn a metric space in which classification is performed by computing distances to embeddings of classes prototypes. In this work, we extend randomized smoothing to few-shot learning models that map inputs to normalized embeddings. We provide analysis of Lipschitz continuity of such models and derive robustness certificate against ℓ_2-bounded perturbations that may be useful in few-shot learning scenarios. Our theoretical results are confirmed by experiments on different datasets.

1 Introduction

In the regime of scarce data or when new classes emerge constantly, such as in face recognition, *few-shot learning* is required. Modern computer vision methods of learning from a few images are based on deep neural networks. These neural networks are intriguingly vulnerable to adversarial perturbations [40, 10] – accurately crafted small modifications of the input that may significantly alter the model's prediction. For safety-critical scenarios, these perturbations present a serious threat. Hence, it is important to investigate ways to protect neural networks from undesired scenarios.

Several works studied this phenomena in different applications of neural networks – image classification [2, 33, 32, 39], object detection [17, 26, 46, 48], face recognition [18, 5, 52], semantic segmentation [7, 12, 48]. This shows how easy for adversaries to maliciously force a model to behave in the desired way. As a result, defenses, both empirical [4, 53, 14] and provable [49, 21, 3, 45, 50, 15, 44, 34], were proposed recently. Although empirical ones can be (and often are) broken by more powerful attacks, the provable ones are of a big interest since they make it possible to provide *guarantees* of the correctness of the work of a model under certain assumptions, and, thus, possibly broaden the scope of tasks which may be trusted to the neural networks.

Randomized smoothing [21, 3, 25] is the state-of-the-art approach used for constructing classification models provably robust against small-norm additive adversarial perturbations. This approach is scalable to large datasets and can be applied to any classifier since it does not use any assumptions about model's architecture. Generally, the idea is following. Suppose, we are given a base neural network classier $f : \mathbb{R}^n \to [0,1]^K$ that maps an input image x to a fixed number of K class probabilities. Its smoothed version with the standard Gaussian distribution is:

$$g(x) = \mathop{\mathbb{E}}_{\varepsilon \sim \mathcal{N}(0,\Sigma)} f(x + \varepsilon). \tag{1}$$

Interestingly, as shown in [3], the new (smoothed) classifier is provably robust at x to ℓ_2-bounded perturbations if the base classifier f is confident enough at x. However, the proof of certification

Figure 1: Illustration of certification pipeline for a single image x. Given a model $f(\cdot)$ and n realisations of zero-mean Gaussian noise $\varepsilon_1, \ldots, \varepsilon_n \sim \mathcal{N}(0, \sigma^2 I)$, an estimate $\hat{g}(x) = \frac{1}{n} \sum_{i=1}^{n} f(x + \varepsilon_i)$ of $g(x) = \mathbb{E}_{\varepsilon \sim \mathcal{N}(0, \sigma^2 I)} f(x + \varepsilon)$ is computed. Note that $g(x)$ is L-Lipschitz with $L = \sqrt{2/\pi\sigma^2}$, according to the Theorem 1. The number of samples n is increased until adversarial embedding risk γ from the Theorem 2 is computed with Algorithms 1-2 and certified radius $r = \frac{\gamma}{L}$ is determined. The model $g(\cdot)$ is treated as certified at x for all additive perturbations $\delta : \|\delta\|_2 < r$.

heavily exploits the fact that classifiers are restricted to map an input to a fixed number of class probabilities. Thus, directly applying randomized smoothing to classifiers in metric space, such as in few-shot learning, is a challenging task.

There are several works that aim at improving the robustness for few-shot classification [20, 9, 51, 28]. However, the focus in such works is either on the improvement of empirical robustness or probabilistic guarantees of certified robustness; none of them provide theoretical guarantees on the worst-case model behavior.

In this work, we fill this gap, by generalizing and theoretically justifying the idea of randomized smoothing to few-shot learning. In this scenario, provable certification needs to be obtained not in the space of output class probabilities, but in the space of descriptive embeddings. This work is the first, to our knowledge, where the theoretical robustness guarantees for few-shot scenario is provided.

Our contributions are summarized as follows:

- We provide the first theoretical robustness guarantee for few-shot learning classification.

- Analysis of Lipschitz continuity of such models and providing the robustness certificates against ℓ_2-bounded perturbations for few-shot learning scenarios.

- We propose to estimate confidence intervals not for distances between the approximation of smoothed embedding and class prototype but for the dot product of vectors which has expectation equal to the distance between actual smoothed embedding and class prototype.

2 Problem statement

2.1 Notation

We consider a few-shot classification problem where we are given a set of labeled objects $(x_1, y_1), \ldots, (x_m, y_m)$ where $x_i \in \mathbb{R}^n$ and $y_i \in \{1, \ldots, K\}$ are corresponding labels. We follow the notation from [38] and denote S_k as the set of objects of class k.

2.2 Few-shot learning classification

Suppose we have a function $f : \mathbb{R}^n \to \mathbb{R}^d$ that maps input objects to the space of normalized embeddings. Then, $d-$dimensional prototypes of classes are computed as follows (expression is given for the prototype of class k):

$$c_k = \frac{1}{|S_k|} \sum_{x \in S_k} f(x). \tag{2}$$

In order to classify a sample, one should compute the distances between its embedding and class prototypes – a sample is assigned to the class with the closest prototype. Namely, given a distance function $\rho : \mathbb{R}^d \times \mathbb{R}^d \to [0, +\infty)$, the class c of the sample x is computed as below:

$$c = \underset{k \in \{1,\ldots,K\}}{\arg\min} \rho\left(f(x), c_k\right). \tag{3}$$

Given an embedding function f, our goal is to construct a classifier g provably robust to additive perturbations Δ of a small norm. In other words, we want to find a norm threshold t such that equality

$$\underset{k \in \{1,\ldots,K\}}{\arg\min} \rho\left(g(x), c_k\right) = \underset{k \in \{1,\ldots,K\}}{\arg\min} \rho\left(g(x + \delta), c_k\right), \tag{4}$$

will be satisfied for all $\delta : \|\delta\|_2 \leq t$.

In this paper, the solution of a problem of constructing a classifier that satisfies the condition in (4) is approached by extending the analysis of the robustness of smoothed classifiers described in (1) to the case of vector functions. The choice of the distance metric in (4) is motivated by an analysis of Lipschitz-continuity given in the next section.

3 Randomized smoothing

3.1 Background

Randomized smoothing [21, 3] is described as a technique of convolving a base classifier f with an isotropic Gaussian noise such that the new classifier $g(x)$ returns the most probable prediction of f of a random variable $\xi \sim \mathcal{N}(x, \sigma^2 I)$, where the choice of Gaussian distribution is motivated by the restriction on g to be robust against additive perturbations of bounded norm. In this case, given a classifier $f : \mathbb{R}^n \to [0, 1]$ and smoothing distribution $\mathcal{N}(0, \sigma^2 I)$, the classifier g looks as follows:

$$g(x) = \frac{1}{(2\pi\sigma^2)^{\frac{n}{2}}} \int_{\mathbb{R}^n} f(x + \varepsilon) \exp\left(-\frac{\|\varepsilon\|_2^2}{2\sigma^2}\right) d\varepsilon. \tag{5}$$

One can show by Stein's Lemma that given the fact that the function f in (5) is bounded (namely, $\forall x \in D(f), |f(x)| \leq 1$), then the function g is $L-$Lipschitz:

$$\forall x, x' \in D(g), \ \|g(x) - g(x')\|_2 \leq L\|x - x'\|_2, \tag{6}$$

with $L = \sqrt{\frac{2}{\pi\sigma^2}}$, what immediately produce theoretical robustness guarantee on g.

Although this approach is simple and effective, it has a serious drawback: in practice, it is impossible to compute the expectation in (5) exactly and, thus, impossible to compute the prediction of the smoothed function g at any point. Instead the integral is computed with the use of Monte-Carlo approximation with n samples to obtain the prediction with an arbitrary level of confidence. Notably, to achieve an appropriate accuracy of the Monte-Carlo approximation, the number of samples n should be large enough that may dramatically affect inference time.

In this work, we generalize the analysis of Lipschitz-continuity to the case of vector functions $g : \mathbb{R}^n \to \mathbb{R}^d$ and provide robustness guarantees for classification performed in the space of embeddings. The certification pipeline is illustrated in the Figure 1.

3.2 Randomized smoothing for vector functions

Lipschitz-continuity of vector function. In the work of [37], the robustness guarantee from [3] is proved by estimating the Lipschitz constant of a smoothed classifier. Unfortunately, a straightforward generalization of this approach to the case of vector functions leads to the estimation of the expectation of the norm of a multivariate Gaussian which is known to depend on the number of dimensions of the space. Instead, we show that a simple adjustment to this technique may be done such that the estimate of the Lipschitz constant is the same as for the function in (5). Our results are formulated in the theorems below proofs of which are moved to the Appendix in order not to distract the reader.

97 **Theorem 1** *(Lipschitz-continuity of smoothed vector function) Suppose that $f : \mathbb{R}^n \to \mathbb{R}^d$ is a*
98 *deterministic function and $g(x) = \mathbb{E}_{\varepsilon \sim \mathcal{N}(0,\sigma^2 I)} f(x + \varepsilon)$ is continuously differentiable for all x. If*
99 *for all x, $\|f(x)\|_2 = 1$, then $g(x)$ is $L-$Lipschitz in l_2-norm with $L = \sqrt{\frac{2}{\pi\sigma^2}}$.*

100 **Remark 1** *We perform the analysis of Lipschitz-continuity in the Theorem 1 in l_2-norm, so the*
101 *distance metric in (4) is l_2-distance. We do not consider other norms in this paper.*

102 **Robust classification in the space of embeddings.** To provide certification for a classifica-
103 tion in the space of embeddings, one should estimate the maximum deviation of the classi-
104 fied embedding that does not change the closest class prototype. In the Theorem 2, we show
105 how this deviation is connected with the mutual arrangement of embedding and class prototype.
106

107 **Theorem 2** *(Adversarial embedding risk)*
108 *Given an input image $x \in \mathbb{R}^n$ and the em-*
109 *bedding $g : \mathbb{R}^n \to \mathbb{R}^d$ the closest point on to*
110 *decision boundary in the embedding space (see*
111 *Figure 2) is located at a distance (defined as*
112 *adversarial embedding risk):*

$$\gamma = \|\Delta\|_2 = \frac{\|c_2 - g(x)\|_2^2 - \|c_1 - g(x)\|_2^2}{2\|c_2 - c_1\|_2^2}, \tag{7}$$

113 *where $c_1 \in \mathbb{R}^d$ and $c_2 \in \mathbb{R}^d$ are the two closest*
114 *prototypes. The value of γ is the distance be-*
115 *tween classifying embedding and the decision*
116 *boundary between classes represented by c_1 and*
117 *c_2. Note that this is the minimum l_2-distortion*
118 *in the embedding space required to change the*
119 *prediction of g.*

Figure 2: Illustration of the Theorem 2, one-shot case. The direction of adversarial risk in the space of embeddings is always parallel to the vector $c_1 - c_2$. This is also true for the case of $\|c_1\|_2 \neq \|c_2\|_2$.

120 Two theorems combined result in an l_2-robustness guarantee for few-shot classification as:

121 **Theorem 3** *(Robustness guarantee) L_2-robustness guarantee r for an input image x in the*
122 *$n-$dimensional input metric space under classification by a classifier g from the Theorem 1 is*
123 *$r = \frac{\gamma}{L}$, where L is the Lipschitz constant from the Theorem 1 and γ is the adversarial risk from the*
124 *Theorem 2. The value of r is the certified radius of g at x, or, in other words, minimum l_2-distortion*
125 *in the input space required to change the prediction of g. The proof of this fact straightforwardly*
126 *follows from the definition (6) and results from Theorems 1-2.*

4 Certification protocol

128 Here, we describe the numerical implementation of our approach and estimate its failure probability.

4.1 Estimation of prediction of smoothed classifier

130 As mentioned previously, the procedure of few-shot classification is performed by assigning an object
131 x to the closest class prototype. Unfortunately, given the smoothed function g in the form from the
132 Theorem 1 and class prototype c_k from (2), it is impossible to compute the value $\rho(g(x), c_k)$ explicitly
133 as well as to determine the closest prototype, since it is in general unknown how does $g(x)$ look like.
134 We propose both to estimate the closest prototype for classification and to estimate the distance to
135 the closest decision boundary γ from Theorem 2 as the largest class-preserving perturbation in the
136 embedding space by computing two-sided confidence intervals for random variables

$$\xi_1 = \|\hat{g}(x) - c_1\|_2^2, \, \ldots, \, \xi_K = \|\hat{g}(x) - c_K\|_2^2, \tag{8}$$

137 where $\hat{g}(x) = \frac{1}{n} \sum_{i=1}^n f(x + \varepsilon_i)$ is the estimation of $g(x)$ computed as empirical mean by n samples
138 of noise, and one-sided confidence interval for γ from the Theorem 2, respectively. Pseudo-code for
139 both procedures is presented in Algorithms 1-2.

Algorithm 1 Closest prototype computation algorithm.
GIVEN: base classifier f, noise σ, object x, number of samples n for $\hat{g}(x)$, class prototypes $\{c_i\}_{i=1}^K$, maximum number of samples T and confidence level α,
RETURNS: index A of the closest prototype.

Function CLOSEST($f, \sigma, x, n, \{c_i\}_{i=1}^K, T, \alpha$)
$fs \leftarrow \emptyset$
$i \leftarrow 0$
$n_0 = n$
while $n \leq T$ **do**
   $\varepsilon_1, \dots, \varepsilon_n \sim \mathcal{N}(0, \sigma^2 I)$
   $\hat{g}(x) \leftarrow \frac{1}{n} \sum_{i=1}^n f(x + \varepsilon_i)$
   $fs \leftarrow fs \cup \hat{g}(x)$
   $CI \leftarrow \emptyset$
   for all $C \in \{c_i\}_{i=1}^K$ **do**
      $dsToC \leftarrow \rho(fs, C)$
      $(\alpha_C, \beta_C) \leftarrow$ TwoSidedConfInt($dsToC, \alpha$)
      $CI \leftarrow CI \cup (\alpha_C, \beta_C)$
   end for
   $A \leftarrow \arg\min \{\alpha_i\}_{i=1}^K$
   if $\beta_A < \min(\{\alpha_i\}_{i=1, i \neq A}^K)$ **then**
      Return A, fs
   else
      $n \leftarrow n + n_0$ {Increase number of samples used for computing an approximation $\hat{g}(x)$ until the number of observations is large enough to determine two leftmost intervals or until $n = T$}
   end if
end while
EndFunction

The Algorithm 1 describes an inference procedure for the smoothed classifier from the Theorem 1; the Algorithm 2 uses Algorithm 1 and, given input parameters, estimates an adversarial risk from the Theorem 2 – it determines two closest to smoothed embedding $g(x)$ prototypes A and B and produces the lower confidence bound for the distance between $g(x)$ and the decision boundary between A and B. Combined with analysis from the Theorem 1, it provides the certified radius for a sample – the smallest value of l_2-norm of perturbation in the input space required to change the prediction of the smoothed classifier.

In the next subsection, we discuss in detail the procedure of computing confidence intervals in Algorithms 1-2.

4.2 Applicability of algorithms

The computations of smoothed function and distances to class prototypes and decision boundary in Algorithms 1-2, respectively, are numerical and operate with estimations of a random variable, thus, it is necessary to analyze their applicability. In this section, we propose a way to compute confidence intervals for squares of the distances between estimates of embeddings in the form from of sample mean and class prototypes.

Computation of confidence intervals for the squares of distances. Recall that one way to estimate the value of a parameter of a random variable is to compute a confidence interval for the corresponding statistic. In this work, we construct intervals by applying well-known Hoeffding inequality [13] in the form

$$\mathbb{P}\left(|\overline{X} - \mathbb{E}(\overline{X})| \geq t\right) \leq 2\exp\left(-\frac{2t^2 n^2}{\sum_{i=1}^n (b_i - a_i)^2}\right), \tag{9}$$

where $\overline{X}$ and $\mathbb{E}(\overline{X})$ are sample mean and population mean of random variable X, respectively, n is the number of samples and numbers a_i, b_i are such that $\mathbb{P}(X_i \in (a_i, b_i)) = 1$.

Algorithm 2 Adversarial embedding risk computation algorithm.

GIVEN: base classifier f, noise σ, object x, number of samples n for $\hat{g}(x)$, class prototypes $\{c_i\}_{i=1}^K$, maximum number of samples T for $\hat{g}(x)$ and confidence level α

RETURNS: lower bound Γ for the adversarial risk γ.

Function EMBEDDING-RISK($f, \sigma, x, n, \{c_i\}_{i=1}^K, T, \alpha$)
$A,\ fs_A \leftarrow$ CLOSEST($f, \sigma, x, n, \{c_i\}_{i=1}^K, T, \alpha$)
$B,\ fs_B \leftarrow$ CLOSEST($f, \sigma, x, n, \{c_i\}_{i=1,i\neq A}^K, T, \alpha$)
$fs \leftarrow fs_A \cup fs_B$
$\gamma s \leftarrow \emptyset$
for all $f \in fs$ **do**
   $\gamma = \frac{\|c_B - g\|^2 - \|c_A - g\|^2}{2\|c_B - c_A\|^2}$
   $\gamma s \leftarrow \gamma s \cup \gamma$
end for
$\Gamma \leftarrow \texttt{LowerConfBound}(\gamma s, \alpha)$
Return Γ
EndFunction

However, a confidence interval for the distance $\|\hat{g}(x) - c_k\|_2$ with a certain confidence covers an *expectation of distance* $\mathbb{E}(\|\hat{g}(x) - c_k\|_2)$, not the *distance for expectation* $\|\mathbb{E}(\hat{g}(x) - c_k)\|_2 = \|g(x) - c_k\|_2$.

To solve this problem, we propose to compute confidence intervals for the dot product of vectors. Namely, given a quantity $\xi_{x,k} = \langle g_1(x) - c_k, g_2(x) - c_k \rangle$, we sample its unbiased estimate with at maximum $2n$ samples of noise (here we have to mention that the number of samples n from Algorithm 1 actually doubles since we need a pair of estimates $\hat{g}(x)$ of smoothed embeddings):

$$\hat{\xi}_{x,k} = \langle \frac{1}{n}\sum_{i=1}^{n} f(x + \varepsilon_i) - c_k, \frac{1}{n}\sum_{j=n+1}^{2n} f(x + \varepsilon_j) - c_k \rangle \tag{10}$$

and compute confidence interval $(\alpha_{x,k}, \beta_{x,k})$ such that given

$$\frac{\alpha}{3} = 2\exp\left(-\frac{2t^2 n^2}{\sum_{i=1}^{T}(b_i - a_i)^2}\right), \tag{11}$$

the population mean $\mathbb{E}(\hat{\xi}_{x,k})$ is most probably located within it, or, equivalently, $\mathbb{P}\left(\alpha_{x,k} \leq \mathbb{E}(\hat{\xi}_{x,k}) \leq \beta_{x,k}\right) \geq 1 - \alpha$. We have to mention that there are three confidence intervals for three terms (one with quadratic number of samples and two with the linear numbers of samples) in the expression (10), that is why there is fraction $\frac{1}{3}$ in the equation (11). Also note that the population mean $\mathbb{E}(\hat{\xi}_{x,k})$ is exactly $\|g(x) - c_k\|_2^2$, since

$$\mathbb{E}(\hat{\xi}_{x,k}) = \mathbb{E}\langle \frac{1}{n}\sum_{i=1}^{n} f(x + \varepsilon_i) - c_k, \frac{1}{n}\sum_{j=n+1}^{2n} f(x + \varepsilon_j) - c_k \rangle = \|g(x) - c_k\|_2^2 \tag{12}$$

since $f(x + \varepsilon_i)$ and $f(x + \varepsilon_j)$ are independent random variables for $i \neq j$. Finally, note that the confidence interval $(\alpha_{x,k}, \beta_{x,k})$ for the quantity $\|g(x) - c_k\|_2^2$ implies confidence interval

$$\left(\sqrt{\alpha_{x,k}}, \sqrt{\beta_{x,k}}\right) \tag{13}$$

for the quantity $\|g(x) - c_k\|_2$. Thus, the procedures $\texttt{TwoSidedConfInt}$ and $\texttt{LowerConfBound}$ from algorithms return an interval from (13) and its left bound for the random variable representing corresponding distance, respectively.

(a) Cub-200-2011   (b) CIFAR-FS   (c) *mini*ImageNet

Figure 3: Dependency of certified accuracy on attack radius ε for different values of σ, 1-shot case, $n = 1000$.

(a) Cub-200-2011   (b) CIFAR-FS   (c) *mini*ImageNet

Figure 4: Dependency of certified accuracy on attack radius ε for different values of σ, 5-shot case, $n = 1000$.

5 Experiments

5.1 Datasets

For the experimental evaluation of our approach we use several well-known datasets for few-shot learning classification. *Cub-200-2011* [43] is a dataset with $11,788$ images of 200 bird species, where 5864 images of 100 species are in the train subset and 5924 images of other 100 species are in the test subset. It is notable that a lot of species presented in dataset have degree of visual similarity, making classification of ones a challenging task even for humans. *mini*ImageNet [42] is a substet of images from *ILSVRC 2015* [36] dataset with 80 images categories in train subset and 20 categories in test subset with 600 images of size 84×84 in each category. *CIFAR FS* [1] is a subset of *CIFAR 100* [19] dataset which was generated in the same way as *mini*ImageNet and contains 37800 images of 64 categories in the train set and 11400 images of 20 categories in the test set. Experimental setup for all the datasets is presented in the next section.

5.2 Experimental settings and computation cost

Following [3], we compute approximate certified test set accuracy to estimate the performance of the smoothed model prediction with the Algorithm 1 and embedding risk computation with the Algorithm 2. The baseline model we used for experiments is a prototypical network introduced in [38] with ConvNet-4 backbone. Compared to the original architecture, an additional fully-connected layer was added in the tail of the network to map embeddings to 512-dimensional vector space. The model was trained to solve 1-shot and 5-shot classification tasks on each dataset, with 5-way classification on each iteration.

Parameters of expeiments. For data augmentation, we applied Gaussian noise with zero mean, unit variance and probability 0.3 of augmentation. Each dataset was certified on a subsample of 500 images with default parameters for the Algorithm 1: number of samples $n = 1000$, confidence level $\alpha = 0.001$ and variance $\sigma = 1.0$, unless stated otherwise. For our settings, it may be shown from

simple geometry that values (a_i, b_i) from (9) are such that $b_i - a_i \leq 4$ so we use $b_i - a_i = 4$. The maximum number of samples T in the Algorithm 1 is set to be $T = 5 \times 10^5$.

Computation cost. In the table below, we report the computation time of the certification procedure per image on Tesla V100 GPU for *Cub-200-2011* dataset. Standard deviation in seconds appears to be significant because the number of main loop iterations required to separate the two leftmost confidence intervals varies from image to image in the test set.

Table 1: Computation time per image of implementation of the Algorithm 2, Cub-200-2011.

n	10^3	10^4	10^5
t, sec	0.044 ± 0.030	0.509 ± 0.403	4.744 ± 2.730

5.3 Results of experiments

In this section, we report results of our experiments. In our evaluation protocol, we compute approximate certified test set accuracy, CA. Given a sample x, a smoothed classifier $g(\cdot)$ from the Algorithm 1 with an assigned classification rule $h(x) = \arg\min_{i \in \{1,...,K\}} \|g(x) - c_k\|_2$, threshold value ε for l_2-norm of additive perturbation and the robustness guarantee $r = r(x)$ from the Algorithm 3, we compute CA on test set S as follows:

$$CA(S, \varepsilon) = \frac{|(x, y) \in S : r(x) > \varepsilon \,\&\, h(x) = y|}{|S|}. \tag{14}$$

In other words, we treat the model $g(\cdot)$ as certified at point x under perturbation of norm ε if x is correctly classified by $g(\cdot)$ (what means that the procedure of classification described in the Algorithm 1 does not abstain from classification of x) and $g(\cdot)$ has the value of certified radius $r(x) > \varepsilon$.

Visualization of results. The figures 3-4 from below represent dependencies of certified accuracy on the value of norm of additive perturbation (attack radius) for different learning settings (1-shot and 5-shot learning). The value of attack radius corresponds to the threshold ε from (14). For *Cub-200-2011* dataset we provide a dependency of certified accuracy for different number of samples n for the Algorithm 1 (in the Figure 5).

6 Limitations

In this section, we describe limitations of our approach. Namely, we provide failure probability of Algorithms 1-2 and discuss abstains from classification in the Algorithm 1.

6.1 Estimation of errors of algorithms

Note that the value of α from (11) is the probability of the value of $\rho_{x,k} = \|g(x) - c_k\|_2$ not to belong to the corresponding interval of the form from (13).

Given a sample x, the procedure in the Algorithm 1 returns two closest prototypes to the $g(x)$. Note that if two leftmost confidence intervals are determined, two closest to $g(x)$ prototypes are established with probability at least $1 - \alpha$ for each one, thus, according to the independence of computing these two intervals, the error probability for the Algorithm 1 is $q_1 = 1 - (1 - \alpha)^2$. This value corresponds to returning a pair of class prototypes at least one of which is not actually among the two closest to $g(x)$ prototypes given the fact that the Algorithm 1 does not abstain.

Similarly, the procedure in the Algorithm 2 outputs the lower bound for the adversarial risk with coverage at least $1 - \alpha$ and depend on the output of the Algorithm 1 inside, and, thus, has error probability $q_2 = 1 - (1 - \alpha)^3$ that corresponds to returning an overestimated lower bound for the adversarial risk from the Theorem 2.

6.2 Abstains from classification

It is crucial to note that the procedure in the Algorithm 1 may require a lot of samples to distinguish two leftmost confidence intervals and sometimes does not finish before reaching threshold value T for

sample size. As a result, there may be input objects at which the smoothed classifier can be neither evaluated nor certified. In this subsection, we report the numbers of objects in which the Algorithm 1 abstains from determining the closest class prototype. The fractions of abstained samples for different values of confidence level α for both 1-shot and 5-shot scenarios are reported in the Tables 2-3 below.

Figure 5: Dependency of certified accuracy on attack radius ε for different number of samples n of the Algorithm 1, *CIFAR-FS* dataset, 5-shot case. Is is notable that relatively small number of samples may be used to achieve satisfactory level of certified accuracy.

Table 2: Percentage of non-certified objects in test subset, 1-shot case.

	$\alpha = 10^{-2}$	$\alpha = 10^{-3}$	$\alpha = 10^{-4}$
Cub-200-2011	1.6%	1.6%	1.6%
CIFAR-FS	2.2%	2.2%	2.4%
*mini*ImageNet	1.9%	2.2%	2.4%

Table 3: Percentage of non-certified objects in test subset, 5-shot case.

	$\alpha = 10^{-2}$	$\alpha = 10^{-3}$	$\alpha = 10^{-4}$
Cub-200-2011	1.2%	1.2%	1.4%
CIFAR-FS	3.0%	3.4%	3.8%
*mini*ImageNet	2.9%	2.9%	3.0%

7 Related work

Breaking neural networks with adversarial attacks and empirical defending from them have a long history of cat-and-mouse game. Namely, for a particular proposed defense against existing adversarial perturbations, a new more aggressive attack is found. This motivated researchers to find defenses that are mathematically provable and certifiably robust to different kinds of input manipulations. Several works proposed exactly verified neural networks based on Satisfiability Modulo Theories solvers [16, 6], or mixed-integer linear programming [30, 8]. These methods are found to be computationally inefficient, although they guarantee to find adversarial examples, in the case if they exist. Another line of works use more relaxed certification [45, 11, 35]. Although these methods aim to guarantee that an adversary does not exist in a certain region around a given input, they suffer from scalability to big networks and large datasets. The only scalable to large datasets provable defense against adversarial perturbations is *randomized smoothing*. Initially, it was found as an empirical defense to mitigate adversarial effects in neural networks [29, 47]. Later several works showed its mathematical proof of certified robustness [21, 25, 3, 37]. Lecuyer et al [21] first provided proof of certificates against adversarial examples using differential privacy. Then Li et al [25] proposed tighter bounds of guarantees using Renyi divergence. Later, Cohen et al [3] provided the tightest bound using Neyman-Pearson lemma. Interestingly, alternative proof using Lipschitz continuity was found [37]. The scalability and simplicity of randomized smoothing attracted significant attention, and it was extended beyond l_2-perturbations [22, 41, 27, 24, 23, 20, 31, 49].

8 Conclusion and future work

In this work, we extended randomized smoothing as a defense against additive norm-bounded adversarial attacks to the case of classification in the embedding space that is used in few-shot learning scenarios. We performed an analysis of Lipschitz continuity of smoothed normalized embeddings and derived a robustness certificate against l_2-attacks. Our theoretical findings are supported experimentally on several datasets. There are several directions for future work: our approach can possibly be extended to other types of attacks, such semantic transformations; also, it is important to reduce the computational complexity of the certification procedure.

References

[1] Luca Bertinetto, Joao F Henriques, Philip HS Torr, and Andrea Vedaldi. Meta-learning with differentiable closed-form solvers. *arXiv preprint arXiv:1805.08136*, 2018.

[2] Nicholas Carlini and David Wagner. Towards evaluating the robustness of neural networks. In *2017 ieee symposium on security and privacy (sp)*, pages 39–57. IEEE, 2017.

[3] Jeremy Cohen, Elan Rosenfeld, and Zico Kolter. Certified adversarial robustness via randomized smoothing. In *International Conference on Machine Learning*, pages 1310–1320. PMLR, 2019.

[4] Guneet S. Dhillon, Kamyar Azizzadenesheli, Zachary C. Lipton, Jeremy Bernstein, Jean Kossaifi, Aran Khanna, and Anima Anandkumar. Stochastic activation pruning for robust adversarial defense, 2018.

[5] Yinpeng Dong, Hang Su, Baoyuan Wu, Zhifeng Li, Wei Liu, Tong Zhang, and Jun Zhu. Efficient decision-based black-box adversarial attacks on face recognition. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 7714–7722, 2019.

[6] Ruediger Ehlers. Formal verification of piece-wise linear feed-forward neural networks. In *International Symposium on Automated Technology for Verification and Analysis*, pages 269–286. Springer, 2017.

[7] Volker Fischer, Mummadi Chaithanya Kumar, Jan Hendrik Metzen, and Thomas Brox. Adversarial examples for semantic image segmentation. *arXiv preprint arXiv:1703.01101*, 2017.

[8] Matteo Fischetti and Jason Jo. Deep neural networks as 0-1 mixed integer linear programs: A feasibility study. *arXiv preprint arXiv:1712.06174*, 2017.

[9] Micah Goldblum, Liam Fowl, and Tom Goldstein. Adversarially robust few-shot learning: A meta-learning approach. *Advances in Neural Information Processing Systems*, 33, 2020.

[10] Ian J Goodfellow, Jonathon Shlens, and Christian Szegedy. Explaining and harnessing adversarial examples. *arXiv preprint arXiv:1412.6572*, 2014.

[11] Sven Gowal, Krishnamurthy Dvijotham, Robert Stanforth, Rudy Bunel, Chongli Qin, Jonathan Uesato, Relja Arandjelovic, Timothy Mann, and Pushmeet Kohli. On the effectiveness of interval bound propagation for training verifiably robust models. *arXiv preprint arXiv:1810.12715*, 2018.

[12] Jan Hendrik Metzen, Mummadi Chaithanya Kumar, Thomas Brox, and Volker Fischer. Universal adversarial perturbations against semantic image segmentation. In *Proceedings of the IEEE international conference on computer vision*, pages 2755–2764, 2017.

[13] Wassily Hoeffding. Probability inequalities for sums of bounded random variables. In *The collected works of Wassily Hoeffding*, pages 409–426. Springer, 1994.

[14] Yunseok Jang, Tianchen Zhao, Seunghoon Hong, and Honglak Lee. Adversarial defense via learning to generate diverse attacks. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 2740–2749, 2019.

[15] Jinyuan Jia, Xiaoyu Cao, Binghui Wang, and Neil Zhenqiang Gong. Certified robustness for top-k predictions against adversarial perturbations via randomized smoothing. *arXiv preprint arXiv:1912.09899*, 2019.

[16] Guy Katz, Clark Barrett, David L Dill, Kyle Julian, and Mykel J Kochenderfer. Reluplex: An efficient smt solver for verifying deep neural networks. In *International Conference on Computer Aided Verification*, pages 97–117. Springer, 2017.

[17] Edgar Kaziakhmedov, Klim Kireev, Grigorii Melnikov, Mikhail Pautov, and Aleksandr Petiushko. Real-world attack on mtcnn face detection system. In *2019 International Multi-Conference on Engineering, Computer and Information Sciences (SIBIRCON)*, pages 0422–0427. IEEE, 2019.

[18] Stepan Komkov and Aleksandr Petiushko. Advhat: Real-world adversarial attack on arcface face id system. In *2020 25th International Conference on Pattern Recognition (ICPR)*, pages 819–826. IEEE, 2021.

[19] Alex Krizhevsky, Geoffrey Hinton, et al. Learning multiple layers of features from tiny images. 2009.

[20] Aounon Kumar and Tom Goldstein. Center smoothing: Certified robustness for networks with structured outputs. *Advances in Neural Information Processing Systems*, 34, 2021.

[21] Mathias Lecuyer, Vaggelis Atlidakis, Roxana Geambasu, Daniel Hsu, and Suman Jana. Certified robustness to adversarial examples with differential privacy. In *2019 IEEE Symposium on Security and Privacy (SP)*, pages 656–672. IEEE, 2019.

[22] Guang-He Lee, Yang Yuan, Shiyu Chang, and Tommi S Jaakkola. Tight certificates of adversarial robustness for randomly smoothed classifiers. *arXiv preprint arXiv:1906.04948*, 2019.

[23] Alexander Levine and Soheil Feizi. Robustness certificates for sparse adversarial attacks by randomized ablation. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 34, pages 4585–4593, 2020.

[24] Alexander Levine and Soheil Feizi. Wasserstein smoothing: Certified robustness against wasserstein adversarial attacks. In *International Conference on Artificial Intelligence and Statistics*, pages 3938–3947. PMLR, 2020.

[25] Bai Li, Changyou Chen, Wenlin Wang, and Lawrence Carin. Certified adversarial robustness with additive noise. *arXiv preprint arXiv:1809.03113*, 2018.

[26] Debang Li, Junge Zhang, and Kaiqi Huang. Universal adversarial perturbations against object detection. *Pattern Recognition*, 110:107584, 2021.

[27] Linyi Li, Maurice Weber, Xiaojun Xu, Luka Rimanic, Bhavya Kailkhura, Tao Xie, Ce Zhang, and Bo Li. Tss: Transformation-specific smoothing for robustness certification, 2021.

[28] Fan Liu, Shuyu Zhao, Xuelong Dai, and Bin Xiao. Long-term cross adversarial training: A robust meta-learning method for few-shot classification tasks. *arXiv preprint arXiv:2106.12900*, 2021.

[29] Xuanqing Liu, Minhao Cheng, Huan Zhang, and Cho-Jui Hsieh. Towards robust neural networks via random self-ensemble. In *Proceedings of the European Conference on Computer Vision (ECCV)*, pages 369–385, 2018.

[30] Alessio Lomuscio and Lalit Maganti. An approach to reachability analysis for feed-forward relu neural networks. *arXiv preprint arXiv:1706.07351*, 2017.

[31] Jeet Mohapatra, Ching-Yun Ko, Tsui-Wei Weng, Pin-Yu Chen, Sijia Liu, and Luca Daniel. Higher-order certification for randomized smoothing. *arXiv preprint arXiv:2010.06651*, 2020.

[32] Seyed-Mohsen Moosavi-Dezfooli, Alhussein Fawzi, Omar Fawzi, and Pascal Frossard. Universal adversarial perturbations. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 1765–1773, 2017.

[33] Seyed-Mohsen Moosavi-Dezfooli, Alhussein Fawzi, and Pascal Frossard. Deepfool: a simple and accurate method to fool deep neural networks. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 2574–2582, 2016.

[34] Mikhail Pautov, Nurislam Tursynbek, Marina Munkhoeva, Nikita Muravev, Aleksandr Petiushko, and Ivan Oseledets. CC-Cert: A probabilistic approach to certify general robustness of neural networks. *arXiv preprint arXiv:2109.10696*, 2021.

[35] Aditi Raghunathan, Jacob Steinhardt, and Percy Liang. Certified defenses against adversarial examples. *arXiv preprint arXiv:1801.09344*, 2018.

[36] Olga Russakovsky, Jia Deng, Hao Su, Jonathan Krause, Sanjeev Satheesh, Sean Ma, Zhiheng Huang, Andrej Karpathy, Aditya Khosla, Michael Bernstein, et al. Imagenet large scale visual recognition challenge. *International journal of computer vision*, 115(3):211–252, 2015.

[37] Hadi Salman, Greg Yang, Jerry Li, Pengchuan Zhang, Huan Zhang, Ilya Razenshteyn, and Sebastien Bubeck. Provably robust deep learning via adversarially trained smoothed classifiers. *arXiv preprint arXiv:1906.04584*, 2019.

[38] Jake Snell, Kevin Swersky, and Richard S Zemel. Prototypical networks for few-shot learning. *arXiv preprint arXiv:1703.05175*, 2017.

[39] Jiawei Su, Danilo Vasconcellos Vargas, and Kouichi Sakurai. One pixel attack for fooling deep neural networks. *IEEE Transactions on Evolutionary Computation*, 23(5):828–841, 2019.

[40] Christian Szegedy, Wojciech Zaremba, Ilya Sutskever, Joan Bruna, Dumitru Erhan, Ian Goodfellow, and Rob Fergus. Intriguing properties of neural networks. *arXiv preprint arXiv:1312.6199*, 2013.

[41] Jiaye Teng, Guang-He Lee, and Yang Yuan. ℓ_1 adversarial robustness certificates: a randomized smoothing approach. 2019.

[42] Oriol Vinyals, Charles Blundell, Timothy Lillicrap, Daan Wierstra, et al. Matching networks for one shot learning. *Advances in neural information processing systems*, 29:3630–3638, 2016.

[43] Catherine Wah, Steve Branson, Peter Welinder, Pietro Perona, and Serge Belongie. The caltech-ucsd birds-200-2011 dataset. 2011.

[44] Lily Weng, Pin-Yu Chen, Lam Nguyen, Mark Squillante, Akhilan Boopathy, Ivan Oseledets, and Luca Daniel. Proven: Verifying robustness of neural networks with a probabilistic approach. In *International Conference on Machine Learning*, pages 6727–6736. PMLR, 2019.

[45] Eric Wong and Zico Kolter. Provable defenses against adversarial examples via the convex outer adversarial polytope. In *International Conference on Machine Learning*, pages 5286–5295. PMLR, 2018.

[46] Zuxuan Wu, Ser-Nam Lim, Larry S Davis, and Tom Goldstein. Making an invisibility cloak: Real world adversarial attacks on object detectors. In *European Conference on Computer Vision*, pages 1–17. Springer, 2020.

[47] Cihang Xie, Jianyu Wang, Zhishuai Zhang, Zhou Ren, and Alan Yuille. Mitigating adversarial effects through randomization. *arXiv preprint arXiv:1711.01991*, 2017.

[48] Cihang Xie, Jianyu Wang, Zhishuai Zhang, Yuyin Zhou, Lingxi Xie, and Alan Yuille. Adversarial examples for semantic segmentation and object detection. In *Proceedings of the IEEE International Conference on Computer Vision*, pages 1369–1378, 2017.

[49] Greg Yang, Tony Duan, J Edward Hu, Hadi Salman, Ilya Razenshteyn, and Jerry Li. Randomized smoothing of all shapes and sizes. In *International Conference on Machine Learning*, pages 10693–10705. PMLR, 2020.

[50] Dinghuai Zhang, Mao Ye, Chengyue Gong, Zhanxing Zhu, and Qiang Liu. Black-box certification with randomized smoothing: A functional optimization based framework. *arXiv preprint arXiv:2002.09169*, 2020.

[51] Hongyang Zhang, Yaodong Yu, Jiantao Jiao, Eric Xing, Laurent El Ghaoui, and Michael Jordan. Theoretically principled trade-off between robustness and accuracy. In *International Conference on Machine Learning*, pages 7472–7482. PMLR, 2019.

[52] Yaoyao Zhong and Weihong Deng. Towards transferable adversarial attack against deep face recognition. *IEEE Transactions on Information Forensics and Security*, 16:1452–1466, 2020.

[53] Jianli Zhou, Chao Liang, and Jun Chen. Manifold projection for adversarial defense on face recognition. In *European Conference on Computer Vision*, pages 288–305. Springer, 2020.