T-Graphormer: Using Transformers for Spatiotemporal Forecasting

Abstract

Time series data is ubiquitous and appears in all fields of study. In multivariate time series, observations are interconnected both temporally and across components. For instance, in traffic flow analysis, traffic speeds at different intersections exhibit complex spatiotemporal correlations. This dual structure presents unique challenges for modelling. Most existing forecasting methods address this by learning the spatial and temporal dependencies separately. Here, we propose Temporal Graphormer (T-Graphormer), a transformer-based method that models spatiotemporal correlations directly. By extending the Graphormer architecture over time, each node is updated based on all other nodes within the historical context window, allowing the model to learn powerful representations. We demonstrate the efficacy of T-Graphormer by evaluating it on two real-world traffic prediction benchmarking datasets. Compared to state-of-the-art methods, our method shows a reduction in root mean squared error (RMSE) by up to 10% and mean absolute percentage error (MAPE) by up to 10%.

1 Introduction

Time series data is prevalent across various disciplines and appears in different forms. In retail, it manifests as customer orders over time; in finance, as stock prices; in energy grid optimization, as electricity consumption or transformer temperature (Böse et al., 2017); and in geography, as geopotential or temperature measurements. Accurate prediction of time series has long been a critical problem with significant applications, leading to the development of many techniques such as spectral analysis, linear models, and state-space models (Brockwell & Davis, 2002).

In multivariate time series, each observation at time t is a vector (or matrix), indicating that the observations are not only interrelated over time but also across components. This dual structure (temporal dependence and cross-sectional dependence) presents unique challenges and opportunities for modelling. To provide an example, in a multivariate time series of economic indicators, the GDP, inflation rate, and unemployment rate are all interrelated at each time step, necessitating models that can effectively capture their complex dynamics.

Figure 1: Visualization of a multivariate time series with graph structure. In this example, the graph remains static over time, similar to traffic networks. The node colours become more opaque to indicate more recent data points.

In this work, we focus on multivariate time series forecasting where the components are organized in a graph structure (Figure 1). Traffic flow is a prime example of such data. While traffic networks might appear "grid-like", their spatial structure is non-Euclidean. Two roads close in Euclidean space can exhibit different behaviours yet roads far in Euclidean space could exhibit similar behaviours (Li et al., 2018). For example in a city like Los Angeles, two geographically close roads (a residential street and a parallel highway) might experience vastly different

traffic conditions due to differences in traffic volume, speed limits, and access points. Conversely, roads that are far in Euclidean space (two separate segments of the same highway) can exhibit similar behaviours if they are influenced by the same traffic flow dynamics. These complex spatial relationships combined with the non-stationarity of traffic flow have proven difficult for traditional machine learning techniques such as ARIMA and Kalman filtering (Okutani & Stephanedes, 1984; Lippi et al., 2013; Box et al., 2015).

Spatiotemporal forecasting, similar to advancements seen in computer vision and natural language processing (Krizhevsky et al., 2012; He et al., 2016; Radford et al., 2018; Devlin et al., 2018), has shifted from traditional machine learning methods to non-linear deep learning models. With growing efforts in data mining and improvements in computational resources, these models are increasingly capable of learning representations that capture the complex dynamics of multivariate time series, leading to more accurate predictions. Many researchers have employed convolutional modules to address spatial and temporal dependencies separately (Li et al., 2018; Yu et al., 2018; Wu et al., 2019; 2020). By interleaving temporal learning modules with spatial learning modules, these approaches facilitate the exchange of features between the time domain and the graph domain, enabling the decoupled modelling of spatiotemporal dependencies.

In this paper, we investigate whether directly modelling spatiotemporal data within a single unified framework leads to superior representation learning compared to approaches that use separate spatial and temporal learning modules. To do so, we explore variants of the Transformer architecture. Although originally designed for sequential data such as text and speech, Transformers have shown great promise in handling more complex data structures through additional encoding techniques. For instance, architectures like Graphormer (Ying et al., 2021) and Vision Transformer (ViT) (Dosovitskiy et al., 2020; Feichtenhofer et al., 2022) have successfully adapted these techniques to recover and utilize structural information when data is flattened and treated sequentially.

Building on this foundation, we introduce T-Graphormer (Temporal-Graphormer), which extends the encoding techniques of Graphormer into the temporal dimension. This approach allows T-Graphormer to leverage the global attention mechanism inherent in Transformers to capture spatial *and* temporal relationships simultaneously. Our extensive experiments on real-world traffic forecasting datasets demonstrate that T-Graphormer achieves state-of-the-art performance, surpassing existing methods by a significant margin. Furthermore, through ablation studies, we identify which encoding methods in T-Graphormer are responsible for its predictive abilities. These results highlight the potential of using Transformers as a unified framework for spatiotemporal modelling.

2 RELATED WORKS

In this section, we first review recent advancements in spatiotemporal forecasting. Then, we examine the relevant literature on the adoption of Transformers for various applications.

2.1 TRAFFIC PREDICTION

Traditional methods for time series modelling have long been foundational, with Autoregressive Moving-Average (ARMA) being a cornerstone linear model for stationary processes. To accommodate non-stationary time series, Autoregressive Integrated Moving-Average (ARIMA) was introduced (Box et al., 2015; Brockwell & Davis, 2002). Many have extended these models for multivariate time series. For instance, Lippi et al. (2013) and Williams & Hoel (2003) evaluated several statistical algorithms on traffic forecasting, including ARIMA with Kalman filters to estimate unobserved variables (the moving average components) and Support Vector Regression (SVR) models.

As deep learning showed tremendous success in Natural Language Processing (NLP) and computer vision, many borrowed ideas and architectures from these fields for traffic forecasting. Yu et al. (2018) proposed Spatio-Temporal Graph Convolutional Networks (STGCN), which uses Convolutional Neural Network (CNN) architectures to extract graphical and temporal features in traffic data. Each layer in STGCN contains a "sandwich" structure with two gated sequential convolution layers and a spatial graph convolution layer in between. Around the same time, Li et al. (2018) developed Diffusion Convolutional Recurrent Neural Network (DCRNN). Inspired by the work by Atwood & Towsley (2016), it captures spatial dependencies using diffusion convolution, which models traffic flow as a diffusion process characterized by random walks. DCRNN then captures temporal de-

pendencies with Recurrent Neural Network (RNN). Subsequently, Wu et al. (2019) created Graph WaveNet, which combines graph convolutional networks with the WaveNet architecture (Oord et al., 2016). In WaveNet, dilated causal convolutions (Yu & Koltun, 2016) are used to expand the receptive field for capturing historical temporal context. These convolutions are efficient, requiring fewer layers by skipping inputs based on a dilation factor that typically grows exponentially with each layer. Dilated convolutions are also utilized in Multivariate Time Series Forecasting with Graph Neural Networks (MTGNN) by Wu et al. (2020).

With the introduction of the attention mechanism in Transformers, many models began integrating it into their spatial and temporal learning modules. For instance, Attention-based Spatial-Temporal Graph Convolutional Network (ASTGCN) (Guo et al., 2019) integrates convolutional networks with temporal and spatial attention modules to selectively focus on critical information. Similarly, Zheng et al. (2020) proposed GMAN, which uses an autoencoder architecture where each block integrates spatial and temporal attention mechanisms.

More recently, Jiang et al. (2023) and Liu et al. (2023) introduced PDFormer and STAEformer, respectively. Both models utilize Transformer-based encoders for representation learning and fully connected layers for prediction. PDFormer incorporates meticulously designed self-attention modules, whereas STAEformer employs learnable spatiotemporal embeddings. Our proposed model, T-Graphormer, aligns with STAEformer's minimal reliance on inductive biases in its architecture. However, T-Graphormer fundamentally differs in its approach to information processing. Unlike models with separate temporal and spatial learning modules, T-Graphormer enables all nodes to attend to one another and leverages the Transformer's inherent global attention capacity to learn coupled spatiotemporal dependencies simultaneously.

Most of the models we have discussed so far interleave temporal learning modules with spatial learning modules, transferring features between the time domain and the graph domain. In another direction, Spatial-Temporal Synchronous Graph Convolutional Network (STSGCN) simultaneously captures spatial and temporal dependencies using a novel synchronous graph convolution operation. This is done by adding positional embeddings and connecting the nodes across time steps, improving the model's ability to handle complex and evolving traffic conditions (Song et al., 2020). While this approach aligns with our goal of avoiding separate spatial and temporal learning modules, it is important to note that STSGCN treats the input as a graph and uses GCN for message-passing. In comparison, T-Graphormer processes the input as a sequence. This distinction underscores a fundamental difference in how the two models integrate spatial and temporal information.

2.2 TRANSFORMERS

Transformers (Vaswani et al., 2017) were originally designed for NLP applications. Before its introduction, models such as RNN (Rumelhart et al., 1986) and Long Short-Term Memory (LSTM) (Hochreiter & Schmidhuber, 1997) suffered from poor long-range dependency and faced training issues such as vanishing/exploding gradients (Pascanu et al., 2013). Since they store information about previous time steps in a hidden state, the number of operations required to relate two distant signals grows as a function of the distance between them. This is mitigated in transformers with the attention mechanism, where the input to the model is the full sequence and tokens are related to each other in a constant number of operations. The multi-headed attention mechanism has allowed transformers to model long-range dependency and extract useful features, making them flexible and powerful for many data types, including text (Brown et al., 2020; Touvron et al., 2023; Ouyang et al., 2022), image (Dosovitskiy et al., 2020), and graph (Ying et al., 2021; Dwivedi & Bresson, 2020; Kreuzer et al., 2021).

In NLP, Devlin et al. (2018) showed that by randomly masking tokens in sequences, Bidirectional Encoder Representations from Transformers (BERT) can learn to integrate context from both the preceding and succeeding text. Since transformers apply the attention operation to each token independently, they benefit from parallelized computing, allowing them to pre-train on billions of pages of web data and scale to billions of parameters. Overall, pre-trained models have better generalization to downstream tasks such as sentiment analysis, named entity recognition, and question answering (Radford et al., 2018; Devlin et al., 2018; Radford et al., 2019; Brown et al., 2020).

As transformers showed state-of-the-art results in NLP, many brought powerful self-supervised pre-training techniques to other data modalities. However, they only operate on linear sequences, so we

first explore how they accept non-text input without significant architecture modifications. Dosovitskiy et al. (2020) proposed ViT to extend transformers to images. To exploit the strengths of the transformer architecture, ViT flattens images into patches (or with CNN patches directly), maps them to the latent vector size (patch embedding) with a trainable linear projection, and adds positional embeddings to retain structural information. Compared to CNNs, ViTs have little image-specific inductive bias (no convolution kernels) while leveraging the efficient global attention mechanism, allowing the models to scale.

3 PRELIMINARIES

This section covers the notations and definitions used in multivariate time series analysis, along with an overview of the self-attention mechanism in Transformers, which is important for understanding T-Graphormer.

3.1 DEFINITIONS

Formally, a time series is a set of observations X_t, where t denotes the time of observation. While the observation across time can be continuous, we will focus on the discrete form. The forecasting of time series is the task where given T' historical data at time t, $(X_{t-T'+1}, X_{t-T'+2}, \ldots, X_t)$, we wish to predict the next T observations in the future $(X_{t+1}, X_{t+2}, \ldots, X_{t+T})$.

In multivariate time series, each observation is a vector (or a matrix). Let $X_{t,i} \in \mathbb{R}^{1 \times C}$ be the ith component of such observation at time t, and let

$$\mathbf{X}_t = (X_{t,1}^\top, X_{t,2}^\top, \ldots, X_{t,N}^\top)^\top \in \mathbb{R}^{N \times C}$$

denote the observation at time t with N components each having C features. The goal of multivariate time series forecasting is to predict

$$\boldsymbol{\mathcal{Y}} = \left(\mathbf{X}_{t+1}^\top, \mathbf{X}_{t+2}^\top, \ldots, \mathbf{X}_{t+T}^\top\right)^\top \in \mathbb{R}^{T \times N \times C}$$

based on the historical data at time t

$$\boldsymbol{\mathcal{X}} = \left(\mathbf{X}_{t-T'+1}^\top, \mathbf{X}_{t-T'+2}^\top, \ldots, \mathbf{X}_t^\top\right)^\top \in \mathbb{R}^{T' \times N \times C}$$

In our traffic prediction problem, the components of an observation lie in a graph $\mathcal{G} = (\mathcal{V}, \mathcal{E}, \mathbf{W})$. Here, $\mathcal{G}$ denotes a graph with the set of vertices $\mathcal{V}$ with size N and the set of edges $\mathcal{E}$ with size M, and $\mathbf{W} \in \mathbb{R}^{N \times N}$ denotes the weighted adjacency matrix with $\mathbf{W}_{i,j}$ being the edge length. In other words, each ith component of the observation $\mathbf{X}_t$ at time t is the node value of node v_i.

3.2 TRANSFORMERS

The Transformer architecture is a key component in many modern deep-learning models. It consists of multiple layers, each composed of two main parts: a self-attention mechanism and a position-wise Feed-Forward Network (FFN).

Given an input sequence $H = \left(h_1^\top, \ldots, h_l^\top\right)^\top \in \mathbb{R}^{l \times d}$ where d is the hidden dimension and $h_i \in \mathbb{R}^{1 \times d}$ is the hidden representation at position i, three matrices are used to project H to obtain Q, K, V.

$$Q = HW_Q, \quad K = HW_K, \quad V = HW_V \tag{1}$$

where the three matrices are $W_Q \in \mathbb{R}^{d \times d_K}, W_K \in \mathbb{R}^{d \times d_K}, W_V \in \mathbb{R}^{d \times d_V}$ respectively. The similarity matrix A is calculated as

$$A = \frac{QK^\top}{\sqrt{d_K}}, \tag{2}$$

which measures the semantic similarity between query vectors in Q and key vectors in K. Finally, this attention score matrix is used to retrieve the learned value vectors:

$$\text{Attention}(H) = \text{softmax}(A)V \tag{3}$$

Figure 2: T-Graphormer model architecture. Graph node values across time are flattened to obtain node features. Centrality encoding and positional encoding are added to the node feature vector, which is then passed into the Graphormer encoder blocks. The edge weights of the graph are used to compute spatial encodings that determine the attention bias. Finally, the prediction layer maps the learned representation onto the output space. In this Figure, a `cls` token (white fill) is added to the beginning of the sequence. The illustration of node feature, centrality encoding, and spatial encoding vectors are consistent with the example in Figure 1.

This defines one attention head. In multi-headed attention, the outputs of each head are concatenated and projected again. After the self-attention operation, each position i in the sequence H is processed independently and identically by a position-wise FFN. The FFN consists of two linear transformations with an activation function in between:

$$\text{FFN}(h_i) = \text{activation}(h_i W_1 + b_1) W_2 + b_2. \tag{4}$$

4 T-Graphormer

In this section, we discuss how Graphormer can be easily extended in the temporal dimension to produce T-Graphormer that learns from spatiotemporal data. We also provide implementation details that were beneficial in practice.

4.1 Node Feature Embedding

Following Graph WaveNet by Wu et al. (2019), we project the observed node values from C to d dimensions with a linear layer $W_0 \in \mathbb{R}^{C \times d}$. Let $\mathcal{X} \in \mathbb{R}^{T' \times N \times C}$ be the historical data, we denote the initial node features as $\mathcal{X} \in \mathbb{R}^{T' \times N \times d}$.

4.2 Structural Encodings

As discussed in section 2, structured data must be flattened before it can be processed by Transformers. We vectorize $\mathcal{X}$ into

$$\mathbf{x} = (X_{t-T'+1,1}, \ldots, X_{t+2,N}, \ldots, X_{t,N}) \in \mathbb{R}^{l \times d}$$

where $l = T' \times N$. However, information is lost during this process, so when applying Transformers to spatiotemporal data, structural encoding methods are essential to introduce inductive biases that

inform the model about the structure in $\mathcal{X}$. In T-Graphormer, we extend the structural encoding techniques introduced in Graphormer (Ying et al., 2021) to effectively capture the spatiotemporal relationships within the data. This is mainly done in two ways: modifications to the node features and modifications to the attention mechanism (see Figure 2).

Let $x_{t,i} \in \mathbb{R}^{1 \times d}$ be the feature vector of the ith node at time t, centrality encoding is added to $x_{t,i}$ to inform the model about node importance. Intuitively, in a traffic network, intersections with more road connections have significant effect on the downstream traffic conditions. Let $\deg^-(v)$ denote the in-degree of node v, and $\deg^+(v)$ denote the out-degree, centrality encoding, $Z^- \in \mathbb{R}^{\deg^-(V) \times d}$ and $Z^+ \in \mathbb{R}^{\deg^+(V) \times d}$, are real-valued learnable embedding matrices indexed by $\deg(v)$ where the number of rows corresponds to the maximum node in-degree and out-degree in $\mathcal{G}$ respectively. Concretely, centrality encoding is applied to all initial node features before entering the first Transformer block

$$h_{t,i}^0 = x_{t,i} + z_{\deg^-(v_i)}^- + z_{\deg^+(v_i)}^+. \tag{5}$$

Note that the encoding is time-agnostic and is determined solely by the degree of the corresponding node. In other words, for $x_{t_1,i}$ and $x_{t_2,i}$ the centrality encodings are both $z_{\deg(v_i)}$ (as shown in Figure 2 centrality encoding). Also in cases of undirected graphs, only $Z \in \mathbb{R}^{\deg(V) \times d}$ is used.

To account for the temporal structure in multivariate time series, we also add learnable positional encoding (Vaswani et al., 2017; Dosovitskiy et al., 2020) to the initial node features. Let $P \in \mathbb{R}^{l \times d}$ denote the learned matrix where $l = T'N$, we update the initial node features in equation 5 as

$$h_{t,i}^0 = x_{t,i} + z_{\deg^-(v_i)}^- + z_{\deg^+(v_i)} + p_{t,i}. \tag{6}$$

Note that, unlike centrality encoding, positional encoding vectors $p_{t,i}$ are specific to each token in the vectorized time series. While Feichtenhofer et al. (2022) adopts separate positional embeddings when applying ViT on videos, with one for time and one for space, we find T-Graphormer performs better when the spatiotemporal positional embedding is learned simultaneously.

While the attention mechanism in Transformers has an effective global receptive field, the spatial encoding method is another important space-time inductive bias that improves spatial representation learning. Given the graph network $\mathcal{G} = (\mathcal{V}, \mathcal{E}, \mathbf{W})$, the model can leverage the weighted adjacency matrix to determine which nodes are closer in topological space for updating representations. Let $\phi(v_i, v_j) : \mathcal{V} \times \mathcal{V} \mapsto \mathbb{R}$ denote a function that measures the spatial relation between nodes, the attention score (equation 2) between tokens (t_1, i) and (t_2, j) is updated as:

$$A_{(t_1,i),(t_2,j)} = \frac{(h_{t_1,i} W_Q)(h_{t_2,i} W_K)^\top}{\sqrt{d}} + b_{\phi(i,j)} \tag{7}$$

where $b_{\phi(i,j)}$ is the learnable attention bias scalar indexed by $\phi(i, j)$ from Φ.

Similar to Graphormer, we define ϕ as the shortest path distance (SPD) between nodes and $\Phi \in \mathbb{R}^{N \times N}$ as the matrix storing the SPD values for all node pairs. For example, if the longest path between any two nodes in $\mathcal{G}$ is 3, the learnable attention bias embedding B will have shape $3 \times 3 \times$ *number of heads*. Like centrality encoding, spatial encoding is time-independent; for nodes i and j, the term remains consistent across time steps (see Figure 2, Spatial Encoding).

4.3 IMPLEMENTATION DETAILS

To project the learned node representations from the encoder to the output space, we explore two architectures. In the first, a vanilla setup, we use two linear layers to project the hidden representation at the last layer $H_k \in \mathbb{R}^{l \times d}$ from d dimensions to $\frac{d}{2}$ and then to C. In the second setup, we introduce additional dilated causal convolutional layers (Yu & Koltun, 2016). This imposes a structural inductive bias that ensures future predictions are based solely on representations from previous time steps. The output from these convolutional layers is then projected to C dimensions using the same linear layers.

Before passing the node features through the Transformer blocks, we experiment with adding special tokens to the sequence:

- No special token added, the length of the sequence is $T' \times N$ before passing through the encoder.

- Adding a `cls` token to the start of the sequence (see Figure 2), resulting in $(T' \times N) + 1$ tokens. The implementation is similar to the virtual node in Graphormer, where a learnable embedding of size $\mathbb{R}^{1 \times d}$ is introduced and concatenated with the initial node features $\mathcal{X}$. This token acts as a supernode, aggregating information from the entire sequence and propagating it back to other tokens (Ying et al., 2021).

- Adding a `graph` token to the start of each graph signal, resulting in $T' \times (N + 1)$ tokens. The implementation is similar to the `cls` token, with a learnable embedding used to represent the `graph` token. Its function is analogous to the `sep` token in BERT (Devlin et al., 2018), serving as a delimiter for graph signals at different time steps.

For all special tokens, we form virtual connections to other nodes. $b_{\phi(\texttt{token},v)}$ is learned separately.

Following what has been observed with current Transformer implementations, we find that using layer normalization (Ba et al., 2016) before multi-headed attention and FFN improves T-Graphormer performance. We also find Gaussian Error Linear Unit (GELU) to be the best activation function.

5 EXPERIMENTS

In this section, we detail the experimental settings used to evaluate T-Graphormer on two traffic prediction datasets. We compare T-Graphormer's performance against 10 baseline methods. Additionally, to gain deeper insights into T-Graphormer, we conduct ablation studies focusing on its structural encodings and the impact of added special tokens.

5.1 DATASETS

Following Li et al. (2018); Wu et al. (2019; 2020); Shao et al. (2022), we evaluate T-Graphormer on two commonly used spaiotemporal forecasting datasets (see Table 1 for details):

- PEMS-BAY (Chen et al., 2001): A traffic speed dataset collected from California Transportation Agencies (CalTrans) Performance Measurement System (PeMS).

- METR-LA (Jagadish et al., 2014): A traffic speed dataset collected from loop detectors on the highway of Los Angeles County.

Datasets	# Sensors	# Samples	Sampling Rate	Mean	Std
PEMS-BAY	325	52116	5 minute	54.40	19.49
METR-LA	207	34727	5 minute	62.73	9.44

Table 1: Details of the dataset used for evaluation. The mean and standard deviation (std) are calculated across time and space.

For both datasets, we follow the same pre-processing implementation as Li et al. (2018)[1]. Specifically, each sample $\mathbf{X}_t$ is a 5-minute traffic speed reading from all sensors in the network. We aggregate 12 consecutive samples (representing a 1-hour context window) to construct $\boldsymbol{\mathcal{X}} \in \mathbb{R}^{12 \times N \times 1}$. The ground truth $\boldsymbol{\mathcal{Y}}$ consists of the next T future traffic speed readings from all sensors. To ensure consistency with the baseline methods, we evaluate the models on predictions for $T = \{3, 6, 12\}$, corresponding to 15 minutes, 30 minutes, and 1 hour, respectively. We also concatenate a one-hot-encoding vector signifying the time of day to all node values at time t.

The data is split such that approximately 70% is used for training, 20% for testing, and 10% for validation. To avoid data leakage in the traffic prediction task, the time slices are kept in their original order before splitting. Only the training dataset is shuffled for different training iterations and used to perform Z-score normalization on the validation and testing datasets. To construct the graph $\mathcal{G} = (\mathcal{V}, \mathcal{E}, \mathbf{W})$, we follow the same implementation as Li et al. (2018) and refer readers to that work for further details.

---

[1]https://github.com/liyaguang/DCRNN

Dataset	Method	Horizon 3			Horizon 6			Horizon 12		
		MAE	RMSE	MAPE (%)	MAE	RMSE	MAPE	MAE	RMSE	MAPE
PEMS-BAY	VAR	1.74	3.16	3.60	2.32	4.25	5.00	2.93	5.44	6.50
	FC-LSTM	2.05	4.19	4.80	2.20	4.55	5.20	2.37	4.96	5.70
	DCRNN	1.38	2.95	2.90	1.74	3.97	3.90	2.07	4.74	4.90
	STGCN	1.36	2.96	2.90	1.81	4.27	4.17	2.49	5.69	5.79
	Graph WaveNet	1.30	2.74	2.73	1.63	3.70	3.67	1.95	4.54	4.63
	ASTGCN	1.52	3.13	3.22	2.01	4.27	4.48	2.61	5.42	6.00
	STSGCN	1.44	3.01	3.04	1.83	4.18	4.17	2.26	5.21	5.40
	GMAN	1.34	2.91	2.86	1.63	3.76	3.68	1.86	4.32	4.37
	STEP	**1.26**	2.73	**2.59**	1.55	3.58	3.43	1.79	4.20	4.18
	PDFormer	1.32	2.83	2.78	1.64	3.79	3.71	1.91	4.43	4.51
	STAEformer	1.31	2.78	2.76	1.62	3.68	3.62	1.88	4.34	4.41
	T-Graphormer	1.31	**2.55**	2.71	**1.52**	**3.14**	**3.23**	**1.76**	**3.78**	**3.91**
METR-LA	VAR	4.42	7.80	13.00	5.41	9.13	12.70	6.52	10.11	15.80
	FC-LSTM	3.44	6.30	9.60	3.77	7.23	10.09	4.37	8.69	14.00
	DCRNN	2.77	5.38	7.30	3.15	6.45	8.80	3.60	7.60	10.50
	STGCN	2.88	5.74	7.62	3.47	7.24	9.57	4.59	9.40	12.70
	Graph WaveNet	2.69	5.15	6.90	3.07	6.22	8.37	3.53	7.37	10.01
	ASTGCN	4.86	9.27	9.21	5.43	10.61	10.13	6.51	12.52	11.64
	STSGCN	3.31	7.62	8.06	4.13	9.77	10.29	5.06	11.66	12.91
	GMAN	2.80	5.55	7.41	3.12	6.49	8.73	3.44	7.35	10.07
	STEP	**2.61**	**4.98**	**6.60**	2.96	**5.97**	7.96	3.37	6.99	9.61
	PDFormer	2.83	5.45	7.77	3.20	6.46	9.19	3.62	7.47	10.91
	STAEformer	2.65	5.11	6.85	2.97	6.00	8.13	**3.34**	7.02	9.70
	T-Graphormer	2.67	5.37	6.65	**2.94**	5.98	**7.46**	3.35	**6.92**	**8.61**

Table 2: Spatiotemporal forecasting results on two traffic network datasets. We report the results from the best configuration of T-Graphormer on each dataset. The best-performing model for each metric is bolded. Details of the datasets and metrics are described in sections 5.1 and 5.2
.

5.2 SETTINGS

We conduct extensive experiments to investigate how different hyperparameters influence the performance of T-Graphormer. Specifically, we evaluate 2 different Transformer configurations with $d = \{128, 384\}$, $k = \{6, 10\}$, and number of heads $= \{4, 8\}$. These configurations are chosen to maximize the available hardware memory. As detailed in section 4.3, we test 2 distinct prediction layer architectures. For dilated causal convolutions, we select a dilation factor of 2 and use 3 layers.

Training of T-Graphormer is guided by minimizing the mean squared error (MSE) between predicted values $\hat{Y}$ and ground truth $\mathcal{Y}$ for $T = 12$ only. When evaluating the prediction performance on horizons 3 and 6, we simply remove the redundant token values. We employ the AdamW optimizer (Loshchilov & Hutter, 2019) with an effective batch size of 128, using a cosine decay learning rate schedule with warmup (Loshchilov & Hutter, 2017). After training, model configurations with the lowest mean absolute error (MAE) on the validation dataset are selected for testing. T-Graphormer is implemented in `PyTorch` (Paszke et al., 2019) and utilizes distributed data parallelism to speed up training and increase batch size.

T-Graphormer is compared against the following baseline methods: 1. Vector Autoregressive (VAR) (Zivot & Wang, 2006), 2. Support Vector Regression (SVR) (Smola & Schölkopf, 2004), 3. FC-L-STM (Sutskever et al., 2014), 4. Graph Multi-Attention Network (GMAN) (Zheng et al., 2020), 5. STGNN is Enhanced by scalable time series Pre-training model (STEP) (Shao et al., 2022), 6. PDFormer (Jiang et al., 2023), 7. STAEformer (Liu et al., 2023). Additional baselines, including DCRNN, STGCN, Graph WaveNet, MTGNN, ASTGCN, and STSGCN, are discussed in section 2.1. It is worth noting that STEP leverages masked pre-training on long-term historical time series data, enabling models to capture long-term dependencies.

For more information on experimental settings, see Appendix at section A.

5.3 MAIN RESULTS

T-Graphormer demonstrates exceptional performance in long-range traffic prediction. As shown in Table 2, T-Graphormer outperforms all other models across every metric when predicting the next 12 time steps (1-hour window). Notably, with minimal spacetime inductive bias, it achieves a

10.00% reduction in RMSE on the PEMS-BAY dataset and a **10.40%** reduction in MAPE on the METR-LA dataset compared to the state-of-the-art model STEP. We attribute this success to the global receptive field provided by the self-attention mechanism, a key feature of Transformers.

However, T-Graphormer underperforms in short-range traffic prediction. When forecasting the next 15 minutes, it consistently lags behind STEP across all metrics. One possible explanation is that T-Graphormer's reliance on structural encoding methods is limiting its ability to capture local space-time patterns which are critical for short-term predictions. Another factor could be overfitting, as the model is optimized by backpropagation on the prediction error for the next hour (Horizon 12), and short-range predictions (Horizon 3 and 6) are evaluated by masking the extra tokens.

We observe that T-Graphormer performed differently across the two datasets (see Table 6) as the prediction task on METR-LA is harder. In Figure 5, we see that despite overfitting, the training loss of the best model is much lower in PEMS-BAY (9.27) than in METR-LA (55.28). The difficulty of the task is further illustrated in Figure 6 where the validation MAPE is around 4 for PEMS-BAY but increased to around 9 for METR-LA. This is unsurprising since the traffic speed standard deviation (19.49) of METR-LA is much higher than that of PEMS-BAY (9.44), meaning there is more variability in the road conditions of the Los Angeles traffic grid.

Additionally, when comparing the training and validation loss over epochs in Figure 5, the 2 loss curves follow much more closely in PEMS-BAY than in METR-LA, a sign that the model is significantly overfitting on METR-LA. From the dataset side, this can be explained by the fact that PEMS-BAY has 50% more samples than METR-LA (52116 vs. 34727), which allows the model to fully learn the spatiotemporal relationships between flattened tokens on the PEMS-BAY dataset.

This overfitting behaviour is inspected from another perspective in Figure 7. Between the 3 model sizes, although the initial loss differences appear random, a trend emerges towards the end of training, where the bigger the model, the bigger the loss difference between training and validation. This overfitting behaviour is consistent with the recent findings on the empirical scaling laws for training LLM (Kaplan et al., 2020). Using equation (6.6) from this work: $D \propto N^{0.74}$, we find that the traffic prediction dataset sizes are only optimal for training the mini models, but too small for the larger models and cause overfitting.

5.4 ABLATION EXPERIMENTS

In this section, we examine the efficacy of the added structural encoding methods and assess the impact of special tokens. This is done by re-training the best-performing model with the same configuration but with missing components.

It is evident from Table 3 that positional encoding and spatial encoding are the critical structural inductive biases when applying Transformers to spatiotemporal data. When positional encoding is removed, the model fails to predict accurately, leading to a **15.22%** increase in MAE. This is unsurprising since Transformers lack recurrence or convolutional mechanisms and thus rely on positional encoding to capture temporal information.

When spatial encoding is removed, the performance drops **8.06%**. This is consistent with findings from the growing literature in traffic prediction(Li et al., 2018; Yu et al., 2018; Wu et al., 2019; Guo et al., 2019), where adding structural inductive biases (e.g. in the form of using Graph Neural Network (GNN)s) generally improves prediction performance. When positional and spatial encodings

Model				Horizon 3			Horizon 6			Horizon 12		
Positional	Spatial	Centrality	Token	MAE	RMSE	MAPE	MAE	RMSE	MAPE	MAE	RMSE	MAPE
✗	✓	✓	✗	3.29	6.87	8.55	3.51	7.42	9.18	4.12	9.04	10.53
✓	✗	✓	✗	3.35	6.82	8.45	3.51	7.23	8.91	3.89	8.15	9.83
✗	✓	✓	cls	3.15	6.34	8.33	3.38	6.93	8.94	3.86	8.14	10.07
✓	✗	✓	cls	3.07	6.36	7.60	3.29	6.99	8.24	3.62	7.71	9.22
✓	✓	✗	cls	2.75	5.52	7.15	3.05	6.26	8.02	3.51	7.31	9.24
✓	✓	✓	✗	2.78	5.73	7.16	3.11	6.56	8.03	3.50	7.38	9.10
✓	✓	✗	✗	2.74	5.64	7.30	3.05	6.42	8.19	3.45	7.35	9.36
✓	✓	✓	graph	2.81	5.79	7.47	3.08	6.41	8.22	3.42	7.01	9.22
✓	✓	✓	cls	2.67	5.37	6.65	2.94	5.98	7.46	3.35	6.92	8.61

Table 3: Ablation results on the METR-LA dataset. The rows are sorted by descending order on horizon 12 prediction MAE.

are both removed, the drop in performance we observe is additive such that MAE is increased by **22.98%**.

Removing centrality encoding has a less pronounced effect, with only a 4.78% increase in MAE. This limited impact may be attributed to the fact that in our setting, graphs are static over time, so with enough learning, positional encoding can provide sufficient information about node importance. Consistent with the work by Ying et al. (2021), we also observe that adding special tokens improves performance. We also find that adding `cls` or `graph` token noticeably improves prediction performance, and `cls` is generally better.

Interestingly, when `cls` token and centrality encoding are *both* excluded (row 7), the MAE increases to 3.45, which is lower than the error increase when either feature is excluded individually (3.51 and 3.50 in rows 5 and 6). This indicates that models perform better when the features are excluded together. We find this behaviour explainable in one direction: without node degree embedding, it is better to also exclude `cls` token. Since centrality encoding is applied only to the real nodes in the graph signal, it helps the model distinguish regular nodes from the `cls` token. Without it, the `cls` token confuses the model. However, the other direction (without `cls` token, it is better to also exclude centrality encoding) is more difficult to explain. It could be that when both features are present, they contribute complementary information to the model, but when both are excluded, the model adapts by leveraging other available features, such as positional encoding, to compensate for the missing information about node centrality.

6 CONCLUSION

We introduce a novel framework for modelling multivariate time series. By leveraging existing structural encoding methods and extending them along the temporal dimension, we show that the Transformer architecture can be directly applied to spatiotemporal data without requiring separate temporal and spatial learning modules. This integration allows T-Graphormer to simultaneously capture spatiotemporal dependencies, achieving state-of-the-art results on traffic prediction datasets with minimal inductive bias. Building on this foundation, future work can readily incorporate domain knowledge into the architecture, such as using adaptive spatiotemporal embeddings from STAEformer, or developing custom spatial attention mechanisms, as demonstrated with PDFormer.

However, our study has certain limitations that merit discussion. While T-Graphormer exhibits considerable strength in modelling spatiotemporal data, it incurs high memory demands due to attention mechanism's $\mathcal{O}(n^2)$ complexity. Flattening the entire time series into a sequence significantly increases context length as more historical data is included. For example, in the PEMS-BAY dataset, adding a single additional time step increases the context length by 325, corresponding to the number of network nodes. This dramatically impacts memory usage, constraining T-Graphormer's applicability to large networks or extended historical sequences. For instance, training T-Graphormer on the large-scale traffic forecasting dataset LargeST (Liu et al., 2024), which includes up to 8600 nodes, poses significant challenges. Incorporating techniques such as sparse attention (Beltagy et al., 2020) could mitigate this issue and enable the model to handle longer sequences.

Additionally, this work focuses on applying T-Graphormer to static graphs, where the graph structure remains constant over time. Dynamic graphs, where the graph structure evolves, present a promising area for extension. For instance, Shang et al. (2021) demonstrated that graph learning techniques can effectively re-parameterize dynamic graphs for forecasting tasks. Adapting T-Graphormer to dynamic graphs would require strategies such as introducing a maximum graph size and applying padding to handle structural changes over time. Such enhancements could expand T-Graphormer's applicability to a broader range of spatiotemporal forecasting tasks and provide deeper insights into its graph representation learning capabilities. Furthermore, T-Graphormer could be applied to other data modalities with grid-like structures, such as video data (Han et al., 2022) or geographical measurements (Bi et al., 2023).

Transformer's success in NLP can be attributed to its self-supervised pre-training step (Devlin et al., 2018; Radford et al., 2018; 2019). Following the approaches of Feichtenhofer et al. (2022) and Shao et al. (2022), T-Graphormer can be readily utilized as a masked autoencoder for pre-training. Our preliminary results indicate that masked pre-training can improve T-Graphormer training stability and reduce training time (see Figure 8).

7 REPRODUCIBILITY STATEMENT

For reproducibility, we have included links to the anonymized code repository, the datasets, and the pre-trained model weights in section A.1. We also summarize the training configurations and environments. All experimental logs are saved and available online at Weights and Biases upon request.

REFERENCES

James Atwood and Don Towsley. Diffusion-convolutional neural networks. *Advances in neural information processing systems*, 29, 2016.

Jimmy Lei Ba, Jamie Ryan Kiros, and Geoffrey E Hinton. Layer normalization. *arXiv preprint arXiv:1607.06450*, 2016.

Iz Beltagy, Matthew E Peters, and Arman Cohan. Longformer: The long-document transformer. *arXiv preprint arXiv:2004.05150*, 2020.

Kaifeng Bi, Lingxi Xie, Hengheng Zhang, Xin Chen, Xiaotao Gu, and Qi Tian. Accurate medium-range global weather forecasting with 3d neural networks. *Nature*, 619(7970):533–538, 2023.

Joos-Hendrik Böse, Valentin Flunkert, Jan Gasthaus, Tim Januschowski, Dustin Lange, David Salinas, Sebastian Schelter, Matthias Seeger, and Yuyang Wang. Probabilistic demand forecasting at scale. *Proceedings of the VLDB Endowment*, 10(12):1694–1705, 2017.

George EP Box, Gwilym M Jenkins, Gregory C Reinsel, and Greta M Ljung. *Time series analysis: forecasting and control*. John Wiley & Sons, 2015.

Peter J Brockwell and Richard A Davis. *Introduction to time series and forecasting*. Springer, 2002.

Tom Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared D Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, et al. Language models are few-shot learners. *Advances in neural information processing systems*, 33:1877–1901, 2020.

Chao Chen, Karl Petty, Alexander Skabardonis, Pravin Varaiya, and Zhanfeng Jia. Freeway performance measurement system: mining loop detector data. *Transportation research record*, 1748 (1):96–102, 2001.

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. Bert: Pre-training of deep bidirectional transformers for language understanding. *arXiv preprint arXiv:1810.04805*, 2018.

Alexey Dosovitskiy, Lucas Beyer, Alexander Kolesnikov, Dirk Weissenborn, Xiaohua Zhai, Thomas Unterthiner, Mostafa Dehghani, Matthias Minderer, Georg Heigold, Sylvain Gelly, et al. An image is worth 16x16 words: Transformers for image recognition at scale. In *International Conference on Learning Representations*, 2020.

Vijay Prakash Dwivedi and Xavier Bresson. A generalization of transformer networks to graphs. *AAAI Workshop on Deep Learning on Graphs: Methods and Applications*, 2020.

Christoph Feichtenhofer, Yanghao Li, Kaiming He, et al. Masked autoencoders as spatiotemporal learners. *Advances in neural information processing systems*, 35:35946–35958, 2022.

Shengnan Guo, Youfang Lin, Ning Feng, Chao Song, and Huaiyu Wan. Attention based spatial-temporal graph convolutional networks for traffic flow forecasting. In *Proceedings of the AAAI conference on artificial intelligence*, volume 33, pp. 922–929, 2019.

Kai Han, Yunhe Wang, Jianyuan Guo, Yehui Tang, and Enhua Wu. Vision gnn: An image is worth graph of nodes. *Advances in neural information processing systems*, 35:8291–8303, 2022.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 770–778, 2016.

Sepp Hochreiter and Jürgen Schmidhuber. Long short-term memory. *Neural computation*, 9(8): 1735–1780, 1997.

Hosagrahar V Jagadish, Johannes Gehrke, Alexandros Labrinidis, Yannis Papakonstantinou, Jignesh M Patel, Raghu Ramakrishnan, and Cyrus Shahabi. Big data and its technical challenges. *Communications of the ACM*, 57(7):86–94, 2014.

Jiawei Jiang, Chengkai Han, Wayne Xin Zhao, and Jingyuan Wang. Pdformer: Propagation delay-aware dynamic long-range transformer for traffic flow prediction. In *Proceedings of the AAAI conference on artificial intelligence*, volume 37, pp. 4365–4373, 2023.

Jared Kaplan, Sam McCandlish, Tom Henighan, Tom B Brown, Benjamin Chess, Rewon Child, Scott Gray, Alec Radford, Jeffrey Wu, and Dario Amodei. Scaling laws for neural language models. *arXiv preprint arXiv:2001.08361*, 2020.

Devin Kreuzer, Dominique Beaini, Will Hamilton, Vincent Létourneau, and Prudencio Tossou. Rethinking graph transformers with spectral attention. *Advances in Neural Information Processing Systems*, 34:21618–21629, 2021.

Alex Krizhevsky, Ilya Sutskever, and Geoffrey E Hinton. Imagenet classification with deep convolutional neural networks. In F. Pereira, C.J. Burges, L. Bottou, and K.Q. Weinberger (eds.), *Advances in Neural Information Processing Systems*, volume 25. Curran Associates, Inc., 2012. URL https://proceedings.neurips.cc/paper_files/paper/2012/file/c399862d3b9d6b76c8436e924a68c45b-Paper.pdf.

Yaguang Li, Rose Yu, Cyrus Shahabi, and Yan Liu. Diffusion convolutional recurrent neural network: Data-driven traffic forecasting. In *International Conference on Learning Representations*, 2018.

Marco Lippi, Matteo Bertini, and Paolo Frasconi. Short-term traffic flow forecasting: An experimental comparison of time-series analysis and supervised learning. *IEEE Transactions on Intelligent Transportation Systems*, 14(2):871–882, 2013.

Hangchen Liu, Zheng Dong, Renhe Jiang, Jiewen Deng, Jinliang Deng, Quanjun Chen, and Xuan Song. Spatio-temporal adaptive embedding makes vanilla transformer sota for traffic forecasting. In *Proceedings of the 32nd ACM international conference on information and knowledge management*, pp. 4125–4129, 2023.

Xu Liu, Yutong Xia, Yuxuan Liang, Junfeng Hu, Yiwei Wang, Lei Bai, Chao Huang, Zhenguang Liu, Bryan Hooi, and Roger Zimmermann. Largest: A benchmark dataset for large-scale traffic forecasting. *Advances in Neural Information Processing Systems*, 36, 2024.

Ilya Loshchilov and Frank Hutter. SGDR: Stochastic gradient descent with warm restarts. In *International Conference on Learning Representations*, 2017. URL https://openreview.net/forum?id=Skq89Scxx.

Ilya Loshchilov and Frank Hutter. Decoupled weight decay regularization. In *International Conference on Learning Representations*, 2019. URL https://openreview.net/forum?id=Bkg6RiCqY7.

Iwao Okutani and Yorgos J Stephanedes. Dynamic prediction of traffic volume through kalman filtering theory. *Transportation Research Part B: Methodological*, 18(1):1–11, 1984.

Aaron van den Oord, Sander Dieleman, Heiga Zen, Karen Simonyan, Oriol Vinyals, Alex Graves, Nal Kalchbrenner, Andrew Senior, and Koray Kavukcuoglu. Wavenet: A generative model for raw audio. *arXiv preprint arXiv:1609.03499*, 2016.

Long Ouyang, Jeffrey Wu, Xu Jiang, Diogo Almeida, Carroll Wainwright, Pamela Mishkin, Chong Zhang, Sandhini Agarwal, Katarina Slama, Alex Ray, et al. Training language models to follow instructions with human feedback. *Advances in neural information processing systems*, 35: 27730–27744, 2022.

Razvan Pascanu, Tomas Mikolov, and Yoshua Bengio. On the difficulty of training recurrent neural networks. In *International conference on machine learning*, pp. 1310–1318. Pmlr, 2013.

Adam Paszke, Sam Gross, Francisco Massa, Adam Lerer, James Bradbury, Gregory Chanan, Trevor Killeen, Zeming Lin, Natalia Gimelshein, Luca Antiga, et al. Pytorch: An imperative style, high-performance deep learning library. *Advances in neural information processing systems*, 32, 2019.

Alec Radford, Karthik Narasimhan, Tim Salimans, Ilya Sutskever, et al. Improving language understanding by generative pre-training. *OpenAI blog*, 2018.

Alec Radford, Jeffrey Wu, Rewon Child, David Luan, Dario Amodei, Ilya Sutskever, et al. Language models are unsupervised multitask learners. *OpenAI blog*, 1(8):9, 2019.

Colin Raffel, Noam Shazeer, Adam Roberts, Katherine Lee, Sharan Narang, Michael Matena, Yanqi Zhou, Wei Li, and Peter J Liu. Exploring the limits of transfer learning with a unified text-to-text transformer. *Journal of machine learning research*, 21(140):1–67, 2020.

David E Rumelhart, Geoffrey E Hinton, and Ronald J Williams. Learning internal representations by error propagation, parallel distributed processing, explorations in the microstructure of cognition, ed. de rumelhart and j. mcclelland. vol. 1. 1986. *Biometrika*, 71:599–607, 1986.

Chao Shang, Jie Chen, and Jinbo Bi. Discrete graph structure learning for forecasting multiple time series. In *International Conference on Learning Representations*, 2021.

Zezhi Shao, Zhao Zhang, Fei Wang, and Yongjun Xu. Pre-training enhanced spatial-temporal graph neural network for multivariate time series forecasting. In *Proceedings of the 28th ACM SIGKDD conference on knowledge discovery and data mining*, pp. 1567–1577, 2022.

Alex J Smola and Bernhard Schölkopf. A tutorial on support vector regression. *Statistics and computing*, 14:199–222, 2004.

Chao Song, Youfang Lin, Shengnan Guo, and Huaiyu Wan. Spatial-temporal synchronous graph convolutional networks: A new framework for spatial-temporal network data forecasting. In *Proceedings of the AAAI conference on artificial intelligence*, volume 34, pp. 914–921, 2020.

Nitish Srivastava, Geoffrey Hinton, Alex Krizhevsky, Ilya Sutskever, and Ruslan Salakhutdinov. Dropout: a simple way to prevent neural networks from overfitting. *The journal of machine learning research*, 15(1):1929–1958, 2014.

Ilya Sutskever, Oriol Vinyals, and Quoc V Le. Sequence to sequence learning with neural networks. *Advances in neural information processing systems*, 27, 2014.

Hugo Touvron, Thibaut Lavril, Gautier Izacard, Xavier Martinet, Marie-Anne Lachaux, Timothée Lacroix, Baptiste Rozière, Naman Goyal, Eric Hambro, Faisal Azhar, et al. Llama: Open and efficient foundation language models. *arXiv preprint arXiv:2302.13971*, 2023.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. *Advances in neural information processing systems*, 30, 2017.

Billy M Williams and Lester A Hoel. Modeling and forecasting vehicular traffic flow as a seasonal arima process: Theoretical basis and empirical results. *Journal of transportation engineering*, 129:664–672, 2003.

Zonghan Wu, Shirui Pan, Guodong Long, Jing Jiang, and Chengqi Zhang. Graph wavenet for deep spatial-temporal graph modeling. In *Proceedings of the 28th International Joint Conference on Artificial Intelligence*, pp. 1907–1913, 2019.

Zonghan Wu, Shirui Pan, Guodong Long, Jing Jiang, Xiaojun Chang, and Chengqi Zhang. Connecting the dots: Multivariate time series forecasting with graph neural networks. In *Proceedings of the 26th ACM SIGKDD international conference on knowledge discovery & data mining*, pp. 753–763, 2020.

Chengxuan Ying, Tianle Cai, Shengjie Luo, Shuxin Zheng, Guolin Ke, Di He, Yanming Shen, and Tie-Yan Liu. Do transformers really perform badly for graph representation? *Advances in Neural Information Processing Systems*, 34:28877–28888, 2021.

Bing Yu, Haoteng Yin, and Zhanxing Zhu. Spatio-temporal graph convolutional networks: A deep learning framework for traffic forecasting. In *Proceedings of the 27th International Joint Conference on Artificial Intelligence (IJCAI)*, 2018.

Fisher Yu and Vladlen Koltun. Multi-scale context aggregation by dilated convolutions. In *ICLR*, 2016.

Chuanpan Zheng, Xiaoliang Fan, Cheng Wang, and Jianzhong Qi. Gman: A graph multi-attention network for traffic prediction. In *Proceedings of the AAAI conference on artificial intelligence*, volume 34, pp. 1234–1241, 2020.

Eric Zivot and Jiahui Wang. Vector autoregressive models for multivariate time series. *Modeling financial time series with S-PLUS®*, pp. 385–429, 2006.

A APPENDIX

A.1 Additional Implementation Details

To construct the sensor graph, we compute the pairwise road network distances between sensors and build the adjacency matrix using thresholded Gaussian kernel (Li et al., 2018). $W_{i,j} = \exp\left(-\frac{\text{dist}(v_i, v_j)^2}{\sigma^2}\right)$ if $\text{dist}(v_i, v_j) \leq \kappa$, otherwise 0, where $W_{i,j}$ is the edge distance between nodes i, j, and dist measures the physical distance between the nodes. σ is the standard deviation of the distances, and κ is the threshold for determining if an edge exists.

We also use the training dataset to Z-score normalize the entire dataset. In cases where the time of day information is available for the dataset, we concatenate it to the traffic speed measurement to enrich the input.

Besides the details mentioned in the main text, we also use gradient accumulation to increase batch size. This results in an effective batch size that is calculated by multiplying the original batch size by the number of GPUs (graphics processing units) used in distributed data parallelism and the number of accumulated gradient iterations. We also utilize layer-wise learning rate decay following (Raffel et al., 2020), where the learning rate decays exponentially in earlier layers. This is typically used to stabilize training when fine-tuning Transformer models. We find using gradient clipping and dropout improves T-Graphormer training as well (Srivastava et al., 2014).

We summarize our training configurations in Tables 4 and 5. All training has been done on SLURM workload manager environments. For T-Graphormer mini and small models (including causal mini and causal small), training was done on 4 compute nodes. Each compute node has 187 gigabytes of memory, 2 Intel Silver 4216 Cascade CPUs (central processing units), and 4 NVIDIA V100 Volta GPUs with 32 gigabytes of memory. For training the medium-sized models, we used 4 compute nodes with 498 gigabytes of memory, 2 AMD Milan 7413 CPUs, and 4 NVIDIA A100SXM4 GPUs with 40 gigabytes of memory. On the PEMS-BAY dataset, training validation and model checkpoint took an average of 7.5 hours for mini-sized models, 13.8 hours for small-sized models, and 10.0 hours for medium-sized models (due to GPU difference). On the METR-LA dataset, it took an average of 4.5 hours for mini-sized models, 8.5 hours for small-sized models, and 10.0 hours for medium-sized models. When training on the PEMS-BAY dataset, we also find that medium-sized models tend to overfit after 22 epochs, so we evaluate the saved models at the 22nd epoch. For per epoch training time on the METR-LA dataset, see Figure 8.

- Code: `https://anonymous.4open.science/r/t-graphormer/gmae_st/`
- Datasets (Li et al., 2018): `https://github.com/liyaguang/DCRNN`
- Pre-trained model weights: `https://drive.google.com/drive/folders/1xRyxP_K0y5NoMkwzXFIgdt-6elLo3xdK?usp=drive_link`

A.2 Additional Results

We also analyze the scalability of the models by evaluating their performances on the testing dataset. The results for the best-performing models with configurations listed in section 5.2 are shown in

Configuration	Model					
	mini	small	medium	causal mini	causal small	causal medium
optimizer	AdamW (Loshchilov & Hutter, 2019)					
optimizer momentum	$\beta_1, \beta_2 = 0.9, 0.999$					
learning rate schedule	cosine decay (Loshchilov & Hutter, 2017)					
hidden dimension (d)	128	192	384	128	192	384
epochs	50	50	30	50	50	30
learning rate	1.50e-3	3.00e-3	1.25e-3	1.25e-3	1.50e-3	1.50e-3
gradient clipping	1.0	1.0	1.0	1.0	1.0	1.0
weigh decay	1e-4	1e-4	1e-4	1e-4	1e-4	1e-5
warmup epochs	10	10	10	10	10	10
batch size	128	96	96	128	96	96
dropout	0.1	0.1	0.1	0.1	0.1	0.1
layer-wise decay	0.90	0.75	0.90	0.90	0.90	0.90
# of parameters (M)	1.76	4.44	19.61	1.91	4.76	20.91

Table 4: Best training hyperparameters of T-Graphormer on PEMS-BAY dataset.

Configuration	Model					
	mini	small	medium	causal mini	causal small	causal medium
optimizer	AdamW (Loshchilov & Hutter, 2019)					
optimizer momentum	$\beta_1, \beta_2 = 0.9, 0.999$					
learning rate schedule	cosine decay (Loshchilov & Hutter, 2017)					
hidden dimension (d)	128	192	384	128	192	384
epochs	100	100	100	100	100	30
learning rate	4.50e-3	1.25e-3	1.50e-3	4.85e-3	5.85e-3	1.00e-3
gradient clipping	5.0	5.0	5.0	5.0	5.0	5.0
weigh decay	1e-5	1e-5	1e-4	1e-5	1e-6	1e-6
warmup epochs	30	30	30	30	30	30
batch size	128	128	128	128	128	128
dropout	0.1	0.1	0.1	0.1	0.1	0.1
layer-wise decay	0.90	0.90	0.90	0.90	0.90	0.90
# of parameters (M)	1.57	4.15	19.04	1.68	4.48	20.34

Table 5: Best training hyperparameters of T-Graphormer on METR-LA dataset.

Dataset	Model	Horizon 3			Horizon 6			Horizon 12		
		MAE	RMSE	MAPE (%)	MAE	RMSE	MAPE	MAE	RMSE	MAPE (%)
PEMS-BAY	**mini**	**1.31**	**2.55**	**2.71**	**1.51**	**3.14**	**3.25**	**1.76**	**3.78**	**3.91**
	small	**1.31**	2.66	2.77	1.54	3.33	3.37	1.79	3.99	4.04
	medium	**1.31**	2.62	2.76	1.53	3.22	3.32	1.77	3.85	3.99
	causal mini	1.33	**2.55**	2.91	1.58	3.19	3.56	1.84	3.84	4.27
	causal small	1.35	2.78	3.01	1.60	3.52	3.69	1.88	4.21	4.44
	causal medium	1.90	4.14	4.65	2.00	4.35	4.90	2.13	4.64	5.25
METR-LA	mini	2.69	5.76	6.75	3.01	6.65	7.60	3.52	7.92	8.88
	small	2.70	5.98	6.53	3.06	7.03	7.54	3.62	8.42	9.01
	medium	2.69	5.86	6.75	3.02	6.77	7.65	3.50	7.98	8.96
	causal mini	**2.67**	5.37	**6.65**	**2.94**	**5.98**	**7.46**	**3.35**	**6.92**	**8.61**
	causal small	2.70	**5.30**	6.96	3.01	6.06	7.91	3.45	7.06	9.20
	causal medium	2.91	6.06	7.19	3.33	7.11	78.36	3.96	8.73	9.98

Table 6: Additional spatiotemporal forecasting results on two traffic network datasets. The row with the best metric for each prediction length is bolded. The overall best-performing model for each dataset is also bolded.

Figure 3: T-Graphormer prediction visualization on the PEMS-BAY dataset. It is evident that T-Graphormer can learn the dynamic and complex traffic patterns between different traffic intersections.

Table 6. We confirm that on both datasets, models with added causal dilated convolution in their final prediction layers scale poorly. Specifically, the "causal mini" models consistently outperform the "causal small" models which outperform the "causal medium" model. This might be due to the added spatiotemporal bias in dilated causal convolution, which leads to easier overfitting as the model size grows. Another possible explanation is that since we fix the number of dilated convolution layers (3 layers with a dilation factor of 2) across model sizes, the larger embedding sizes in these models may require more dilated convolution layers to fully capture the context of the learned representations. In other words, the number of dilated convolution layers should grow with the embedding size.

Conversely, models with a simple linear final prediction layer scale better in the PEMS-BAY dataset where the "medium" models perform the second best, and the "small" models perform the third best. However, this comparison is not entirely fair since there are inconsistencies in our training configurations for medium-sized models. Specifically, we found that early-stopping and training the medium-sized models for 30 epochs instead of 50 works better on the PEMS-BAY dataset.

Finally, T-Graphormer prediction layer variants perform differently on the two datasets. The best-performing model on METR-LA utilizes causal dilated convolutions in its prediction layer. While this increases the number of parameters, we theorize that the additional temporal bias introduced by causal convolutions improves the model's prediction accuracy under limited training samples. However, it remains unclear why linear prediction layers perform poorly on the METR-LA dataset and why casual prediction layers perform poorly on the PEMS-BAY dataset.

Figure 4: T-Graphormer prediction visualization on the METR-LA dataset. It is evident that T-Graphormer can learn the different traffic patterns between different traffic intersections. For instance, although all nodes have decreased traffic speed at around hour 15 and hour 38, the rush hour behaviour is unique to each node. It is also evident that T-Graphormer recognizes node 141 has an additional traffic speed drop at around hour 5. Note that there are multiple time steps of missing values. It has become common practice to pad these missing values with the historical mean during data preprocessing, which is not done in this work.

(a) PEMS-BAY   (b) METR-LA

Figure 5: Training and validation loss of the best-performing models on two traffic prediction datasets. For model Training loss is plotted as the global average per epoch, and validation loss is computed as the average per epoch. Both losses are mean squared errors. For PEMS-BAY, the gap between training and validation is much closer than that of METR-LA.

(a) PEMS-BAY (b) METR-LA

Figure 6: Validation metrics on two traffic prediction datasets. The best-performing model is displayed.

(a) PEMS-BAY (b) METR-LA

Figure 7: Mean squared error differences of the best-performing models on the respective training and validation dataset. Compared to the mini and small models, the medium model on PEMS-BAY only has 30 epochs since it is the best configuration we found.

(a) Causal Prediction Layer   (b) Vanilla Prediction Layer

Figure 8: Performance comparison on the METR-LA traffic prediction dataset between masked self-supervised pre-training and training from scratch. Three masking ratios are evaluated for each prediction layer architecture. Each data point represents one epoch on the validation set. For pre-trained methods, the wall-clock time is calculated by adding the total pre-training time to the per-epoch training time (129 seconds for the vanilla prediction layer and 137 seconds for the causal prediction layer). Notably, higher masking ratios result in reduced pre-training time due to fewer tokens per batch. Since the METR-LA dataset is quite small, further experiments on larger datasets are needed to demonstrate the full pre-training potential.