Deep Learning Solution of the Eigenvalue Problem for Differential Operators

Abstract

Solving the eigenvalue problem for differential operators is a common problem in many scientific fields. Classical numerical methods rely on intricate domain discretization, and yield non-analytic or non-smooth approximations. We introduce a novel Neural Network (NN)-based solver for the eigenvalue problem of differential self-adjoint operators where the eigenpairs are learned in an unsupervised end-to-end fashion. We propose three different training procedures, for solving increasingly challenging tasks towards the general eigenvalue problem. The proposed solver is able to find the M smallest eigenpairs for a general differential operator.

We demonstrate the method on the Laplacian eigenproblem which is of particular interest in image processing, computer vision, shape analysis among many other applications. Unlike other numerical methods such as finite differences, the partial derivatives of the network approximation of the eigenfunction can be analytically calculated to any order. Therefore, the proposed framework enables the solution of higher order operators and on free shape domain or even on a manifold. Non-linear operators can be investigated by this approach as well.

1 Introduction

Eigenfunctions and eigenvalues of the Laplacian (among other operators) are important in various applications ranging, inter alia, from image processing to computer vision and shape analysis. It is also of major importance in various engineering applications where resonance is crucial for design and safety Benouhiba & Belyacine (2013). Additionally, Laplacian eigenfunctions allow us to perform spectral analysis of data measured at more general domains or even on graphs and networks Shi & Malik (2000). In this paper we present a novel numerical method for the computation of these eigenfunctions (efs) and eigenvalues (evs), where the efs are parameterized by NNs with continuous activation functions, and the evs are directly calculated via the Rayleigh quotient. The resulting efs are therefore *smooth* functions defined in a parametric way. This is in contrast to the finite element Pradhan & Chakraverty (2019) and finite difference SADD (2005) methods in which the efs are defined on either a grid or as piecewise linear/polynomial functions with limited smoothness.

Following Bar & Sochen (2019), we suggest an unsupervised approach to learn the eigenpairs of a differential operator on a specified domain with boundary conditions, where the network approximates the eigenfunction at every entry x. The method is based on a uniformly distributed point set which is trained to satisfy two fidelity terms of the eigenvalue problem formulated as the L_2 and L_∞-like norms, boundary conditions, orthogonality constraint and regularization.

There are several advantages of the proposed setting: (i) the framework is general in the sense that it can be used for non linear differential operators with high order derivatives as well. (ii) Since we sample the domain with a point cloud, we are not limited to standard domains. The problem can be therefore solved in an arbitrary regular domain. (iii) The framework is generic such that additional constraints and regularizers can be naturally integrated in the cost function. The method is applied in 1D and 2D for both known and multiple unknown eigenvalues of the Laplacian operator. Quantitative analysis demonstrates the robustness of the method compared with the classical inverse power method.

2   RELATED WORK

2.1   PDEs AND ODEs WITH NEURAL NETWORKS

Many recent approaches have shown promise in using the power of NNs to approximate solutions of differential equations. Classical methods are often prone to weakness due to the discretization of the domain Ω. In Bar & Sochen (2019), the authors propose a solver for both forward and inverse problems, using NNs to model the solution, and penalizing using both the automatic differentiation, and boundary conditions. In Raissi et al. (2017), a similar approach was taken to solve both continuous and discrete time models. In Chen et al. (2018), differential equation solvers are used as part of the network architecture, and are shown to enhance the smoothness and convergence of the solutions.

In order to properly solve differential equations, a representation that captures high-order derivatives is desired. Recently, Sitzmann et al. (2020) proposed a network architecture that illustrates these requirements using periodic activation functions with the proper initialization. Additionally, Rippel et al. (2015) proposed leveraging Discrete Fourier Transform (DFT) to represent the network in spectral space.

2.2   THE FUNCTIONAL EIGENVALUE PROBLEM

The well-known power method and its variants Eastman & Estep (2007) has been the main method for addressing the eigenvalue problem. The method works on specific *Linear* operators, $\mathcal{L} : L_2(\mathbb{R}^d) \to L_2(\mathbb{R}^d)$. Erickson et al. (1995) showed the usage of the power method for spectral operators on Hilbert Spaces. Hait-Fraenkel & Gilboa (2019) proposed a modified method for non-linear differential operators. Furthermore, most power method variants for operators, converge to a single eigenpair. Finding the M smallest eigenpairs can be both computationally and algorithmically challenging.

3   PRELIMINARIES

Let $\mathcal{H}$ be a Hilbert space where the inner product for $u, v \in \mathcal{H}$ is (u, v). Let $A \in O(\mathcal{H})$ be an operator. Let A^* be the adjoined operator defined by $(A^*u, v) = (u, Av) \ \forall u, v \in \mathcal{H}$. Then A is said to be self-adjoint if $A = A^*$. We start with a short Lemma on self-adjoint operators Conway (1985).

Lemma 3.1 *Let $\mathcal{H}$ be a Hilbert space. Let $A \in O(\mathcal{H})$ be a self-adjoint operator. Then all eigenvalues of A are real.*

In this work we focus on self-adjoint operators. An eigenpair is defined as: (u, λ) s.t. $\lambda \in \mathbb{R}$, where u is the eigenfunction and λ is the corresponding eigenvalue. Let $\mathcal{L}$ be a self-adjoint operator $\mathcal{L} : L_2(\mathbb{R}^d) \to L_2(\mathbb{R}^k)$. Our objective is to search for eigenpairs $\{u_i, \lambda_i\}$ such that

$$\mathcal{L}u_i + \lambda_i u_i = 0 \ \forall i. \tag{1}$$

The proposed algorithm approximates the eigenfunction set $u_i(x)$ by a NN $u_i(x; w_{u_i})$ parameterized by w_{u_i}. The input to the network is $x \in \mathbb{R}^d$, one input node for each dimension. The network consists of several fully connected layers with an activation function, and a linear sum in the last layer. The network parameters are optimized to minimize a cost function which consists of the following elements: L_2 and L_∞-like fidelity terms which enforce equation 1 to be satisfied within the domain Ω, boundary conditions constraints and optional regularizers. This method can be regarded as an unsupervised regression, since the network output is a real-valued number, and the learning procedure does not use any ground truth solutions for training.

4   SINGLE KNOWN EIGENVALUE

We first address the problem of finding a single eigenfunction $u(x)$ given its corresponding eigenvalue λ. We approximate $u(x)$ by a NN and optimize the following cost function

$$\mathcal{F}_1\left((u(x, w_u)\right) = \alpha\|\mathcal{T}u\|_2^2 + \mu\|\mathcal{T}u\|_\infty + \delta\|u - u_0\|_{1,\partial\Omega} + \beta\Big|\|u\|_2^2 - c\Big| + \rho\|w_u\|_2^2, \tag{2}$$

Figure 1: The solution to $u'' + 4u = 0$ with $u(0) = u(\pi/2) = 0$ at iterations (from left to right) 1, 100 and 2500. At the last iteration RMSE = $6.52e - 04$ and PSNR=28.84.

where
$$\mathcal{T}u := \mathcal{L}u + \lambda u,$$
with the Laplacian operator
$$\mathcal{L} = \Delta.$$
The first two terms in equation 2 are the L_2 and L_∞ fidelity terms where the latter promotes a *pointwise* solution such that the equation is satisfied for isolated points as well Bar & Sochen (2019). The third term imposes boundary conditions and the forth normalizes the squared length of u to $c = 1$ due to scale invariance of the eigenfunction (since $(\alpha u, \lambda)$ is a valid eigenpair for $\alpha \neq 0$). The final term is the standard weight decay term which stabilizes the network weights. The L_2 norm $\|.\|_2^2$ is defined as the Monte-Carlo Integral approximation norm:

$$\|u\|_2^2 = \frac{\text{Vol}(\Omega)}{N} \sum_{x=x_1}^{x_N} |u(x)|^2 \sim \int_\Omega |u(x)|^2 dx. \tag{3}$$

In the first example we apply the Laplacian operator in 1D where $\lambda = 4$ and $u(0) = u(\pi/2) = 0$. Then,
$$\mathcal{T}u = u''(x) + 4u(x).$$
The normalized analytical solution is therefore

$$u(x) = \frac{2}{\sqrt{\pi}} \sin(2x).$$

Figure 1 demonstrates the outcome of the algorithm at iterations 1, 100 and 2500. As can be seen, the approximated solution approaches the $\sin$ function with Relative Mean Square Error (RMSE)=$6.52e - 04$ and peak signal-to-noise ratio (PSNR)=28.84.

5 SINGLE EIGENPAIR WITH THE SMALLEST EIGENVALUE

Next, we address the case where the eigenvalue is not known in advance. We therefore constrain ourselves to the smallest nontrivial eigenpair. This approach is analogue to power method approach, where only one dominant eigenpair is found. Recall the Rayleigh quotient defined as Miller (2016), Feld et al. (2019)

$$R(u) := -\frac{(\mathcal{L}u, u)}{(u, u)}. \tag{4}$$

It can be shown that the eigenfunction u is a critical point of $R(u)$, where $R(u)$ is its corresponding (nontrivial) eigenvalue λ. Furthermore, if $\tilde{u}$ is a function which is close to u then $R(\tilde{u})$ approximates λ. In the following cost function we replace λ by $R(u)$. Then equation 2 is modified to

$$\mathcal{F}_2(u(x, w_u)) = \alpha\|\mathcal{T}u\|_2^2 + \mu\|\mathcal{T}u\|_\infty + \delta\|u - u_0\|_{1,\partial\Omega} + \beta\big|\|u\|_2^2 - c\big| + \rho\|w_u\|_2^2 + \gamma\|R(u)\|_2^2, \tag{5}$$

where
$$\mathcal{T}u = \mathcal{L}u + R(u)u.$$
The last term minimizes $R(u)$ and therefore attracts the solution to the lowest nontrivial eigenvalue. The ground truth eigenpair is given by $\left(\sqrt{\frac{2}{\pi}}\sin(x), 1\right)$ for $\Omega = [0, \pi]$. Figure 2 shows the outcome

Figure 2: The solution to $u'' + \lambda u = 0$ with $u(0) = u(\pi) = 0$ at iterations $1, 500$ and 1000. The associated eigenvalues are $\lambda = 70 \pm 53,\ 5.5 \pm 0.5,\ 1 \pm 0.03$. Note that the solution is up to a sign.

of the proposed method at three iterations. The approximated eigenfunction is obtained up to a sign. The eigenvalue which is the value of the Rayleigh quotient converges to the true value $\lambda = 1$ with decreasing standard deviation along the mini-batches. Quantitative results are shown in row 1 of tables 1 and 2 where MAE stands for Mean Absolute Error and MRE for Mean Relative Error.

6   MULTIPLE EIGENPAIRS WITH THE SMALLEST EIGENVALUES

A generalization of the former case is to find M eigenpairs with the corresponding bottom-M eigenvalues. Following Hait-Fraenkel & Gilboa (2019), and using the orthogonality property of the eigenfunctions we optimize the following cost function:

$$\mathcal{F}_3(\mathbf{u}, (x, w_u)) = \sum_{i=1}^{M} \left(\alpha \|\mathcal{T} u_i\|_2^2 + \mu \|\mathcal{T} u_i\|_\infty + \delta \|u_i - u_0\|_{1,\partial\Omega} + \beta \left| \|u_i\|_2^2 - c \right| + \gamma_i \|R(u_i)\|_2^2 \right)$$
$$+ \rho \|w_u\|_2^2 + \nu \sum_{i<j} (u_i, u_j).$$

(6)

For each eigenfunction u_i we impose the L_2 and L_∞ terms, boundary conditions and normalization as before. The weight of the Rayleigh quotient is multiplied by $\gamma_i = 1/i$ since we want a monotonic penalty of the size of λ_i. The last term enforces the orthogonality of distinct eigenfunctions. Figure 3 demonstrates the outcome of the algorithm in the one dimensional case. In this case we have one network with M output values, one for every eigenfunctuion. The ground truth eigenfunctions of the Laplacian with $u(0) = u(\pi) = 0$ are given by

$$u_n(x) = \sqrt{\frac{2}{\pi}} \sin(nx),\ \lambda_n = n^2,\ n = 1, 2, 3, \ldots \quad .$$

The left panel of Figure 3 shows the results for $M = 3$ and in the right for $M = 4$. The right figure in the right panel shows the convergence of the four eigenvalues which as expected have the values $1, 4, 9$ and 16. Quantitative results are summarized in tables 1 and 2.

Next, we tested the method in two-dimensions where we trained M different networks simultaneously, each with a single output, one for each eigenfunction. We found this architecture adequate for the multiple eigenpairs problem in the 2D case. The ground truth solution is then

$$u_{nm}(x, y) = \frac{2}{\pi} \sin(nx) \sin(my),\ \lambda_{nm} = n^2 + m^2,\ n, m = 1, 2, 3 \ldots$$

for $\Omega = [0, \pi]^2$ and $u(x, 0) = u(x, \pi) = u(0, y) = u(\pi, y) = 0$. Figure 4 shows the results at different iterations for $M = 1$. The expected eigenvalue is the lowest one ($n = 1,\ m = 1$).

Figure 3: Left panel: eigenfunctions for $M = 3$. Right panel: eigenfunctions for $M = 4$ are shown on the left and the convergence of the eigenvalues are shown on the right. Clearly the convergence of the functions are $u_n(x) = \sqrt{\frac{2}{\pi}} \sin(nx)$, $\lambda_n = n^2$, up to a sign.

Table 1: Dimension= 1, Eigenfunction Error Analysis

M	Mean PSNR (per ef.)	Mean RMSE (per ef.)
1	28.84	1.30e-3
2	56.58	2.21e-6
3	52.21	8.54e-6
4	48.78	2.05e-5

Table 2: Dimension= 1, Eigenvalue Error Analysis

M	Ground Truth	Predicted	Mean MAE (per ev.)	Mean MRE (per ev.)
1	1	1.02	0.02	0.02
2	1, 4	1.11, 4.09	0.10	0.07
3	1, 4, 9	1.08, 8.93, 4.13	0.09	0.04
4	1, 4, 9, 16	1.12, 4.09, 9.03, 15.95	0.07	0.04

Figure 4: The solution to the 2D Laplace eigevalue problem, with $M = 1$ at iterations (from left to right) 1, 100 and 1000.

Figure 5: The solution to the 2D Laplace eigenvalue problem for $M = 4$. The Iterations $1, 100, 1000$ are shown from top to bottom, for each of the 4 eigenfunctions.

As the algorithm converges, the expected eigenfunction is clearly seen (right image). We further tested our performance for $M = 4$, see Figure 5. The figures from left to right stand for the four eigenfunctions. The rows from top to bottom are iterations 1, 500 and 1000 respectively. As can be easily shown, these results are with accordance with the theoretical eigenfunctions $(n, m) = (1, 1), (1, 2), (2, 1), (2, 2)$. Quantitative results are summed up in tables 3 and 4 where SSIM stands for structural similarity index measure.

7 COMPARISON TO THE INVERSE POWER METHOD

The power method is a well known iterative algorithm where given a diagonalizable matrix A the algorithm finds the maximal eigenvalue and its corresponding eigenfunction, while the inverse power method finds the lowest one Bronson et al. (2014). We adopted the inverse power method to our problem following Bozorgnia (2016), where the Laplacian operator replaces the matrix A and the eigenfunction u was discretized with spacing h. Figure 6 shows the outcome of the inverse power method implemented in Matlab with $h = 0.03$ and initial eigenvalue $\lambda_0 = 1$ in two dimensions. On the left is the estimated eigenfunction which corresponds to the lowest eigenvalue ($m = 1$, $n = 1$).

Figure 6: Inverse power method. Left: Approximated eigenfunction, Middle: error $|u_{gt} - u|$. Right: convergence of the eigenvalue. $\lambda = 2.02$, RMSE=8.76e$-$3, PSNR=20.57, SSIM=0.99

Table 3: Dimension= 2, Eigenfunction Error Analysis

M	Mean PSNR(per ef.)	Mean SSIM(per ef.)	Mean RMSE(per ef.)
1	36.67	0.93	2.14e-4
2	31.66	0.8980	1.33e-3
3	24.84	0.8368	3.92e-3
4	18.97	0.5234	1.52e-1

In the middle is the error $|u_{gt}(x, y) - u(x, y)|$ and in the right is the convergence plot of the eigenvalue which was converged to 2.02. The Laplacian operator was discretized by finite differences. In our experiments the algorithm seemed to be sensitive to discretization and initialization. Table 5 shows the performance of the proposed algorithm compard with the inverse power method. Better results in obtained in almost all quantitative measures. Furthermore, the inverse power method finds only a *single* eigenpair, while the proposed method outputs the M smallest eigenpairs.

8 IMPLEMENTATION DETAILS

Our network was constructed as 5 hidden layers architecture, each with a varying number of neurons, from $26 - 100$. Our code was implemented in PyTorch. Each of our models was trained for 5000 iterations on NVIDIA QUADRO RTX-5000 Graphics card.

As for the activation function, since we are modeling smooth functions, we found that *ReLU* and its variants were less suitable both theoretically and experimentally. For the 1D experiments we used the tanh activation function, and in the 2d experiments we used the *SIREN* Sitzmann et al. (2020)

Table 4: Dimension= 2, Eigenvalue Error Analysis

M	GT	Predicted	MAE	MRE	Rayleigh Quotient std
1	2	2.01	0.0073	0.0037	0.0170
1	2	1.99	0.05	0.01	0.0432
	5	4.91			
3	2	1.94	0.07	0.019	0.0603
	5	5.08			
	5	4.93			
4	2	1.98	0.0490	0.0093	0.0234
	5	4.93			
	5	4.96			
	8	7.91			

Table 5: Comparison to the Inverse Power Method where $\lambda_{gt} = 2$

	λ	PSNR	SSIM	RMSE
Inverse power method	2.02	20.57	**0.99**	8.76e$-$3
Proposed	**2.01**	**36.67**	0.93	**2.14e$-$4**

activation function. The *SIREN* activation has been shown to excel in modeling complex signals, and their higher-order derivatives.

We used an Adam optimizer Kingma & Ba (2014) with default parameters. A Starting LR (Learning Rate) of 4e$-$3 was used such that it was reduced every 100 epochs by the factor of 0.7 until the min LR reached 5e$-$5.

We found that the weight initialization Kunin (2019) was important for convergence. In our 1D experiments a Gaussian initialization with 0.0 mean and 1.0 std was used. In the 2D experiments, we used the standard initialization proposed in Sitzmann et al. (2020).

Our hyperparameters were set as follows: $\alpha = 1e-1, \mu = 1e-1, \delta = 5e-1, \beta = 1.5, c = 1, \rho = 1e-8, \gamma_i = \frac{1}{i}, \nu = 2$. Our point set consisted of $45,000$ inner-points, and 1200 boundary points. In the one-dimensional case, the boundary conditions had two actual points. In the two-dimensional case, points were taken along the boundary of the square. Instead of using an exact $\|\mathcal{T}u\|_\infty$, we used a relaxed approximation: $\frac{\mu}{K} \sum_{k\in\text{top}_K(|L_i|)} |L_k|$, with $K = 40$ for broader effect of the L_∞ fidelity term.

9   CONCLUSION

Interesting works have been recently published in the field of solving ODEs and PDEs with NNs Raissi et al. (2017), Flamant et al. (2020), Bar & Sochen (2019), Chen et al. (2018), Sitzmann et al. (2020), Sirignano & Spiliopoulos (2018). We propose a novel method to exploit these new innovations, along with specific constraints that exist in the mathematical nature of such problems, and shed some light on the well-known eigenvalue problem.

Finding eigenpairs of both linear and non-linear differential operators is a problem that appears in many different areas in science and in many problems that arise in nature Qua (1976) Jos R. Lpez-Blanco (2013). Due to the possible complex nature of such operators, finding a robust method for solving this problem is challenging. Additionally, most such problems do not necessarily have a rectangular domain, and will therefore make the task more difficult across methods. Our method fits any free-form domain, and is able to alleviate these constraints. Furthermore, the proposed method can be used in principle on higher order, non-linear operators and on higher dimensional manifolds.

When using the Rayleigh quotient to learn both the eigenfunction and its corresponding eigenvalue, the end-to-end learning process seems to assist the convergence, each acting as a constraint towards the other. When learning multiple eigenpairs at once, the orthogonality term eliminates degeneration. Empirically, it seems that these constraints also assist both the efs and the evs to converge towards more accurate solutions. This suggests that the orthogonality term serves as a regularizer on each eigenpair during the training process.

The training process produces *smooth* solutions, due to the fact that the networks are composed of linear layers and smooth activation functions (namely *tanh* and *SIREN*). Since these solutions are deterministic and parameterized by the learned weights, they are infinitely differentiable. The fact that the solution is given in an explicit form, enables to carry differentiation analytically with no approximation involved.

Rigorous analysis of the approximation error and its relation to the network architecture and design are under current study. Future research includes higher dimensions and non-linear operators, non-uniform point sampling and generalization to non self-adjoint operator with complex eigenpairs.

REFERENCES

Quantum mechanics. In A. S. Davydov (ed.), *Quantum Mechanics. Translated, edited, and with additions by D. ter Haar (2nd ed.)*, pp. 237 – 288. Oxford: Pergamon Press, second edition, 1976.

L. Bar and N. Sochen. Unsupervised deep learning algorithm for PDE-based forward and inverse problems. *arXiv 1904.05417v1*, 2019.

N. Benouhiba and Z. Belyacine. On the solutions of the (p,q)-laplacian problem at resonance. *Nonlinear Analysis*, 77, 2013.

F. Bozorgnia. Convergence of inverse power method for first eigenvalue of p-laplace operator. *Numerical Functional Analysis and Optimization*, 37, 2016.

Richard Bronson, Gabriel B. Costa, and John T. Saccoman. Chapter 4 - eigenvalues, eigenvectors, and differential equations. In Richard Bronson, Gabriel B. Costa, and John T. Saccoman (eds.), *Linear Algebra (Third Edition)*, pp. 237 – 288. Academic Press, third edition edition, 2014. ISBN 978-0-12-391420-0. doi: https://doi.org/10.1016/B978-0-12-391420-0.00004-4. URL `http://www.sciencedirect.com/science/article/pii/B9780123914200000044`.

Ricky T. Q. Chen, Yulia Rubanova, Jesse Bettencourt, and David K Duvenaud. Neural ordinary differential equations. In S. Bengio, H. Wallach, H. Larochelle, K. Grauman, N. Cesa-Bianchi, and R. Garnett (eds.), *Advances in Neural Information Processing Systems 31*, pp. 6571–6583. Curran Associates, Inc., 2018. URL `http://papers.nips.cc/paper/7892-neural-ordinary-differential-equations.pdf`.

John B. Conway. *A Course in Functional Analysis*. Springer-Verlag New York, 1985.

S. Eastman and D. Estep. A power method for nonlinear operators. *Applicable Analysis*, 86(10): 1303–1314, 2007. doi: 10.1080/00036810701667305. URL `https://doi.org/10.1080/00036810701667305`.

M. A. Erickson, R. S. SMITH, and A. J. LAUB. Power methods for calculating eigenvalues and eigenvectors of spectral operators on hilbert spaces. *International Journal of Control*, 62(5): 1117–1128, 1995. doi: 10.1080/00207179508921586. URL `https://doi.org/10.1080/00207179508921586`.

Tal Feld, Jean-François Aujol, Guy Gilboa, and Nicolas Papadakis. Rayleigh quotient minimization for absolutely one-homogeneous functionals. *Inverse Problems*, 2019.

Cedric Flamant, Pavlos Protopapas, and David Sondak. Solving Differential Equations Using Neural Network Solution Bundles. *arXiv e-prints*, art. arXiv:2006.14372, June 2020.

E. Hait-Fraenkel and G. Gilboa. Numeric solutions of eigenvalue problems for generic nonlinear operators. *arXiv 1909.12775*, 2019.

Jos I. Aliaga et. al Jos R. Lpez-Blanco, Ruymn Reyes. Exploring large macromolecular functional motions on clusters of multicore processors. *Journal of Computational Physics*, 246, 2013.

Diederik P. Kingma and Jimmy Ba. Adam: A Method for Stochastic Optimization. *arXiv e-prints*, art. arXiv:1412.6980, December 2014.

Katanforoosh Kunin. Initializing neural networks, 2019.

G. Miller. *Spectral Graph Theory and The Laplacian Paradigm, Lecture 27*, 2016. `http://www.cs.cmu.edu/afs/cs/academic/class/15859n-f16/Handouts/TrefethenBau/RayleighQuotient-27.pdf`.

Karan Kumar Pradhan and Snehashish Chakraverty. Chapter four - finite element method. In Karan Kumar Pradhan and Snehashish Chakraverty (eds.), *Computational Structural Mechanics*, pp. 25 – 28. Academic Press, 2019. ISBN 978-0-12-815492-2. doi: https://doi.org/10.1016/B978-0-12-815492-2.00010-1. URL `http://www.sciencedirect.com/science/article/pii/B9780128154922000101`.

Maziar Raissi, Paris Perdikaris, and George Em Karniadakis. Physics Informed Deep Learning (Part I): Data-driven Solutions of Nonlinear Partial Differential Equations. *arXiv e-prints*, art. arXiv:1711.10561, November 2017.

Oren Rippel, Jasper Snoek, and Ryan P. Adams. Spectral Representations for Convolutional Neural Networks. *arXiv e-prints*, art. arXiv:1506.03767, June 2015.

MARTIN H. SADD. 5 - formulation and solution strategies. In MARTIN H. SADD (ed.), *Elasticity*, pp. 83 – 102. Academic Press, Burlington, 2005. ISBN 978-0-12-605811-6. doi: https://doi.org/10.1016/B978-012605811-6/50006-3. URL http://www.sciencedirect. com/science/article/pii/B9780126058116500063.

J. Shi and J. Malik. Normalized cuts and image segmentation. *IEEE TRANSACTIONS ON PATTERN ANALYSIS AND MACHINE INTELLIGENCE*, 22, 2000.

J. Sirignano and K. Spiliopoulos. DGM: A deep learning algorithm for solving partial differential equations. *Journal of Computational Physics*, 375:1339–1364, December 2018. doi: 10.1016/j. jcp.2018.08.029.

Vincent Sitzmann, Julien N. P. Martel, Alexand er W. Bergman, David B. Lindell, and Gordon Wetzstein. Implicit Neural Representations with Periodic Activation Functions. *arXiv e-prints*, art. arXiv:2006.09661, June 2020.