CREATING TRAINING SETS VIA WEAK INDIRECT SUPERVISION

ABSTRACT

Creating labeled training sets has become one of the major roadblocks in machine learning. To address this, recent *Weak Supervision (WS)* frameworks synthesize training labels from multiple potentially noisy supervision sources. However, existing frameworks are restricted to supervision sources that share the same output space as the target task. To extend the scope of usable sources, we formulate *Weak Indirect Supervision (WIS)*, a new research problem for automatically synthesizing training labels based on *indirect supervision sources* that have different output label spaces. To overcome the challenge of mismatched output spaces, we develop a probabilistic modeling approach, PLRM, which uses user-provided label relations to model and leverage indirect supervision sources. Moreover, we provide a theoretically-principled test of the distinguishability of PLRM for unseen labels, along with an generalization bound. On both image and text classification tasks as well as an industrial advertising application, we demonstrate the advantages of PLRM by outperforming baselines by a margin of 2%-9%.

1 INTRODUCTION

One of the greatest bottlenecks of using modern machine learning models is the need for substantial amounts of manually-labeled training data. In real-world applications, such manual annotations are typically time-consuming, labor-intensive and static. To reduce the efforts of annotation, researchers have proposed Weak Supervision (WS) frameworks (Ratner et al., 2016; 2018; 2019; Fu et al., 2020) for synthesizing labels from multiple *weak supervision sources*, *e.g.*, heuristics, knowledge bases, or pre-trained classifiers. These frameworks have been widely applied on various machine learning tasks (Dunnmon et al., 2020; Fries et al., 2021; Safranchik et al., 2020; Lison et al., 2020; Zhou et al., 2020; Hooper et al., 2021; Zhan et al., 2019; Varma et al., 2019) and industrial data (Bach et al., 2019). Among them, *data programming* (Ratner et al., 2016), one representative example that generalizes many approaches in the literature, represents weak supervision sources as *labeling functions (LFs)* and synthesizes training labels using Probabilistic Graphical Model (PGM).

Given both the increasing popularity of WS and the general increase in open-source availability of machine learning models and tools, there is a rising tide of available supervision sources that WS frameworks and practitioners could potentially leverage, including pre-trained machine learning models or prediction APIs (Chen et al., 2020; d'Andrea & Mintz, 2019; Yao et al., 2017). However, existing WS frameworks only utilize weak supervision sources with the same label space as the target task. This incompatibility largely limits the scope of usable sources, necessitating manual effort from domain experts to provide supervision for *unseen* labels. For example, consider target task of classifying {"*dog*", "*wolf*", "*cat*", "*lion*"} and a set of three weak supervision sources (e.g. trained classifiers or expert heuristics) with disjoint output spaces {"*caninae*", "*felidae*"}, {"*domestic animals*", "*wild animals*"} and {"*husky*", "*bengal cat*"} respectively. We call these types of sources *indirect supervision sources*. For concreteness, we follow the general convention of *data programming* (Ratner et al., 2016) and refer to these sources as *indirect labeling functions (ILFs)*. Despite their apparent utility, existing weak supervision methods could not directly leverage such ILFs, as their output spaces have no overlap with the target one.

In this paper, we formulate a novel research problem that aims to leverage such ILFs automatically, minimizing the manual efforts to develop and deploy new models. We refer to this as the *Weak Indirect Supervision (WIS)* setting, a new Weak Supervision paradigm which leverages only ILFs, along with

some partial knowledge of the relational structures between individual labels, to automatically create labeled training sets.

The key difficulty of leveraging ILFs is due to the mismatched label spaces. To overcome this, we introduce pairwise relations between individual labels to the WIS setup, which are often available in structured sources (e.g. off-the-shelf Knowledge Bases (Miller, 1995; Sinha et al., 2015; Dong et al., 2020) or large scale label hierarchies (Murty et al., 2017; The Gene Ontology Consortium, 2018; Partalas et al., 2015) for various domains), or can be provided by subject matter experts in far less time than generating entirely new sets of weak supervision sources. For example, in the aforementioned example, we could rely on a biological species ontology to see that the unseen labels "*dog*" and "*cat*" are both subsumed by the seen label "*domestic animals*". Based on the label relations, we can automatically leverage the supervision sources as ILFs for the target task.

The remaining questions are (1) *how to synthesize labels based on pair-wise label relations and ILFs?* and (2) *How can we know whether, given a set of ILFs and label relations, the unseen labels are distinguishable or not?* To address the first question, we develop a *probabilistic label relation model (PLRM)*, the first PGM for WIS which aggregates the output of ILFs and models the label relations as dependencies between random variables. In turn, we use the learned PLRM to produce labels for training an end model. Furthermore, we derive the generalization error bound of PLRM based on assumptions similar to previous work (Ratner et al., 2016).

The second question presents an important stumbling block when dealing with unseen labels, as we may not be able to distinguish the unseen labels given existing label relations and ILFs, resulting in an unsatisfactory synthesized training set. To address this issue, we formally introduce the notion of *distinguishability* in WIS setting and theoretically establish an equivalence between: (1) the distinguishability of the label relation structure as well as the ILFs, and (2) the capability of PLRM to distinguish unseen labels. This result then leads to a simple sanity test for preventing the model from failing to distinguish unseen labels. In preliminary experiments, we observe a significant drop in model performance when the condition is violated.

In experiments, we make non-trivial adaptations for baselines from related settings to the new WIS problem. On both text and image classification tasks, we demonstrate the advantages of PLRM over adapted baselines. Finally, in a commercial advertising system where developers need to collect annotations for new ads tags, we illustrate how to formulate the training label collection as a WIS problem and apply PLRM to achieve an effective performance.

Summary of Contributions. Our contributions are summarized as follows:

- We formulate Weak Indirect Supervision (WIS), a new research problem which synthesizes training labels based on indirect supervision sources and label relations, minimizing human efforts of both data annotation and weak supervision sources construction;

- We develop the first model for WIS, the Probabilistic Label Relation Model (PLRM) with comparable statistical efficiency to previous WS frameworks and standard supervised learning;

- We introduce a new notion of distinguishability in WIS setting, and provide a simple test of the distinguishability of PLRM for unseen labels by theoretically establishing the connection between the label relation structures and distinguishability;

- We showcase the potential of the WIS formulation and the effectiveness of PLRM in a commercial advertising system for synthesizing training labels of new ads tags. On academic image and text classification tasks, we demonstrate the advantages of PLRM over baselines by quantitative experiments. Overall, PLRM outperforms baselines by a margin of 2%-9%.

2 RELATED WORK

We briefly review related settings. The comparison between WIS and related tasks is in Table 1.

Weak Supervision: We draw motivation from recent work which model and integrate weak supervision sources using PGMs (Ratner et al., 2016; 2018; 2019; Fu et al., 2020) and other methods (Guan et al., 2018; Khetan et al., 2018) to create training sets. While they assume supervision sources share the same label space as the new tasks, we aim to leverage indirect supervision sources with mismatched label spaces in a labor-free way.

Table 1: Comparisons between the proposed *weak indirect supervision (WIS)* and related machine learning tasks. Compared to normal and weakly supervised learning, WIS handles mismatched train and test label spaces. WIS is similar in spirit to indirect supervision (IS) and zero-shot learning (ZSL), but distinct in that WIS only takes as input weak or noisy labels and a simple set of logical label relations, and aims to output a training data set rather than a trained model, affording complete modularity in which final model class is used.

Task	Label Type	$\mathcal{Y}_{train} = \mathcal{Y}_{test}$	Label Information	When Label Info. is Required
Supervised Learning (SL)	Clean Labels	✓	–	–
Weak Supervision (WS)	Noisy Sources	✓	–	–
Indirect Supervision (IS)	Clean Labels		Label Trans. Matrix	Training
Zero-Shot Learning (ZSL)	Clean Labels		Label Embed. / Attribute	Training & Test
Weak Indirect Supervision (WIS)	Noisy Sources		Label Relation	Training

Indirect Supervision: Indirect supervision arises more generally in latent-variable models for various domains (Brown et al., 1993; Liang et al., 2013; Quattoni et al., 2004; Chang et al., 2010; Zhang et al., 2019). Very recently, Raghunathan et al. (2016) proposed to use the linear moment method for indirect supervision, wherein the *transition* between desired label space $\mathcal{Y}$ and indirect supervision space $\mathcal{O}$ is known, as well as the ground truth of indirect supervisions for training. In contrast, both are unavailable in WIS. Theoretically, Wang et al. (2020) developed a unified framework for analyzing the learnability of indirect supervision with shared or superset label spaces, while we focus on *disjoint* label spaces and the consequent unique challenge of *distinguishability* of unseen classes.

Zero-Shot Learning: Zero-Shot Learning (ZSL) (Lampert et al., 2009; Wang et al., 2019) aims to learn a classifier that is able to generalize to unseen classes. The WIS problem differentiates from ZSL by (1) in ZSL setting, the training and test data belong to seen and unseen classes, respectively, and training data is labeled, while for WIS, both training and test data belong to unseen classes and unlabeled; (2) ZSL tends to render a classifier that could predict unseen classes given certain label information, *e.g.*, label attributes (Romera-Paredes & Torr, 2015), label descriptions (Srivastava et al., 2018) or label similarities (Frome et al., 2013), while WIS aims to provide training labels for unlabeled training data, allowing users to train *any* machine learning models, and the label relations are used only in synthesizing training labels.

3 PRELIMINARY: WEAK SUPERVISION

We first describe the ordinary Weak Supervision (WS) setting.

Definitions and notations. We assume a k-way classification task, and have an *unlabeled* dataset D consisting of m data points. Denote by $X_i \in \mathcal{X}$ the individual data point and $Y_i \in \{0,1\}^k$ the *unobserved* true label vector of X_i. We adopt y to represent a semantic label, *e.g.*, "*dog*", $\mathcal{Y}$ to represent the set y belongs to (label space), and $[\cdot]$ as indexing for vector, *e.g.*, $Y_i[a]$ is the value of Y_i corresponding to y_a. We also have n sources, each represented by a labeling function (LF) and denoted by λ_j. For each λ_j, its output on X_i is a one-hot vector Λ_{ij}, and its label space is $\mathcal{Y}_{\lambda_j}$ with $|\mathcal{Y}_{\lambda_j}| = k_{\lambda_j}$. Similarly, we denote the concatenation of LFs' output as $\hat{\Lambda}_i = [\Lambda_{i1}, \ldots, \Lambda_{in}]$, and the union set of LFs' label spaces as $\hat{\mathcal{Y}}$ with $|\hat{\mathcal{Y}}| = \hat{k}$. Note that $\hat{k}$ is not necessarily equal to the sum over k_{λ_j}, since LFs may have overlapping label spaces. We call labels in $\hat{\mathcal{Y}}$ *seen* labels and those in $\mathcal{Y}$ *desired* labels. Notably, in WS settings we have $\hat{\mathcal{Y}} \supset \mathcal{Y}$.

The goal of WS. The goal is to infer the training labels for the dataset D based on LFs, and to use them to train an *end* discriminative classifier $f_W : \mathcal{X} \mapsto \mathcal{Y}$, *all without ground truth training labels*.

4 WEAK INDIRECT SUPERVISION

Now, we introduce the new Weak Indirect Supervision (WIS) problem. Unlike the standard WS setting, we only have indirect labeling functions (ILFs) instead of LFs, and an additional label graph is given. The goal of WIS remains the same as WS. An example of WIS problem is in Fig. 1.

Indirect Labeling Function. In WIS, we only have indirect labeling functions (ILFs), which cannot directly predict any desired labels, *i.e.*, $\hat{\mathcal{Y}} \cap \mathcal{Y} = \emptyset$. Therefore, we refer to the desired labels as *unseen*

Figure 1: **An example of WIS problem:** the input consists of an unlabeled dataset, a label graph, and n indirect labeling functions (ILFs). The ILFs represent weak supervision sources such as pretrained classifiers, knowledge bases, heuristic rules, etc. We can see that the ILFs cannot predict desired labels *i.e.*, {"*dog*", "*wolf*", "*cat*", "*lion*"}. To address this, a label graph is given; here we only visualize the subsuming relation. Finally, a label model, instantiated as a PGM, takes the ILF's outputs and produces probabilistic labels in the target output space, which are in turn used to train an end machine learning model that can generalize beyond them.

labels. To make it possible to leverage the ILFs, a label graph is given, which encodes pair-wise label relations between different seen and unseen labels.

Label Graph. Concretely, a label graph $G = (\mathcal{V}, \mathcal{E})$ consists of (1) a set of all the labels as nodes, *i.e.*, $\mathcal{V} = \hat{\mathcal{Y}} \cup \mathcal{Y}$, and (2) a set of pair-wise label relations as typed edges, *i.e.*, $\mathcal{E} = \{(y_i, y_j, t_{ij}) | t_{ij} \in \mathcal{T}, i < j, \forall y_i, y_j \in \mathcal{V}\}$. Here, $\mathcal{T}$ is the set of label relation types and, similar to Deng et al. (2014), there are four types of label relations: *exclusive*, *overlapping*, *subsuming*, *subsumed*, notated by t^o, t^e, t^{sg}, t^{sd}, respectively. Notably, for any *ordered* pair of labels (y_i, y_j), their label relation should fall into *one* of the four types. For convenience, we denote the set of *non-exclusive neighbors* of a given label y_d in $\hat{\mathcal{Y}}$ as $\hat{\mathcal{Y}}(y_d)$, *i.e.*, $\hat{\mathcal{Y}}(y_d) = \{y_a \in \hat{\mathcal{Y}} | (y_d, y_a, t_{da}) \in \mathcal{E} \wedge t_{da} \neq t^e\}$.

5 PROBABILISTIC LABEL RELATION MODEL

One of the key difficulties in both WS and WIS is that we do not observe the true label Y. Following prior work (Ratner et al., 2016; 2019; Fu et al., 2020), we use a latent variable Probabilistic Graphical Model (PGM) for estimating Y based on the random vector $\hat{\Lambda}$ output by ILFs. Specifically, the PGM is instantiated as a factor graph model. This standard technique lets us describe the family of generative distributions in terms of M known dependencies/factor functions $\{\phi\}$, and an unknown parameter $\Theta \in \mathbb{R}^M$ as $p_\Theta(\cdot) \propto \exp(\Theta^\top \Phi(\cdot))$, where Φ is the concatenation of $\{\phi\}$. However, the unique challenge for WIS is that the dependencies $\{\phi\}$ between Y and $\hat{\Lambda}$ are unknown due to the mismatches of label spaces. We overcome these by leveraging the label graph G to build the dependencies for the PGM.

5.1 A BASELINE PGM FOR WIS

In prior work, the PGM for WS is governed by accuracy dependencies:

$$\phi^{\text{Acc}}(Y_i[d], \Lambda_{ij}[d]) := \mathbb{1}[Y_i[d] = \Lambda_{ij}[d]]$$

where y_d is a desired label and Λ_{ij} is the output of a source λ_j. However, in WIS, the ILF λ_j cannot predict the unseen label y_d.

As a simple baseline approach to start, we leverage the coarse-grained exclusive/non-exclusive label relation to build a corresponding "accuracy" factor. Specifically, for a ILF λ_j and one of its outputting label $y_a \in \mathcal{Y}_{\lambda_j}$, given a desired label $y_d \in \mathcal{Y}$, if y_a and y_d have non-exclusive label relation, we

expect a certain portion of data belonging to y_a should be labeled as y_d. Thus, we treat $\Lambda_{\cdot j}[a]$ as a pseudo indicator of $Y[d]$ and add a pseudo accuracy dependency between them:

$$\phi_{y_d, y_a, j}^{\text{Acc}}(Y_i, \hat{\Lambda}_i) = \phi^{\text{Acc}}(Y_i[d], \Lambda_{ij}[a]) := \mathbb{1}[Y_i[d] = \Lambda_{ij}[a]]$$

We call the PGM governed by pseudo accuracy dependencies Weak Supervision with Label Graph (WS-LG). Notably, it can be treated as a simple adaptation of PGM in existing WS frameworks (Ratner et al., 2016; 2019; Fu et al., 2020) for the WIS problem. However, such a naïve adaptation might have two drawbacks:

1. It does not model specific dependencies ILFs with different undesired labels. For example, two ILFs outputting "*husky*" and "*bulldog*" respectively would be naively modeled the same as if they both output "*dog*".

2. It can only directly model exclusive/non-exclusive label relations, ignoring the prior knowledge encoded in other relation types, *i.e.*, subsuming, subsumed, or overlapping. For example, given an unseen label "*dog*" and some ILFs outputting "*husky*" or "*domestic animals*", WS-LG would treat all ILFs as indicators of "*dog*". However, we know a "*husky*" is of course a "*dog*" (subsumed relation) while a "*domestic animals*" is not necessarily a "*dog*" (subsuming relation).

5.2 PROBABILISTIC LABEL RELATION MODEL

To more directly model the full range and nuance of label relations, we propose a new *probabilistic label relation model (PLRM)*. In PLRM, we explicitly model both (1) the dependency between ILF outputs and the true labels in their output spaces, i.e. their direct accuracy, and (2) the dependencies between these labels and the target unseen labels, as separate dependency types, thus explicitly incorporating the full label relation graph into our model and learning its corresponding weights.

Concretely, we augment the WS-LG model with (1) latent variables representing the seen labels output by the ILFs, and (2) label relation dependencies which capture fine-grained label relations between these output labels and desired labels. To model each seen label $y_a \in \hat{\mathcal{Y}}$, we introduce a binary latent variable $\mathbf{y}^a$ indicating whether the data belongs to y_a, and $\hat{Y} \in \{0, 1\}^{\hat{k}}$ representing the concatenation of each individual $\mathbf{y}$. Then, we utilize $\Lambda_{\cdot j}[a]$ as an indicator of $\mathbf{y}^a$ by adding accuracy dependency:

$$\phi_{y_a, j}^{\text{Acc}}(\hat{Y}_i, \hat{\Lambda}_i) = \phi^{\text{Acc}}(\hat{Y}_i[a], \Lambda_{ij}[a]) := \mathbb{1}[\mathbf{y}_i^a = \Lambda_{ij}[a]]$$

Then, to model fine-grained label relations, for a desired label $y_d \in \mathcal{Y}$, we add *label relation* dependencies between $Y[d]$ and $\mathbf{y}^a$. We enumerate the label relation dependencies corresponding to the four label relation types, *i.e.*, exclusive, overlapping, subsuming, subsumed, as follows:

$$\phi_{y_d, y_a}^e(Y_i, \hat{Y}_i) = \phi^e(Y_i[d], \hat{Y}_i[a]) := -\mathbb{1}[Y_i[d] = \mathbf{y}_i^a = 1]$$

$$\phi_{y_d, y_a}^o(Y_i, \hat{Y}_i) = \phi^o(Y_i[d], \hat{Y}_i[a]) := \mathbb{1}[Y_i[d] = \mathbf{y}_i^a = 1]$$

$$\phi_{y_d, y_a}^{sg}(Y_i, \hat{Y}_i) = \phi^{sg}(Y_i[d], \hat{Y}_i[a]) := -\mathbb{1}[Y_i[d] = 0 \wedge \mathbf{y}_i^a = 1]$$

$$\phi_{y_d, y_a}^{sd}(Y_i, \hat{Y}_i) = \phi^{sd}(Y_i[d], \hat{Y}_i[a]) := -\mathbb{1}[Y_i[d] = 1 \wedge \mathbf{y}_i^a = 0]$$

■ Label Relation Dependency
■ True Accuracy Dependency
▨ Pseudo Accuracy Dependency

Figure 2: PLRM.

The above dependencies encode the prior knowledge of the label relations, but also allow the model to learn corresponding parameters. For example, an exclusive label relation dependency $\phi^e(a, b)$ outputs -1 when $a = b = 1$, otherwise 0, which reflects our prior knowledge of reducing the probability density when two exclusive labels are activated at the same time; and the corresponding parameter can be treated as the *strength* of the label relation. Likewise, for any pair of seen labels y_a, y_b, we add label relation dependency $\phi_{y_a, y_b}^{t_{ab}}$ following the same convention. Finally, we give an example of the factor graph of PLRM in Fig. 2, where we highlight different dependencies with different colors, and specify the model as:

$$p_\Theta(\hat{\Lambda}, Y, \hat{Y}) \propto \exp\left(\Theta^\top \Phi(\hat{\Lambda}, Y, \hat{Y})\right). \tag{1}$$

Learning Objective. We estimate the parameters $\hat{\Theta}$ by minimizing the negative log marginal likelihood $p_\Theta(\hat{\Lambda})$ for observed ILF outputs $\hat{\Lambda}_{1:m}$:

$$\hat{\Theta} = \arg\min_\Theta \ -\sum_{i=1}^m \log \sum_{Y, \hat{Y}} p_\Theta(\hat{\Lambda}_i, Y, \hat{Y}). \tag{2}$$

We follow Ratner et al. (2016) to optimize the objective using stochastic gradient descent.

Training an End Model. Let $p_{\hat{\Theta}}(\tilde{Y} \mid \hat{\Lambda})$ be the probabilistic label (i.e. distribution) predicted by learned PLRM. We then train an end model $f_W : \mathcal{X} \mapsto \mathcal{Y}$ parameterized by W, by minimizing the empirical *noise-aware loss* (Ratner et al., 2019) with respect to $\hat{\Theta}$ over m unlabeled data points:

$$\hat{W} = \arg\min_W \frac{1}{m} \sum_{i=1}^{m} \mathbb{E}_{\tilde{Y} \sim \hat{\Theta}|\hat{\Lambda}_i} \ell(\tilde{Y}, f_W(X_i)), \tag{3}$$

where $\ell(\tilde{Y}, f_W(X_i))$ is a standard cross entropy loss.

Generalization Error Bound. We extend previous results from (Ratner et al., 2016) to bound both the expected error of learned parameter $\hat{\Theta}$ and the expected risk for $\hat{W}$. All the proof details and description of assumptions can be found in Appendix.

Theorem 1. *Suppose that we run stochastic gradient descent to produce $\hat{\Theta}$ and $\hat{W}$ based on Eqs. (2) and (3), respectively, and that our setup satisfies certain assumptions (App D.2). Let $|D|$ be the size of the unlabeled dataset. Then we have*

$$\mathbb{E}\left\|\hat{\Theta} - \Theta^*\right\|^2 \leq O\left(M \frac{\log|D|}{|D|}\right), \quad \mathbb{E}\left[\ell(\hat{W}) - \ell(W^*)\right] \leq \chi + O\left(H \sqrt{\frac{\log|D|}{|D|}}\right).$$

Interpreting the Bound. By Theorem 1, the two errors decrease by the rate $\tilde{O}(1/D)$ and $\tilde{O}(1/D^{1/2})$ respectively as $|D|$ increases. This shows that although we trade computational efficiency for the reduction of human efforts by using complex dependencies and more latent variables, we maintain comparable statistical efficiency as previous WS frameworks and supervised learning theoretically.

6 DISTINGUISHABILITY OF UNSEEN LABELS

One unique challenge of WIS is that there may exist pairs of unseen labels which cannot be distinguished by the learned model. For example, as shown in Fig. 3, where "*Dog*" is a seen label for which LFs could predict for and "*Husy*" and "*Bulldog*" are unseen labels for which we want to generate training labels; however, we could not distinguish between "*Husy*" and "*Bulldog*" even though the LFs make correct predictions of seen label "*Dog*", because both "*Husy*" and "*Bulldog*" share the same label relation to "*Dog*".

Figure 3: Example of indistinguishable unseen labels "*Husky*" and "*Bulldog*".

To tackle this issue, we theoretically connect the distinguishability of unseen labels to the label relation structures and provide a testable condition for the distinguishability. Intuitively, same label relation structures could lead to indistinguishable unseen labels as shown in Fig. 3; however, *it turns out to be challenging to prove that different label relation structures could guarantee the distinguishability with respect to the model*. To illustrate, we formally define the distinguishability of a pair of unseen labels as below.

Definition 1 (Distinguishability). *For any model $p_\Theta(Y, \hat{Y}, \hat{\Lambda})$ with parameters Θ, any pair of unseen labels $y_i, y_j \in \mathcal{Y}$ are distinguishable w.r.t. the model, if $\forall \Theta > 0$, a.e., there does NOT exist a $\tilde{\Theta}$, such that, for $\forall (a, b) \in \{0, 1\} \times \{0, 1\}$, $\hat{Y}$, and $\hat{\Lambda}$, the following equations hold*

$$\mathbb{P}_\Theta(Y[i] = a, Y[j] = b|\hat{Y}, \hat{\Lambda}) = \mathbb{P}_{\tilde{\Theta}}(Y[i] = b, Y[j] = a|\hat{Y}, \hat{\Lambda}), \tag{4}$$

$$\mathbb{P}_\Theta(\hat{\Lambda}) = \mathbb{P}_{\tilde{\Theta}}(\hat{\Lambda}). \tag{5}$$

From the definition, we can see that the opposite of distinguishability, *i.e.*, indistinguishability, describes an undesired model: for any learned parameter $\Theta > 0$, we can always find another $\tilde{\Theta}$ which optimizes the loss equally well (Eq. (5)), but Eq. (4) implies *whenever $\mathbb{P}_\Theta$ predict y_i, $\mathbb{P}_{\tilde{\Theta}}$ will predict y_j instead*, which reflects that the model cannot distinguish the two unseen labels. Note that the notion of distinguishability is different from the *identifiability* in PGMs: the *generic identifiability* (Allman et al., 2015), the strongest notion of identifiability, requires the model to be identifiable *up to label swapping*, while the distinguishability aims to avoid the label swapping.

However, distinguishability itself is hard to verify since Eqs. (4) and (5) need to hold for *any* possible configuration of (a, b), $\hat{Y}$, and $\hat{\Lambda}$. Fortunately, for the proposed PLRM, we prove that distinguishability is *equivalent* to the asymmetry of the label relation structures when two conditions hold. To state the required conditions, we first introduce the notations of consistency and informativeness to characterize the label graph and ILFs.

Consistency. We discuss the *consistency* of a label graph to avoid an ambiguous or unrealistic label graph. We interpret semantic labels y_a, y_b as *sets* A, B, and then connect the label relations to the set relations (Fig. 4). Given the set interpretations, we define the *consistency* of label graph as:

Definition 2 (Consistent Label Graph). *A label graph $G = (\mathcal{Y}, \mathcal{E})$ is consistent if the induced set relations are consistent.*

Figure 4: The one-to-one mapping between label relations and set relations.

For example, assume $\mathcal{Y} = \{y_a, y_b, y_c\}$, and $t_{ab} = t_{bc} = t_{ca} = t^{sg}$. From t_{ab}, t_{bc}, we can observe that $A \supsetneq B \supsetneq C$, which contradicts to $C \supsetneq A$ implied by $t_{ca} = t^{sg}$. Thus, G is inconsistent.

Informativeness. In addition, we try to describe what kind of ILF is desired. For example, if the desired label space $\mathcal{Y}$ is {"*dog*", "*bird*"}, then for a ILF λ_1 outputting {"*husky*", "*bulldog*"}, we know "*dog*" is non-exclusive to "*husky*" and "*bulldog*", but "*bird*" exclusive to both. In such case, λ_1 can hardly provide information to help distinguish "*dog*" from "*bird*", because it always votes for "*dog*". On the other hand, a binary classifier of "*husky*", *i.e.*, λ_2, is favorable since it could output zero to avoid consistently voting for "*dog*". We can see an undesired ILF always votes for a single desired label. To formally describe this, we define an *informative ILF* as:

Definition 3 (Informative ILF). *An ILF λ is informative if, for $\forall y \in \mathcal{Y}$ s.t. $\mathcal{Y}_\lambda(y) \neq \emptyset$, there exists $X \in \mathcal{X}$ s.t. the values of output $\Lambda_\lambda(X)$ indexed by $\mathcal{Y}_\lambda(y)$ are all zero, i.e., $\Lambda_\lambda(X)[\mathcal{Y}_\lambda(y)] = \mathbf{0}$.*

Referring back to our examples, for ILF λ_2, we know $\mathcal{Y}_{\lambda_2}("dog")=\{"husky"\}$ and for some data point X, we have $\Lambda_{\lambda_2}(X)=\{"husky"=0\}$, while for "*bird*", $\mathcal{Y}_{\lambda_2}("bird")=\emptyset$. Thus, λ_2 is informative. And for ILF λ_1, we know $\mathcal{Y}_{\lambda_1}("dog")=\{"husky", "bulldog"\}$, but we cannot find an X such that $\Lambda_{\lambda_1}(X)=\{"husky"=0, "bulldog"=0\}$, which makes λ_1 uninformative.

Testable Conditions for Distinguishability. Based on the introduced notations, we prove the *necessary* and *sufficient* condition for learned PLRM being able to distinguish unseen labels:

Theorem 2. *For PLRM induced from a consistent label graph, as well as informative ILFs, for any pair of $y_i, y_j \in \mathcal{Y}$, they are indistinguishable, if and only if $t_{ik} = t_{jk}$ for $\forall y_k \in \hat{\mathcal{Y}}$.*

Theorem 2 provides users with a testable condition: *for any pair of unseen labels y_i, y_j, there should exist at least one seen labels y_k such that y_k has different label relations to y_i and y_j, i.e., $t_{ik} \neq t_{jk}$, so that PLRM is able to distinguish y_i and y_j.* In preliminary experiments, we observe the violation of this condition causes a dramatic drop in overall performance (about 10 points). Notably, based on Theorem 2, users could theoretically guarantee the distinguishability of a pair of unseen labels by adding only one seen label and corresponding ILFs to break the symmetry.

7 EXPERIMENTS

We demonstrate the applicability and performance of our method on image classification tasks derived from ILSVRC2012 (Russakovsky et al., 2015) and text classification tasks derived from LSHTC-3 (Partalas et al., 2015). Both datasets have off-the-shelf label hierarchies (Deng et al., 2014; Partalas et al., 2015), from which we could query pairwise label relations. The ILSVRC2012 dataset (Russakovsky et al., 2015) consists of 1.2M training images from 1,000 leave classes; for

non-leave classes, we follow Deng et al. (2014) to aggregate images belonging to its descendent classes as its data points. The LSHTC-3 dataset (Partalas et al., 2015) consists of 456,886 documents and 36,504 categories organized in a label hierarchy.

7.1 SETUP

For each dataset, we randomly sample 100 different label graphs, each of which consists of 8 classes, and use each label graph to construct a WIS task. For each label graph, we treat 3 of the sampled classes as unseen classes and the other 5 as seen classes. The distinguishable condition in Sec. 6 is ensured for all the WIS tasks, and the performance drop when it is violated can be found in App. G.1. The pairwise label relations are directly queried from the label hierarchy of each dataset. We sample data belonging to unseen classes for our experiments and split them into train, validation and test set. For image classification tasks, we follow Mazzetto et al. (2021b;a) to train a branch of image classifiers as supervision sources of seen classes. For text classification tasks, we made keyword-based labeling functions as supervision sources of seen classes following Zhang et al. (2021); each of the labeling functions returns its associated label when a certain keyword exists in the text, otherwise abstains. Notably, all the involved supervision sources are "weak" because they cannot predict the desired unseen classes. Experimental details and additional results can be found in App. F.

7.2 COMPARED METHODS AND RESULTS

In addition to the WS-LG baseline, which is an adaptation of Data Programming (Ratner et al., 2019) to WIS task, and PLRM, we also include the following baselines. Note that all compared methods input the same data, ILFs, and label relations throughout our experiments for fair comparisons.

Label Relation Majority Voting (LR-MV).   We modify the majority voting method based on the label's non-exclusive neighbors: we replace y_a predicted by any ILF with the set of labels $\mathcal{Y}(y_a)$, *i.e.*, $\mathcal{Y}(y_a) = \{y_d \in \mathcal{Y} | (y_d, y_a, t_{da}) \in \mathcal{E} \wedge t_{da} \neq t^e\}$, then aggregate the modified ILFs' output.

Weighted Label Relation Majority Voting (W-LR-MV).   LR-MV only leverages exclusive/non-exclusive label relations. To leverage fine-grained label relations, W-LR-MV attaches a *weight* to each replaced label. Specifically, if the ILF's output y_a is replaced with its *ancestor* label y_d (subsumed relation), then the weight of y_d equals 1, while for the other relations, the weight is $\frac{1}{|\mathcal{Y}^*(y_a)|}$, where $\mathcal{Y}^*(y_a) = \{y_d \in \mathcal{Y}(y_a) | t_{ad} \neq t^{sd}\}$.

For the above methods, we compare the performance of (1) directly applying included models on the test set and (2) the end models (classifiers) trained with inferred training labels.

Zero-Shot Learning (ZSL).   It is non-trivial to apply ZSL methods, because ZSL assumes label attributes for all classes and a labeled training set of seen classes, while WIS input an unlabeled dataset of unseen classes, label relations and ILFs. Fortunately, the Direct Attribute Prediction (DAP) (Lampert et al., 2013) method is able to make predictions solely based on attributes without labeled data, by training attribute classifier $p(a_i|x)$ for each attribute a_i. Therefore we include it in our experiments. To apply DAP, we use both label relations and ILFs to construct attributes for both unseen classes and unlabeled data points. Then, we train the attribute classifiers, which in turn are used to predict unseen labels on the test set as in Lampert et al. (2013). The details of attribute construction can be found in App. F.2.

For a fair comparison, we fix the network architecture of the classifiers for all the methods. For image classification, we use ResNet-32 (He et al., 2016) and for text classification, we use logistic regression with pre-trained text embedding (Reimers & Gurevych, 2019).

Evaluation Results.   The overall results for both datasets can be found in Table 2. From the results, we can see that PLRM consistently outperforms baselines. The advantages of PLRM show the effect of not just leveraging the label graph, as the baselines do, but modeling the accuracy of ILFs and the strengths of label relations as PLRM does. The reported results have high variance, which actually indicates the 100 different WIS tasks are diverse and have varying difficulty. Also, we can see the end models are much better than directly applying the label models on the test set; this shows that the end models are able to generalize beyond the training labels produced by label models. Therefore,

Table 2: Averaged evaluation results over 100 WIS tasks derived from LSHTC-3 and ILSVRC2012.

Method		LSHTC-3		ILSVRC2012	
		Accuracy	F1-score	Accuracy	F1-score
DAP		42.90 ± 13.53	35.98 ± 15.73	33.25 ± 3.68	29.13 ± 4.63
Label Model	LR-MV	58.86 ± 10.50	54.33 ± 11.10	46.88 ± 10.66	40.11 ± 16.44
	W-LR-MV	59.28 ± 10.47	54.55 ± 11.36	41.39 ± 10.80	30.19 ± 16.94
	WS-LG	62.60 ± 10.12	57.50 ± 11.19	53.68 ± 7.62	52.15 ± 7.94
	PLRM	$\mathbf{64.65} \pm 11.30$	$\mathbf{60.01} \pm 13.39$	$\mathbf{56.18} \pm 7.35$	$\mathbf{54.94} \pm 7.44$
End Model	LR-MV	67.17 ± 12.25	62.49 ± 13.95	49.60 ± 12.80	42.83 ± 18.17
	W-LR-MV	66.57 ± 11.73	61.80 ± 13.24	42.61 ± 12.46	31.34 ± 18.20
	WS-LG	70.69 ± 13.05	67.36 ± 14.24	56.56 ± 9.68	54.57 ± 11.17
	PLRM	$\mathbf{72.32} \pm 13.18$	$\mathbf{69.37} \pm 14.41$	$\mathbf{58.38} \pm 8.27$	$\mathbf{56.83} \pm 8.49$

we could use the trained end models as LF and then iteratively train label/end models, similar to the framework of self-training, which has been explored in ordinary WS setting (Karamanolakis et al., 2021) and we leave as future work.

7.3 REAL-WORLD APPLICATION

In this section, on a commercial advertising system (CAS), we showcase how to reduce human annotation efforts of new labeling tasks by formulating them as WIS problems. In a CAS, ads tagging (classification) is a critical application for understanding the semantics of ads copy. When new ads and tags are added to the system, manual annotations need to be collected for training a new classifier for each tag. As tags are commonly organized as taxonomies, the label relations between existing and new tags are readily available or can be trivially figured out by humans; Existing classifiers and the heuristic rules previously used for annotating existing tags could serve as ILFs. Therefore, given (1) an unlabeled dataset which requires annotations of new tags, (2) the label relations, and (3) ILFs, we could formulate it as a WIS problem.

We apply such WIS formulation, as well as our method and baselines, to the industrial scenario of synthesizing training labels for the classifiers of new tags. Specifically, we have two WIS tasks where the tags are under the "*Car Accessories*" and "*Furniture*" categories respectively. For both tasks, we have 3 new tags and leverage 5 existing tags related to the new ones with given relations. On a test set, we evaluate the performance of DAP and the quality of labels produced by label models, as shown in Table 3. Note that since we re-use the existing labeling sources tailored for existing tags as ILFs and obtain label relations from an existing taxonomy, we achieve these results without any manual annotation or creation of new labeling functions. This demonstrates the potential of the proposed WIS task on reducing human efforts in real-world scenarios.

Table 3: Evaluation on product tagging with new tags.

Category	Metric	DAP	LR-MV	W-LR-MV	WS-LG	PLRM
Car Accessories	F1	50.62	68.68	68.06	66.85	**76.37**
	Accuracy	52.83	68.17	67.67	66.33	**75.83**
Furniture	F1	30.81	64.70	61.45	70.59	**80.57**
	Accuracy	33.60	72.53	72.13	74.51	**82.02**

8 CONCLUSION

We propose Weak Indirect Supervision (WIS), a new research problem which leverages indirect supervision sources and label relations to synthesize training labels for training machine learning models. We develop the first method for WIS called Probabilistic Label Relation Model (PLRM) with the generalization error bound of both PLRM and end model. We provide a theoretically-principled sanity test to ensure the distinguishability of unseen labels. Finally, we provide experiments to demonstrate the effectiveness of PLRM and its advantages over baselines on both academic datasets and industrial scenario.

Reproducibility Statement. All the assumptions and proofs of our theory can be found in App. C & D. Examples and illustrations of label graph are in App. E. Experimental details can be found in App. F. Additional experiments are in App. G. We will put the link to our code in the comment directed to the reviewers and area chairs when the forum is open as suggested by Author Guide.

REFERENCES

Elizabeth S Allman, John A Rhodes, Elena Stanghellini, and Marco Valtorta. Parameter identifiability of discrete bayesian networks with hidden variables. *Journal of Causal Inference*, 3(2):189–205, 2015.

Stephen H. Bach, Daniel Rodriguez, Yintao Liu, Chong Luo, Haidong Shao, Cassandra Xia, Souvik Sen, Alex Ratner, Braden Hancock, Houman Alborzi, Rahul Kuchhal, Chris Ré, and Rob Malkin. Snorkel drybell: A case study in deploying weak supervision at industrial scale. In *Proceedings of the 2019 International Conference on Management of Data*, SIGMOD '19, pp. 362–375, New York, NY, USA, 2019. Association for Computing Machinery. ISBN 9781450356435. doi: 10.1145/3299869.3314036. URL https://doi.org/10.1145/3299869.3314036.

Peter F Brown, Stephen A Della Pietra, Vincent J Della Pietra, and Robert L Mercer. The mathematics of statistical machine translation: Parameter estimation. *Computational linguistics*, 19(2):263–311, 1993.

Ming-Wei Chang, Vivek Srikumar, Dan Goldwasser, and Dan Roth. Structured output learning with indirect supervision. In *ICML*, pp. 199–206, 2010.

Lingjiao Chen, Matei Zaharia, and James Zou. Frugalml: How to use ml prediction apis more accurately and cheaply. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2020.

Carlos d'Andrea and André Mintz. Studying the live cross-platform circulation of images with computer vision api: An experiment based on a sports media event. *International Journal of Communication*, 13(0), 2019. ISSN 1932-8036.

Jia Deng, Nan Ding, Yangqing Jia, Andrea Frome, Kevin Murphy, Samy Bengio, Yuan Li, Hartmut Neven, and Hartwig Adam. Large-scale object classification using label relation graphs. In *European conference on computer vision*, pp. 48–64. Springer, 2014.

Xin Luna Dong, Xiang He, Andrey Kan, Xian Li, Yan Liang, Jun Ma, Yifan Ethan Xu, Chenwei Zhang, Tong Zhao, Gabriel Blanco Saldana, et al. Autoknow: Self-driving knowledge collection for products of thousands of types. In *Proceedings of the 26th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining*, pp. 2724–2734, 2020.

Jared A. Dunnmon, Alexander J. Ratner, Khaled Saab, Nishith Khandwala, Matthew Markert, Hersh Sagreiya, Roger Goldman, Christopher Lee-Messer, Matthew P. Lungren, Daniel L. Rubin, and Christopher Ré. Cross-modal data programming enables rapid medical machine learning. *Patterns*, 1(2):100019, 2020. ISSN 2666-3899. doi: https://doi.org/10.1016/j.patter.2020.100019. URL https://www.sciencedirect.com/science/article/pii/S2666389920300192.

Jason A Fries, Ethan Steinberg, Saelig Khattar, Scott L Fleming, Jose Posada, Alison Callahan, and Nigam H Shah. Ontology-driven weak supervision for clinical entity classification in electronic health records. *Nature Communications*, 12(1), 2021.

Andrea Frome, Greg S Corrado, Jon Shlens, Samy Bengio, Jeff Dean, Marc' Aurelio Ranzato, and Tomas Mikolov. Devise: A deep visual-semantic embedding model. In C. J. C. Burges, L. Bottou, M. Welling, Z. Ghahramani, and K. Q. Weinberger (eds.), *Advances in Neural Information Processing Systems*, volume 26, pp. 2121–2129. Curran Associates, Inc., 2013. URL https://proceedings.neurips.cc/paper/2013/file/7cce53cf90577442771720a370c3c723-Paper.pdf.

Daniel Y. Fu, Mayee F. Chen, Frederic Sala, Sarah M. Hooper, Kayvon Fatahalian, and Christopher Ré. Fast and three-rious: Speeding up weak supervision with triplet methods. In *Proceedings of the 37th International Conference on Machine Learning (ICML 2020)*, 2020.

Melody Y. Guan, Varun Gulshan, Andrew M. Dai, and Geoffrey E. Hinton. Who said what: Modeling individual labelers improves classification. In *AAAI*, 2018.

K. He, X. Zhang, S. Ren, and J. Sun. Deep residual learning for image recognition. In *2016 IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 770–778, 2016. doi: 10.1109/CVPR.2016.90.

Sarah Hooper, Michael Wornow, Ying Hang Seah, Peter Kellman, Hui Xue, Frederic Sala, Curtis Langlotz, and Christopher Re. Cut out the annotator, keep the cutout: better segmentation with weak supervision. In *International Conference on Learning Representations*, 2021. URL https://openreview.net/forum?id=bjkX6Kzb5H.

Giannis Karamanolakis, Subhabrata Mukherjee, Guoqing Zheng, and Ahmed Hassan Awadallah. Self-training with weak supervision. In *NAACL-HLT*, pp. 845–863, 2021. doi: 10.18653/v1/2021. naacl-main.66. URL https://www.aclweb.org/anthology/2021.naacl-main. 66.

Ashish Khetan, Zachary C. Lipton, and Anima Anandkumar. Learning from noisy singly-labeled data. In *International Conference on Learning Representations*, 2018. URL https://openreview. net/forum?id=H1sUHgb0Z.

Christoph H Lampert, Hannes Nickisch, and Stefan Harmeling. Learning to detect unseen object classes by between-class attribute transfer. In *2009 IEEE Conference on Computer Vision and Pattern Recognition*, pp. 951–958. IEEE, 2009.

Christoph H Lampert, Hannes Nickisch, and Stefan Harmeling. Attribute-based classification for zero-shot visual object categorization. *IEEE transactions on pattern analysis and machine intelligence*, 36(3):453–465, 2013.

Percy Liang, Michael I Jordan, and Dan Klein. Learning dependency-based compositional semantics. *Computational Linguistics*, 39(2):389–446, 2013.

Pierre Lison, Jeremy Barnes, Aliaksandr Hubin, and Samia Touileb. Named entity recognition without labelled data: A weak supervision approach. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pp. 1518–1533, Online, July 2020. Association for Computational Linguistics. doi: 10.18653/v1/2020.acl-main.139. URL https://www. aclweb.org/anthology/2020.acl-main.139.

Alessio Mazzetto, Cyrus Cousins, Dylan Sam, Stephen H Bach, and Eli Upfal. Adversarial multi class learning under weak supervision with performance guarantees. In Marina Meila and Tong Zhang (eds.), *Proceedings of the 38th International Conference on Machine Learning*, volume 139 of *Proceedings of Machine Learning Research*, pp. 7534–7543. PMLR, 18–24 Jul 2021a. URL https://proceedings.mlr.press/v139/mazzetto21a.html.

Alessio Mazzetto, Dylan Sam, Andrew Park, Eli Upfal, and Stephen Bach. Semi-supervised aggregation of dependent weak supervision sources with performance guarantees. In Arindam Banerjee and Kenji Fukumizu (eds.), *Proceedings of The 24th International Conference on Artificial Intelligence and Statistics*, volume 130 of *Proceedings of Machine Learning Research*, pp. 3196–3204. PMLR, 13–15 Apr 2021b. URL https://proceedings.mlr.press/v130/ mazzetto21a.html.

George A Miller. Wordnet: a lexical database for english. *Communications of the ACM*, 38(11): 39–41, 1995.

Shikhar Murty, Pat Verga, L. Vilnis, and A. McCallum. Finer grained entity typing with typenet. *AKBC Workshop*, 2017.

Ioannis Partalas, Aris Kosmopoulos, Nicolas Baskiotis, Thierry Artières, George Paliouras, Éric Gaussier, Ion Androutsopoulos, Massih-Reza Amini, and Patrick Gallinari. LSHTC: A benchmark for large-scale text classification. *CoRR*, abs/1503.08581, 2015.

Ariadna Quattoni, Michael Collins, and Trevor Darrell. Conditional random fields for object recognition. *Advances in neural information processing systems*, 17:1097–1104, 2004.

Aditi Raghunathan, Roy Frostig, John Duchi, and Percy Liang. Estimation from indirect supervision with linear moments. In *International Conference on Machine Learning (ICML)*, 2016.

A. J. Ratner, Christopher M. De Sa, Sen Wu, Daniel Selsam, and C. Ré. Data programming: Creating large training sets, quickly. In *Proceedings of the 29th Conference on Neural Information Processing Systems (NIPS 2016)*, Barcelona, Spain, 2016.

A. J. Ratner, B. Hancock, J. Dunnmon, F. Sala, S. Pandey, and C. Ré. Training complex models with multi-task weak supervision. In *Proceedings of the AAAI Conference on Artificial Intelligence*, Honolulu, Hawaii, 2019.

Alexander Ratner, Stephen H. Bach, Henry Ehrenberg, Jason Fries, Sen Wu, and Christopher Ré. Snorkel: Rapid training data creation with weak supervision. In *Proceedings of the 44th International Conference on Very Large Data Bases (VLDB)*, Rio de Janeiro, Brazil, 2018.

Nils Reimers and Iryna Gurevych. Sentence-bert: Sentence embeddings using siamese bert-networks. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing*. Association for Computational Linguistics, 11 2019. URL https://arxiv.org/abs/1908.10084.

Bernardino Romera-Paredes and Philip Torr. An embarrassingly simple approach to zero-shot learning. In *International conference on machine learning*, pp. 2152–2161. PMLR, 2015.

Olga Russakovsky, Jia Deng, Hao Su, Jonathan Krause, Sanjeev Satheesh, Sean Ma, Zhiheng Huang, Andrej Karpathy, Aditya Khosla, Michael Bernstein, Alexander C. Berg, and Li Fei-Fei. Imagenet large scale visual recognition challenge. *Int. J. Comput. Vision*, 115(3):211–252, December 2015. ISSN 0920-5691. doi: 10.1007/s11263-015-0816-y. URL https://doi.org/10.1007/s11263-015-0816-y.

Esteban Safranchik, Shiying Luo, and Stephen Bach. Weakly supervised sequence tagging from noisy rules. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 34, pp. 5570–5578, 2020.

Arnab Sinha, Zhihong Shen, Yang Song, Hao Ma, Darrin Eide, Bo-June Paul Hsu, and Kuansan Wang. An overview of microsoft academic service (mas) and applications. In *WWW*, 2015.

Shashank Srivastava, Igor Labutov, and Tom Mitchell. Zero-shot learning of classifiers from natural language quantification. In *Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 306–316, Melbourne, Australia, July 2018. Association for Computational Linguistics. doi: 10.18653/v1/P18-1029. URL https://www.aclweb.org/anthology/P18-1029.

The Gene Ontology Consortium. The Gene Ontology Resource: 20 years and still GOing strong. *Nucleic Acids Research*, 47(D1):D330–D338, 11 2018. ISSN 0305-1048. doi: 10.1093/nar/gky1055. URL https://doi.org/10.1093/nar/gky1055.

Paroma Varma, Frederic Sala, Shiori Sagawa, Jason Alan Fries, Daniel Y. Fu, Saelig Khattar, Ashwini Ramamoorthy, Ke Xiao, Kayvon Fatahalian, James Priest, and Christopher Ré. Multi-resolution weak supervision for sequential data. In Hanna M. Wallach, Hugo Larochelle, Alina Beygelzimer, Florence d'Alché-Buc, Emily B. Fox, and Roman Garnett (eds.), *Advances in Neural Information Processing Systems 32: Annual Conference on Neural Information Processing Systems 2019, NeurIPS 2019, December 8-14, 2019, Vancouver, BC, Canada*, pp. 192–203, 2019. URL https://proceedings.neurips.cc/paper/2019/hash/93db85ed909c13838ff95ccfa94cebd9-Abstract.html.

Kaifu Wang, Qiang Ning, and Dan Roth. Learnability with indirect supervision signals. *Advances in Neural Information Processing Systems 32*, 2020.

Wei Wang, Vincent W Zheng, Han Yu, and Chunyan Miao. A survey of zero-shot learning: Settings, methods, and applications. *ACM Transactions on Intelligent Systems and Technology (TIST)*, 10 (2):1–37, 2019.

Yuanshun Yao, Zhujun Xiao, Bolun Wang, Bimal Viswanath, Haitao Zheng, and Ben Y. Zhao. Complexity vs. performance: Empirical analysis of machine learning as a service. In *Proceedings of the 2017 Internet Measurement Conference*, IMC '17, pp. 384–397, New York, NY, USA, 2017. Association for Computing Machinery. ISBN 9781450351188. doi: 10.1145/3131365.3131372. URL https://doi.org/10.1145/3131365.3131372.

Eric Zhan, Stephan Zheng, Yisong Yue, Long Sha, and Patrick Lucey. Generating multi-agent trajectories using programmatic weak supervision. In *International Conference on Learning Representations*, 2019. URL https://openreview.net/forum?id=rkxw-hAcFQ.

Jieyu Zhang, Yue Yu, Yinghao Li, Yujing Wang, Yaming Yang, Mao Yang, and Alexander Ratner. Wrench: A comprehensive benchmark for weak supervision. *arXiv preprint arXiv:2109.11377*, 2021.

Yivan Zhang, Nontawat Charoenphakdee, and Masashi Sugiyama. Learning from indirect observations, 2019.

Wenxuan Zhou, Hongtao Lin, Bill Yuchen Lin, Ziqi Wang, Junyi Du, Leonardo Neves, and Xiang Ren. Nero: A neural rule grounding framework for label-efficient relation extraction. *The Web Conference*, 2020.

SUPPLEMENTARY MATERIALS FOR "CREATING TRAINING SETS VIA WEAK INDIRECT SUPERVISION"

The supplementary materials are organized as follows. In Appendix A, we provide a glossary of variables and symbols used in this paper. In Appendix B, we provide the details of PLRM model. In Appendix C and D, we provide the detailed proofs of Theorem 2 and Theorem 1 respectively. In Appendix E, we provide the detailed examples and illustrations of label graph in WIS. In Appendix F and G, we provide experimental details and additional experiment resulst respectively.

A GLOSSARY OF SYMBOLS

Table 4: Glossary of variables and symbols used in this paper.

Symbol	Used for
Ω^k	The set of one-hot vector with dimension k, *i.e.*, $\{v \in \{0,1\}^k | \sum_i^k v[i] = 1\}$
X	Data point, $X \in \mathcal{X}$
m	Number of data points
y	Semantic label, *e.g.*, "dog"
$\mathcal{Y}$	The set of desired semantic labels
Y	Label vector for each data point, $Y \in \Omega^k$
$Y[d]$	The value of Y corresponding to y_d
$\mathbf{Y}$	Random vector of Y
k	Cardinality of $\mathcal{Y}$, *i.e.*, $k = |\mathcal{Y}|$
λ	Indirect labeling function (ILF)
n	Number of ILF
$\mathcal{Y}_\lambda$	Output label space of ILF λ
k_λ	Cardinality of the output space of ILF λ, *i.e.*, $k_\lambda = |\mathcal{Y}_\lambda|$
$\hat{\mathcal{Y}}$	Union set of all the $\mathcal{Y}_\lambda$
$\hat{k}$	Cardinality of the $\hat{\mathcal{Y}}$, *i.e.*, $\hat{k} = |\hat{\mathcal{Y}}|$
Λ	Label vector output by ILF λ, $\Lambda \in \Omega^{k_\lambda}$
$\hat{\Lambda}$	Concatenation of label vectors output by all ILFs, $\hat{\Lambda}_i = [\Lambda_{i1}, \dots, \Lambda_{in}]$
$\hat{\Omega}$	The set of all possible $\hat{\Lambda}$
$\hat{\mathbf{\Lambda}}$	Random vector of $\hat{\Lambda}$
G	Label graph, $G = (\hat{\mathcal{Y}} \cup \mathcal{Y}, \mathcal{E})$
$\mathcal{E}$	The set of label relations, $\mathcal{E} = \{(y_i, y_j, t_{ij}) | t_{ij} \in \mathcal{T}, i < j, \forall y_i, y_j \in \hat{\mathcal{Y}} \cup \mathcal{Y}\}$
$\mathcal{T}$	The set of label relation types, $\mathcal{T} = \{t^e, t^o, t^{sd}, t^{sg}\}$
t^e	Exclusive label relation
t^o	Overlap label relation
t^{sg}	Subsuming label relation
t^{sd}	Subsumed label relation
$\mathbf{y}^a$	Latent binary variable for a semantic label y_a
$\hat{Y}$	Concatenation of all latent binary variable, $\hat{Y} = [\mathbf{y}^1, \dots, \mathbf{y}^{K-k}] \in \{0,1\}^{K-k}$
$\hat{\mathbf{Y}}$	Random vector of $\hat{Y}$
ϕ	A single dependency, or, factor function
Φ	Concatenation of all individual dependency
M	Number of total dependencies
θ	A single parameter
Θ	Concatenation of all parameters, $\Theta \in \mathbb{R}^M$
$p_\Theta(\hat{\Lambda}, Y, \hat{Y})$	The Probabilistic Graphical Model (PGM) parameterized by Θ
$\tilde{Y}$	Probabilistic training label, i.e. $P_\Theta(Y|\lambda)$
$f_W(X)$	The end model trained using $(X, \tilde{Y})$

B DETAILS OF THE PLRM

We use $\mathbf{Y}, \hat{\mathbf{Y}}, \hat{\mathbf{\Lambda}}$ and $\mathbf{\Lambda}$ to represent random vector, while $Y, \hat{Y}, \hat{\Lambda}$ and Λ to represent the specific value of the corresponding random vector. Then, we give the formal form of the PLRM as:

$$p_\Theta(\hat{\mathbf{\Lambda}}, \mathbf{Y}, \mathbf{Y}^c) \propto \prod_i^m \exp\left(\Theta^\mathsf{T} \Phi(\hat{\Lambda}_i, Y_i, \hat{Y}_i)\right) . \tag{6}$$

Where

$$
\begin{aligned}
\Theta^\mathsf{T}\Phi(\hat{\Lambda}_i, Y_i, \hat{Y}_i) =& \sum_{d=1}^k \sum_{j=1}^n \sum_{y_a \in \mathcal{Y}_{\lambda_j}(y_d)} \theta^{\text{Acc}}_{y_d, y_a, j} \phi^{\text{Acc}}_{y_d, y_a, j}(Y_i[d], \Lambda_{ij}[a]) \\
&+ \sum_{j=1}^n \sum_{y_a \in \mathcal{Y}_{\lambda_j}} \theta^{\text{Acc}}_{y_a, j} \phi^{\text{Acc}}_{y_a, j}(\hat{Y}_i[a], \Lambda_{ij}[a]) \\
&+ \sum_{1 \le a, b \le \hat{k}} \theta^{t_{ab}}_{y_a, y_b} \phi^{t_{ab}}_{y_a, y_b}(\hat{Y}_i[a], \hat{Y}_i[b]) \\
&+ \sum_{d=1}^k \sum_{a=1}^{\hat{k}} \theta^{t_{da}}_{y_d, y_a} \phi^{t_{da}}_{y_d, y_a}(Y_i[d], \hat{Y}_i[a])
\end{aligned}
$$

The first term corresponds to the pseudo accuracy dependencies, while the second term is the true accuracy dependencies. The third term represents the label relation dependencies between seen labels, and the final term is the label relation dependencies between unseen and seen labels.

C PROOF OF THEOREM 2

C.1 NOTATIONS

To simplify the indexing of label vectors, for $y_{d_i} \in \mathcal{Y}$, we use $\mathbf{Y}[i]$ to represent $\mathbf{Y}[d_i]$ for simplicity (similar for $\hat{\mathbf{Y}}[i]$ and $\mathbf{\Lambda}_j[i]$). Besides, without involving specific data point X_i, we use Λ_j to represent the output of ILF λ_j.

To simplify the indexing of dependencies, we use ϕ^1 to represent the concatenation of ϕ which involvs both $\mathbf{Y}$ and $\hat{\mathbf{Y}}$, ϕ^2 to represent the concatenation of ϕ which involve both $\mathbf{Y}$ and $\hat{\mathbf{\Lambda}}$, and ϕ^3 to represent the concatenation of remaining ϕ which do not involve $\mathbf{Y}$. Furthermore, we use subscript i to represent the concatenation of ϕ wherein $\mathbf{Y}[i]$ is involved, *e.g.*, ϕ^1_i represents the concatenation of elements in ϕ^1 which involve $\mathbf{Y}[i]$; use subscript i, j to represent the concatenation of ϕ in ϕ^2 wherein $\mathbf{Y}[i]$ and $\mathbf{\Lambda}_j$ involved; and use subscript i, j, a to represent the particular ϕ involving $\mathbf{Y}[i]$ and $\mathbf{\Lambda}_j[a]$. Likewise, the indexing of model parameters Θ follows the same convention.

Then, based on the simplified notations, we could expand the joint probability as:

$$
\begin{aligned}
&\mathbb{P}_\Theta(\mathbf{Y} = Y, \hat{\mathbf{Y}} = \hat{Y}, \hat{\mathbf{\Lambda}} = \hat{\Lambda}) = \\
&\frac{\exp\left(\sum_{i=1}^k (\Theta^1_i)^\mathsf{T}\Phi^1_i(Y[i], \hat{Y}) + \sum_{i=1}^k (\Theta^2_i)^\mathsf{T}\Phi^2_i(Y[i], \hat{\Lambda}) + (\Theta^3)^\mathsf{T}\Phi^3(\hat{Y}, \hat{\Lambda})\right)}{\sum_{\mathbf{Y}, \hat{\mathbf{Y}}, \hat{\mathbf{\Lambda}}} \exp\left(\sum_{i=1}^k (\Theta^1_i)^\mathsf{T}\Phi^1_i(\mathbf{Y}[i], \hat{\mathbf{Y}}) + \sum_{i=1}^k (\Theta^2_i)^\mathsf{T}\Phi^2_i(\mathbf{Y}[i], \hat{\mathbf{\Lambda}}) + (\Theta^3)^\mathsf{T}\Phi^3(\hat{\mathbf{Y}}, \hat{\mathbf{\Lambda}})\right)}
\end{aligned} \tag{7}
$$

C.2 PROPOSITIONS AND LEMMAS

First, we state some propositions and lemmas that will be useful in the proof to come.

Proposition 1 (Multi-class classification). *For a multi-class classification task, $\forall y_{d_i}, y_{d_j} \in \mathcal{Y}$, we have $t_{d_i d_j} = t^e$. Similarly, $\forall y_a, y_b \in \mathcal{Y}_\lambda$, we have $t_{ab} = t^e$.*

Proposition 2 (One-hot Label Vector). *For a multi-class classification task, the label vector Y is a one-hot vector. Similarly, the output Λ of each ILF λ is also one-hot vector.*

Lemma 1. *For a consistent label graph G and $\forall y_a \in \hat{\mathcal{Y}}, \forall y_{d_i} y_{d_j} \in \mathcal{Y}$, if $t_{d_i a} = t^o$, we have $t_{d_j b} \neq t^{sg}$.*

Proof. For $\forall y_{d_i}, y_{d_j} \in \mathcal{Y}$, based on Proposition 1, we know $t_{d_i d_j} = t^e$, which implies (1) $y_{d_i} \cap y_{d_j} = \emptyset$. For $\forall y_a \in \hat{\mathcal{Y}}$, if $t_{d_i a} = t^o$, we have the corresponding set relation (2) $y_{d_i} \cap y_a \neq \emptyset$. If $t_{d_j a} = t^{sg}$, which implies (3) $y_{d_j} \supsetneq y_a$. Based on (2)(3), we have $y_{d_i} \cap y_{d_j} \neq \emptyset$, which is contradictory to (1). Thus, we prove when $t_{d_i a} = t^o, t_{d_j a} \neq t^{sg}$. $\qquad\square$

Lemma 2. *For an informative ILF λ_j and $\forall y_d \in \mathcal{Y}$, we are allowed to set dependency vector $\phi_{d,j}^2(\mathbf{Y}[d], \mathbf{\Lambda}_j) = \phi_{d,j}^2(\mathbf{Y}[d], \mathbf{0})$.*

Proof. Because ILF λ_j is informative, we know there exists one $y_a \in \mathcal{Y}_{\lambda_j}$ such that y_a is exclusive to y_d, which implies there is no such a dependency $\phi_{d,j}^2(\mathbf{Y}[d], \mathbf{\Lambda}_j[a])$ in $\phi_{d,j}^2$. Then, we set $\mathbf{\Lambda}_j[a] = 1$. Based on Proposition 2, we know $\mathbf{\Lambda}_j[b] = 0$ for $\forall y_b \in \mathcal{Y}_{\lambda_j} \setminus \{y_a\}$, which implies $\phi_{d,j}^2(\mathbf{Y}[d], \mathbf{\Lambda}_j) = \phi_{d,j}^2(\mathbf{Y}[d], \mathbf{0})$. $\qquad\square$

C.3 DEFINITIONS

Before the main proof, we connect the indistinguishablity of label relation structure with the dependency structure of PLRM by introducing the concept of *symmetry* as follows:

Definition 4 (Symmetry). *for $y_{d_i}, y_{d_j} \in \mathcal{Y}$, we say $\mathbf{Y}[i], \mathbf{Y}[j]$ have symmetric dependency structure if for any $\hat{Y}$ and $\hat{\Lambda}$,*

$$\Phi_i^1(\cdot, \hat{Y}) = \Phi_j^1(\cdot, \hat{Y}) \quad and \quad \Phi_i^2(\cdot, \hat{\Lambda}) = \Phi_j^2(\cdot, \hat{\Lambda}). \tag{8}$$

Based on the construction of PLRM, we know that for $\forall y_{d_i}, y_{d_j} \in \mathcal{Y}, \forall y_a \in \hat{\mathcal{Y}}, t_{d_i a} = t_{d_j a}$ (the statement in Theorem 2) is *equivalent* to $\mathbf{Y}[i], \mathbf{Y}[j]$ have symmetric dependency structure.

C.4 EQUIVALENT STATEMENT OF THEOREM 2

Our main result states that asymmetric is equivalent to distinguishable as in the following theorem, which can readily be seen to be identical to Theorem 2 in the main body of the paper:

Theorem 3. *For a probability model defined as Eq. (7) induced from a consistent label graph and informative ILFs, for any pair of $y_{d_i}, y_{d_j} \in \mathcal{Y}$, y_{d_i} and y_{d_j} are distinguishable if and only if $\mathbf{Y}[i]$ and $\mathbf{Y}[j]$ have asymmetric dependency structure.*

C.5 PROOF OF THEOREM 3: NECESSARY CONDITION

We first prove that $\mathbf{Y}[i]$ and $\mathbf{Y}[j]$ have asymmetric dependency structure is the *necessary* condition of any pair of $y_{d_i}, y_{d_j} \in \mathcal{Y}$ to be distinguishable.

Proof. We start by calculating $\mathbb{P}_\Theta(\mathbf{Y}[i] = Y[i], \mathbf{Y}[j] = Y[j]|\hat{\mathbf{Y}} = \hat{Y}, \hat{\mathbf{\Lambda}} = \hat{\Lambda})$. By Eq. (7), joint distribution of $\mathbf{Y}[i]$ and $\mathbf{Y}[j]$ condition on any $\hat{Y}$ and $\hat{\Lambda}$ can be calculated as follows:

$$\mathbb{P}_\Theta(\mathbf{Y}[i] = Y[i], \mathbf{Y}[j] = Y[j]|\hat{\mathbf{Y}} = \hat{Y}, \hat{\mathbf{\Lambda}} = \hat{\Lambda}) = \frac{\mathbb{P}_\Theta(\mathbf{Y}[i] = Y[i], \mathbf{Y}[j] = Y[j], \hat{\mathbf{Y}} = \hat{Y}, \hat{\mathbf{\Lambda}} = \hat{\Lambda})}{\mathbb{P}_\Theta(\hat{\mathbf{Y}} = \hat{Y}, \hat{\mathbf{\Lambda}} = \hat{\Lambda})}.$$

On the other hand, if $\mathbf{Y}[i] = 1$, because $\mathbf{Y}$ is one-hot vector, we have

$$\mathbb{P}_\Theta(\mathbf{Y}[i] = 1, \mathbf{Y}[j] = 0, \hat{\mathbf{Y}} = \hat{Y}, \hat{\mathbf{\Lambda}} = \hat{\Lambda}) = \mathbb{P}_\Theta(\mathbf{Y}[i] = 1, \hat{\mathbf{Y}} = \hat{Y}, \hat{\mathbf{\Lambda}} = \hat{\Lambda})$$

and therefore

$$\mathbb{P}_\Theta(\mathbf{Y}[i] = 1, \mathbf{Y}[j] = 0 | \hat{\mathbf{Y}} = \hat{Y}, \hat{\mathbf{\Lambda}} = \hat{\Lambda})$$

$$= \frac{\exp\left((\Theta_i^1)^\mathsf{T}\Phi_i^1(1,\hat{Y}) + (\Theta_j^1)^\mathsf{T}\Phi_j^1(0,\hat{Y}) + \sum_{l \neq i,j}(\Theta_l^1)^\mathsf{T}\Phi_l^1(0,\hat{Y}) + \sum_{l \neq i,j}(\Theta_l^2)^\mathsf{T}\Phi_l^2(0,\hat{\Lambda}) + (\Theta^3)^\mathsf{T}\Phi^3(\hat{Y},\hat{\Lambda})\right)}{\sum_\mathbf{Y} \exp\left(\sum_{l=1}^k(\Theta_l^1)^\mathsf{T}\Phi_l^1(\mathbf{Y}[l],\hat{Y}) + \sum_{l=1}^k(\Theta_l^2)^\mathsf{T}\Phi_l^2(\mathbf{Y}[l],\hat{\Lambda}) + (\Theta^3)^\mathsf{T}\Phi^3(\hat{Y},\hat{\Lambda})\right)}$$

$$\cdot \exp\left((\Theta_i^2)^\mathsf{T}\Phi_i^2(1,\hat{\Lambda}) + (\Theta_j^2)^\mathsf{T}\Phi_j^2(0,\hat{\Lambda})\right)$$

$$= \frac{\exp\left((\Theta_i^1)^\mathsf{T}\Phi_i^1(1,\hat{Y}) + (\Theta_j^1)^\mathsf{T}\Phi_j^1(0,\hat{Y}) + \sum_{l \neq i,j}(\Theta_l^1)^\mathsf{T}\Phi_l^1(0,\hat{Y}) + \sum_{l \neq i,j}(\Theta_l^2)^\mathsf{T}\Phi_l^2(0,\hat{\Lambda})\right)}{\sum_\mathbf{Y} \exp\left(\sum_{l=1}^k(\Theta_l^1)^\mathsf{T}\Phi_l^1(\mathbf{Y}[l],\hat{Y}) + \sum_{l=1}^k(\Theta_l^2)^\mathsf{T}\Phi_l^2(\mathbf{Y}[l],\hat{\Lambda})\right)}$$

$$\cdot \exp\left((\Theta_i^2)^\mathsf{T}\Phi_i^2(1,\hat{\Lambda}) + (\Theta_j^2)^\mathsf{T}\Phi_j^2(0,\hat{\Lambda})\right) \tag{9}$$

which is independent of Θ^3. Similarly,

$$\mathbb{P}_\Theta(\mathbf{Y}[i] = 0, \mathbf{Y}[j] = 1 | \hat{\mathbf{Y}} = \hat{Y}, \hat{\mathbf{\Lambda}} = \hat{\Lambda})$$

$$= \frac{\exp\left((\Theta_i^1)^\mathsf{T}\Phi_i^1(0,\hat{Y}) + (\Theta_j^1)^\mathsf{T}\Phi_j^1(1,\hat{Y}) + \sum_{l \neq i,j}(\Theta_l^1)^\mathsf{T}\Phi_l^1(0,\hat{Y}) + \sum_{l \neq i,j}(\Theta_l^2)^\mathsf{T}\Phi_l^2(0,\hat{\Lambda})\right)}{\sum_\mathbf{Y} \exp\left(\sum_{l=1}^k(\Theta_l^1)^\mathsf{T}\Phi_l^1(\mathbf{Y}[l],\hat{Y}) + \sum_{l=1}^k(\Theta_l^2)^\mathsf{T}\Phi_l^2(\mathbf{Y}[l],\hat{\Lambda})\right)}$$

$$\cdot \exp\left((\Theta_i^2)^\mathsf{T}\Phi_i^2(0,\hat{\Lambda}) + (\Theta_j^2)^\mathsf{T}\Phi_j^2(1,\hat{\Lambda})\right), \tag{10}$$

and

$$\mathbb{P}_\Theta(\mathbf{Y}[i] = 0, \mathbf{Y}[j] = 0 | \hat{\mathbf{Y}} = \hat{Y}, \hat{\mathbf{\Lambda}} = \hat{\Lambda})$$

$$= \frac{\sum_{l \neq i,j}\exp\left((\Theta_l^1)^\mathsf{T}\Phi_l^1(1,\hat{Y}) + (\Theta_l^2)^\mathsf{T}\Phi_l^2(1,\hat{\Lambda}) + \sum_{s \neq l}(\Theta_s^1)^\mathsf{T}\Phi_s^1(0,\hat{Y}) + \sum_{s \neq l}(\Theta_s^2)^\mathsf{T}\Phi_s^2(0,\hat{\Lambda})\right)}{\sum_\mathbf{Y} \exp\left(\sum_{l=1}^k(\Theta_l^1)^\mathsf{T}\Phi_l^1(\mathbf{Y}[l],\hat{Y}) + \sum_{l=1}^k(\Theta_l^2)^\mathsf{T}\Phi_l^2(\mathbf{Y}[l],\hat{\Lambda})\right)}. \tag{11}$$

If $\mathbf{Y}[i]$ and $\mathbf{Y}[j]$ are symmetric, let $\tilde{\Theta}_i^l = \Theta_j^l$, and $\tilde{\Theta}_j^l = \Theta_i^l$ ($l \in [2]$), we have

$$\frac{\mathbb{P}_\Theta(\mathbf{Y}[i] = 1, \mathbf{Y}[j] = 0 | \hat{\mathbf{Y}} = \hat{Y}, \hat{\mathbf{\Lambda}} = \hat{\Lambda})}{\mathbb{P}_{\tilde{\Theta}}(\mathbf{Y}[i] = 0, \mathbf{Y}[j] = 1 | \hat{\mathbf{Y}} = \hat{Y}, \hat{\mathbf{\Lambda}} = \hat{\Lambda})}$$

$$= \frac{\sum_\mathbf{Y} \exp\left(\sum_{l=1}^k(\tilde{\Theta}_l^1)^\mathsf{T}\Phi_l^1(\mathbf{Y}[l],\hat{Y}) + \sum_{l=1}^k(\tilde{\Theta}_l^2)^\mathsf{T}\Phi_l^2(\mathbf{Y}[l],\hat{\Lambda})\right)}{\sum_\mathbf{Y} \exp\left(\sum_{l=1}^k(\Theta_l^1)^\mathsf{T}\Phi_l^1(\mathbf{Y}[l],\hat{Y}) + \sum_{l=1}^k(\Theta_l^2)^\mathsf{T}\Phi_l^2(\mathbf{Y}[l],\hat{\Lambda})\right)}$$

$$\cdot \exp\left((\Theta_i^1)^\mathsf{T}(\Phi_i^1(1,\hat{Y}) - \Phi_j^1(1,\hat{Y})) + (\Theta_j^1)^\mathsf{T}(\Phi_j^1(0,\hat{Y}) - \Phi_i^1(0,\hat{Y}))\right).$$

Similarly,

$$\frac{\mathbb{P}_\Theta(\mathbf{Y}[i] = 0, \mathbf{Y}[j] = 1 | \hat{\mathbf{Y}} = \hat{Y}, \hat{\mathbf{\Lambda}} = \hat{\Lambda})}{\mathbb{P}_{\tilde{\Theta}}(\mathbf{Y}[i] = 1, \mathbf{Y}[j] = 0 | \hat{\mathbf{Y}} = \hat{Y}, \hat{\mathbf{\Lambda}} = \hat{\Lambda})}$$

$$= \frac{\sum_\mathbf{Y} \exp\left(\sum_{l=1}^k(\tilde{\Theta}_l^1)^\mathsf{T}\Phi_l^1(\mathbf{Y}[l],\hat{Y}) + \sum_{l=1}^k(\tilde{\Theta}_l^2)^\mathsf{T}\Phi_l^2(\mathbf{Y}[l],\hat{\Lambda})\right)}{\sum_\mathbf{Y} \exp\left(\sum_{l=1}^k(\Theta_l^1)^\mathsf{T}\Phi_l^1(\mathbf{Y}[l],\hat{Y}) + \sum_{l=1}^k(\Theta_l^2)^\mathsf{T}\Phi_l^2(\mathbf{Y}[l],\hat{\Lambda})\right)}$$

$$\cdot \exp\left((\Theta_i^1)^\mathsf{T}(\Phi_i^1(0,\hat{Y}) - \Phi_j^1(0,\hat{Y})) + (\Theta_j^1)^\mathsf{T}(\Phi_j^1(1,\hat{Y}) - \Phi_i^1(1,\hat{Y}))\right),$$

and

$$\frac{\mathbb{P}_\Theta(\mathbf{Y}[i] = 0, \mathbf{Y}[j] = 0 | \hat{\mathbf{Y}} = \hat{Y}, \hat{\mathbf{\Lambda}} = \hat{\Lambda})}{\mathbb{P}_{\tilde{\Theta}}(\mathbf{Y}[i] = 0, \mathbf{Y}[j] = 0 | \hat{\mathbf{Y}} = \hat{Y}, \hat{\mathbf{\Lambda}} = \hat{\Lambda})}$$

$$= \frac{\sum_\mathbf{Y} \exp\left(\sum_{l=1}^k(\tilde{\Theta}_l^1)^\mathsf{T}\Phi_l^1(\mathbf{Y}[l],\hat{Y}) + \sum_{l=1}^k(\tilde{\Theta}_l^2)^\mathsf{T}\Phi_l^2(\mathbf{Y}[l],\hat{\Lambda})\right)}{\sum_\mathbf{Y} \exp\left(\sum_{l=1}^k(\Theta_l^1)^\mathsf{T}\Phi_l^1(\mathbf{Y}[l],\hat{Y}) + \sum_{l=1}^k(\Theta_l^2)^\mathsf{T}\Phi_l^2(\mathbf{Y}[l],\hat{\Lambda})\right)}$$

$$\cdot \exp\left((\Theta_i^1)^\mathsf{T}(\Phi_i^1(0,\hat{Y}) - \Phi_j^1(0,\hat{Y})) + (\Theta_j^1)^\mathsf{T}(\Phi_j^1(0,\hat{Y}) - \Phi_i^1(0,\hat{Y}))\right).$$

By Definition 4, we have

$$0 = (\Theta_i^1)^\mathsf{T}(\Phi_i^1(0,\hat{Y}) - \Phi_j^1(0,\hat{Y})) + (\Theta_j^1)^\mathsf{T}(\Phi_j^1(0,\hat{Y}) - \Phi_i^1(0,\hat{Y}))$$

$$= (\Theta_i^1)^\mathsf{T}(\Phi_i^1(1,\hat{Y}) - \Phi_j^1(1,\hat{Y})) + (\Theta_j^1)^\mathsf{T}(\Phi_j^1(0,\hat{Y}) - \Phi_i^1(0,\hat{Y}))$$

$$= (\Theta_i^1)^\mathsf{T}(\Phi_i^1(0,\hat{Y}) - \Phi_j^1(0,\hat{Y})) + (\Theta_j^1)^\mathsf{T}(\Phi_j^1(1,\hat{Y}) - \Phi_i^1(1,\hat{Y})), \tag{12}$$

which leads to:

$$\frac{\mathbb{P}_\Theta(\mathbf{Y}[i] = 1, \mathbf{Y}[j] = 0|\hat{Y}, \hat{\Lambda})}{\mathbb{P}_{\tilde{\Theta}}(\mathbf{Y}[i] = 0, \mathbf{Y}[j] = 1|\hat{Y}, \hat{\Lambda})} = \frac{\mathbb{P}_\Theta(\mathbf{Y}[i] = 0, \mathbf{Y}[j] = 1|\hat{Y}, \hat{\Lambda})}{\mathbb{P}_{\tilde{\Theta}}(\mathbf{Y}[i] = 1, \mathbf{Y}[j] = 0|\hat{Y}, \hat{\Lambda})} = \frac{\mathbb{P}_\Theta(\mathbf{Y}[i] = 0, \mathbf{Y}[j] = 0|\hat{Y}, \hat{\Lambda})}{\mathbb{P}_{\tilde{\Theta}}(\mathbf{Y}[i] = 0, \mathbf{Y}[j] = 0|\hat{Y}, \hat{\Lambda})}.$$

Since

$$\mathbb{P}_\Theta(\mathbf{Y}[i] = 1, \mathbf{Y}[j] = 0|\hat{Y}, \hat{\Lambda}) + \mathbb{P}_\Theta(\mathbf{Y}[i] = 0, \mathbf{Y}[j] = 1|\hat{Y}, \hat{\Lambda}) + \mathbb{P}_\Theta(\mathbf{Y}[i] = 0, \mathbf{Y}[j] = 0|\hat{Y}, \hat{\Lambda}) = 1,$$

and

$$\mathbb{P}_{\tilde{\Theta}}(\mathbf{Y}[i] = 0, \mathbf{Y}[j] = 1|\hat{Y}, \hat{\Lambda}) + \mathbb{P}_{\tilde{\Theta}}(\mathbf{Y}[i] = 1, \mathbf{Y}[j] = 0|\hat{Y}, \hat{\Lambda}) + \mathbb{P}_{\tilde{\Theta}}(\mathbf{Y}[i] = 0, \mathbf{Y}[j] = 0|\hat{Y}, \hat{\Lambda}) = 1,$$

Eq. (12) further leads to

$$\mathbb{P}_\Theta(\mathbf{Y}[i] = 1, \mathbf{Y}[j] = 0|\hat{Y}, \hat{\Lambda}) = \mathbb{P}_{\tilde{\Theta}}(\mathbf{Y}[i] = 0, \mathbf{Y}[j] = 1|\hat{Y}, \hat{\Lambda})$$

$$\mathbb{P}_\Theta(\mathbf{Y}[i] = 0, \mathbf{Y}[j] = 1|\hat{Y}, \hat{\Lambda}) = \mathbb{P}_{\tilde{\Theta}}(\mathbf{Y}[i] = 1, \mathbf{Y}[j] = 0|\hat{Y}, \hat{\Lambda})$$

$$\mathbb{P}_\Theta(\mathbf{Y}[i] = 0, \mathbf{Y}[j] = 0|\hat{Y}, \hat{\Lambda}) = \mathbb{P}_{\tilde{\Theta}}(\mathbf{Y}[i] = 0, \mathbf{Y}[j] = 0|\hat{Y}, \hat{\Lambda}).$$

Since $\mathbb{P}_\Theta(\mathbf{Y}[i] = 1, \mathbf{Y}[j] = 1|\hat{Y}, \hat{\Lambda}) = \mathbb{P}_{\tilde{\Theta}}(\mathbf{Y}[i] = 1, \mathbf{Y}[j] = 1|\hat{Y}, \hat{\Lambda}) = 0$ trivially holds, we have that y_{d_i} and y_{d_j} indistinguishable.

The proof is completed. $\qquad\square$

C.6 PROOF OF THEOREM 3: SUFFICIENT CONDITION

We then prove that if $\mathbf{Y}[i]$ and $\mathbf{Y}[j]$ have asymmetric dependency structures, then y_{d_i} and y_{d_j} are distinguishable.

Proof. Let $\Theta = (\{\Theta_s^l\}_{(s,l) \in [k] \times [2]}, \Theta^3)$ be any pair of parameter satisfying that there exists $\{\tilde{\Theta}_s^l\}_{(s,l) \in \{i,j\} \times [2]}$, such that Eq. (4) holds. By Eqs. (10), (9), and Eq. (11) together with Eq. (4), we have

$$\frac{\exp\left((\Theta_i^1)^\mathsf{T}\Phi_i^1(1, \hat{Y}) + (\Theta_j^1)^\mathsf{T}\Phi_j^1(0, \hat{Y}) + (\Theta_i^2)^\mathsf{T}\Phi_i^2(1, \hat{\Lambda}) + (\Theta_j^2)^\mathsf{T}\Phi_j^2(0, \hat{\Lambda})\right)}{\exp\left((\tilde{\Theta}_i^1)^\mathsf{T}\Phi_i^1(0, \hat{Y}) + (\tilde{\Theta}_j^1)^\mathsf{T}\Phi_j^1(1, \hat{Y}) + (\tilde{\Theta}_i^2)^\mathsf{T}\Phi_i^2(0, \hat{\Lambda}) + (\tilde{\Theta}_j^2)^\mathsf{T}\Phi_j^2(1, \hat{\Lambda})\right)}$$

$$=\frac{\exp\left((\Theta_i^1)^\mathsf{T}\Phi_i^1(0, \hat{Y}) + (\Theta_j^1)^\mathsf{T}\Phi_j^1(1, \hat{Y}) + (\Theta_i^2)^\mathsf{T}\Phi_i^2(0, \hat{\Lambda}) + (\Theta_j^2)^\mathsf{T}\Phi_j^2(1, \hat{\Lambda})\right)}{\exp\left((\tilde{\Theta}_i^1)^\mathsf{T}\Phi_i^1(1, \hat{Y}) + (\tilde{\Theta}_j^1)^\mathsf{T}\Phi_j^1(0, \hat{Y}) + (\tilde{\Theta}_i^2)^\mathsf{T}\Phi_i^2(1, \hat{\Lambda}) + (\tilde{\Theta}_j^2)^\mathsf{T}\Phi_j^2(0, \hat{\Lambda})\right)}$$

$$=\frac{\exp\left((\Theta_i^1)^\mathsf{T}\Phi_i^1(0, \hat{Y}) + (\Theta_j^1)^\mathsf{T}\Phi_j^1(0, \hat{Y}) + (\Theta_i^2)^\mathsf{T}\Phi_i^2(0, \hat{\Lambda}) + (\Theta_j^2)^\mathsf{T}\Phi_j^2(0, \hat{\Lambda})\right)}{\exp\left((\tilde{\Theta}_i^1)^\mathsf{T}\Phi_i^1(0, \hat{Y}) + (\tilde{\Theta}_j^1)^\mathsf{T}\Phi_j^1(0, \hat{Y}) + (\tilde{\Theta}_i^2)^\mathsf{T}\Phi_i^2(0, \hat{\Lambda}) + (\tilde{\Theta}_j^2)^\mathsf{T}\Phi_j^2(0, \hat{\Lambda})\right)}$$

$$=\frac{\sum_\mathbf{Y} \exp\left((\Theta^1)^\mathsf{T}\Phi^1(\mathbf{Y}, \hat{Y}) + (\Theta^2)^\mathsf{T}\Phi^2(\mathbf{Y}, \hat{\Lambda})\right)}{\sum_\mathbf{Y} \exp\left((\tilde{\Theta}^1)^\mathsf{T}\Phi^1(\mathbf{Y}, \hat{Y}) + (\tilde{\Theta}^2)^\mathsf{T}\Phi^2(\mathbf{Y}, \hat{\Lambda})\right)}.$$

Therefore, there exists a function $g(\hat{\Lambda}, \hat{Y})$, such that, for any $(Y[i], Y[j]) \in \{0, 1\} \times \{0, 1\}/\{(1, 1)\}$

$$g(\hat{\Lambda}, \hat{Y}) = ((\Theta_i^1)^\mathsf{T}\Phi_i^1(Y[i], \hat{Y}) + (\Theta_j^1)^\mathsf{T}\Phi_j^1(Y[j], \hat{Y}) + (\Theta_i^2)^\mathsf{T}\Phi_i^2(Y[i], \hat{\Lambda}) + (\Theta_j^2)^\mathsf{T}\Phi_j^2(Y[j], \hat{\Lambda}))$$
$$- ((\tilde{\Theta}_i^1)^\mathsf{T}\Phi_i^1(Y[j], \hat{Y}) + (\tilde{\Theta}_j^1)^\mathsf{T}\Phi_j^1(Y[i], \hat{Y}) + (\tilde{\Theta}_i^2)^\mathsf{T}\Phi_i^2(Y[j], \hat{\Lambda}) + (\tilde{\Theta}_j^2)^\mathsf{T}\Phi_j^2(Y[i], \hat{\Lambda})). \tag{13}$$

In Eq. (13), fix $Y[i] = 0$ and set $Y[j]$ respectively to 0 and 1, we obtain that

$$((\Theta_j^1)^\mathsf{T}\Phi_j^1(1, \hat{Y}) + (\Theta_j^2)^\mathsf{T}\Phi_j^2(1, \hat{\Lambda})) - ((\tilde{\Theta}_i^1)^\mathsf{T}\Phi_i^1(1, \hat{Y}) + (\tilde{\Theta}_i^2)^\mathsf{T}\Phi_i^2(1, \hat{\Lambda}))$$
$$=((\Theta_j^1)^\mathsf{T}\Phi_j^1(0, \hat{Y}) + (\Theta_j^2)^\mathsf{T}\Phi_j^2(0, \hat{\Lambda})) - ((\tilde{\Theta}_i^1)^\mathsf{T}\Phi_i^1(0, \hat{Y}) + (\tilde{\Theta}_i^2)^\mathsf{T}\Phi_i^2(0, \hat{\Lambda})). \tag{14}$$

We further set $\hat{Y}$ in Eq. (14) respectively to e_a and $\mathbf{0}$ for any fixed $y_a \in \hat{\mathcal{Y}}$ and minus them, i.e.,

$$((\Theta_j^1)^\mathsf{T}\Phi_j^1(1, e_a) - (\Theta_j^1)^\mathsf{T}\Phi_j^1(1, \mathbf{0})) - ((\tilde{\Theta}_i^1)^\mathsf{T}\Phi_i^1(1, e_a) - (\tilde{\Theta}_i^1)^\mathsf{T}\Phi_i^1(1, \mathbf{0}))$$
$$=((\Theta_j^1)^\mathsf{T}\Phi_j^1(0, e_a) - (\Theta_j^1)^\mathsf{T}\Phi_j^1(0, \mathbf{0})) - ((\tilde{\Theta}_i^1)^\mathsf{T}\Phi_i^1(0, e_a) - (\tilde{\Theta}_i^1)^\mathsf{T}\Phi_i^1(0, \mathbf{0})).$$

By simple rearranging, we obtain

$$\theta_{j,a}^1(\phi_{j,a}^1(1,1) - \phi_{j,a}^1(1,0) - \phi_{j,a}^1(0,1)) = \tilde{\theta}_{i,a}^1(\phi_{i,a}^1(1,1) - \phi_{i,a}^1(1,0) - \phi_{i,a}^1(0,1)).$$

Since $\theta_{j,a}^1, \tilde{\theta}_{i,a}^1 > 0$, by definition we have

$$|\phi_{j,a}^1(1,1) - \phi_{j,a}^1(1,0) - \phi_{j,a}^1(0,1)| = 1,$$

and

$$|\phi_{i,a}^1(1,1) - \phi_{i,a}^1(1,0) - \phi_{i,a}^1(0,1)| = 1,$$

we further have $\theta_{j,a}^1 = \tilde{\theta}_{i,a}^1$, and

$$\phi_{j,a}^1(1,1) - \phi_{j,a}^1(1,0) - \phi_{j,a}^1(0,1) = \phi_{i,a}^1(1,1) - \phi_{i,a}^1(1,0) - \phi_{i,a}^1(0,1). \tag{15}$$

Therefore, either $t_{d_j a} \in \{t^o, t^{sd}, t^{sg}\}$ and $t_{d_i a} \in \{t^o, t^{sd}, t^{sg}\}$, or $t_{d_j a} = t^e$ and $t_{d_i a} = t^e$, which by definition further indicates that $\Phi_i^2 = \Phi_j^2$ (recall the way we build dependency between Y and $\hat{\Lambda}$).

As a is arbitrarily picked, Θ_j^1 is equal to $\tilde{\Theta}_i^1$ component-wisely.

By fixing $Y[j]$ and following exact the same routine, we also have $\tilde{\Theta}_j^1 = \Theta_i^1$.

On the other hand, since $\hat{\Lambda}$ is concatenation of label vectors output by all ILFs, *i.e.*, $\hat{\Lambda} = (\Lambda_l)_{l=1}^n$, where Λ_l is the output of the l-th mode λ_l. For any $y_a \in \hat{\mathcal{Y}}$ and λ_l, such that there is a dependency between $\mathbf{Y}[i]$ and $\mathbf{\Lambda}_l[a]$, we have $\phi_{i,a,l}^2(1,1) = 1$. Therefore, fixing $\hat{Y}$ and Λ_s ($\forall s \neq l$), and setting $\Lambda_l[a] = 1$ while $\Lambda_l[b] = 0$ ($\forall b \neq a$), we have

$$((\Theta_j^1)^\mathsf{T} \Phi_j^1(1, \hat{Y}) + \theta_{j,a,l}^2 \phi_{j,a,l}^2(1,1) + \sum_{b \neq a} \theta_{j,b,l}^2 \phi_{j,b,l}^2(1,0) + \sum_{s \neq l} \sum_c \theta_{j,c,s}^2 \phi_{j,c,s}^2(1, \Lambda_s[c]))$$

$$-((\tilde{\Theta}_i^1)^\mathsf{T} \Phi_i^1(1, \hat{Y}) + \tilde{\theta}_{i,a,l}^2 \phi_{i,a,l}^2(1,1) + \sum_{b \neq a} \tilde{\theta}_{i,b,l}^2 \phi_{i,b,l}^2(1,0) + \sum_{s \neq l} \sum_c \tilde{\theta}_{i,c,s}^2 \phi_{i,c,s}^2(1, \Lambda_s[c]))$$

$$=((\Theta_j^1)^\mathsf{T} \Phi_j^1(0, \hat{Y}) + \theta_{j,a,l}^2 \phi_{j,a,l}^2(0,1) + \sum_{b \neq a} \theta_{j,b,l}^2 \phi_{j,b,l}^2(0,0) + \sum_{s \neq l} \sum_c \theta_{j,c,s}^2 \phi_{j,c,s}^2(0, \Lambda_s[c]))$$

$$-((\tilde{\Theta}_i^1)^\mathsf{T} \Phi_i^1(0, \hat{Y}) + \tilde{\theta}_{i,a,l}^2 \phi_{i,a,l}^2(0,1) + \sum_{b \neq a} \tilde{\theta}_{i,b,l}^2 \phi_{i,b,l}^2(0,0) + \sum_{s \neq l} \sum_c \tilde{\theta}_{i,c,s}^2 \phi_{i,c,s}^2(0, \Lambda_s[c])).$$

On the other hand, by Lemma 2, we can fixing $\hat{Y}$ and Λ_s ($\forall s \neq l$), and setting $\Lambda_l[b] = 0$ ($\forall b$ s.t. $\mathbf{\Lambda}_l[b]$ has dependency with $\mathbf{Y}[i]$). By $\Phi_i^2 = \Phi_j^2$, we have $\Lambda_l[b] = 0$ ($\forall b$ s.t. $\mathbf{\Lambda}_l[b]$ has dependency with $\mathbf{Y}[j]$). We then have

$$((\Theta_j^1)^\mathsf{T} \Phi_j^1(1, \hat{Y}) + \theta_{j,a,l}^2 \phi_{j,a,l}^2(1,0) + \sum_{b \neq a} \theta_{j,b,l}^2 \phi_{j,b,l}^2(1,0) + \sum_{s \neq l} \sum_c \theta_{j,c,s}^2 \phi_{j,c,s}^2(1, \Lambda_s[c]))$$

$$-((\tilde{\Theta}_i^1)^\mathsf{T} \Phi_i^1(1, \hat{Y}) + \tilde{\theta}_{i,a,l}^2 \phi_{i,a,l}^2(1,0) + \sum_{b \neq a} \tilde{\theta}_{i,b,l}^2 \phi_{i,b,l}^2(1,0) + \sum_{s \neq l} \sum_c \tilde{\theta}_{i,c,s}^2 \phi_{i,c,s}^2(1, \Lambda_s[c]))$$

$$=((\Theta_j^1)^\mathsf{T} \Phi_j^1(0, \hat{Y}) + \theta_{j,a,l}^2 \phi_{j,a,l}^2(0,0) + \sum_{b \neq a} \theta_{j,b,l}^2 \phi_{j,b,l}^2(0,0) + \sum_{s \neq l} \sum_c \theta_{j,c,s}^2 \phi_{j,c,s}^2(0, \Lambda_s[c]))$$

$$-((\tilde{\Theta}_i^1)^\mathsf{T} \Phi_i^1(0, \hat{Y}) + \tilde{\theta}_{i,a,l}^2 \phi_{i,a,l}^2(0,0) + \sum_{b \neq a} \tilde{\theta}_{i,b,l}^2 \phi_{i,b,l}^2(0,0) + \sum_{s \neq l} \sum_c \tilde{\theta}_{i,c,s}^2 \phi_{i,c,s}^2(0, \Lambda_s[c])).$$

Subtracting the above two equations leads to $\theta_{j,a,l}^2 = \tilde{\theta}_{i,a,l}^2$. Since a and l are arbitrarily picked, we conclude that $\Theta_j^2 = \tilde{\Theta}_i^2$. Following the same routine, we also have $\Theta_i^2 = \tilde{\Theta}_j^2$.

Therefore, by applying $\Theta_j^1 = \tilde{\Theta}_i^1$, $\Theta_i^1 = \tilde{\Theta}_j^1$, $\Theta_j^2 = \tilde{\Theta}_i^2$, and $\Theta_i^2 = \tilde{\Theta}_j^2$ in Eq. (13), we have for any $(Y[i], Y[j]) \in \{0,1\} \times \{0,1\}/\{(1,1)\}$,

$$g(\hat{\Lambda}, \hat{Y}) = ((\Theta_i^1)^\mathsf{T} \Phi_i^1(Y[i], \hat{Y}) + (\Theta_j^1)^\mathsf{T} \Phi_j^1(Y[j], \hat{Y})) - ((\Theta_j^1)^\mathsf{T} \Phi_i^1(Y[j], \hat{Y}) + (\Theta_i^1)^\mathsf{T} \Phi_j^1(Y[i], \hat{Y})),$$

which is equivalent to

$$(\Theta_i^1)^\mathsf{T}\Phi_i^1(1,\hat{Y}) - (\Theta_i^1)^\mathsf{T}\Phi_j^1(1,\hat{Y}) = (\Theta_i^1)^\mathsf{T}\Phi_i^1(0,\hat{Y}) - (\Theta_i^1)^\mathsf{T}\Phi_j^1(0,\hat{Y}),$$

$$(\Theta_j^1)^\mathsf{T}\Phi_j^1(1,\hat{Y}) - (\Theta_j^1)^\mathsf{T}\Phi_i^1(1,\hat{Y}) = (\Theta_j^1)^\mathsf{T}\Phi_j^1(0,\hat{Y}) - (\Theta_j^1)^\mathsf{T}\Phi_i^1(0,\hat{Y}).$$

Let $\hat{Y} = \mathbf{1}_{\hat{k}}$, we have

$$(\Theta_i^1)^\mathsf{T}((\Phi_i^1(1,\mathbf{1}_{\hat{k}}) - \Phi_i^1(0,\mathbf{1}_{\hat{k}})) - ((\Phi_j^1(1,\mathbf{1}_{\hat{k}}) - \Phi_j^1(0,\mathbf{1}_{\hat{k}})))) = 0, \tag{16}$$

$$(\Theta_j^1)^\mathsf{T}((\Phi_i^1(1,\mathbf{1}_{\hat{k}}) - \Phi_i^1(0,\mathbf{1}_{\hat{k}})) - ((\Phi_j^1(1,\mathbf{1}_{\hat{k}}) - \Phi_j^1(0,\mathbf{1}_{\hat{k}})))) = 0. \tag{17}$$

Since $\mathbf{Y}[i]$ and $\mathbf{Y}[j]$ are asymmetric, we have that there exists a, such that $t_{d_i a} \neq t_{d_j a}$. Concretely, by Eq. (15), we have $t_{d_i a} \in \{t^o, t^{sd}, t^{sg}\}$, $t_{d_j a} = \{t^o, t^{sd}, t^{sg}\}$, and $t_{d_i a} \neq t_{d_j a}$. On the other hand,

$$\phi_{i,a}^1(1,1) - \phi_{i,a}^1(0,1)) = \phi_{j,a}^1(1,1) - \phi_{j,a}^1(0,1)$$

if and only if $t_{d_i a} = t^o$, $t_{d_j a} = t^{sg}$, or $t_{d_j a} = t^o$, $t_{d_i a} = t^{sg}$, which contradicts Lemma 1.

Therefore,

$$\phi_{i,a}^1(1,1) - \phi_{i,a}^1(0,1)) \neq \phi_{j,a}^1(1,1) - \phi_{j,a}^1(0,1).$$

In this case, solutions of Θ_i^1, Θ_j^1 subject to respectively Eqs. (16) and (17) lie along a zero-measure set.

The proof is completed. $\qquad\qquad\square$

D   PROOF OF THEOREM 1

D.1   LEARNING ALGORITHM

We first present the algorithm for producing $\hat{\Theta}$ and $\hat{W}$ in Algorithm 1.

Algorithm 1 WIS

Require: Step size η, dataset $D \subset \mathcal{X}$, and initial parameter Θ_0.

   $\hat{\Theta} \rightarrow \Theta_0$.

   for all $X \in D$ **do**

      Independently sample $(\hat{\Lambda}, \hat{Y}, Y)$ from $\pi_{\hat{\Theta}}$, and $(\hat{\Lambda}', \hat{Y}', Y')$ from $\pi_{\hat{\Theta}}$ conditionally given $\hat{\Lambda}' = \hat{\Lambda}(X)$.

      $\hat{\Theta} \leftarrow \hat{\Theta} + \eta(\Phi(\hat{\Lambda}, \hat{Y}, Y) - \Phi(\hat{\Lambda}', \hat{Y}', Y'))$.

   Compute $\hat{W}$ as described in (3) using $\hat{\Theta}$.

output $(\hat{\Theta}, \hat{W})$

D.2   ASSUMPTIONS

First, the problem distribution π^* needs to be accurately modeled by some distribution Θ^* in the family that we are trying to learn:

$$\exists\Theta^* \text{ s.t. } \forall(\hat{\Lambda}, Y), \ p_{(X,Y)\sim\pi^*}(\hat{\Lambda}, Y) = p_{\theta^*}(\hat{\Lambda}, Y). \tag{18}$$

Secondly, given an example $(X, Y) \sim \pi^*$, we assume Y is independent of X given $\hat{\Lambda}(X)$:

$$(X, Y) \sim \pi^* \Rightarrow Y \perp X \mid \hat{\Lambda}(X). \tag{19}$$

This assumption encodes the idea that while the ILFs can be arbitrarily dependent on the features, they provide sufficient information to accurately identify the true label vector. Then, for any Θ, accurately learning Θ from data distribution is possible. That is, there exists an unbiased estimator $\hat{\Theta}(D)$ which is a function of the dataset D of i.i.d from π_Θ, such that, for any Θ and some $c > 0$,

$$\mathbf{Cov}(\hat{\Theta}(D)) \preceq \frac{I}{2c|D|}. \tag{20}$$

And we are reasonably certain in our guess of latent variables, *i.e.*, Y and $\hat{Y}$. That is, for any Θ, Θ^*,

$$\mathbb{E}_{\hat{\Lambda}^* \sim \Theta^*}[\mathbf{Var}_{\max}[\hat{\Lambda}^*]] \leq \frac{c}{\sqrt{2MKc_{\max}^{\frac{1}{2}}}}, \tag{21}$$

where K is the total number of labels; M is the dimension of Θ or, in other words, the number of dependencies; $c_{\max}$ is the maximum *degree* of latent variables in the factor graph; and $\mathbf{Var}_{\max}[\hat{\Lambda}^*]$ is the maximum variance of latent variables given $\hat{\Lambda}^*$. We also assume that the output of the last layer of end model h_W has bounded ℓ_∞ norm, that is, for any possible parameter W,

$$\|h_W\|_\infty \leq H. \tag{22}$$

Finally, we assume that solving Eq. (3) has bounded generalization risk such that for some $\chi > 0$, solution $\hat{W}$ satisfies

$$\mathbb{E}_{\hat{W}}\left[\ell_{\hat{\Theta}}(\hat{W}) - \min_W \ell_{\hat{\Theta}}(W)\right] \leq \chi. \tag{23}$$

D.3 PROOF OF THEOREM 1

To begin with, we state two basic lemmas needed for proofs throughout this section: Let $\mathbf{x}_1$, $\mathbf{x}_2$ be two binary random variable. Then we have variance of product of $\mathbf{x}_1$ and $\mathbf{x}_2$ can be bounded as

$$\mathbf{Var}\left[\mathbf{x}_1\mathbf{x}_2\right] \leq \mathbf{Var}\left[\mathbf{x}_1\right] + \mathbf{Var}\left[\mathbf{x}_2\right].$$

Let Y be a random vector and $\|\cdot\|_2$ be the spectral norm. Then we have

$$\|\mathbf{Cov}(Y, Y)\|_s \leq \sum_i \mathbf{Var}(Y_i).$$

Then, we borrow two lemmas from (Ratner et al., 2016), which are slightly different from the original ones but can be easily proved following the same derivations: [Lemma D.1 in (Ratner et al., 2016)] Given a family of maximum-entropy distributions

$$\pi_\Theta(\hat{\Lambda}, Y, \hat{Y}) = \frac{1}{Z_\Theta} \exp\left(\Theta^\mathsf{T} \Phi(\hat{\Lambda}, Y, \hat{Y})\right).$$

If we let J be the maximum expected log-likelihood objective, under another distribution π^*, for the event associated with the observed labeling function values $\hat{\Lambda}$,

$$J(\Theta) = \mathbb{E}_{(\hat{\Lambda}^*, Y^*, \hat{Y}^*) \sim \pi^*}\left[\log \mathbb{P}_{(\hat{\Lambda}, Y, \hat{Y}) \sim \pi_\Theta}\left(\hat{\Lambda} = \hat{\Lambda}^*\right)\right],$$

then its Hessian can be calculated as

$$\nabla^2 J(\Theta) = \mathbb{E}_{(\hat{\Lambda}^*, Y^*, \hat{Y}^*) \sim \pi^*}\left[\mathbf{Cov}_{(\hat{\Lambda}, Y, \hat{Y}) \sim \pi_\Theta}\left(\phi(\hat{\Lambda}, Y, \hat{Y}) \mid \hat{\Lambda} = \hat{\Lambda}^*\right)\right] - \mathbf{Cov}_{(\hat{\Lambda}, Y, \hat{Y}) \sim \pi_\Theta}(\phi(\hat{\Lambda}, Y, \hat{Y})).$$

[Lemma D.4 in (Ratner et al., 2016)] Suppose that we are looking at a WIS maximum likelihood estimation problem and the objective function $J(\Theta)$ is strongly concave with concavity parameter $c > 0$. If we run stochastic gradient descent using unbiased samples from a true distribution π_{Θ^*}, then if we set step size as

$$\eta = \frac{c\epsilon^2}{4},$$

and run (using a fresh sample at each iteration) for T steps, where

$$T = \frac{2}{c^2\epsilon^2} \log\left(\frac{2\|\Theta_0 - \Theta^*\|^2}{\epsilon}\right).$$

We can bound the expected parameter estimation error with

$$\mathbb{E}\left\|\hat{\Theta} - \Theta^*\right\|^2 \leq M\epsilon^2, \tag{24}$$

where M is the dimension of Θ.

Based on Lemma D.3, in order to obtain the optimization error with respect to the estimated $\hat{\Theta}$ produced by Algorithm 1, we only need to show that the WIS object function $J(\Theta)$[1] is strongly concave. We prove this through the following lemma, which is a non-trivial extension of Lemma D.3 in (Ratner et al., 2016) given the fact that we have multiple latent variables and relatively complex dependency structures with comparison to (Ratner et al., 2016):

[Extension of Lemma D.3 in (Ratner et al., 2016)] With conditions (20) and (21), the WIS objective function $J(\Theta)$ is strongly concave with strong convexity c.

We then come to bound the generalization error of $\hat{W}$ produced by Algorithm 1, using the following non-trivial extension of Lemma D.5 in (Ratner et al., 2016): [Extension of Lemma D.5 in (Ratner et al., 2016)] Suppose that conditions (18)-(23) hold. Let $\hat{W}$ be the learned parameters of the end model produced by Algorithm 1, and $\ell(W^*)$ be the minimum of cross entropy loss function ℓ. Then, we can bound the expected risk with

$$\mathbb{E}\left[\ell(\hat{W}) - \ell(W^*)\right] \leq \chi + 4cH\epsilon.$$

Finally, we conclude Lemmas (D.3), (D.3) and (D.3) as the following theorem, which is identical to the Theorem 1 in the main body of the paper:

Theorem 4 (Extension of Theorem 2 in (Ratner et al., 2016))**.** *Suppose that we run Algoirthm 1 on a WIS specification to produce $\hat{\Theta}$ and $\hat{W}$, and all conditions of Lemmas (D.3) and (D.3) are satisfied. Then, for any $\epsilon > 0$, if we set the step size to be*

$$\eta = \frac{c\epsilon^2}{4}$$

and the input dataset D is large enough such that

$$|D| > \frac{2}{c^2\epsilon^2} \log\left(\frac{2\|\Theta_0 - \Theta^*\|^2}{\epsilon}\right),$$

then we can bound the expected parameter error and the expected risk as:

$$\mathbb{E}\left\|\hat{\Theta} - \Theta^*\right\|^2 \leq M\epsilon^2, \quad \mathbb{E}\left[\ell(\hat{W}) - \ell(W^*)\right] \leq \chi + 4cH\epsilon.$$

D.4 PROOFS OF LEMMAS

Let $\mathbf{x}_1$, $\mathbf{x}_2$ be two binary random variable. Then we have variance of product of $\mathbf{x}_1$ and $\mathbf{x}_2$ can be bounded as

$$\mathbf{Var}\left[\mathbf{x}_1\mathbf{x}_2\right] \leq \mathbf{Var}\left[\mathbf{x}_1\right] + \mathbf{Var}\left[\mathbf{x}_2\right].$$

Proof. Joint distribution of $\mathbf{x}_1$ and $\mathbf{x}_2$ can be listed as the following table: (where $p_1 + p_2 + p_3 + p_4 = 1$)

$\mathbf{x_1}/\mathbf{x_2}$	0	1
0	p_1	p_2
1	p_3	p_4

Then we have

$$\mathbf{Var}\left[\mathbf{x}_1\mathbf{x}_2\right] = p_4 - p_4^2 = p_4(p_1 + p_2 + p_3),$$

while

$$\mathbf{Var}\left[\mathbf{X}_1\right] + \mathbf{Var}\left[\mathbf{X}_2\right] = (p_2 + p_4)(p_1 + p_3) + (p_3 + p_4)(p_1 + p_2) \geq p_4(p_1 + p_2 + p_3).$$

The proof is completed. □

---

[1]Note that, in the Eq. (2) of the main body of the paper, we are minimizing $-J(\Theta)$, which is equivalent to maximizing $J(\Theta)$ as discussed here.

Let Y be a random vector and $\|\cdot\|_2$ be the spectral norm. Then we have

$$\|\mathbf{Cov}(Y,Y)\|_s \leq \sum_i \mathbf{Var}(Y_i).$$

Proof. By definition of spectral norm, we have

$$\|\mathbf{Cov}(Y,Y)\|_s = \max_{\|\boldsymbol{x}\|_2 \leq 1} \boldsymbol{x}^\mathsf{T} \mathbf{Cov}(Y,Y)\boldsymbol{x}$$

Where $\boldsymbol{x}$ is a constant vector. And by Cauchy-Schwarz inequality,

$$\boldsymbol{x}^\mathsf{T}\mathbf{Cov}(Y,Y)\boldsymbol{x} = \mathbb{E}\left[\boldsymbol{x}^\mathsf{T}(Y - \mathbb{E}\left[Y\right])(Y - \mathbb{E}\left[Y\right])^\mathsf{T}\boldsymbol{x}\right] \leq \mathbb{E}\left[\|\boldsymbol{x}\|^2 \|Y - \mathbb{E}\left[Y\right]\|^2\right].$$

Because $\boldsymbol{x}$ is a constant vector and $\|\boldsymbol{x}\| \leq 1$,

$$\max_{\|\boldsymbol{x}\|_2 \leq 1} \mathbb{E}\left[\|\boldsymbol{x}\|^2 \|Y - \mathbb{E}\left[Y\right]\|^2\right]$$

$$= \max_{\|\boldsymbol{x}\|_2 \leq 1} \|\boldsymbol{x}\|^2 \mathbb{E}\left[\|Y - \mathbb{E}\left[Y\right]\|^2\right]$$

$$= \max_{\|\boldsymbol{x}\|_2 \leq 1} \|\boldsymbol{x}\|^2 \left[\sum_i \mathbf{Var}(Y_i)\right]$$

$$= \sum_i \mathbf{Var}(Y_i).$$

The proof is completed. □

[Extension of Lemma D.3 in (Ratner et al., 2016)] With conditions (20) and (21), the WIS objective function $J(\Theta)$ is strongly concave with strong convexity c.

Proof. By Lemma D.3, hessian matrix of J can be decomposed as follows:

$$\nabla^2 J(\Theta) = \mathbb{E}_{\hat{\Lambda}^* \sim \pi_{\Theta^*}} \left[\mathbf{Cov}_{(Y,\hat{Y},\hat{\Lambda}) \sim \pi_\Theta} \left(\Phi(Y,\hat{Y},\hat{\Lambda}) \mid \hat{\Lambda} = \hat{\Lambda}^*\right)\right] - \mathbf{Cov}_{(\hat{\Lambda},Y,\hat{Y}) \sim \pi_\Theta}(\Phi(\hat{\Lambda},Y,\hat{Y})).$$

Basically, to prove that $J(\Theta)$ is strongly concave with strong convexity c, we need to show for a real number $c > 0$,

$$\nabla^2 J(\Theta) \preceq c\mathbf{I}.$$

We calculate each term separately:

for the first term

$$A = \mathbb{E}_{\hat{\Lambda}^* \sim \pi_{\Theta^*}} \left[\mathbf{Cov}_{(Y,\hat{Y},\hat{\Lambda}) \sim \pi_\Theta} \left(\Phi(Y,\hat{Y},\hat{\Lambda}) \mid \hat{\Lambda} = \hat{\Lambda}^*\right)\right],$$

since A is symmetric, for any real number c, $A \leq c\mathbf{I}$, if and only if its spectral norm $\|A\|_s \leq c$, where $\|A\|_s$ equals to the eigenvalue of A with largest absolute value. Thus, we estimate $\|A\|_s$ and by Lemma D.3 we have

$$\|A\|_s \leq \mathbb{E}_{\hat{\Lambda}^* \sim \pi_\Theta^*} \left[\sum_i \mathbf{Var}_{(\hat{\Lambda},Y,\hat{Y}) \sim \pi_\Theta} \left(\phi_i(\hat{\Lambda},Y,\hat{Y}) \mid \hat{\Lambda} = \hat{\Lambda}^*\right)\right].$$

Since by definition, vector function $\Phi(\hat{\Lambda},Y,\hat{Y})$ can be represented as:

$$\Phi(\hat{\Lambda},Y,\hat{Y}) = \begin{pmatrix} \left(\phi_{y_i,y_a,j}^{\mathrm{Acc}}(Y[i],\hat{\Lambda}_j[a])\right)_{j\in[n],i\in[k],y_a\in\mathcal{Y}_{\lambda_j}(y_i)} \\ \left(\phi_{y_a,j}^{\mathrm{Acc}}(Y[a],\hat{\Lambda}_j[a])\right)_{j\in[n],y_a\in\mathcal{Y}_{\lambda_j}} \\ \left(\phi_{y_a,y_b}^{t_{ab}}(\hat{Y}[a],\hat{Y}[b])\right)_{a,b\in[\hat{k}]} \\ \left(\phi_{y_i,y_a}^{t_{ia}}(Y[i],\hat{Y}[a])\right)_{i\in[k],a\in[\hat{k}]} \end{pmatrix},$$

So we have

$$
\mathbb{E}_{\hat{\Lambda}^* \sim \pi_\Theta^*} \left[\sum_i \mathbf{Var}_{(\hat{\Lambda}, Y, \hat{Y}) \sim \pi_\Theta} \left(\phi_i(\hat{\Lambda}, Y, \hat{Y}) \mid \hat{\Lambda} = \hat{\Lambda}^* \right) \right]
$$

$$
= \left(\mathbb{E}_{\hat{\Lambda}^* \sim \pi_{\Theta^*}} \left[\left(\sum_{i=1}^k \sum_{j=1}^n \sum_{y_a \in \mathcal{Y}_{\lambda_j}(y_i)} \mathbf{Var}_{(\hat{\Lambda}, Y, \hat{Y}) \sim \pi_\Theta} \left(\phi_{y_i, y_a, j}^{\mathrm{Acc}}(Y[i], \hat{\Lambda}_j[a]) \mid \hat{\Lambda} = \hat{\Lambda}^* \right) \right) \right] \right.
$$

$$
+ \mathbb{E}_{\hat{\Lambda}^* \sim \pi_{\Theta^*}} \left[\left(\sum_{j=1}^n \sum_{y_a \in \mathcal{Y}_{\lambda_j}} \mathbf{Var}_{(\hat{\Lambda}, Y, \hat{Y}) \sim \pi_\Theta} \left(\phi_{y_a, j}^{\mathrm{Acc}}(Y[a], \hat{\Lambda}_j[a]) \mid \hat{\Lambda} = \hat{\Lambda}^* \right) \right) \right]
$$

$$
+ \mathbb{E}_{\hat{\Lambda}^* \sim \pi_{\Theta^*}} \left[\left(\sum_{1 \le a, b \le \hat{k}} \mathbf{Var}_{(\hat{\Lambda}, Y, \hat{Y}) \sim \pi_\Theta} \left(\phi_{y_a, y_b}^{t_{ab}}(\hat{Y}[a], \hat{Y}[b]) \mid \hat{\Lambda} = \hat{\Lambda}^* \right) \right) \right]
$$

$$
+ \mathbb{E}_{\hat{\Lambda}^* \sim \pi_{\Theta^*}} \left[\left(\sum_{i=1}^k \sum_{a=1}^{\hat{k}} \mathbf{Var}_{(\hat{\Lambda}, Y, \hat{Y}) \sim \pi_\Theta} \left(\phi_{y_i, y_a}^{t_{ia}}(Y[i], \hat{Y}[a]) \mid \hat{\Lambda} = \hat{\Lambda}^* \right) \right) \right] \right)
$$

$$
= A_1 + A_2 + A_3 + A_4,
$$

where

$$
A_1 = \mathbb{E}_{\hat{\Lambda}^* \sim \pi_{\Theta^*}} \left[\left(\sum_{i=1}^k \sum_{j=1}^n \sum_{y_a \in \mathcal{Y}_{\lambda_j}(y_i)} \mathbf{Var}_{(\hat{\Lambda}, Y, \hat{Y}) \sim \pi_\Theta} \left(\phi_{y_i, y_a, j}^{\mathrm{Acc}}(Y[i], \hat{\Lambda}_j[a]) \mid \hat{\Lambda} = \hat{\Lambda}^* \right) \right) \right];
$$

$$
A_2 = \mathbb{E}_{\hat{\Lambda}^* \sim \pi_{\Theta^*}} \left[\left(\sum_{j=1}^n \sum_{y_a \in \mathcal{Y}_{\lambda_j}} \mathbf{Var}_{(\hat{\Lambda}, Y, \hat{Y}) \sim \pi_\Theta} \left(\phi_{y_a, j}^{\mathrm{Acc}}(Y[a], \hat{\Lambda}_j[a]) \mid \hat{\Lambda} = \hat{\Lambda}^* \right) \right) \right];
$$

$$
A_3 = \mathbb{E}_{\hat{\Lambda}^* \sim \pi_{\Theta^*}} \left[\left(\sum_{1 \le a, b \le \hat{k}} \mathbf{Var}_{(\hat{\Lambda}, Y, \hat{Y}) \sim \pi_\Theta} \left(\phi_{y_a, y_b}^{t_{ab}}(\hat{Y}[a], \hat{Y}[b]) \mid \hat{\Lambda} = \hat{\Lambda}^* \right) \right) \right];
$$

$$
A_4 = \mathbb{E}_{\hat{\Lambda}^* \sim \pi_{\Theta^*}} \left[\left(\sum_{i=1}^k \sum_{a=1}^{\hat{k}} \mathbf{Var}_{(\hat{\Lambda}, Y, \hat{Y}) \sim \pi_\Theta} \left(\phi_{y_i, y_a}^{t_{ia}}(Y[i], \hat{Y}[a]) \mid \hat{\Lambda} = \hat{\Lambda}^* \right) \right) \right].
$$

We then bound the four terms respectively. As for A_1, for fixed $\hat{\Lambda}^*$, we have

$$
\sum_{i=1}^k \sum_{j=1}^n \sum_{y_a \in \mathcal{Y}_{\lambda_j}(y_i)} \mathbf{Var}_{(\hat{\Lambda}, Y, \hat{Y}) \sim \pi_\Theta} \left(\phi_{y_i, y_a, j}^{\mathrm{Acc}}(Y[i], \hat{\Lambda}_j[a]) \mid \hat{\Lambda} = \hat{\Lambda}^* \right)
$$

$$
= \sum_{i=1}^k \sum_{j=1}^n \sum_{y_a \in \mathcal{Y}_{\lambda_j}(y_i)} \mathbf{Var}_{(\hat{\Lambda}, Y, \hat{Y}) \sim \pi_\Theta} \left(\mathbf{1}_{Y[i] = \hat{\Lambda}_j[a]} \mid \hat{\Lambda} = \hat{\Lambda}^* \right)
$$

$$
= \sum_{i=1}^k \left[\sum_{j \in [n], y_a \in \mathcal{Y}_{\lambda_j}(y_i), \hat{\Lambda}_j[a] = 1} \mathbf{Var}_{(\hat{\Lambda}, Y, \hat{Y}) \sim \pi_\Theta} \left(\mathbf{1}_{Y[i] = \hat{\Lambda}_j[a]} \mid \hat{\Lambda} = \hat{\Lambda}^* \right) \right]
$$

$$
= \sum_{i=1}^k \left[\sum_{j \in [n], y_a \in \mathcal{Y}_{\lambda_j}(y_i), \hat{\Lambda}_j[a] = 1} \mathbf{Var}_{(\hat{\Lambda}, Y, \hat{Y}) \sim \pi_\Theta} \left(Y[i] \mid \hat{\Lambda} = \hat{\Lambda}^* \right) \right]
$$

$$
\le \sum_{i=1}^k n_i \mathbf{Var}_{(\hat{\Lambda}, Y, \hat{Y}) \sim \pi_\Theta} \left(Y[i] \mid \hat{\Lambda} = \hat{\Lambda}^* \right),
$$

where n_i is the number of ILFs whose label space contains label that is non-exclusive to label y_i, $i.e.$, $n_i = |\{j \in [n] | \mathcal{Y}_{\lambda_j}(y_i) \neq \emptyset\}|$.

Therefore, we have

$$A_1 \leq \sum_{i=1}^{k} n_i \mathbb{E}_{\hat{\Lambda}^* \sim \pi_{\Theta^*}} \mathbf{Var}_{(\hat{\Lambda}, Y, \hat{Y}) \sim \pi_{\Theta}} \left(Y[i] \mid \hat{\Lambda} = \hat{\Lambda}^* \right).$$

Similarly, for A_2, we have

$$A_2 \leq \sum_{i=k+1}^{k+\hat{k}} n_i \mathbb{E}_{\hat{\Lambda}^* \sim \pi_{\Theta^*}} \mathbf{Var}_{(\hat{\Lambda}, Y, \hat{Y}) \sim \pi_{\Theta}} \left(\hat{Y}[i] \mid \hat{\Lambda} = \hat{\Lambda}^* \right),$$

As for A_3, for fixed $\hat{\Lambda}^*$ and any $y_a, y_b \in \hat{\mathcal{Y}}$, we further separate the proof into subcases by t_{ab}:

(1). $t_{ab} = t^o$. In this case,

$$\mathbf{Var}_{(\hat{\Lambda}, Y, \hat{Y}) \sim \pi_{\Theta}} \left(\phi_{y_a, y_b}^{t_{ab}}(\hat{Y}[a], \hat{Y}[b]) \mid \hat{\Lambda} = \hat{\Lambda}^* \right)$$

$$= \mathbf{Var}_{(\hat{\Lambda}, Y, \hat{Y}) \sim \pi_{\Theta}} \left(\mathbf{1}_{\hat{Y}[a] = \hat{Y}[b]} \mid \hat{\Lambda} = \hat{\Lambda}^* \right)$$

$$= \mathbf{Var}_{(\hat{\Lambda}, Y, \hat{Y}) \sim \pi_{\Theta}} \left(\hat{Y}[a] * \hat{Y}[b] \mid \hat{\Lambda} = \hat{\Lambda}^* \right)$$

$$\overset{(*)}{\leq} \mathbf{Var}_{(\hat{\Lambda}, Y, \hat{Y}) \sim \pi_{\Theta}} \left(\hat{Y}[a] \mid \hat{\Lambda} = \hat{\Lambda}^* \right) + \mathbf{Var}_{(\hat{\Lambda}, Y, \hat{Y}) \sim \pi_{\Theta}} \left(\hat{Y}[b] \mid \hat{\Lambda} = \hat{\Lambda}^* \right),$$

where Eq. $(*)$ is due to Lemma D.3.

(2). $t_{ab} = t^e$. Similarly,

$$\mathbf{Var}_{(\hat{\Lambda}, Y, \hat{Y}) \sim \pi_{\Theta}} \left(\phi_{y_a, y_b}^{t_{ab}}(\hat{Y}[a], \hat{Y}[b]) \mid \hat{\Lambda} = \hat{\Lambda}^* \right)$$

$$= \mathbf{Var}_{(\hat{\Lambda}, Y, \hat{Y}) \sim \pi_{\Theta}} \left(-\mathbf{1}_{\hat{Y}[a] = \hat{Y}[b] = 1} \mid \hat{\Lambda} = \hat{\Lambda}^* \right)$$

$$= \mathbf{Var}_{(\hat{\Lambda}, Y, \hat{Y}) \sim \pi_{\Theta}} \left(\mathbf{1}_{\hat{Y}[a] = \hat{Y}[b] = 1} \mid \hat{\Lambda} = \hat{\Lambda}^* \right)$$

$$= \mathbf{Var}_{(\hat{\Lambda}, Y, \hat{Y}) \sim \pi_{\Theta}} \left(\hat{Y}[a] * \hat{Y}[b] \mid \hat{\Lambda} = \hat{\Lambda}^* \right)$$

$$\leq \mathbf{Var}_{(\hat{\Lambda}, Y, \hat{Y}) \sim \pi_{\Theta}} \left(\hat{Y}[a] \mid \hat{\Lambda} = \hat{\Lambda}^* \right) + \mathbf{Var}_{(\hat{\Lambda}, Y, \hat{Y}) \sim \pi_{\Theta}} \left(\hat{Y}[b] \mid \hat{\Lambda} = \hat{\Lambda}^* \right),$$

(3). $t_{ab} = t^{sg}$. In this case,

$$\mathbf{Var}_{(\hat{\Lambda}, Y, \hat{Y}) \sim \pi_{\Theta}} \left(\phi_{y_a, y_b}^{t_{ab}}(\hat{Y}[a], \hat{Y}[b]) \mid \hat{\Lambda} = \hat{\Lambda}^* \right)$$

$$= \mathbf{Var}_{(\hat{\Lambda}, Y, \hat{Y}) \sim \pi_{\Theta}} \left(-\mathbf{1}_{\hat{Y}[a] = 1, \hat{Y}[b] = 0} \mid \hat{\Lambda} = \hat{\Lambda}^* \right)$$

$$= \mathbf{Var}_{(\hat{\Lambda}, Y, \hat{Y}) \sim \pi_{\Theta}} \left((1 - \hat{Y}[a]) * \hat{Y}[b] \mid \hat{\Lambda} = \hat{\Lambda}^* \right)$$

$$\leq \mathbf{Var}_{(\hat{\Lambda}, Y, \hat{Y}) \sim \pi_{\Theta}} \left(1 - \hat{Y}[a] \mid \hat{\Lambda} = \hat{\Lambda}^* \right) + \mathbf{Var}_{(\hat{\Lambda}, Y, \hat{Y}) \sim \pi_{\Theta}} \left(\hat{Y}[b] \mid \hat{\Lambda} = \hat{\Lambda}^* \right)$$

$$= \mathbf{Var}_{(\hat{\Lambda}, Y, \hat{Y}) \sim \pi_{\Theta}} \left(\hat{Y}[a] \mid \hat{\Lambda} = \hat{\Lambda}^* \right) + \mathbf{Var}_{(\hat{\Lambda}, Y, \hat{Y}) \sim \pi_{\Theta}} \left(\hat{Y}[b] \mid \hat{\Lambda} = \hat{\Lambda}^* \right),$$

(4). $t_{ab} = t^{sd}$. Similar to (3).,

$$\mathbf{Var}_{(\hat{\Lambda}, Y, \hat{Y}) \sim \pi_{\Theta}} \left(\phi_{y_a, y_b}^{t_{ab}}(\hat{Y}[a], \hat{Y}[b]) \mid \hat{\Lambda} = \hat{\Lambda}^* \right)$$

$$= \mathbf{Var}_{(\hat{\Lambda}, Y, \hat{Y}) \sim \pi_{\Theta}} \left(-\mathbf{1}_{\hat{Y}[a] = 0, \hat{Y}[b] = 1} \mid \hat{\Lambda} = \hat{\Lambda}^* \right)$$

$$= \mathbf{Var}_{(\hat{\Lambda}, Y, \hat{Y}) \sim \pi_{\Theta}} \left((1 - \hat{Y}[b]) * \hat{Y}[a] \mid \hat{\Lambda} = \hat{\Lambda}^* \right)$$

$$\leq \mathbf{Var}_{(\hat{\Lambda}, Y, \hat{Y}) \sim \pi_{\Theta}} \left((1 - \hat{Y}[b]) \mid \hat{\Lambda} = \hat{\Lambda}^* \right) + \mathbf{Var}_{(\hat{\Lambda}, Y, \hat{Y}) \sim \pi_{\Theta}} \left(\hat{Y}[a] \mid \hat{\Lambda} = \hat{\Lambda}^* \right)$$

$$= \mathbf{Var}_{(\hat{\Lambda}, Y, \hat{Y}) \sim \pi_{\Theta}} \left(\hat{Y}[a] \mid \hat{\Lambda} = \hat{\Lambda}^* \right) + \mathbf{Var}_{(\hat{\Lambda}, Y, \hat{Y}) \sim \pi_{\Theta}} \left(\hat{Y}[b] \mid \hat{\Lambda} = \hat{\Lambda}^* \right),$$

Combining (1), (2), (3), and (4), we have

$$A_3 \le \sum_{i=k+1}^{k+\hat{k}} (\hat{k}-1)\mathbb{E}_{\hat{\Lambda}^* \sim \pi_{\Theta^*}} \mathbf{Var}_{(\hat{\Lambda},Y,\hat{Y})\sim\pi_\Theta} \left(\hat{Y}[i] \mid \hat{\Lambda} = \hat{\Lambda}^* \right),$$

As for A_4, by similar discussion of A_3,

$$A_4 \le \sum_{i=k+1}^{k+\hat{k}} k\mathbb{E}_{\hat{\Lambda}^* \sim \pi_{\Theta^*}} \mathbf{Var}_{(\hat{\Lambda},Y,\hat{Y})\sim\pi_\Theta} \left(\hat{Y}[i] \mid \hat{\Lambda} = \hat{\Lambda}^* \right) + \sum_{i=1}^{k} \hat{k}\mathbb{E}_{\hat{\Lambda}^* \sim \pi_{\Theta^*}} \mathbf{Var}_{(\hat{\Lambda},Y,\hat{Y})\sim\pi_\Theta} \left(Y[i] \mid \hat{\Lambda} = \hat{\Lambda}^* \right).$$

Combining estimation of A_1, A_2, A_3, A_4, and by condition (21) we have

$$\|A\|_s \le A_1 + A_2 + A_3 + A_4$$

$$\le \mathbb{E}_{\hat{\Lambda}^* \sim \pi_{\Theta^*}} \left[\sum_{i=1}^{k} (n_i + \hat{k})\mathbf{Var}_{\hat{\Lambda},Y}(Y[i]|\hat{\Lambda} = \hat{\Lambda}^*) + \sum_{i=k+1}^{\hat{k}+k} (n_i + k + \hat{k} - 1)\mathbf{Var}_{\hat{\Lambda},\hat{Y}}(\hat{Y}[i]|\hat{\Lambda} = \hat{\Lambda}^*) \right]$$

$$\le \mathbb{E}_{\hat{\Lambda}^* \sim \pi_{\Theta^*}} \left[\sum_{i=1}^{k} (n_i + \hat{k})\mathbf{Var}_{\hat{\Lambda},Y}^2(Y[i]|\hat{\Lambda} = \hat{\Lambda}^*) + \sum_{i=k+1}^{k+\hat{k}} (n_i + k + \hat{k} - 1)\mathbf{Var}_{\hat{\Lambda},\hat{Y}}^2(\hat{Y}[i]|\hat{\Lambda} = \hat{\Lambda}^*) \right]^{\frac{1}{2}}$$

$$\cdot \left(\sum_{i=1}^{k}(n_i + \hat{k}) + \sum_{i=k+1}^{k+\hat{k}} (n_i + k + \hat{k} - 1) \right)^{\frac{1}{2}}$$

$$\le \frac{c}{\sqrt{2M}} \cdot \sqrt{2M} \le c,$$

which further leads to

$$A \preceq c\mathbf{I}.$$

For the second term $B = \mathbf{Cov}_{(\hat{\Lambda},Y)\sim\pi_\Theta}(\phi(\hat{\Lambda},Y))$,

$$B = \mathbb{E}_{(\hat{\Lambda},Y)\sim\pi_\Theta} \left[(\Phi(\hat{\Lambda},Y) - \mathbb{E}_{(\hat{\Lambda},Y)\sim\pi_\Theta}[\Phi(\hat{\Lambda},Y)])^2 \right]$$

$$= \mathbb{E}_{(\hat{\Lambda},Y)\sim\pi_\Theta} \left[\left(\Phi(\hat{\Lambda},Y) - \frac{\sum_{\hat{\mathbf{\Lambda}},\mathbf{Y}} \Phi(\hat{\mathbf{\Lambda}},\mathbf{Y}) \exp\left(\Theta^T \Phi(\hat{\mathbf{\Lambda}},\mathbf{Y})\right)}{\sum_{\hat{\mathbf{\Lambda}},\mathbf{Y}} \exp\left(\Theta^T \Phi(\hat{\mathbf{\Lambda}},\mathbf{Y})\right)} \right)^2 \right]$$

$$= \mathbb{E}_{(\hat{\Lambda},Y)\sim\pi_\Theta} \left[\left(\nabla_\Theta \log\left(\exp\left(\Theta^T\Phi(\hat{\Lambda},Y)\right) \right) - \nabla_\Theta \log\left(\sum_{\hat{\mathbf{\Lambda}},\mathbf{Y}} \exp\left(\Theta^T\Phi(\hat{\mathbf{\Lambda}},\mathbf{Y})\right) \right) \right)^2 \right]$$

$$= \mathbb{E}_{(\hat{\Lambda},Y)\sim\pi_\Theta} \left[\left(\nabla_\Theta \log \pi_\Theta(\hat{\Lambda},Y) \right)^2 \right],$$

where $\mathbb{E}_{(\hat{\Lambda},Y)\sim\pi_\Theta} \left[\left(\nabla_\Theta \log \pi_\Theta(\hat{\Lambda},Y) \right)^2 \right]$ is Fisher Information of Θ. By Cramér-Rao bound and condition (20),

$$\frac{I}{2c|D|} \ge \mathbf{Cov}(\hat{\Theta}) \ge \left(D\mathbb{E}_{(\hat{\Lambda},Y)\sim\pi_\Theta} \left[\left(\nabla_\Theta \log \pi_\Theta(\hat{\Lambda},Y) \right)^2 \right] \right)^{-1},$$

which further leads to

$$B = \mathbb{E}_{(\hat{\Lambda},Y)\sim\pi_\Theta} \left[\left(\nabla_\Theta \log \pi_\Theta(\hat{\Lambda},Y) \right)^2 \right] \succeq 2cI.$$

The proof is completed by putting estimation of terms A and B together. $\qquad\square$

[Extension of Lemma D.5 in (Ratner et al., 2016)] Suppose that conditions (18)-(23) hold. Let $\hat{W}$ be the learned parameters of the end model produced by Algorithm 1, and $\ell(W^*)$ be the minimum of cross entropy loss function ℓ. Then, we can bound the expected risk with

$$\mathbb{E}\left[\ell(\hat{W}) - \ell(W^*)\right] \leq \chi + 4cH\epsilon.$$

Proof. We begin by rewriting objective of expected loss minimization problem using law of total expectation as follows:

$$\ell(W) = \mathbb{E}_{(\bar{X},\bar{Y})\sim\pi^*}\left[\mathbb{E}_{(X,Y)\sim\pi^*}\left[\mathcal{H}(Y, \sigma(h(\bar{X}, W)))\big|X = \bar{X}\right]\right]$$

and by our conditional independence assumption (condition (19)),

$$\ell(W) = \mathbb{E}_{(\bar{X},\bar{Y})\sim\pi^*}\left[\mathbb{E}_{(X,Y)\sim\pi^*}\left[\mathcal{H}(Y, \sigma(h(\bar{X}, W)))\big|\hat{\Lambda}(X) = \hat{\Lambda}(\bar{X})\right]\right]$$
$$= \mathbb{E}_{(\bar{X},\bar{Y})\sim\pi^*}\left[\mathbb{E}_{(\hat{\Lambda},Y)\sim\pi_{\Theta^*}}\left[\mathcal{H}(Y, \sigma(h(\bar{X}, W)))\big|\hat{\Lambda} = \hat{\Lambda}(\bar{X})\right]\right]$$

On the other hand, if we are minimizing the model with learned parameter $\hat{\Theta}$, we will be actually minimizing

$$\ell_{\hat{\Theta}}(W) = \mathbb{E}_{(\bar{X},\bar{Y})\sim\pi^*}\left[\mathbb{E}_{(\hat{\Lambda},Y)\sim\pi_{\hat{\Theta}}}\left[\mathcal{H}(Y, \sigma(h(\bar{X}, W)))\big|\hat{\Lambda} = \hat{\Lambda}(\bar{X})\right]\right].$$

Since by definition label vector Y is one hot, $\mathbb{E}_{(\hat{\Lambda},Y)\sim\pi_{\hat{\Theta}}}\left[\mathcal{H}(Y, \sigma(h(\bar{X}, W)))\big|\hat{\Lambda} = \hat{\Lambda}(\bar{X})\right]$ can be further extended into

$$\mathbb{E}_{(\hat{\Lambda},Y)\sim\pi_{\hat{\Theta}}}\left[\mathcal{H}(Y, \sigma(h(\bar{X}, W)))\big|\hat{\Lambda} = \hat{\Lambda}(\bar{X})\right]$$
$$= \sum_{l=1}^{k}\log\left(\sigma(h(\bar{X}, W))_l\right)\mathbb{P}_{(\hat{\Lambda},Y)\sim\pi_{\hat{\Theta}}}(Y[l] = 1|\hat{\Lambda} = \hat{\Lambda}(\bar{X})).$$

For simplification, we re-write $\mathbb{P}_{(\hat{\Lambda},Y)\sim\pi_{\hat{\Theta}}}(Y[l] = 1|\hat{\Lambda} = \hat{\Lambda}(\bar{X}))$ as follows with slight abuse of notations:

$$\mathbb{P}_{(\hat{\Lambda},Y)\sim\pi_{\hat{\Theta}}}(Y[l] = 1|\hat{\Lambda} = \hat{\Lambda}(\bar{X})) = \mathbb{P}_{\pi_{\hat{\Theta}}}(Y[l] = 1|\hat{\Lambda}(\bar{X})),$$

and similarly

$$\mathbb{E}_{(\bar{X},\bar{Y})\sim\pi^*} = \mathbb{E}_{\pi^*},$$

Let

$$l_{\bar{X}} = \arg\min_l \log\left(\sigma(h(\bar{X}, W))_l\right)$$

the difference between the loss functions will be

$$\left|\ell_{\hat{\Theta}}(W) - \ell(W)\right| = \left|\mathbb{E}_{\pi^*}\left[\sum_{l=1}^{k}\log\left(\sigma(h(\bar{X}, W))_l\right)\left(\mathbb{P}_{\pi_{\Theta^*}}(Y[l] = 1|\hat{\Lambda}(\bar{X})) - \mathbb{P}_{\pi_{\hat{\Theta}}}(Y[l] = 1|\hat{\Lambda}(\bar{X}))\right)\right]\right|$$
$$= \left|\mathbb{E}_{\pi^*}\left[\log\left(\sigma(h(\bar{X}, W))_{l_{\bar{X}}}\right)\left(\mathbb{P}_{\pi_{\Theta^*}}(Y[l_{\bar{X}}] = 1|\hat{\Lambda}(\bar{X})) - \mathbb{P}_{\pi_{\hat{\Theta}}}(Y[l_{\bar{X}}] = 1|\hat{\Lambda}(\bar{X}))\right)\right]\right.$$
$$\left. + \mathbb{E}_{\pi^*}\left[\sum_{l=1,l\neq l_{\bar{X}}}^{k}\log\left(\sigma(h(\bar{X}, W))_l\right)\left(\mathbb{P}_{\pi_{\Theta^*}}(Y[l] = 1|\hat{\Lambda}(\bar{X})) - \mathbb{P}_{\pi_{\hat{\Theta}}}(Y[l] = 1|\hat{\Lambda}(\bar{X}))\right)\right]\right|.$$

Furthermore,

$$
\Bigg| \mathbb{E}_{\pi^*} \left[\log \left(\sigma(h(\bar{X}, W))_{l_{\bar{X}}} \right) \left(\mathbb{P}_{\pi_{\Theta^*}}(Y[l_{\bar{X}}] = 1 | \hat{\Lambda}(\bar{X})) - \mathbb{P}_{\pi_{\hat{\Theta}}}(Y[l_{\bar{X}}] = 1 | \hat{\Lambda}(\bar{X})) \right) \right]
$$

$$
+ \mathbb{E}_{\pi^*} \left[\sum_{l=1, l \neq l_{\bar{X}}}^{k} \log \left(\sigma(h(\bar{X}, W))_l \right) \left(\mathbb{P}_{\pi_{\Theta^*}}(Y[l] = 1 | \hat{\Lambda}(\bar{X})) - \mathbb{P}_{\pi_{\hat{\Theta}}}(Y[l] = 1 | \hat{\Lambda}(\bar{X})) \right) \right] \Bigg|
$$

$$
= \Bigg| \mathbb{E}_{\pi^*} \left[\log \left(\sigma(h(\bar{X}, W))_{l_{\bar{X}}} \right) \left(- \sum_{j=1, j \neq l_{\bar{X}}}^{k} \mathbb{P}_{\pi_{\Theta^*}}(Y[j] = 1 | \hat{\Lambda}(\bar{X})) + \sum_{j=1, j \neq l_{\bar{X}}}^{k} \mathbb{P}_{\pi_{\hat{\Theta}}}(Y[j] = 1 | \hat{\Lambda}(\bar{X})) \right) \right]
$$

$$
+ \mathbb{E}_{\pi^*} \left[\sum_{l=1, l \neq l_{\bar{X}}}^{k} \log \left(\sigma(h(\bar{X}, W))_l \right) \left(\mathbb{P}_{\pi_{\Theta^*}}(Y[l] = 1 | \hat{\Lambda}(\bar{X})) - \mathbb{P}_{\pi_{\hat{\Theta}}}(Y[l] = 1 | \hat{\Lambda}(\bar{X})) \right) \right] \Bigg|
$$

$$
= \Bigg| \mathbb{E}_{\pi^*} \left[\sum_{l=1, l \neq l_{\bar{X}}}^{k} \left(\log \left(\sigma(h(\bar{X}, W))_l \right) - \log \left(\sigma(h(\bar{X}, W))_{l_{\bar{X}}} \right) \right) \left(\mathbb{P}_{\pi_{\Theta^*}}(Y[l] = 1 | \hat{\Lambda}(\bar{X})) - \mathbb{P}_{\pi_{\hat{\Theta}}}(Y[l] = 1 | \hat{\Lambda}(\bar{X})) \right) \right] \Bigg|
$$

$$
= \Bigg| \mathbb{E}_{\pi^*} \left[\sum_{l=1, l \neq l_{\bar{X}}}^{k} \left(h(\bar{X}, W)_l - h(\bar{X}, W)_{l_{\bar{X}}} \right) \left(\mathbb{P}_{\pi_{\Theta^*}}(Y[l] = 1 | \hat{\Lambda}(\bar{X})). - \mathbb{P}_{\pi_{\hat{\Theta}}}(Y[l] = 1 | \hat{\Lambda}(\bar{X})) \right) \right] \Bigg|.
$$

$$
\tag{25}
$$

Let

$$
\bar{h}(l_1, l_2) = h(\bar{X}, W)_{l_1} - h(\bar{X}, W)_{l_2}.
$$

By Eq. (22), we have for any $l \in [k]$,

$$
0 \leq \bar{h}(l, l_{\bar{X}}) \leq 2H.
$$

For any fixed X, define $g_X(\Theta)$ as follows:

$$
g_X(\Theta) = \sum_{l=1, l \neq l_{\bar{X}}}^{k} \bar{h}(l, l_{\bar{X}}) \mathbb{P}_{\pi_{\Theta}}(Y[l] = 1 | \hat{\Lambda}(\bar{X})).
\tag{26}
$$

By First Mean Value Theorem,

$$
g_X(\hat{\Theta}) - g_X(\Theta^*) = \langle \nabla g_X(\xi), \hat{\Theta} - \Theta^* \rangle \leq \| \hat{\Theta} - \Theta^* \| \| \nabla g_X(\xi) \|.
$$

We then bound $\nabla g_X(\xi)$ element-wisely:

(1). For any $y_d \in \mathcal{Y}, j \in [n], y_a \in \mathcal{Y}_{\lambda_j}(y_d)$, if $y_d = l_{\bar{X}}, \hat{\Lambda}_{j,a}[X] = 1$,

$$
\left| \frac{\partial g_X(\xi)}{\partial \theta_{y_d, y_a, j}^{\mathrm{Acc}}} \right| = \left| \sum_{l=1, l \neq l_{\bar{X}}}^{k} \bar{h}(l, l_{\bar{X}}) \frac{\partial \mathbb{P}_{\pi_\xi}(Y[l] = 1 | \hat{\Lambda}(\bar{X}))}{\partial \theta_{y_d, y_a, j}^{\mathrm{Acc}}} \right|
$$

$$
= \left| - \sum_{l=1, l \neq l_{\bar{X}}}^{k} \bar{h}(l, l_{\bar{X}}) \mathbb{P}_{\pi_\xi}(Y[d] = 1 | \hat{\Lambda}(\bar{X})) \mathbb{P}_{\pi_\xi}(Y[l] = 1 | \hat{\Lambda}(\bar{X})) \right|
$$

$$
= \sum_{l=1, l \neq l_{\bar{X}}}^{k} \bar{h}(l, l_{\bar{X}}) \mathbb{P}_{\pi_\xi}(Y[d] = 1 | \hat{\Lambda}(\bar{X})) \mathbb{P}_{\pi_\xi}(Y[l] = 1 | \hat{\Lambda}(\bar{X}))
$$

$$
\leq 2H \mathbb{P}_{\pi_\xi}(Y[d] = 1 | \hat{\Lambda}(\bar{X}))(1 - \mathbb{P}_{\pi_\xi}(Y[d] = 1 | \hat{\Lambda}(\bar{X})))
$$

$$
= \mathbf{Var} \left[Y[d] | \hat{\Lambda}(\bar{X}) \right].
$$

If $y_d \neq l_{\bar{X}}$, $\hat{\Lambda}_{j,a}[X] = 1$,

$$
\begin{aligned}
\left| \frac{\partial g_X(\xi)}{\partial \theta^{\text{Acc}}_{y_d,y_a,j}} \right| &= \left| \sum_{l=1, l \neq l_{\bar{X}}}^{k} \bar{h}(l, l_{\bar{X}}) \frac{\partial \mathbb{P}_{\pi_\xi}(Y[l] = 1 | \hat{\Lambda}(\bar{X}))}{\partial \theta^{\text{Acc}}_{y_d,y_a,j}} \right| \\
&= \left| - \sum_{l=1, l \notin \{d, l_{\bar{X}}\}}^{k} \bar{h}(l, l_{\bar{X}}) \mathbb{P}_{\pi_\xi}(Y[d] = 1 | \hat{\Lambda}(\bar{X})) \mathbb{P}_{\pi_\xi}(Y[l] = 1 | \hat{\Lambda}(\bar{X})) \right. \\
&\quad \left. + \bar{h}(d, l_{\bar{X}}) \left(\mathbb{P}_{\pi_\xi}(Y[d] = 1 | \hat{\Lambda}(\bar{X})) - \mathbb{P}_{\pi_\xi}(Y[d] = 1 | \hat{\Lambda}(\bar{X})) \mathbb{P}_{\pi_\xi}(Y[d] = 1 | \hat{\Lambda}(\bar{X})) \right) \right| \\
&\leq \max \left\{ \sum_{l=1, l \notin \{d, l_{\bar{X}}\}}^{k} \bar{h}(l, l_{\bar{X}}) \mathbb{P}_{\pi_\xi}(Y[d] = 1 | \hat{\Lambda}(\bar{X})) \mathbb{P}_{\pi_\xi}(Y[l] = 1 | \hat{\Lambda}(\bar{X})), \right. \\
&\quad \left. \bar{h}(d, l_{\bar{X}}) \left(\mathbb{P}_{\pi_\xi}(Y[d] = 1 | \hat{\Lambda}(\bar{X})) - \mathbb{P}_{\pi_\xi}(Y[d] = 1 | \hat{\Lambda}(\bar{X})) \mathbb{P}_{\pi_\xi}(Y[d] = 1 | \hat{\Lambda}(\bar{X})) \right) \right\} \\
&\leq 2H \mathbb{P}_{\pi_\xi}(Y[d] = 1 | \hat{\Lambda}(\bar{X}))(1 - \mathbb{P}_{\pi_\xi}(Y[d] = 1 | \hat{\Lambda}(\bar{X}))) \\
&= 2H \mathbf{Var}\left[Y[d] | \hat{\Lambda}(\bar{X}) \right].
\end{aligned}
$$

If $\hat{\Lambda}_{j,a}[X] = 0$,

$$
\left| \frac{\partial g_X(\xi)}{\partial \theta^{\text{Acc}}_{y_d,y_a,j}} \right| = \left| \sum_{l=1, l \neq l_{\bar{X}}}^{k} \bar{h}(l, l_{\bar{X}}) \frac{\partial \mathbb{P}_{\pi_\xi}(Y[l] = 1 | \hat{\Lambda}(\bar{X}))}{\partial \theta^{\text{Acc}}_{y_d,y_a,j}} \right| = 0.
$$

(2). For $j \in [n], y_a \in \mathcal{Y}_{\lambda_j}$, if $\hat{\Lambda}_{j,a}[X] = 1$,

$$
\begin{aligned}
\left| \frac{\partial g_X(\xi)}{\partial \theta^{\text{Acc}}_{y_a,j}} \right| &= \left| \sum_{l=1, l \neq l_{\bar{X}}}^{k} \bar{h}(l, l_{\bar{X}}) \frac{\partial \mathbb{P}_{\pi_\xi}(Y[l] = 1 | \hat{\Lambda}(\bar{X}))}{\partial \theta^{\text{Acc}}_{y_a,j}} \right| \\
&= \left| \sum_{l=1, l \neq l_{\bar{X}}}^{k} \bar{h}(l, l_{\bar{X}}) \left(\mathbb{P}_{\pi_\xi}(Y[l] = 1, \hat{Y}[a] = 1 | \hat{\Lambda}(\bar{X})) - \mathbb{P}_{\pi_\xi}(Y[l] = 1 | \hat{\Lambda}(\bar{X})) \mathbb{P}_{\pi_\xi}(\hat{Y}[a] = 1 | \hat{\Lambda}(\bar{X})) \right) \right|.
\end{aligned}
$$

Let

$$
\begin{aligned}
f_1(l) &= \mathbb{P}_{\pi_\xi}(Y[l] = 1, \hat{Y}[a] = 1 | \hat{\Lambda}(\bar{X})) \\
f_2(l) &= \mathbb{P}_{\pi_\xi}(Y[l] = 1 | \hat{\Lambda}(\bar{X})) \mathbb{P}_{\pi_\xi}(\hat{Y}[a] = 1 | \hat{\Lambda}(\bar{X})),
\end{aligned}
$$

and

$$
\begin{aligned}
\mathcal{B}^1 &= \{l : f_1(l) \geq f_2(l), l \neq l_{\bar{X}}\}, \\
\mathcal{B}^2 &= \{l : f_1(l) < f_2(l), l \neq l_{\bar{X}}\}.
\end{aligned}
$$

Therefore,

$$\left| \sum_{l=1, l \neq l_{\bar{X}}}^{k} \bar{h}(l, l_{\bar{X}}) \left(\mathbb{P}_{\pi_\xi}(Y[l] = 1, \hat{Y}[a] = 1 | \hat{\Lambda}(\bar{X})) - \mathbb{P}_{\pi_\xi}(Y[l] = 1 | \hat{\Lambda}(\bar{X})) \mathbb{P}_{\pi_\xi}(\hat{Y}[a] = 1 | \hat{\Lambda}(\bar{X})) \right) \right|$$

$$= \left| \sum_{l=1, l \neq l_{\bar{X}}}^{k} \bar{h}(l, l_{\bar{X}}) \left(f_1(l) - f_2(l) \right) \right|$$

$$= \left| \sum_{l \in \mathcal{B}^1} \bar{h}(l, l_{\bar{X}}) \left(f_1(l) - f_2(l) \right) + \sum_{l \in \mathcal{B}^2} \bar{h}(l, l_{\bar{X}}) \left(f_1(l) - f_2(l) \right) \right|$$

$$\leq \max_{t=1,2} \left| \sum_{l \in \mathcal{B}^{\mathsf{T}}} \bar{h}(l, l_{\bar{X}}) \left(f_1(l) - f_2(l) \right) \right|$$

$$= \max \left\{ \sum_{l \in \mathcal{B}^1} \bar{h}(l, l_{\bar{X}}) \left(f_1(l) - f_2(l) \right), \sum_{l \in \mathcal{B}^2} \bar{h}(l, l_{\bar{X}}) \left(f_2(l) - f_1(l) \right) \right\}.$$

On the other hand,

$$\sum_{l \in \mathcal{B}^1} \bar{h}(l, l_{\bar{X}}) \left(f_1(l) - f_2(l) \right)$$

$$= \sum_{l \in \mathcal{B}^1} \bar{h}(l, l_{\bar{X}}) \left(\mathbb{P}_{\pi_\xi}(Y[l] = 1, \hat{Y}[a] = 1 | \hat{\Lambda}(\bar{X})) - \mathbb{P}_{\pi_\xi}(Y[l] = 1 | \hat{\Lambda}(\bar{X})) \mathbb{P}_{\pi_\xi}(\hat{Y}[a] = 1 | \hat{\Lambda}(\bar{X})) \right)$$

$$\leq 2H \left(\mathbb{P}_{\pi_\xi}(Y[l] = 1, \hat{Y}[a] = 1 | \hat{\Lambda}(\bar{X})) - \mathbb{P}_{\pi_\xi}(Y[l] = 1 | \hat{\Lambda}(\bar{X})) \mathbb{P}_{\pi_\xi}(\hat{Y}[a] = 1 | \hat{\Lambda}(\bar{X})) \right)$$

$$= 2H \left(\mathbb{P}_{\pi_\xi}(Y[l] = 1, \exists l \in \mathcal{B}^1, \hat{Y}[a] = 1 | \hat{\Lambda}(\bar{X})) - \mathbb{P}_{\pi_\xi}(Y[l] = 1, \exists l \in \mathcal{B}^1 | \hat{\Lambda}(\bar{X})) \mathbb{P}_{\pi_\xi}(\hat{Y}[a] = 1 | \hat{\Lambda}(\bar{X})) \right)$$

$$= 2H \left(\mathbb{P}_{\pi_\xi}(Y[l] = 1, \exists l \in \mathcal{B}^1, \hat{Y}[a] = 1 | \hat{\Lambda}(\bar{X})) \mathbb{P}_{\pi_\xi}(\hat{Y}[a] = 0 | \hat{\Lambda}(\bar{X})) - \mathbb{P}_{\pi_\xi}(Y[l] = 1, \exists l \in \mathcal{B}^1, \hat{Y}[a] = 0 | \hat{\Lambda}(\bar{X})) \mathbb{P}_{\pi_\xi}(\hat{Y}[a] = \right.$$

$$\leq 2H \left(\mathbb{P}_{\pi_\xi}(\hat{Y}[a] = 1 | \hat{\Lambda}(\bar{X})) \mathbb{P}_{\pi_\xi}(\hat{Y}[a] = 0 | \hat{\Lambda}(\bar{X})) \right)$$

$$= 2H \mathbf{Var} \left[\hat{Y}[a] | \hat{\Lambda}(\bar{X}) \right].$$

Similarly, we have

$$\sum_{l \in \mathcal{B}^1} \bar{h}(l, l_{\bar{X}}) \left(f_2(l) - f_1(l) \right) - \sum_{l \in \mathcal{B}^2} \bar{h}(l, l_{\bar{X}}) \left(\mathbb{P}_{\pi_\xi}(Y[l] = 1, \hat{Y}[a] = 1 | \hat{\Lambda}(\bar{X})) + \mathbb{P}_{\pi_\xi}(Y[l] = 1 | \hat{\Lambda}(\bar{X})) \mathbb{P}_{\pi_\xi}(\hat{Y}[a] = 1 | \hat{\Lambda}(\bar{X}))$$

$$\leq 2H \mathbf{Var} \left[\hat{Y}[a] | \hat{\Lambda}(\bar{X}) \right].$$

Conclusively, we have

$$\left| \frac{\partial g_X(\xi)}{\partial \theta^{\text{Acc}}_{y_a, j}} \right| \leq \mathbf{Var} \left[\hat{Y}[a] | \hat{\Lambda}(\bar{X}) \right].$$

If $\hat{\Lambda}_{j,a}[X] = 1$, similar to (1)., we have

$$\left| \frac{\partial g_X(\xi)}{\partial \theta^{\text{Acc}}_{y_a, j}} \right| = 0.$$

(3). For $y_a, y_b \in \hat{\mathcal{Y}}$, let $(\gamma_a, \gamma_b) \in \{0, 1\}^2$, such that, $\phi^{t_{ab}}_{y_a, y_b}(\gamma_a, \gamma_b) \neq 0$. Similar to (2), let

$$f_3(l) = \mathbb{P}_{\pi_\xi}(Y[l] = 1, \hat{Y}[a] = \gamma_a, \hat{Y}[b] = \gamma_b | \hat{\Lambda}(\bar{X}))$$

$$f_4(l) = \mathbb{P}_{\pi_\xi}(Y[l] = 1 | \hat{\Lambda}(\bar{X})) \mathbb{P}_{\pi_\xi}(\hat{Y}[a] = \gamma_a, \hat{Y}[b] = \gamma_b | \hat{\Lambda}(\bar{X}))$$

and

$$\mathcal{B}^3 = \{l : f_3(l) \geq f_4(l), l \neq l_{\bar{X}}\},$$
$$\mathcal{B}^4 = \{l : f_3(l) < f_4(l), l \neq l_{\bar{X}}\}$$

we have

$$\left|\frac{\partial g_X(\xi)}{\partial \theta_{y_a,y_b}^{t_{ab}}}\right| = \max\left\{\sum_{l \in \mathcal{B}^3} \bar{h}(l, l_{\bar{X}})(f_3(l) - f_4(l)), \sum_{l \in \mathcal{B}^4} \bar{h}(l, l_{\bar{X}})(f_4(l) - f_3(l))\right\}$$
$$\leq 2H \mathbf{Var}\left[\phi_{y_a,y_b}^{t_{ab}}(\hat{Y}_i[a], \hat{Y}_i[b])|\hat{\Lambda}(\bar{X})\right]$$
$$\overset{(*)}{\leq} 2H\left(\mathbf{Var}\left[\hat{Y}[a]|\hat{\Lambda}(\bar{X})\right] + \mathbf{Var}\left[\hat{Y}[b]|\hat{\Lambda}(\bar{X})\right]\right),$$

where inequality (*) comes from Lemma D.3.

(4). For any $y_d \in \mathcal{Y}, y_a \in \hat{\mathcal{Y}}$, let $(\gamma_d, \gamma_a) \in \{0,1\}^2$ satisfies $\phi_{y_d,y_a}^{t_{da}}(\gamma_d, \gamma_a)$. We further divide the proof into two cases: $\gamma_d = 0$, and $\gamma_d = 1$.

(4a). If $\gamma_d = 0$, we have $\gamma_a = 1$. Similar to (1-3)., we have

$$\left|\frac{\partial g_X(\xi)}{\partial \theta_{y_d,y_a}^{t_{da}}}\right| = \left|\sum_{l=1,l\neq l_{\bar{X}}}^{k} \bar{h}(l, l_{\bar{X}})\frac{\partial \mathbb{P}_{\pi_\xi}(Y[l] = 1|\hat{\Lambda}(\bar{X}))}{\partial \theta_{y_d,y_a}^{t_{da}}}\right|$$
$$= \left|\sum_{l=1}^{k} \bar{h}(l, l_{\bar{X}})\frac{\partial \mathbb{P}_{\pi_\xi}(Y[l] = 1|\hat{\Lambda}(\bar{X}))}{\partial \theta_{y_d,y_a}^{t_{da}}}\right|$$
$$= \left|\sum_{l=1,l\neq d}^{k} \bar{h}(l, l_{\bar{X}})\left(\mathbb{P}_{\pi_\xi}(Y[l] = 1, \hat{Y}[a] = 1|\hat{\Lambda}(\bar{X})) - \mathbb{P}_{\pi_\xi}(Y[l] = 1|\hat{\Lambda}(\bar{X}))\mathbb{P}_{\pi_\xi}(Y[d] = 0, \hat{Y}[a] = 1|\hat{\Lambda}(\bar{X}))\right)\right.$$
$$\left. - \bar{h}(d, l_{\bar{X}})\mathbb{P}_{\pi_\xi}(Y[d] = 1|\hat{\Lambda}(\bar{X}))\mathbb{P}_{\pi_\xi}(Y[d] = 0, \hat{Y}[a] = 1|\hat{\Lambda}(\bar{X}))\right|.$$

Let

$$f_5(l) = \mathbb{P}_{\pi_\xi}(Y[l] = 1, \hat{Y}[a] = 1|\hat{\Lambda}(\bar{X}))$$
$$f_6(l) = \mathbb{P}_{\pi_\xi}(Y[l] = 1|\hat{\Lambda}(\bar{X}))\mathbb{P}_{\pi_\xi}(Y[d] = 0, \hat{Y}[a] = 1|\hat{\Lambda}(\bar{X}))$$

and

$$\mathcal{B}^5 = \{l : f_5(l) \geq f_6(l), \quad l \neq d\},$$
$$\mathcal{B}^6 = \{l : f_5(l) < f_6(l), \quad l \neq d\}$$

Then we have

$$\left|\frac{\partial g_X(\xi)}{\partial \theta_{y_d,y_a}^{t_{da}}}\right| \leq \max\left\{\sum_{l \in \mathcal{B}^5} \bar{h}(l, l_{\bar{X}})(f_5(l) - f_6(l)), \sum_{l \in \mathcal{B}^6} \bar{h}(l, l_{\bar{X}})(f_6(l) - f_5(l)) + \bar{h}(d, l_{\bar{X}})f_6(d)\right\}.$$

On one hand,

$$\sum_{l \in \mathcal{B}^5} \bar{h}(l, l_{\bar{X}}) \left(f_5(l) - f_6(l) \right)$$

$$= \sum_{l \in \mathcal{B}^5} \bar{h}(l, l_{\bar{X}}) \left(\mathbb{P}_{\pi_\xi}(Y[l] = 1, \hat{Y}[a] = 1 | \hat{\Lambda}(\bar{X})) - \mathbb{P}_{\pi_\xi}(Y[l] = 1 | \hat{\Lambda}(\bar{X})) \mathbb{P}_{\pi_\xi}(Y[d] = 0, \hat{Y}[a] = 1 | \hat{\Lambda}(\bar{X})) \right)$$

$$\leq \sum_{l \in \mathcal{B}^5} 2H \left(\mathbb{P}_{\pi_\xi}(Y[l] = 1, \hat{Y}[a] = 1 | \hat{\Lambda}(\bar{X})) - \mathbb{P}_{\pi_\xi}(Y[l] = 1 | \hat{\Lambda}(\bar{X})) \mathbb{P}_{\pi_\xi}(Y[d] = 0, \hat{Y}[a] = 1 | \hat{\Lambda}(\bar{X})) \right)$$

$$= 2H \left(\mathbb{P}_{\pi_\xi}(Y[l] = 1, \exists l \in \mathcal{B}^5, \hat{Y}[a] = 1 | \hat{\Lambda}(\bar{X})) - \mathbb{P}_{\pi_\xi}(Y[l] = 1, \exists l \in \mathcal{B}^5 | \hat{\Lambda}(\bar{X})) \mathbb{P}_{\pi_\xi}(Y[d] = 0, \hat{Y}[a] = 1 | \hat{\Lambda}(\bar{X})) \right)$$

$$= 2H \left(\mathbb{P}_{\pi_\xi}(Y[l] = 1, \exists l \in \mathcal{B}^5, \hat{Y}[a] = 1 | \hat{\Lambda}(\bar{X}))(1 - \mathbb{P}_{\pi_\xi}(Y[d] = 0, \hat{Y}[a] = 1 | \hat{\Lambda}(\bar{X}))) \right.$$

$$\left. - \mathbb{P}_{\pi_\xi}(Y[l] = 1, \exists l \in \mathcal{B}^5, \hat{Y}[a] = 0 | \hat{\Lambda}(\bar{X})) \mathbb{P}_{\pi_\xi}(Y[d] = 0, \hat{Y}[a] = 1 | \hat{\Lambda}(\bar{X})) \right)$$

$$\leq 2H \mathbb{P}_{\pi_\xi}(Y[d] = 0, \hat{Y}[a] = 1 | \hat{\Lambda}(\bar{X}))(1 - \mathbb{P}_{\pi_\xi}(Y[d] = 0, \hat{Y}[a] = 1 | \hat{\Lambda}(\bar{X})))$$

$$= 2H \mathbf{Var}_{\pi_\xi} \left[\phi_{y_d, y_a}^{t_{da}}(Y_i[d], \hat{Y}_i[a]) | \hat{\Lambda}(\bar{X}) \right]$$

$$\leq \mathbf{Var}_{\pi_\xi} \left[Y[d] | \hat{\Lambda}(\bar{X}) \right] + \mathbf{Var}_{\pi_\xi} \left[\hat{Y}[a] | \hat{\Lambda}(\bar{X}) \right].$$

On the other hand,

$$\sum_{l \in \mathcal{B}^6} \bar{h}(l, l_{\bar{X}}) \left(f_6(l) - f_5(l) \right) + \bar{h}(d, l_{\bar{X}}) f_6(d)$$

$$= - \sum_{l \in \mathcal{B}^6} \bar{h}(l, l_{\bar{X}}) \left(\mathbb{P}_{\pi_\xi}(Y[l] = 1, \hat{Y}[a] = 1 | \hat{\Lambda}(\bar{X})) + \mathbb{P}_{\pi_\xi}(Y[l] = 1 | \hat{\Lambda}(\bar{X})) \mathbb{P}_{\pi_\xi}(Y[d] = 0, \hat{Y}[a] = 1 | \hat{\Lambda}(\bar{X})) \right)$$

$$+ \bar{h}(d, l_{\bar{X}}) \mathbb{P}_{\pi_\xi}(Y[d] = 1 | \hat{\Lambda}(\bar{X})) \mathbb{P}_{\pi_\xi}(Y[d] = 0, \hat{Y}[a] = 1 | \hat{\Lambda}(\bar{X}))$$

$$\leq 2H \left(-\mathbb{P}_{\pi_\xi}(Y[l] = 1, \exists l \in \mathcal{B}^6, \hat{Y}[a] = 1 | \hat{\Lambda}(\bar{X}))(1 - \mathbb{P}_{\pi_\xi}(Y[d] = 0, \hat{Y}[a] = 1 | \hat{\Lambda}(\bar{X}))) \right.$$

$$- \mathbb{P}_{\pi_\xi}(Y[l] = 1, \exists l \in \mathcal{B}^6, \hat{Y}[a] = 0 | \hat{\Lambda}(\bar{X})) \mathbb{P}_{\pi_\xi}(Y[d] = 0, \hat{Y}[a] = 1 | \hat{\Lambda}(\bar{X})) + \mathbb{P}_{\pi_\xi}(Y[d] = 1 | \hat{\Lambda}(\bar{X})) \mathbb{P}_{\pi_\xi}(Y[d] = 0, \hat{Y}[a] = 1 | \hat{\Lambda}$$

$$\leq 2H \left(\mathbb{P}_{\pi_\xi}(Y[l] = 1, \exists l \in \mathcal{B}^6, \hat{Y}[a] = 0 | \hat{\Lambda}(\bar{X})) \mathbb{P}_{\pi_\xi}(Y[d] = 0, \hat{Y}[a] = 1 | \hat{\Lambda}(\bar{X})) + \mathbb{P}_{\pi_\xi}(Y[d] = 1 | \hat{\Lambda}(\bar{X})) \mathbb{P}_{\pi_\xi}(Y[d] = 0, \hat{Y}[a] = \right.$$

$$\leq 2H \left(\mathbb{P}_{\pi_\xi}(\hat{Y}[a] = 0 | \hat{\Lambda}(\bar{X})) \mathbb{P}_{\pi_\xi}(\hat{Y}[a] = 1 | \hat{\Lambda}(\bar{X})) + \mathbb{P}_{\pi_\xi}(Y[d] = 1 | \hat{\Lambda}(\bar{X})) \mathbb{P}_{\pi_\xi}(Y[d] = 0, \hat{Y}[a] = 1 | \hat{\Lambda}(\bar{X})) \right)$$

$$\leq \mathbf{Var}_{\pi_\xi} \left[Y[d] | \hat{\Lambda}(\bar{X}) \right] + \mathbf{Var}_{\pi_\xi} \left[\hat{Y}[a] | \hat{\Lambda}(\bar{X}) \right].$$

Therefore, in this case, we have

$$\left| \frac{\partial g_X(\xi)}{\partial \theta_{y_d, y_a}^{t_{da}}} \right| \leq \mathbf{Var}_{\pi_\xi} \left[Y[d] | \hat{\Lambda}(\bar{X}) \right] + \mathbf{Var}_{\pi_\xi} \left[\hat{Y}[a] | \hat{\Lambda}(\bar{X}) \right].$$

(4b). If $\gamma_d = 1$, similar to $(4a)$., we have

$$\left| \frac{\partial g_X(\xi)}{\partial \theta_{y_d, y_a}^{t_{da}}} \right| = \left| - \sum_{l=1, l \neq d}^{k} \bar{h}(l, l_{\bar{X}}) \mathbb{P}_{\pi_\xi}(Y[l] = 1 | \hat{\Lambda}(\bar{X})) \mathbb{P}_{\pi_\xi}(Y[d] = 1, \hat{Y}[a] = 1 | \hat{\Lambda}(\bar{X})) \right.$$

$$\left. + \bar{h}(d, l_{\bar{X}}) \left(\mathbb{P}_{\pi_\xi}(Y[d] = 1, \hat{Y}[a] = 1 | \hat{\Lambda}(\bar{X})) - \mathbb{P}_{\pi_\xi}(Y[d] = 1 | \hat{\Lambda}(\bar{X})) \mathbb{P}_{\pi_\xi}(Y[d] = 1, \hat{Y}[a] = 1 | \hat{\Lambda}(\bar{X})) \right) \right|.$$

Since

$$\bar{h}(d, l_{\bar{X}}) \left(\mathbb{P}_{\pi_\xi}(Y[d] = 1, \hat{Y}[a] = 1 | \hat{\Lambda}(\bar{X})) - \mathbb{P}_{\pi_\xi}(Y[d] = 1 | \hat{\Lambda}(\bar{X})) \mathbb{P}_{\pi_\xi}(Y[d] = 1, \hat{Y}[a] = 1 | \hat{\Lambda}(\bar{X})) \right)$$

$$= \bar{h}(d, l_{\bar{X}}) \mathbb{P}_{\pi_\xi}(Y[d] = 1, \hat{Y}[a] = 1 | \hat{\Lambda}(\bar{X})) \mathbb{P}_{\pi_\xi}(Y[d] = 0 | \hat{\Lambda}(\bar{X}))$$

$$\geq 0,$$

we have

$$\left|\frac{\partial g_X(\xi)}{\partial \theta_{y_d,y_a}^{t_{da}}}\right| \leq \max\left\{\bar{h}(d, l_{\bar{X}})\mathbb{P}_{\pi_\xi}(Y[d] = 1, \hat{Y}[a] = 1|\hat{\Lambda}(\bar{X}))\mathbb{P}_{\pi_\xi}(Y[d] = 0|\hat{\Lambda}(\bar{X}))\,,\right.$$

$$\left.\sum_{l=1,l\neq d}^{k} \bar{h}(l, l_{\bar{X}})\mathbb{P}_{\pi_\xi}(Y[l] = 1|\hat{\Lambda}(\bar{X}))\mathbb{P}_{\pi_\xi}(Y[d] = 1, \hat{Y}[a] = 1|\hat{\Lambda}(\bar{X}))\right\}$$

$$\leq 2H\mathbf{Var}\left[Y[d]|\hat{\Lambda}(\bar{X})\right].$$

Combining (4a). and (4b)., we have that

$$\left|\frac{\partial g_X(\xi)}{\partial \theta_{y_d,y_a}^{t_{da}}}\right| \leq 2H\left(\mathbf{Var}_{\pi_\xi}\left[Y[d]|\hat{\Lambda}(\bar{X})\right] + \mathbf{Var}_{\pi_\xi}\left[\hat{Y}[a]|\hat{\Lambda}(\bar{X})\right]\right).$$

Combining (1-4)., we then have

$$\|\nabla g_X(\xi)\|^2 \leq 4H^2\sum_{y_d\in\mathcal{Y}}\sum_{j\in[n],\mathcal{Y}_{\lambda_j}(y_d)\neq\emptyset}\mathbf{Var}_{\pi_\xi}\left[Y[d]|\hat{\Lambda}(\bar{X})\right]^2$$

$$+ 4H^2\sum_{j\in[n],\mathcal{Y}_{\lambda_j}(y_d)\neq\emptyset}\mathbf{Var}_{\pi_\xi}\left[\hat{Y}[a]|\hat{\Lambda}(\bar{X})\right]^2$$

$$+ 4H^2\sum_{(y_a,y_b)\in\hat{\mathcal{Y}}}\left(\mathbf{Var}_{\pi_\xi}\left[\hat{Y}[a]|\hat{\Lambda}(\bar{X})\right] + \mathbf{Var}_{\pi_\xi}\left[\hat{Y}[b]|\hat{\Lambda}(\bar{X})\right]\right)^2$$

$$+ 4H^2\sum_{y_d\in\mathcal{Y},y_a\in\hat{\mathcal{Y}}}\left(\mathbf{Var}_{\pi_\xi}\left[Y[d]|\hat{\Lambda}(\bar{X})\right] + \mathbf{Var}_{\pi_\xi}\left[\hat{Y}[a]|\hat{\Lambda}(\bar{X})\right]\right)^2$$

$$\leq 8H^2\left(\sum_{i=1}^{k}(n_i + \hat{k})\mathbf{Var}_{\hat{\Lambda},Y\sim\Theta}(Y[i]|\hat{\Lambda} = \hat{\Lambda}^*)^2 + \sum_{i=k+1}^{k+\hat{k}}(n_i + k + \hat{k} - 1)\mathbf{Var}_{\hat{\Lambda},\hat{Y}\sim\Theta}(\hat{Y}[i]|\hat{\Lambda} = \hat{\Lambda}^*)^2\right)$$

$$\leq \frac{4H^2c^2}{M}. \tag{27}$$

Therefore, by Eqs. (25), (26), and (27), we have

$$|\ell(W) - \ell_{\hat{\Theta}}(W)| = \left|\mathbb{E}_{\pi^*}\left[\sum_{l=1,l\neq l_{\bar{X}}}^{k}\bar{h}(l, l_{\bar{X}})\left(\mathbb{P}_{\pi_{\Theta^*}}(Y[l] = 1|\hat{\Lambda}(\bar{X})) - \mathbb{P}_{\pi_{\hat{\Theta}}}(Y[l] = 1|\hat{\Lambda}(\bar{X}))\right)\right]\right|$$

$$= \left|\mathbb{E}_{\pi^*}\left[g_X(\Theta^*) - g_X(\hat{\Theta})\right]\right|$$

$$\leq \left|\mathbb{E}_{\pi^*}\|\nabla g_X(\xi)\|\|\Theta^* - \hat{\Theta}\|\right|$$

$$\leq \frac{2cH}{\sqrt{M}}\|\Theta^* - \hat{\Theta}\|.$$

Now, we apply the assumption that we are able to solve the empirical problem, producing an estimate $\hat{W}$ that satisfies

$$\mathbb{E}\left[\ell_{\hat{\Theta}}(\hat{W}) - \ell_{\hat{\Theta}}(W_{\hat{\Theta}}^*)\right] \leq \chi,$$

where $W_{\hat{\Theta}}^*$ is the true solution to

$$W_{\hat{\Theta}}^* = \arg\min_W \ell_{\Theta}(W).$$

Therefore,

$$
\begin{aligned}
\mathbb{E}\left[\ell(\hat{W}) - \ell(W^*)\right] &= \mathbb{E}\left[\ell_{\hat{\Theta}}(\hat{W}) - \ell_{\hat{\Theta}}(W^*_{\hat{\Theta}}) + \ell_{\hat{\Theta}}(W^*_{\hat{\Theta}}) - \ell_{\hat{\Theta}}(\hat{W}) + \ell(\hat{W}) - \ell(W^*)\right] \\
&\overset{(*)}{\leq} \chi + \mathbb{E}\left[\ell_{\hat{\Theta}}(W^*_{\hat{\Theta}}) - \ell_{\hat{\Theta}}(\hat{W}) + \ell(\hat{W}) - \ell(W^*)\right] \\
&\leq \chi + 4cH\frac{1}{\sqrt{M}}\mathbb{E}\|\hat{\Theta} - \Theta^*\| + \mathbb{E}\left[\ell_{\hat{\Theta}}(W^*_{\hat{\Theta}}) - \ell_{\hat{\Theta}}(\hat{W}) + \ell_{\hat{\Theta}}(\hat{W}) - \ell_{\hat{\Theta}}(W^*)\right] \\
&\leq \chi + 4cH\frac{1}{\sqrt{M}}\mathbb{E}\|\hat{\Theta} - \Theta^*\|,
\end{aligned}
$$

where Eq. $(*)$ comes from condition (23).

With Eqs. (20) and (21), we have Eq. (24) by Lemma D.3, i.e.,

$$
\left(\mathbb{E}\|\hat{\Theta} - \Theta^*\|\right)^2 \leq \mathbb{E}\|\hat{\Theta} - \Theta^*\|^2 \leq \varepsilon^2 M.
$$

We can now bound this using the result of Lemma D.3, which results in

$$
\mathbb{E}\left[\ell(\hat{W}) - \ell(W^*)\right] \leq \chi + 4cH\epsilon.
$$

The proof is completed.

$\square$

E   EXAMPLES AND ILLUSTRATIONS

E.1   LABEL GRAPH AND LABEL HIERARCHY

Fig 5 shows the mapping between a label hierarchy and the corresponding label graph. Indeed, any label hierarchy represented as a DAG can be converted to exact one consistent label graph based on the four types of label relations we defined.

Figure 5: The illustration of mapping between a label hierarchy and a label graph.

E.2   AN EXAMPLE OF INCONSISTENT LABEL GRAPH

Fig. 6 shows an example of an inconsistent label graph. We can see that the label graph is unrealistic and ambiguous because "*Husky*" subsumes "*Canidae*", but (1) "*Canidae*" subsumes "*Dog*" and (2) "*Dog*" subsuems "*Husyky*" combined imply that "*Husky*" should be subsumed by "*Canidae*". Also, from the example, we can see that label graph induced from cyclic label hierarchy must be inconsistent.

Figure 6: The illustration of inconsistent label graph.

E.3 ENUMERATION OF INCONSISTENT TRIANGLE LABEL GRAPH

For a triangle label graph G, we list all inconsistent label relation structures. The consistency of larger label graph with more labels can be verified by checking the consistency of every triangle inside. One example proof of {Exclusive, Overlap, Subsuming} can be found in Lemma 1.

Table 5: Enumeration of Inconsistent Label Relation Triplets.

label relation Triplets		
t_{ab}	t_{bc}	t_{ac}
Overlap	Subsumed	Subsuming
Overlap	Subsumed	Exclusive
Overlap	Subsuming	Subsumed
Overlap	Exclusive	Subsumed
Exclusive	Subsumed	Subsuming
Exclusive	Overlap	Subsuming
Exclusive	Subsuming	Subsuming
Exclusive	Subsuming	Subsumed
Exclusive	Subsuming	Overlap
Subsuming	Exclusive	Subsumed
Subsuming	Subsumed	Exclusive
Subsuming	Overlap	Subsumed
Subsuming	Overlap	Exclusive
Subsuming	Subsuming	Exclusive
Subsuming	Subsuming	Subsumed
Subsuming	Subsuming	Overlap
Subsumed	Overlap	Subsuming
Subsumed	Subsumed	Exclusive
Subsumed	Subsumed	Subsuming
Subsumed	Subsumed	Overlap
Subsumed	Exclusive	Subsuming
Subsumed	Exclusive	Subsumed
Subsumed	Exclusive	Overlap

E.4 AN EXAMPLE OF INDISTINGUISHABLE LABEL GRAPH

Fig. 7 shows an example label graph with indistinguishable label relation structure. Again, red labels represent desired unseen labels, while gray labels are undesired and seen. We can see that unseen label "*Husky*" and "*Bulldog*" have indistinguishable label relation structures because for all seen labels, their label relations are equal. For example, seen label "*Dog*" subsumes both "*Husky*" and "*Bulldog*". In contrast, for "*Husky*" and "*Bengal Cat*", seen label "*Cat*" subsumes the latter but exclusive to the former, which indicates that "*Husky*" and "*Bengal Cat*" have distinguishable label relation structure. Note that "*Bengal Cat*" and "*Persian Cat*" also have indistinguishable label relation structure, but the former is unseen desired label while the latter is seen and can be predicted by some ILF(s). We are only interested in the distinguishablity of a pair of unseen labels.

In practice, users could "break the symmetry" by adding new ILFs with new labels. For example, if we add a ILF that could predict "*Arctic Animals*", then the new seen label "*Arctic Animals*" will be added into label graph as shown in Fig. 8. We know that "*Arctic Animals*" subsumes "*Husky*" but not "*Bulldog*", so we break the indistinguishable label relation structure of "*Husky*" and "*Bulldog*" successfully.

Figure 7: An example of an indistinguishable label relation structure ("*Husky*" and "*Bulldog*").

Figure 8: An example of fixing an indistinguishable label relation structure ("*Husky*" and "*Bulldog*") by adding a new label ("*Arctic Animals*").

F EXPERIMENTAL DETAILS

F.1 DATASET

Large scale Text Classification Dataset[2]**:** LSHTC-3 (Partalas et al., 2015), a large scale hierarchical text classification dataset, which consists of 456,886 documents and 36,504 categories organized in a label hierarchy. We filter out the documents with multiple labels, and preserve categories with more than 500 documents. We use a pre-trained sentence transformer (Reimers & Gurevych, 2019) to obtain document embeddings for classification. We follow Zhang et al. (2021) to generate 5 keyword-based labeling functions for each seen label as ILFs.

Large scale Image Classification Dataset[3]**:** ILSVRC2012 (Russakovsky et al., 2015), a large scale image classification dataset, which consists of 1.2M training images from 1000 object classes based

---

[2]http://lshtc.iit.demokritos.gr/
[3]http://image-net.org/challenges/LSVRC/2012/index#data

on ImageNet. Following Deng et al. (2014) we use WordNet as the label hierarchy, and because all the images are assigned to leave labels in WordNet, for each non-leave label, we aggregate images belonging to its descendants as its data points (Deng et al., 2014). For weak supervision sources creation, we follow Mazzetto et al. (2021b;a) to train 10 image classifiers as ILFs. We randomly sampling 2 or 3 exclusive seen labels from the label graph as well as 500 images for each label to train a ResNet-32 classifier.

F.2 ATTRIBUTES CONSTRUCTION FOR DAP

To construct attributes for unseen labels and data points, we leverage the outputs of ILFs and label relations.

First, based on the label relations and basic logistic rules, we enumerate all the possible assignments of seen labels given a data point. For example, if label A is subsumed by label B, then for a data point, when it belongs to label A, it must also belong to B; And if label A and B are exclusive, then one data cannot belong to both at the same time. Let $s \in S$ denote one possible label assignment and S is the set of all possible s. Then we define the attribute as a vector of $|S|$ dimension where each dimension corresponds to one s.

Second, we define the attribute of unseen labels. For an unseen label A and a label assignment s, if A is not exclusive to any label in s then we set the corresponding attribute $a_s = 1$ for label A, other wise 0. The intuition is that, if A is not exclusive to labels in s, it's likely that when a data belongs to assignment s, it also belongs to label A. For each data point, we use the labels assigned by ILFs to build their attributes. If a data belongs to assignment s then its corresponding attribute $a_s = 1$, otherwise 0.

Then, we can train attribute classifier $p(a|x)$ for each attribute based on data point attributes. During inference, we use unseen label attribute as well as attribute classifier as in Lampert et al. (2013):

$$f(x) = \arg\max_c \prod_{m=1}^{|S|} \frac{p(a_m^c|x)}{p(a_m^c|x)} \tag{28}$$

F.3 HYPER-PARAMETERS

For the training of PGMs, we set the learning rate to be $\frac{1}{n}$ where n is the number of training data. For training logistic regression model, we use the default parameters in scikit-learn library. For training ResNet model, we set batch size as 256 and use Adam optimizer with learning rate being 1e-3 and weight decay being 5e-5.

F.4 HARDWARE AND IMPLEMENTATION DETAILS

All experiments ran on a machine with an Intel(R) Xeon(R) CPU E5-2678 v3 with a 512G memory and a GeForce GTX 1080Ti-11GB GPU.

All the code was implemented in Python. We use the standard implementation of the logistic regression model from Python scikit-learn library[4] and the ResNet model from torchvision library[5].

Our code will be released upon the acceptance.

F.5 DATASET DETAILS OF REAL-WORLD APPLICATIONS

We list the tags we used in the real-world application (Sec. 7.3) and examples of label relations we query from the existing product category taxonomy.

---

[4]https://scikit-learn.org/stable/modules/generated/sklearn.linear_model.LogisticRegression.html
[5]https://pytorch.org/docs/stable/torchvision/models.html

Table 6: The tags and examples of label relations of "*Car Accessories*" category.

new unseen tags:	"*Performance Modifying Parts*", "*Vehicle Tires & Tire Parts*", "*Car Engines & Engine Parts*"
existing tags:	"*Car Modification Parts*", "*Car Parts & Accessories*"
"*Car & Truck Tires*", "*Replacement Car Parts*", "*Car & Truck Wheels*"
label relation examples:	"*Replacement Car Parts*" **subsumes** "*Car Engines & Engine Parts*"
"*Car & Truck Tires*" **is subsumed by** "*Vehicle Tires & Tire Parts*"

Table 7: The tags and examples of label relations of "*Furniture Accessories*" category.

new unseen tags:	"*Clothing & Shoe Storage*", "*Living Room Furniture*", "*Beds & Headboards*"
existing tags:	"*Coffee Tables & End Tables*", "*Entertainment & Media Centers*"
"*Bedroom Furniture*", "*Sofas & Chairs*", "*Mattresses*"
label relation examples:	"*Bedroom Furniture*" **subsumes** "*Beds & Headboards*"
"*Sofas & Chairs*" **is subsumed by** "*Living Room Furniture*"

G ADDITIONAL EXPERIMENTS

G.1 PERFORMANCE DROP WHEN THE DISTINGUISHABLE CONDITION IS VIOLATED

To validate the effectiveness of the distinguishable condition, we drive another 100 WIS tasks from LSHTC-3 dataset where each task has at least one pair of unseen labels sharing exactly the same label relation structure. In Table 8, we report the performance drop on the averaged evaluation results over the 100 WIS tasks with comparison to the numbers in Table 2. Although the two sets of WIS tasks are different and therefore are not individually comparable, the averaged performance drop does indicates that the violation of the distinguishable condition results in undesirable synthesized training labels, which implicitly demonstrates the effectiveness of the distinguishable condition.

Table 8: Performance drop on averaged evaluation results over 100 WIS tasks derived from LSHTC-3 when the distinguishable condition is violated.

Method		Accuracy	F1-score
Label Model	LR-MV	-11.49	-13.83
	W-LR-MV	-11.51	-13.47
	WS-LG	-9.28	-8.63
	PLRM	-9.66	-9.63
End Model	LR-MV	-16.14	-17.08
	W-LR-MV	-15.27	-15.97
	WS-LG	-13.13	-13.78
	PLRM	-13.39	-14.09

G.2 THE PERCENTAGE OF EACH METHOD BEING THE BEST

As we have 100 WIS tasks for each dataset, we are also curious about how many times the proposed PLRM method performs the best. To see this, we plot in Fig. 9 the percentage of each method being the best one among the 100 WIS tasks for both datasets. From the figures we can see that (1) PLRM is the one with the most perform-the-best times and (2) in around or more than 50% cases, PLRM is the best method. We do not expect the PLRM to be the best method across all the 100 WIS tasks since the WIS task could be very diverse depending on the label relation structure and the accuracy/coverage of ILFs. However, results here indicate the advantages of PLRM over baseline methods.

G.3 EXPLANATORY EXPERIMENTS ON SYNTHETIC DATASETS

In this section, we study how different set-up parameters influence both the WIS problem and the methods applied. We conduct a series of explanatory experiments on synthetic dataset. First, we

(a) LSHTC   (b) ILSVRC2012

Figure 9: The percentage of each method being the best one over the 100 WIS tasks for both datasets.

Figure 10: accuracy of inferred labels with respect to different scenarios, where sub-figures (a), (b) and (c) correspond to set-up parameters $\frac{\hat{k}}{k}$, $\frac{n}{k}$ and r, respectively.

study how the accuracy of ILFs affect the WIS problem. We introduce a parameter r, which controls the accuracy of ILF by randomly corrupting $r\%$ of the labels used to train ILF. Larger r results in less accurate ILFs. Then, we fix the number of unseen labels k and study the effect of (1) the number of ILFs n and (2) the number of seen labels $\hat{k}$ on WIS. These two parameters correspond to the following scenarios: (1) users have varying amount of ILFs, and (2) there are varying amount of undesired labels, respectively. Where r is the *label corruption ratio* used to control the accuracy of input models only for synthetic dataset. We generate 100 WIS tasks with each set of parameters and report average accuracy of the inferred training labels in Fig. 10. Overall, we can see that PLRM consistently surpasses baselines in varying scenarios.

Study of r: how the accuracy of ILFs affect the WIS?   From the results in Fig. 10 (c), we can see when ILFs become less accurate, the performances of all the methods decrease as expected. Also, with inaccurate ILFs, the PLRM has almost the same performance as the WS-LG model, which indicates adding complex dependencies do not confer performance gain. The result aligns with the intuition that with limited number of inaccurate ILFs, it is hard to learn undesired labels well and transit them to desired labels via label relations.

Study of $\frac{n}{k}$: how the number of ILFs affects the WIS?   From the results in Fig. 10 (b), we can see with more ILFs, the overall performances increase as expected. This seems reasonable as with more ILFs, we are now able to learn each undesired label and the label relations well, so the PLRM surpasses the WS-LG model and the gap increases along with the number of models.

Study of $\frac{\hat{k}}{k}$: how the number of seen labels affects the WIS?   From the results in Fig. 10 (a), we observe a decrease in overall performance when involving more undesired labels, since ILFs have more diverse label space and it is harder to aggregate their output. Surprisingly, we observe

that adding the complex label relation dependencies still boosts the performance, as the PLRM outperforms the WS-LG model by a large margin. We speculate the reason is: the complex label relation dependencies serve as a regularization to help aggregate diverse ILFs.