META-LEARNING BLACK-BOX OPTIMIZATION VIA BLACK-BOX OPTIMIZATION

ABSTRACT

Optimizing functions without access to gradients is the remit of black-box methods such as evolution strategies. While highly general, their learning dynamics are often times heuristic and inflexible — exactly the limitations that meta-learning can address. Hence, we propose to discover effective update rules for evolution strategies via meta-learning. Concretely, our approach employs a search strategy parametrized by a self-attention-based architecture, which guarantees the update rule is invariant to the ordering of the candidate solutions. We show that meta-evolving this system on a small set of representative low-dimensional analytic optimization problems is sufficient to discover new evolution strategies capable of generalizing to unseen optimization problems, population sizes and optimization horizons. Furthermore, the same learned evolution strategy can outperform established neuroevolution baselines on supervised and continuous control tasks. As additional contributions, we ablate the individual neural network components of our method; reverse engineer the learned strategy into an explicit heuristic form, which remains highly competitive; and show that it is possible to self-referentially train an evolution strategy from scratch, with the learned update rule used to drive the outer meta-learning loop.

1 INTRODUCTION

Black-box optimization (BBO) methods are those general enough for the optimization of functions without access to gradient evaluations. Recently, BBO methods have shown competitive performance to gradient-based optimization, namely of control policies (Salimans et al., 2017; Such et al., 2017; Lee et al., 2022). Evolution Strategies (ES) are a class of BBO that iteratively refines the sufficient statistics of a (typically Gaussian) sampling distribution, based on the function evaluations (or fitness) of sampled candidates (population members). Their update rule is traditionally formalized by equations based on first principles (Wierstra et al., 2014; Ollivier et al., 2017), but the resulting specification is inflexible. On the other hand, the evolutionary algorithms community has proposed numerous variants of BBO, derived from very different metaphors, some of which have been shown to be equivalent (Weyland, 2010).

One way to attain flexibility without having to hand-craft heuristics is to *learn* the update rules of BBO algorithms from data, in a way that makes them more adaptive and scalable. This is the approach we propose: We meta-learn a neural network parametrization of a BBO update rule, on a set of representative task families, while leveraging evaluation parallelism of different BBO instances on modern accelerators, building on recent developments in learned optimization (e.g. Metz et al., 2022). This procedure discovers novel black-box optimization methods via meta-black-box optimization, and is abbreviated by *MetaBBO*. Here, we investigate one particular instance of MetaBBO and leverage it to discover a *learned evolution strategy* (LES).[1]

The concrete LES architecture can be viewed as a minimal Set Transformer (Lee et al., 2019), which naturally enforces an update rule that is invariant to the ordering of candidate solutions within a batch of black-box evaluations. After meta-training, LES has learned to flexibly interpolate between copying the best-performing candidate solution (hill-climbing) and successive moving average updating (finite difference gradients). Our contributions are summarized as follows:

---

[1]Pronounced 'meta-boh' and 'less'.

Figure 1: Overview diagram of MetaBBO, LES & performance on continuous control tasks. **Left: MetaBBO**. The outer loop samples a set of inner loop tasks (uniformly), and a set of candidate LES parameters $\{\theta_i\}_{i=1}^M$ from a meta-ES (here: CMA-ES). After obtaining a normalized meta-fitness score of each LES instance, the meta-ES is updated and we iterate the meta-optimization process. **Middle: LES**. In the inner loop and for each task, we iteratively sample candidate solutions from a Gaussian search distribution and evaluate their fitness. Afterwards, a (meta-learned) Set Transformer-inspired search strategy processes tokens of fitness transformations corresponding to the population member performance. It outputs a set of recombination weights, which are used to update the mean and standard deviation of the diagonal Gaussian search distribution. An additional RNN module (not shown) computes per-dimension learning rates by processing momentum-like statistics and a timestamp. **Right: Neuroevolution of control policies**. Average normalized performance across 8 continuous control Brax environments (Freeman et al., 2021). The LES discovered by MetaBBO on a small set of analytic meta-training problems generalizes far beyond its meta-training distribution, in terms of problem type, population size, search dimension and optimization horizon. In fact, LES outperforms diagonal ES baselines and scales well with an increased population size. Results are averaged over 10 independent runs (± 1.96 standard errors). Each task-specific learning curve is normalized by the largest and smallest fitness across all considered ES. Afterwards, the normalized learning curves are averaged across tasks. More training details and results can be found in Section 5 and in the supplementary information (SI, A.2 and A.6, Figure 14).

1. We propose a novel self-attention-based ES parametrization, and demonstrate that it is possible to meta-learn black-box optimization algorithms that outperform existing hand-crafted ES algorithms on neuroevolution tasks (Figure 1, right). The learned strategy generalizes across optimization problems, compute resources and search space dimensions.

2. We investigate the importance of the meta-task distribution and meta-training protocol. We find that in order to meta-evolve a well-performing ES, only a handful of core optimization classes are needed at meta-training time. These include separable, multi-modal and high conditioning functions (Section 5).

3. We reverse-engineer the learned search strategy. More specifically, we ablate the black-box components recovering an interpretable strategy and show that all neural network components have a positive effect on the early performance of the search strategy (Section 6). The *discovered evolution strategy* provides a simple to implement yet competitive new ES.

4. We demonstrate how to generate a new LES starting from a blank-slate LES: A randomly initialized LES can bootstrap its own learning progress and *self-referentially* meta-learn its own weights (Section 7).

2 RELATED WORK

Evolution Strategies & Neuroevolution. Unlike gradient descent-based optimization methods, ES (Rechenberg, 1973; Schwefel, 1977; Beyer & Schwefel, 2002) rely only on black-box function evaluations without the necessity of access to gradient evaluations. Instead, they iterate between the sampling of candidate solutions, their evaluation and the updating of the sampling distribution. ES can be grouped into estimation of distribution algorithms, which refine the sufficient statistics of a sampling distribution in order to increase the likelihood of high fitness solutions (Hansen & Ostermeier, 2001) and finite-difference gradient-based methods (Wierstra et al., 2014; Nesterov & Spokoiny, 2017). They can address non-differentiable problem settings and yield competitive wall-clock times on neural network tasks due to parallel fitness evaluation (Salimans et al., 2017; Such et al., 2017).

Discovering Algorithm Components from Data. The history of machine learning has been characterized by the successive replacement of manually designed components by modules that are informed by data. This includes the use of convolutional neural networks that learn filters (Fukushima, 1975; LeCun et al., 1998), neural architecture search (Elsken et al., 2019), initilization schemes (Dauphin & Schoenholz, 2019) or hyperparameter search (Chen et al., 2017; 2022). Recently, these efforts have been extended to the end-to-end discovery of objective functions in Reinforcement Learning (Kirsch et al., 2019; Oh et al., 2020; Xu et al., 2020; Lu et al., 2022), the online refinement of hyperparameter schedules (Xu et al., 2018; Zahavy et al., 2020; Flennerhag et al., 2021; Parker-Holder et al., 2022) and the meta-learning of entire learning algorithms (Wang et al., 2016; Kirsch & Schmidhuber, 2021; Kirsch et al., 2022). Furthermore, the discovery process can be supported by suitable inductive biases provided by the underlying network architecture. Our proposed LES architecture leverages the invariance property of set transformers to the input ordering (Lee et al., 2019; Kossen et al., 2021; Tang & Ha, 2021) in order to derive a neural network-based family of ES.

Meta-Learned Gradient-Based Optimization. An exciting direction aims to meta-learn gradient descent-based learning rules (Bengio et al., 1992; Andrychowicz et al., 2016; Metz et al., 2019) to update the weights of a neural network. Unlike our proposed method, these approaches require access to gradient calculations using the backpropagation algorithm implemented by automatic differentiation software. The gradient and several summary statistics are processed by a small neural network, whose weights have been meta-learned on a distribution of tasks (Metz et al., 2020). The resulting outputs are calculated on a per-parameter basis and used to characterize the magnitude and direction of the weight change. It has been shown that this approach can extract useful inductive biases for domain-specific gradient-based optimization (Merchant et al., 2021; Metz et al., 2022) but can struggle to broadly generalize to task domains beyond the meta-training distribution.

Self-Referential Meta-Learning. Our current learning systems are not capable of flexibly refining their own learning behavior. Schmidhuber (1987) first articulated the vision of self-referentially updating a genetic algorithm to improve its own performance. Fast weight programmers (Schmidhuber, 1993; Irie et al., 2022) and hypernetworks (Ha et al., 2016; Von Oswald et al., 2019) provide a first step into a direction of neural network systems capable of self-improvement and bootstrapping their own learning progress. Kirsch & Schmidhuber (2022) further formulated a simple heuristic to allocate compute resources for population-based self-referential learning. Metz et al. (2021a) showed that the recursive meta-training of gradient-based optimizers is feasible using an improvement mechanism based on population-based training (Jaderberg et al., 2017). Here, we introduce a simple self-referential MetaBBO loop, which successfully meta-evolves a LES capable of generalization to continuous control tasks.

3 PRELIMINARIES: GAUSSIAN EVOLUTION STRATEGIES

Many common ES use Gaussian search distributions, with the most scalable ones using isotropic or diagonal (axis-aligned) Gaussian approximations. They have shown to effectively scale to large search space dimensions, specifically in the context of neuroevolution (Salimans et al., 2017), and can outperform full covariance search methods (Ros & Hansen, 2008). We therefore chose them as the starting point for our neural network-based LES architecture, and use three common ones as baselines throughout: OpenES (Salimans et al., 2017), sep-CMA-ES (Ros & Hansen, 2008) and SNES (Schaul et al., 2011).

Diagonal ES maintain mean $\mathbf{m} \in \mathbb{R}^D$ and standard deviation vectors $\boldsymbol{\sigma} \in \mathbb{R}^D$, where D denotes the number of search space dimensions. At each generation one samples a population of candidate solutions $\mathbf{x}_j \in \mathbb{R}^D \sim \mathcal{N}(\mathbf{m}, \boldsymbol{\sigma} \mathbf{1}_D)$ for all $j = 1, ..., N$ population members. Each solution vector is evaluated, producing fitness estimates $f_j \in \mathbb{R}$, which are used to construct recombination weights $\boldsymbol{w}_j$. These weights define how to update the search distribution (mean and standard deviations). Most often, the weights are assigned based on the rank of the fitness $\text{rank}(j) \in [1, N]$ among the current population, for example:

$$w_{t,j}(\{f_k\}_{k=1}^N) = w_{\text{rank}(j)} = \begin{cases} \frac{1}{E}, & \text{if } \text{rank}(j) \leq E, \\ 0, & \text{otherwise,} \end{cases} \tag{1}$$

where $w_{\text{rank}(j)}$ denotes the weight assigned to the rank of member j, and E denotes the number of high-fitness candidates that contribute to the update. The search distribution is then updated using an exponentially moving fitness-weighted average:

$$\mathbf{m}_{t+1} = (1 - \boxed{\boldsymbol{\alpha}_{m,t}})\mathbf{m}_t + \boxed{\boldsymbol{\alpha}_{m,t}} \sum_{j=1}^N \boxed{\boldsymbol{w}_{t,j}} \mathbf{x}_j, \tag{2}$$

$$\boldsymbol{\sigma}_{t+1} = (1 - \boxed{\boldsymbol{\alpha}_{\sigma,t}})\boldsymbol{\sigma}_t + \boxed{\boldsymbol{\alpha}_{\sigma,t}} \sqrt{\sum_{j=1}^N \boxed{\boldsymbol{w}_{t,j}} (\mathbf{x}_j - \mathbf{m}_t)^2}, \tag{3}$$

which can be interpreted as a finite-difference gradient update on the expected fitness. Both the learning rates $\boldsymbol{\alpha}_m, \boldsymbol{\alpha}_\sigma$ and the weighting scheme $\boldsymbol{w}_t$, highlighted in red, are commonly fixed across the update generations $t = 1, ..., T$, which is an obvious restriction to the flexibility of the ES. The main aim of our proposed meta-learned neural network parametrization is to overcome the implied limitations by meta-learning these.

4 META-EVOLVING EVOLUTION STRATEGIES

In this section, we first introduce the learned evolution strategy architecture (Figure 1, middle), a self-attention-based generalization of the diagonal Gaussian ES in equations 2 and 3. Section 4.2 then outlines the MetaBBO procedure (Figure 1, left) used to meta-evolve the weights of LES.

4.1 *Learned Evolution Strategies (LES)*: POPULATION ORDER-INVARIANCE VIA ATTENTION

A fundamental property that any (learned) ES has to fulfill is invariance in the ordering of population members within a generation. Intuitively, the order of the population members is arbitrary and should therefore not affect the search distribution update. A natural inductive bias for an appropriate neural network-based parametrization is given by the dot-product self-attention mechanism. Our proposed learned evolution strategy processes a matrix F_t of population member-specific tokens (Figure 1, middle). $F_t \in \mathbb{R}^{N \times 3}$ consists of (1) the z-scored population fitness scores, (2) a centered rank transformation (lying within $[-0.5, 0.5]$), and (3) a Boolean indicating whether the fitness score exceeds the previously best score. This fitness matrix is embedded into queries ($Q \in \mathbb{R}^{N \times D_K}$), keys ($K \in \mathbb{R}^{N \times D_K}$) and values ($V \in \mathbb{R}^{N \times 1}$) using learned linear transforms with weights W_K, W_Q, W_V. Recombination weights are computed as attention scores over the members:

$$\boldsymbol{w}_t = \text{softmax}\left(\text{softmax}\left(\frac{QK^T}{\sqrt{N}}\right) V\right) = \text{softmax}\left(\text{softmax}\left(\frac{F_t W_Q W_K^T F_t^T}{\sqrt{N}}\right) F_t W_V\right) \in \mathbb{R}^N.$$

The resulting recombination weights are shared across the search space dimensions, but vary across the generations t.[2] Instead of using a set of fixed learning rates, we additionally modulate $\boldsymbol{\alpha}_{m,t}, \boldsymbol{\alpha}_{\sigma,t} \in \mathbb{R}^D$ by an LSTM (Hochreiter & Schmidhuber, 1997) parametrized by ϕ and shared across D. It processes a timestamp embedding and parameter-specific information provided by momentum-like statistics (see SI A.1). The chosen parametrization can in principle smoothly interpolate between integrating information from many population members and copying over a single

---

[2]The LES architecture normalizes the query-key dot-product by $\sqrt{N}$ and not $\sqrt{D_k}$. We found this to help with population size generalization (SI, Figure 11). It implicitly encourages LES to average well-performing candidate solutions for larger population sizes. We study the effect on the learned $\boldsymbol{w}_t$ in Section 6.

best performing solution by setting a single recombination weight and $\boldsymbol{\alpha}_{m,t}$ to one for all dimensions. The set of LES parameters are given by $\theta = \{W_k, W_q, W_v, \phi\}$, whose total number is usually small (<1000) given a sufficient key embedding size ($D_K = 8$). The complexity of the proposed LES scales linearly with the number of parameters and quadratically in the population size.

4.2 *MetaBBO*: META-BLACK-BOX OPTIMIZATION OF BLACK-BOX OPTIMIZERS

How do we learn the LES parameters θ, so that they provide useful inductive biases for blackbox optimization? Meta-learning via evolutionary optimization has previously proven successful in the context of learned gradient-based optimization (Vicol et al., 2021) and RL objective discovery (Lu et al., 2022). It avoids exploding meta-gradients (Metz et al., 2021b), myopic meta-solutions (Flennerhag et al., 2021; Lange & Sprekeler, 2022), and allows to optimize θ through long inner loop ES executions involving stochastic sampling. We adopt this meta-evolution approach in MetaBBO and iterate the following steps (Figure 1, left; SI Algorithm 1):

1. **Meta-sampling**. At each meta-generation we sample a population of LES network parametrizations θ_i for $i = 1, \ldots, M$ meta-population members using a standard off-the-shelf ES algorithm with meta-mean μ and covariance Σ.

2. **Inner loop search**. Next, we estimate the performance of different LES parametrizations on a set of tasks. We sample a set of inner loop optimization problems. For each task we initialize a mean $\mathbf{m}_0 \in \mathbb{R}^D$, standard deviation $\boldsymbol{\sigma}_0 \in \mathbb{R}^D$. Each LES instance is then executed on a batch of inner loop tasks (in parallel) with N population members and for a fixed set of inner-loop generations $t = 1, \ldots, T$.

3. **Meta-normalize**. In order to ensure stable meta-optimization with optimization problems that can exhibit very different fitness scales, we normalize (z-score) the fitness scores within tasks and across meta-population members. We average the scores over inner-loop tasks, and maximize over inner-loop population members and over generations.

4. **Meta-updating**. Given the meta-performance estimate for the different LES parametrizations, we update the meta-ES search distribution μ', Σ' and iterate.

The choice of the meta-task distribution is crucial to ensure generalization of the meta-learned evolution strategy. We select a small set of classic black-box optimization functions, to characterize a space of representative optimization problems. The problem space includes smooth functions with and without high curvature and multi-modal surfaces with global and local structure. Furthermore, we apply Gaussian additive noise to the fitness evaluations to mimic unreliable estimation and sample optima offsets. MetaBBO differs from standard meta-learning in a couple aspects: First, we use BBO in both the inner and outer loop. This allows for flexible LES design, stochastic sampling and long inner loop ES execution. We also leverage the so-called 'Pegasus-trick' (Ng & Jordan, 2000) and use the same task parameters, $\mathbf{m}_0$ and fixed randomness for all meta-population members θ_i. The fixed stochasticity and task-based normalization enhances stable meta-optimization.

5 EXPERIMENTS

In this section we discuss the results of meta-learning LES parameters via MetaBBO. We answer the following questions: Does MetaBBO discover an ES capable of generalization beyond the meta-training distribution and can the LES meta-trained only on a limited set of functions even generalize to unseen neural network tasks with different fitness functions & network architectures?

5.1 META-TRAINING ON THE BLACK-BOX OPTIMIZATION BENCHMARK

Throughout, we meta-train on functions from the BBOB (Hansen et al., 2010) benchmark, which comprise a set of challenging functions for optimization (Table 1). From BBOB, we construct a *small*, *medium*, and *large* meta-training set (detailed in Section 5.2). To create a task instance, we randomly sample: (1) a function f from the meta-training set, (2) a dimensionality $D \sim U\{2, 3, \ldots, 10\}$ for $f : \mathbb{R}^D \to \mathbb{R}$, (3) a noise-level $\Xi \sim U[0, 0.1]$, and (4) an optimum offset $\boldsymbol{z} \sim U[-5, 5]^D$, which together creates a stochastic objective $\hat{f}(\boldsymbol{x}) \sim f(\boldsymbol{x} + \boldsymbol{z}) + \Xi \mathcal{N}(0, 1)$. Finally, (5) we sample an initialization $\boldsymbol{m}_0 \sim [-5, 5]^D$.

Figure 2: BBOB evaluation of LES. **Left**. MetaBBO fitness objective over meta-generations. The optimization process is robust to the choice of meta-ES. **Middle**. Minimization performance on Sphere task across dimensions and population size ($T = 25$). Boxed cells indicate meta-training tasks. **Right**. Relative performance on different BBOB test functions ($D = 10, N = 16, T = 100$), lower is better. Despite LES only being meta-trained on a population size of $N = 16$ and low-dimensional ($D \leq 10$) search spaces, it is capable of generalizing to different functions, problem settings and resources. Detailed meta-training curves can be found in SI A.6 (Figures 7, 8).

In the MetaBBO outer loop we optimize θ using CMA-ES (Hansen & Ostermeier, 2001) for 1500 meta-generations with a meta-population size of $M = 256$. We sample 128 tasks and train each sampled LES on each task independently. Each LES is unrolled for $T = 50$ generations, with $N = 16$ population members in each iteration. Each LES-task pair is assigned a raw fitness score according to the highest fitness (lowest loss) obtained in the rollout. These raw scores are meta-normalized per task before we average them to obtain a fitness score for each sampled LES. During MetaBBO training, we find average meta-training improves rapidly (Figure 2, top left) and is invariant to the choice of the meta-ES optimizer. We assess the performance of LES obtained through the MetaBBO outer loop, on the BBOB functions (Figure 2, right). LES generalizes well to larger dimensions and larger evaluation budgets on both meta-training and meta-testing function classes. While the task complexity increases with D and performance drops for a fixed population size, LES is capable of making use of the additional evaluations provided by an increased population. We now turn to evaluating LES trained on BBOB on other domains and even learning paradigms.

5.2 META-GENERALIZATION OF LES TO UNSEEN NEUROEVOLUTION TASKS

Our results on BBOB suggests that LES have strong generalizing properties, thus prompting the question, what are the limits of LES' generalization capabilities? In this section, we evaluate an LES trained on BBOB on a set of CNN-based classification tasks and continuous control tasks (Figure 3) using MLP policies. This requires LES to generalize beyond the 10-dimensional problems it was trained on to thousands of dimensions. Not only that, but also to completely different loss surfaces, and even learning paradigms (in the case of continuous control).

Figure 3 shows that LES is indeed capable of successfully evolving CNN classifiers on different MNIST variants. We also find that it is capable of evolving 4-layer MLP policies for robotics tasks (Freeman et al., 2021). We consider three budgets for *test-time* optimisation (that vary in inner loop length T and population size N, see Figure 3). LES generally outperforms ES baselines[3] across test-time budgets. It enjoys a substantial advantage in small budgets, where it outperforms baselines on 5 out of 7 tasks. LES still performs best on the majority of tasks for the medium and large adaptation budgets, which requires it to generalize to larger populations and longer unroll lengths.

Next, we evaluate the impact of the meta-training distribution on the generalization of LES. The *small* meta-training set consists of 1 BBOB function and restricts dimenionality to $D = 2$ with inner loop length $T = 25$. *medium* is restricted to 5 functions., with $D \in \{1, 2, \ldots, 5\}$ and $T = 25$; *large* is given by 10 functions, $D \in \{1, 2, \ldots, 10\}$ and $T = 50$. Figure 4 shows that training on broader meta-training distributions has a positive effect on the generalization capability of the trained LES, as measured on continuous control tasks. In particular, we find that meta-training with larger populations in the inner loop especially benefits from scaling up the meta-training set.

---

[3]For all considered ES we grid-searched over different $\boldsymbol{\sigma}_0$ initial scales. The learning rate of the baselines were additionally tuned on the Brax ant environment. More hyperparameter details can be found in the SI A.4.

Figure 3: Evaluation of LES on classification and continuous control tasks. **Top**. BBOB meta-evolved LES generalizes to classification tasks including MNIST/Fashion-MNIST/K-MNIST classification using a simple Convolutional Neural Network. **Bottom**. The learned strategy can also evolve control policies based on a 4 hidden layer Tanh MLP architecture with 32 hidden units in 8 different control environments. Results are averaged over 5 (vision) and 10 (control) independent runs and max/min normalized for Brax for better comparison. Detailed learning curves can be found in SI A.6 (Figures 14, 15).

6   REVERSE ENGINEERING LEARNED EVOLUTION STRATEGIES

In order to investigate which algorithmic components are discovered by the MetaBBO procedure, we start by ablating the different meta-learned neural network modules. Fixing both recombination weights and the learning rate modulation, as per the simple Gaussian ES in Section 3 degrades performance significantly (Figure 5, top left). Fixing the recombination weights (as in equation 1, $E = 0.5N$) also decreases performance, but fixing the learning rates to $\alpha_m = 1, \alpha_\sigma = 0.1$ does not hurt performance significantly. We observed that the learning rates are flexibly adapted early in training, but settle quickly to constant values (Figure 5, right). Next, we visualized the recombination weights for a LES run on the Walker2D Brax task (Figure 5, top middle). LES performs a variable amount of selection and either applies hill-climbing or integrates information

Figure 4: The performance of LES increases as it is meta-trained on richer task distributions. We plot the relative performance of LES on Brax tasks against OpenES (Salimans et al., 2017).

from multiple well-performing solutions. We plot the weights as a function of the centered rank (for $N = 256$) for sampled Gaussian fitness scores (Figure 5, bottom middle). The recombination weights can be well approximated by a softmax parametrization of the centered ranks:

$$\boldsymbol{w}_{t,j} = \text{softmax}\left(\beta \times (\text{rank}(j)/N - 0.5)\right), \ \forall j = 1, ..., N, \tag{4}$$

with a temperature parameter $\beta \approx 16$. Intuitively, the temperature regulates the amount of selection pressure applied by the recombination weights. Based on these insights, we implement an inter-

Figure 5: Reverse engineering of LES. **Left**. Ablation study of LES and performance of reverse-engineered DES on continuous control tasks. The self-attention-based recombination weights contribute most to the performance of LES. Furthermore, DES provides a competitive ES when sufficiently tuning β. Results are averaged over 5 independent runs (± 1.96 standard errors). **Middle**. Recombination weights in the first 20 LES generations on the Walker2D task. LES can perform both hill climbing by assigning high recombination weight to the best performing population member and distribute the recombination weight across multiple well-performing candidates. The LES recombination weights can be approximated well by equation (4). **Right**. Learning rate modulation of LES on a subset of dimensions. LES learning rates quickly converge to fixed values after initial adaption. Detailed learning curves can be found in SI A.6 (Figures 10, 16).

pretable ES that uses the discovered recombination weight approximation. We call the resulting algorithm *Discovered Evolution Strategy* (DES, SI Algorithm 2). DES($\beta = 16$) performs similarly to LES on the Brax benchmark tasks and can be further improved by tuning the temperature parameter (Figure 5, bottom left). This result highlights that MetaBBO can be used not only to discover black-box ES strategies, but also to discover new interpretable inductive biases.

7 Self-Referential Meta-Evolution of LES

Given a choice of meta-ES, MetaBBO can discover LES that performs competitively with baseline ES. It is therefore natural to ask, can we use an LES to discover a new LES? And can this be a purely self-referential loop, starting from a random initialization? To address this question we consider a two-step self-referential metaBBO paradigm, which starts from a random θ_{meta} (Figure 6, left):

1. We evaluate a set of candidate LES parametrizations $\theta_i \sim \mathcal{N}(\mu, \Sigma)$ with $\Sigma = \boldsymbol{\sigma}\mathbb{1}$. After obtaining the meta-fitness scores $f(\theta_i)$, we update the strategy statistics using the meta-LES update rule $\mu', \Sigma' \leftarrow \text{LES}(\{\theta_i, f_i\}_{i=1}^M | \mu, \Sigma, \theta_{meta})$.

2. If the meta-fitness has improved, we replace $\theta_{meta} \leftarrow \arg\max_{\theta_i} f(\theta_i)$ using a hill-climbing step that copies the best performing inner-loop mean $\mu' \leftarrow \theta_{meta}$. Additionally, we reset the meta-search variance to induce additional exploration around the newly improved meta-search mean: $\Sigma \leftarrow \sigma_0 \mathbb{1}_D$.

Note that this procedure starts out as simple random search with hill-climbing selection. As the meta-parameters are updated, the meta-search is improved by the newly learned inductive biases. Thereby, LES is capable of improving its own optimization behavior. Figure 6 compares different meta-training procedures for LES, including the usage of CMA-ES, a previously meta-trained and

Figure 6: Self-Referential MetaBBO of LES. **Left**. We use LES to meta-evolve its own parameters θ starting from a random initialization and using hill climbing replacement. **Middle**. Meta-performance over training. It is possible to meta-train LES using both a previously trained and frozen instance and a self-referentially improved random initialization. **Right, Top**. Performance on 8-dimensional Sphere and Acrobot control tasks throughout meta-training. **Right, Bottom**. While the LES discovered by a frozen pre-trained version does not generalize to Brax meta-testing, the self-referentially meta-trained one does. Results are averaged over 5 independent runs (+/- 1.96 standard errors). Detailed learning curves can be found in SI A.6 (Figures 17, 8).

fixed LES instance, and our proposed self-referential training paradigm. We find it is indeed feasible to effectively self-evolve LES starting from a random initialization. While the meta-fitness is improved fastest by the pre-trained LES instance, we observe that the resulting meta-trained LES does not generalize well to the downstream Brax evaluation (Figure 6, bottom right). Both the CMA-ES optimizer and self-referential meta-training procedure, on the other hand, are capable of meta-evolving stable and performant LES, that do not overfit to the meta-training task distribution. We speculate that self-referential meta-training performs implicit regularization: LES is forced to simultaneously perform well on the inner loop tasks and to progress its own continual improvement.

8 CONCLUSION & DISCUSSION

Summary. We introduced a self-attention-based ES architecture and a procedure to effectively meta-learn its parametrization. The resulting learned evolution strategy is flexible and outperforms established baseline strategies on both vision and continuous control tasks. We reverse engineered the discovered search update rule into a simple and competitive DES. Finally, we showed that it is possible to successfully self-referentially evolve a LES starting from a random initialization of itself.

Limitations. The LES considered in this paper only applies to diagonal covariance strategies. This limits its effectiveness on non-separable problems. We observed that the learning rate module can struggle to generalize to long time horizons indicating a degree of temporal meta-overfitting. Finally, the self-attention mechanism scales quadratically in the number of population members, which may pose a challenge for large-scale applications.

Future work. Our LES architecture meta-learns to modulate the search distribution update solely based on fitness transformations. One potential extension is to provide additional information (agent trajectory or multiple evaluations) to the attention module. Thereby, the MetaBBO could discover behavioural descriptors in the context of quality-diversity optimization (Pugh et al., 2016; Cully & Demiris, 2017) or application-specific denoising procedures. Furthermore, one may want to attend over an archive of well-performing solutions (e.g. as in genetic algorithms) using cross-attention that implements a cross-over operation. Finally, our experiments indicate the potential of further scaling of the MetaBBO procedure to broader meta-training task distributions.

REFERENCES

Marcin Andrychowicz, Misha Denil, Sergio Gomez, Matthew W Hoffman, David Pfau, Tom Schaul, Brendan Shillingford, and Nando De Freitas. Learning to learn by gradient descent by gradient descent. *Advances in neural information processing systems*, 29, 2016.

Samy Bengio, Yoshua Bengio, Jocelyn Cloutier, and Jan Gescei. On the optimization of a synaptic learning rule. In *Optimality in Biological and Artificial Networks?*, pp. 281–303. Routledge, 1992.

Hans-Georg Beyer and Hans-Paul Schwefel. Evolution strategies–a comprehensive introduction. *Natural computing*, 1(1):3–52, 2002.

James Bradbury, Roy Frostig, Peter Hawkins, Matthew James Johnson, Chris Leary, Dougal Maclaurin, George Necula, Adam Paszke, Jake VanderPlas, Skye Wanderman-Milne, and Qiao Zhang. JAX: composable transformations of Python+NumPy programs, 2018. URL http://github.com/google/jax.

Yutian Chen, Matthew W. Hoffman, Sergio Gómez Colmenarejo, Misha Denil, Timothy P. Lillicrap, Matt Botvinick, and Nando de Freitas. Learning to learn without gradient descent by gradient descent. In Doina Precup and Yee Whye Teh (eds.), *Proceedings of the 34th International Conference on Machine Learning*, volume 70 of *Proceedings of Machine Learning Research*, pp. 748–756. PMLR, 06–11 Aug 2017. URL https://proceedings.mlr.press/v70/chen17e.html.

Yutian Chen, Xingyou Song, Chansoo Lee, Zi Wang, Qiuyi Zhang, David Dohan, Kazuya Kawakami, Greg Kochanski, Arnaud Doucet, Marc'aurelio Ranzato, et al. Towards learning universal hyperparameter optimizers with transformers. *arXiv preprint arXiv:2205.13320*, 2022.

Antoine Cully and Yiannis Demiris. Quality and diversity optimization: A unifying modular framework. *IEEE Transactions on Evolutionary Computation*, 22(2):245–259, 2017.

Yann N Dauphin and Samuel Schoenholz. Metainit: Initializing learning by learning to initialize. *Advances in Neural Information Processing Systems*, 32, 2019.

Thomas Elsken, Jan Hendrik Metzen, and Frank Hutter. Neural architecture search: A survey. *The Journal of Machine Learning Research*, 20(1):1997–2017, 2019.

Sebastian Flennerhag, Yannick Schroecker, Tom Zahavy, Hado van Hasselt, David Silver, and Satinder Singh. Bootstrapped meta-learning. *arXiv preprint arXiv:2109.04504*, 2021.

C Daniel Freeman, Erik Frey, Anton Raichuk, Sertan Girgin, Igor Mordatch, and Olivier Bachem. Brax–a differentiable physics engine for large scale rigid body simulation. *arXiv preprint arXiv:2106.13281*, 2021.

Kunihiko Fukushima. Cognitron: A self-organizing multilayered neural network. *Biological cybernetics*, 20(3):121–136, 1975.

David Ha, Andrew Dai, and Quoc V Le. Hypernetworks. *arXiv preprint arXiv:1609.09106*, 2016.

Nikolaus Hansen and Andreas Ostermeier. Completely derandomized self-adaptation in evolution strategies. *Evolutionary computation*, 9(2):159–195, 2001.

Nikolaus Hansen, Anne Auger, Steffen Finck, and Raymond Ros. *Real-parameter black-box optimization benchmarking 2010: Experimental setup*. PhD thesis, INRIA, 2010.

Charles R Harris, K Jarrod Millman, Stéfan J Van Der Walt, Ralf Gommers, Pauli Virtanen, David Cournapeau, Eric Wieser, Julian Taylor, Sebastian Berg, Nathaniel J Smith, et al. Array programming with numpy. *Nature*, 585(7825):357–362, 2020.

Sepp Hochreiter and Jürgen Schmidhuber. Long short-term memory. *Neural computation*, 9(8): 1735–1780, 1997.

John D Hunter. Matplotlib: A 2d graphics environment. *Computing in science & engineering*, 9 (03):90–95, 2007.

Kazuki Irie, Imanol Schlag, Róbert Csordás, and Jürgen Schmidhuber. A modern self-referential weight matrix that learns to modify itself. *arXiv preprint arXiv:2202.05780*, 2022.

Max Jaderberg, Valentin Dalibard, Simon Osindero, Wojciech M Czarnecki, Jeff Donahue, Ali Razavi, Oriol Vinyals, Tim Green, Iain Dunning, Karen Simonyan, et al. Population based training of neural networks. *arXiv preprint arXiv:1711.09846*, 2017.

Louis Kirsch and Jürgen Schmidhuber. Meta learning backpropagation and improving it. *Advances in Neural Information Processing Systems*, 34:14122–14134, 2021.

Louis Kirsch and Jürgen Schmidhuber. Self-referential meta learning. In *Decision Awareness in Reinforcement Learning Workshop at ICML 2022*, 2022.

Louis Kirsch, Sjoerd van Steenkiste, and Jürgen Schmidhuber. Improving generalization in meta reinforcement learning using learned objectives. *arXiv preprint arXiv:1910.04098*, 2019.

Louis Kirsch, Sebastian Flennerhag, Hado van Hasselt, Abram Friesen, Junhyuk Oh, and Yutian Chen. Introducing symmetries to black box meta reinforcement learning. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 36, pp. 7202–7210, 2022.

Jannik Kossen, Neil Band, Clare Lyle, Aidan N Gomez, Thomas Rainforth, and Yarin Gal. Self-attention between datapoints: Going beyond individual input-output pairs in deep learning. *Advances in Neural Information Processing Systems*, 34:28742–28756, 2021.

Robert Tjarko Lange. evosax: JAX-based evolution strategies, 2022a. URL http://github.com/RobertTLange/evosax.

Robert Tjarko Lange. gymnax: A JAX-based reinforcement learning environment library, 2022b. URL http://github.com/RobertTLange/gymnax.

Robert Tjarko Lange and Henning Sprekeler. Learning not to learn: Nature versus nurture in silico. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 36, pp. 7290–7299, 2022.

Yann LeCun, Léon Bottou, Yoshua Bengio, and Patrick Haffner. Gradient-based learning applied to document recognition. *Proceedings of the IEEE*, 86(11):2278–2324, 1998.

Juho Lee, Yoonho Lee, Jungtaek Kim, Adam Kosiorek, Seungjin Choi, and Yee Whye Teh. Set transformer: A framework for attention-based permutation-invariant neural networks. In *International conference on machine learning*, pp. 3744–3753. PMLR, 2019.

Kuang-Huei Lee, Ofir Nachum, Tingnan Zhang, Sergio Guadarrama, Jie Tan, and Wenhao Yu. Pi-ars: Accelerating evolution-learned visual-locomotion with predictive information representations. *arXiv preprint arXiv:2207.13224*, 2022.

Chris Lu, Jakub Grudzien Kuba, Alistair Letcher, Luke Metz, Christian Schroeder de Witt, and Jakob Nicolaus Foerster. Discovered policy optimisation. In *Decision Awareness in Reinforcement Learning Workshop at ICML 2022*, 2022.

Amil Merchant, Luke Metz, Samuel S Schoenholz, and Ekin D Cubuk. Learn2hop: Learned optimization on rough landscapes. In *International Conference on Machine Learning*, pp. 7643–7653. PMLR, 2021.

Luke Metz, Niru Maheswaranathan, Jeremy Nixon, Daniel Freeman, and Jascha Sohl-Dickstein. Understanding and correcting pathologies in the training of learned optimizers. In *International Conference on Machine Learning*, pp. 4556–4565. PMLR, 2019.

Luke Metz, Niru Maheswaranathan, C Daniel Freeman, Ben Poole, and Jascha Sohl-Dickstein. Tasks, stability, architecture, and compute: Training more effective learned optimizers, and using them to train themselves. *arXiv preprint arXiv:2009.11243*, 2020.

Luke Metz, C Daniel Freeman, Niru Maheswaranathan, and Jascha Sohl-Dickstein. Training learned optimizers with randomly initialized learned optimizers. *arXiv preprint arXiv:2101.07367*, 2021a.

Luke Metz, C Daniel Freeman, Samuel S Schoenholz, and Tal Kachman. Gradients are not all you need. *arXiv preprint arXiv:2111.05803*, 2021b.

Luke Metz, C Daniel Freeman, James Harrison, Niru Maheswaranathan, and Jascha Sohl-Dickstein. Practical tradeoffs between memory, compute, and performance in learned optimizers. *arXiv preprint arXiv:2203.11860*, 2022.

Yurii Nesterov and Vladimir Spokoiny. Random gradient-free minimization of convex functions. *Foundations of Computational Mathematics*, 17(2):527–566, 2017.

Andrew Y Ng and Michael I Jordan. Pegasus: A policy search method for large mdps and pomdps. In *Proceedings of the Sixteenth Conference on Uncertainty in Artificial Intelligence (UAI)*, pp. 406–415, 2000.

Junhyuk Oh, Matteo Hessel, Wojciech M Czarnecki, Zhongwen Xu, Hado P van Hasselt, Satinder Singh, and David Silver. Discovering reinforcement learning algorithms. *Advances in Neural Information Processing Systems*, 33:1060–1070, 2020.

Yann Ollivier, Ludovic Arnold, Anne Auger, and Nikolaus Hansen. Information-geometric optimization algorithms: A unifying picture via invariance principles. *Journal of Machine Learning Research*, 18(18):1–65, 2017.

Jack Parker-Holder, Raghu Rajan, Xingyou Song, André Biedenkapp, Yingjie Miao, Theresa Eimer, Baohe Zhang, Vu Nguyen, Roberto Calandra, Aleksandra Faust, et al. Automated reinforcement learning (autorl): A survey and open problems. *Journal of Artificial Intelligence Research*, 74: 517–568, 2022.

Justin K Pugh, Lisa B Soros, and Kenneth O Stanley. Quality diversity: A new frontier for evolutionary computation. *Frontiers in Robotics and AI*, pp. 40, 2016.

Ingo Rechenberg. Evolutionsstrategie. *Optimierung technischer Systeme nach Prinzipien derbiologischen Evolution*, 1973.

Raymond Ros and Nikolaus Hansen. A simple modification in cma-es achieving linear time and space complexity. In *International conference on parallel problem solving from nature*, pp. 296–305. Springer, 2008.

Tim Salimans, Jonathan Ho, Xi Chen, Szymon Sidor, and Ilya Sutskever. Evolution strategies as a scalable alternative to reinforcement learning. *arXiv preprint arXiv:1703.03864*, 2017.

Tom Schaul, Tobias Glasmachers, and Jürgen Schmidhuber. High dimensions and heavy tails for natural evolution strategies. In *Proceedings of the 13th annual conference on Genetic and evolutionary computation*, pp. 845–852, 2011.

Jürgen Schmidhuber. *Evolutionary principles in self-referential learning, or on learning how to learn: the meta-meta-... hook*. PhD thesis, Technische Universität München, 1987.

Jürgen Schmidhuber. A 'self-referential' weight matrix. In *International conference on artificial neural networks*, pp. 446–450. Springer, 1993.

Hans-Paul Schwefel. Evolutionsstrategien für die numerische optimierung. In *Numerische Optimierung von Computer-Modellen mittels der Evolutionsstrategie*, pp. 123–176. Springer, 1977.

Gresa Shala, André Biedenkapp, Noor Awad, Steven Adriaensen, Marius Lindauer, and Frank Hutter. Learning step-size adaptation in cma-es. In *International Conference on Parallel Problem Solving from Nature*, pp. 691–706. Springer, 2020.

Felipe Petroski Such, Vashisht Madhavan, Edoardo Conti, Joel Lehman, Kenneth O Stanley, and Jeff Clune. Deep neuroevolution: Genetic algorithms are a competitive alternative for training deep neural networks for reinforcement learning. *arXiv preprint arXiv:1712.06567*, 2017.

Yujin Tang and David Ha. The sensory neuron as a transformer: Permutation-invariant neural networks for reinforcement learning. *Advances in Neural Information Processing Systems*, 34: 22574–22587, 2021.

Yujin Tang, Yingtao Tian, and David Ha. Evojax: Hardware-accelerated neuroevolution. *arXiv preprint arXiv:2202.05008*, 2022.

Paul Vicol, Luke Metz, and Jascha Sohl-Dickstein. Unbiased gradient estimation in unrolled computation graphs with persistent evolution strategies. In *International Conference on Machine Learning*, pp. 10553–10563. PMLR, 2021.

Johannes Von Oswald, Christian Henning, João Sacramento, and Benjamin F Grewe. Continual learning with hypernetworks. *arXiv preprint arXiv:1906.00695*, 2019.

Jane X Wang, Zeb Kurth-Nelson, Dhruva Tirumala, Hubert Soyer, Joel Z Leibo, Remi Munos, Charles Blundell, Dharshan Kumaran, and Matt Botvinick. Learning to reinforcement learn. *arXiv preprint arXiv:1611.05763*, 2016.

Michael L Waskom. Seaborn: statistical data visualization. *Journal of Open Source Software*, 6 (60):3021, 2021.

Dennis Weyland. A rigorous analysis of the harmony search algorithm: How the research community can be misled by a "novel" methodology. *International Journal of Applied Metaheuristic Computing (IJAMC)*, 1(2):50–60, 2010.

Daan Wierstra, Tom Schaul, Tobias Glasmachers, Yi Sun, Jan Peters, and Jürgen Schmidhuber. Natural evolution strategies. *The Journal of Machine Learning Research*, 15(1):949–980, 2014.

Zhongwen Xu, Hado P van Hasselt, and David Silver. Meta-gradient reinforcement learning. *Advances in neural information processing systems*, 31, 2018.

Zhongwen Xu, Hado P van Hasselt, Matteo Hessel, Junhyuk Oh, Satinder Singh, and David Silver. Meta-gradient reinforcement learning with an objective discovered online. *Advances in Neural Information Processing Systems*, 33:15254–15264, 2020.

Tom Zahavy, Zhongwen Xu, Vivek Veeriah, Matteo Hessel, Junhyuk Oh, Hado P van Hasselt, David Silver, and Satinder Singh. A self-tuning actor-critic algorithm. *Advances in Neural Information Processing Systems*, 33:20913–20924, 2020.

A APPENDIX

A.1 META-TRAINING DETAILS

Function Name	Reference	Property	Meta-Distribution
Sphere	Hansen et al. (p. 5, 2010)	Separable (Independent)	Small
Rosenbrock	Hansen et al. (p. 40, 2010)	Moderate Condition	Medium
Discus	Hansen et al. (p. 55, 2010)	High Condition	Medium
Rastrigin	Hansen et al. (p. 75, 2010)	Multi-Modal (Local)	Medium
Schwefel	Hansen et al. (p. 100, 2010)	Multi-Modal (Global)	Medium
BuecheRastrigin	Hansen et al. (p. 20, 2010)	Separable (Independent)	Large
AttractiveSector	Hansen et al. (p. 30, 2010)	Moderate Condition	Large
Weierstrass	Hansen et al. (p. 80, 2010)	Multi-Modal (Global)	Large
SchaffersF7	Hansen et al. (p. 85, 2010)	Multi-Modal (Global)	Large
GriewankRosenbrock	Hansen et al. (p. 95, 2010)	Multi-Modal (Global)	Large

Table 1: Meta-training black-box optimization tasks with different structural properties.

During meta-training we uniformly sample task parameters ξ_k for $k = 1, ..., K$ different tasks, characterizing the inner fitness $f : \mathbb{R}^D \to \mathbb{R}$, namely the function identifier and the number of dimensions $D \in [2, 10]$. In addition, we sample a constant offset to the optimum $x^\star$ and a noise level $\mathbb{E}_\epsilon[f(x) + \epsilon] = f(x)$ with $\epsilon \sim \mathcal{N}(0, \Xi)$. The initial mean is sampled $\mathbf{m}_0 \in [-5, 5]^D$ in order to ensure solutions that are robust to their starting initialization. We unroll the LES for $T = 50$ generations with $N = 16$ population members/function evaluations each. The meta-objective is computed based on the collected inner loop fitness scores:

$$\left[\left[\left[\{ f(x_{j,t}|\xi_k) \}_{j=1}^N \right]_{t=1}^T \right]_{k=1}^K |\theta_i \right]_{i=1}^M \in \mathbb{R}^{N \times T \times K \times M}.$$

More specifically, for each candidate LES θ_i we minimize over time and population members. Afterwards, we z-score the task-specific results over all population members and compute the mean across all tasks:

$$\left[[f(\theta_i|\xi_k)]_{i=1}^M \right]_{k=1}^K = \min_t \min_j \left[\left[\left[\{ f(x_{j,t}|\xi_k) \}_{j=1}^N \right]_{t=1}^T \right]_{k=1}^K |\theta_i \right]_{i=1}^M$$

$$\{ \tilde{f}(\theta_i) \}_{i=1}^M = \frac{1}{K} \sum_{k=1}^K \left[\text{Z-Score} \left([f(\theta_i|\xi_k)]_{i=1}^M \right) \right]_{k=1}^K.$$

In practice we found that it can be helpful to meta-optimize the median across tasks of the z-scored fitness. Inspired by Shala et al. (2020), the learning rate modulation of $\boldsymbol{\alpha}_m, \boldsymbol{\alpha}_\sigma$ is performed using a small LSTM that outputs two sigmoid activations corresponding to the per-parameter learning rates (mean/std) using a tanh timestamp embedding as in (Metz et al., 2022) and a set of evolution paths, which mimic momentum terms at different timescales:

$$\boldsymbol{\alpha}_{m,t,d}, \boldsymbol{\alpha}_{\sigma,t,d} = \text{LSTM}(\mathbf{p}_{c,t+1,d}, \mathbf{p}_{\sigma,t,d}, \rho(t), \mathbf{h}_{t,d})$$
$$\mathbf{p}_{c,t+1} = (1 - \boldsymbol{\alpha}_{p_c})\mathbf{p}_{c,t} + \boldsymbol{\alpha}_{p_c}(\sum_j w_j(x_j - \mathbf{m}_t) - \mathbf{p}_{c,t}) \in \mathbb{R}^{D \times 3}$$
$$\mathbf{p}_{\sigma,t+1} = (1 - \boldsymbol{\alpha}_{p_\sigma})\mathbf{p}_{\sigma,t} + \boldsymbol{\alpha}_{p_\sigma}(\sum_j w_j(x_j - \mathbf{m}_t)/\boldsymbol{\sigma}_t - \mathbf{p}_{\sigma,t}) \in \mathbb{R}^{D \times 3},$$

with three time-scales $\boldsymbol{\alpha}_{p_c} = \boldsymbol{\alpha}_{p_\sigma} = [0.1, 0.5, 0.9]$ and per-parameter hidden state $\mathbf{h}_{t,d}$.

A.2 METABBO ALGORITHM

Algorithm 1 MetaBBO Training of Learned Evolution Strategies

1: **Inputs:** Meta-population members M, meta-task size K, inner loop population size N, inner loop generations T, `MetaES` (e.g. CMA-ES)
2: Initialize the meta-search mean and covariance μ, Σ.
3: **while** not done **do**
4:     Sample K tasks with parameters ξ_k, $\forall k = 1, ..., K$
5:     Sample LES candidates: $\theta_i \sim \mathcal{N}(\mu, \Sigma)$, $\forall i = 1, ..., M$
6:     Evaluate all M LES candidates (in parallel) on K tasks:
7:     **for** $k = 1, ..., K$ **do**
8:         **for** $i = 1, ..., M$ **do**
9:             Initialize inner loop search means/std $\mathbf{m}_{0,k,i} \in \mathbb{R}^{D_k}, \boldsymbol{\sigma}_{0,k,i} \in \mathbb{R}^{D_k}$
10:             **for** $t = 0, ..., T - 1$ **do**
11:                 Sample inner loop candidates: $x_{j,t} \sim \mathcal{N}(\mathbf{m}_{t,k,i}, \boldsymbol{\sigma}_{t,k,i}\mathbf{1}_{D_k})$, $\forall i = 1, ..., N$
12:                 Evaluate all inner loop candidates: $f(x_{j,t}|\xi_k)$, $\forall i = 1, ..., N$
13:                 Update LES mean/std using equation (2) and (3) $\rightarrow \mathbf{m}_{t+1,k,i}, \boldsymbol{\sigma}_{t+1,k,i}$ with θ_i
14:             **end for**
15:         **end for**
16:     **end for**
17:     Collect all inner loop fitness scores $\left[\left[\left[\{f(x_{j,t}|\xi_k)\}_{j=1}^N\right]_{t=1}^T\right]_{k=1}^K |\theta_i\right]_{i=1}^M \in \mathbb{R}^{N \times T \times K \times M}$
18:     Compute the population normalized and task aggregated meta-fitness scores $\{\tilde{f}(\theta_i)\}_{i=1}^M$
19:     Update meta-mean, meta-std $\mu', \Sigma' \leftarrow$ `MetaES`$(\{\theta_i, \tilde{f}\}_{i=1}^M |\mu, \Sigma)$
20: **end while**

A.3 DISCOVERED EVOLUTION STRATEGY

Algorithm 2 Discovered Evolution Strategy (DES)

1: **Inputs:** Population members N, search dimensions D, generations T, Initial scale $\boldsymbol{\sigma}_0 \in \mathbb{R}^D$, Mean and std learning rates $\alpha_m = 1, \alpha_\sigma = 0.1$, temperature parameter $\beta \approx 16$.
2: Initialize the search mean $\mathbf{m}_0 = \mathbf{0}_D \in \mathbb{R}^D$
3: **for** $t = 0, ..., T - 1$ **do**
4:     Sample candidates: $x_j \sim \mathcal{N}(\mathbf{m}_t, \sigma_t\mathbf{1}_D)$
5:     Evaluate all candidates: f_j, $\forall j = 1, ..., N$
6:     Compute weights using: $\boldsymbol{w}_{t,j} = \text{softmax}\left(\beta \times (\text{rank}(j)/N - 0.5)\right)$, $\forall j = 1, ..., N$
7:     Update mean using equation (2) $\rightarrow \mathbf{m}_{t+1}$
8:     Update std using equation (3) $\rightarrow \boldsymbol{\sigma}_{t+1}$
9: **end for**

A.4 HYPERPARAMETER SETTINGS

MetaBBO Hyperparameters for LES Discovery			
Hyperparameter	Value	Hyperparameter	Value
Meta-Generations	1500	Meta-Population	256
Meta-Tasks	128	Meta-ES	CMA-ES
CMA-ES σ_0	0.1	Inner-Population	16
Inner-Generations	50	m_0 range	[-5, 5]
		σ_0 range	[1, 1]
D_k Attention keys	8	LSTM Hidden dim.	4

Brax Task Evaluation Hyperparameters			
Hyperparameter	Value	Hyperparameter	Value
Generations	2000	Population	256
MC Evaluations	16	MLP Layers	4
Hidden Units	32	Activation	Tanh

MNIST Task Evaluation Hyperparameters			
Hyperparameter	Value	Hyperparameter	Value
Generations	4000	Population	128
MC Evaluations	1	CNN Layers	1
Batchsize	1024	Activation	ReLU

We tuned all baselines and LES by running a grid search over $\sigma_0 \in [0.05, 0.2]$ for all environments. Furthermore, we previously calibrated the learning rate of all baselines on the Brax ant environment. Note that LES only has a single hyperparameter σ_0 and is fairly robust (see SI A.6.4). The Brax experiments all used observation normalization.

A.5 SOFTWARE

This project has been made possible by the usage of freely available Open Source software. This includes the following:

- NumPy: Harris et al. (2020)
- Matplotlib: Hunter (2007)
- Seaborn: Waskom (2021)
- JAX: Bradbury et al. (2018)
- Evosax: Lange (2022a)
- Gymnax: Lange (2022b)
- Evojax: Tang et al. (2022)

A.6 ADDITIONAL RESULTS

A.6.1 META-EVOLUTION TRAINING CURVES

Figure 7: Comparing different meta-evolution training distributions and input ablations to LES. Results are averaged over 5 independent runs (+/- 1.96 standard errors).

Figure 8: Comparing different meta-evolution optimizers and training setups (MetaBBO & self-referential MetaBBO). Results are averaged over 5 independent runs (+/- 1.96 standard errors).

A.6.2 IMPACT OF META-TASK DISTRIBUTION ON BRAX PERFORMANCE

Figure 9: Impact of Meta-Task Distribution on Brax Performance. Results are averaged over 5 independent runs (+/- 1.96 standard errors).

A.6.3 DETAILED ABLATION PERFORMANCE ON BRAX TASKS

Figure 10: Brax LES Neural Network Components Ablation Study. Results are averaged over 5 independent runs (+/- 1.96 standard errors).

Figure 11: Brax Performance Comparison $\sqrt{N}$ vs $\sqrt{D_K}$ Self-Attention. Results are averaged over 5 independent runs (+/- 1.96 standard errors).

A.6.4 SCALE ROBUSTNESS OF LES

Figure 12: Robustness to initial scale of standard deviations σ_0. Results are averaged over 5 independent runs (+/- 1.96 standard errors).

Figure 13: Best initial scale of standard deviations across population sizes. Results are averaged over 5 independent runs (+/- 1.96 standard errors).

A.6.5 DETAILED NEUROEVOLUTION LEARNING CURVES

Figure 14: Detailed Brax Learning Curves. PPO scores were taken from Lu et al. (2022) using default settings provided by the Brax implementation (Freeman et al., 2021). Results are averaged over 5 independent runs (+/- 1.96 standard errors).

Figure 15: Detailed Learning Curves on MNIST variants. Results are averaged over 5 independent runs (+/- 1.96 standard errors).

Under review as a conference paper at ICLR 2023

Figure 16: Detailed Brax Learning Curves with DES(β) variants. Results are averaged over 5 independent runs (+/- 1.96 standard errors).

Figure 17: Detailed Brax Learning Curves with Self-Referentially Meta-Trained LES. Results are averaged over 5 independent runs (+/- 1.96 standard errors).