Deconfounded Representation Similarity for Comparison of Neural Networks

Abstract

Similarity metrics such as representational similarity analysis (RSA) and centered kernel alignment (CKA) have been used to understand neural networks by comparing their layer-wise representations. However, these metrics are confounded by the population structure of data items in the input space, leading to inconsistent conclusions about the *functional* similarity between neural networks, such as spuriously high similarity of completely random neural networks and inconsistent domain relations in transfer learning. We introduce a simple and generally applicable fix to adjust for the confounder with covariate adjustment regression, which improves the ability of CKA and RSA to reveal functional similarity and also retains the intuitive invariance properties of the original similarity measures. We show that deconfounding the similarity metrics increases the resolution of detecting functionally similar neural networks across domains. Moreover, in real-world applications, deconfounding improves the consistency between CKA and domain similarity in transfer learning, and increases correlation between CKA and model out-of-distribution accuracy similarity.

1 Introduction

Deep neural networks (NNs) have achieved state-of-the-art performance on a wide range of machine learning tasks by automatically learning feature representations from data [1, 2, 3, 4, 5]. However, these networks do not offer interpretable predictions on most applications and are seen as "black boxes". It is thus crucial to understand the intricacies of neural networks before they are deployed on critical applications. Previous work has made progress in understanding how a single neural network makes decisions with axiomatic attribution methods [6, 7] and understanding how multiple neural networks relate to each other with representation similarity measures [8]. Several similarity measures between representations have been proposed with different principles, including linear regression [9], canonical correlation analysis (CCA; [10, 11]), statistical shape analysis [12], and functional behaviors on down-stream tasks [13, 14, 15]. Another main-stream approach is based on representational similarity analysis (RSA, [8, 16, 17, 18]) and centered kernel alignment (CKA, [19]), which compute the similarity between (dis)similarity matrices of two neural network representations on the same dataset.

RSA and CKA have been successfully applied to understand biological [20] and artificial NNs [21] by studying the similarity of *representations* of different NNs in a *single* data domain. However, we find that the inter-example (dis)similarity matrices in the representation space of different NNs are highly correlated with a shared factor (i.e., a confounder): the (dis)similarity structure of the data items in the input space, especially for shallow layers. This confounding issue limits the ability of CKA to reveal similarity of models on the *functional* level [15], and can result in a spuriously high CKA even between two random NNs. Moreover, this can lead to counter-intuitive conclusions when using CKA

Figure 1: **Demonstration of the confounder in CKA.** CKA calculates the similarity between inter-example similarities for two representations, which are confounded by the inter-example similarities in the input space, such that input pairs with high (★) and low (★) input similarities also have high and low representation similarities on both random NNs (*Left*) and trained NNs (*Right*) representations. Moreover, the confounder leads to the counterintuitive conclusion that CKA on random NNs is higher than pretrained and finetuned NNs on similar domains (0.99 vs. 0.95). This is resolved by deconfounding (0.43 vs. 0.72).

to compare models trained in *multiple* domains and/or to deduce *functional* similarities of NNs, such as in understanding transfer learning, multitask learning, and meta learning [22, 23, 24, 25, 26].

In this paper, we propose to adjust the representation similarity to improve its consistency w.r.t. the functional similarity by regressing out the confounder, the inter-example (dis)similarity matrix in the input space, from the (dis)similarity matrices of two representations, inspired by the covariate adjusted correlation analysis widely studied in biostatistics [27, 28]. This approach is simple and widely applicable on any similarity measure built on the CKA and RSA framework. Moreover, we study the invariance properties of the deconfounded representation similarity and demonstrate its benefits on public image and natural language datasets with various NN architectures.

Overall, our contributions are:

- We study the confounding effect of the input inter-example similarity on the representation similarity between two NNs, which limits CKA and RSA from revealing consistent *functional* similarities. We propose a simple and generally applicable deconfounding fix and discuss the invariance properties of the deconfounded similarities.
- We verify that deconfounded similarities can detect functionally similar NNs from random NNs, and small NN changes across domains where previous similarity measures fail.
- We show that deconfounded similarities are more consistent with domain similarities in transfer learning, on both image and language datasets, compared with existing methods.
- We demonstrate that deconfounded similarities on in-distribution datasets are more correlated with out-of-distribution accuracy than the corresponding original similarities [15].

2 Preliminaries

2.1 Notation and prior work

Let $X \in \mathbb{R}^{n \times p}$ denote the input dataset with n datapoints and p features, and $X_{f_1}^{m_1} \in \mathbb{R}^{n \times p_1}$ and $X_{f_2}^{m_2} \in \mathbb{R}^{n \times p_2}$ denote the m_1th and m_2th layer representations of two NNs of interest, $f_1(X)$ and $f_2(X)$, with p_1 and p_2 nodes respectively. We center and normalize the representation matrices by first removing the mean of each feature (i.e., each column), and then dividing by the Frobenius norm.

A standard approach for comparing representations of two NNs is to compare the similarity structures in each network representation. This can be done by first computing the similarity between every pair of examples in $X_{f_1}^{m_1}$ and $X_{f_2}^{m_2}$ with a similarity measure $k(\cdot, \cdot)$:

$$K_{f_1}^{m_1} = k(X_{f_1}^{m_1}, X_{f_1}^{m_1}), \ K_{f_2}^{m_2} = k(X_{f_2}^{m_2}, X_{f_2}^{m_2}). \tag{1}$$

66 Here $K_{f_1}^{m_1}, K_{f_2}^{m_2} \in \mathbb{R}^{n \times n}$ are called representational similarity matrices (RSMs)[1]. Second, another
67 similarity measure $s(\cdot, \cdot)$ is applied to compare these two similarity structures, $K_{f_1}^{m_1}$ and $K_{f_2}^{m_2}$:

$$s_{f_1,f_2}^{m_1,m_2} = s(K_{f_1}^{m_1}, K_{f_2}^{m_2}). \tag{2}$$

68 This gives the similarity between the two representations.

69 The existing approaches vary by using different similarity measures for both levels of comparison.
70 CKA [19] employs a kernel function for the first level similarity $k(\cdot, \cdot)$, and a Hilbert-Schmidt
71 Independence Criterion (HSIC) estimator for the second, $s(\cdot, \cdot)$. On the other hand, RSA-based
72 methods use Euclidean distance to measure the inter-example **dis**similarity structure, and apply
73 Pearson's correlation [8] or Spearman's rank correlation [18] to quantify the similarity between two
74 dissimilarity structures. Although other approaches, e.g., linear regression [29] and CCA [10], have
75 been proposed to compare NN representations, we focus on CKA and RSA in this paper due to their
76 wide usage in understanding the properties of NNs, such as transfer learning [22, 23, 30].

2.2 Illustration of the confounding in representation similarity

78 Given a dataset X with an inter-example similarity matrix $K^0 = k(X, X)$ in the input space, making
79 predictions with NNs can be seen as modifying K^0 layer-by-layer, such that similarities between data
80 items with different labels decrease and those with the same label increase. In CKA and RSA, the
81 similarity between two RSMs, $K_{f_1}^{m_1}$ and $K_{f_2}^{m_2}$, defines the similarity between two NNs, as shown in
82 Eq.2. However, both $K_{f_1}^{m_1}$ and $K_{f_2}^{m_2}$ are affected by the same factor (i.e., a confounder): the similarity
83 structure of input dataset K^0, which can cause spuriously high similarity. Intuitively, (dis)similar
84 data points (green stars and red stars in Figure 1) in the input space are likely to be (dis)similar in the
85 representation space of the first few layers, regardless of how the NN operates, and the representation
86 similarity structure of different NNs would be similar even for random NNs that have totally different
87 functional behaviors. Hence, CKA/RSA naturally depends on the specifics of the dataset, and for
88 different datasets (e.g., from different domains) with different K^0, comparing CKA/RSA across the
89 datasets may lead to inconsistent comparison results. This is undesirable especially when the goal
90 of calculating the similarity measures for NNs is to quantify how similar the networks are in the
91 functional level, which should not be affected by the specifics of the dataset at hand.

92 We fix this by regressing out the input similarity K^0 from $K_{f_1}^m$ and $K_{f_2}^m$, i.e., deconfounding. After
93 deconfounding, if two data items are very similar in the NN latent space, it is because the NN made
94 them so and not because they were similar in the first place. In this way, the deconfounded metric
95 more directly focuses the comparison on the functional form of the NNs and is less affected by the
96 structure of the given dataset in the input space.

97 Figure 1 illustrates the spurious similarity using the CKA similarity measure as an example, and
98 compares that with the deconfounded dCKA (defined in the next section) on the first-layer of ResNets
99 [31] with 20 random samples from CIFAR-10 [32] test set. We consider two pairs of ResNets: 1.
100 two random ResNets generated by adding different Gaussian noise, $\mathcal{N}(0, 1)$, to each parameter of
101 the pretrained ResNet-18[2] on ImageNet [33]; 2. the pretrained (PT) ResNet-18 and a finetuned (FT)
102 ResNet-18 on CIFAR-10. We notice that CKA on random NNs is almost 1, and counterintuitively
103 it is even higher than the CKA between PT and FT ResNets on a similar domain (0.99 vs. 0.95),
104 although we would expect the PT and FT networks to learn similar low-level features and hence be
105 more similar than random networks. This happens because the similarities between samples in the
106 input space confound their similarities in the representation space. After adjusting for the confounder
107 with dCKA, the similarity between the two random ResNets is much smaller than the similarity of
108 the PT and FT networks (0.43 vs. 0.72).

3 Methods

110 In this section, we first propose a general fix on the NNs similarities (defined in Eq.1-2) by regressing
111 out the confounder, i.e., the input similarity, in Section 3.1, and we give two examples of deconfounded
112 similarities: deconfounded CKA and deconfounded RSA in Section 3.2. We then study the invariance
113 properties of deconfounded similarities in Section 3.3.

---

[1]Note that $k(\cdot, \cdot)$ can also be dissimilarity measure, but we call K_f^m a similarity matrix for simplicity.
[2]https://pytorch.org/vision/stable/models.html

3.1 Deconfounding representation similarity

We propose a simple approach to adjust the spurious similarity caused by the confounder by regressing out the input similarity structure from the representation similarity structure [34]. That is:

$$dK_{f_1}^{m_1} = K_{f_1}^{m_1} - \hat{\alpha}_{f_1}^{m_1} K^0, \ dK_{f_2}^{m_2} = K_{f_2}^{m_2} - \hat{\alpha}_{f_2}^{m_2} K^0, \tag{3}$$

where K^0 is the input similarity structure, and $\hat{\alpha}_{f_1}^{m_1}$ and $\hat{\alpha}_{f_2}^{m_2}$ are the regression coefficients that minimize the Frobenius norm of $dK_{f_1}^{m_1}$ and $dK_{f_2}^{m_2}$ respectively. Furthermore, the letter d in front of a similarity matrix, e.g. as in $dK_{f_1}^{m_1}$, denotes the deconfounded version of $K_{f_1}^{m_1}$, and similarly the letter d is applied throughout the text to denote all defounded quantities. To do the deconfounding, we assume that the input similarity structure K^0 has a linear and additive effect on K_f^m, i.e.,

$$\text{vec}(K_f^m) = (\alpha_f^m)^T \text{vec}(K^0) + \epsilon_f^m, \tag{4}$$

where $\text{vec}(\cdot)$ flattens a matrix to a vector. Noise ϵ_f^m is assumed to be independent from the confounder with $\hat{\epsilon}_f^m = \text{vec}(dK_f^m)$, and

$$\hat{\alpha}_f^m = (\text{vec}(K^0)^T \text{vec}(K^0))^{-1} \text{vec}(K^0)^T \text{vec}(K_f^m). \tag{5}$$

In Appendix A, we further verify that the linearity assumption in Eq.4 holds in general, i.e., adding additional nonlinear terms of $\text{vec}(K^0)$ to Eq.4 does not improve the fit, and the noise term ϵ_f^m is not auto-correlated (solution Eq.5 is not misspecified) under the the Durbin-Watson test [35].

After the deconfounded similarity structures are obtained with Eq.3, we use the same similarity measure to calculate the deconfounded representation similarity:

$$ds_{f_1, f_2}^{m_1, m_2} = s(dK_{f_1}^{m_1}, dK_{f_2}^{m_2}). \tag{6}$$

Note that dK_f^m is not always positive semi-definite, even when K_f^m is positive semi-definite (PSD). For a similarity measure $s(\cdot, \cdot)$ that takes two kernel matrices as input, such as the CKA, we transform dK_f^m into a positive semi-definite matrix by removing all the negative eigenvalues according to [36]. Specifically, we have the eigenvalue decomposition of dK_f^m, such that

$$dK_f^m = Q\Lambda Q^T = Q(\Lambda_+ - \Lambda_-)Q^T, \ \Lambda_\pm = \text{diag}\{\max(0, \pm\lambda_1), \ldots, \max(0, \pm\lambda_n)\}, \tag{7}$$

where λ_i is the ith eigenvalue of dK_f^m. We approximate dK_f^m with a PSD matrix $d\tilde{K}_f^m$:

$$dK_f^m \approx d\tilde{K}_f^m = \rho^2 Q\Lambda_+ Q^T; \ \ \rho = |\text{tr}(\Lambda)/\text{tr}(\Lambda_+)|. \tag{8}$$

3.2 Examples of deconfounded similarity indices

Deconfounded CKA. In CKA [19], the similarity structure in the feature space is represented with a valid kernel $l(\cdot, \cdot)$, i.e., $K_{f_1}^{m_1} = l(X_{f_1}^{m_1}, X_{f_1}^{m_1})$ and $K_{f_2}^{m_2} = l(X_{f_2}^{m_2}, X_{f_2}^{m_2})$, such as the linear or RBF kernel. Then an empirical estimator of HSIC [37] is used to align two kernels:

$$\text{HSIC}_{f_1, f_2}^{m_1, m_2} = \frac{1}{(n-1)^2} \text{tr}(K_{f_1}^{m_1} H K_{f_2}^{m_2} H), \tag{9}$$

where H is the centering matrix. CKA is given by the normalized HSIC such that

$$\text{CKA}(K_{f_1}^{m_1}, K_{f_2}^{m_2}) = \text{HSIC}_{f_1, f_2}^{m_1, m_2} \Big/ \sqrt{\text{HSIC}_{f_1, f_1}^{m_1, m_1} \text{HSIC}_{f_2, f_2}^{m_2, m_2}}. \tag{10}$$

To deconfound the representation similarity matrices $K_{f_1}^{m_1}$ and $K_{f_2}^{m_2}$, we apply the same kernel to measure the inter-example similarity in the input space $K^0 = l(X, X)$, and adjust its confounding effect with Eq.3. However, matrices $dK_{f_1}^{m_1}$ and $dK_{f_2}^{m_2}$, obtained by regressing out one kernel matrix from another kernel, are no longer kernels, and they are not applicable for computing HSIC. Fortunately, with Eq.8, we can approximate the $dK_{f_1}^{m_1}$ and $dK_{f_2}^{m_2}$ with two valid kernels $d\tilde{K}_{f_1}^{m_1}$ and $d\tilde{K}_{f_2}^{m_2}$, which are then used to construct the deconfounded CKA (dCKA):

$$\text{dCKA}(K_{f_1}^{m_1}, K_{f_2}^{m_2}) = \text{CKA}(d\tilde{K}_{f_1}^{m_1}, d\tilde{K}_{f_2}^{m_2}). \tag{11}$$

145 We use linear kernels here because Kornblith et al. [19] report similar results with RBF kernels.

146 **Deconfounded RSA.** Different from CKA, the similarity structure in RSA [8] is measured by the
147 pairwise Euclidean distance between examples in the feature space. Specifically, each element of
148 $K_{f_1}^{m_1}$ and $K_{f_2}^{m_2}$ is obtained by $K_{f_1,ij}^{m_1} = \|\boldsymbol{x}_{f_1,i}^{m_1} - \boldsymbol{x}_{f_1,j}^{m_1}\|^2$ and $K_{f_2,ij}^{m_2} = \|\boldsymbol{x}_{f_2,i}^{m_2} - \boldsymbol{x}_{f_2,j}^{m_2}\|^2$, where
149 $\boldsymbol{x}_{f_1,i}^{m_1}$ is the m_1-layer representation of the ith example in NN f_1. Thus, the input similarity structure
150 K^0 is measured with the pairwise Euclidean distance in the input space. After K^0 is adjusted with
151 Eq.3, we apply Spearman's ρ correlation to measure the similarity between the upper triangular part
152 of $dK_{f_1}^{m_1}$ and $dK_{f_2}^{m_2}$, i.e., $\mathrm{triu}(dK_{f_1}^{m_1})$ and $\mathrm{triu}(dK_{f_2}^{m_2})$, that is

$$\mathrm{dRSA}(K_{f_1}^{m_1}, K_{f_2}^{m_2}) = \rho(\mathrm{triu}(dK_{f_1}^{m_1}), \mathrm{triu}(dK_{f_2}^{m_2})). \tag{12}$$

153 Note that rank correlation does not require two similarity matrices to be positive semi-definite.
154 Therefore, we skip the steps of constructing the PSD approximation.

155 **Additional computational complexity.** The computational cost of the deconfounding (Eq.3) and
156 PSD approximation (Eq.8) steps are $O(n^2)$ and $O(n^3)$ respectively. Therefore, dCKA has the same
157 complexity as CKA: $O(n^3)$. For RSA, only the deconfounding step with $O(n^2)$ complexity is needed.
158 In experiments, computing dCKA between two XLM-RoBERTa models [38] takes 0.37 ± 0.11s
159 longer than CKA for each layer on 3000 random English sentences with a single 2080Ti GPU.

3.3 Theoretical properties

161 In this section, we study the invariance properties of the deconfounded representation similarity. For
162 similarity measures that we studied, i.e., CKA and RSA, the corresponding deconfounded similarity
163 indices have the same invariance properties, such as invariance to orthogonal transformation and
164 isotropic scaling, as the original similarity measures.

165 **Proposition 3.1.** *Deconfounded CKA and deconfounded RSA are invariant to orthogonal transfor-*
166 *mation, if the (dis)similarity measure $k(\cdot, \cdot)$ that compare inter-examples are orthogonal invariant.*

167 **Proposition 3.2.** *Deconfounded CKA with a linear kernel and deconfounded RSA are invariant to*
168 *isotropic scaling.*

169 Intuitively, as long as $k(\cdot, \cdot)$ is invariant to orthogonal transformation, e.g., linear kernels and Eu-
170 clidean distance, the deconfounded representation similarity matrix dK_f^m in Eq.3 is also invariant
171 to orthogonal transformation, because it is defined in terms of the kernel k. Thus all operations on
172 dK_f^m are invariant to orthogonal transformation. Moreover, if one representation is scaled by a scalar,
173 dK_f^m and $d\tilde{K}_f^m$ will be scaled by the same scalar, whose effects will be finally eliminated in the
174 normalization step in CKA (Eq.10) and the rank correlation step in RSA (Eq.12). We give proofs in
175 Appendix B.

4 Experiments

177 In this section, we design experiments to verify that deconfounding can improve the consistency of
178 CKA and RSA with the functional similarity of NNs from various perspectives. First, in Section
179 4.1, we check if these representation similarity measures can separate functionally similar NN pairs
180 from random NN pairs. In Section 4.2 we study how consistent the similarity measures are with
181 small changes of NNs across different domains. We then extend a recent framework [15], which uses
182 rank correlation to compare the representation similarity and the functional similarity of NNs, to
183 transfer learning on multi-domain image and natural language datasets (Section 4.3), and to conduct
184 challenging out-of-distribution generalization tests [15] (Section 4.4).

4.1 Ability of detecting functionally similar NN pairs from random NN pairs

186 **Setup:** We check if similarity measures can identify *functionally* similar NN representations from
187 random NN representations. For each model block of ResNets (containing 2-3 convolutional layers),
188 we generate two distributions of similarities: the null distribution $\mathcal{H}_0$ and the alternative distribution
189 $\mathcal{H}_1$. The $\mathcal{H}_0$ contains similarities between 50 pairs of random ResNets on CIFAR-10 test set. We
190 generate random NNs by randomly initializing the weight of an untrained ResNet-18 from $\mathcal{N}(0, 10)$

Figure 2: *Left*: **Proportion of ImageNet-CIFAR ResNets pairs identified from random ResNets for each block**. The proportions for the last four blocks are omitted as they are 0 for all metrics. The average proportions across layers are shown next to the method's name in the legend. We observe that deconfounding improves the identification of functionally similar NNs from random NNs. *Right*: **Histograms of similarities in the first block**. Compared with CKA and RSA, dCKA and dRSA increase separation of ImageNet-CIFAR pairs from the random network pairs, even when the proportion of identified network pairs with CKA and dCKA is the same.

with different random seeds. We also consider permuting the weight matrix of the pretrained ResNet-18 to generate random NNs, which preserves parameter distributions, in Appendix D.1. Distribution $\mathcal{H}_1$ contains similarities between the pretrained ImageNet NN and each of the 50 ResNets trained on CIFAR-10 from scratch with different random initializations, on the same CIFAR-10 test as $\mathcal{H}_0$.

Results: We expect the similarities in $\mathcal{H}_1$ to be significantly larger than those in $\mathcal{H}_0$. Intuitively, models trained on ImageNet and CIFAR-10 are *functionally* similar in shallow blocks because their domains are similar; hence similar low-level features are expected [39], while sufficiently randomized untrained NNs are functionally different. We compute the proportion (shown in Figure 2 *Left*) of 50 ImageNet-CIFAR NN pairs in $\mathcal{H}_1$ whose similarity is significantly larger than $\mathcal{H}_0$, i.e., larger than the upper bound of its 95% CI. In Figure 2 *Left*, we observe that in shallow blocks the deconfounded similarity can detect a larger proportion of ImageNet-CIFAR pairs from random NN pairs than the original measures. For example, in the third and fourth block, dCKA can still detect all functionally similar pairs whereas the original CKA fails to detect any from random pairs. By averaging proportions of all blocks, deconfounding increases CKA from 0.24 to 0.5 and RSA from 0.02 to 0.25. In Figure 2 *Right*, we visualize the alternative distribution $\mathcal{H}_1$ and the null distributions $\mathcal{H}_0$ of each similarity measure as histograms in the first block. We observe that although CKA and dCKA can identify the same proportion of ImageNet-CIFAR pairs in block 1, the difference between $\mathcal{H}_1$ and $\mathcal{H}_0$ is more significant with the deconfounded similarities. Moreover, in deep layers, e.g., after block 4, no method can identify ImageNet-CIFAR pairs. We hypothesise that ImageNet and CIFAR-10 contain different classes of images, thus their high-level representations are significantly different. We discuss this more in Appendix D.

4.2 Consistency of NN functional similarities across domains

Setup: Ideally, a functional similarity between NNs would not depend on the domain in which the networks are applied. Here, we study this by constructing a set of 6 NNs, $\{f_i | i \in \{1, 2, 3, 4, 5, 6\}\}$, by adding independent Gaussian noise $i \times \mathcal{N}(0, 0.1)$ to each parameter of the pretrained ResNet-18, f^*. Hence, the similarity $s(f_i, f^*)$ should be higher than $s(f_{i+1}, f^*)$ regardless of the input domain in which the the networks are applied to calculate representations. Thus, we calculate the similarity $s(f_i, f^*)$ for every f_i on each domain of the corrupted CIFAR-10-C dataset [40] that contains 19 domains with different types of corruptions to the original CIFAR-10. We compute the average similarity μ_{f_i, f^*} across the 19 domains and its standard error σ_{f_i, f^*}. We say f_i is significantly more similar to f^* than to f_{i+1} across domains, if

$$\mu_{f_i, f^*} - 1.96\sigma_{f_i, f^*} > \mu_{f_{i+1}, f^*} + 1.96\sigma_{f_{i+1}, f^*}. \tag{13}$$

We repeat the above experiments 20 times with different random seeds, i.e., generate 20 different sets of NNs, to measure the proportion of cases where f_i is significantly more similar to f^* than f_{i+1} for each block, as well as the confidence interval of the proportion.

Results: In Figure 3(A) *Left*, we show the proportion of identified NNs averaged over all blocks for each noise level. We observe that the deconfounded similarity improves the proportion of identified NNs compared with the corresponding original similarity for all noise levels. The averaged proportion increases 59.7% for CKA (from 0.18 to 0.29) and 43.1% for RSA (from 0.16 to 0.23)

Figure 3: **(A): Proportion of identified similar NNs across 19 domains summarized for different noise levels (*Left*) and different NN blocks (*Right*).** We observe that the deconfounded similarity can identify more similar models compared with the corresponding original similarity. **(B): histograms and kernel density estimations (KDE) of CKA and dCKA across 19 domains on the first-block representations**. We observe that dCKA can separate $s(f_2, f^*)$ from $s(f_3, f^*)$ better than CKA with relative histogram overlap 13.5% and 28.9% respectively.

after deconfounding. We also observe that deconfounding can improve CKA/RSA on different inputs from the *same* domain, but the improvement is relatively smaller (23% for CKA, from 0.65 to 0.8, and 7% for RSA, from 0.75 to 0.8), shown in Appendix E. Moreover, the proportion decreases as the noise level increases for all similarity measures, because for large noise level (large i), both f_{i+1} and f_i are far from f^*. In Figure 3(A) *Right*, we show the the proportion of consistently identified similarities for each block where the results are averaged over different noise levels. In general, we expect to identify fewer similar NNs with deeper layer representations, because the Gaussian noise is added to each parameter and deeper representations consequently accumulate more noise than shallow layers. We visualize the histogram of CKA and dCKA between f_2 and f^* and between f_3 and f^* on the first-block representations of inputs from 19 domains in Figure 3(B), where we can clearly observe that f_2 and f_3 are more separable in terms of dCKA than CKA. Moreover, the relative overlap areas between two histograms are 13.5% and 28.9% for dCKA and CKA respectively.

4.3 Transfer learning: domain similarity vs. the similarity of pretrained and finetuned NNs

Motivation: Ding et al. [15] argued that the similarity metric must be sensitive to changes that affect the *functionality* of the networks we compare, and we extend this to transfer learning under domain shift. Consider two models with the same initialization from a pretrained (PT) model which are finetuned (FT) on data from different domains. We then expect the similarity of the layer representations between the finetuned and pretrained models to be different for each target domain, and ideally it should be correlated with the similarity between the source and target domains.

Setup: To study this in detail for dCKA and CKA, we choose datasets from two modalities – image and text – that display such domain shift. For text, we use the Multi-lingual STS-B dataset [41] and choose English, Spanish, Polish, and Russian languages as the target domains. For images, we use the Real, Clipart, Sketch, and Quickdraw as target domains from the DomainNet dataset [42].

First, we finetune separate models for each domain from both modalities. For text, we initialize a PT XLM-RoBERTa [38] model and for images, we pretrain a ResNet-50 model on ImageNet [33]. We compute the layer-wise CKA and dCKA between each FT model and the corresponding PT model on the test set of the target domain [22]. We repeat the above procedure 10 times to construct error bars. Then, we quantify the similarity between two domains according to [43]. Specifically, we build a cross-domain classifier and create a dataset using an equal number of samples from each domain. Next, we train a weak discriminator to predict the appropriate true domain for each sample. For the discriminator, we use EfficientNet-B0 [44] for images and Distil-RoBERTa [45] for text. The discriminator is essentially a binary classifier and thus the test binary cross entropy (BCE) loss would be an indicator of the similarity between the two domains (higher meaning more similar). Finally, we measure the Spearman's ρ and Kendall's τ correlation [15] between the domain similarity (measured by the BCE loss of cross-domain classifier) and the layer-wise CKA and dCKA between PT and FT models of each domain. We average the rank correlations over all layers.

Results: Table 1 summarizes the averaged rank correlations of CKA and dCKA for each modality. We can see that the dCKA is more correlated with the domain similarity as compared to CKA on both modalities. Figure 4 *Left* shows the results for the test BCE loss when the cross-domain classifier was trained to discriminate between the domains on STS-B: English-English, English-Spanish, English-

Table 1: **Rank correlation with standard error (in parentheses) between the domain similarity and the CKA between pretrained and finetuned models**. We see that compared to CKA, the dCKA has higher correlation with domain similarity in terms of Spearman's ρ and Kendall's τ.

Modality	CKA		dCKA	
	ρ	τ	ρ	τ
DomainNet	0.675 (0.020)	0.626 (0.018)	**0.751 (0.020)**	**0.718 (0.018)**
Multi STS-B	-0.231 (0.018)	-0.185 (0.016)	**0.717 (0.014)**	**0.641 (0.013)**

Figure 4: **dCKA adjusts for transfer learning under domain shift.** *Left* shows the ground truth domain similarity (between English and other languages) as measured by test binary cross entropy (BCE) loss of the cross-domain classifier. We plot the CKA (*Center*) and dCKA (*Right*) between the pretrained XLM-RoBERTa model and models finetuned for different languages on the STS-B task. The average similarities across layers are shown next to the languages in the legend. We observe that dCKA is better correlated with the domain similarity than CKA.

Polish, and English-Russian, and we see that the similarity of two English domains is higher than the similarity of English and Russian domains, as expected. The layer-wise CKA and dCKA between the pretrained and finetuned XLM-RoBERTa model is shown Figure 4 (*Center* and *Right*), respectively. The models finetuned on highly dissimilar domains (e.g., English-Russian) are expected to have lower layer-wise similarity with the pretrained model. However, the CKA gives counter-intuitively high similarities between PT and FT for English-Russian, and negative rank correlations in Table 1. This is not because FT is close to PT, but because the Russian FT dataset is used to calculate the CKA, which causes the representations of PT and FT to be similar on that dataset. As expected, dCKA (Figure 4 *Right*) captures the domain similarity precisely by removing the input structure. We provide results on DomainNet in Appendix F.

4.4 Model generalization: in-distribution similarity vs. out-of-distribution accuracy

Setup: Here we use a challenge task used in previous work [15], which evaluates the sensitiveness of similarities to changes that affect the NNs generalizations on out-of-distribution (OOD) data, and we would expect similar NNs to have similar OOD accuracy. We follow the same setup as [15]: 1. We train 50 ResNet-18, f_i, with different random initialization on CIFAR-10; 2. Evaluate the OOD accuracy of each model on CIFAR-10-C [40], $\text{acc}(f_i)$, and select the most accurate ResNet as the reference model, f^*; 3. Compute the similarity between each f_i and f^*, $s(f_i, f^*)$, of each block on CIFAR-10 test set (in-distribution similarity), and compute the accuracy difference on CIFAR-10-C test set $|\text{acc}(f_i) - \text{acc}(f^*)|$ (OOD accuracy similarity); 4. Measure the Kendall's τ and Spearman's ρ between $1 - s(f_i, f^*)$ and $|\text{acc}(f_i) - \text{acc}(f^*)|$ for each block. A good similarity should have a high rank correlation, meaning that the similarity in the input space correlates with OOD accuracy.

Results: CIFAR-10-C dataset contains 19 different corruptions and 5 levels for each corruption. We average rank correlations over all blocks of ResNet-18 as [15] because the ranking between similarity measures were shown to be consistent across different layers/blocks. We report the averaged rank correlation over all types of corruptions in Table 2. We observe that dCKA is more correlated with OOD accuracy on all 5 levels of corruption, especially on levels 3-5, compared with CKA. Moreover, we also notice marginal improvements of dCKA in terms of in distribution accuracy (ID accuracy). Figure 5(A) shows the improvement of dCKA vs. CKA for each corruption averaged over 5 corruption levels, and we see that deconfounded CKA improves the most in the 'contrast' corruption (15%) and the least in the 'zoom blur' corruption (1%). We visualize examples of original in-distribution images together with the above two corruptions in Figure 5(B), and we observe that 'contrast' is very different from the in-distribution 'CIFAR' images whereas 'zoom blur' is more

Table 2: **Rank correlation with standard error (in parentheses) between CKA and the prediction accuracy similarity of models**. We observe that dCKA improves correlations significantly on average, in terms of Spearman's ρ and Kendall's τ, with prediction accuracy on OOD test sets.

Corruption level	CKA		dCKA	
	ρ	τ	ρ	τ
1	0.147 (0.004)	0.103 (0.003)	0.151 (0.004)	0.105 (0.003)
2	0.150 (0.004)	0.106 (0.003)	0.157 (0.004)	0.110 (0.003)
3	0.132 (0.004)	0.094 (0.002)	**0.140 (0.003)**	**0.099 (0.003)**
4	0.130 (0.003)	0.091 (0.002)	**0.138 (0.003)**	**0.096 (0.003)**
5	0.135 (0.003)	0.094 (0.002)	0.140 (0.004)	0.098 (0.003)
Average	0.139 (0.002)	0.098 (0.001)	**0.145 (0.002)**	**0.102 (0.001)**
ID accuracy	0.163 (0.020)	0.116 (0.014)	0.167 (0.020)	0.118 (0.014)

Figure 5: **dCKA improves CKA on each corruption type. (A):** percentage improvement of dCKA over CKA and corresponding standard error on each type of corruptions. **(B):** visualization of corruptions with largest improvement ('contrast', red) and smallest improvement ('zoom blur', green). We observe that 'contrast' is more different from the uncorrupted dataset compared with 'zoom blur', in terms of mean pair-wise distance (MD) of images.

similar to the original images visually. Moreover, we compute the mean pairwise Euclidean distances (MD) between images for each type. We find the MD of the original CIFAR test set (MD= 658.7) is close to the 'zoom blur' (MD=513.7), and very far from the 'contrast' corruption (MD= 34.7). Hence, the benefit of dCKA vs. CKA appear greatest when the OOD domain is least similar to the original domain, which aligns with the expectation that dCKA is less domain specific due to the correction for the input domain population structure.

5   Discussion

We investigated the confounding effect of the input similarity structure on commonly used similarity measures between NNs representations. The confounder can lead to a high similarity even for completely random NNs and counter-intuitive conclusions when NNs trained in multiple domains are considered. We proposed a simple deconfounding algorithm by regressing out the input similarity from the representation similarity. The deconfounded similarity measures studied in this paper retain the invariance properties of the original measures. Moreover, deconfounding significantly improves the consistency of similarities w.r.t. *functional* similarities of NNs, which is especially beneficial in understanding NNs when multiple domains are involved, such as studying the closeness between the finetuned and pretrained models in transfer learning (Figure 4). Although the deconfounded similarity does not improve models' performance directly, some insights can potentially inspire the future development of better machine learning models. For instance, in (low-resource) transfer learning, we could encourage the dCKA between the finetuned and pretrained models to be correlated with the known domain similarity during training, as we observed a high correlation between domain similarity and PT-FT similarity in Section 4.3.

We further clarify that the original CKA can provide a meaningful representation similarity in applications with a *single* domain, such as in understanding NN trained with different initializations [19] or with different architectures [21] on the same dataset, and in these cases dCKA is expected to yield similar conclusions with CKA (Appendix G). Moreover, in specific neuroscience applications [46], the input similarity structure can be a feature that should not be removed, and dCKA is not expected to be effective. However, in applications involving *multiple* domains, such as transfer

learning, we showed that deconfounding yields more intuitive results, and we expect other applications with multiple domains or data sets, such as meta learning, to benefit from the insights in this paper.

There are still few limitations and open questions. We assumed that the confounder is linearly separable from the representation similarity in Eq.4, and showed that adding higher-order polynomial terms cannot improve the model evidence in Appendix A. However, it is still possible that the input similarity structure is not entirely *additively* separable from representation similarity structures, especially for deeper layers, and this may explain the fact that deconfounding similarities are more beneficial for shallow layers (e.g., Figure 2 *Left* and Figure 3). One possible solution is regressing out the similarity structure in the previous layer instead of the input layer, which improves detecting similar networks from random networks for deep blocks (Appendix D.2). However, this discards information from all previous layers and eventually loses the ability of representing the similarity between functional behaviors. We consider this as an open question to motivate progress on developing more functionally consistent similarity measures.

References

[1] Alex Krizhevsky, Ilya Sutskever, and Geoffrey E Hinton. Imagenet classification with deep convolutional neural networks. *Advances in Neural Information Processing Systems*, 25:1097–1105, 2012.

[2] Alex Wang, Amanpreet Singh, Julian Michael, Felix Hill, Omer Levy, and Samuel R Bowman. GLUE: A multi-task benchmark and analysis platform for natural language understanding. *arXiv preprint arXiv:1804.07461*, 2018.

[3] Jeremy Irvin, Pranav Rajpurkar, Michael Ko, Yifan Yu, Silviana Ciurea-Ilcus, Chris Chute, Henrik Marklund, Behzad Haghgoo, Robyn Ball, Katie Shpanskaya, et al. Chexpert: A large chest radiograph dataset with uncertainty labels and expert comparison. In *Proceedings of the AAAI conference on Artificial Intelligence*, volume 33, pages 590–597, 2019.

[4] Pranav Rajpurkar, Jian Zhang, Konstantin Lopyrev, and Percy Liang. Squad: 100,000+ questions for machine comprehension of text. *arXiv preprint arXiv:1606.05250*, 2016.

[5] Tsung-Yi Lin, Michael Maire, Serge Belongie, James Hays, Pietro Perona, Deva Ramanan, Piotr Dollár, and C Lawrence Zitnick. Microsoft coco: Common objects in context. In *European Conference on Computer Vision*, pages 740–755. Springer, 2014.

[6] Mukund Sundararajan, Ankur Taly, and Qiqi Yan. Axiomatic attribution for deep networks. In *International Conference on Machine Learning*, pages 3319–3328. PMLR, 2017.

[7] Scott M Lundberg and Su-In Lee. A unified approach to interpreting model predictions. In *Proceedings of the 31st International Conference on Neural Information Processing Systems*, pages 4768–4777, 2017.

[8] Johannes Mehrer, Courtney J Spoerer, Nikolaus Kriegeskorte, and Tim C Kietzmann. Individual differences among deep neural network models. *Nature Communications*, 11(1):1–12, 2020.

[9] Adriana Romero, Nicolas Ballas, Samira Ebrahimi Kahou, Antoine Chassang, Carlo Gatta, and Yoshua Bengio. Fitnets: Hints for thin deep nets. *arXiv preprint arXiv:1412.6550*, 2014.

[10] Maithra Raghu, Justin Gilmer, Jason Yosinski, and Jascha Sohl-Dickstein. SVCCA: Singular vector canonical correlation analysis for deep learning dynamics and interpretability. *arXiv preprint arXiv:1706.05806*, 2017.

[11] Ari S Morcos, Maithra Raghu, and Samy Bengio. Insights on representational similarity in neural networks with canonical correlation. *arXiv preprint arXiv:1806.05759*, 2018.

[12] Alex Williams, Erin Kunz, Simon Kornblith, and Scott Linderman. Generalized shape metrics on neural representations. *Advances in Neural Information Processing Systems*, 34, 2021.

[13] Guillaume Alain and Yoshua Bengio. Understanding intermediate layers using linear classifier probes. *arXiv preprint arXiv:1610.01644*, 2016.

[14] Yunzhen Feng, Runtian Zhai, Di He, Liwei Wang, and Bin Dong. Transferred discrepancy: Quantifying the difference between representations. *arXiv preprint arXiv:2007.12446*, 2020.

[15] Frances Ding, Jean-Stanislas Denain, and Jacob Steinhardt. Grounding representation similarity with statistical testing. *arXiv preprint arXiv:2108.01661*, 2021.

[16] Shimon Edelman. Representation is representation of similarities. *Behavioral and Brain Sciences*, 21(4):449–467, 1998.

[17] Nikolaus Kriegeskorte, Marieke Mur, and Peter A Bandettini. Representational similarity analysis-connecting the branches of systems neuroscience. *Frontiers in Systems Neuroscience*, 2:4, 2008.

[18] Mahdiyar Shahbazi, Ali Shirali, Hamid Aghajan, and Hamed Nili. Using distance on the Riemannian manifold to compare representations in brain and in models. *NeuroImage*, page 118271, 2021.

[19] Simon Kornblith, Mohammad Norouzi, Honglak Lee, and Geoffrey Hinton. Similarity of neural network representations revisited. In *International Conference on Machine Learning*, pages 3519–3529. PMLR, 2019.

[20] James V Haxby, M Ida Gobbini, Maura L Furey, Alumit Ishai, Jennifer L Schouten, and Pietro Pietrini. Distributed and overlapping representations of faces and objects in ventral temporal cortex. *Science*, 293(5539):2425–2430, 2001.

[21] Thao Nguyen, Maithra Raghu, and Simon Kornblith. Do wide and deep networks learn the same things? Uncovering how neural network representations vary with width and depth. *arXiv preprint arXiv:2010.15327*, 2020.

[22] Behnam Neyshabur, Hanie Sedghi, and Chiyuan Zhang. What is being transferred in transfer learning? *arXiv preprint arXiv:2008.11687*, 2020.

[23] Simon Kornblith, Ting Chen, Honglak Lee, and Mohammad Norouzi. Why do better loss functions lead to less transferable features? *Advances in Neural Information Processing Systems*, 34, 2021.

[24] Nicolas Gonthier, Yann Gousseau, and Saïd Ladjal. An analysis of the transfer learning of convolutional neural networks for artistic images. In *International Conference on Pattern Recognition*, pages 546–561. Springer, 2021.

[25] Yipeng Zhang, Tyler L Hayes, and Christopher Kanan. Disentangling transfer and interference in multi-domain learning. *arXiv preprint arXiv:2107.05445*, 2021.

[26] Micah Goldblum, Steven Reich, Liam Fowl, Renkun Ni, Valeriia Cherepanova, and Tom Goldstein. Unraveling meta-learning: Understanding feature representations for few-shot tasks. In *International Conference on Machine Learning*, pages 3607–3616. PMLR, 2020.

[27] Han-Ming Wu, Yin-Jing Tien, Meng-Ru Ho, Hai-Gwo Hwu, Wen-chang Lin, Mi-Hua Tao, and Chun-houh Chen. Covariate-adjusted heatmaps for visualizing biological data via correlation decomposition. *Bioinformatics*, 34(20):3529–3538, 2018.

[28] Qi Liu, Chun Li, Valentine Wanga, and Bryan E Shepherd. Covariate-adjusted Spearman's rank correlation with probability-scale residuals. *Biometrics*, 74(2):595–605, 2018.

[29] Daniel LK Yamins, Ha Hong, Charles F Cadieu, Ethan A Solomon, Darren Seibert, and James J DiCarlo. Performance-optimized hierarchical models predict neural responses in higher visual cortex. *Proceedings of the National Academy of Sciences*, 111(23):8619–8624, 2014.

[30] Maithra Raghu, Thomas Unterthiner, Simon Kornblith, Chiyuan Zhang, and Alexey Dosovitskiy. Do vision transformers see like convolutional neural networks? *Advances in Neural Information Processing Systems*, 34, 2021.

[31] Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on Computer Vision and Pattern Recognition*, pages 770–778, 2016.

[32] Alex Krizhevsky, Geoffrey Hinton, et al. Learning multiple layers of features from tiny images. 2009.

[33] Jia Deng, Wei Dong, Richard Socher, Li-Jia Li, Kai Li, and Li Fei-Fei. Imagenet: A large-scale hierarchical image database. In *2009 IEEE conference on Computer Vision and Pattern Recognition*, pages 248–255. Ieee, 2009.

[34] Damla Şentürk and Hans-georg Müller. Covariate adjusted correlation analysis via varying coefficient models. *Scandinavian Journal of Statistics*, 32(3):365–383, 2005.

[35] James Durbin and Geoffrey S Watson. Testing for serial correlation in least squares regression. i. In *Breakthroughs in Statistics*, pages 237–259. Springer, 1992.

[36] Grace Chan and Andrew TA Wood. Algorithm as 312: An algorithm for simulating stationary Gaussian random fields. *Applied Statistics*, pages 171–181, 1997.

[37] Arthur Gretton, Olivier Bousquet, Alex Smola, and Bernhard Schölkopf. Measuring statistical dependence with Hilbert-Schmidt norms. In *International Conference on Algorithmic Learning Theory*, pages 63–77. Springer, 2005.

[38] Alexis Conneau, Kartikay Khandelwal, Naman Goyal, Vishrav Chaudhary, Guillaume Wenzek, Francisco Guzmán, Édouard Grave, Myle Ott, Luke Zettlemoyer, and Veselin Stoyanov. Unsupervised cross-lingual representation learning at scale. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pages 8440–8451, 2020.

[39] Ian Goodfellow, Yoshua Bengio, and Aaron Courville. *Deep Learning*. MIT press, 2016.

[40] Dan Hendrycks and Thomas Dietterich. Benchmarking neural network robustness to common corruptions and perturbations. *arXiv preprint arXiv:1903.12261*, 2019.

[41] Philip May. Machine translated multilingual STS benchmark dataset. 2021.

[42] Xingchao Peng, Qinxun Bai, Xide Xia, Zijun Huang, Kate Saenko, and Bo Wang. Moment matching for multi-source domain adaptation. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 1406–1415, 2019.

[43] Stephan Rabanser, Stephan Günnemann, and Zachary C Lipton. Failing loudly: An empirical study of methods for detecting dataset shift. *arXiv preprint arXiv:1810.11953*, 2018.

[44] Mingxing Tan and Quoc Le. Efficientnet: Rethinking model scaling for convolutional neural networks. In *International Conference on Machine Learning*, pages 6105–6114. PMLR, 2019.

[45] Victor Sanh, Lysandre Debut, Julien Chaumond, and Thomas Wolf. DistilBERT, a distilled version of BERT: smaller, faster, cheaper and lighter. *arXiv*, abs/1910.01108, 2019.

[46] Nikolaus Kriegeskorte, Marieke Mur, Douglas A Ruff, Roozbeh Kiani, Jerzy Bodurka, Hossein Esteky, Keiji Tanaka, and Peter A Bandettini. Matching categorical object representations in inferior temporal cortex of man and monkey. *Neuron*, 60(6):1126–1141, 2008.

[47] Kevin P Murphy. *Machine Learning: A Probabilistic Perspective*. MIT press, 2012.

[48] Ilya Loshchilov and Frank Hutter. Decoupled weight decay regularization. In *International Conference on Learning Representations*, 2018.

A Statistical checks of the deconfounding assumption in Eq.4

A.1 Linearity assumption of the input similarity structure

In Eq.4, we assume that the representation similarity structures **linearly** depend on the input similarity structure. To validate if the linear assumption is sufficient, we check if adding higher-order polynomial terms of input similarity to the regression model (Eq.4) can help explain the representation similarity structure. We show the effect of adding higher-order polynomial terms on a pretrained ResNet-18 (contains 20 layers in total) with CIFAR-10 inputs in Figure 6. We observe that neither the R^2 nor the Bayesian information criterion (BIC) [47], approximating the model evidence, changes much when adding higher-order terms. Although R^2 can be marginally improved by increasing the order in the deeper layers (e.g., layer 20), we only consider the linear model in this paper for simplicity.

A.2 Independence assumption of the noise term across the dataset

In Eq.4, we consider the collection of distance between each pair of examples is the dataset of the linear regression. A potential issue is that the noise term ϵ_f^m can be correlated for different pairs, while we assume independent noise when fitting model Eq.4. Because the noise $\epsilon_{f,ij}^m$ of the distance between example i and j and $\epsilon_{f,ik}^m$ of the distance between example i and k contain the same information about example i, which might induce correlation between $\epsilon_{f,ij}^m$ and $\epsilon_{f,ik}^m$. Checking noise correlation is important to justify if the model solution Eq.5 is misspecified.

For each i, we apply the Durbin-Watson (DW) test on $\{\epsilon_{f,ij}^m | \forall j\}$, and average the test statistics over the index i. DW is always in $[0, 4]$, and if there is no evidence of noise correlation, the test statistics equals to 2. Otherwise, the closer to 0 the statistic, the more evidence for positive correlation, while the closer to 4 means a negative correlation. We show the histogram of DW statistics as well as the averaged DW for each layer in Figure 6, where no serious noise correlation is observed.

Figure 6: *Left*: **Log R^2 and BIC of regression models with different orders of input similarity**. We empirically observe that correcting for the confounder with a linear model is sufficient, especially for shallow layers (demonstrated with ResNet-18 on CIFAR-10). *Right*: **Durbin-Watson histogram and averaged DW statistics for each layer.**

B Proofs of propositions

B.1 Proof of Proposition 3.1

If the similarity measure $k(\cdot, \cdot)$ is invariant to orthogonal transformation, the representational similarity matrices are invariant to orthogonal transformation too. Thus, for any two full-rank orthonormal matrices U and V, such that $U^T U = I$ and $V^T V = I$, we have:

$$K(X_{f_1}^{m_1} U, X_{f_1}^{m_1} U) = K(X_{f_1}^{m_1}, X_{f_1}^{m_1}); \quad K(X_{f_2}^{m_2} V, X_{f_2}^{m_2} V) = K(X_{f_2}^{m_2}, X_{f_2}^{m_2}), \qquad (14)$$

and the deconfounded RSMs are also invariant to orthogonal transformation:

$$dK(X_{f_1}^{m_1} U, X_{f_1}^{m_1} U) = K(X_{f_1}^{m_1} U, X_{f_1}^{m_1} U) - \hat{\alpha}_{f_1}^{m_1} K^0 = K(X_{f_1}^{m_1}, X_{f_1}^{m_1}) - \hat{\alpha}_{f_1}^{m_1} K^0 = dK(X_{f_1}^{m_1}, X_{f_1}^{m_1});$$
$$dK(X_{f_2}^{m_2} V, X_{f_2}^{m_2} V) = K(X_{f_2}^{m_2} U, X_{f_2}^{m_2} U) - \hat{\alpha}_{f_2}^{m_2} K^0 = K(X_{f_2}^{m_2}, X_{f_2}^{m_2}) - \hat{\alpha}_{f_2}^{m_2} K^0 = dK(X_{f_2}^{m_2}, X_{f_2}^{m_2}). \qquad (15)$$

Therefore the deconfounded similarity is invariant to orthogonal transformation:

$$s(dK(X_{f_1}^{m_1} U, X_{f_1}^{m_1} U), dK(X_{f_2}^{m_2} V, X_{f_2}^{m_2} V)) = s(dK(X_{f_1}^{m_1}, X_{f_1}^{m_1}), dK(X_{f_2}^{m_2}, X_{f_2}^{m_2})), \qquad (16)$$

528 which completes the proof.

529 Note that the PSD approximation will not affect the orthogonal invariance property, because decon-
530 founded RSMs are invariant to orthogonal transformations.

B.2   Proof of Proposition 3.2

532 We use dRSA as an example to show the proof. For any $\gamma, \theta \in \mathbb{R}$, we have:

$$K(\gamma X_{f_1}^{m_1}, \gamma X_{f_1}^{m_1}) = \gamma^2 K(X_{f_1}^{m_1}, X_{f_1}^{m_1}); \quad K(\theta X_{f_2}^{m_2}, \theta X_{f_2}^{m_2}) = \theta^2 K(X_{f_2}^{m_2}, X_{f_2}^{m_2}), \quad (17)$$

533 because of using the Euclidean distance. Moreover, the deconfounded RSMs are scaled with λ^2 and
534 θ^2 as well, because the regression coefficient, α in Eq.5, is scaled with the same value. Therefore,
535 the rank correlation between two scaled deconfounded RSMs does not change because the rank is
536 invariant to scaling all objects.

537 The PSD approximation will not affect the isotropic scaling invariance property too, because the PSD
538 approximation matrix will be scaled at the same level.

C   Training details of NNs

C.1   ResNet training on CIFAR-10

541 We trained 50 ResNet-18 models without any pretrained model from different initializations on the
542 CIFAR-10 training set. We use 200 epochs with batch size 128. We train models with SGD: learning
543 rate 0.1, momentum 0.9, and weight decay 5e-4. We also use cosine annealing learning rate with
544 $T_{max} = 200$. The averaged accuracy of trained models on CIFAR-10 test set is 0.89, with standard
545 deviation 0.3%. Model training takes around 10 hours.

C.2   ResNet training on DomainNet

547 We finetune Resnet-50 models which had been pretrained on the Imagenet dataset. Separate models
548 are trained on each domain of the DomainNet dataset, namely Real, Clipart, Sketch and Quickdraw.
549 The DomainNet task is to classify each image among 345 different classes. For each domain, we
550 repeat the training for 10 random restarts. To keep the training uniform, we sample 5000 images from
551 each domain and train the Resnet model for 2000 iterations with a batch size of 32. All the input
552 images are resized to 224×224 pixels, and we perform no other form of data augmentation. We
553 use the AdamW optimizer [48] with a base learning rate of $1e - 3$, which was varied using a cosine
554 annealing scheduler with a warm-up of 600 steps. The fine-tuning takes around 8 hours in total for
555 all random seeds.

556 Figure 7 *Left* shows the F1 scores of the finetuned model for each domain. As expected, the score
557 for the Real domain is the highest since it is the most similar to Imagenet. The higher score on the
558 Quickdraw domain is possibly due to the simplicity of the Quickdraw input distribution (since it
559 consists of doodles) as compared to the other domains.

Figure 7: *Left*: Test F1 scores for each of the domains from DomainNet for Resnet-50 models. We
can see that the Real domain, which is the most similar to Imagenet achieves the highest F1 score.
Right: Test Spearman's correlation for the XLM-RoBERTa model when finetuned on each language.

C.3   XLM-RoBERTa training on STS-B

Since we are training on different languages, we use the XLM-RoBERTa model as the base model and finetune it on different STS-B tasks on English, Spanish, Polish and Russian languages. For finetuning we use AdamW optimizer with a learning rate of $2e - 5$ which is linearly annealed, with 30% of total steps for warmup, for 3 epochs. We use a batch size of 8 and regularize the training with a weight decay of 0.01. The fine-tuning takes around 5 hours in total for all random seeds.

Figure 7 *Right* shows Spearman's correlation of the predicted sentence similarity with the ground truth. The performance on English is the highest while that on Russian is the lowest. This performance across the languages correlates perfectly with the domain similarity reported in Section 4.3.

C.4   Computational resources

We used two GPUs: 2080Ti and Tesla V100, in our internal cluster.

D   Additional experiments on detecting similar NNs from random NNs.

D.1   Generate random NNs with permutation

Different from the main text where we consider random NNs as untrained NNs with different initializations, here we permute the weight matrix of each layer given a pretrained ResNet-18 on ImageNet. This can preserve the parameter distributions of the pretrained ResNet while generating random functions. From Figure 8, we observe that the conclusion drawn in the main text also holds when the null distribution is constructed with permutation.

Figure 8: *Left*: Proportion of ImageNet-CIFAR ResNets pairs identified from permuted ResNets for each block. The proportions for the last four blocks are omitted as they are 0 for all metrics. *Right*: Histograms of similarities in the first two blocks with two different random NNs.

D.2   Recursive deconfounding

From Table 2 *Left*, we observe that although deconfounded similarities improve detecting semantically similar NNs from random NNs, no similarity can identify ImageNet-CIFAR pairs for deep layers. One hypothesis is that the confounding effect of input similarity cannot be approximated well with additively separable functions for deeper layers, because of the model nonlinearity added by each NN layer.

Here we consider a natural extension of deconfounding input similarity: instead of regressing out the input similarity directly (in Eq.3), we regress out the representation similarity structure from the previous layer recursively:

$$dK_{f_1}^{m_1} = K_{f_1}^{m_1} - \hat{\beta}_{f_1}^{m_1} K_{f_1}^{m_1-1};$$
$$dK_{f_2}^{m_2} = K_{f_2}^{m_2} - \hat{\beta}_{f_2}^{m_2} K_{f_2}^{m_2-1}. \tag{18}$$

Although Eq.18 has the same additively separable assumption as Eq.3, but Eq.18 is easier to satisfy because it only assumes additively separable for one layer. We call the similarity generated by Eq.18 recursive deconfounded similarity.

We apply recursive deconfounded similarity, such as rdCKA and rdRSA, on the experiments of detecting similar networks from random networks described in Section 4.1. We show the comparison results between dCKA/dRSA with rdCKA/rdRSA in Table 3, where we observe a marginal

Table 3: Proportion of ImageNet-CIFAR ResNets pairs identified from random ResNets.

Block	dCKA	rdCKA	dRSA	rdRSA
1	1.0, 1.0	1.0, 1.0	1.0, 1.0	1.0, 1.0
2	1.0, 1.0	1.0, 1.0	1.0, 1.0	0.44, 0.98
3	1.0, 1.0	1.0, 1.0	0.0.0, 0.08	1.0, 1.0
4	1.0, 1.0	0.42, 1.0	0.0, 0.0	0.08, 0.02
5	0.0, 0.04	0.0, 0.78	0.0, 0.0	0.18, 0.0
6	0.0, 0.02	0.0, 0.04	0.0, 0.0	0.28, 0.4
7	0.0, 0.0	0.0, 0.0	0.0, 0.0	0.0, 0.0
8	0.0, 0.0	0.18, 0.12	0.0, 0.0	0.02, 0.18
Average	**0.5**, 0.51	0.45, **0.62**	0.25, 0.26	**0.38, 0.45**

Figure 9: Histogram of each similarity measure for the last three blocks.

improvement from dCKA to rdCKA but a significant improvement from dRSA to rdRSA. However, the proportion of identified similar networks is still low for deeper layers. Thus, we consider that ImageNet and CIFAR-10 learn different high-level representations because they contain different classes of images, as mentioned in the main text.

We visualize the histogram of each similarity measure for the last 3 blocks in Figure 9. We observe that CKA/dCKA and RSA/dRSA are much smaller than two null distributions, while rdCKA/rdRSA can have a similar level as the corresponding null distribution.

E Consistency of in-domain NN functional similarities.

In Section 4.2, we test the consistency of different NN similarities across 19 different domains. In this section, we verify if NN similarities are consistent across different input samples from the same domain. We repeat the same procedure described in Section 4.2, except that we calculate the similarity $s(f_i, f^*)$ on 20 different sets of examples sampled from the same domain, i.e., the CIFAR-10 test set, instead of 19 different OOD domains.

Figure 10: **Proportion of identified similar NNs across different samples from the same domain.** We observe that the deconfounded similarity can still identify more similar models compared with the corresponding original similarity.

We show the results in Figure 10, where we observe that deconfounding can improve CKA/RSA with different inputs from the same domain, but the improvement is marginal compared with cross-domain experiments: 23% for CKA (from 0.65 to 0.8) and 7% for RSA (from 0.75 to 0.8), although the proportion of identified similar NNs are much larger than the cross-domain examples for all similarity measures.

F Layer-wise CKA and dCKA on DomainNet

We show the results of the DomainNet transfer learning tasks (Section 4.3) in Figure 11. We observe that dCKA gives more consistent ranking w.r.t. the domain similarity in middle blocks.

Figure 11: **dCKA adjusts for transfer learning under domain shift.** *Left* shows the ground truth domain similarity (between ImageNet and other domains in DomainNet) as measured by test binary cross entropy (BCE) loss of the cross-domain classifier. We plot the CKA (*Center*) and dCKA (*Right*) between the pretrained ResNet-50 model and models finetuned for different languages on the DomainNet tasks. We observe that dCKA is better correlated with the domain similarity than CKA.

G Consistency of dCKA for NNs trained with different initialization

One advantage of original CKA is that it can reveal consistent relationships between layers of NNs trained with different initializations, while other representation similarity measures, such as PWCCA and Procrustes, can not [19, 15]. Here we show that dCKA has a similar behavior as CKA when studying the similarity between representations of NNs with different initializations given one domain.

As in [15], we first take 5 ResNet-18 models trained on CIFAR-10 dataset with different initializations. For one model (model i), we compute the similarity between every pair of layers of the model. We then choose another model with a different initialization (model j), and compute the similarity between every layer of model i and every layer of model j. We average the results for five different models. We show the results in Figure 12, where we observe that for both CKA and dCKA and for each layer of the model i, the most similar layer in model j is the same corresponding layer. Hence, similarly to CKA, dCKA can identify consistent relationships of layers between different networks.

H Licenses

The source code and pretrained model for XLM-RoBERTa are available at `https://huggingface.co/transformers/v4.9.2/model_doc/xlmroberta.html` under the Apache License 2.0.

The source code of Distil-RoBERTa are available at `https://huggingface.co/distilroberta-base` under the Apache License 2.0.

The source code and pretrained model of ResNets on ImageNet are available at `https://pytorch.org/hub/pytorch_vision_resnet/` under license `https://github.com/pytorch/pytorch/blob/master/LICENSE`.

The source code of EfficientNet-50 are available at `https://pytorch.org/hub/nvidia_deeplearningexamples_efficientnet/` under license `https://github.com/pytorch/pytorch/blob/master/LICENSE`.

The DomainNet dataset is available from `http://ai.bu.edu/M3SDA/#dataset` with copyright information on the same website.

The STS-B dataset is available from `https://paperswithcode.com/dataset/sts-benchmark` under CC-BY-SA.

Figure 12: **CKA (A) and dCKA (B) between layers**. *Left* panel: layers are from the same NN. *Right* panel: layers are from NNs trained with different initializations. Like CKA, dCKA can reveal consistent relationships between layers of NNs trained with different initializations.

The CIFAR-10 dataset is available from `https://www.cs.toronto.edu/~kriz/cifar.html` under MIT license.

The CIFAR-10-C dataset is available from `https://zenodo.org/record/2535967#.YoThrKjP2Uk` under CC-BY 4.0.