Hierarchical classification at multiple operating points

Abstract

Many classification problems consider classes that form a hierarchy. Classifiers that are aware of this hierarchy may be able to make confident predictions at a coarse level despite being uncertain at the fine-grained level. While it is generally possible to vary the granularity of predictions using a threshold at inference time, most contemporary work considers only leaf-node prediction, and almost no prior work has compared methods at multiple operating points. We present an efficient algorithm to produce operating characteristic curves for any method that assigns a score to every class in the hierarchy. Applying this technique to evaluate existing methods reveals that top-down classifiers are dominated by a naïve flat softmax classifier across the entire operating range. We further propose two novel loss functions and show that a soft variant of the structured hinge loss is able to significantly outperform the flat baseline. Finally, we investigate the poor accuracy of top-down classifiers and demonstrate that they perform relatively well on unseen classes.

1 Introduction

Many classification problems involve classes that can be recursively grouped into a hierarchy of progressively larger superclasses. This hierarchy can be represented by a directed graph where the nodes are classes and the edges define a superset-of relation. Knowledge of the hierarchy can be useful in many different respects. For example, mistake severity can be quantified using distance in the graph [9, 2], classifiers can make predictions at a coarse level to avoid an error at the fine-grained level [11, 38], classes with few labels in a long-tailed distribution can benefit from the examples of similar classes [38], and a cascade can be used to reduce inference time [26, 16, 14].

Whereas many recent works consider only leaf-node prediction, we are interested in the setting where the classifier may predict any class in the hierarchy, including internal nodes. In this setting, prediction involves an inherent trade-off between specificity and correctness: more general predictions contain less information but have a greater chance of being correct. The trade-off can typically be controlled using an inference threshold, analogous to the trade-off between sensitivity and specificity in binary classification or precision and recall in detection. However, while it is standard to evaluate these problems using trade-off curves, most works on hierarchical classification consider only a single operating point. It is important to consider the full trade-off curve in order to ensure a fair comparison and enable the selection of classifiers according to design specifications. This paper presents an efficient algorithm to obtain trade-off curves for existing hierarchical metrics.

The proposed technique is subsequently used to compare the trade-offs realized by different methods. Given the effectiveness of deep learning, we focus on loss functions for training differentiable models. Experiments on the iNat21 [36] and ImageNet-1k [10] datasets for image classification reveal that a naïve flat softmax classifier *dominates* recent top-down classifiers, obtaining better accuracy at any operating point. We further introduce a soft structured-prediction loss that dominates the flat softmax.

Submitted to 36th Conference on Neural Information Processing Systems (NeurIPS 2022). Do not distribute.

While it was already known that top-down approaches provide worse *leaf-node* predictions than a flat softmax [31, 2], we did not expect this to hold for non-leaf predictions. We hypothesize that the top-down approaches obtain worse accuracy than the "bottom-up" flat softmax because the coarse classes can be highly diverse, and thus better learned by a union of distinct classifiers when the fine-grained labels are available. To support this hypothesis, we show that training a flat softmax classifier at a lower level and testing at a higher level provides better accuracy than training at the higher level. Finally, we consider a synthetic *out-of-distribution* problem where a hierarchical classifier that explicitly assigns scores to higher-level classes may be expected to have an advantage.

The key contributions of this paper are as follows.

- We introduce a novel, efficient technique for evaluating hierarchical classifiers that captures the full trade-off between specificity and correctness using a threshold-based inference rule.

- We propose two novel loss functions, soft-max-descendant and soft-max-margin, as well as a simple but effective modification to the predictions of Deep RTC [38]. While soft-max-descendant is ineffective, soft-max-margin and Deep RTC achieve the best results.

- We conduct an empirical comparison of loss functions and inference rules using the iNat21-mini dataset and its hierarchy of 10,000 species. The naïve softmax loss outperforms past approaches except for Deep RTC. The threshold-based inference rule is shown to be effective.

- We evaluate the robustness of different methods to unseen leaf-node classes. The top-down methods are more competitive for unseen classes, while Deep RTC [38] is the most effective.

2   Related work

There are several different types of hierarchical classification problem. In the terminology of Silla and Freitas [33], we consider problems with tree structure, Single-Path Labels (SPL) and Non-Mandatory Leaf-Node Prediction (NMLNP). *Tree structure* means that there is a unique root node and every other node has exactly one parent, *Single-Path Labels* means that a sample cannot belong to two separate classes (unless one is a superclass of the other) and *Non-Mandatory Leaf-Node Prediction* means that the classifier may predict any class in the hierarchy, not just leaf nodes. This work assumes the hierarchy is known and does not consider the separate problem of learning the hierarchy.

MLNP with deep learning.   Several recent works have sought to leverage a class hierarchy to improve leaf-node prediction. Wu et al. [37] trained a softmax classifier by optimizing a "win" metric comprising a weighted combination of likelihoods on the path from the root to the label. Bertinetto et al. [2] proposed a similar Hierarchical Cross-Entropy (HXE) loss comprising weighted losses for the conditional likelihood of each node given its parent, as well as a Soft Label loss that generalized label smoothing [27] to incorporate the hierarchy. Karthik et al. [20] demonstrated that a flat softmax classifier still effective for MLNP and proposed an alternative inference method, Conditional Risk Minimization (CRM). Guo et al. [18] performed inference using an RNN starting from the root node. Other works have proposed architectures that reflect the hierarchy (*e.g.* [40, 1, 42]). This paper seeks to compare loss functions under a simple inference procedure.

Non-MLNP methods.   Comparatively few works have entertained hierarchical classifiers that can predict arbitrary nodes. Deng et al. [11] highlighted the trade-off between specificity and accuracy, and sought to obtain the most-specific classifier for a given error rate. Davis et al. [7, 8] re-calibrated a flat softmax classifier within a hierarchy using a held-out set and performed inference by starting at the most-likely leaf-node and climbing the tree until a threshold was met, comparing methods at several fixed thresholds. Wu et al. [38] proposed the Deep Realistic Taxonomic Classifier (Deep RTC), which obtains a score for each node by summing over those of its ancestors [32] and whose loss is evaluated at random cuts of the tree. They perform inference by traversing down from the root until a score threshold is crossed (by default, zero). In the YOLO-9000 detector, Redmon and Farhadi [31] introduced a conditional softmax classifier that resembled the efficiency-driven approach of Morin and Bengio [26]. The model outputs a concatenation of logit vectors that each parameterize (via softmax) the conditional distribution of children given a parent. It was noted to provide elegant degradation but the hierarchical predictions were not rigorously evaluated. Brust and Denzler [4] generalized the conditional approach to multi-path labels in a DAG hierarchy by replacing the softmax with a sigmoid for each class given *each* of its parents. Inference was performed by seeking the class with the maximum likelihood excluding its children, which may predict non-leaf nodes. Most of the above loss functions will be compared in the main evaluation.

Hierarchical metrics. There are many ways to measure the accuracy of hierarchical classifiers [6, 21]. For the specific case of NMLNP, it is important to consider metrics for both correctness and specificity. The Wu-Palmer metrics [39] measure precision and recall using the depth of the Lowest Common Ancestor (LCA). Deng et al. [11] proposed to measure specificity using information content to account for an imbalanced tree, and Zhao et al. [41] modified the Wu-Palmer metrics to use information rather than depth. These are the metrics that we adopt, although our technique can be applied to construct curves for any simply metric. Examples of other metrics include the fraction of examples receiving non-root classifications [7] and the fraction of true-negative leaf nodes for correct predictions [38].

Structured prediction. The max-margin structured-prediction loss saw historical use for hierarchical classification with linear SVMs, originally for document classification [5] and later to achieve efficient inference [34]. More recently, a soft max-margin loss [29, 15] has been used to train deep models for sequence-to-sequence learning [13] and long-tail classification [25]. We believe this paper is the first to recognize its utility for hierarchical classification with deep learning.

3 Problem definition

3.1 Class hierarchy

Let $\mathcal{Y}$ be the set of classes, including both leaf nodes and their superclasses. The hierarchy is defined by a tree with edges $\mathcal{E} \subset \mathcal{Y}^2$. The edges define a transitive, non-strict superset relation $\supseteq$ over the classes. It is helpful to think of the classes as sets of samples. A sample x that belongs to class y also belongs to the ancestors (superclasses) of y; that is, $x \in y$ and $y \subseteq y'$ implies $x \in y'$. Hierarchical classification can be seen as multi-label classification, since samples belong to multiple classes simultaneously. However, samples cannot belong to *arbitrary* subsets of $\mathcal{Y}$, since belonging to one class implies belonging to its superclasses. Furthermore, we consider only class hierarchies in which siblings are *mutually exclusive*; that is, a sample x can only belong to two classes y and y' if one is a superclass of the other. The problem is therefore to assign a single label $y \in \mathcal{Y}$ to an example, with this label signifying membership in class y and all of its superclasses. While any superclass of the ground-truth label is deemed to be a correct classification, it is preferable for the classifier to predict the most-specific correct label.

We briefly introduce our notation for the tree. Let $\mathbf{r} \in \mathcal{Y}$ be the unique root node, let $\pi(y) \in \mathcal{Y}$ be the unique parent for every node $y \in \mathcal{Y} \setminus \{\mathbf{r}\}$, let $\mathcal{C}(y) \subseteq \mathcal{Y}$ be the children of node y, let $\mathcal{L} \subseteq \mathcal{Y}$ be the set of leaf nodes, let $\mathcal{A}(y) \subseteq \mathcal{Y}$ be the ancestors of node y, and let $\mathcal{D}(y) \subseteq \mathcal{Y}$ be the descendants of node y. We define the ancestors and descendants inclusively, such that $\mathcal{D}(y) \cap \mathcal{A}(y) = \{y\}$. It will also be useful to introduce $\mathcal{L}(y) = \mathcal{L} \cap \mathcal{D}(y)$ to denote the set of leaf descendants of node y and $\mathcal{S}(y) = \mathcal{C}(\pi(y))$ to denote its siblings. The superset relation over classes is equivalent to the ancestor relation in the tree; that is, $u \supseteq v$ iff $u \in \mathcal{A}(v)$.

We focus on models that map a sample x to a conditional likelihood $p(y|x)$ over all labels in the hierarchy. If we consider $\mathcal{Y}$ with its superset relation and mutually exclusivity of siblings as an event space, then a function $p : \mathcal{Y} \to [0, 1]$ must satisfy

$$\forall u \in \mathcal{Y} : \quad p(u) \geq \sum_{v \in \mathcal{C}(u)} p(v) \tag{1}$$

to be a probability function on $\mathcal{Y}$. If this holds with equality, we say that the children are exhaustive. We generally expect that the root node is uninformative $p(\mathbf{r}) = 1$.

3.2 Metrics

Metrics $M(y, \hat{y})$ measure the quality of predicted label $\hat{y}$ for ground-truth label y. When making non-leaf predictions, it is important to capture both correctness and specificity, either using a pair of metrics or a single combined metric. The simplest such pair are the binary metrics

$$\text{Correct}(y, \hat{y}) = [\hat{y} \supseteq y] , \qquad\qquad \text{Exact}(y, \hat{y}) = [\hat{y} = y] . \tag{2}$$

If the ground-truth label is not a leaf node, then it is possible for the predicted label to be below it, $\hat{y} \subset y$. This is not considered an error, and we replace $\hat{y} \leftarrow y$ where this occurs.

Since the EXACT metric is often too strict, it is useful to introduce a non-binary measure of label specificity. Two popular choices are the depth of the node $d(y)$ and its information content $I(y) =$

$-\log p(y) = \log|\mathcal{L}| - \log|\mathcal{L}(y)|$ (assuming a uniform distribution over the leaf nodes [11, 41]). We prefer information as it better accounts for an imbalanced tree; in a perfect k-ary tree, $I(y) \propto d(y)$. Rather than directly measure the specificity of the predictions [11], the specificity measure can be used to define precision and recall metrics [41] using the Lowest Common Ancestor (LCA):

$$\text{Recall}(y, \hat{y}) = \frac{I(\text{lca}(y, \hat{y}))}{I(y)} , \qquad \text{Precision}(y, \hat{y}) = \frac{I(\text{lca}(y, \hat{y}))}{I(\hat{y})} . \qquad (3)$$

Correct and Precision are metrics for correctness (decreasing with depth), whereas Exact and Recall are metrics for specificity (increasing with depth). Each type should not be used without the other.

4 Inference and loss functions

We adopt the paradigm that a differentiable model f with parameters ϕ maps an input x to a real vector $\theta = f(x, \phi)$ that parameterizes the conditional likelihood $p(\cdot|x) = q(\theta) \in [0, 1]^{\mathcal{Y}}$. Learning will be performed using Stochastic Gradient Descent (SGD) to minimize the expected value of a loss function $\ell(y, \theta)$ on a training set. Inference will be performed using a function $\xi : [0, 1]^{\mathcal{Y}} \to \mathcal{Y}$ to obtain $\hat{y} = \xi(q(\theta))$. We consider the training method to be defined by the pair (ℓ, q) and the inference method to be defined by ξ. The dimension of θ depends on the training method.

4.1 Inference functions

In standard flat classification, inference simply selects the most likely class $\xi(p) = \arg\max_{y \in \mathcal{Y}} p(y)$. However, in the hierarchical setting, this would always select the uninformative root node. We can consider **leaf** inference $\xi(p) = \arg\max_{y \in \mathcal{L}} p(y)$, but this will never select an internal node. We propose **confidence threshold** inference, taking the maximum-information node

$$\xi_\tau(p) = \arg\max_{y \in \mathcal{Y}} I(y) \quad \text{subject to} \quad p(y) > \tau . \qquad (4)$$

When $\tau \geq 0.5$ and p satisfies (1), there is a single path in the tree whose nodes satisfy the threshold, *i.e.* $p(y) > \tau \iff y \in \mathcal{A}(\hat{y})$. Inference can therefore be performed by traversing down from the root and the maximizer is unique assuming that $I(y)$ is strictly increasing on the edges of the tree. While these properties are nice, we also entertain arbitrary p and $\tau < 0.5$ in the remainder of the paper. We refer to the special case of $\tau = 0.5$ as **majority** inference. Rather than consider a single threshold τ, we propose to study the *operating characteristic curve* in the following section.

Two straightforward variants are **plurality** inference, which instead seeks the maximum-information label which is more likely than any other non-ancestor, and **information threshold** inference, which reverses the roles of the terms to instead maximize $p(y)$ subject to $I(y) \geq \zeta$. While the latter can also generate an operating curve, it does not provide adaptive specificity according to confidence.

Deng et al. [11] proposed an inference rule that maximizes the augmented expected information

$$\xi_\lambda(p) = \arg\max_{y \in \mathcal{Y}} (I(y) + \lambda)p(y) \qquad (5)$$

with the factor $\lambda \geq 0$ chosen by bisection to yield the desired accuracy on a held-out set. Each value of λ represents a particular balance between expected information $I(y)p(y)$ and confidence $p(y)$. As $\lambda \to \infty$, the maximizer eventually becomes the root node, which maximizes $p(y)$. Although $p(y)$ and $I(y)$ are monotonic with respect to depth (decreasing and increasing, respectively), there is no such guarantee for the product $I(y)p(y)$, and therefore an increase in λ is not guaranteed to move the prediction towards the root. For $\lambda = 0$, we call this **expected information** inference.

Karthik et al. [20] and Deng et al. [9] proposed **conditional risk minimization (CRM)** for the MLNP setting. This selects the leaf-node label $\hat{y}$ to minimize the expected cost $\mathbb{E}[C(Y, \hat{y})]$ with $Y \sim p(\cdot|x)$ being a random leaf node whose distribution is the predicted conditional likelihood

$$\xi(p) = \arg\min_{y \in \mathcal{L}} \sum_{u \in \mathcal{L}} C(u, y) p(u) . \qquad (6)$$

When p satisfies (1), we extend CRM to predict non-leaf nodes by performing both the optimization and the expectation over *all* nodes $\mathcal{Y}$ using the exclusive likelihood $\tilde{p}(y)$ of a node and *not* its children

$$\xi(p) = \arg\min_{y \in \mathcal{Y}} \sum_{u \in \mathcal{Y}} C(u, y) \tilde{p}(u) , \qquad \tilde{p}(u) = p(u) - \sum_{v \in \mathcal{C}(u)} p(v) . \qquad (7)$$

We choose $C(y, \hat{y}) = -\text{Correct}(y, \hat{y})I(\hat{y})$ to maximize the expected correct information of $\hat{y}$.

4.2 Loss functions and likelihood parameterizations

We first present existing loss functions before introducing our novel loss functions. The most straightforward approach is a **flat softmax** classifier over the leaf nodes with a parameter vector θ in $\mathbb{R}^{\mathcal{L}}$. The likelihood of internal nodes is obtained as a recursive sum

$$q_y(\theta) = \frac{\exp \theta_y}{\sum_{u \in \mathcal{L}} \exp \theta_y}, \quad y \in \mathcal{L} \qquad q_y(\theta) = \sum_{v \in \mathcal{C}(y)} q_v(\theta), \quad y \notin \mathcal{L}. \qquad (8)$$

The NLL is the familiar cross-entropy loss when the ground-truth label is a leaf node. However, it is non-convex when the label is an internal node, resembling a Multiple Instance Learning loss [22].

$$\ell(y, \theta) = -\log q_y(\theta) = \begin{cases} -\theta_y + \log \sum_{u \in \mathcal{L}} \exp \theta_u = \mathrm{CE}_{\mathcal{L}}(y, \theta) & y \in \mathcal{L} \text{ (convex)} \\ -\log \sum_{u \in \mathcal{L}(y)} \exp \theta_u + \log \sum_{u \in \mathcal{L}} \exp \theta_u & y \notin \mathcal{L} \text{ (non-convex)} \end{cases} \qquad (9)$$

Bertinetto et al. [2] proposed an alternative loss function for the same parameterization. Their **Hierarchical Cross Entropy (HXE)** loss places geometrically decreasing weight on the conditional distribution of deeper nodes given their parents. To define the (non-convex) loss, let $\gamma = e^{-\alpha} \leq 1$ be a discount factor and let $\omega_0, \ldots, \omega_{d(y)} \in \mathcal{Y}$ denote the ordered ancestors of y in

$$\ell_\alpha(y, \theta) = \sum_{k=1}^{d(y)} -\gamma^{k-1} \log \hat{p}_\theta(\omega_k | \omega_{k-1}) = \sum_{k=1}^{d(y)} \gamma^{k-1} \left[-\log \sum_{u \in \mathcal{L}(\omega_k)} \exp \theta_u + \log \sum_{u \in \mathcal{L}(\omega_{k-1})} \exp \theta_u \right]. \qquad (10)$$

Besides the flat softmax, another naïve baseline which is unaware of the hierarchy is a **multi-label sigmoid** classifier; that is, independent binary logistic regression per node. The likelihoods are parameterized by a vector θ in $\mathbb{R}^{\mathcal{Y}}$ according to $q_y(\theta) = \sigma(\theta_y) = 1/(1 + \exp(-\theta_y))$, which is not guaranteed to satisfy (1). We adopt the Focal Loss [23] since the binary problems are imbalanced:

$$\ell_{\alpha,\gamma}(y, p) = \sum_{u \in \mathcal{Y}} \mathrm{FL}_{\alpha,\gamma}([u \subseteq y], \sigma(\theta_u)), \quad \mathrm{FL}_{\alpha,\gamma}(y, p) = \begin{cases} -\alpha(1-p)^\gamma \log p, & y = 1 \\ -(1-\alpha)p^\gamma \log(1-p), & y = 0. \end{cases}$$

Redmon and Farhadi [31] introduced the **conditional softmax** classifier, which uses a separate softmax for the conditional distribution over each internal node's children. The parameter vector θ is in $\mathbb{R}^{\mathcal{Y} \setminus \{\mathbf{r}\}}$ and the likelihood of each node is obtained as a top-down product, with $p(\mathbf{r}|x) = 1$

$$p(v|u, x) = q_{v|u}(\theta) = \frac{\exp \theta_v}{\sum_{v' \in \mathcal{C}(u)} \exp \theta_{v'}}, \qquad p(y|x) = q_y(\theta) = \prod_{u \in \mathcal{A}(y) \setminus \{\mathbf{r}\}} q_{u|\pi(u)}(\theta). \qquad (11)$$

The NLL of this parameterization is a sum of cross-entropy losses, convex for any label $y \in \mathcal{Y}$:

$$\ell(y, \theta) = -\log q_y(\theta) = \sum_{u \in \mathcal{A}(y) \setminus \mathbf{r}} \mathrm{CE}_{\mathcal{S}(u)}(u, \theta) \qquad (12)$$

Brust and Denzler [4] similarly proposed a **conditional sigmoid** classifier for the more general problem of multi-path labels in a DAG hierarchy. We adapt this for a tree by replacing $q_{v|u}(\theta) = \sigma(\theta_v)$ above. This ensures that parents are more likely than each child, but does not guarantee the condition in (1). Their proposed loss function is Binary Cross Entropy for children of ancestors of the label:

$$\ell(y, \theta) = \sum_{u \in \mathcal{A}(y)} \sum_{v \in \mathcal{C}(u)} \mathrm{BCE}([v \supseteq y], \sigma(\theta_v)), \quad \mathrm{BCE}(y, p) = \begin{cases} -\log p, & y = 1 \\ -\log(1-p), & y = 0. \end{cases} \qquad (13)$$

Wu et al. [38] proposed the **Deep Realistic Taxonomic Classifier (Deep RTC)** based on the idea of parameter inheritance [32, 34]. A score for each class is obtained as the sum of individual scores of its ancestors $\beta_y = \sum_{u \in \mathcal{A}(y)} \theta_u$ and inference involves traversing down from the root until encountering a node with score less than zero. The model is optimized using softmax cross-entropy. To ensure that internal nodes get a positive score even when all annotations are leaf nodes, the loss is computed at a random cut obtained by terminating at each node with a fixed probability. While the original definition did not provide a normalized conditional distribution $p(y|x)$, we propose a **sigmoid variant** that uses the total score of each node $q_y(\theta) = \sigma(\beta_y)$ and is more faithful to the original, as well as a **softmax variant** that uses the total scores of only the leaf nodes to construct a proper distribution.

We now introduce our new loss functions for hierarchical classification. The first is the **soft-max-descendant** classifier, which is similar to the flat softmax except that it has scores $\theta \in \mathbb{R}^{\mathcal{Y} \setminus \{\mathbf{r}\}}$ for

internal nodes as well as leaf nodes. The motivation is to permit the model to recognise internal nodes in and of themselves, with the evidence for a class varying *like* the maximum over its descendants

$$q_y(\theta) = \frac{\sum_{u \in \mathcal{D}(y)} \exp \theta_u}{\sum_{v \in \mathcal{L}} \exp \theta_v}, \qquad \log q_y(\theta) \propto \log \sum_{u \in \mathcal{D}(y)} \exp \theta_u \sim \max_{u \in \mathcal{D}(y)} \theta_u . \tag{14}$$

If we simply minimize the NLL, the loss would be non-convex and the scores of internal nodes may have little incentive to be increased. We therefore propose the loss function

$$\ell(y, \theta) = \sum_{u \in \mathcal{A}(y)} \frac{1}{|\mathcal{L}(u)|} \, \text{CE}_{\{u\} \cup \mathcal{N}(u)}(u, \theta) \tag{15}$$

where $\mathcal{N}(y) = \mathcal{Y} \setminus (\mathcal{A}(y) \cup \mathcal{D}(y))$ is the set of negative labels for y; that is, labels which are neither ancestors nor descendants. Normalization is necessary to prevent higher-level nodes from dominating. Finally, inspired by recent work [25], we propose a **soft-max-margin** loss for the same parameterization. This is a soft version of the structured hinge loss [35], defined in [29, 15, 13] as:

$$\ell(y, \theta) = \text{CE}_{\mathcal{Y}}(y, \theta + \alpha C(y, \cdot)) = \log \left(1 + \sum_{y' \in \mathcal{Y} \setminus \{y\}} \exp\{\theta_{y'} - \theta_y + \alpha C(y, y')\} \right) \tag{16}$$

with $C(y, y')$ being the desired margin of y from y'. We adopt $C(y, y') = 1 - \text{Correct}(y, y')$ to seek greater separation of the ground-truth label from incorrect classes than from correct classes. While the "hard" structured hinge loss is also convex, we were unable to use it to train a deep model to high accuracy. We set $\alpha = 5$ in all experiments.

5   Operating characteristic curve

Given a classifier that predicts a conditional distribution over the class hierarchy, the set of predictions that can be attained using confidence-threshold inference with *any* value of τ is the Pareto set

$$\mathcal{H}(p(\cdot|x)) = \{y \in \mathcal{Y} : \nexists u (p(u|x) > p(y|x) \wedge I(u) > I(y))\} . \tag{17}$$

For a single example (x, y), let us define the sequence $\hat{y}_0, \dots, \hat{y}_{K-1}$ to denote the elements of the Pareto set ordered such that $p(\hat{y}_k|x) \geq p(\hat{y}_{k+1}|x)$ and $I(\hat{y}_k) \leq I(\hat{y}_{k+1})$. Further let $c_k = p(\hat{y}_k|x)$ denote the corresponding confidence such that the prediction is a piecewise-continuous function of τ with $\hat{y}(\tau) = \hat{y}_k$ for $c_k > \tau \geq c_{k+1}$. The value of any metric $M(y, \hat{y}(\tau))$ is also a piecewise-continuous function of τ, taking values $z_k = M(y, \hat{y}_k)$.

The cumulative metric $Z(\tau)$ for a set of examples $\{(x^i, y^i)\}_i$ is a sum of piecewise-constant functions $M(y^i, \hat{y}^i(\tau))$ and therefore piecewise-constant itself, with the form $Z(\tau) = Z_j$ for $C_j > \tau \geq C_{j+1}$. The values of Z_j and C_j can be obtained by introducing $\delta_k^i = z_k^i - z_{k-1}^i$ and reordering sums:

$$Z(\tau) = \sum_i M(y^i, \hat{y}^i(\tau)) = \sum_i (z_0^i + \sum_{k : c_k^i > \tau} \delta_k^i) = \sum_i z_0^i + \sum_{(i,k) : c_k^i > \tau} \delta_k^i . \tag{18}$$

Therefore Z_j is obtained as a partial sum $Z_j = Z_0 + \sum_{u=1}^{j} \Delta_u$ with $Z_0 = \sum_i z_0^i$ and the sequences C_j and Δ_j obtained by merging the ordered lists of (c_k^i, δ_k^i) pairs to be descending in c. The following section will compare different loss functions using the curves of correctness and specificity metrics.

The ordered Pareto set for a single example can be obtained in $O(|\mathcal{Y}| \log |\mathcal{Y}|)$ time. For arbitrary p and I, the worst-case running time for a dataset of size N is $O(N|\mathcal{Y}|(\log N + \log |\mathcal{Y}|))$, although each Pareto set can be computed independently in parallel. If we assume that the tree is relatively balanced, $p(\cdot|x)$ satisfies (1) and restrict ourselves to $\tau \in [0.5, 1]$, then the size of the set is bounded by the maximum depth of the tree, which is $O(\log |\mathcal{Y}|)$. This results in a running time of $O(N|\mathcal{Y}| \log |\mathcal{Y}|)$ to find the Pareto sets and $O(N \log N \log |\mathcal{Y}|)$ to merge the sequences. Otherwise, ensuring that all leaf nodes have equal information guarantees that the Pareto set contains at most one leaf node, reducing the worst-case merge time by a factor of $1 - |\mathcal{L}|/|\mathcal{Y}|$.

6   Empirical study

We now apply this technique to compare different loss functions. Most experiments consider image classification on the iNat21-Mini dataset [36], containing 50 examples each for 10,000 biological species in a seven-level taxonomy. All examples have leaf-node (full-depth) annotation. For all iNat21 experiments, we use a ResNet-18 model [19] with input images of size 224×224. We start

Figure 1: Correctness-specificity trade-offs for different methods and metrics on the iNat21 validation set. Markers indicates operating points obtained by inference functions. Comparing methods using single operating points would not provide a complete perspective. The dashed line is the part of the curve with threshold below 0.5. The shaded areas depict two standard deviations to either side.

Table 1: Overall metrics derived from operating curves on the iNat21 validation set. Average Precision (AP) and Average Correct (AC) are integrals with respect to Recall, while R@XC indicates Recall at X% Correct. All precision and recall metrics use information as the specificity measure (not depth). The error ranges are two standard deviations.

| % | From operating curves | | | | Majority | Leaf |
	AP	AC	R@90C	R@95C	F_1	F_1
Flat	66.90 ±0.16	64.71 ±0.18	52.44 ±0.42	45.88 ±0.30	63.68 ±0.19	69.86 ±0.13
Multilabel focal	57.56	53.25	32.84	26.94	63.30	63.80
Cond softmax [31]	60.72 ±0.11	57.47 ±0.13	42.03 ±0.12	35.71 ±0.20	58.54 ±0.20	65.27 ±0.11
Cond sigmoid [4]	60.64 ±0.17	57.13 ±0.16	40.52 ±0.13	34.29 ±0.18	56.73 ±0.07	65.52 ±0.19
Deep RTC [38] (sigmoid)	66.13	60.88	31.50	17.49	**71.64**	**71.64**
Deep RTC [38] (softmax)	**68.78**	**66.76**	55.53	48.99	67.96	*71.53*
Soft-max-descendant	66.46 ±0.37	64.19 ±0.39	49.15 ±0.36	43.29 ±0.56	60.99 ±0.33	70.01 ±0.33
Soft-max-margin	*67.63* ±0.25	*65.97* ±0.26	**56.53** ±0.28	**50.65** ±0.41	67.92 ±0.27	69.89 ±0.24

from the Pytorch ImageNet-pretrained checkpoint [28] and train for 20 epochs using SGD with momentum 0.9, cosine schedule [24], batch size 64, initial learning rate 0.01 and weight decay 0.0003. Most experiments were conducted on a single machine with one Nvidia A6000 GPU. Each epoch of iNat21-Mini takes about 20 minutes (5-8 minibatches per second). To obtain error-bars, we used a second, larger machine with 8 Nvidia V100 GPUs that was shared with other users. The code was implemented using the Pytorch library [28] and will be released under an MIT license.

6.1 Operating characteristic curves

Our main experiment trains and evaluates each of the methods on the iNat21-Mini dataset to obtain operating curves. The results presented here are $\mu \pm 2\sigma$ from five trials[1] with different random seeds. Figure 1 presents curves for precision-vs-recall and correct-vs-exact. The most striking observation is that all methods except Deep RTC [38] and our soft-max-margin loss are effectively dominated by the flat softmax classifier at all operating points. For the precision-recall trade-off, Deep RTC (with softmax) is the best at high recall and soft-max-margin is the best at high precision. The soft-max-margin has a distinct advantage in the correct-exact trade-off. The least effective method is the binary multilabel baseline, followed by the two approaches that learn top-down conditional distributions [31, 4]. The singular operating points achieved by different inference methods are also depicted in the figure, with the operating curve always containing majority inference and leaf inference as special cases. For parameterizations $p(\cdot|x) = q(\theta)$ that respect the hierarchy, specificity and correctness should be monotonic in τ for $\tau > 0.5$, and a dashed line is used for the segment with $\tau < 0.5$. It is observed that plurality inference enables more-specific predictions than majority inference, but it is often below the operating curve. In fact, most inference methods lie on or below

---

[1]Only one trial could be performed for the multilabel focal loss and Deep RTC due to compute constraints. However, these fall well outside of the range of the other methods, enabling rejection of the null hypothesis.

Figure 2: ImageNet-1k operating curves for (left) ResNet-50 from scratch and (right) linear model with CLIP ViT-B/32 features.

Table 2: iNat21-Mini accuracy at level j when training at level i.

%	$j = 3$	4	5	6
$i = 3$	82.7			
4	85.2	60.7		
5	86.6	64.6	50.6	
6	86.9	68.2	56.8	44.6
7	**87.3**	**70.4**	**59.8**	**49.2**

% AP (wrt Recall)	All	Seen	Unseen
Flat	*59.2*	69.3	49.5
Cond softmax	57.3	63.4	*51.6*
Cond sigmoid	56.9	63.1	51.1
Deep RTC (sigmoid)	57.1	68.1	46.0
Deep RTC (softmax)	**61.3**	**70.6**	**52.3**
Soft-max-descendant	58.3	68.1	49.2
Soft-max-margin	59.1	*70.0*	48.3

% AC (wrt Exact)	All	Seen	Unseen
Flat	36.7	50.8	23.5
Cond softmax	31.0	38.9	24.1
Cond sigmoid	30.3	38.4	23.4
Deep RTC (sigmoid)	38.1	*51.2*	*25.3*
Deep RTC (softmax)	*38.2*	51.2	**26.4**
Soft-max-descendant	32.1	44.9	22.0
Soft-max-margin	**38.7**	**54.0**	23.9

Figure 3: Operating curves for the out-of-distribution experiment on iNat21, divided into examples from seen and unseen classes. The top-down methods (conditional softmax, conditional sigmoid) are much more competitive on unseen classes. The soft-max-margin is most effective on seen classes but Deep RTC with softmax normalization is the most robust.

the curve. Further enquiry is required to understand the cause of the "knot" observed in the curves for the soft-max-descendant method. Critically, the curves are much more useful than single operating points for the purposes of algorithm development and selection. Table 1 further presents several integral and intercept metrics obtained from the curves. For comparison, the F_1 metrics for majority and leaf inference are shown. Flat softmax, Deep RTC [38] and our proposed methods achieve the best results across all metrics, although Deep RTC is less effective in the intercept metrics, which measure recall at high rates of correctness.

Several of the proposed loss functions have additional hyper-parameters to specify. Figure 4 in the appendix examines the impact of (i) label smoothing in the flat softmax, (ii) focal loss parameters in the multilabel classifier, (iii) exponential discount in HXE [2] and (iii) cut probability in the Deep RTC loss [38]. Label smoothing and HXE include the flat softmax as a special case, and this was the optimal hyper-parameter choice in both cases. For this reason, they were excluded from our main experiment. The optimal cut probability for Deep RTC (sigmoid) was zero, meaning it reduces to a softmax loss with logits obtained by parameter inheritance. This was surprising, as it gives little incentive for the model to increase the scores of the internal nodes.

We conducted additional experiments with a subset of loss functions on ImageNet-1k using the hierarchy of [2], training a ResNet-50 model from scratch. Figure 2 presents operating curves for this experiment. The trends are consistent: our soft-max-margin method achieves a better trade-off than existing methods, Deep RTC (sigmoid) is strong at high recall but mediocre for high precision,

and the conditional softmax is worse than the flat softmax across the full range. We used the same training configuration except only trained for 15 epochs. Figure 2 also shows the impact of using each loss function to train a *linear* model on top of the feature representation of a CLIP [30] model with ViT-B/32 [12] architecture. The soft-max-margin still provides an improvement over the baseline, whereas the (non-)Deep RTC model with softmax normalization is mathematically equivalent to a flat softmax (but for weight decay). Compared to training from scratch, higher recall is achieved, presumably due the strong feature representation. However, the conditional softmax is much worse, suggesting that the high-level classes are less easily separated in this representation. The linear model was trained for 20 epochs with batch size 256, initial learning rate 0.1 and weight decay 10^{-5}.

6.2 Flat classifiers at different levels

It was unexpected that the conditional softmax would fail to out-perform the flat softmax at *any* operating point. One possible explanation is that the high-level classes are better learned using a union of low-level classifiers than a single high-level classifier because the latter effectively ignores the fine-grained annotations. To investigate this hypothesis, we trained flat models at each level of the hierarchy and compared the classifiers trained at level i with those trained at levels $i + 1$, $i + 2$ and so on, shown in Table 2. Classifiers trained at deeper levels consistently achieved higher accuracy, although with diminishing returns. This motivated the design of our proposed loss functions, which predict scores for low-level and high-level classes.

6.3 Unseen classes

We hypothesized that the parameterizations which explicitly estimate scores for internal nodes might achieve better generalization to examples from "unseen" classes, which belong to an internal node but not a leaf node. To evaluate the ability of models to correctly classify such examples, we randomly select half of the leaf nodes and remove them from the dataset *and* the hierarchy during training. At test time, examples from these classes were preserved with their labels projected onto the sub-tree.

Figure 3 presents the operating curves and integral metrics for the examples from seen and unseen classes. The conditional softmax [31] and conditional sigmoid [4] are much more competitive for unseen classes, although Deep RTC (softmax) remains the most effective. The soft-max-margin approach is excellent for seen classes and relatively poor for unseen classes, suggesting that it learns a highly tailored model that could be worse in an out-of-distribution setting. The soft-max-descendant approach is uncompetitive in both settings.

7 Conclusion

This work has presented a new approach for evaluating hierarchical classifiers for the prediction of non-leaf nodes. It was shown that the flat softmax classifier, despite having no knowledge of the hierarchy during training, is nonetheless a competitive baseline. Several novel loss functions were proposed, and the soft-max-margin loss was shown to out-perform several existing methods. On the other hand, the proposed soft-max-descendant losses were shown to be relatively ineffective. Surprisingly, top-down classifiers were found to be inferior across the entire operating range. Evidence suggests that this is due to the difficulty of learning a classifier to separate high-level classes without fine-grained supervision. The top-down classifiers were shown to be more effective on a synthetic out-of-distribution experiment, where recognition of internal-node classes is required.

One potential disadvantage of the soft-max-margin loss is that it requires the practitioner to choose the margin. Future work could investigate different margins, direct optimization of the area under the curve [3] or the impact of calibration [17]. It would also be interesting to compare the losses for long-tail learning in a class hierarchy, and to investigate other problems where the soft-max-margin loss could be applied. One limitation of using a fully-connected prediction layer is that it may not scale to millions of classes, where embeddings or metric learning are more suitable.

Social impact. While hierarchical classifiers may mitigate some of the risks of misclassification by their ability to fail gracefully, this may enable more widespread use of automatic classification or lead human users to place more trust in the system. Caution should always be exercised when employing automatic classification in consequential settings. A class hierarchy with *tree* structure may also encourage an oversimplified view of a problem due to the inability for classes to intersect.

References

[1] K. Ahmed, M. H. Baig, and L. Torresani. Network of experts for large-scale image categorization. In *European Conference on Computer Vision*, pages 516–532. Springer, 2016.

[2] L. Bertinetto, R. Mueller, K. Tertikas, S. Samangooei, and N. A. Lord. Making better mistakes: Leveraging class hierarchies with deep networks. In *CVPR*, pages 12506–12515, 2020.

[3] A. Brown, W. Xie, V. Kalogeiton, and A. Zisserman. Smooth-AP: Smoothing the path towards large-scale image retrieval. In *European Conference on Computer Vision*, pages 677–694. Springer, 2020.

[4] C.-A. Brust and J. Denzler. Integrating domain knowledge: using hierarchies to improve deep classifiers. In *Asian Conference on Pattern Recognition*, pages 3–16. Springer, 2019.

[5] L. Cai and T. Hofmann. Hierarchical document categorization with support vector machines. In *Proceedings of the Thirteenth ACM International Conference on Information and Knowledge Management*, pages 78–87, 2004.

[6] E. Costa, A. Lorena, A. Carvalho, and A. Freitas. A review of performance evaluation measures for hierarchical classifiers. In *Evaluation Methods for Machine Learning II: Papers from the AAAI-2007 workshop*, pages 1–6, 2007.

[7] J. Davis, T. Liang, J. Enouen, and R. Ilin. Hierarchical semantic labeling with adaptive confidence. In *International Symposium on Visual Computing*, pages 169–183. Springer, 2019.

[8] J. Davis, T. Liang, J. Enouen, and R. Ilin. Hierarchical classification with confidence using generalized logits. In *ICPR*, pages 1874–1881. IEEE, 2021.

[9] J. Deng, A. C. Berg, K. Li, and L. Fei-Fei. What does classifying more than 10,000 image categories tell us? In *European Conference on Computer Vision*, pages 71–84. Springer, 2010.

[10] J. Deng, W. Dong, R. Socher, L.-J. Li, K. Li, and L. Fei-Fei. ImageNet: A large-scale hierarchical image database. In *2009 IEEE Conference on Computer Vision and Pattern Recognition*, pages 248–255. Ieee, 2009.

[11] J. Deng, J. Krause, A. C. Berg, and L. Fei-Fei. Hedging your bets: Optimizing accuracy-specificity trade-offs in large scale visual recognition. In *2012 IEEE Conference on Computer Vision and Pattern Recognition*, pages 3450–3457. IEEE, 2012.

[12] A. Dosovitskiy, L. Beyer, A. Kolesnikov, D. Weissenborn, X. Zhai, T. Unterthiner, M. Dehghani, M. Minderer, G. Heigold, S. Gelly, et al. An image is worth 16x16 words: Transformers for image recognition at scale. In *International Conference on Learning Representations*, 2021.

[13] S. Edunov, M. Ott, M. Auli, D. Grangier, and M. Ranzato. Classical structured prediction losses for sequence to sequence learning. In *Proceedings of the 2018 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long Papers)*, pages 355–364, 2018.

[14] T. Gao and D. Koller. Discriminative learning of relaxed hierarchy for large-scale visual recognition. In *2011 International Conference on Computer Vision*, pages 2072–2079. IEEE, 2011.

[15] K. Gimpel and N. A. Smith. Softmax-margin CRFs: Training log-linear models with cost functions. In *Human Language Technologies: The 2010 Annual Conference of the North American Chapter of the Association for Computational Linguistics*, pages 733–736, 2010.

[16] G. Griffin and P. Perona. Learning and using taxonomies for fast visual categorization. In *2008 IEEE Conference on Computer Vision and Pattern Recognition*, pages 1–8. IEEE, 2008.

[17] C. Guo, G. Pleiss, Y. Sun, and K. Q. Weinberger. On calibration of modern neural networks. In *International Conference on Machine Learning*, pages 1321–1330. PMLR, 2017.

[18] Y. Guo, Y. Liu, E. M. Bakker, Y. Guo, and M. S. Lew. CNN-RNN: A large-scale hierarchical image classification framework. *Multimedia Tools and Applications*, 77(8):10251–10271, 2018.

[19] K. He, X. Zhang, S. Ren, and J. Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 770–778, 2016.

[20] S. Karthik, A. Prabhu, P. K. Dokania, and V. Gandhi. No cost likelihood manipulation at test time for making better mistakes in deep networks. In *International Conference on Learning Representations*, 2021.

[21] A. Kosmopoulos, I. Partalas, E. Gaussier, G. Paliouras, and I. Androutsopoulos. Evaluation measures for hierarchical classification: a unified view and novel approaches. *Data Mining and Knowledge Discovery*, 29(3):820–865, 2015.

[22] O. Z. Kraus, J. L. Ba, and B. J. Frey. Classifying and segmenting microscopy images with deep multiple instance learning. *Bioinformatics*, 32(12):i52–i59, 2016.

[23] T.-Y. Lin, P. Goyal, R. Girshick, K. He, and P. Dollár. Focal loss for dense object detection. In *Proceedings of the IEEE International Conference on Computer Vision*, pages 2980–2988, 2017.

[24] I. Loshchilov and F. Hutter. SGDR: Stochastic gradient descent with warm restarts. In *International Conference on Learning Representations*, 2017.

[25] A. K. Menon, S. Jayasumana, A. S. Rawat, H. Jain, A. Veit, and S. Kumar. Long-tail learning via logit adjustment. In *International Conference on Learning Representations*, 2020.

[26] F. Morin and Y. Bengio. Hierarchical probabilistic neural network language model. In *AISTATS*, volume 5, pages 246–252. Citeseer, 2005.

[27] R. Müller, S. Kornblith, and G. E. Hinton. When does label smoothing help? *Advances in Neural Information Processing Systems*, 32, 2019.

[28] A. Paszke, S. Gross, F. Massa, A. Lerer, J. Bradbury, G. Chanan, T. Killeen, Z. Lin, N. Gimelshein, L. Antiga, et al. Pytorch: An imperative style, high-performance deep learning library. *Advances in Neural Information Processing Systems*, 32, 2019.

[29] P. Pletscher, C. S. Ong, and J. M. Buhmann. Entropy and margin maximization for structured output learning. In *Joint European Conference on Machine Learning and Knowledge Discovery in Databases*, pages 83–98. Springer, 2010.

[30] A. Radford, J. W. Kim, C. Hallacy, A. Ramesh, G. Goh, S. Agarwal, G. Sastry, A. Askell, P. Mishkin, J. Clark, et al. Learning transferable visual models from natural language supervision. In *International Conference on Machine Learning*, pages 8748–8763. PMLR, 2021.

[31] J. Redmon and A. Farhadi. Yolo9000: Better, faster, stronger. In *CVPR*, pages 7263–7271, 2017.

[32] R. Salakhutdinov, A. Torralba, and J. Tenenbaum. Learning to share visual appearance for multiclass object detection. In *CVPR 2011*, pages 1481–1488. IEEE, 2011.

[33] C. N. Silla and A. A. Freitas. A survey of hierarchical classification across different application domains. *Data Mining and Knowledge Discovery*, 22(1):31–72, 2011.

[34] M. Sun, W. Huang, and S. Savarese. Find the best path: An efficient and accurate classifier for image hierarchies. In *Proceedings of the IEEE International Conference on Computer Vision*, pages 265–272, 2013.

[35] I. Tsochantaridis, T. Hofmann, T. Joachims, and Y. Altun. Support vector machine learning for interdependent and structured output spaces. In *Proceedings of the Twenty-First International Conference on Machine Learning*, page 104, 2004.

[36] G. Van Horn, E. Cole, S. Beery, K. Wilber, S. Belongie, and O. Mac Aodha. Benchmarking representation learning for natural world image collections. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 12884–12893, 2021.

[37] C. Wu, M. Tygert, and Y. LeCun. A hierarchical loss and its problems when classifying non-hierarchically. *PLOS ONE*, 14(12):e0226222, 2019.

[38] T.-Y. Wu, P. Morgado, P. Wang, C.-H. Ho, and N. Vasconcelos. Solving long-tailed recognition with deep realistic taxonomic classifier. In *ECCV*, pages 171–189. Springer, 2020.

[39] Z. Wu and M. Palmer. Verb semantics and lexical selection. *arXiv preprint cmp-lg/9406033*, 1994.

[40] Z. Yan, H. Zhang, R. Piramuthu, V. Jagadeesh, D. DeCoste, W. Di, and Y. Yu. HD-CNN: hierarchical deep convolutional neural networks for large scale visual recognition. In *Proceedings of the IEEE International Conference on Computer Vision*, pages 2740–2748, 2015.

[41] H. Zhao, X. Puig, B. Zhou, S. Fidler, and A. Torralba. Open vocabulary scene parsing. In *Proceedings of the IEEE International Conference on Computer Vision*, pages 2002–2010, 2017.

[42] X. Zhu and M. Bain. B-CNN: Branch convolutional neural network for hierarchical classification. *arXiv preprint arXiv:1709.09890*, 2017.