VFEM: Visual Feature Empowered Multivariate Time Series Forecasting with Cross-Modal Fusion

Abstract

Large time series foundation models often adopt channel-independent architectures to handle varying data dimensions, but this design ignores crucial cross-channel dependencies. Meanwhile, existing cross-modal methods predominantly rely on textual modalities, leaving the spatial pattern recognition capabilities of vision models underexplored for time series analysis. To address these limitations, we propose VFEM, a cross-modal forecasting model that leverages pre-trained large vision models (LVMs) to capture complex cross-variable patterns. VFEM transforms multivariate time series into visual representations, enabling LVMs to perceive spatial relationships that are not explicitly modeled by channel-independent models. Through a dual-branch architecture, visual and temporal features are independently extracted and then fused via cross-modal attention, allowing complementary information from both modalities to enhance forecasting. By freezing the LVM and training only 7.45% of the total parameters, VFEM achieves competitive performance on multiple benchmarks, offering a new perspective on multivariate time series forecasting.

1 Introduction

Time series forecasting has been widely applied in diverse settings such as weather, power systems, transportation, and finance Allen et al. (2025); Wu et al. (2021b); Liu et al. (2023); Yi et al. (2023). These scenarios often involve a wide variety of temporal data, where different time series frequently exhibit intricate interrelationships. Early time series forecasting methods focus on statistical models and signal processing techniques like decomposition Wu et al. (2021a; 2022) and frequency analysis Zhou et al. (2022). With the development of deep learning, many studies improve prediction by fusing information across both variable and temporal dimensions Zhang & Yan (2023); donghao & wang xue (2024); Nie et al. (2023); Wang et al. (2023). The emergence of large foundation models Ansari et al. (2024); Woo et al. (2024); Liu et al. (2024b); Goswami et al. (2024); Darlow et al. has further advanced the field, leveraging pretrained architectures to achieve strong zero-shot or few-shot forecasting performance.

However, several issues remain unresolved Tan et al. (2024). Firstly, the channel-independent architecture is commonly adopted in large time series models. While this design allows the model to handle varying numbers of variables across datasets, it does not explicitly model the correlations among different variables that could enhance forecasting accuracy. Although some studies Woo et al. (2024); Liu et al. (2024b) employ channel-dependent designs, they require full-parameter training on large-scale time series datasets, which entails substantial data requirements and computational costs. Despite this, such models may not fully capture the distinct cross-variable dependency patterns inherent to time series from different domains, and flattening multivariate series into a univariate sequence can obscure cross-channel patterns.

Secondly, previous cross-modal fusion methods have predominantly relied on textual modalities to provide auxiliary temporal information Jin et al. (2024); Cao et al. (2024); Sun et al. (2023); Liu et al. (2024a; 2025a). While these text-based approaches have achieved notable success, they have not fully leveraged the spatial pattern recognition capabilities inherent in vision models. Multivariate time series, when rendered as 2D images, can exhibit visual patterns—such as periodicity, lead-lag relationships, and anomalous events—that vision models are well-suited to recognize (Figure 1). Recent work like VisionTS Chen et al. (2025)

has begun to explore this direction. While it demonstrates the potential of vision models, it follows a channel-independent design without cross-modal fusion, leaving room for further exploration in cross-modal integration and cross-variable dependency modeling.

To address these challenges, we propose VFEM, a cross-modal forecasting framework with dual branches: a visual branch that transforms time series into 2D representations and extracts spatial patterns via a pretrained vision encoder, and a temporal branch that models sequential dependencies through self-attention. Features from both branches are concatenated and jointly processed through self-attention layers to capture cross-modal interactions. Experiments validate the effectiveness of our design and demonstrate competitive forecasting performance. This work makes three main contributions:

- We propose a cross-modal framework that transforms multivariate time series into visual representations, enabling pretrained vision models to perceive cross-channel spatial patterns. This design handles arbitrary variable dimensions while capturing complex inter-variable dependencies.

- We freeze the vision encoder and train only 7.45% of total parameters. Ablation studies validate this training strategy, and t-SNE visualization shows that the vision encoder can capture meaningful time series representations.

- Through cross-modal fusion of visual and temporal branches, VFEM achieves competitive forecasting performance on multiple benchmarks, demonstrating the effectiveness of the proposed design.

2 Related Work

2.1 Time Series Foundation Models

The emergence of foundation models has transformed time series forecasting. GPT4TS Zhou et al. (2023) demonstrates that pretrained language model weights can transfer to temporal domains. Building on this, Chronos Ansari et al. (2024) introduces a tokenization scheme for probabilistic forecasting, achieving strong zero-shot performance. Moirai Woo et al. (2024) and Timer Liu et al. (2024b) propose unified frameworks pretrained on large-scale time series corpora, while MOMENT Goswami et al. (2024) and DAM Darlow et al. explore diverse pretraining strategies.

A critical architectural choice in these models is the treatment of multivariate series. Most foundation models adopt channel-independent designs, processing each variable separately to handle arbitrary input dimensions. While this enables zero-shot generalization, it does not explicitly model cross-variable dependencies that can be beneficial for forecasting. Channel-dependent alternatives like Moirai require large-scale pretraining, and may not fully capture domain-specific inter-variable patterns. Our work explores an alternative approach by leveraging visual representations that naturally encode spatial relationships between variables.

2.2 Cross-Modal Methods for Time Series

Cross-modal learning has emerged as a promising direction for enhancing time series models with knowledge from pretrained foundation models. The majority of existing approaches focus on the textual modality.

TimeLLM Jin et al. (2024) pioneers the reprogramming paradigm, transforming time series into text-like representations for frozen LLMs. TEMPO Cao et al. (2024) uses prompts to guide LLMs in decomposing time series into trend and seasonal components. TEST Sun et al. (2023) aligns time series embeddings with text prototypes, while UniTime Liu et al. (2024a) incorporates domain-specific instructions for multi-domain forecasting. TimeCMA Liu et al. (2025a) introduces explicit cross-modality alignment objectives.

While text-based methods have achieved notable success, they primarily leverage LLMs' semantic understanding and reasoning capabilities. The visual modality offers complementary strengths: spatial pattern recognition, local-global feature extraction, and inherent 2D structure that naturally aligns with multivariate time series. VisionTS Chen et al. (2025) demonstrates this potential by reformulating forecasting as masked image reconstruction, showing that visual masked autoencoders pretrained on ImageNet can achieve competitive zero-shot performance.

These vision-based approaches process each channel independently and focus mainly on univariate scenarios. The potential to capture spatial relationships between multiple variables arranged in a 2D image remains unexplored. VFEM attempts to explore this direction by rendering multivariate series as images where rows represent variables and columns represent time steps, enabling vision models to perceive cross-variable patterns. Unlike existing vision-based methods, VFEM adopts a cross-modal fusion design that combines visual features with temporal representations, allowing complementary information from both modalities to enhance forecasting.

2.3 Multivariate Dependency Modeling

Capturing cross-variable dependencies remains an important challenge in multivariate forecasting. Crossformer Zhang & Yan (2023) introduces a two-stage attention mechanism for temporal and cross-variable modeling. iTransformer Liu et al. (2023) inverts the attention paradigm, treating variables as tokens, while ModernTCN donghao & wang xue (2024) uses large-kernel convolutions to capture cross-channel patterns.

These approaches rely on learned weights to discover variable relationships from training data. VFEM takes a different approach by utilizing pretrained visual knowledge for cross-variable modeling. Visual patterns in rendered time series—color gradients, periodic stripes, correlation structures—share similarities with natural image patterns, which can be helpful for knowledge transfer from pretrained vision models.

Figure 1: Clear Patterns in Electricity and Traffic Time Series Visualization: Periodicity, Lead-Lag Relationships, Anomalous Events.

3 Methods

3.1 Problem Formulation

Given a multivariate time series $\mathbf{X} \in \mathbb{R}^{L \times M}$ with look-back window length L and M variables, where $x_{t,m}$ denotes the value of variable $m \in \{1, \ldots, M\}$ at time step $t \in \{1, \ldots, L\}$, the forecasting task aims to predict the future values $\hat{\mathbf{Y}} \in \mathbb{R}^{F \times M}$ for the next F time steps. The objective is to learn a mapping $f_\theta : \mathbb{R}^{L \times M} \to \mathbb{R}^{F \times M}$ that minimizes the mean squared error:

$$\mathcal{L}(\theta) = \frac{1}{FM} \sum_{t=1}^{F} \sum_{m=1}^{M} (\hat{y}_{t,m} - y_{t,m})^2 \tag{1}$$

Our model processes the input through two parallel modality branches—visual and temporal—before fusing them for prediction. For the visual modality, we construct the input $\mathbf{X}_{vs} \in \mathbb{R}^{M \times L \times c}$ by treating the transposed time series matrix $\mathbf{X}^\top \in \mathbb{R}^{M \times L}$ as a single-channel intensity map and expanding it to a three-channel representation through channel replication, where $c = 3$:

$$\mathbf{X}_{vs}[:,:,c] = \mathbf{X}^\top, \quad c \in \{1, 2, 3\} \tag{2}$$

In this formulation, each element of the time series directly corresponds to a pixel intensity value, where rows represent variables and columns represent time steps. This conversion process is illustrated in Figure 3. As shown in Figure 3(c-d), the color-rendered visualization highlights value variations across variables and time, while the actual input uses grayscale replication to preserve the original intensity distribution without introducing artificial color mappings.

Figure 2: The overall architecture of VFEM. The model consists of two parallel branches: a visual branch that transforms time series into images and extracts features via a frozen vision encoder with projection layers, and a temporal branch that applies instance normalization followed by spatiotemporal self-attention. The outputs from both branches are concatenated and processed through a fusion encoder before the final prediction.

3.2 Visual Analysis of Multivariate Time Series

We first examine whether multivariate time series contain visually recognizable patterns. Figure 1 shows visualizations of the ECL (Electricity) and Traffic datasets. The values across different variables exhibit distinct color variations over time, revealing clear characteristics such as daily periodic changes.

In the upper subplot displaying ECL data, different variables exhibit distinct periodic characteristics. Some variables demonstrate brief yet pronounced peak patterns, while others display superimposed daily and weekly cycles. Certain variable pairs also maintain stable lead-lag relationships, which can help capture cross-variable dependencies. The Traffic dataset visualization in the lower subplot exhibits multi-period superimposed patterns. From the zoomed-in section, distinct diurnal (day-night) traffic flow variations can be observed. Significant differences exist between weekday and weekend patterns: weekdays show pronounced morning and evening rush hours, while weekends exhibit reduced congestion. Small holidays can also be identified, showing extended periods of reduced traffic lasting more than two days.

These patterns suggest that visual representations can capture meaningful information from multivariate time series, motivating the integration of temporal and spatial dimensions in our model design.

3.3 Model Architecture

As depicted in Figure 2, the VFEM model comprises three key stages: (1) unimodal feature extraction through independent visual and temporal processing branches, (2) cross-modal feature fusion via concatenation, and (3) a spatiotemporal Transformer encoder followed by a prediction layer. The overall forward process can be formulated as:

$$\hat{\mathbf{Y}} = \mathcal{F}_{\text{pred}} \left(\mathcal{F}_{\text{fuse}} \left([\mathbf{H}_{vs}; \mathbf{H}_{ts}] \right) \right) \tag{3}$$

where $[\cdot; \cdot]$ denotes concatenation along the feature dimension, $\mathbf{H}_{vs} \in \mathbb{R}^{M \times d}$ and $\mathbf{H}_{ts} \in \mathbb{R}^{M \times d}$ are the visual and temporal hidden states respectively, $\mathcal{F}_{\text{fuse}}$ represents the fusion encoder, and $\mathcal{F}_{\text{pred}}$ is the prediction layer.

3.4 Temporal Modality Processing

The temporal branch independently processes the raw time series through normalization and self-attention mechanisms.

Instance Normalization. Following the reversible instance normalization (RevIN) approach Kim et al. (2022), we normalize the input along the temporal dimension. For each variable m, we compute the mean and standard deviation from the last W time steps:

$$\mu_m = \frac{1}{W} \sum_{t=L-W+1}^{L} x_{t,m} \tag{4}$$

$$\sigma_m = \sqrt{\frac{1}{W} \sum_{t=L-W+1}^{L} (x_{t,m} - \mu_m)^2} \tag{5}$$

The entire sequence is then normalized using these statistics:

$$\tilde{x}_{t,m} = \frac{x_{t,m} - \mu_m}{\sigma_m + \epsilon}, \quad \forall t \in \{1, \ldots, L\} \tag{6}$$

where ϵ is a small constant for numerical stability. These statistics μ_m and σ_m are preserved and applied for denormalization after the cross-modal fusion stage, restoring the predictions to the original data scale. The normalized series $\tilde{\mathbf{X}} \in \mathbb{R}^{M \times L}$ preserves temporal patterns while removing distribution shift.

Temporal Self-Attention. The normalized series is processed through a spatiotemporal self-attention encoder. Given input $\mathbf{Z} \in \mathbb{R}^{M \times L}$, we first partition the temporal dimension into N_s segments of length $P = L/N_s$ and rearrange the tensor to interleave spatial and temporal dimensions:

$$\mathbf{Z}' = \text{Rearrange}(\mathbf{Z}) \in \mathbb{R}^{(P \cdot M) \times N_s} \tag{7}$$

This rearrangement enables attention to capture dependencies across both variables and time segments simultaneously. The query, key, and value representations are computed via MLP-based projections with residual connections:

$$\mathbf{Q} = f_Q(\mathbf{Z}'), \quad \mathbf{K} = f_K(\mathbf{Z}'), \quad \mathbf{V} = f_V(\mathbf{Z}') \tag{8}$$

where $f_Q, f_K, f_V : \mathbb{R}^{N_s} \to \mathbb{R}^{N_s}$ are two-layer MLPs. The attention output is computed as:

$$\text{Attn}(\mathbf{Q}, \mathbf{K}, \mathbf{V}) = \text{softmax}\left(\frac{\mathbf{Q}\mathbf{K}^\top}{\sqrt{N_s}}\right)\mathbf{V} \tag{9}$$

The encoder applies N_t layers, each containing two attention sublayers with residual connections. After processing, the output is rearranged back to the original shape:

$$\mathbf{Z}^{(l+1)} = \mathbf{Z}^{(l)} + \mathcal{E}^{(l)}(\mathbf{Z}^{(l)}), \quad l = 0, \ldots, N_t - 1 \tag{10}$$

with $\mathbf{Z}^{(0)} = \tilde{\mathbf{X}}$, where $\mathcal{E}^{(l)}$ denotes the l-th encoder layer. The output is projected to the hidden dimension:

$$\mathbf{H}_{ts} = \mathbf{Z}^{(N_t)}\mathbf{W}_{ts} \in \mathbb{R}^{M \times d} \tag{11}$$

where d is the unified hidden dimension.

3.5 Visual Modality Processing

The visual branch leverages a pretrained vision encoder to extract semantic representations from the constructed visual input. We employ SigLIP-2-base-NaFlex Tschannen et al. (2025), a vision-language model that supports flexible input resolutions, as the visual backbone. All parameters of the vision encoder remain frozen during training.

Image Encoding. The visual input $\mathbf{X}_{vs}$ is processed by the vision encoder to obtain a global image representation:

$$\mathbf{e}_{vs} = \mathcal{V}_{\text{enc}}(\mathbf{X}_{vs}) \in \mathbb{R}^{d_v} \tag{12}$$

where $\mathcal{V}_{\text{enc}}(\cdot)$ denotes the frozen vision encoder and d_v is the visual embedding dimension.

Figure 3: Visual input construction process. (a) Original multivariate time series $\mathbf{X} \in \mathbb{R}^{L \times M}$. (b) Transposed matrix $\mathbf{X}^\top \in \mathbb{R}^{M \times L}$ with variables as rows and time steps as columns. (c) Color-rendered visualization for demonstration, where value magnitudes are mapped to colors. (d) Actual input format: three-channel grayscale image $\mathbf{X}_{vs} \in \mathbb{R}^{M \times L \times c}$ with $c = 3$, created by replicating the transposed matrix across RGB channels.

Variable-wise Expansion. Since the vision model produces a single global embedding capturing the holistic patterns of the entire visual representation, we replicate this embedding across all M variables to enable each variable to access the shared visual context during cross-modal fusion:

$$\mathbf{E}_{vs} = \mathbf{1}_M \otimes \mathbf{e}_{vs} \in \mathbb{R}^{M \times d_v} \tag{13}$$

where $\mathbf{1}_M \in \mathbb{R}^M$ is an all-ones vector and $\otimes$ denotes the outer product.

Feature Projection. The expanded embedding is transformed through a learnable projection network to bridge the domain gap between pretrained visual features and time series representations. The projection includes residual connections:

$$\mathbf{H}'_{vs} = \phi(\mathbf{E}_{vs}\mathbf{W}_1)\mathbf{W}_2 + \mathbf{E}_{vs}\mathbf{W}_1 \tag{14}$$

where $\phi(\cdot)$ is the GELU activation function and $\mathbf{W}_1, \mathbf{W}_2 \in \mathbb{R}^{d_v \times d_v}$ are learnable matrices. The output is mapped to the hidden dimension:

$$\mathbf{H}_{vs} = \mathbf{H}'_{vs}\mathbf{W}_{vs} \in \mathbb{R}^{M \times d} \tag{15}$$

By freezing the vision encoder, the trainable parameters are reduced to only 30M, accounting for 7.45% of the total, as shown in Table 1.

3.6 Cross-Modal Fusion

After obtaining the visual and temporal hidden states from their respective branches, we perform cross-modal fusion by concatenating the representations:

$$\mathbf{H}_f = [\mathbf{H}_{vs}; \mathbf{H}_{ts}] \in \mathbb{R}^{M \times 2d} \tag{16}$$

Table 1: Parameter distribution in the VFEM model.

	Frozen Part	Trainable Part			
	Visual Encoder	Visual Projection	Temporal Encoder	Fusion Network	Total
Parameters	375M	1.8M	16M	12M	30M
Proportion	92.55%	0.45%	4.00%	3.00%	7.45%

The concatenated features are processed through a fusion encoder that shares the same attention structure as the temporal encoder, with N_f self-attention layers operating on the combined $2d$-dimensional features:

$$\mathbf{H}^{(l+1)} = \mathbf{H}^{(l)} + \text{Attn}^{(l)}(\mathbf{H}^{(l)}), \quad l = 0, \ldots, N_f - 1 \tag{17}$$

with $\mathbf{H}^{(0)} = \mathbf{H}_f$. Since the concatenated dimension contains features from both modalities, the attention mechanism models cross-modal interactions alongside cross-variable dependencies.

3.7 Prediction and Denormalization

The fusion encoder output is passed through a linear prediction layer:

$$\hat{\mathbf{Y}}_{\text{norm}} = \mathbf{H}^{(N_f)}\mathbf{W}_{\text{pred}} \in \mathbb{R}^{M \times F} \tag{18}$$

where $\mathbf{W}_{\text{pred}} \in \mathbb{R}^{2d \times F}$ projects the hidden representation to the forecast horizon.

Finally, we apply reverse instance normalization to recover the predictions in the original scale:

$$\hat{y}_{t,m} = \hat{y}_{t,m}^{\text{norm}} \cdot (\sigma_m + \epsilon) + \mu_m \tag{19}$$

where μ_m and σ_m are the per-variable statistics computed during input normalization.

4 Experiments

4.1 Setup

Since the number of variates in multivariate time series varies across different datasets, and the variable dimension and temporal dimension length of the input time series are often highly imbalanced, we adopt the encoder of SigLip2-base-Naflex Tschannen et al. (2025) as the backbone of the vision encoder, which allows arbitrary adjustment of image height and width ($d_v = 768$). During training, all parameters of the visual encoder are frozen, and only the remaining parts of VFEM are trained, with trainable parameters accounting for only 7.45% of the total parameters.

The key hyperparameters are configured as follows: input sequence length $L = 512$, prediction horizon $F \in \{96, 192, 336, 720\}$, normalization window $W = 512$, number of segments $N_s = 32$, hidden dimension $d = 1024$, number of temporal encoder layers $N_t = 1$, and number of fusion encoder layers $N_f = 1$. We use the Adam optimizer with learning rate 10^{-4} and train for 300 epochs with early stopping.

We select multiple competitive models as baselines, covering diverse approaches: large-scale foundation models (Chronos Ansari et al. (2024) and Moirai Woo et al. (2024) in both Base and Large versions), LLM-based cross-modal methods (GPT4TS Zhou et al. (2023)), and specialized time series architectures (UniTST Liu et al. (2025b), TimesNet Wu et al. (2022), PatchTST Nie et al. (2023)). For fair comparison, we adopt the results reported in each model's original publication, ensuring that all baselines operate under their optimal configurations. All experiments follow the same evaluation protocol with identical dataset splits and metrics. Experiments were conducted on 7 datasets, including ETTh1, ETTh2, ETTm1, ETTm2, Electricity, Weather, and Traffic. To ensure the robustness of results, each experiment was run 3 times with different random seeds. Chronos and Moirai did not report results on the Traffic dataset, as this dataset has an excessive number of variables.

Table 2: Forecasting results comparison. MSE and MAE are evaluated with prediction horizon $F \in \{96, 192, 336, 720\}$. Lower values are better. **Bold** denotes the best result, underline denotes the second best.

Models		VFEM		Chronos_{Base}		Chronos_{Large}		Moirai_{Base}		Moirai_{Large}		GPT4TS		UniTST		TimesNet		PatchTST	
Metric		MSE	MAE	MSE	MAE	MSE	MAE	MSE	MAE	MSE	MAE	MSE	MAE	MSE	MAE	MSE	MAE	MSE	MAE
ETTh1	96	**0.348**	**0.383**	0.440	0.393	0.441	0.390	0.376	0.392	0.381	0.388	0.376	0.397	0.383	0.398	0.452	0.463	0.404	0.413
	192	**0.383**	**0.405**	0.492	0.426	0.502	0.524	0.412	0.413	0.434	0.415	0.416	0.418	0.434	0.426	0.474	0.477	0.454	0.430
	336	**0.398**	**0.414**	0.550	0.462	0.576	0.467	0.433	0.428	0.485	0.445	0.442	0.433	0.471	0.445	0.493	0.489	0.497	0.462
	720	**0.401**	**0.434**	0.882	0.591	0.835	0.583	0.447	0.444	0.611	0.510	0.477	0.515	0.479	0.469	0.560	0.534	0.496	0.481
	Avg	**0.383**	**0.409**	0.591	0.468	0.589	0.491	0.417	0.419	0.478	0.440	0.428	0.441	0.442	0.435	0.495	0.491	0.463	0.447
ETTh2	96	**0.266**	**0.330**	0.308	0.343	0.320	0.345	0.294	**0.330**	0.296	**0.330**	0.285	0.342	0.292	0.342	0.340	0.374	0.312	0.358
	192	**0.328**	**0.369**	0.384	0.392	0.406	0.399	0.365	0.375	0.361	0.371	0.354	0.389	0.370	0.390	0.402	0.414	0.397	0.408
	336	**0.357**	**0.394**	0.429	0.430	0.492	0.453	0.376	0.390	0.390	0.390	0.373	0.407	0.382	0.408	0.452	0.452	0.435	0.440
	720	**0.372**	**0.413**	0.501	0.477	0.603	0.511	0.416	0.433	0.423	0.418	0.406	0.441	0.409	0.431	0.462	0.468	0.436	0.449
	Avg	**0.331**	**0.377**	0.406	0.411	0.455	0.427	0.363	0.382	0.368	0.377	0.355	0.395	0.363	0.393	0.414	0.427	0.395	0.414
ETTm1	96	**0.291**	**0.343**	0.454	0.408	0.457	0.403	0.363	0.356	0.380	0.361	0.292	0.346	0.313	0.352	0.338	0.375	0.344	0.373
	192	**0.325**	**0.364**	0.567	0.477	0.530	0.450	0.388	0.375	0.412	0.383	0.332	0.372	0.359	0.380	0.371	0.387	0.367	0.386
	336	**0.355**	**0.381**	0.662	0.525	0.577	0.481	0.416	0.392	0.436	0.400	0.366	0.394	0.395	0.404	0.410	0.411	0.392	0.407
	720	**0.406**	**0.411**	0.900	0.591	0.660	0.526	0.460	0.418	0.462	0.420	0.417	0.421	0.449	0.440	0.478	0.450	0.464	0.442
	Avg	**0.344**	**0.375**	0.646	0.500	0.556	0.465	0.407	0.385	0.423	0.391	0.352	0.383	0.379	0.394	0.399	0.406	0.392	0.402
ETTm2	96	**0.166**	**0.255**	0.199	0.274	0.197	0.271	0.205	0.273	0.211	0.274	0.173	0.262	0.178	0.262	0.187	0.267	0.177	0.260
	192	**0.220**	**0.292**	0.261	0.322	0.254	0.314	0.275	0.316	0.281	0.318	0.229	0.301	0.243	0.304	0.249	0.309	0.246	0.305
	336	**0.276**	**0.328**	0.326	0.366	0.313	0.353	0.329	0.350	0.341	0.355	0.286	0.341	0.302	0.341	0.321	0.351	0.305	0.343
	720	**0.368**	**0.385**	0.455	0.439	0.416	0.415	0.437	0.411	0.485	0.428	0.378	0.401	0.398	0.395	0.497	0.403	0.410	0.405
	Avg	**0.258**	**0.315**	0.310	0.350	0.295	0.338	0.312	0.338	0.330	0.344	0.267	0.326	0.280	0.326	0.314	0.333	0.285	0.328
ECL	96	**0.128**	**0.220**	0.154	0.231	0.152	0.229	0.160	0.250	0.153	0.241	0.139	0.238	0.139	0.235	0.184	0.288	0.186	0.269
	192	**0.147**	**0.238**	0.179	0.254	0.172	0.250	0.175	0.263	0.169	0.255	0.153	0.251	0.155	0.250	0.192	0.295	0.190	0.273
	336	**0.161**	**0.255**	0.214	0.284	0.203	0.276	0.187	0.277	0.187	0.273	0.169	0.266	0.170	0.268	0.200	0.303	0.206	0.290
	720	**0.193**	**0.288**	0.311	0.346	0.289	0.337	0.228	0.309	0.237	0.313	0.206	0.297	0.198	0.293	0.228	0.325	0.247	0.322
	Avg	**0.157**	**0.250**	0.215	0.279	0.204	0.273	0.188	0.275	0.187	0.271	0.167	0.263	0.166	0.262	0.201	0.303	0.207	0.289
Weather	96	**0.153**	**0.201**	0.203	0.238	0.194	0.235	0.220	0.217	0.199	0.211	0.162	0.212	0.156	0.202	0.169	0.228	0.177	0.218
	192	**0.201**	**0.248**	0.256	0.290	0.249	0.285	0.271	0.259	0.246	0.251	0.204	0.248	0.207	0.250	0.222	0.269	0.222	0.259
	336	**0.250**	0.290	0.314	0.336	0.302	0.327	0.286	0.297	0.274	0.291	0.254	0.286	0.263	0.292	0.290	0.310	0.277	0.297
	720	**0.319**	**0.337**	0.397	0.396	0.372	0.378	0.373	0.354	0.337	0.340	0.326	0.337	0.340	0.341	0.376	0.364	0.352	0.347
	Avg	**0.231**	**0.269**	0.293	0.315	0.279	0.306	0.288	0.282	0.264	0.273	0.237	0.271	0.242	0.271	0.264	0.293	0.257	0.280
Traffic	96	**0.362**	**0.251**	-	-	-	-	-	-	-	-	0.388	0.282	0.402	0.255	0.593	0.315	0.462	0.295
	192	**0.376**	**0.259**	-	-	-	-	-	-	-	-	0.407	0.290	0.426	0.268	0.596	0.317	0.466	0.296
	336	**0.398**	**0.269**	-	-	-	-	-	-	-	-	0.412	0.294	0.449	0.275	0.600	0.319	0.482	0.304
	720	**0.429**	**0.284**	-	-	-	-	-	-	-	-	0.450	0.312	0.489	0.297	0.619	0.335	0.514	0.322
	Avg	**0.391**	**0.266**	-	-	-	-	-	-	-	-	0.414	0.295	0.442	0.274	0.602	0.322	0.481	0.304

4.2 Results

Table 3: Ablation analysis on the ETTh1 and ETTh2 datasets

Variant	ETTh1				ETTh2			
	96	192	336	720	96	192	336	720
w/o TS modal	0.358	0.389	0.402	0.425	0.276	0.332	0.359	0.382
w/o VS modal	0.355	0.389	0.412	0.441	0.273	0.336	0.359	0.386
w/o projection	0.353	0.385	0.405	0.416	**0.266**	**0.328**	0.360	0.376
w/ all	**0.348**	**0.383**	**0.398**	**0.401**	**0.266**	**0.328**	**0.357**	**0.372**

As shown in Table 2, the VFEM model achieved lower MSE and MAE loss values on 7 datasets. The visual modality also enhances the ability to recognize long-term patterns in time series, which makes the model performance degrade more slowly in long-sequence forecasting. For example, the MSE loss with the forecasting length of 720 is only increased by 0.75% and 5% compared to the forecasting length of 336 for the ETTh1 and ETTh2 datasets, respectively, showing competitive long-term forecasting capability.

4.2.1 Module Contribution Analysis

To analyze the contribution of each module to the predictive performance of VFEM, we conducted ablation experiments as shown in Table 3, which examine the impact of each modality processing module and the projection layer. From the results, the absence of any module leads to a decrease in performance, among which the visual module has a relatively greater impact on long-term forecasting. The projection layer also helps align information from the two modalities, facilitating cross-modal fusion.

4.2.2 Cross-Modal Fusion Strategies

Table 4: Ablation study on cross-modal fusion strategies on ETTh1. Best results are in **bold**.

Fusion Type	$F{=}96$		$F{=}192$		$F{=}336$		$F{=}720$	
	MSE	MAE	MSE	MAE	MSE	MAE	MSE	MAE
Add	0.365	0.394	0.392	0.409	0.410	0.418	0.406	0.436
Gated Add	0.355	0.390	0.390	0.411	0.413	0.423	0.431	0.455
Bilinear	0.562	0.514	0.395	0.413	0.416	0.427	0.436	0.454
Concat+MLP	0.362	0.394	0.393	0.415	0.415	0.428	0.428	0.450
Cross-Attn (TS→VS)	0.357	0.388	0.388	0.407	0.424	0.434	0.438	0.463
Cross-Attn (VS→TS)	0.362	0.393	0.390	0.408	0.421	0.436	0.410	0.442
Ours	**0.348**	**0.383**	**0.383**	**0.405**	**0.398**	**0.414**	**0.401**	**0.434**

We compare several fusion strategies: (1) Add: element-wise addition; (2) Gated Add: addition with learnable gating weights; (3) Bilinear: bilinear pooling; (4) Concat+MLP: concatenation followed by MLP; (5-6) Cross-Attn: cross-attention with either temporal or visual features as query.

As shown in Table 4, our default strategy achieves the best performance across different prediction horizons. Simple addition performs competitively for long-term forecasting ($F{=}720$), while bilinear fusion shows instability at shorter horizons. Cross-attention variants show mixed results. In comparison, our concatenation-based approach with self-attention provides a simple and effective fusion.

4.2.3 Visual Encoder Freezing Strategies

Table 5: Ablation study on visual encoder freezing strategies. Best results are in **bold**.

Strategy	**ETTh1**				**ETTh2**			
	$F{=}96$		$F{=}720$		$F{=}96$		$F{=}720$	
	MSE	MAE	MSE	MAE	MSE	MAE	MSE	MAE
Unfreeze-2	0.355	0.385	0.413	0.442	0.273	0.336	0.374	0.415
Unfreeze-4	0.354	0.385	0.411	0.440	0.271	0.335	0.378	0.417
Full Fine-tune	0.353	0.384	0.423	0.452	0.272	0.336	0.378	0.417
Ours	**0.348**	**0.383**	**0.401**	**0.434**	**0.266**	**0.330**	**0.372**	**0.413**

We compare four freezing strategies: (1) Unfreeze-2: unfreeze the last 2 layers; (2) Unfreeze-4: unfreeze the last 4 layers; (3) Full Fine-tune: make all layers trainable; (4) Ours: keep all layers frozen.

As shown in Table 5, fully freezing the encoder achieves the lowest error. This is consistent with observations in cross-modal learning that freezing the pretrained encoder can help preserve its learned representations. When training with heterogeneous modalities, the gradient dynamics differ between branches, and unfreezing the visual encoder may affect its feature extraction capability.

4.2.4 Representation Quality Analysis

To validate that the projection layers learn meaningful time series representations, we compare three embedding types on ETTh1: (a) hand-crafted statistical features including mean, standard deviation, max, min, skewness, kurtosis, trend, and autocorrelation for each variable; (b) frozen SigLIP2 encoder outputs without fine-tuning; and (c) outputs after passing through the trained projection layers. We sample 500 sequences from training and test sets respectively, apply K-Means clustering ($k{=}10$), and evaluate using the Silhouette Score Rousseeuw (1987), which measures clustering quality by comparing intra-cluster cohesion with inter-cluster separation.

Figure 4: Embedding quality comparison on train and test sets. t-SNE visualizations of three embedding types: statistical features (left), raw SigLIP2 (center), and trained projection (right), evaluated on training set (top row) and test set (bottom row). Colors indicate K-Means cluster assignments (k=10). Silhouette Scores are shown for each configuration. The trained projection achieves the highest scores on both splits (0.453/0.468), demonstrating that the projection layers successfully adapt pre-trained visual features to the time series domain with strong generalization.

As shown in Figure 4, the trained projection achieves higher Silhouette Scores on both training set 0.453 and test set 0.468, compared to frozen encoder outputs at 0.146 and 0.135. The test set score slightly exceeds training with a gap of only 0.014, indicating good generalization. The low score of frozen SigLIP2 embeddings reflects the domain gap between natural images and time series, while the improvement after projection suggests that the projection layers help adapt visual features to the time series domain. The trained projection also outperforms statistical features with 0.468 versus 0.297 on test set, suggesting that the vision encoder captures patterns beyond hand-crafted statistics.

5 Conclusions

This work proposes VFEM, a cross-modal forecasting framework that integrates visual and temporal modalities for multivariate time series forecasting. By transforming time series into visual representations, VFEM enables pretrained vision models to perceive cross-variable spatial patterns that are difficult to capture with channel-independent architectures. The dual-branch design processes visual and temporal information independently before fusing them through self-attention.

By freezing the vision encoder and training only 7.45% of total parameters, VFEM leverages pretrained visual knowledge while avoiding overfitting on limited time series data. Ablation studies and representation analysis validate the effectiveness of each component. Experiments on seven benchmark datasets demonstrate that this cross-modal paradigm offers a viable alternative to existing approaches for capturing multivariate dependencies.

References

Anna Allen, Stratis Markou, Will Tebbutt, James Requeima, Wessel P Bruinsma, Tom R Andersson, Michael Herzog, Nicholas D Lane, Matthew Chantry, J Scott Hosking, et al. End-to-end data-driven weather prediction. *Nature*, 641(8065):1172–1179, 2025.

Abdul Fatir Ansari, Lorenzo Stella, Ali Caner Turkmen, Xiyuan Zhang, Pedro Mercado, Huibin Shen, Oleksandr Shchur, Syama Sundar Rangapuram, Sebastian Pineda Arango, Shubham Kapoor, Jasper Zschiegner, Danielle C. Maddix, Hao Wang, Michael W. Mahoney, Kari Torkkola, Andrew Gordon Wilson, Michael Bohlke-Schneider, and Bernie Wang. Chronos: Learning the language of time series. *Transactions on Machine Learning Research*, 2024. ISSN 2835-8856. URL https://openreview.net/forum?id=gerNCVqqtR. Expert Certification.

Defu Cao, Furong Jia, Sercan O Arik, Tomas Pfister, Yixiang Zheng, Wen Ye, and Yan Liu. TEMPO: Prompt-based generative pre-trained transformer for time series forecasting. In *The Twelfth International Conference on Learning Representations*, 2024.

Mouxiang Chen, Lefei Shen, Zhuo Li, Xiaoyun Joy Wang, Jianling Sun, and Chenghao Liu. VisionTS: Visual masked autoencoders are free-lunch zero-shot time series forecasters. In *Forty-second International Conference on Machine Learning*, 2025. URL https://openreview.net/forum?id=CmJLXLDOXa.

Luke Nicholas Darlow, Qiwen Deng, Ahmed Hassan, Martin Asenov, Rajkarn Singh, Artjom Joosen, Adam Barker, and Amos Storkey. DAM: Towards a foundation model for forecasting. In *The Twelfth International Conference on Learning Representations*.

Luo donghao and wang xue. ModernTCN: A modern pure convolution structure for general time series analysis. In *The Twelfth International Conference on Learning Representations*, 2024. URL https://openreview.net/forum?id=vpJMJerXHU.

Mononito Goswami, Konrad Szafer, Arjun Choudhry, Yifu Cai, Shuo Li, and Artur Dubrawski. MOMENT: A family of open time-series foundation models. In *Forty-first International Conference on Machine Learning*, 2024. URL https://openreview.net/forum?id=FVvf69a5rx.

Ming Jin, Shiyu Wang, Lintao Ma, Zhixuan Chu, James Y. Zhang, Xiaoming Shi, Pin-Yu Chen, Yuxuan Liang, Yuan-Fang Li, Shirui Pan, and Qingsong Wen. Time-LLM: Time series forecasting by reprogramming large language models. In *The Twelfth International Conference on Learning Representations*, 2024. URL https://openreview.net/forum?id=Unb5CVPtae.

Taesung Kim, Jinhee Kim, Yunwon Tae, Cheonbok Park, Jang-Ho Choi, and Jaegul Choo. Reversible instance normalization for accurate time-series forecasting against distribution shift. In *International Conference on Learning Representations*, 2022.

Chenxi Liu, Qianxiong Xu, Hao Miao, Sun Yang, Lingzheng Zhang, Cheng Long, Ziyue Li, and Rui Zhao. Timecma: Towards llm-empowered multivariate time series forecasting via cross-modality alignment, 2025a. URL https://arxiv.org/abs/2406.01638.

Juncheng Liu, Chenghao Liu, Gerald Woo, Yiwei Wang, Bryan Hooi, Caiming Xiong, and Doyen Sahoo. UniTST: Effectively modeling inter-series and intra-series dependencies for multivariate time series forecasting. *Transactions on Machine Learning Research*, 2025b. ISSN 2835-8856. URL https://openreview.net/forum?id=p3y5q4cvzV.

Xu Liu, Junfeng Hu, Yuan Li, Shizhe Diao, Yuxuan Liang, Bryan Hooi, and Roger Zimmermann. UniTime: A language-empowered unified model for cross-domain time series forecasting. In *Proceedings of the ACM on Web Conference 2024*, pp. 4095–4106, 2024a.

Yong Liu, Tengge Hu, Haoran Zhang, Haixu Wu, Shiyu Wang, Lintao Ma, and Mingsheng Long. itransformer: Inverted transformers are effective for time series forecasting. *arXiv preprint arXiv:2310.06625*, 2023.

Yong Liu, Haoran Zhang, Chenyu Li, Xiangdong Huang, Jianmin Wang, and Mingsheng Long. Timer: Generative pre-trained transformers are large time series models, 2024b. URL https://arxiv.org/abs/2402.02368.

Yuqi Nie, Nam H. Nguyen, Phanwadee Sinthong, and Jayant Kalagnanam. A time series is worth 64 words: Long-term forecasting with transformers, 2023.

Peter J Rousseeuw. Silhouettes: a graphical aid to the interpretation and validation of cluster analysis. *Journal of Computational and Applied Mathematics*, 20:53–65, 1987.

Chenxi Sun, Yaliang Li, Hongyan Li, and Shenda Hong. TEST: Text prototype aligned embedding to activate llm's ability for time series. *arXiv preprint arXiv:2308.08241*, 2023.

Mingtian Tan, Mike Merrill, Vinayak Gupta, Tim Althoff, and Tom Hartvigsen. Are language models actually useful for time series forecasting? *Advances in Neural Information Processing Systems*, 37:60162–60191, 2024.

Michael Tschannen, Alexey Gritsenko, Xiao Wang, Muhammad Ferjad Naeem, Ibrahim Alabdulmohsin, Nikhil Parthasarathy, Talfan Evans, Lucas Beyer, Ye Xia, Basil Mustafa, Olivier Hénaff, Jeremiah Harmsen, Andreas Steiner, and Xiaohua Zhai. Siglip 2: Multilingual vision-language encoders with improved semantic understanding, localization, and dense features, 2025. URL https://arxiv.org/abs/2502.14786.

Huiqiang Wang, Jian Peng, Feihu Huang, Jince Wang, Junhui Chen, and Yifei Xiao. MICN: Multi-scale local and global context modeling for long-term series forecasting. In *The Eleventh International Conference on Learning Representations*, 2023.

Gerald Woo, Chenghao Liu, Akshat Kumar, Caiming Xiong, Silvio Savarese, and Doyen Sahoo. Unified training of universal time series forecasting transformers. *arXiv preprint arXiv:2402.02592*, 2024.

Haixu Wu, Jiehui Xu, Jianmin Wang, and Mingsheng Long. Autoformer: Decomposition transformers with auto-correlation for long-term series forecasting. *Advances in neural information processing systems*, 34: 22419–22430, 2021a.

Haixu Wu, Tengge Hu, Yong Liu, Hang Zhou, Jianmin Wang, and Mingsheng Long. Timesnet: Temporal 2d-variation modeling for general time series analysis. *arXiv preprint arXiv:2210.02186*, 2022.

Tao Wu, Xiangyun Gao, Sufang An, and Siyao Liu. Time-varying pattern causality inference in global stock markets. *International Review of Financial Analysis*, 77:101806, 2021b.

Kun Yi, Qi Zhang, Wei Fan, Hui He, Liang Hu, Pengyang Wang, Ning An, Longbing Cao, and Zhendong Niu. FourierGNN: Rethinking multivariate time series forecasting from a pure graph perspective. In *Thirty-seventh Conference on Neural Information Processing Systems*, 2023.

Yunhao Zhang and Junchi Yan. Crossformer: Transformer utilizing cross-dimension dependency for multivariate time series forecasting. In *The Eleventh International Conference on Learning Representations*, 2023. URL https://openreview.net/forum?id=vSVLM2j9eie.

Tian Zhou, Ziqing Ma, Qingsong Wen, Xue Wang, Liang Sun, and Rong Jin. Fedformer: Frequency enhanced decomposed transformer for long-term series forecasting. In *International conference on machine learning*, pp. 27268–27286. PMLR, 2022.

Tian Zhou, Peisong Niu, Liang Sun, Rong Jin, et al. One fits all: Power general time series analysis by pretrained lm. *Advances in neural information processing systems*, 36:43322–43355, 2023.