CO-PILOT: COllaborative Planning and reInforcement Learning On sub-Task curriculum

Abstract

Goal-conditioned reinforcement learning (RL) usually suffers from sparse reward and inefficient exploration in long-horizon tasks. Planning can find the shortest path to a distant goal **that defines a dense reward**, but it is inaccurate without an accurate environment model. We show that RL and planning can collaboratively learn from each other to overcome their drawbacks. In "**CO-PILOT**", a path-planner and an RL agent provide dense feedback to train each other on a curriculum of tree-structured sub-tasks. Firstly, the planner decomposes a task to a tree of coarse-to-fine sub-tasks, each layer generating a path of sub-goals to the final goal, and the planning policy is trained to minimize the RL agent's cost to finish the path. This top-down tree construction gradually increases sub-goals on the path and forms an easy-to-hard curriculum to train the planner. Next, a bottom-up traversal of the tree trains the RL agent from easier sub-tasks with denser rewards to harder ones and collects each sub-task's cost to train the planner in the next episode. CO-PILOT repeats this mutual training for multiple episodes before switching to a new task, so the RL agent and planner are fully optimized for the other's training. We compare CO-PILOT with RL (SAC, PPO), planning (RRT*, NEXT, SGT), and their combination (SoRB) on navigation and continuous control tasks. CO-PILOT significantly improves the success rate and sample efficiency.

1 Introduction

Although AI can surpass humans on certain tasks, humans still perform much better in making sequential decisions via learning from interactions with the environment. Reinforcement learning (RL) [49] aims to bridge this gap by learning to optimize the trajectories of agents (e.g., controllers, robots, game players, self-driving cars, etc) to achieve the maximal return. However, in complicated long-horizon tasks, RL usually suffers from poor sample efficiency and costly data collection. Moreover, the data quality is often low due to sparse rewards when rollouts fail and cannot provide informative feedback. Model-based RL and off-policy RL improve the sample complexity with the price of extra biases, causing unstable and brittle optimization. Instead of reaching a single goal, goal-conditioned RL [26] learns one model for any given goal input to its model(s). However, it needs to be trained to reach many possible goals, and the resulted model's performance still degrades drastically for distant goals.

Instead, planning algorithms are usually more robust and effective on long-horizon tasks. Given a distance metric, they discretize the state space to a grid/graph and seek for the shortest collision-free path between states using graph search such as Dijkstra's algorithm or A* [21]. Thereby, it only needs a local policy to navigate between consecutive states on the path. However, it is challenging to learn or estimate the distance accurately in complicated tasks such as mazes. Moreover, planning every step on the path is as difficult as the original RL and requires fine-grained discretization impractical for high-dimensional states. Planning only a few milestone states leaves the RL agent to solve relatively long-horizon sub-tasks. Although sampling-based search heuristics can build a graph with a better exploration-exploitation trade-off, they are not optimized for the RL policy, and the graph cannot be shared across tasks. [13] adapt planning to a learned RL policy, which can provide distances estimated from its replay buffer, but the performance largely depends on the RL policy and its exploration.

A critical insight of this paper is that planning at even a coarse level can be used for reward shaping and substantially improves RL on long-horizon tasks with sparse reward. In contrast, experiences of the RL agent on the planned sub-tasks can improve the distance metric of planning to produce

Submitted to 35th Conference on Neural Information Processing Systems (NeurIPS 2021). Do not distribute.

better paths/sub-tasking for the RL agent. Hence, the RL agent and path-planner can provide dense and informative feedback to train each other. Thus, combining their strengths helps to overcome the bottleneck of each one and improve their exploration efficiency.

Figure 1: Figure (a) shows the mutual training process of RL and planning in CO-PILOT. Figure (b) indicates how SoRB [13] combines RL with planning algorithm. Note that in (a),(b), the brown arrows only happen in training process and the black arrows happen both in training and testing.

In this paper, we propose "**CO-PILOT**", a collaborative learning scheme between planning and goal-conditioned RL, which trains each model under the other's guidance along with a curriculum of sub-tasks. Unlike most existing planning methods, we train a planning policy to recursively decomposes a task into two easier sub-tasks, which finally yields a tree containing coarse-to-fine trajectories of sub-goals to the final goal. The tree naturally forms a curriculum for more effective training. During the top-down tree construction, we start from training the planner to find the shortest path on a coarser graph with fewer sub-goals, which is an easier training task, and gradually request it to generate detailed paths with denser sub-goals. We measure the distance by the cost of an RL agent navigating between consecutive sub-goals, so the planner is optimized to produce the most efficient path for the RL agent.

With the sub-goal tree constructed, we then train the goal-conditioned RL agent by a bottom-up curriculum, starting from easier sub-tasks with dense reward along the path and gradually enforcing the RL agent to navigate between more distant sub-goals. The sub-goals previously generated by the planner now provide an accurate reward shaping since they constitute cost-efficient paths for the RL agent. As a byproduct of rollouts on the sub-tasks, the RL policy helps to explore the environment topology and collect cost data between states to refine the distance metric for planning. Hence, the top-down (bottom-up) curriculum training of planner (RL agent) eases the training on the original tasks and collects more informative feedback to train the RL agent (planner). CO-PILOT repeats the above procedures for episodes of mutual boosting between the two until they are fully optimized for the other. In experiments, we apply CO-PILOT to navigation and continuous control. Compared to existing RL, planning and combining them, CO-PILOT significantly improves the sample efficiency and the final success rate for long-horizon tasks.

2 Related Work

RL: Goal-conditioned RL [39, 26, 44] takes a goal as an additional input to its model(s) and aims to handle different goals/tasks using the same policy. However, it requires more exploration and expensive training on various possible goals, and it still easily fails to reach distant goals in practice. Goal-relabeling and reward shaping [3, 39, 18] have been commonly studied to mitigate these issues. Recent methods [15, 54] improve it by learning a compact representation of the goal space. The goal-conditioned value function $V(s|g)$ naturally provides an ideal distance metric for shortest path planning. [10, 53] propose to train RL policy on a curriculum of environments adaptive to the RL. In CO-PILOT, we use sub-goal tree planning to generate a sample-efficient and adaptive training curriculum for goal-conditioned RL to learn to reach distant goals progressively. On the other hand, the goal-conditioned policy is used to more efficiently explore the environment to improve the planning policy.

Planning: Planning algorithms [49, 33] are more effective in solving long-horizon tasks in practice [36, 28]. Planning usually refers to dynamic programming that finds the optimal path on a

graph. Planning methods in RL, e.g., value/policy iteration [32, 36], utilize or learn an environment model to improve the policy. Compared to a reactive policy, an advantage of a complete plan is that the planned trajectory provides a global view of future steps. However, learning the environment model usually requires expensive sampling/exploration of state space [12, 34, 23, 38], structured and compact modeling of the environment/graph [7, 40], and an accurate distance metric [13]. In CO-PILOT, we apply path-planning to sub-tasking a long-horizon task and use the sub-tasks for reward shaping in RL to avoid sparse rewards and improve RL efficiency. CO-PILOT does not require delicate modeling of the environment. We adopt recent sub-goal tree (SGT) planning [24] to generate tree-structured sub-tasks for more efficient and strategic mutual learning. Moreover, we use the RL agent's training to explore the planning and use the RL agent's cost as the distance metric. Hence, planning in CO-PILOT mainly serves for RL's training and is much easier. This collaborative training process is the main difference between our method with [38].

Combine RL with Planning: A line of recent works [1, 35, 48, 45] embeds a planning model as one part of an RL agent's model and train it together with the RL policy in an end-to-end manner. [9, 14, 43] find that combining the two can help agents to reach distant goals in specific tasks. [13, 43] propose planning strategies with graph search based on the replay buffer of experiences from a given RL policy. [45] proposes to use Monte-Carlo tree search when planning in latent space to achieve a better optimization on value function. These results inspire our work, but our primary difference is the mutual training between RL and planning, which does not require either a pre-trained policy or strong heuristics about the distance metric. In CO-PILOT, both are trained from scratch and can mutually boost and guide each other's training via an auto-generated curriculum of easy-to-hard sub-tasks. This mutual training leads to a principled learning framework adaptive to a vast amount of potential applications.

Hierarchical RL: Hierarchical RL (HRL) [25, 17, 37, 31] learns a sequence of primeval policies towards complicated tasks. e.g., learn policies for low-level skills and sequentially combine them to form a high-level policy addressing complex tasks, or transfer the learned knowledge of a morphologically simpler agent to a more complex one [22, 8]. HRL for goal-reaching tasks has been studied in [13, 37]. An important topic in HRL is how to automatically discover low-level skills or sub-goals [11, 16, 47, 2]. In CO-PILOT, we train a planning policy to automatically propose sub-tasks of increasing difficulty levels to train the RL agent. Therefore, RL agent starts from learning how to reach nearby sub-goals and progressively improve its skills for long-horizon tasks.

3 CO-PILOT

3.1 Goal-conditioned Reinforcement Learning

Goal-conditioned RL or multi-goal RL learns a policy that can be adapted to different goals. Given the state space $\mathcal{S}$, the action space $\mathcal{A}$, and the goal space $\mathcal{G}$, a goal-conditioned policy is a mapping $\pi(a|s,g) : \mathcal{S} \times \mathcal{G} \mapsto \mathcal{A}$ that outputs an action a (or probabilities $\Pr(a|s,g)$ over actions $a \in \mathcal{A}$) given a state-goal pair (s,g). An RL agent uses $\pi(a|s,g)$ to interact with an environment described by a Markov decision process (MDP) $\{\mathcal{S}, \mathcal{A}, \mathcal{G}, p, r, \gamma\}$, where $p(s'|s,a) \triangleq \Pr(s_{t+1} = s'|s_t = s, a_t = a)$ is the transition probability for the agent from state s to s' after taking action a, $r(s,a|g) : \mathcal{S} \times \mathcal{A} \times \mathcal{G} \mapsto \mathbb{R}$ is a reward function, and $\gamma \in [0,1]$ is a discount factor.

In each episode, the agent starts from an initial state $s_0 \sim p_0(s)$ and aims to reach a given goal $g \in \mathcal{G}$. In every time step t, it takes an action $a_t = \pi(a|s_t,g)$ (deterministic) or $a_t \sim \pi(a|s_t,g)$ (stochastic), receives a reward $r(s_t, a_t|g)$, and moves to a new state $s_{t+1} \sim p(s'|s_t, a_t)$. RL aims to learn a policy π maximizing the expected return $\mathbb{E}_{(s_0,g)}[\mathbb{E}_\pi(R_0)]$. Define the action-value function $Q(s,a|g) \triangleq \mathbb{E}(R_t|s_t = s, a_t = a, g)$, the optimal policy π^* achieves the maximal $Q(s,a|g)$ for any feasible (s,a,g). Define the value function $V(s|g) \triangleq \mathbb{E}(R_t|s_t = s, g) = \mathbb{E}_{a\sim\pi}[Q(s,a|g)] = \sum_{a\in\mathcal{A}} \pi(a|s,g)Q(s,a|g)$. Directly maximizing the expected return or V w.r.t. π results in the vanilla policy gradient method [49], which usually samples inefficient and suffers from the high variance of R_t. Actor-critic methods [50] additionally learns a model of V or Q as a "critic" to the "actor" π, which performs as a baseline to effectively reduce the variance. The optimization of V or Q aims to minimize the Bellman residual

$$J_{Q^\pi} = \mathbb{E}_{(s_t,a_t,g)} \left[Q^\pi(s_t, a_t|g) - r(s_t, a_t|g) - \gamma \mathbb{E}_{s_{t+1}}[V(s_{t+1}|g)] \right]^2, \tag{1}$$

Given the critic Q, maximizing the expected return w.r.t. π reduces to minimizing

$$J_\pi = \mathbb{E}_{(s_t,g)}[-V(s|g)] = \mathbb{E}_{(s_t,g)}[\mathbb{E}_{a_t}[-Q^\pi(s,a|g)]]. \tag{2}$$

A typical actor-critic algorithm alternates between minimizing J_Q and J_π. To encourage exploration, we use soft actor-critic (SAC) [19] that augments V with an entropy term (with temperature α), i.e.,

$$V(s|g) = \mathbb{E}_{a \sim \pi}[Q^\pi(s,a|g) - \alpha \log \pi(a|s,g)]. \tag{3}$$

In order to encourage the above equation, SAC additionally optimizes V by minimizing the mean square error

$$J_V = \mathbb{E}_{(s_t,g)}\left[V(s_t|g) - \mathbb{E}_{a \sim \pi}[Q^\pi(s_t,a_t|g) - \alpha \log \pi(a_t|s_t,g)]\right]^2. \tag{4}$$

SAC alternatively optimizes J_V, J_Q and J_π (using the augmented V in Eq. (3)) defined in Eq. (1)-(4) by using stochastic gradient decent (SGD) on batches of sampled (s_t, a_t, g). Although we use SAC in our experiments, CO-PILOT can work with any other RL algorithm besides SAC.

3.2 Reward Shaping by Path-Planning

In various environments, an RL agent receives a nonzero reward only when reaching the ϵ-ball $B(g, \epsilon)$ around the goal g, i.e., $r(s, a|g) = \mathbb{1}[s \in B(g, \epsilon)]$ with $\mathbb{1}$ being the indicator, so $r(s, a|g)$ for most steps/trajectories cannot provide informative feedback to policy training. RL is unstable and can easily fail with such sparse reward, especially in long-horizon tasks when g is far away from s_0 or too difficult to reach for the agent-in-training. To address this problem, reward shaping method [30] augments the environment reward with a dense reward $r'(s, a|g)$ that can be issued to more non-goal states, e.g., intrinsic motivation/curiosity that encourages effective exploration, or human-engineered task-specific rewards. The ideal dense reward, which is, however unavailable without knowing π^*, is $V^*(s|g)$. Planning methods, e.g., value iteration [51] or fitted-Q iteration [4], can approximate $V^*(s|g)$ but accurately estimating $V^*(s|g)$ is as challenging as the policy learning.

Path-planning and motion-planning methods [12] usually adopt a heuristic distance or cost $c(s, g)$ (e.g., Euclidean distance or time cost) to replace the unknown $V^*(s|g)$. They discretize the state space into a grid/graph and find the shortest path connecting the initial state s_0 and the goal g. In goal-conditioned RL, s_0 and g can be any feasible states on the graph, so path-planning needs to solve the all-pairs shortest path(APSP) problem [42], i.e.,

$$\min_{g_0 = s_0, g_{1:T-1}, g_T = g} \sum_{t=0}^{T-1} c(g_t, g_{t+1}), \quad \forall s_0 \in \mathcal{S}, g \in \mathcal{G}, \tag{5}$$

where $g_{1:T-1}$ denotes a discrete sequence of sub-goals $(g_1, g_2, \ldots, g_{T-1})$ between $g_0 = s_0$ and $g_T = g$. Planning every step for an agent is usually challenging and requires an accurate $c(\cdot, \cdot)$ or environment model. But we only use planning for reward shaping, which can tolerate a small T, i.e.,

$$\bar{r}(s, a|g_{0:T}) = \frac{1}{T} \sum_{t=1}^{T} r(s, a|g_t). \tag{6}$$

As T increases, $\bar{r}(s, a|g_{0:T})$ becomes denser and the RL agent can receive more effective feedback for policy training. However, the quality of $\bar{r}(s, a|g_{0:T})$ also heavily depends on the cost for the agent to reach g by following the path $g_{0:T}$, since issuing reward to an inefficient/long path misleads the policy training. Therefore, in CO-PILOT, we use a prediction model to predict $c(\cdot, \cdot)$ and train the planning policy to generate $g_{0:T}$ incurring the smallest cost as in Eq. (5).

Remarks: This closes the loop and results in a collaborative learning and mutual boosting scheme between RL and planning: planning provides dense rewards and sub-tasks to train the RL agent, while the RL agent collects the costs on the sub-tasks to further improve the planning policy towards producing better reward shaping. In addition, this scheme makes both RL and planning easier to overcome their bottlenecks: the RL **does not need to learn from long-horizon tasks directly**, while the planning can be coarse (with small T) and does not require accurate modeling of MDP. We will introduce how to achieve this next.

3.3 Curriculum from Sub-task Tree Planning

In the above scheme, planning serves RL like a copilot in an aircraft to encourage more efficient training. The main advantage of a tree structure planner is to provide a global view of future milestones to the RL policy, which mainly focuses on local steps and might lack long-term sight. However, many planning algorithms are based on Bellman equation and sequentially predict the sub-goals, which may suffer from accumulated errors [41]. In addition, as the aforementioned, a larger T results in easier sub-tasks for the RL agent but also increases the difficulty of planning, and vice versa. Hence, it is challenging to train both the RL and planning policy from scratch using either a small or a large T. This motivates us to seek coarse-to-fine planning that can generate multiple trajectories of sub-goals with increasing T, so the planning policy can be trained on an easy-to-hard

curriculum [5], i.e., generating coarse-to-fine shortest paths from small T to large T. At the same time, the RL agent can also be trained on an easy-to-hard curriculum of sub-tasks, i.e., by following the trajectories from large T to small T.

Therefore, we apply "sub-goal tree (SGT)" [24] to recursively divide a trajectory from small T to large T and produce a sub-task tree. We define a planning policy $\pi_p(g|g_i, g_j)$ as a stochastic mapping from two nearby endpoints g_i and g_j to a predicted sub-goal g in the middle of g_i and g_j. In our scheme, we use $\pi_p(g|g_i, g_j)$ to break down a task with initial state g_i and goal g_j (denoted by (g_i, g_j)) to two sub-tasks (g_i, g) and (g, g_j). Hence, we can generate a tree of sub-goals by recursively sampling sub-goals from $\pi_p(g|g_i, g_j)$ as below, which finally generates a planning trajectory $g_{0:T}$ with a tree structure, i.e.,

$$\Pr_{\pi_p}(g_{0:T}|g_0 = s_0, g_T = g) \triangleq \Pr_{\pi_p}\left(g_{0:\frac{T}{2}}\left|g_0, g_{\frac{T}{2}}\right.\right)\Pr_{\pi_p}\left(g_{\frac{T}{2}:T}\left|g_{\frac{T}{2}}, g\right.\right)\pi_p\left(g_{\frac{T}{2}}\left|s_0, g\right.\right), \quad (7)$$

where $T = 2^K$ with K being the depth of the tree. As shown in Figure 1 (a), for layer-k, the sub-goal tree $g_{0:T}$ interpolates a sequence of $2^k - 1$ sub-goals $g^k_{1:(2^k-1)} \triangleq \left(g^k_1, g^k_2, \ldots, g^k_{2^k-1}\right)$ between s_0 and g, where $g^k_j = g_{Tj/2^k}$ in $g_{0:T}, \forall j \in [2^k-1]$. In layer-1, we have the coarsest trajectory $(s_0, g^1_1 = g_{T/2}, g)$. In the bottom layer-$K$, we have the finest trajectory $g_{0:T}$. The in-between layers and their sub-goal trajectories naturally form a coarse-to-fine sub-tasking curriculum, e.g., the planning in layer-1 requires the agent to accomplish two hard and long-horizon sub-tasks to reach g, while layer-K's planning requires the agent to accomplish T much simpler and shorter-horizon sub-tasks.

To train the planning policy π_p, we apply it to produce a tree-structured $g_{0:T}$ via Eq. (7) and evaluate the cost $c\left(g^k_{0:2^k}\right)$ of the trajectory $g^k_{0:2^k}$ by integrating the cost of every segment/sub-task $c\left(g^k_{tT/2^k}, g^k_{(t+1)T/2^k}\right)$ along the trajectory, i.e., $c\left(g^k_{0:2^k}\right) \triangleq \sum_{t=0}^{2^k-1} c\left(g^k_{tT/2^k}, g^k_{(t+1)T/2^k}\right)$. We will elaborate on our option of cost function $c(\cdot, \cdot)$ later in Eq. (12). The objective of π_p aims to minimize the total cost $c(g_{0:T})$ of the sub-goal tree, which sums over all trajectories' costs across the K layers,

$$c(g_{0:T}) \triangleq \sum_{k=0}^{K} c\left(g^k_{0:2^k}\right). \quad (8)$$

According to APSP objective in Eq. (5), the optimal planning policy π^*_p minimizes the expected cost J_{π_p} over all possible planning trajectories defined below:

$$J_{\pi_p} \triangleq \mathbb{E}_{g_{0:T}}[c(g_{0:T})] = \mathbb{E}_{(s_0,g)}\mathbb{E}_{g_{1:T-1}\sim\pi_p}[c(g_{0:T})], \quad (9)$$

where $g_{1:T-1} \sim \pi_p$ denotes the recursive sampling of $g_{1:T-1}$ in Eq. (7). Any policy gradient method can be used to minimize J_{π_p}, with the gradient w.r.t. π_p computed as

$$\nabla J_{\pi_p} = \mathbb{E}_{g_{0:T}\sim\pi_p}\left[c(g_{0:T}) \cdot \nabla \log \Pr_{\pi_p}(g_{0:T}|s_0, g)\right]. \quad (10)$$

To form an easy-to-hard curriculum for training π_p, during the top-down growing of the tree, we minimizes $c(g_{0:T})$ up to every layer-k before reaching the bottom layer-K, in which the summation in Eq. (8) is only up to $k = K$. In Algorithm 1, we will use $J^K_{\pi_p}$ to denote the corresponding J_{π_p} with $c(g_{0:T})$ and $\Pr_{\pi_p}(g_{0:T}|s_0, g)$ computed up to $k = K$.

Cost function of sub-tasks: As discussed in the end of Section 3.2, the cost function $c(g_t, g_{t+1})$ should reflect the difficulty of sub-task (g_t, g_{t+1}) for the agent. Euclidean distance $\|g_t - g_{t+1}\|_2$ is commonly used by previous path-planning methods but not adaptive to the evolution of agent policy and environment, e.g., the difficulty of sub-task (g_t, g_{t+1}) with/without nearby obstacles can vary drastically. A more adaptive cost is the time steps of the agent to finish a sub-task. Therefore, we propose to use a monotonic hyperbolic model $c_\phi(g, g')$ to predict the time steps $\tau_{g,g'}$ for the agent navigating from g to g'. c_ϕ is trained with planner to adapt to the learning process of RL policy. Hence, the time cost of a sub-task is

$$\tau(g_t, g_{t+1}) = \min\{c_\phi(g, g'), \tau_{\max}\}. \quad (11)$$

We start from $\mathcal{D}_\tau = \emptyset$ and gradually collect $(g, g', \tau_{g,g'})$ during the course of training. Hence, we can expect that in the early stages $\tau(g_t, g_{t+1}) = \tau_{\max}$ for most sub-tasks. To address this "cold-start" issue, we combine the Euclidean distance and the time cost in the form of

$$c(g_t, g_{t+1}) = \alpha\|g_t - g_{t+1}\|_2 + (1 - \alpha)\tau(g_t, g_{t+1}). \quad (12)$$

We start from α close to 1 and gradually reduce it towards 0 as the dataset $\mathcal{D}_\tau$ grows.

3.4 Mutual Training between RL and Planning

CO-PILOT is a mutual training scheme between the RL policy π and the planning policy π_p, each generating dense cost/reward on tree-structured sub-tasks to train the other.

By top-down construction of sub-task tree from $k = 0$ to $k = K$, it firstly trains the planning policy π_p on a curriculum of generating coarse-to-fine trajectories. On each layer-k, it generates 2^k sub-tasks through rollouts of π_p. Given $\mathcal{D}_\tau$ and the cost $c(\cdot, \cdot)$ in Eq. (12), CO-PILOT updates π_p by minimizing J_{π_p} in Eq. (9).

At the very beginning of CO-PILOT, $\mathcal{D}_\tau = \emptyset$ and the cost solely depends on the Euclidean distance. However, as we are collecting more experiences into $\mathcal{D}_\tau$, π_p will be trained towards producing the easiest sub-task trajectory for the RL agent to finish and thus increases its chance of receiving non-zero rewards. The complete procedures of top-down construction are given in Algorithm 1. Being updated using the most recent $\mathcal{D}_\tau$, π_p keeps tracking the RL agent's learning progress to produce the

---

Algorithm 1 Top-Down Construction of Sub-Task Tree

1: **Input:** a task (s_0, g), T, $\mathcal{D}_\tau$, planning policy π_p
2: **Output:** tree structured sub-goals $g_{0:T}$, π_p
3: **for** $k = 1, 2, \ldots, K$ **do**
4:     **for** $t = 0, 1, \ldots, 2^{k-1} - 1$ **do**
5:         Recursively predict sub-goals using π_p
6:         Compute the cost for sub-tasks $\left(g_t^{k-1}, g_t^k\right)$ and $\left(g_t^k, g_{t+1}^{k-1}\right)$ using Eq. (11)-(12);
7:     **end for**
8:     Apply a policy gradient method to minimize $J_{\pi_p}^k$, i.e., J_{π_p} in Eq. (9) computed only up to layer-k;
9:     Update the prediction model c in Eq. (11)
10: **end for**

---

most cost-efficient paths for the agent. Moreover, the top-down construction naturally forms an **easy-to-hard curriculum for the planning policy** π_p. In Line 8 of Algorithm 1 , we train π_p to produce sub-goal trajectories up to layer-k. Hence, the training of π_p is more smooth and less challenging than learning the optimal V^* or Q^*.

After the top-down construction of the sub-task tree, CO-PILOT trains the **RL policy π on a curriculum of easy-to-hard** sub-tasks by **bottom-up traversal** of the tree from $k = K$ to $k = 0$. The sub-goal trajectory in each layer aims to guild the agent to complete the original task from s_0 to g. At layer-k, CO-PILOT applies π sequentially to the 2^k sub-tasks (as the conditioned goal). It then updates π by SAC, which alternates among the minimization of J_Q, J_π and J_V in Eq. (1)-(4) to update π, V and Q. Note we can replace SAC with other RL algorithms in the general framework of CO-PILOT.

The rollouts of π on the sub-tasks not only collect experiences to train itself but also collect tuples of $(g, g', \tau_{g,g'})$ added to $\mathcal{D}_\tau$, which will be used to train π_p. It is possible that π fail on some sub-task within $\tau_{\max}$ steps. In this case, we treat the actual ending state as g' in the tuple for $D\tau$ and initialize the the next sub-task from this state. The bottom-up traversal is detailed in Algorithm 2, where Line 9-13 apply π to reach sub-goal $g_{tT/2^k}$. The bottom-up traversal forms an easy-to-hard curriculum to train π, in which the sub-tasks from the bottom layers are easier so the agent by larger chance can receive non-zero rewards. Given a task (s_0, g), the curriculum guides the agent first to learn how to finish it by following a detailed planning path of many sub-goals. It then gradually increases the hardness by halving the number of sub-goals

---

Algorithm 2 Bottom-Up Traversal of Sub-Task Tree

1: **Input:** RL policy π, sub-goal tree of $g_{0:T}$, $\tau_{\max}$, ϵ
2: **Output:** π, $\mathcal{D}_\tau$
3: **Initialize:** $\mathcal{D}_\tau \leftarrow \emptyset$
4: **for** $k = K, \ldots, 1, 0$ **do**
5:     Set RL agent's initial state to be $s_0 \leftarrow g_0$;
6:     **for** $t = 1, 2, 3, \ldots, 2^k$ **do**
7:         Set the condition of V, Q, π in SAC to be g_t^k;
8:         $\tau \leftarrow 0$, $\mathcal{B} \leftarrow \emptyset$;
9:         **while** $\tau \leq \tau_{\max}$ or $s_\tau \notin B(g_t^k, \epsilon)$ **do**
10:             RL agent takes action $a_\tau \sim \pi(a_\tau | s_\tau, g_t^k)$;
11:             RL agent moves to $s_{\tau+1} \sim p(s_{\tau+1} | s_\tau, a_\tau)$ and receives reward $r(s_\tau, a_\tau | g_t^k)$;
12:             $\mathcal{B} \leftarrow \mathcal{B} \cup (s_\tau, a_\tau, r(s_\tau, a_\tau | g_t^k), s_{\tau+1})$;
13:         **end while**
14:         $\mathcal{D}_\tau \leftarrow \mathcal{D}_\tau \cup (s_0, s_\tau, \tau)$, $s_0 \leftarrow s_\tau$;
15:         **for** every gradient step **do**
16:             Apply gradient steps in SAC: update Q, V, π to minimize J_Q, J_π and J_V in Eq. (1)-(4) using samples drawn from $\mathcal{B}$;
17:         **end for**
18:     **end for**
19: **end for**

---

until recovering the original task. Therefore, it critically alleviates the sparse reward problem that usually fails or considerably slows down RL on long-horizon tasks.

A prominent advantage and difference of CO-PILOT compared to other methods that combine RL and planning is to repeat the top-down construction and bottom-up traversal for multiple (b in Algorithm 3) episodes on each task (s_0, g). Thereby, the RL agent and the planning policy are fully optimized for each other's training, forming an adaptive curriculum without human engineering. The complete procedures of CO-PILOT are listed in Algorithm 3.

Algorithm 3 CO-PILOT

1: **Input:** $\mathcal{G}, p_0, T, \tau_{\max}, \epsilon, b$
2: **Output:** RL agent's policy π, planning policy π_p
3: **Initialize:** $\pi, \pi_p, \mathcal{D}_\tau$ by Euclidean distance
4: **while** not converge **do**
5:     Sample a task (s_0, g) with $s_0 \sim p_0(s)$ and $g \in \mathcal{G}$;
6:     **for** episode $= 1, 2, \ldots, b$ **do**
7:         **Algorithm 1**: top-down construction of a sub-task tree $g_{0:T}$, train planning policy π_p based on $\mathcal{D}_\tau$;
8:         **Algorithm 2**: bottom-up traversal of the sub-task tree $g_{0:T}$, train RL policy π, collect $\mathcal{D}_\tau$;
9:     **end for**
10: **end while**

---

4 Experiments

We evaluate CO-PILOT on three tasks: a maze and two continuous control tasks for robotic navigation in Mujoco and BipedalWalker. CO-PILOT outperforms strong baselines from RL, planning, and methods combining them on both sample efficiency and final success rate.

4.1 Environment Setup

Maze environment: We build a maze environment of size 1×1 containing square obstacles(obstacle states) and free-to-reach states as shown in Figure 4. For each benchmark(the design of benchmark refer to Figure 2), We randomly sample 300 pairs of (s_0, g) for training and 100 pairs for test from a uniform distribution on the coordinate range and remove the ones in obstacles. It averagely takes an RL agent ≥ 200 steps moving from s_0 to g, which is a long-horizon task. The task succeeds if the agent reaches $B(g, \epsilon = 0.025)$ without collision.

Mujoco Ant-v1: We evaluate CO-PILOT and baselines in the Mujoco environment with an Ant-v1 agent (Quadruped [52]) with an 8-dim action space. As shown in Figure 2 (d), we train the agent to navigate in the maze without self-rotation and collisions to the wall. We randomly sample 50 (s_0, g) pairs for training and 10 pairs for test.

BipedalWalker: The BipedalWalker environment [6] offers a new perspective of tasks rather than maze type. The learning agent, embodied in a bipedal walker, receives positive rewards for moving forward and penalties for torque usage and angular head movements. Agents are allowed 2000 steps to reach the other side of the map. The environment producing tracks paved with stumps varying by their height parameter μ_h and an independent sampled spacing parameter $\Delta_s \in \mathcal{N}(\mu_h, 0.1)$. We design three agents with different length of legs (as shown in figure 3) for each benchmark. Performance is evaluated periodically by sampling 10 tracks in each track distribution of a fixed evaluation set of 50 distributions sampled uniformly in the parameter space. We measure the percentage of mastered tracks.

Baselines: In the maze environment, we compare CO-PILOT with (1) three planning methods: RRT* [27] (Rapidly-exploring Random Trees), NEXT [7] (Neural Exploration-Exploitation Trees) and SGTPG [24] (Sub-Goal Tree Policy Gradient); two model-free RL algorithms: valued-based method SAC [20] and policy-based method PPO [46] (in CO-PILOT, we use the former to train the RL policy and the latter to train the planning policy); and (3) a RL-planning hybrid method: SoRB [13], which trains planning strategies based on the experiences of a given RL policy. Since we use SAC for RL in CO-PILOT, we change the RL algorithm in SoRB to SAC. In the Mujoco environment, we compare CO-PILOT with SAC, SoRB, and a hierarchical RL [22]. In BipedalWalker, we compare CO-PILOT with SAC and SoRB.

Figure 2: **(a)** Success rate on test tasks of Maze environment: 2D/3D/5D denote the DoF (degrees of free action space) of the agent respectively (point mass/rigid body robot/snake robot). **(b)** Ant-v1 average return in Mujoco. **(c)** Success rate of CO-PILOT with different depth K for the sub-goal tree.**(d)** Ant-v1 agent and maze environment in Mujoco.

4.2 Training Details and Hyperparameters

In CO-PILOT, we initialize the dataset $\mathcal{D}_\tau$ with 50,000 tuples of $(g, g', \tau_{g,g'})$ with $\tau_{g,g'}$ being the Euclidean distance. We use SAC to train the RL policy and PPO [46] to train the planning policy in Line 8 of Algorithm 1, since the former encourages exploration and the latter is simple and efficient. We set a reward of 1 (1000, 200) to each task (s_0, g) in Maze (Mujoco,BipedalWalker). According to Eq (6), the reward of each sub-task in layer-k is $1/2^k$ ($1000/2^k$, $200/2^k$). For planning cost, if the segment between (g_t, g_{t+1}) trespasses any obstacle, we add a penalty of 10 to $\tau(g_t, g_{t+1})$ in Eq. (12). We linearly reduce α in Eq. 12 from 0.9 to 0.1 throughout every episode. For planning policy training, we apply PPO with a trust region of $\epsilon = 0.2$ and use Adam optimizer [29] with a learning rate of 0.005. For RL training with SAC, we use its default hyperparameters. In both environment, we set $T = 2^5$ (ablation study of different T in Figure 2 (c)) and $b = 5$ (further increasing it does not improve the performance). We set $\tau_{\max} = 25$, $\tau_{\max} = 200$ and $\tau_{max} = 2000$ for Maze, Mujoco and BipedalWalker respectively. For efficiency, in Line 5 of Algorithm 3, we instead sample a mini-batch of 30 (Maze) or 50 (Mujoco) pairs of (s_0, g). The (s_0, g) is fixed in BipedalWalker, we randomly sample 20 tracks in each track distribution from the same 50 distributions mentioned in section 4.1.

4.3 Main Results and Ablation Study

In Figure 2 (a), we compare the performance of CO-PILOT with all baselines on the test tasks of the Maze environment. CO-PILOT achieves the highest success rate across all benchmarks and significantly outperforms SAC and SGTPG. Figure 4 (a)-(c) report how the success rate of all methods change during training as the number of interaction steps with the environment increases. We limit the total environment steps of all methods $\leq 1.8 \times 10^6$ except for NEXT (since

Figure 3: **Main results and comparison in BipedalWalker.** The mean performance (32 seeded runs) is plotted with shaded areas representing the standard error of the mean.

NEXT requires the pre-training of RRT*). In Figure 4 (a), CO-PILOT and SGTPG are very close in the early training period because the cost data collected by the RL agent are insufficient, and the Euclidean distance dominates the cost $c(\cdot, \cdot)$ in Eq. 12 during the earlier stages. The performance of SoRB and SAC are similar because SoRB needs to pre-train the RL policy at first when no planning is required. SoRB surpasses SAC during the later stages. Similarly, NEXT needs to pre-train RRT* and then apply self-improving training, explaining why we do not see the change of cost and collision checks for NEXT during the earlier stages. Note that the performance of SAC also represents what if **no planner help** in CO-PILOT training and testing phase.

The average return on Mujoco tasks is shown in Figure 2 (b). Furthermore, the percentage of mastered environments on BipedalWalker is shown in Figure 3. For simplicity, we denote [22] as HRL. SoRB and HRL start later because the RL policy is under pre-training. The experimental results show that CO-PILOT achieves much better sample efficiency than all the baselines, including SoRB. The final performance is comparable with SoRB but significantly outperforms SAC and HRL(Mujoco).

Ablation study on sub-task tree depth K: In Figure 2 (c), we evaluate CO-PILOT on 5 different tree depths with all the other hyperparameter fixed. It shows a trade-off discussed in our paper, i.e., a deeper sub-task tree eases the learning of the RL agent for denser reward and more detailed sub-tasking guidance, but it also makes the planning more challenging. In this experiment, the best trade-off is achieved when depth $K = 5$.

4.4 Visualization of Mutual Training in CO-PILOT

To understand the mutual training of CO-PILOT in our experiments, we show how a sub-task tree evolves over episodes in Algorithm 3 in Figure 4 (d), where we show the sub-goal paths of layer-$2, 3, 4$ generated in Episode-$1, 3, 5$ for the same task (s_0, g). We are particularly interested in two questions: how does planning guide RL agent's learning by sub-tasking? How does RL agent's cost affect the planning paths? The sub-goal paths in Episode-1 from all the three layers, trespass the obstacles in the middle and are too close to the obstacles elsewhere, which cannot provide reliable guidance for the RL agent and thus result in poor reward shaping. The Euclidean distance is almost equal for different sub-tasks on a path, but the corresponding costs in the histogram vary a lot, which is not preferred since some sub-tasks are too hard, but some are too easy for the RL agent. Hence, the planning policy

Figure 4: **(a)** Success rate. **(b)** Average path length (normalized by RRT*) in terms of Euclidean distance. **(c)** Average collision checks (normalized by RRT*) as every method increases its interaction steps with the environment. CO-PILOT achieves the best sample efficiency among all methods. **(d)** Visualization of the sub-goal paths on layer-$k = 2, 3, 4$ of the sub-task tree in Episode-$1, 3, 5$ for a task with initial state s_0 (red dot) and goal g (blue dot) in Maze. Each histogram reports the RL agent's cost $\tau_{g_t, g_{t+1}}$ for sub-tasks along the path. As episode increases, planning paths across all layers are improved, and on each path the costs of all sub-tasks reduce towards a similar value, though the Euclidean distances are still different, since the planner learned to produce more sub-tasks near complicated obstacles.

is not fully optimized to find cost-efficient paths for the RL agent. Moreover, the time cost for the RL agent to finish the whole task is much higher than the later episodes, indicating a poor RL policy.

In Episode-3, the generated sub-goals paths become more adaptive to the environment. In all layers, we can see that the planner tends to generate longer segments for places with fewer nearby obstacles and collision risks while adding more fine-grained sub-tasks to get around the corners. This phenomenon implies that the planning policy is learning to produce better and more adaptive guidance. The planned path is collision-free for the deepest layer-3 and thus can provide an accurate reward shaping for the RL agent. However, restricted by the number of sub-goals, the paths in layer-2, 3 can still be improved. It is also clear in the histograms that sub-tasks' costs drastically reduced compared to Episode-1, indicating that the planning policy learned to generate more cost-efficient paths and the RL policy is also improved under the guidance of planning.

In Episode-5, the planning paths are almost optimal, especially for the one in layer-4, which keeps in the very middle position between the obstacles. Moreover, the costs in the histograms are not only much lower than the previous two episodes but also have similar values. Hence, both the planning and RL policies are significantly improved on their tasks. They are also fully optimized for the other, e.g., the planned sub-tasks' costs are less dependent on the Euclidean distance but more related to the actual time cost of the RL agent, and the planning policy is able to find cost-efficient paths for the RL agent. Note that the sub-goal path in layer-5 is not step-by-step planning, but the RL agent is already capable of accomplishing the whole task. Therefore, the mutual training in CO-PILOT improves the sample efficiency of learning the two coupled policies and makes both the RL and planning more accessible than when they are independently applied to the same task.

5 Conclusion

We presented Co-PILOT, a mutual learning framework combining RL with a tree structure planner, that trains both planning and RL from easy-to-hard. In our experiments, we show that our method can adapt to different types of tasks, e.g. path planning in maze and robot controlling navigation. All tasks in our experiments are conditioned on very sparse reward and long-horizon transition for RL agent.

References

[1] Brandon Amos, Ivan Dario Jimenez Rodriguez, Jacob Sacks, B. Boots, and J. Z. Kolter. Differentiable mpc for end-to-end planning and control. In *NeurIPS*, 2018.

[2] Jacob Andreas, D. Klein, and S. Levine. Modular multitask reinforcement learning with policy sketches. *ArXiv*, abs/1611.01796, 2017.

[3] Marcin Andrychowicz, Dwight Crow, Alex Ray, J. Schneider, Rachel H Fong, P. Welinder, Bob McGrew, Josh Tobin, P. Abbeel, and W. Zaremba. Hindsight experience replay. 2017.

[4] András Antos, Csaba Szepesvári, and Rémi Munos. Fitted q-iteration in continuous action-space mdps. 20:9–16, 2008.

[5] Yoshua Bengio, Jérôme Louradour, Ronan Collobert, and Jason Weston. Curriculum learning. page 41–48, 2009.

[6] G. Brockman, V. Cheung, L. Pettersson, J. Schneider, J. Schulman, J. Tang, and W. Zaremba. Openai gym. 2016.

[7] Binghong Chen, Bo Dai, Qinjie Lin, G. Ye, H. Liu, and L. Song. Learning to plan in high dimensions via neural exploration-exploitation trees. 2020.

[8] Tao Chen, A. Murali, and A. Gupta. Hardware conditioned policies for multi-robot transfer learning. In *NeurIPS*, 2018.

[9] Hao-Tien Lewis Chiang, Aleksandra Faust, Marek Fiser, and Anthony Francis. Learning navigation behaviors end-to-end with autorl. *IEEE Robotics and Automation Letters*, 4:2007–2014, 2019.

[10] Michael Dennis, Natasha Jaques, Eugene Vinitsky, A. Bayen, Stuart J. Russell, Andrew Critch, and Sergey Levine. Emergent complexity and zero-shot transfer via unsupervised environment design. *ArXiv*, abs/2012.02096, 2020.

[11] C. Drummond. Accelerating reinforcement learning by composing solutions of automatically identified subtasks. *ArXiv*, abs/1106.1796, 2002.

[12] M. Elbanhawi and M. Simic. Sampling-based robot motion planning: A review. *IEEE Access*, 2:56–77, 2014.

[13] Benjamin Eysenbach, R. Salakhutdinov, and S. Levine. Search on the replay buffer: Bridging planning and reinforcement learning. In *NeurIPS*, 2019.

[14] Aleksandra Faust, O. Ramírez, Marek Fiser, Kenneth Oslund, A. Francis, James O. Davidson, and L. Tapia. Prm-rl: Long-range robotic navigation tasks by combining reinforcement learning and sampling-based planning. *2018 IEEE International Conference on Robotics and Automation (ICRA)*, pages 5113–5120, 2018.

[15] Carlos Florensa, J. Degrave, N. Heess, Jost Tobias Springenberg, and Martin A. Riedmiller. Self-supervised learning of image embedding for continuous control. *ArXiv*, abs/1901.00943, 2019.

[16] R. Fox, S. Krishnan, I. Stoica, and Ken Goldberg. Multi-level discovery of deep options. *ArXiv*, abs/1703.08294, 2017.

[17] Kevin Frans, Jonathan Ho, Xi Chen, P. Abbeel, and John Schulman. Meta learning shared hierarchies. *ArXiv*, abs/1710.09767, 2018.

[18] Dibya Ghosh, A. Gupta, Ashwin Reddy, Justin Fu, C. Devin, Benjamin Eysenbach, and S. Levine. Learning to reach goals via iterated supervised learning. *arXiv: Learning*, 2019.

[19] T. Haarnoja, Aurick Zhou, P. Abbeel, and S. Levine. Soft actor-critic: Off-policy maximum entropy deep reinforcement learning with a stochastic actor. 2018.

[20] T. Haarnoja, Aurick Zhou, Kristian Hartikainen, G. Tucker, Sehoon Ha, J. Tan, V. Kumar, H. Zhu, A. Gupta, P. Abbeel, and S. Levine. Soft actor-critic algorithms and applications. *ArXiv*, abs/1812.05905, 2018.

[21] P. E. Hart, N. J. Nilsson, and B. Raphael. A formal basis for the heuristic determination of minimum cost paths. *IEEE Transactions on Systems Science and Cybernetics*, 4(2):100–107, 1968.

[22] Donald J. Hejna, P. Abbeel, and Lerrel Pinto. Hierarchically decoupled imitation for morphological transfer. *ArXiv*, abs/2003.01709, 2020.

[23] D. Hsu, J. . Latombe, and R. Motwani. Path planning in expansive configuration spaces. 3:2719–2726 vol.3, 1997.

[24] T. Jurgenson, Or Avner, E. Groshev, and Aviv Tamar. Sub-goal trees - a framework for goal-based reinforcement learning. *ArXiv*, abs/2002.12361, 2020.

[25] L. Kaelbling. Hierarchical learning in stochastic domains: Preliminary results. In *ICML*, 1993.

[26] L. Kaelbling. Learning to achieve goals. In *IJCAI*, 1993.

[27] Sertac Karaman and Emilio Frazzoli. Sampling-based algorithms for optimal motion planning. *The International Journal of Robotics Research*, 30(7):846–894, 2011.

[28] L. E. Kavraki, P. Svestka, J. . Latombe, and M. H. Overmars. Probabilistic roadmaps for path planning in high-dimensional configuration spaces. *IEEE Transactions on Robotics and Automation*, 12(4):566–580, 1996.

[29] Diederik P. Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *CoRR*, abs/1412.6980, 2015.

[30] Sven Koenig and Reid G. Simmons. The effect of representation and knowledge on goal-directed exploration with reinforcement-learning algorithms. *Mach. Learn.*, 22(1–3):227–250, January 1996.

[31] Tejas D. Kulkarni, Karthik Narasimhan, A. Saeedi, and J. Tenenbaum. Hierarchical deep reinforcement learning: Integrating temporal abstraction and intrinsic motivation. In *NIPS*, 2016.

[32] M. Lau and J. Kuffner. Behavior planning for character animation. In *SCA '05*, 2005.

[33] S. M. LaValle. *Planning Algorithms*. Cambridge University Press, Cambridge, U.K., 2006.

[34] Steven M. Lavalle. Rapidly-exploring random trees: A new tool for path planning. 1998.

[35] L. Lee, Emilio Parisotto, Devendra Singh Chaplot, E. Xing, and R. Salakhutdinov. Gated path planning networks. In *ICML*, 2018.

[36] S. Levine, Y. Lee, V. Koltun, and Z. Popovic. Space-time planning with parameterized locomotion controllers. *ACM Trans. Graph.*, 30:23:1–23:11, 2011.

[37] Ofir Nachum, Shixiang Gu, H. Lee, and S. Levine. Data-efficient hierarchical reinforcement learning. In *NeurIPS*, 2018.

[38] Karl Pertsch, Oleh Rybkin, Frederik Ebert, Chelsea Finn, Dinesh Jayaraman, and S. Levine. Long-horizon visual planning with goal-conditioned hierarchical predictors. *ArXiv*, abs/2006.13205, 2020.

[39] Vitchyr H. Pong, Shixiang Gu, Murtaza Dalal, and S. Levine. Temporal difference models: Model-free deep rl for model-based control. *ArXiv*, abs/1802.09081, 2018.

[40] Markus Rickert, O. Brock, and A. Knoll. Balancing exploration and exploitation in motion planning. *2008 IEEE International Conference on Robotics and Automation*, pages 2812–2817, 2008.

[41] S. Ross, G. Gordon, and J. Bagnell. A reduction of imitation learning and structured prediction to no-regret online learning. 2011.

[42] Stuart J. Russell and Peter Norvig. *Artificial Intelligence: A Modern Approach.* Pearson Education, 2 edition, 2003.

[43] Nikolay Savinov, A. Dosovitskiy, and V. Koltun. Semi-parametric topological memory for navigation. *ArXiv*, abs/1803.00653, 2018.

[44] Tom Schaul, Daniel Horgan, Karol Gregor, and David Silver. Universal value function approximators. pages 1312–1320, 2015.

[45] J. Schrittwieser, I. Antonoglou, T. Hubert, K. Simonyan, L. Sifre, S. Schmitt, A. Guez, E. Lockhart, D Hassabis, and T. Graepel. Mastering atari, go, chess and shogi by planning with a learned model. 2019.

[46] John Schulman, Filip Wolski, Prafulla Dhariwal, Alec Radford, and Oleg Klimov. Proximal policy optimization algorithms. *CoRR*, abs/1707.06347, 2017.

[47] Ö. Simsek, Alicia P. Wolfe, and A. Barto. Identifying useful subgoals in reinforcement learning by local graph partitioning. In *ICML '05*, 2005.

[48] A. Srinivas, A. Jabri, P. Abbeel, S. Levine, and Chelsea Finn. Universal planning networks. *ArXiv*, abs/1804.00645, 2018.

[49] Richard S. Sutton and Andrew G. Barto. *Reinforcement Learning: An Introduction.* A Bradford Book, Cambridge, MA, USA, 2018.

[50] Richard S. Sutton, David McAllester, Satinder Singh, and Yishay Mansour. Policy gradient methods for reinforcement learning with function approximation. NIPS'99, page 1057–1063, Cambridge, MA, USA, 1999. MIT Press.

[51] A. Tamar, S. Levine, P. Abbeel, Yi Wu, and G. Thomas. Value iteration networks. 2016.

[52] Yuval Tassa, Yotam Doron, Alistair Muldal, Tom Erez, Yazhe Li, Diego de Las Casas, David Budden, Abbas Abdolmaleki, Josh Merel, Andrew Lefrancq, Timothy P. Lillicrap, and Martin A. Riedmiller. Deepmind control suite. 2018.

[53] Rui Wang, J. Lehman, J. Clune, and K. Stanley. Paired open-ended trailblazer (poet): Endlessly generating increasingly complex and diverse learning environments and their solutions. *ArXiv*, abs/1901.01753, 2019.

[54] Y. Wu, G. Tucker, and Ofir Nachum. The laplacian in rl: Learning representations with efficient approximations. *ArXiv*, abs/1810.04586, 2019.