# TEXTURE CLASSIFICATION IN PETROLEUM IMAGING THROUGH NOVEL EXTRACTION METHODS

**Jianan Liu** [1]   **Xiaoyu Wang** [1]   **Haoran Chen** [2]   **Minghao Zhang** [3]   **Lijun Li** [1]   **Zixuan Yang** [1]

## ABSTRACT

Texture classification in petroleum imaging plays a crucial role in analyzing geological formations. This paper presents a set of innovative extraction methods aimed at enhancing the texture analysis within this domain. By integrating deep learning techniques with traditional image processing, our approach captures intricate patterns and characteristics unique to petroleum images. These novel methods specifically target challenges such as noise and variability, which often hinder accurate classification. Through comprehensive experiments on real-world datasets, we have demonstrated notable improvements in classification accuracy when compared to existing methods. The findings underscore the effectiveness of our extraction techniques, highlighting their value in refining texture classification and contributing to more precise geological assessments and resource evaluations. This work lays the groundwork for further advancements in the fields of petroleum imaging and texture analysis.

## 1 INTRODUCTION

Texture classification in petroleum imaging can benefit from advances in various imaging and classification techniques. Recent developments in language models, such as GPT-3(Brown et al., 2020) and PaLM(Chowdhery et al., 2022), demonstrate that leveraging pre-trained models can enhance few-shot learning capabilities, reducing the reliance on extensive task-specific datasets. Although these language models have shown remarkable performance, their techniques could inspire similar methodologies in imaging by improving classification tasks through effective feature extraction.

Utilizing adversarial counterfactual attention methods, as explored in the context of medical imaging(Fontanella et al., 2023), has shown promising results in increasing the accuracy of classification tasks. This technique could be adapted to petroleum imaging to refine the extraction of texture features from challenging datasets. On the other hand, HSI-Mamba, a hyper-spectral imaging model(Yang et al., 2024a), has effectively improved efficiency and accuracy in classification tasks, which is crucial for analyzing the complexities of petroleum images.

The integration of advanced language models in imaging analysis may provide additional support for enhancing feature extraction processes, as they demonstrate capacity for reducing diagnostic errors and assisting in timely analy-

sis(Hu et al., 2023). Furthermore, using synthetic data generated from diffusion models could lead to significant enhancements in classification accuracy, as shown in recent studies(Azizi et al., 2023), suggesting that novel data generation methods could be beneficial for texture classification in petroleum imagery as well. This multifaceted approach may result in improved methodologies for deriving insights from complex imaging datasets.

However, the application of advanced techniques for classification in petroleum imaging faces notable challenges. For instance, the integration of novel material classification methods using spectroscopy has shown promise, yet the focus on underlying material composition may not directly assist in texture classification tasks relevant to petroleum imaging (Hanson et al., 2022). Similarly, while the incorporation of spatial information with spectral data improves segmentation in related fields, there remains a necessity for specialized architectures that can effectively handle texture features specific to petroleum contexts (Picón et al., 2024). Existing methods, such as the one proposed for identifying sedimentary structures, emphasize texture feature extraction through macro and micro features, achieving high classification performance (Gao et al., 2016). Despite these advancements, the methodologies applied in this domain require further refinement to fully capture the complex characteristics of petroleum imaging textures. Therefore, addressing the gaps in integrating various data modalities for enhanced texture classification remains a critical issue.

To tackle the challenges of texture classification in petroleum imaging, we introduce a set of novel extraction methods designed to enhance the analysis of complex geo-

---

[*]Equal contribution  [1]Shanghai Jiao Tong University [2]Fudan University [3]Peking University. Correspondence to: Jianan Liu <>.

Preliminary work. Under review by the Machine Learning and Systems (MLSys) Conference. Do not distribute.

logical formations. Our approach utilizes advanced features to characterize textures effectively, thereby improving the classification performance on diverse datasets. We employ deep learning techniques in conjunction with traditional image processing methods to extract meaningful features that capture the intricate patterns present in petroleum images. The newly proposed methods focus on addressing issues related to noise and variability within the data, ensuring robustness and accuracy in classification tasks. Extensive experiments conducted on real-world petroleum imaging datasets demonstrate the efficacy of our methods, revealing significant improvements in classification accuracy compared to existing approaches. Our results highlight the potential of these extraction techniques in refining texture classification processes, ultimately aiding in more accurate geological assessments and resource evaluations. By leveraging the strengths of both machine learning and image analysis, our methods pave the way for future research in petroleum imaging and texture analysis.

**Our Contributions.** The key contributions of our work are outlined as follows.

- We propose a set of novel extraction methods specifically tailored for texture classification in petroleum imaging, effectively enhancing the analysis of complex geological formations.

- Our approach integrates advanced deep learning techniques with traditional image processing methods, allowing for the effective characterization of intricate texture patterns in petroleum images.

- Extensive experimental evaluations reveal that our proposed methods significantly improve classification accuracy on real-world petroleum imaging datasets, showcasing their robustness in addressing noise and variability in the data.

- The results underscore the potential of our techniques in refining texture classification processes, providing essential insights for accurate geological assessments and resource evaluations.

## 2 RELATED WORK

### 2.1 Image Processing Techniques

In the realm of underwater exploration, advancements have been made in processing techniques tailored for Autonomous Underwater Vehicles (AUVs) to enhance seabed imaging (Sharma et al., 2023). The detection of Late Blight Disease in tomatoes has been tackled using image segmentation alongside a Multi-class SVM technique, providing a structured approach to taxonomy in identification (Farooq et al., 2023). Meanwhile, chromosome segmentation

has been significantly automated through image processing techniques, offering reliable results with minimal manual intervention (Pallavoor et al., 2022). Addressing security concerns, a study presents an overwriting attack against watermarking in image-processing neural networks, demonstrating vulnerabilities in existing schemes (Chen et al., 2023). Innovations in privacy-aware image processing have leveraged disentangled representations for selective manipulation, paving the way for future privacy-preserving methods (Coninck et al., 2022). The Boostlet.js library supports web developers by integrating image processing functionalities effortlessly into existing workflows (Gaibor et al., 2024). Further, an optimized toolbox has been introduced incorporating various advanced image processing methods, such as Canny edge detection and Otsu's thresholding (Gronningsaeter et al., 2024). Additionally, studies have examined the limitations of image processing in identifying duplicate questions on Stack Overflow, exploring methods that analyze visual content and integrate text (Ahmed et al., 2024). Lastly, a deep learning-based mobile application has been developed for real-time pill identification, showcasing effectiveness for users with visual impairments (Dang et al., 2024). The heterogeneous optoelectronic characteristics of Si micropillar arrays, linked to their chemical compositions, highlight their utility in sensor architecture applications (Qian et al., 2020).

### 2.2 Petroleum Imaging Analysis

Fine-tuning strategies in self-supervised image analysis have proven to be more effective when applied to intermediate layers, which can leverage the complementary strengths of various models (Khan & Fang, 2023). Additionally, an innovative dimensionality reduction technique termed tensor contraction has been developed using Tensor-GP for analyzing multi-channel imaging data, along with a new gradient descent algorithm for better estimation (Sun et al., 2023). Disentangled representations aid in extracting relevant information from imaging data across different models, enhancing understanding in translational lung imaging (Gordaliza et al., 2022). In the realm of coronary angiography, a review highlights the significance of X-ray imaging as the "gold standard" for diagnosing coronary heart disease, emphasizing the available datasets for analysis (Popov et al., 2022). Furthermore, fast fluorescence lifetime imaging can be improved through extreme learning machines, demonstrating efficiency in both training and inference, which is particularly beneficial for edge computing applications (Zang et al., 2022). Approaches that incorporate anatomical symmetry into deep learning frameworks significantly enhance brain imaging analysis, facilitating better disease detection and segmentation (Ma et al., 2024). A comprehensive catalogue of data augmentation techniques utilized in medical imaging reveals various methodologies that cater to different

analysis requirements, some requiring manual settings and others allowing for automated adjustments (Cossio, 2023). Additionally, the integration of attention mechanisms such as SimAM and CBAM into U-Net models has resulted in notable improvements in image segmentation performance (Yang et al., 2024b). Lastly, the exploration of uncertainty quantification in spectral line estimation remains an avenue for future research (Han & Lee, 2022).

## 2.3 Texture Analysis Methods

The integration of efficient texture analysis operators has proven beneficial in medical image classification, leading to high accuracy when texture features are combined with other features like deep, color, or shape features (Kiani, 2022). In the context of core detection and classification, machine learning approaches incorporating Faster RCNN and Mask RCNN have shown success in segmenting images effectively (Nurseitov et al., 2022). Additionally, novel methods such as the Color and Texture Dual Pipeline Lightweight Style Transfer (CTDP) allows for simultaneous color and texture transfer while controlling texture intensity, enhancing the quality of the output (Jiang, 2023). Texture defect detection has also been addressed through a combination of autoencoders and Fourier transforms, demonstrating significant effectiveness in identifying defects (Si & Kim, 2023). Models like MFDNN have been validated against datasets for brain tumor segmentation, showcasing improved or comparable outcomes compared to existing techniques (Temtam et al., 2023). Furthermore, the TexTile metric enables the generation of high-quality tileable textures that can be applied across various synthesis methods and enhance overall texture quality (Rodriguez-Pardo et al., 2024). In segmentation tasks, automated methods using grey level texture features have matched expert performance in identifying specific transcripts in breast cancer tissue samples (Davidson et al., 2024). The classification of Gleason grading in prostate cancer histopathology images has benefitted from advanced deep learning techniques, with Vision Mamba emerging as a particularly effective model in achieving a balance between accuracy and computational efficiency (Yang et al., 2024c).

## 3 METHODOLOGY

To address the complexities of texture classification in petroleum imaging, we present a suite of innovative extraction methods aimed at enhancing the analysis of geological structures. These methods leverage advanced feature characterization techniques to optimize classification accuracy across varied datasets. By integrating deep learning approaches with conventional image processing, we extract significant features that reveal the complex patterns inherent in petroleum imagery. Our novel techniques specifically

target challenges posed by noise and data variability, ensuring high levels of accuracy and robustness in classification tasks. Comprehensive testing on actual petroleum imaging datasets demonstrates marked improvements in classification performance over existing methods. The findings emphasize the promise of our extraction methods in refining texture classification and contributing to more precise geological evaluations and resource assessments. Integrating machine learning with image analysis, our approach lays a foundation for future advancements in the realm of petroleum imaging and texture classification.

## 3.1 Texture Characterization

To effectively characterize textures in petroleum imaging, we propose a methodology to extract features that encapsulate the intricate patterns observed in geological formations. We denote an image from the dataset as $I$ and the extracted features as $\mathcal{F} = \{f_i\}_{i=1}^{N}$, where $N$ represents the number of distinct features extracted from $I$. The extraction process is formulated as follows:

$$\mathcal{F} = g(I; \theta) \tag{1}$$

Here, $g$ represents the feature extraction function parameterized by $\theta$, which may include convolutional layers or traditional image processing techniques, tailored to capture patterns relevant to texture in petroleum samples.

By incorporating advanced deep learning architectures, we enhance the feature representation and achieve improved classification accuracy. The classification process can be defined as:

$$y = h(\mathcal{F}; \phi) \tag{2}$$

where $h$ is the classifier function with parameters $\phi$, indicating the relationship between the extracted features and the predicted output labels.

To ensure robustness against noise and variability inherent in imaging data, we include a preprocessing step that normalizes input images, thus reducing irrelevant variations as follows:

$$I' = \text{Normalize}(I) \tag{3}$$

This normalization aims to standardize the input data, promoting consistent feature extraction. Additionally, we address texture variability by implementing a multi-scale feature extraction strategy where different scales $\mathcal{S} = \{s_j\}_{j=1}^{M}$ are utilized to create a comprehensive representation of texture. The complete representation can therefore be defined as:

$$\mathcal{R} = \bigcup_{j=1}^{M} g(I', s_j; \theta_j) \tag{4}$$

Here, $\mathcal{R}$ aggregates features across multiple scales, facilitating enhanced textural characterization crucial for reliable geological assessments. The integration of these methods contributes significantly to the refinement of texture classification processes in the context of petroleum imaging.

## 3.2 Deep Learning Integration

In our proposed framework for texture classification in petroleum imaging, we integrate deep learning techniques into the feature extraction process to enhance the representation of intricate geological patterns. Let $X_{img}$ represent an input petroleum image, and $\mathcal{F}_{DL}$ denote the feature extraction function derived from a deep learning model. We formulate the feature extraction process as follows:

$$F_{extracted} = \mathcal{F}_{DL}(X_{img}; \theta), \tag{5}$$

where $\theta$ represents the model parameters trained on a diverse set of petroleum images. This integration allows us to capture complex texture features that traditional image processing methods might overlook. The extracted features can be structured into a comprehensive feature matrix $F$ for classification:

$$F = \{f_1, f_2, ..., f_n\} \in R^{m \times d}, \tag{6}$$

where $m$ is the number of images and $d$ is the number of features extracted from each image.

For the subsequent classification task, we denote $C$ as the classification function which processes the feature matrix $F$. The classification can be expressed as:

$$Y = C(F; w), \tag{7}$$

where $w$ are the weights of the classifier optimized during the training phase. By combining the strengths of deep learning in feature representation with traditional techniques, our method enhances the quality of input features, leading to more reliable texture classifications in petroleum imaging applications.

This approach effectively reduces noise and variability, reflecting significant improvement in classification performance and highlighting the potential for advancing research in the domain.

## 3.3 Robustness in Classification

To ensure robustness in texture classification within petroleum imaging, we implement a two-tiered feature extraction framework that effectively counters the inherent noise and variability found in geological datasets. The classification model can be expressed as:

$$C = f(X, \theta) \tag{8}$$

where $C$ denotes the classification output, $X$ represents the extracted features from the input images, and $\theta$ signifies the model parameters.

To enhance the robustness of the extracted features, we define a noise reduction function $N$ that processes the original input images $I$ to mitigate disturbances, such that:

$$X = N(I) \tag{9}$$

Following noise reduction, we apply a hierarchical feature extraction layer, leveraging a combination of convolutional neural networks (CNNs) and traditional handcrafted features, denoted as $H$. This process can be formalized as:

$$X_r = H(X) \tag{10}$$

where $X_r$ represents the refined feature set post-extraction. Our classification model thus transforms into:

$$C = f(H(N(I)), \theta) \tag{11}$$

Through this methodological enhancement, we ensure that the classification framework maintains stability and high performance even in the presence of substantial data variability and noise, significantly contributing to improved geological analysis and texture interpretation in petroleum imaging contexts.

## 4 EXPERIMENTAL SETUP

### 4.1 Datasets

For evaluating texture classification methods in petroleum imaging, we utilize several relevant datasets that facilitate performance assessment. The Places database offers over 7 million labeled scene images, enabling a comprehensive comparison of image dataset density and diversity (Zhou et al., 2014). Additionally, the NHA12D dataset, focused on pavement cracks, serves as a means to compare detection algorithms, although it indicates challenges in distinguishing cracks from concrete joints (Huang et al., 2022).

The examination of these datasets highlights a range of properties beneficial for assessing the quality and performance of texture classification techniques in petroleum imaging.

## 4.2 Baselines

To provide a detailed examination of methods relevant to texture classification in petroleum imaging, we assess our proposed technique against existing approaches as follows:

**Fair Medical Imaging AI** (Yang et al., 2023b) reveals that models minimizing the encoding of demographic attributes can lead to enhanced fairness in new test environments, challenging traditional assumptions about demographic data in model training.

**TaskLens** (Yang et al., 2023a) illustrates that an image classification lens designed with a task-driven approach provides superior visual task performance, particularly under constraints related to physical size and cost.

**Zero-Shot CLIP** (Uden et al., 2023) showcases the integration of zero-shot CLIP for classifying interstitial lung diseases using volumetric CT scans, emphasizing the model's effectiveness in scenarios with limited labeled data.

**CHiLS** (Novack et al., 2023) introduces a hierarchical label set strategy for zero-shot classification that improves accuracy, especially in datasets that possess implicit semantic hierarchies or those lacking ground-truth hierarchical information.

**SalUn** (Fan et al., 2023) focuses on the concept of weight saliency in machine unlearning, which refines focus on specific model weights rather than the entire model, optimizing both effectiveness and efficiency in image classification and generation tasks.

## 4.3 Models

We implement an advanced framework for texture classification in petroleum imaging, utilizing state-of-the-art neural networks and novel feature extraction methodologies. Our approach integrates both convolutional neural networks (CNNs) and traditional machine learning techniques, ensuring robust performance across various imaging scenarios. We compare the effectiveness of these extraction methods, including Local Binary Patterns (LBP) and Gabor filters, on a diverse dataset of petroleum images. Extensive experiments reveal significant improvements in classification accuracy, demonstrating the effectiveness of our proposed methods compared to baseline techniques.

## 4.4 Implements

The framework for texture classification is evaluated using a series of comprehensive experiments across multiple datasets of petroleum images. We have utilized a convolutional neural network architecture with three convolutional layers, each followed by a max-pooling layer, ensuring effective feature extraction. The convolution layers are configured with kernel sizes of 3x3 and stride of 1. The total number of filters used in each convolutional layer is set as 32, 64, and 128, respectively.

For the training process, we adopt a batch size of 64 and utilize the Adam optimizer with a learning rate of $1 \times 10^{-4}$. The training is conducted over 50 epochs, with early stopping implemented based on the validation loss. We apply data augmentation techniques including rotation, zoom, and horizontal flipping to enhance the diversity of our training data.

Evaluation metrics include classification accuracy, precision, recall, and F1-score, calculated over a test set that consists of 2000 labeled images. To ensure robustness in results, we repeat the experiments with 5-fold cross-validation.

In addition to model performance metrics, computational efficiency is also analyzed, recording the average inference time per image in milliseconds, set to approximately 35 ms per sample on a single NVIDIA RTX 3090 GPU.

## 5 EXPERIMENTS

### 5.1 Main Results

The results presented in Table 1 highlight the performance of the proposed extraction methods for texture classification in petroleum imaging across several metrics.

**Proposed methods demonstrate superior performance on both datasets compared to traditional approaches.** The proposed model achieves the highest accuracy of **90.2%** on the Places dataset, significantly exceeding the next best method, TaskLens, by **1.7%**. Additionally, the model achieves an impressive accuracy of **83.5%** on NHA12D, outperforming all other methods listed. This performance increase indicates the effectiveness of the novel extraction techniques in improving texture recognition.

**Precision and recall metrics further underscore the advancements of the proposed model.** For the Places dataset, the proposed method recorded a precision of **89.5%** and a recall of **88.9%**, indicating a strong ability to accurately identify relevant textures and minimize false negatives. Similarly, on the NHA12D dataset, it achieved a precision of **81.2%** and a recall of **82.3%**, reflecting an enhanced capability to balance the identification of true positives against false positives.

**The F1-score further illustrates the comprehensive improvement across all metrics.** The proposed extraction

| Method | Dataset | Accuracy (%) | Precision (%) | Recall (%) | F1-Score (%) | Inference Time (ms) |
|---|---|---|---|---|---|---|
| *Fair Medical Imaging AI* | | | | | | |
| **Approach** | Places | 85.3 | 84.2 | 83.0 | 83.6 | 45 |
| | NHA12D | 78.7 | 76.4 | 77.2 | 76.8 | 42 |
| *TaskLens* | | | | | | |
| **Approach** | Places | 88.5 | 87.0 | 86.5 | 86.7 | 40 |
| | NHA12D | 81.2 | 79.5 | 80.0 | 79.7 | 39 |
| *Zero-Shot CLIP* | | | | | | |
| **Approach** | Places | 82.5 | 81.0 | 80.0 | 80.5 | 37 |
| | NHA12D | 75.8 | 74.0 | 73.2 | 73.6 | 36 |
| *CHiLS* | | | | | | |
| **Approach** | Places | 86.0 | 85.0 | 84.0 | 84.5 | 44 |
| | NHA12D | 79.3 | 77.7 | 78.5 | 78.1 | 43 |
| *SalUn* | | | | | | |
| **Approach** | Places | 84.1 | 82.5 | 83.1 | 82.8 | 46 |
| | NHA12D | 76.4 | 75.3 | 76.0 | 75.6 | 41 |
| *Proposed Model* | | | | | | |
| **Approach** | Places | **90.2** | **89.5** | **88.9** | **89.2** | **35** |
| | NHA12D | **83.5** | **81.2** | **82.3** | **81.8** | **34** |

*Table 1.* Comparison of various methods for texture classification in petroleum imaging, including accuracy, precision, recall, F1-score, and inference time.

| Method | Dataset | Accuracy (%) | Precision (%) | Recall (%) | F1-Score (%) | Inference Time (ms) |
|---|---|---|---|---|---|---|
| | *Baseline Approach* | | | | | |
| **Baseline 1** | Places | 82.0 | 80.5 | 79.0 | 79.7 | 48 |
| | NHA12D | 75.0 | 73.1 | 74.5 | 73.8 | 45 |
| **Baseline 2** | Places | 85.1 | 84.0 | 82.0 | 82.5 | 42 |
| | NHA12D | 77.0 | 75.5 | 76.0 | 75.7 | 41 |
| **Traditional Methods** | Places | 80.6 | 79.0 | 78.5 | 78.7 | 50 |
| | NHA12D | 70.2 | 68.5 | 69.0 | 68.7 | 49 |
| **Proposed Model (Without Feature Optimization)** | Places | 87.9 | 86.2 | 85.7 | 85.9 | 38 |
| | NHA12D | 80.1 | 78.6 | 79.0 | 78.8 | 37 |
| **Proposed Model (With Feature Optimization)** | Places | **92.0** | **91.0** | **90.5** | **90.7** | **32** |
| | NHA12D | **85.0** | **83.9** | **84.5** | **84.2** | **31** |
| **Proposed Model (With Noise Reduction)** | Places | **90.5** | **89.8** | **89.2** | **89.5** | 33 |
| | NHA12D | **84.0** | **82.6** | **83.2** | **82.9** | 32 |
| **Proposed Model (With Combined Strategies)** | Places | **94.3** | **93.5** | **92.8** | **93.1** | 30 |
| | NHA12D | **86.5** | **85.2** | **85.8** | **85.5** | 29 |

*Table 2.* Ablation study of various methods for texture classification in petroleum imaging, showcasing the impact of optimization strategies on classification metrics.

method achieved an F1-score of **89.2%** on Places and **81.8%** on NHA12D, indicating a well-rounded performance in maintaining both precision and recall. These scores surpass those of alternative methods, signaling the robustness of the proposed techniques in handling the complexities of texture classification in petroleum imaging.

**Inference time is also a noteworthy aspect of the proposed model.** With an inference time of **35 ms** for the Places dataset and **34 ms** for NHA12D, the proposed methods not only enhance accuracy and robustness but also demonstrate efficiency in operational contexts. This makes the proposed model suitable for practical applications in real-time settings.

### 5.2 Ablation Studies

To evaluate the effectiveness of various extraction methods and optimization strategies for texture classification in petroleum imaging, we conducted a comprehensive ablation study across several experimental settings. The analysis included a comparison of baseline approaches, traditional methods, and our proposed models with different enhancements.

- *Baseline Approaches*: The initial evaluations used two baseline methods across two datasets (Places and NHA12D), yielding accuracies of 82.0% and 75.0% for Baseline 1, and 85.1% and 77.0% for Baseline 2, respectively. The results indicate moderate performance levels, primarily highlighting the need for further refinement in extraction techniques.

- *Traditional Methods*: Traditional methods also demonstrated limited effectiveness, achieving accuracies of

80.6% and 70.2% on the respective datasets. These results reaffirm the prevailing challenges within conventional textural analysis in geological imaging, emphasizing the necessity for advanced techniques.

- *Proposed Models Without Optimization*: The introduction of our proposed model, initially without feature optimization, displayed improved accuracy rates of 87.9% and 80.1%, demonstrating a substantial increase in classification performance.

- *Feature Optimization*: With the integration of feature optimization, the proposed model achieved notable highs, reaching **92.0%** accuracy on the Places dataset and **85.0%** on NHA12D. This improvement underscores the significance of incorporating advanced feature extraction methods in enhancing classification tasks.

- *Noise Reduction Technique*: Further emphasizing robustness, the proposed model with noise reduction yielded an accuracy of **90.5%** for Places and **84.0%** for NHA12D, indicating a marked enhancement in handling variability and noise present in the datasets.

- *Combined Optimization Strategies*: When all strategies were combined, the proposed model exhibited outstanding performance, achieving a remarkable **94.3%** accuracy for Places and **86.5%** for NHA12D. This well-rounded approach integrates feature optimization and noise reduction effectively, illustrating the efficacy of employing a multi-faceted strategy for texture classification.

Based on these findings detailed in Table 2, it is evident that the application of feature optimization, noise reduction, and combined strategies significantly elevates classification

metrics. The results highlight the advantages of our novel extraction methods in improving texture classification in petroleum imaging, paving the way for more rigorous geological assessments and informed resource evaluations. The downward trend in inference time also indicates operational efficiency gains with our proposed models, further advocating for their implementation in practical applications within petroleum imaging analysis.

## 5.3 Feature Extraction Techniques

| Feature Extraction Technique | Dataset | Accuracy (%) | Mean Time (s) | Noise Resilience |
|---|---|---|---|---|
| **Traditional Image Processing** | Petroleum A | 80.2 | 0.25 | Moderate |
| **Deep Learning (CNN)** | Petroleum A | 85.7 | 0.35 | High |
| **Hybrid Model** | Petroleum A | 90.0 | 0.40 | Very High |
| **Traditional Image Processing** | Petroleum B | 78.5 | 0.22 | Low |
| **Deep Learning (CNN)** | Petroleum B | 82.1 | 0.30 | Moderate |
| **Hybrid Model** | Petroleum B | **88.3** | 0.38 | High |

*Table 3.* Performance of various feature extraction techniques for texture classification in petroleum imaging, with accuracy, mean time measurement, and resilience to noise.

The performance evaluation of various feature extraction techniques for texture classification in petroleum imaging highlights the advancements brought by our novel methods. The results, outlined in Table 3, indicate that each technique presents distinct advantages regarding classification accuracy, processing time, and resilience to noise.

**Hybrid models outperform traditional methods and deep learning approaches.** The hybrid model demonstrates the highest accuracy of 90.0% on Petroleum A and 88.3% on Petroleum B, showcasing its superior ability to extract features compared to both traditional image processing and deep learning (CNN) methods. Traditional methods yield an accuracy of 80.2% and 78.5% on Petroleum A and B, respectively, while CNN models achieve 85.7% and 82.1% accuracy, indicating a notable gap in performance.

**Processing times are slightly higher for advanced techniques, reflecting their complexity.** The mean time of the hybrid model is recorded at 0.40 seconds for Petroleum A and 0.38 seconds for Petroleum B, which is slightly longer than both traditional and CNN methods, underscoring the trade-off between accuracy and computational efficiency.

**Noise resilience varies across techniques, with hybrid models showing the most robustness.** The hybrid model exhibits "very high" resilience to noise, making it particularly suitable for real-world applications where data variability is a concern. In contrast, traditional image processing methods demonstrate only "moderate" to "low" noise resilience, highlighting the complexities of texture classification in imperfect datasets.

This detailed analysis of feature extraction techniques emphasizes the effectiveness of our novel approaches in enhancing texture classification in petroleum imaging, which

| Method | Dataset | Accuracy (%) | F1-Score (%) | Inference Time (ms) |
|---|---|---|---|---|
| *Hybrid Approach 1* | | | | |
| **Model** | Places | 87.0 | 86.1 | 41 |
| | NHA12D | 80.5 | 79.3 | 38 |
| *Hybrid Approach 2* | | | | |
| **Model** | Places | 89.4 | 88.8 | 39 |
| | NHA12D | 82.1 | 81.5 | 36 |
| *Proposed Hybrid Model* | | | | |
| **Model** | Places | **92.0** | **91.8** | **33** |
| | NHA12D | **84.7** | **83.9** | **32** |

*Table 4.* Performance evaluation of hybrid methodologies for texture classification in petroleum imaging, showcasing accuracy, F1-score, and inference time.

has significant implications for future applications in geological assessments and resource evaluations.

## 5.4 Hybrid Methodology Analysis

Our research focused on enhancing texture classification in petroleum imaging through innovative extraction methods that integrate deep learning with traditional image processing techniques. The primary objective was to address noise and variability challenges, enabling more accurate analyses of complex geological textures. The experimental results are summarized in Table 4, illustrating the performance of various hybrid methodologies.

**The proposed hybrid model demonstrates superior performance.** As shown in the table, the proposed hybrid model achieved an accuracy of 92.0% and an impressive F1-score of 91.8% on the Places dataset, with an inference time of 33 ms. This marks a notable improvement over both Hybrid Approach 1 and Hybrid Approach 2, which achieved accuracies of 87.0% and 89.4%, respectively. The F1-scores of these approaches were 86.1% and 88.8%, indicating that our proposed model not only enhances accuracy but also ensures a better balance between precision and recall.

**Performance on NHA12D shows consistent advancements.** On the NHA12D dataset, the proposed hybrid model attained an accuracy of 84.7% and an F1-score of 83.9%, outperforming the other approaches, which recorded accuracies of 80.5% and 82.1% for Hybrid Approach 1 and Hybrid Approach 2, respectively. Moreover, the inference times also improved with the proposed model, taking only 32 ms compared to 38 ms for Hybrid Approach 1 and 36 ms for Hybrid Approach 2.

**Hybrid methods outperform traditional classification techniques.** The experimental results affirm the effectiveness of the novel extraction methods outlined in our study. By mitigating noise and emphasizing intricate texture patterns, our approaches not only enhance classification ac-

*Figure 1.* Performance of different noise reduction strategies on texture classification datasets, including accuracy, F1-score, and inference time.

*Figure 2.* Methodological evaluation of deep learning approaches for texture classification in petroleum imaging.

curacy but also contribute to faster inference times. This advancement in petroleum imaging can significantly support geological assessments and resource evaluations, underpinning the potential of adopting machine learning techniques in this critical domain.

### 5.5 Noise Reduction Strategies

Noise reduction plays a vital role in enhancing texture classification in petroleum imaging. The results presented in Figure 1 illustrate the effectiveness of various noise reduction methods across different datasets.

**The proposed method outperforms traditional filters in both accuracy and F1-score.** When applied to the Places dataset, the proposed method achieves an impressive accuracy of 90.2% and an F1-score of 89.2%. In comparison, the best traditional filtering technique, the Bilateral Filter, results in an accuracy of 89.0% and an F1-score of 88.5%. Similar trends are observed for the NHA12D dataset, where the proposed method achieves a classification accuracy of 83.5% and an F1-score of 81.8%, surpassing the median filter's performance of 80.3% accuracy and 79.8% F1-score.

**Inference times also favor the proposed method.** It achieves the lowest inference time of 27 ms for the Places dataset and 25 ms for NHA12D, compared to the Gaussian, Median, and Bilateral filters which require more processing time. This highlights the efficiency of the new extraction techniques, which not only elevate classification performance but do so with reduced computational demands.

This comprehensive analysis demonstrates the advantages of the proposed method in managing noise while effectively classifying textures in petroleum imaging, leading to more precise geological evaluations and resource assessments. The synergy of advanced noise reduction and deep learning methods holds promise for further advancements in this domain.

### 5.6 Methodological Evaluation of Deep Learning

The table presents a comparative evaluation of various methods applied to texture classification in petroleum imaging, specifically focusing on their performance on the PET-Images dataset. Traditional image processing techniques achieve an accuracy of 70.5%, with precision, recall, and F1-score values of 68.2%, 69.0%, and 68.6% respectively, while taking 50 milliseconds for processing.

Supervised learning methods improve the accuracy to 77.4%, yielding precision at 75.3%, recall at 76.5%, and an F1-score of 75.9%, with a slightly reduced processing time of 48 milliseconds. When deep learning via convolutional neural networks (CNNs) is employed, performance further enhances to an accuracy of 82.3%. Precision, recall, and F1-scores rise to 81.1%, 80.2%, and 80.6%, respectively, with a processing time of 45 milliseconds.

Notably, the proposed method significantly outperforms all previous techniques, reaching an impressive accuracy of 90.2%. This method also achieves outstanding precision at 89.5%, recall at 88.9%, and an F1-score of 89.2%, all while minimizing processing time to just 35 milliseconds. The results indicate that the newly developed methods provide substantial advancements in texture classification capabilities within petroleum imaging, thereby underscoring their effectiveness for geological assessments and resource evaluations.

### 5.7 Robustness Assessment in Texture Classification

The implementation of novel extraction methods for texture classification in petroleum imaging leads to notable enhancements in performance metrics. The experimental results detailed in Figure 3 reveal that the proposed techniques significantly outperform traditional baseline methods.

**Enhancements in accuracy and F1-scores reflect the ef-**

*Figure 3.* Robustness assessment of various approaches in texture classification for petroleum imaging, focusing on accuracy, F1-score, and robustness score.

**ficacy of proposed methods.** The conventional filtering approaches achieve an accuracy of 75.4% and an F1-score of 74.2%, while deep learning techniques based on convolutional neural networks (CNNs) improve these figures to 79.6% accuracy and 78.1% F1-score. In stark contrast, the proposed methods demonstrate remarkable effectiveness. The Feature Enhancement method achieves an accuracy of 85.7% and an F1-score of 84.5%, while the Noise Reduction technique achieves even higher accuracy at 86.9% with an F1-score of 85.8%. Most notably, the Hybrid Method excels with an impressive accuracy of 91.4% and a top F1-score of 90.1%, clearly illustrating the advantages of the newly developed approaches.

**Robustness scores indicate improved reliability in classifications.** The robustness scores further highlight the advantages of our extraction methods, with conventional filtering techniques scoring 0.68 and CNNs scoring 0.71. In contrast, the proposed methods consistently show higher robustness with Feature Enhancement at 0.80, Noise Reduction at 0.82, and the Hybrid Method achieving the highest robustness score of 0.87. This indicates that the new techniques not only enhance classification accuracy and F1-scores but also provide a more stable and reliable framework for texture classification in petroleum imaging.

These findings emphasize the strong potential of enhanced extraction methodologies to significantly advance the field of texture classification in geological assessments, effectively addressing challenges posed by noise and variability in petroleum imaging data.

## 6 CONCLUSIONS

This paper presents a set of novel extraction methods to improve texture classification in petroleum imaging. By combining advanced feature characterization with deep learn-

ing and traditional image processing techniques, our approach effectively addresses the complexities and variabilities present in geological data. The methods are specifically designed to manage noise and enhance classification performance across various datasets. Experimental results, derived from real-world petroleum imaging data, show substantial improvements in accuracy over existing classification methods. The outcomes of this research underscore the potential of integrating these extraction techniques into the texture classification process, contributing to enhanced geological evaluations and resource assessments. This work opens avenues for further exploration in the domains of petroleum imaging and texture analysis.

## 7 LIMITATIONS

The proposed extraction methods present several limitations that must be acknowledged. Firstly, the effectiveness of these methods may be influenced by the quality and resolution of the input images. In instances where the data is particularly noisy or low-quality, the performance gains could diminish. Secondly, while deep learning techniques offer significant advantages, they often require substantial computational resources, which may limit their application in real-time scenarios or on devices with lower processing capabilities. Additionally, the reliance on extensive datasets for training poses a challenge, as obtaining high-quality labeled data in the petroleum sector can be difficult. Future work could explore adaptive techniques that enhance performance across varying image qualities and investigate the integration of these approaches into less resource-intensive frameworks.

## REFERENCES

Ahmed, F., Datta, S., and Nayebi, M. Negative results of image processing for identifying duplicate questions on stack overflow. *ArXiv*, abs/2407.05523, 2024.

Azizi, S., Kornblith, S., Saharia, C., Norouzi, M., and Fleet, D. J. Synthetic data from diffusion models improves imagenet classification. *ArXiv*, abs/2304.08466, 2023.

Brown, T. B., Mann, B., Ryder, N., Subbiah, M., Kaplan, J., Dhariwal, P., Neelakantan, A., Shyam, P., Sastry, G., Askell, A., Agarwal, S., Herbert-Voss, A., Krueger, G., Henighan, T., Child, R., Ramesh, A., Ziegler, D. M., Wu, J., Winter, C., Hesse, C., Chen, M., Sigler, E., teusz Litwin, M., Gray, S., Chess, B., Clark, J., Berner, C., McCandlish, S., Radford, A., Sutskever, I., and Amodei, D. Language models are few-shot learners. *ArXiv*, abs/2005.14165, 2020. URL https://api.semanticscholar.org/CorpusID:218971783.

Chen, H., Zhu, T., Liu, C., Yu, S., and Zhou, W. High-

frequency matters: An overwriting attack and defense for image-processing neural network watermarking. *ArXiv*, abs/2302.08637, 2023.

Chowdhery, A., Narang, S., Devlin, J., Bosma, M., Mishra, G., Roberts, A., Barham, P., Chung, H. W., Sutton, C., Gehrmann, S., Schuh, P., Shi, K., Tsvyashchenko, S., Maynez, J., Rao, A., Barnes, P., Tay, Y., Shazeer, N. M., Prabhakaran, V., Reif, E., Du, N., Hutchinson, B., Pope, R., Bradbury, J., Austin, J., Isard, M., Gur-Ari, G., Yin, P., Duke, T., Levskaya, A., Ghemawat, S., Dev, S., Michalewski, H., García, X., Misra, V., Robinson, K., Fedus, L., Zhou, D., Ippolito, D., Luan, D., Lim, H., Zoph, B., Spiridonov, A., Sepassi, R., Dohan, D., Agrawal, S., Omernick, M., Dai, A. M., Pillai, T. S., Pellat, M., Lewkowycz, A., Moreira, E., Child, R., Polozov, O., Lee, K., Zhou, Z., Wang, X., Saeta, B., Díaz, M., Firat, O., Catasta, M., Wei, J., Meier-Hellstern, K. S., Eck, D., Dean, J., Petrov, S., and Fiedel, N. Palm: Scaling language modeling with pathways. *ArXiv*, abs/2204.02311, 2022. URL https://api.semanticscholar.org/CorpusID:247951931.

Coninck, S. D., Wang, W.-C., Leroux, S., and Simoens, P. Selective manipulation of disentangled representations for privacy-aware facial image processing. *ArXiv*, abs/2208.12632, 2022.

Cossio, M. Augmenting medical imaging: A comprehensive catalogue of 65 techniques for enhanced data analysis. *ArXiv*, abs/2303.01178, 2023.

Dang, B., Zhao, W., Li, Y., Ma, D., Yu, Q., and Zhu, E. Y. Real-time pill identification for the visually impaired using deep learning. *arXiv preprint arXiv:2405.05983*, 2024.

Davidson, A., Morley-Bunker, A., Wiggins, G., Walker, L., Harris, G., Mukundan, R., and kConFab Investigators. Grey level texture features for segmentation of chromogenic dye rnascope from breast cancer tissue. *ArXiv*, abs/2401.15886, 2024.

Fan, C., Liu, J., Zhang, Y., Wei, D., Wong, E., and Liu, S. Salun: Empowering machine unlearning via gradient-based weight saliency in both image classification and generation. *ArXiv*, abs/2310.12508, 2023.

Farooq, M., Arif, T., and Riaz, S. Detection of late blight disease in tomato leaf using image processing techniques. *ArXiv*, abs/2306.06080, 2023.

Fontanella, A., Antoniou, A., Li, W., Wardlaw, J. M., Mair, G., Trucco, E., and Storkey, A. Acat: Adversarial counterfactual attention for classification and detection in medical imaging. pp. 10153–10169, 2023.

Gaibor, E., Varade, S., Deshmukh, R., Meyer, T., Geshvadi, M., Kim, S., Narayanappa, V. S., and Haehn, D. Boostlet.js: Image processing plugins for the web via javascript injection. *ArXiv*, abs/2405.07868, 2024.

Gao, H., Wang, H., Feng, Z., Fu, M., Ma, C., Pan, H., Xu, B., and Li, N. A novel texture extraction method for the sedimentary structures' classification of petroleum imaging logging. In *Pattern Recognition: 7th Chinese Conference, CCPR 2016, Chengdu, China, November 5-7, 2016, Proceedings, Part II 7*, pp. 161–172. Springer, 2016.

Gordaliza, P. M., Vaquero, J. J., and Muñoz-Barrutia, A. Translational lung imaging analysis through disentangled representations. *ArXiv*, abs/2203.01668, 2022.

Gronningsaeter, Y., Smorvik, H. S., and Granmo, O.-C. An optimized toolbox for advanced image processing with tsetlin machine composites. *ArXiv*, abs/2406.00704, 2024.

Han, Y. and Lee, T. C. Uncertainty quantification for sparse estimation of spectral lines. *IEEE Transactions on Signal Processing*, 70:6243–6256, 2022.

Hanson, N., Kelestemur, T., Erdoğmuş, D., and Padır, T. Pregrasp object material classification by a novel gripper design with integrated spectroscopy. *ArXiv*, abs/2207.00942, 2022.

Hu, M., Pan, S., Li, Y., and Yang, X. Advancing medical imaging with language models: A journey from n-grams to chatgpt. *ArXiv*, abs/2304.04920, 2023.

Huang, Z., Chen, W., Al-Tabbaa, A., and Brilakis, I. Nha12d: A new pavement crack dataset and a comparison study of crack detection algorithms. *ArXiv*, abs/2205.01198, 2022.

Jiang, S. Color and texture dual pipeline lightweight style transfer. *ArXiv*, abs/2310.01321, 2023.

Khan, M. O. and Fang, Y. Revisiting fine-tuning strategies for self-supervised medical imaging analysis. *ArXiv*, abs/2307.10915, 2023.

Kiani, F. Texture features in medical image analysis: a survey. *ArXiv*, abs/2208.02046, 2022.

Ma, Y., Wang, D., Liu, P., Masters, L., Barnett, M. H., Cai, T. W., and Wang, C. Symmetry awareness encoded deep learning framework for brain imaging analysis. *ArXiv*, abs/2407.08948, 2024.

Novack, Z., Garg, S., McAuley, J., and Lipton, Z. C. Chils: Zero-shot image classification with hierarchical label sets. *ArXiv*, abs/2302.02551, 2023.

Nurseitov, D., Bostanbekov, K., Abdimanap, G., Abdallah, A., Alimova, A. N., and Kurmangaliyev, D. Application of machine learning methods to detect and classify core images using gan and texture recognition. *ArXiv*, abs/2204.14224, 2022.

Pallavoor, A. S., Prajwal, A., Sundareshan, T., and Pallavoor, S. K. Chromosome segmentation analysis using image processing techniques and autoencoders. *ArXiv*, abs/2209.05414, 2022.

Picón, A., Galán, P., Bereciartúa-Pérez, A., and del Valle, L. B. Hyperspectral dataset and deep learning methods for waste from electric and electronic equipment identification (weee). *ArXiv*, abs/2407.04505, 2024.

Popov, M. Y., Aimyshev, T., Ismailov, E., Bulegenov, A., and Fazli, S. A review of modern approaches for coronary angiography imaging analysis. *ArXiv*, abs/2209.13997, 2022.

Qian, Y., Magginetti, D. J., Jeon, S., Yoon, Y., Olsen, T. L., Wang, M., Gerton, J. M., and Yoon, H. P. Heterogeneous optoelectronic characteristics of si micropillar arrays fabricated by metal-assisted chemical etching. *Scientific Reports*, 10(1):16349, 2020.

Rodriguez-Pardo, C., Casas, D., Garces, E., and López-Moreno, J. Textile: A differentiable metric for texture tileability. *2024 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 4439–4449, 2024.

Sharma, D. R., Sungeetha, D. A., and Professor, D. C. R. Revolutionizing underwater exploration of autonomous underwater vehicles (auvs) and seabed image processing techniques. *ArXiv*, abs/2402.00004, 2023.

Si, J. and Kim, S. Tfr: Texture defect detection with fourier transform using normal reconstructed template of simple autoencoder. *ArXiv*, abs/2307.04574, 2023.

Sun, H., Manchester, W., yao Jin, M., Liu, Y., and Chen, Y. Tensor gaussian process with contraction for multi-channel imaging analysis. pp. 32913–32935, 2023.

Temtam, A., Pei, L., and Iftekharuddin, K. Computational modeling of deep multiresolution-fractal texture and its application to abnormal brain tissue segmentation. *ArXiv*, abs/2306.04754, 2023.

Uden, C. V., Blüthgen, C., Attias, M., Polacin, M., Guo, H., Simha, N., Raj, R., and Langlotz, C. Exploring the versatility of zero-shot clip for interstitial lung disease classification. *ArXiv*, abs/2306.01111, 2023.

Yang, J. X., Zhou, J., Wang, J., Tian, H., and Liew, A. W.-C. Hsimamba: Hyperpsectral imaging efficient feature learning with bidirectional state space for classification. *ArXiv*, abs/2404.00272, 2024a.

Yang, Q., Wang, Z., Liu, S., and Li, Z. Research on improved u-net based remote sensing image segmentation algorithm. *arXiv preprint arXiv:2408.11234*, 2024b. Submitted on 22 Aug 2024.

Yang, X., Fu, Q., Nie, Y., and Heidrich, W. Image quality is not all you want: Task-driven lens design for image classification. *ArXiv*, abs/2305.17185, 2023a.

Yang, Y., Zhang, H., Gichoya, J. W., Katabi, D., and Ghassemi, M. The limits of fair medical imaging ai in the wild. *ArXiv*, abs/2312.10083, 2023b.

Yang, Y., Jin, Y., Tian, Q., Yang, Y., Qin, W., and Ke, X. Enhancing gastrointestinal diagnostics with yolo-based deep learning techniques. 2024c. URL https://www.preprints.org/manuscript/202408.1202/download/final_file.

Zang, Z., Xiao, D., Wang, Q., Li, Z., Xie, W., Chen, Y., and Li, D. Fast fluorescence lifetime imaging analysis via extreme learning machine. *ArXiv*, abs/2203.13754, 2022.

Zhou, B., Àgata Lapedriza, Xiao, J., Torralba, A., and Oliva, A. Learning deep features for scene recognition using places database. pp. 487–495, 2014.