UNSUPERVISED 3D OBJECT LEARNING THROUGH NEURON ACTIVITY AWARE PLASTICITY

ABSTRACT

We present an unsupervised deep learning model for 3D object classification. Conventional Hebbian learning, a well-known unsupervised model, suffers from loss of local features leading to reduced performance for tasks with complex geometric objects. We present a deep network with a novel **Neuron Activity Aware** (NeAW) Hebbian learning rule that dynamically switches the neurons to be governed by Hebbian learning or anti-Hebbian learning, depending on its activity. We analytically show that NeAW Hebbian learning relieves the bias in neuron activity, allowing more neurons to attend to the representation of the 3D objects. Empirical results show that the NeAW Hebbian learning outperforms other variants of Hebbian learning and shows higher accuracy over fully supervised models when training data is limited.

1 INTRODUCTION

Supervised deep networks for recognizing objects from 3D point clouds have demonstrated high accuracy but generally suffer from poor performance when labeled training data is limited (Wu et al., 2015; Qi et al., 2017a;b; Wang et al., 2019; Maturana & Scherer, 2015). On the other hand, self-supervised or unsupervised models can be trained without labeled data hence improving the performance in data efficient scenarios. Self-supervised learning methods have been studied for 3D object recognition mostly in an autoencoder setting, which necessarily reconstructs input to learn the representation (Achlioptas et al., 2018; Girdhar et al., 2016). Unsupervised learning has also been applied to pre-process the input for an encoder but still largely relying on supervised learning (Li et al., 2018). Conventionally, self-organizing maps and growing neural gas have been used as fully unsupervised learning for 3D objects while they aim to reconstruct the surface of the objects (do Rêgo et al., 2007; Mole & Araújo, 2010). A fully unsupervised deep network for 3D object classification has rarely been studied.

Unsupervised Hebbian learning is known to offer attractive advantages such as data efficiency, noise robustness, and adaptability for various applications (Najarro & Risi, 2020; Kang et al., 2022; Miconi et al., 2018; Zhou et al., 2022). The basic Hebbian and anti-Hebbian learning refer to that synaptic weight is strengthened and weakened, respectively, when pre- and post-synaptic neurons are simultaneously activated (Hebb, 2005). Many past efforts have developed variants of Hebb's rule. Examples include Oja's rule and Grossberg's rule (Oja, 1982; Grossberg, 1976) for object recognition (Amato et al., 2019; Miconi, 2021), ABCD rule (Soltoggio et al., 2007) for meta-learning and reinforcement tasks (Najarro & Risi, 2020), and another variant for hetero-associative memory (Limbacher & Legenstein, 2020). However, Hebbian learning is often vulnerable to the loss of local features (Miconi, 2021; Bahroun et al., 2017; Bahroun & Soltoggio, 2017; Amato et al., 2019). This is a major challenge for applying Hebbian rules for tasks with more complex geometric objects, such as object recognition from 3D point clouds.

In this paper, we present an unsupervised deep learning model for 3D object recognition that uses a novel neuron activity-aware plasticity-based Hebbian learning that mitigates the vanishing of local features, thereby improving the performance of 3D object classification. We observe that, in networks trained with plain Hebbian learning, only a few selected neurons are always activated irrespective of the object class. In other words, spatial features of 3D objects are represented by the activation of only a few specific neurons, which degrades task performance. We develop a hybrid Hebbian learning rule, referred to as the **Neuron Activity Aware** (NeAW) Hebbian, that relieves the

biased activity. The key concept of NeAW Hebbian is to dynamically convert the learning rule of synapses associated with an output neuron from Hebbian to anti-Hebbian or vice versa depending on the activity of the output neuron. The reduction of bias leads to the activation of a different subset of neurons for different objects. Consequently, sample-to-sample variations in the latent space increase, thereby facilitating learning. Our deep learning model uses a feature extraction module trained by NeAW Hebbian learning, and a classifier module is trained by supervised learning. The feature extractor designed as a multi-layer perceptron (MLP) transforms the positional vector of sampled points on 3D objects into high-dimensional space (Qi et al., 2017a;b). The experimental results evaluated on ModelNet10 and ModelNet40 (Wu et al., 2015) show that the proposed NeAW Hebbian learning outperforms the prior Hebbian rules for efficient unsupervised 3D deep learning tasks. This paper makes the following key contributions:

- We present a deep learning model for 3D object recognition with the NeAW Hebbian learning rule that dynamically controls Hebbian and anti-Hebbian learning to relax the biased activity of neurons. The NeAW Hebbian learning efficiently transforms spatial features of various classes of 3D objects into a high-dimensional space defined by neuron activities.

- We analytically prove that the NeAW Hebbian learning relieves the biased activity of output neurons if the input is under a given geometric condition, while solely applying Hebbian or anti-Hebbian learning does not guarantee balanced activity.

- We analytically prove that NeAW Hebbian learning enables a richer subspace representation by relaxing the skewed neuron activity, which leads to improved performance in the classification tasks.

- We empirically demonstrate that the NeAW Hebbian learning rule outperforms the existing variants of Hebbian learning rules in the 3D object recognition task. We also show that NeAW Hebbian learning achieves higher accuracy than end-to-end supervised learning when training data is limited (data-efficient learning).

2   RELATED WORK AND BACKGROUND

Deep Learning Models for 3D Object Recognition.   Supervised 3D convolutional neural network (CNN) models have been developed to process a volumetric representation of 3D objects (Maturana & Scherer, 2015; Wu et al., 2015) but high sparsity in volumetric input increases computation cost, limiting applications to low-resolution point clouds. Multi-view CNN renders 3D objects into images at different views and processes these images using 2D CNN (Su et al., 2015). VGG and ResNet-based models show good performance when the training images are well-engineered under proper multi-views (Su et al., 2018). However, 2D CNN-based approaches are difficult to scale to complex 3D tasks (Qi et al., 2017a). Recently low-complexity point-based models have been designed to process a point cloud where input is (x, y, z) coordinates of points (Qi et al., 2017a). Self-supervised learning models have also been proposed based on autoencoder and generative adversarial networks (Wu et al., 2016; Sharma et al., 2016). Both models accept a voxel representation of 3D objects and learn the latent representation of the objects by reconstructing the voxel. The learned representation is used as the input to an additional classifier. Our unsupervised learning does not use labels, but unlike existing self-supervised models, our approach does not reconstruct the objects.

Hebbian Learning Models.   The variants of the Hebbian learning rule are given as:

$$\Delta\mathbf{w}(t + 1) = \begin{cases} \mathbf{w}(t) + \eta y\mathbf{x} & \text{Hebb's rule} \\ \mathbf{w}(t) + \eta y(\mathbf{x} - y\mathbf{w}(t)) & \text{Oja's rule} \\ \mathbf{w}(t) + \eta y(\mathbf{x} - \mathbf{w}(t)) & \text{Grossberg's rule} \end{cases} \tag{1}$$

where $\mathbf{x}$, y, and $\mathbf{w}$ are the input, output, and weight, η is the learning rate. Hebb's rule is the basic form of Hebbian learning where weights are updated if both the input and output neuron fire (Hebb, 2005). This linear association can be interpreted as biologically plausible principal component analysis (PCA) if the data samples are assumed to be zero-mean (Weingessel & Hornik, 2000). However, the plain Hebb's rule is often vulnerable to the divergence of weight vectors as there is no explicit upper bound (Porr & Wörgötter, 2007). Oja's rule has an additional constraint

Figure 1: 3D object classification model.

term on Hebb's rule to normalize the weight vectors (Oja, 1982). It is derived by dividing the weight update in plain Hebb's rule by its norm, assuming that the input and output are linearly associated. Grossberg's rule is another variant where a constraint term enables the weight to be converged on the input; hence the weight is more aligned with the frequently observed data (Grossberg, 1976). Recent works have used Grossberg's rule for image feature extraction (Miconi, 2021; Amato et al., 2019), We can also modify Grossberg's rule to be identical to Kohonen's self-organizing map (SOM) by applying Winner-Take-All (WTA) to output neurons and can be used for learning two-dimensional or three-dimensional spatial features (Kohonen, 2012; Li et al., 2018). Another variant of Grossberg's rule with the notion of neuron activity is recently studied for learning 2D point sets (Kang et al., 2022). In this paper, we consider neuron activity aware Hebbian learning but focus on developing a mathematical foundation of this NeAW Hebbian learning and use that to design a deep neural network for 3D object classification tasks.

3 PROPOSED APPROACH

3.1 3D OBJECT CLASSIFICATION MODEL

We process (x, y, z) coordinates of points in a point cloud by a shared three-layer MLP with competition layers. NeAW Hebbian learning is applied on the MLP (i.e. encoder), and the other layers (i.e. classifier) are trained by supervised learning. The output vector for a point is written by:

$$\mathbf{x}^{l_{i+1}} = \text{WTA}(\text{ReLU}(\mathbf{W}^{l_i,T}\mathbf{x}^{l_i}) \qquad (2)$$

where $\mathbf{x}^{l_i}$, $\mathbf{W}^{l_i}$, and $\mathbf{x}^{l_{i+1}}$ are the input, weight, and output vector at layer l_i, respectively. Winner-take-all (WTA) is applied on the output of each layer so that the single output neuron with the highest similarity (i.e. the lowest $||\mathbf{x}^{l_i} - \mathbf{W}^{l_i}_{:,j}||$ for $\mathbf{x}^{l_{i+1}}_j$) has a non-zero value while others are forced to be zero (Coates et al., 2011; Hu et al., 2014; Miconi, 2021). Figure 1 shows the architecture of our model. There are two types of inhibition for the last output neurons in the encoder. Each WTA layer makes lateral inhibition, as shown in the figure, and cross-point inhibition is applied to the last output neurons after the lateral inhibition. Then, the model aggregates the transformed vector by summing the elements of the remaining neurons across the columns. The cross-inhibition and the summation can be interpreted as a MaxPooling layer that directly finds the maximum value of each column. The proposed model consequently arrives at a PointNet-style model which combines the MLP and MaxPooling layer in the encoder design. The aggregated activation of the last neurons, the global feature of objects, is processed by FC layers with ReLU and Softmax activation in the classifier. LayerNorm layers are included between the FC layers.

3.2 MOTIVATIONAL STUDY

Figure 2 shows the average neuron activity in the last layer of the encoder with different learning rules. Note, the details of the figure are explained again in Section 4. We measure how frequently each output neuron activates across different points, so-called neuron activity, to quantify whether the transformed vectors are distinguishable in high-dimensional space or merged to a simple global

Figure 2: The average neuron activity of each output neuron for ModelNet10 with (a) Hebbian learning, (b) anti-Hebbian learning, and (c) NeAW Hebbian learning.

feature. We observe that with Hebbian and anti-Hebbian learning, few specific neurons in the last layer are frequently activated regardless of objects. Given input vectors are projected onto weight vectors, the biased activation of output neurons indicates the small number of principal weight vectors in high-dimensional space. In other words, multiple input points are associated with few weight vectors, which significantly decreases the variance of context vectors with different labels and consequently leads to classification failure. Hence, the skewed activity's relaxation is considered the key problem to solve in this paper.

3.3 Neuron activity aware Hebbian learning

Definition 1. *Neuron activity* $p^{(j)}$ of the j-th output neuron is the number of the activation while the neuron processes points in a point cloud divided by the number of entire points.

Definition 2. *Activation boundary* is the plane with the same Euclidean distance from two weight vectors that determine which neuron of the weight vector to activate.

Our learning rule is given by:

$$\mathbf{W}_{:,j}(t+1) = \mathbf{W}_{:,j}(t) + f(p^* - p^{(j)})\frac{\eta}{N}\sum_{i=0}^{N-1}\mathbf{1}_{i \in \arg\min_k \|\mathbf{x}_k - \mathbf{W}_{:,j}(t)\|_2}(\mathbf{x}_i - \mathbf{W}_{:,j}(t)) \quad (3)$$

$$\begin{aligned}
\mathbf{W}_{:,j}(t+1) &= \mathbf{W}_{:,j}(t) + f(p^* - p^{(j)})\frac{\eta}{N}(\mathbf{x}_k - \mathbf{W}_{:,j}(t)) \\
&= \begin{cases} \mathbf{W}_{:,j}(t) + a\frac{\eta}{N}(\mathbf{x}_k - \mathbf{W}_{:,j}(t)) & \text{Hebbian} \\ \mathbf{W}_{:,j}(t) - b\frac{\eta}{N}(\mathbf{x}_k - \mathbf{W}_{:,j}(t)) & \text{anti-Hebbian} \end{cases}
\end{aligned} \quad (4)$$

where $\mathbf{W}_{:,j}(t)$ is the weight vector of the j-th output neuron at t, $\mathbf{x}_i$ is the i-th input vector in a point cloud, p^* is the optimal neuron activity. As WTA layers in the proposed model search the closest weight vectors from the input vectors, the learning rule is motivated by Grossberg's rule and the prior work (Kang et al., 2022). The optimal neuron activity is given by $1/d$ where d is the number of output neurons (Kang et al., 2022). The indicator function is considered another WTA. Each weight vector searches the closest input vector with regard to Euclidean distance and is moved closer or further to the input vector depending on the range of $p^{(j)}$. It describes the conversion between Hebbian and anti-Hebbian learning enabled by the f function, indicating Hebbian learning for low-activity neurons and anti-Hebbian learning for high-activity neurons. The learning rule is simplified to (4) if the k-th input vector is closest to the weight vector. Note, a and b are constants to introduce the different importance of Hebbian and anti-Hebbian learning.

An important question is how the hybridization of the learning rules depending on the neuron activity effectively relaxes the biased neuron activity. In a simplified scenario, we can consider two weight vectors and an input vector with the assumption that the corresponding neuron of each weight vector is highly active or non-active. Also, a and b are assumed to be 1. The problem is whether NeAW Hebbian learning shifts the activation boundary so that the other neuron is activated after learning.

Figure 3: Geometry of input and weight vectors. (a) the initial geometry of the vectors and the changed geometry of the vectors after (b) Hebbian learning, (c) anti-Hebbian learning, and (d) NeAW Hebbian learning.

To help the intuitive understanding of how NeAW Hebbian learning changes the activation boundary, the geometry of the three vectors is described in Figure 3. In Figure 3(a), the activation boundary as a dotted line shows that input $\mathbf{x}_i$ is left to the boundary plane, and the j-th neuron is assumed to be highly active while the j'-th neuron is not active before learning. We expect that the learning properly shifts the activation boundary to activate the j'-th neuron and relieve the biased activity. The geometry of the vectors after Hebbian, anti-Hebbian and NeAW Hebbian learning are compared in Figure 3(b), (c), and (d), respectively. Hebbian and anti-Hebbian learning here is activity-agnostic rules, where the sign function in (4) is forced to be 1 or -1. The activity-agnostic rules move both the weight vectors to be closer to or further from the activation boundary, implying the activation boundary cannot be effectively shifted to either left or right space. It is desirable that both the weight vectors are also shifted in the same direction. In this light, NeAW Hebbian learning offers the appropriate shift of the activation boundary and consequently switches the winner neuron from the highly active j-th neuron to the non-active j'-th neuron, as shown in Figure 3(d).

Based on this idea, we develop formal theorems and corollaries to mathematically prove that NeAW Hebbian learning changes the winner neuron while the others cannot:

Theorem 1. *Let two weight vectors $\mathbf{W}_{:,j}$ and $\mathbf{W}_{:,j'}$ with the biased activity and an input vector $\mathbf{x}_i$ satisfy $\|\mathbf{x}_i - \mathbf{W}_{:,j}(t)\|_2 < \|\mathbf{x}_i - \mathbf{W}_{:,j'}(t)\|_2$ at t. Then, NeAW Hebbian learning changes the sign of the inequality to $\|\mathbf{x}_i - \mathbf{W}_{:,j}(t+1)\|_2 > \|\mathbf{x}_i - \mathbf{W}_{:,j'}(t+1)\|_2$ at $t+1$ if the vectors are on the geometric condition $(1 + \frac{\eta}{N})\|\mathbf{x}_i - \mathbf{W}_{:,j}(t)\|_2 > (1 - \frac{\eta}{N})\|\mathbf{x}_i - \mathbf{W}_{:,j'}(t)\|_2$.*

Proof Sketch. (Formal proof in Appendix A) Due to the biased activity, each weight vector is updated by Hebbian learning or anti-Hebbian learning. Then, we have two update rules, $\mathbf{W}_{:,j}(t+1) = \mathbf{W}_{:,j}(t) - \frac{\eta}{N}(\mathbf{x}_i - \mathbf{W}_{:,j}(t))$ for the high-active j-th neuron and $\mathbf{W}_{:,j'}(t+1) = \mathbf{W}_{:,j'}(t) + \frac{\eta}{N}(\mathbf{x}_i - \mathbf{W}_{:,j'}(t))$ for the low-active j'-th neuron. From the assumption, we have $\|\mathbf{x}_i - \mathbf{W}_{:,j}(t)\|_2 < \|\mathbf{x}_i - \mathbf{W}_{:,j'}(t)\|_2$, which indicates that the winner neuron is the j-th neuron at t. Using the two updates rule to substitute the weight vectors from t to $t+1$, the inequality at $t+1$ is derived. The sign in the inequality is flipped if the Euclidean distances satisfy $(1 + \frac{\eta}{N})\|\mathbf{x}_i - \mathbf{W}_{:,j}(t)\|_2 > (1 - \frac{\eta}{N})\|\mathbf{x}_i - \mathbf{W}_{:,j'}(t)\|_2$.

Corollary 1.1. *Let two weight vectors $\mathbf{W}_{:,j}$ and $\mathbf{W}_{:,j'}$ with the biased activity and an input vector $\mathbf{x}_i$ satisfy $\|\mathbf{x}_i - \mathbf{W}_{:,j}(t)\|_2 < \|\mathbf{x}_i - \mathbf{W}_{:,j'}(t)\|_2$ at t. Then, Hebbian learning preserves the sign of the inequality to $\|\mathbf{x}_i - \mathbf{W}_{:,j}(t+1)\|_2 < \|\mathbf{x}_i - \mathbf{W}_{:,j'}(t+1)\|_2$ at $t+1$.*

Corollary 1.2. *Let two weight vectors $\mathbf{W}_{:,j}$ and $\mathbf{W}_{:,j'}$ with the biased activity and an input vector $\mathbf{x}_i$ satisfy $\|\mathbf{x}_i - \mathbf{W}_{:,j}(t)\|_2 < \|\mathbf{x}_i - \mathbf{W}_{:,j'}(t)\|_2$ at t. Then, anti-Hebbian learning preserves the sign of the inequality to $\|\mathbf{x}_i - \mathbf{W}_{:,j}(t+1)\|_2 < \|\mathbf{x}_i - \mathbf{W}_{:,j'}(t+1)\|_2$ at $t+1$.*

Proof for corollaries is in Appendix A.

The prior study has shown that Grossberg's rule combined with WTA does k-means clustering (Hu et al., 2014). While NeAW Hebbian learning does not aim to minimize the distance between the

input and weight required for the clustering, we can interpret the activated neurons as cluster centroids. The more output neurons the model activates with the balanced activity, the smaller spatial features are responsible for each neuron. In other words, more activated neurons are preferred to avoid the vanishing of local features, which can be achieved by maximizing the variance of the neuron activity. The variance at layer l_i is written by:

$$
\begin{aligned}
\text{Var}(\mathbf{y}^{l_i}) &= \frac{1}{N} \sum_{k=0}^{N-1} (\mathbf{y}_k^{l_i} - \mu_{\mathbf{y}^{l_i}}) \cdot (\mathbf{y}^{l_i} - \mu_{\mathbf{y}^{l_i}}) \\
&= \frac{1}{N} \sum_{k=0}^{N-1} \mathbf{y}_k^{l_i} \cdot \mathbf{y}_k^{l_i} - \frac{1}{N^2} \sum_{k,w=0}^{N-1} \mathbf{y}_k^{l_i} \cdot \mathbf{y}_w^{l_i} = 1 - \frac{1}{N^2} \sum_{k,w=0}^{N-1} \mathbf{y}_k^{l_i} \cdot \mathbf{y}_w^{l_i}
\end{aligned}
\tag{5}
$$

where y^{l_i} is a binary vector whose element is either 0 or 1. It is obtained from (2) by applying a step function on it only to consider whether the neuron is activated or not. Also, $y_k^{l_i} \cdot y_k^{l_i}$ is always 1 as the binary vector has a single non-zero element due to WTA. The proposed NeAW Hebbian learning eventually aims to increase the variance of the activated neurons so that each neuron is responsible for the different geometric parts of 3D objects by properly rotating the weight vectors through the neuron activity aware plasticity, or more formally:

Theorem 2. *For a network of N neurons in the biased activity with weight vectors* $\mathbf{W}$ *and an input vector* $\mathbf{x}$*, the variance of the distribution of activated neurons follows* $\text{Var}(\text{NeAW Hebbian}) \geq \text{Var}(\text{Hebbian}) \text{ or } \text{Var}(\text{anti} - \text{Hebbian})$ *which means NeAW Hebbian learning provides the greatest variance of the neuron activity compared to solely using Hebbian or anti-Hebbian learning.*

Proof Sketch. (Formal proof in Appendix A) First, we note that Hebbian (H) and anti-Hebbian (aH) networks optimize the information capacity by orthonormalizing the principal subspace (Plumbley, 1993). To prove that the neuronal activations for the hybrid learning rule have a greater variance than the standard H and aH learning rules, we first assume that a network with a greater number of neuronal activations can encode a large number of principal components in the subspace. We consider that the local H and aH learning rules recover a principal subspace from the data using a principled cost function (Pehlevan et al., 2015). Hence, we rewrite the problem as:

$$
\text{span}_{\min}(\mathcal{L}_{NeAW}) \geq \text{span}_{\min}(\mathcal{L}_H) \text{ or } \text{span}_{\min}(\mathcal{L}_{aH})
\tag{6}
$$

where $\mathcal{L}_H$ and $\mathcal{L}_{aH}$ denote, the subspace learned using the Hebbian and anti-Hebbian learning rules, respectively. Let us consider the case where we have N neurons learned using H or aH learning rules. Without loss of generality, we can assume that the first n $(n < N)$ neurons are trained using the learning method $\mathcal{L}$ and the metric space of the neuron vectors and the weight vectors to be represented as $\mathcal{W}$. For the $n + 1$-th neuron, the neuron can be trained using either the same learning rule $\mathcal{L}$ or the complementary learning rule $\bar{\mathcal{L}}$. Thus, we study the differential gain from using one learning rule over the other for the $n + 1$-th neuron. A learning rule extracts the principal components of the input space by projecting the input space into the orthogonal subspace, and a neural network with a larger number of principal components can learn a better representation of the input space. Again, H and aH learning rules lead to different principal components (Rubner & Tavan, 1989; Carlson, 1990). Hence, we show that using NeAW Hebbian learning approach leads to an increase in the number of the principal components learned, which leads to a greater span of the learned subspace for the hybrid learning model compared to the homogeneous H or aH learning method, which, in turn, entails a higher variance for the neuronal activity.

4 EXPERIMENTAL RESULT

Experimental setting The proposed model is evaluated on ModelNet10 and ModelNet40 datasets, which include 10-class and 40-class 3D CAD objects for 3D deep learning (Wu et al., 2015). We randomly sample 1024 points on the surface of the objects. The encoder is trained by unsupervised learning with unlabeled datasets while the classifier is trained by supervised learning with object labels. Note, the weights of the encoder are not changed during training the classifier. For all the unsupervised learning rules, we set training epoch 50, learning rate 1e-2, and train batch 4; however, learning rate is proportionally increased when the amount of training data is limited. For example, learning rate is 1e-1 for 10% training data and 4e-2 for 25% training data. For the classifier, we use training epoch 100, learning rate 1e-3, and train batch 32 for both ModelNet10 and ModelNet40. We report average instance accuracy for test datasets.

Figure 4: t-SNE for ModelNet10 in different learning rules. (a) context vectors from the encoder trained by Hebbian learning, (b) anti-Hebbian learning, and (c) NeAW Hebbian learning.

Figure 5: Effect of training with regard to the variance of neuron activity and test accuracy. (a) the variance of neuron activity with the different learning rules in ModelNet10 and (b) ModelNet40 and (c) the test accuracy at different epochs for ModelNet10 and (d) ModelNet40.

Balancing of Neuron Activity   Figure 2 shows the neuron activity of the individual output neuron for various Hebbian learning rules in the same model. x-axis in the figure is the index of output neurons to show the activity of the individual neuron. y-axis is the normalized number of the neuron activation for ModelNet10 test dataset. The activity is first summed over the all test samples and then normalized by the entire activities. In Hebbian and anti-Hebbian leanring cases, the activity is dominated by few neurons, implying only few neurons are used to represent the objects. On the other hand, NeAW Hebbian learning clearly displays the more distributed activity than activity-agnostic cases. In addition, the activity level increases for non-active neurons and decreases for high-active neurons, enabling more output neurons contribute to the representation. We also characterize the property of the latent space learned using NeAW Hebbian learning. Figure 4 shows the t-SNE plots of the context vectors for all the ModelNet10 test samples. The 10 classes are marked with different colors in the figure. Similar to Figure 2, the context vectors are generated from the same model with the different learning rules. We observe that the context vectors are properly clustered in NeAW Hebbian learning while the test samples are more spread out in other cases.

Evolution of Neuron Activity during Unsupervised Learning   We study the evolution of neuron activity and test accuracy as a function of training epochs of the unsupervised encoder. In all the cases, the unsupervised encoder is frozen after training with Hebbian learning for certain number of epochs, followed by full supervised training of the classifier. Figure 5 shows the variance of neuron activity during training of the model. We observe that variance is quickly saturated to a high value in NeAW Hebbian leaning. In comparison, the variance increases slowly and to a lower value with Hebbian learning and anti-Hebbian learning, respectively. Figure 5(c) and (d) represent the test accuracy for ModelNet10 and ModelNet40 at different training epochs with NeAW Hebbian learning. We observe the variance and accuracy converge in 50 training epochs.

Impact of Hyperparameters in NeAW Hebbian Learning Rule.   We evaluate the impact of hyperparameters a and b in (3) on the variance of the neuron activity. Figure 6(a) and (b) show that the higher a and b results in a faster increase of the variance during training. This can be also understood

Figure 6: Effect of a and b for ModelNet40. (a) the variance of the neuron activity when the importance of Hebbian learning is fixed by $a = 1$, (b) when the importance of anti-Hebbian learning is fixed by $b = 1$, and (c) the variance and accuracy with different a and b ratios.

Table 1: Comparison with other unsupervised learning rules.

Learning Rule	ModelNet-10		ModelNet-40	
	Variance	Accuracy (%)	Variance	Accuracy (%)
Hebb's rule	0.9663	72.22 $\pm$0.46	0.9391	41.52 $\pm$1.21
Grossberg's rule	0.8714	74.45 $\pm$0.56	0.8693	55.96 $\pm$0.39
Oja's rule	0.9182	80.40 $\pm$0.03	0.8953	61.22 $\pm$3.82
Ours - Hebbian	0.9165	74.19 $\pm$0.21	0.9251	49.83 $\pm$4.72
Ours - anti-Hebbian	0.8624	64.63 $\pm$0.60	0.8511	35.65 $\pm$0.80
Ours - NeAW Hebbian	0.9793	88.22 $\pm$0.62	0.9741	76.20 $\pm$0.30

through the geometric condition given in Theorem 1:

$$\frac{\|\mathbf{x}_i - \mathbf{W}_{:,j'}(t)\|_2^2}{\|\mathbf{x}_i - \mathbf{W}_{:,j}(t)\|_2^2} < \frac{(1 + \frac{\eta}{N})^2}{(1 - \frac{\eta}{N})^2} \tag{7}$$

which describes that NeAW Hebbian learning relieves the biased activity only if the ratio of the Euclidean distance are lower than the ratio of $\left(1 + \frac{\eta}{N}\right)$ and $\left(1 - \frac{\eta}{N}\right)$. Given a and b can be regarded as different learning rates η, higher a and higher b will increase the numerator and decrease the denominator, respectively. It results in the geometric condition for relieving the biased activity to become weaker, and consequently, such pair of a and b quickly increases the variance. However, in Figure 6(c), we observe the maximum accuracy in different a and b ratios are saturated to the similar level, which implies that finaly accuracy with NeAW Hebbian learning is not sensitive to a and b.

Comparison with other Hebbian learning Table 1 compares variance of neuron activity and test accuracy with plain Hebb's rule, Grossberg's rule, Oja's rule, and NeAW Hebbian learning rule. Test accuracy is evaluated on the trained models with 5 different random seeds, and mean and variance of the accuracy are listed in the table. We observe NeAW Hebbian learning shows the highest variance of neuron activity and improved test accuracy in both datasets. In particular, the accuracy gap increases in ModelNet40, implying the potential pitfalls of the existing learning rules on the complex 3D object datasets. Note, although plain Hebb's rule show higher variance of neuron activity than the Oja's rule, it results in lower test accuracy. This is due to the unbounded norm of the weight vectors. Instead of points that distinguish objects with different labels, commonly appeared points in the training samples continuously strengthens the certain weights (see Figure 8 in Appendix A), which may increase the point-to-point variation, but sacrifice local features.

Comparison with Existing Supervised Learning Models Table 2 compares the proposed model with prior models for 3D object recognition. First, our model shows similar accuracy to other self-supervised model (Wu et al., 2016; Sharma et al., 2016). Accuracy difference with 3D-GAN increases in ModelNet40 but 3D-GAN needs to reconstruct a $(30, 30, 30)$ voxel to learn the representation resulting in high computational cost for high-resolution 3D objects. Our model shows similar accuracy to other fully supervised voxel-based approaches while using $6.2\times$ fewer parameters (Wu et al., 2015). The accuracy difference with other large point-based approaches is more

Table 2: Accuracy (%) and model size comparison with supervised models.

Model	Learning	ModelNet10	ModelNet40	Size (MB)
3DShapeNet (Wu et al., 2015)	Supervised	83.5	77.0	19.2
PointNet (Qi et al., 2017a)	Supervised	-	89.2	40
PointNet++ (Qi et al., 2017b)	Supervised	-	91.9	12
DGCNN (Wang et al., 2019)	Supervised	-	92.9	21
VConv-DAE (Sharma et al., 2016)	Self-supervised	80.5	75.5	-
3D-GAN (Wu et al., 2016)	Self-supervised	91.0	83.3	-
Ours - Backpropagation	Supervised	91.1	77.2	3.1
Ours - NeAW Hebbian	Unsupervised	88.2	76.2	3.1

Figure 7: Comparison with other learning rules in limited training data. (a) the accuracy of end-to-end supervised learning and NeAW Hebbian learning for ModelNet10 and (c) ModelNet40, (b) and the accuracy of other unsupervised learning for ModelNet10 and (d) ModelNet40.

pronounced in ModelNet40 but they use $3.9\times$ to $12.9\times$ more parameters than our model. We also compare unsupervised version and a fully supervised version (i.e., when the encoder is also trained with back-propagation instead of Hebbian learning) of our model. The proposed unsupervised version shows a marginally lower accuracy from the supervised version.

Learning with Less Training Data. We study the performance of NeAW Hebbian as the amount of the training samples decreases (Figure 7). We randomly drop samples from each class based on the percentage amount of the labeled data. For the other Hebbian learning rules, NeAW Hebbian learning always shows higher accuracy in both ModelNet10 and ModelNet40. As shown in Table 2, NeAW Hebbian learning achieves marginally lower accuracy to fully supervised model (denoted as Backpropagation) when the all data is used for training. However, in all other cases with less than 25% labeled data, NeAW Hebbian learning shows higher performance than Backpropagation. Our model also shows better performance than alternative Hebbian rules at reduced training data.

5 CONCLUSION

We present the neuron activity aware (NeAW) plasticity in Hebbian learning that combines Hebbian and anti-Hebbian learning to relieve the biased neuron activity. Multi theorems and corollaries are developed to understand how NeAW Hebbian learning relieves the biased neuron activity and why the balanced activity offers better representation in the classification tasks. Experimental results demonstrate that NeAW Hebbian learning achieved higher accuracy than other Hebbian learning rules and supervised learning with limited training data. We believe this paper provides a theoretical understanding of how neuron activity can be used for modulating the learning rule and its application to unsupervised 3D deep learning.

REFERENCES

Panos Achlioptas, Olga Diamanti, Ioannis Mitliagkas, and Leonidas Guibas. Learning representations and generative models for 3d point clouds. In *International conference on machine learning*, pp. 40–49. PMLR, 2018.

Giuseppe Amato, Fabio Carrara, Fabrizio Falchi, Claudio Gennaro, and Gabriele Lagani. Hebbian learning meets deep convolutional neural networks. In *International Conference on Image Analysis and Processing*, pp. 324–334. Springer, 2019.

Yanis Bahroun and Andrea Soltoggio. Online representation learning with single and multi-layer hebbian networks for image classification. In *International Conference on Artificial Neural Networks*, pp. 354–363. Springer, 2017.

Yanis Bahroun, Eugénie Hunsicker, and Andrea Soltoggio. Building efficient deep hebbian networks for image classification tasks. In *International conference on artificial neural networks*, pp. 364–372. Springer, 2017.

Arthur Carlson. Anti-hebbian learning in a non-linear neural network. *Biological cybernetics*, 64 (2):171–176, 1990.

Adam Coates, Andrew Ng, and Honglak Lee. An analysis of single-layer networks in unsupervised feature learning. In *Proceedings of the fourteenth international conference on artificial intelligence and statistics*, pp. 215–223. JMLR Workshop and Conference Proceedings, 2011.

Renata LME do Rêgo, Aluizio FR Araujo, and Fernando B de Lima Neto. Growing self-organizing maps for surface reconstruction from unstructured point clouds. In *2007 International Joint Conference on Neural Networks*, pp. 1900–1905. IEEE, 2007.

Rohit Girdhar, David F Fouhey, Mikel Rodriguez, and Abhinav Gupta. Learning a predictable and generative vector representation for objects. In *European Conference on Computer Vision*, pp. 484–499. Springer, 2016.

Stephen Grossberg. Adaptive pattern classification and universal recoding: I. parallel development and coding of neural feature detectors. *Biological cybernetics*, 23(3):121–134, 1976.

Donald Olding Hebb. *The organization of behavior: A neuropsychological theory*. Psychology Press, 2005.

Xiaolin Hu, Jianwei Zhang, Peng Qi, and Bo Zhang. Modeling response properties of v2 neurons using a hierarchical k-means model. *Neurocomputing*, 134:198–205, 2014.

Beomseok Kang, Harshit Kumar, Saurabh Dash, and Saibal Mukhopadhyay. Unsupervised hebbian learning on point sets in starcraft ii. *arXiv preprint arXiv:2207.12323*, 2022.

Teuvo Kohonen. *Self-organization and associative memory*, volume 8. Springer Science & Business Media, 2012.

Jiaxin Li, Ben M Chen, and Gim Hee Lee. So-net: Self-organizing network for point cloud analysis. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 9397–9406, 2018.

Thomas Limbacher and Robert Legenstein. H-mem: Harnessing synaptic plasticity with hebbian memory networks. *Advances in Neural Information Processing Systems*, 33:21627–21637, 2020.

Daniel Maturana and Sebastian Scherer. Voxnet: A 3d convolutional neural network for real-time object recognition. In *2015 IEEE/RSJ international conference on intelligent robots and systems (IROS)*, pp. 922–928. IEEE, 2015.

Thomas Miconi. Multi-layer hebbian networks with modern deep learning frameworks. *arXiv preprint arXiv:2107.01729*, 2021.

Thomas Miconi, Kenneth Stanley, and Jeff Clune. Differentiable plasticity: training plastic neural networks with backpropagation. In *International Conference on Machine Learning*, pp. 3559–3568. PMLR, 2018.

Vilson Luiz Dalle Mole and Aluizio Fausto Ribeiro Araújo. Growing self-organizing surface map: Learning a surface topology from a point cloud. *Neural computation*, 22(3):689–729, 2010.

Elias Najarro and Sebastian Risi. Meta-learning through hebbian plasticity in random networks. *Advances in Neural Information Processing Systems*, 33:20719–20731, 2020.

Erkki Oja. Simplified neuron model as a principal component analyzer. *Journal of mathematical biology*, 15(3):267–273, 1982.

Cengiz Pehlevan, Tao Hu, and Dmitri B Chklovskii. A hebbian/anti-hebbian neural network for linear subspace learning: A derivation from multidimensional scaling of streaming data. *Neural computation*, 27(7):1461–1495, 2015.

Mark D Plumbley. A hebbian/anti-hebbian network which optimizes information capacity by orthonormalizing the principal subspace. In *1993 Third International Conference on Artificial Neural Networks*, pp. 86–90. IET, 1993.

Bernd Porr and Florentin Wörgötter. Learning with "relevance": using a third factor to stabilize hebbian learning. *Neural computation*, 19(10):2694–2719, 2007.

Charles R Qi, Hao Su, Kaichun Mo, and Leonidas J Guibas. Pointnet: Deep learning on point sets for 3d classification and segmentation. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 652–660, 2017a.

Charles Ruizhongtai Qi, Li Yi, Hao Su, and Leonidas J Guibas. Pointnet++: Deep hierarchical feature learning on point sets in a metric space. *Advances in neural information processing systems*, 30, 2017b.

Jeanne Rubner and Paul Tavan. A self-organizing network for principal-component analysis. *EPL (Europhysics Letters)*, 10(7):693, 1989.

Nicol Schraudolph and Terrence J Sejnowski. Competitive anti-hebbian learning of invariants. *Advances in Neural Information Processing Systems*, 4, 1991.

Abhishek Sharma, Oliver Grau, and Mario Fritz. Vconv-dae: Deep volumetric shape learning without object labels. In *European conference on computer vision*, pp. 236–250. Springer, 2016.

Andrea Soltoggio, Peter Durr, Claudio Mattiussi, and Dario Floreano. Evolving neuromodulatory topologies for reinforcement learning-like problems. In *2007 IEEE Congress on evolutionary computation*, pp. 2471–2478. IEEE, 2007.

Hang Su, Subhransu Maji, Evangelos Kalogerakis, and Erik Learned-Miller. Multi-view convolutional neural networks for 3d shape recognition. In *Proceedings of the IEEE international conference on computer vision*, pp. 945–953, 2015.

Jong-Chyi Su, Matheus Gadelha, Rui Wang, and Subhransu Maji. A deeper look at 3d shape classifiers. In *Proceedings of the European Conference on Computer Vision (ECCV) Workshops*, pp. 0–0, 2018.

Yue Wang, Yongbin Sun, Ziwei Liu, Sanjay E Sarma, Michael M Bronstein, and Justin M Solomon. Dynamic graph cnn for learning on point clouds. *Acm Transactions On Graphics (tog)*, 38(5): 1–12, 2019.

Satosi Watanabe and Nikhil Pakvasa. Subspace method of pattern recognition. In *Proc. 1st. IJCPR*, pp. 25–32, 1973.

Andreas Weingessel and Kurt Hornik. Local pca algorithms. *IEEE Transactions on Neural Networks*, 11(6):1242–1250, 2000.

Jiajun Wu, Chengkai Zhang, Tianfan Xue, Bill Freeman, and Josh Tenenbaum. Learning a probabilistic latent space of object shapes via 3d generative-adversarial modeling. *Advances in neural information processing systems*, 29, 2016.

Zhirong Wu, Shuran Song, Aditya Khosla, Fisher Yu, Linguang Zhang, Xiaoou Tang, and Jianxiong Xiao. 3d shapenets: A deep representation for volumetric shapes. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 1912–1920, 2015.

Zhenyue Zhang and Yuqing Xia. Minimal sample subspace learning: Theory and algorithms. *J. Mach. Learn. Res.*, 20:143–1, 2019.

Yanpeng Zhou, Maosen Wang, Manas Gupta, Arulmurugan Ambikapathi, Ponnuthurai Nagaratnam Suganthan, and Savitha Ramasamy. Investigating robustness of biological vs. backprop based learning. In *ICASSP 2022-2022 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pp. 3533–3537. IEEE, 2022.

A   PROOF OF THEOREM

Theorem 1. *Let two weight vectors $\mathbf{W}_{:,j}$ and $\mathbf{W}_{:,j'}$ with the biased activity and an input vector $\mathbf{x}_i$ satisfy $\|\mathbf{x}_i - \mathbf{W}_{:,j}(t)\|_2 < \|\mathbf{x}_i - \mathbf{W}_{:,j'}(t)\|_2$ at t. Then, NeAW Hebbian learning changes the sign of the inequality to $\|\mathbf{x}_i - \mathbf{W}_{:,j}(t+1)\|_2 > \|\mathbf{x}_i - \mathbf{W}_{:,j'}(t+1)\|_2$ at $t+1$ if the vectors are on the geometric condition $(1 + \frac{\eta}{N})\|\mathbf{x}_i - \mathbf{W}_{:,j}(t)\|_2 > (1 - \frac{\eta}{N})\|\mathbf{x}_i - \mathbf{W}_{:,j'}(t)\|_2$.*

Proof. Let's say there are an input vector $\mathbf{x}_i$, corresponding winner is the j-th output neuron (i.e. $j = \arg\min_k \|\mathbf{x}_i - \mathbf{W}_{:,k}(t)\|$), and the other loser is the j'-th output neuron. We are interested in how the hybrid update changes the activation boundary. Our learning rule is given by:

$$\mathbf{W}_{:,j}(t+1) = \mathbf{W}_{:,j}(t) + f(p^* - p^{(j)})\frac{\eta}{N} \sum_{i=0}^{N-1} \mathbf{1}_{i \in \arg\min_k \|\mathbf{x}_k - \mathbf{W}_{:,j}(t)\|_2}(\mathbf{x}_i - \mathbf{W}_{:,j}(t)) \qquad (8)$$

Given there is a single input vector, the learning rule can be simplified by:

$$\mathbf{W}_{:,j}(t+1) = \mathbf{W}_{:,j}(t) + f(p^* - p^{(j)})\frac{\eta}{N}(\mathbf{x}_i - \mathbf{W}_{:,j}(t)) \qquad (9)$$

As we are interested in the hybrid update relieves the biased activity such as too high activity or zero activity, the j-th and j'-th neuron are assumed to have higher $p^{(j)}$ and lower $p^{(j')}$ than p^*. Then, with an assumption that a and b are 1 to simplify the case, the equation is again written as:

$$\mathbf{W}_{:,j}(t+1) = \mathbf{W}_{:,j}(t) - \frac{\eta}{N}(\mathbf{x}_i - \mathbf{W}_{:,j}(t)) \qquad (10)$$

$$\mathbf{W}_{:,j'}(t+1) = \mathbf{W}_{:,j'}(t) + \frac{\eta}{N}(\mathbf{x}_i - \mathbf{W}_{:,j'}(t)) \qquad (11)$$

Our goal is to show that the learning rules change the activation boundary. At t before learning, the Euclidean distance for the j-th neuron is lower than the j'-th neuron, or more formally:

$$\|\mathbf{x}_i - \mathbf{W}_{:,j}(t)\|_2^2 < \|\mathbf{x}_i - \mathbf{W}_{:,j'}(t)\|_2^2 \qquad (12)$$

$$\|\mathbf{x}_i - \mathbf{W}_{:,j}(t)\|_2^2 - \|\mathbf{x}_i - \mathbf{W}_{:,j'}(t)\|_2^2 < 0 \qquad (13)$$

$$(\mathbf{W}_{:,j}(t) + \mathbf{W}_{:,j'}(t) - 2\mathbf{x}_i) \cdot (\mathbf{W}_{:,j}(t) - \mathbf{W}_{:,j'}(t)) < 0 \qquad (14)$$

At $t+1$ after learning, the left-hand side of (14) is written as:

$$(\mathbf{W}_{:,j}(t+1) + \mathbf{W}_{:,j'}(t+1) - 2\mathbf{x}_i) \cdot (\mathbf{W}_{:,j}(t+1) - \mathbf{W}_{:,j'}(t+1)) \qquad (15)$$

The hybrid update changes the winner neuron if it is positive. Using (10) and (11), (15) can be re-written as:

$$\begin{aligned} \{\mathbf{W}_{:,j}(t) + \mathbf{W}_{:,j'}(t) - 2\mathbf{x}_i + \frac{\eta}{N}(\mathbf{W}_{:,j}(t) - \mathbf{W}_{:,j'}(t))\} \cdot \\ \{\mathbf{W}_{:,j}(t) - \mathbf{W}_{:,j'}(t) - \frac{\eta}{N}(2\mathbf{x}_i - \mathbf{W}_{:,j}(t) - \mathbf{W}_{:,j'}(t))\} \end{aligned} \qquad (16)$$

$$\frac{4\eta}{N}\|\mathbf{x}_i - \mathbf{W}_{:,j}(t)\|_2^2 + (1 - \frac{\eta}{N})^2(\mathbf{W}_{:,j}(t) + \mathbf{W}_{:,j'}(t) - 2\mathbf{x}_i) \cdot (\mathbf{W}_{:,j}(t) - \mathbf{W}_{:,j'}(t)) \qquad (17)$$

Substituting the second term in (17) by the left-hand side of (13),

$$(1 + \frac{\eta}{N})^2 \|\mathbf{x}_i - \mathbf{W}_{:,j}(t)\|_2^2 - (1 - \frac{\eta}{N})^2 \|\mathbf{x}_i - \mathbf{W}_{:,j'}(t)\|_2^2 \tag{18}$$

Equation (15) is positive if

$$\frac{\|\mathbf{x}_i - \mathbf{W}_{:,j'}(t)\|_2^2}{\|\mathbf{x}_i - \mathbf{W}_{:,j}(t)\|_2^2} < \frac{(1 + \frac{\eta}{N})^2}{(1 - \frac{\eta}{N})^2} \tag{19}$$

∎

Corollary 1.1. *Let two weight vectors* $\mathbf{W}_{:,j}$ *and* $\mathbf{W}_{:,j'}$ *with the biased activity and an input vector* $\mathbf{x}_i$ *satisfy* $\|\mathbf{x}_i - \mathbf{W}_{:,j}(t)\|_2 < \|\mathbf{x}_i - \mathbf{W}_{:,j'}(t)\|_2$ *at t. Then, Hebbian learning preserves the sign of the inequality to* $\|\mathbf{x}_i - \mathbf{W}_{:,j}(t+1)\|_2 < \|\mathbf{x}_i - \mathbf{W}_{:,j'}(t+1)\|_2$ *at* $t + 1$.

Proof. Similar to the proof of Theorem 1, we need to show the equation below is positive if Hebbian learning changes the winner neuron:

$$(\mathbf{W}_{:,j}(t+1) + \mathbf{W}_{:,j'}(t+1) - 2\mathbf{x}_i) \cdot (\mathbf{W}_{:,j}(t+1) - \mathbf{W}_{:,j'}(t+1)) \tag{20}$$

We have Hebbian learning rules for both the j-th and j'-th neuron as:

$$\mathbf{W}_{:,j}(t+1) = \mathbf{W}_{:,j}(t) + \frac{\eta}{N}(\mathbf{x}_i - \mathbf{W}_{:,j}(t)) \tag{21}$$

$$\mathbf{W}_{:,j'}(t+1) = \mathbf{W}_{:,j'}(t) + \frac{\eta}{N}(\mathbf{x}_i - \mathbf{W}_{:,j'}(t)) \tag{22}$$

Using the learning rules to re-write (20),

$$\{\mathbf{W}_{:,j}(t) + \mathbf{W}_{:,j'}(t) - 2\mathbf{x}_i + \frac{\eta}{N}(2\mathbf{x}_i - \mathbf{W}_{:,j}(t) - \mathbf{W}_{:,j'}(t))\} \cdot$$
$$\{\mathbf{W}_{:,j}(t) - \mathbf{W}_{:,j'}(t) - \frac{\eta}{N}(\mathbf{W}_{:,j}(t) - \mathbf{W}_{:,j'}(t))\} \tag{23}$$

$$(1 - \frac{\eta}{N})^2 (\mathbf{W}_{:,j}(t) + \mathbf{W}_{:,j'}(t) - 2\mathbf{x}_i) \cdot (\mathbf{W}_{:,j}(t) - \mathbf{W}_{:,j'}(t)) \tag{24}$$

As we assume

$$(\mathbf{W}_{:,j}(t) + \mathbf{W}_{:,j'}(t) - 2\mathbf{x}_i) \cdot (\mathbf{W}_{:,j}(t) - \mathbf{W}_{:,j'}(t)) < 0 \tag{25}$$

Equation (20) is always negative. Thus Hebbian learning cannot change the winner neuron. ∎

Corollary 1.2. *Let two weight vectors* $\mathbf{W}_{:,j}$ *and* $\mathbf{W}_{:,j'}$ *with the biased activity and an input vector* $\mathbf{x}_i$ *satisfy* $\|\mathbf{x}_i - \mathbf{W}_{:,j}(t)\|_2 < \|\mathbf{x}_i - \mathbf{W}_{:,j'}(t)\|_2$ *at t. Then, anti-Hebbian learning preserves the sign of the inequality to* $\|\mathbf{x}_i - \mathbf{W}_{:,j}(t+1)\|_2 < \|\mathbf{x}_i - \mathbf{W}_{:,j'}(t+1)\|_2$ *at* $t + 1$.

Proof. Similar to the proof of Theorem 1, we need to show the equation below is positive if anti-Hebbian learning changes the winner neuron:

$$(\mathbf{W}_{:,j}(t+1) + \mathbf{W}_{:,j'}(t+1) - 2\mathbf{x}_i) \cdot (\mathbf{W}_{:,j}(t+1) - \mathbf{W}_{:,j'}(t+1)) \tag{26}$$

We have anti-Hebbian learning rules for both the j-th and j'-th neuron as:

$$\mathbf{W}_{:,j}(t+1) = \mathbf{W}_{:,j}(t) - \frac{\eta}{N}(\mathbf{x}_i - \mathbf{W}_{:,j}(t)) \tag{27}$$

$$\mathbf{W}_{:,j'}(t+1) = \mathbf{W}_{:,j'}(t) - \frac{\eta}{N}(\mathbf{x}_i - \mathbf{W}_{:,j'}(t)) \tag{28}$$

Using the learning rules to re-write (26),

$$\{\mathbf{W}_{:,j}(t) + \mathbf{W}_{:,j'}(t) - 2\mathbf{x}_i + \frac{\eta}{N}(2\mathbf{x}_i - \mathbf{W}_{:,j}(t) - \mathbf{W}_{:,j'}(t))\}\cdot$$
$$\{\mathbf{W}_{:,j}(t) - \mathbf{W}_{:,j'}(t) - \frac{\eta}{N}(\mathbf{W}_{:,j}(t) - \mathbf{W}_{:,j'}(t))\} \tag{29}$$

$$(1 - \frac{\eta}{N})^2(\mathbf{W}_{:,j}(t) + \mathbf{W}_{:,j'}(t) - 2\mathbf{x}_i) \cdot (\mathbf{W}_{:,j}(t) - \mathbf{W}_{:,j'}(t)) \tag{30}$$

As we assume
$$(\mathbf{W}_{:,j}(t) + \mathbf{W}_{:,j'}(t) - 2\mathbf{x}_i) \cdot (\mathbf{W}_{:,j}(t) - \mathbf{W}_{:,j'}(t)) < 0 \tag{31}$$

Equation (26) is always negative. Thus anti-Hebbian learning cannot change the winner neuron. ∎

Theorem 2. *For a network of N neurons in the biased activity with weight vectors $\mathbf{W}$ and an input vector $\mathbf{x}$, the variance of the distribution of activated neurons follows* $\mathrm{Var}(\text{NeAW Hebbian}) \geq \mathrm{Var}(\text{Hebbian}) \text{ or } \mathrm{Var}(\text{anti} - \text{Hebbian})$ *which indicates NeAW Hebbian learning provides the greatest variance of the neuron activity compared to solely using Hebbian or anti-Hebbian learning.*

Proof. First, we note the results shown by Plumbley (1993), that Hebbian/Anti-Hebbian networks optimize the information capacity by orthonormalizing the principal subspace. In order to prove that the neuronal activations for the hybrid learning rule have a greater variance than the normal Hebbian or anti-Hebbian learning rules, we first assume that a network with a greater number of neuronal activations can encode a greater number of principal components in the subspace. We consider that the local Hebbian and anti-Hebbian learning rules recover a principal subspace from the data using a principled cost function as shown by Pehlevan et al. (2015).

The subspace method of classification is pattern recognition method where the primary model for a class is a linear subspace of the Euclidean pattern space (Watanabe & Pakvasa, 1973). Let $u_i \in \mathbb{R}^n, i = 1 \ldots m, m < n$ be a set of m linearly independent vectors that spans the subspace L as:

$$P = P(u_1, \ldots, u_m) = \left\{ x \mid x = \sum_{i=1}^{m} \alpha_i u_i \right\}$$

where α_i is some scalar. That is, essentially, the problem can be re-written as:

$$\mathrm{Var}(\text{NeAW Hebbian}) \geq \mathrm{Var}(\text{Hebbian}) \text{ or } \mathrm{Var}(\text{anti} - \text{Hebbian})$$
$$\Rightarrow \mathrm{span}_{\min}(\mathcal{L}_{\text{NeAW Hebbian}}) \geq \mathrm{span}_{\min}(\mathcal{L}_{\text{Hebbian}}) \text{ or } \mathrm{span}_{\min}(\mathcal{L}_{\text{anti}-\text{Hebbian}}) \tag{32}$$

where $\mathrm{span}_{\min}$ is the minimum spanning subspace, i.e., the subspace does not have a smaller subspace spanned by a subset of the samples. For a detailed explanation of minimal sample subspace refer to the works of Zhang & Xia (2019).

As shown before, the learning rules for the Hebbian and anti-Hebbian cases are given, respectively as:

$$\mathbf{W}_{:,j}^{\text{Hebb}}(t+1) = \mathbf{W}_{:,j}^{\text{Hebb}}(t) + \frac{\eta}{N}(\mathbf{x}_i - \mathbf{W}_{:,j}(t))$$
$$\mathbf{W}_{:,j}^{\text{anti-Hebb}}(t+1) = \mathbf{W}_{:,j}^{\text{anti-Hebb}}(t) - \frac{\eta}{N}(\mathbf{x}_i - \mathbf{W}_{:,j}(t)) \tag{33}$$

Now, let us consider the case where we have N neurons which are learned using Hebbian or anti-Hebbian learning rules. We aim to bifurcate the sets of trained neurons into Hebbian and anti-Hebbian classes. Without loss of generality, we can assume that the first n $(n < N)$ neurons are trained using the a learning method $\mathcal{L} \in \{\mathcal{L}_H = \text{Hebbian}, \mathcal{L}_{aH} = \text{anti-Hebbian}\}$. Mathematically, we do a binary partition of the metric space of the neurons and the weights. If we consider the metric space of the neuron vectors and the weight vectors to be represented as $\mathcal{W}$, we define the partition from $X \to Y, Z$ where X denotes the space of all the vectors, Y denotes the space of vectors where all the neurons have already learnt (which is interpreted as a coloring of the vector) using learning algorithm $\mathcal{L}$. Z denotes the space of vectors where none of the neurons have been assigned a learning rule, i.e., they can learn using either $\mathcal{L}_H$ or $\mathcal{L}_{aH}$. We denote the span of the subspace learned using the learning method $\mathcal{L}$ is denoted as $\text{span}(x_1^{\mathcal{L}}, \ldots, x_n^{\mathcal{L}})$.

Now, let us consider the $n+1$-th neuron. There might be two cases that might arise: (i) the neuron is trained using the same learning rule $\mathcal{L}$ with which the previous n neurons are trained. (ii) the neuron is trained using the complementary learning rule $\bar{\mathcal{L}}$. Thus, we study the differential gain by using one learning rule over the other for the $n + 1$-th neuron.

We know that a learning rule basically extracts the principal components of the input space by projecting the input space into the orthogonal subspace. Also, we know that a neural network with a richer subspace, i.e., a subspace with a larger number of orthogonal principal components, can learn a better representation of the input space than a subspace with a fewer number of orthogonal principal components.

Again, let us consider the subspaces learned by the Hebbian $\mathcal{L}_H$ and the anti-Hebbian $\mathcal{L}_{aH}$ learning rules. From previous works (Rubner & Tavan, 1989; Carlson, 1990; Schraudolph & Sejnowski, 1991) we know that anti-Hebbian and Hebbian learning rules lead to different principal components. As described by Schraudolph & Sejnowski (1991) while the built-in temporal smoothness constraint enables Hebbian neurons to learn the invariance classes, anti-Hebbian synapses have been used for lateral decorrelation of feature detectors and removal of temporal variations from the input. A set of Hebbian feature detectors whose weight vectors span the hyperplane would characterize the associated class of stimuli. The anti-Hebbian learning algorithm, however, provides a more efficient representation when the dimensionality of the hyperplane is more than half of the input space. This is because, in that case, we require fewer normal vectors than spanning vectors for unique characterization. Since anti-Hebbian neurons remove the variance within a stimulus class, they present a different output representation to subsequent layers than the Hebbian neurons. Thus, since the linear subspaces learned by the two learning rules are distinct, we can say that:

$$\text{span}(x_1^{\mathcal{L}}, \ldots, x_n^{\mathcal{L}} \cup x_{n+1}^{\mathcal{L}}) \subseteq \text{span}(x_1^{\mathcal{L}}, \ldots, x_n^{\mathcal{L}} \cup x_{n+1}^{\bar{\mathcal{L}}})$$
$$\Rightarrow \text{span}(\text{Hebbian}) \text{ or } \text{span}(\text{anti-Hebbian}) \subseteq \text{span}(\text{NeAW Hebbian}) \qquad (34)$$

Thus, we see that using a hybrid Hebbian learning rule increases the span of the subspace learned, i.e., increases the variance of the neuron activations. ∎

Corollary 2.1. *Hebbian or anti-Hebbian learning on the biased neuron activity leads to a poor subspace representation than NeAW Hebbian learning*

Proof. As we showed before in Theorem 2 in (34), we see that the span of the subspace learned by the NeAW Hebbian learning algorithm is greater than the span of the homogeneous Hebbian or anti-Hebbian learning method. Let us label each neuron as 'H' or 'aH' for Hebbian or anti-Hebbian learning methods depending on the learning algorithm it selects. Now, let us denote the distribution of the nodes marked 'H' and the distribution of the nodes marked 'aH' in the vector space of the neuron weights. We notice that since the total number of neurons is fixed, the total probability mass of these two distributions is also fixed. Thus, if there are a lot more 'H' neurons, the probability mass of the 'aH' neurons is lower - i.e., for the set of neurons $n_i \in \mathcal{N}$, $\mathbb{P}[\sum_{i \in H \sim \mathcal{N}} n_i] > \mathbb{P}[\sum_{i \in aH \sim \mathcal{N}} n_i]$. Now, considering the full set of principal components that the entire network can learn using an infinite number of neurons. As we keep decreasing the number of neurons, we keep learning a subset of this ideal set of principal components. Since the sum of probability masses of the Hebbian and anti-Hebbian learning algorithms are fixed, if the distribution is heavily biased

towards just Hebbian learning, then the principal axes that could be learned from the anti-Hebbian learning are not present. Thus, if we represent the principal axes of the learning rule $\mathcal{L}$ as $\mathbf{a}_{\mathcal{L}}$, then $\text{span}_{\min} \sum \mathbf{a}_{\text{NeAW}} \text{span}_{\min} \sum \mathbf{a}_X$, where X represents either Hebbian or anti-Hebbian learning neurons. Hence, a biased learning algorithm leads to a poorer selection of the principal axes, which leads to worse performance. ∎

B VISUALIZATION OF WEIGHT VECTOR

Figure 8: Visualization of weight vectors. (top) the weight vectors in the last layer trained by NeAW Hebbian learning and (bottom) plain Hebb's rule. Dark elements refer the low values while bright elements are with the high values.

Figure 8 shows the weight vectors of the last layer in the encoder trained by different unsupervised learning rules. While plain Hebb's rule in Table 1 achieves the higher variance of the neuron activity than the other learning rules, the variance between context vectors of different objects is low. It indicates that the trained model uses more neurons to represent objects, but it fails to activate the different subset of neurons for different objects. Given plain Hebb's rule repeatedly strengthens the weight of frequently activated pre- and post- synaptic neurons, the weight vectors will mostly learn the commonly appeared position vectors of objects, which degrade the sample-to-sample variation. Figure 8 describes the sparse weight matrix trained by Hebb's rule showing that the only few elements are with high values.