CONTINUAL POST-TRAINING OF LANGUAGE MODELS

ABSTRACT

Language models (LMs) have been instrumental for the recent rapid advance of natural language processing. Existing research has shown that post-training or adapting an LM using an unlabeled topical/domain corpus can improve the end-task performance in the domain. This paper proposes a novel method to *continually post-train* an LM with a sequence of unlabeled domain corpora to adapt the LM to these domains to improve their end-task performances. The key novelty of our method is a soft-masking mechanism that directly controls the update to the LM. A novel proxy is also proposed to preserve the general knowledge in the original LM. Additionally, it contrasts the representations of the previously learned domain knowledge (including the general knowledge in pre-trained LM) and the knowledge from the current full network to achieve knowledge integration. The method not only overcomes *catastrophic forgetting*, but also achieves *knowledge transfer* to improve end-task performances compared to post-training each domain separately. Empirical evaluation demonstrates the effectiveness of the proposed method. [1]

1 INTRODUCTION

Recently, pre-trained language models (LMs) like BERT (Devlin et al., 2019) and RoBERTa (Liu et al., 2019) have significantly advanced NLP. *Post-training*[2] an LM using a large unlabeled domain corpus before end-task fine-tuning achieves even better results (Gururangan et al., 2020; Xu et al., 2019). This paper goes a step further and asks how to improve an LM's ability to handle new and emerging domains *without* forgetting its learned skills/knowledge. This is important in the real world, where the data shifts constantly and new domains keep emerging (Gururangan et al., 2020). For example, one may adapt an LM trained over a general domain (e.g., News) to some science domains (e.g., ACL and AI papers). From a broader perspective, since training a large LM from scratch is extremely expensive, incrementally updating it with the latest data reflecting the ever changing knowledge is becoming critical. As humans are very effective at incremental learning, if we can imitate this human capability with little/no forgetting, we can push AI research forward significantly.

We call this problem continual learning (CL) of post-training or *continual post-training*. Starting from a *pre-trained* LM (i.e., the LM has already been pre-trained on D_0), we incrementally post-train a sequence of domain corpora $D_1, D_2, ...$ Once a domain is trained, its data is no longer accessible. This is different from conventional CL where each task is an end-task. In continual post-training, each task is an unlabeled domain corpus and the end-task involves fine-tuning the post-trained LM. This is also different from *continual pre-training* (Qin et al., 2022b), where one *builds* the LM from scratch and can access the data (pre-training data D_0) that pre-trains the LM. In continual post-training, however, one *uses* the LM and thus do not have access to the pre-training data but only one's own domain data. We will see how this causes challenges to the problem.

There are multiple desiderata for a continual post-training system: **(1)** It should not suffer from *catastrophic forgetting* (CF) , i.e., it should perform reasonably well on learned domains. This requires the system (a) to overcome CF for each new domain and (b) to overcome CF for the general language knowledge in the LM. This is important because the knowledge learned from each domain alone will not be sufficient for good end-task performances. **(2)** It should encourage knowledge transfer (KT) across domains to achieve improved end-task performances. This requires the system to enable (a) *forward transfer*, learning new domain by leveraging knowledge from previous domains, and (b)

---

[1]The code has been uploaded as supplementary materials.
[2]Depending on different contexts, it also called *domain-adaptive pre-training* or *pre-finetuning*

backwards transfer, gaining improved performance on previous domains after learning a relevant new domain. **(3)** It should learn without requiring domain labels for each end-task fine-tuning.

None of the existing CL methods can achieve all the above. This paper presents a step towards achieving them. The proposed method is called CPS (*C*ontinual *P*ost-training of LMs with *S*oft-masking). CPS proposes a novel *soft-masking mechanism* that computes the importance (a real number between 0 and 1) of units[3] for general or domain knowledge and soft-mask them based on their importance values to control the backward gradient flow. In the forward pass, soft-masking is not applied, which encourages KT across domains. This does not isolate any sub-network for any domain so that the knowledge in the full LM can be leveraged for end-task fine-tuning.

To apply this mechanism, CPS implements two functions: (1) *Initialization*, where the goal is to compute the importance of units to general knowledge without accessing the pre-training data (D_0). It is applied on the pre-trained LM before the continual learning starts, and (2) *continual learning*, where the goal is to prevent CF on general and domain knowledge and to encourage cross-domain KT during post-training. In (1), it is not obvious how to compute the importance without pre-training data. CPS proposes a novel proxy based on *robustness* to compute the importance of units for the general knowledge. In (2), the soft-masking is directly applicable because we have the domain data and the importance can be computed based on its gradient inspired by the pruning community (Li et al., 2021; Michel et al., 2019). Moreover, CPS contrasts the previously learned knowledge and the full (including both the learned domains and the current domain) knowledge to encourage the current domain representation to learn knowledge that is not already in the learned knowledge in previous domains and and integrate it with the learned knowledge[4]. In end-task fine-tuning, CPS does not need the domain id as all knowledge is accumulated into the post-trained LM.

In summary, this work makes the following contributions. **(i)** It proposes the problem of *continual post-training*. Although (Jin et al., 2021) runs systems on a similar setting, it simply regards it as continual pre-training *without* proposing any new method or giving any analysis on the properties or the desiderata. **(ii)** It discovers the full LM is needed for a good continual post-training method. This is, the popular *parameter-isolation* approach in convention CL is not suitable. **(iii)** It proposes a novel soft-masking method to overcome CF and to encourage KT. It further proposes to integrate knowledge across domains. **(iv)** To preserve the general knowledge in the LM, a novel proxy is also proposed. **(v)** Experiments results demonstrate the effectiveness of CPS.

2 RELATED WORK

Post-training (also known as domain-adaptive pre-training). Researchers have applied post-training to many domains, e.g., reviews (Xu et al., 2019; Sun et al., 2019), news and academic papers (Gururangan et al., 2020), and shown improved end-task results. However, they are not about CL.

Continual learning. Many approaches have been proposed to overcome CF: (1) *Regularization methods* (Kirkpatrick et al., 2016; Seff et al., 2017) computes the importance of each parameter to previous tasks and uses a regularization term to penalize the sum of changes. Our CPS is related to EWC (Kirkpatrick et al., 2016), but they are different. (1) CPS does not control each parameter/weight, but only attention heads or neurons based on their importance scores. This gives less forgetting (see the forgetting rate in Table 2) because even a small change to each parameter for a neuron can give a large total change to the neuron's activation. (2) CPS directly controls the backward gradient flow on each neuron, which is more fine-grained and effective than the sum of changes of all parameters. Our experimental results confirms EWC is significantly poorer than CPS (see Table 2). (2) *Replay methods* retain (Rebuffi et al., 2017; Wang et al., 2020) or generate some data of old tasks (Shin et al., 2017; He & Jaeger, 2018) and use them in learning a new task; (3) *parameter-isolation methods* (Serrà et al., 2018; Wortsman et al., 2020) allocate neurons and parameters for different tasks and mask them in task learning. This family has almost no CF in *task-incremental learning* setting where the domain id is known in any time. However, this family is designed for supervised end-task CL and learns *binary/hard masks* to isolate a sub-network for each domain. For continual post-training, we

---

[3]For simplicity, we use the term *units* to mean both *attention heads* and *neurons*

[4]Contrasting the past domain and only the domain-specific knowledge gives poorer results (see Sec. 4.2) as it causes the two types of knowledge to split rather than to integrate.

cannot isolate a sub-network for each domain because it means that end-tasks cannot use the general knowledge in the LM, which results in very poor end-task performances.

In NLP, CL has been used for slot filling (Shen et al., 2019), language learning (Li et al., 2019), sentiment analysis (Shu et al., 2017), topic modeling (Gupta et al., 2020), question answering (Greco et al., 2019) and text classification (Sun et al., 2020; Huang et al., 2021; Chuang et al., 2020). But none is for post-training. Some recent CL papers concern LMs. Madotto et al. (2020) learns separate adapters, it has no CF or knowledge transfer. DEMIX (Gururangan et al., 2021) is similar to (Madotto et al., 2020) but initializes the new adapter with the closest old adapter. Jin et al. (2021) compared several CL methods for continual post-training. ELLE (Qin et al., 2022a) concerns continual pre-training (see the difference in Sec. 1) and uses a large memory (1G per domain) to store replay data and expands the network for each domain. Both are not required in CPS.

Neural network pruning. Many parameters in a network are redundant and can be pruned (Li et al., 2021; Lai et al., 2021; Chen et al., 2020a; Lin et al., 2020; Gao et al., 2021b; Michel et al., 2019; Voita et al., 2019). One method discards parameters with small absolute values (Han et al., 2015; Guo et al., 2016). Other methods include accumulated gradient (Michel et al., 2019), dropout rate (Gomez et al., 2019), and lottery ticket hypothesis (Brix et al., 2020). However, these methods are not directly applicable as we need to preserve not only individual domain knowledge but also the general knowledge in the LM. For general knowledge, we do not have any pre-training data so a proxy is proposed based on robustness. For domain knowledge, we adopt the pruning method but use the importance as soft-masks as we want to accumulate knowledge rather than to compress the LM.

Contrastive Learning. Contrastive learning (Chen et al., 2020b; He et al., 2020) learns good representations by maximizing the similarity of positive pairs and minimizes that of negative pairs:

$$\mathcal{L}_{\text{contrast}} = -\log \frac{e^{(\text{sim}(q_i, q_i^+)/\tau)}}{\sum_{j=1}^{N} e^{(\text{sim}(q_i, q_j^+)/\tau)}}, \tag{1}$$

where N is the batch size, τ is a temperature parameter, $\text{sim}(\cdot)$ is a similarity metric, and q_i and q_i^+ are representations for positive pairs x_i and x_i^+. Our CPS contrasts the learned knowledge from previous domains and pre-trained LM (general knowledge) with the full knowledge (including both the previous domains and current domain knowledge) to achieve a complementary effect.

3 PROPOSED CPS TECHNIQUE

Continual post-training in CPS is based on two main ideas: (1) preserving the important general language knowledge in the LM and knowledge learned from previous domains to overcome CF by soft-masking units based on their importance, which also facilitates cross-task knowledge transfer, and (2) encouraging the model to learn complementary representations of the current domain and previous domains to achieve knowledge integration. Figure 1 gives an overview of CPS.

The whole learning consists of two main functions: (i) *initialization* and (ii) *continual learning*. (i) computes the importance of units to the general language knowledge in the LM. It is done before the continual learning starts. (ii) is for continual learning, which consists of two steps: (a) *task training* and (b) *importance computation*. (a) takes the importance scores accumulated so far (including those to general knowledge and to the learned domains) and the input data of the current domain to learn the domain and to achieve (1) and (2) above, while (b) computes the importance scores for the current domain for future use. The following sub-sections present each function and step in detail.

3.1 INITIALIZATION: COMPUTING IMPORTANCE OF UNITS TO THE GENERAL KNOWLEDGE

This initialization function computes the importance of units (attention heads and neurons) in the Transformer for the *general* knowledge in the original LM. The key components of a Transformer are *multi-head attention layer*, *intermediate layer* and *output layer*. Below, we use "layer" or l to indicate any of these three layers because our method treats the three layers similarly.

Importance of units in a layer. It has been found that not all units in a layer are important (Michel et al., 2019). We introduce a *gate vector*, $\boldsymbol{g}_l$, for computing the importance of unit in a layer l.

$$\hat{\boldsymbol{o}}_l = \boldsymbol{g}_l \otimes \boldsymbol{o}_l, \tag{2}$$

Figure 1: Illustration of CPS. (A) **Initialization** (Sec. 3.1) learns the importance of units for the general knowledge in the LM. (B) **Training** (Sec. 3.2) trains the new domain using the importance scores as soft-masks and contrasts the previously learned knowledge and full knowledge. (C) **Importance Computation** (Sec. 3.3) learns the importance of units for the current domain.

where o_l refers to the output of layer l (which can be any of the three layers mentioned above). The $\otimes$ refers to element-wise multiplication, i.e., each gate variable $g_{l,i}$ in g_l corresponding to a unit (a neuron or attention head) in the layer. A gradient-based importance detection method is proposed in (Michel et al., 2019). Given a dataset $D = \{(\boldsymbol{x}_m, y_m)\}_{m=1}^{M}$ of M samples (y_m is the class label of $\boldsymbol{x}_m$ as Michel et al. (2019) worked on supervised learning), the importance of neurons or heads in the layer is estimated with a gradient-based proxy score

$$\boldsymbol{I}_l = \frac{1}{M} \sum_{m=1}^{M} |\frac{\partial \mathcal{L}_{\text{impt}}(\boldsymbol{x}_m, y_m)}{\partial \boldsymbol{g}_l}|, \tag{3}$$

where $\mathcal{L}_{\text{impt}}$ is a task-specific loss function. Note the gate vector g_l is initialized as all 1's, and is not changed. This is because we need only its average gradient $\nabla_{\boldsymbol{g}_l}$ (the term within $||$ in Eq. 3) over all the data to compute the importance and will not use the gradient to update the gate vector. In training (Sec. 3.2 and Fig 1 (B)), the gate vector can be discarded. The resulting $\boldsymbol{I}_l$ is of the same size as g_l, each entry corresponding to the importance of a unit (a neurons or attention head).

Recall that the *initialization* function is to learn the importance of units to the *general knowledge* in the LM ($\boldsymbol{I}_l^{\text{gen}}$). Although Eq. 3 offers a possible way, it is not directly applicable. If we use the domain data at hand and employ the MLM loss as $\mathcal{L}_{\text{impt}}$, $\nabla_{\boldsymbol{g}_l}$ only indicates the importance score for the *domain-specific* knowledge. However, to compute the importance of units to the general knowledge in the LM (which is our goal), we need the original data used in pre-training the LM to compute the $\mathcal{L}_{\text{impt}}$. In practice, such data is not accessible to users of the LM. Further, label is needed in Eq. 3 but our domain corpus is unlabeled in post-training. To address these issues, we propose a *proxy KL-divergence loss* ($\mathcal{L}_{\text{proxy}}$) to replace $\mathcal{L}_{\text{impt}}$ to learn units importance for the general knowledge.

Proxy KL-divergence loss. We propose to use model *robustness* as the proxy, i.e., we try to detect units that are important for LM's *robustness*. Their gradients, $\nabla_{\boldsymbol{g}_l}$, then indicate the robustness and the importance to the LM model. Our rationale is as follows: If an $I_{l,i}^{\text{gen}}$ (the importance of unit i in layer l) has a high value, then it is important to the LM's robustness because its change can cause the LM to change a lot. It is thus an important unit. In contrast, if $I_{l,i}^{\text{gen}}$ is small, it is a less important unit.

To compute the *robustness* of the LM, we take a subset of the current domain data $\{\boldsymbol{x}_m^{\text{sub}}\}$[5] (no label in post-training) and input $\boldsymbol{x}_m^{\text{sub}}$ twice to the LM to obtain two representations of it and then compute the KL-divergence between them,

$$\mathcal{L}_{\text{impt}} = \text{KL}(f_{\text{LM}}^1(\boldsymbol{x}_m^{\text{sub}}), f_{\text{LM}}^2(\boldsymbol{x}_m^{\text{sub}})), \tag{4}$$

---

[5]We use a subset to save computation as we assume that the post-training domain can be very large. In Sec. 4, we show that a subset is sufficient to compute the importance of units for the general knowledge.

where f_{LM}^1 and f_{LM}^2 are the LM with different dropout masks. We don't need to add any additional dropouts to implement these two as the Transformer already has dropout masks placed on fully-connected layers and attention probabilities. Thus, simply feeding the same input to the Transformer twice will get two representations with different dropout masks. Since dropout is similar to adding noise, the difference between the two representations can be regarded as the *robustness* of the LM.

3.2 TRAINING: LEARNING A NEW DOMAIN VIA SOFT-MASKING AND CONTRASTIVE LOSS

Soft-masking units. Recall we want to preserve the learned knowledge in the LM during post-training using the accumulated importance $\boldsymbol{I}_l^{(\leq t-1)}$ when we learn domain t, which includes both the importance for the general knowledge $\boldsymbol{I}_l^{\text{gen}}$ (Sec. 3.1) and learned domain-specific knowledge $\boldsymbol{I}_l^k$ of each domain k (k can be any domain in $\{1...t-1\}$) that has been learned (Sec. 3.3). This is achieved by soft-masking the learning based on accumulated importance as follows.

Note that the importance values in each layer l for a domain k is normalized via

$$\text{Norm}(I_{l,i}^{(k)}) = |\text{Tanh}(\frac{I_{l,i}^{(k)} - \text{Mean}(\boldsymbol{I}_l^{(k)})}{\sqrt{\text{Var}(\boldsymbol{I}_l^{(k)})}})|. \tag{5}$$

Mean and Var are computed from the importance of all units in layer l. The normalized $I_{l,i}^{(k)}$ has the same size as the un-normalized $I_{l,i}^{(k)}$, and now $\boldsymbol{I}_l^{(k)}$ has the mean of 0 and standard deviation of 1. Absolute value of Tanh ensures that $\boldsymbol{I}_l^{(k)}$ takes values in the interval $[0, 1]$. To simplify the notation, we still use $\boldsymbol{I}_l^{(k)}$ to represent the normalized importance. We accumulate the importance after task $t-1$ was learned is done via element-wise max (EMax) as follows:

$$\boldsymbol{I}_l^{(\leq t-1)} = \text{EMax}(\{\boldsymbol{I}_l^{t-1}, \boldsymbol{I}_l^{(\leq t-2)}\}), \tag{6}$$

where t refers to the current task-ID and $\boldsymbol{I}_l^{(\leq t-2)}$ refers to the previously accumulated importance at task $t-2$. When we learn task 1, $\boldsymbol{I}_l^{(\leq 0)}$ is $\boldsymbol{I}_l^{\text{gen}}$. We do not need to save $\boldsymbol{I}_l^{\text{gen}}$ and all $\{\boldsymbol{I}_l^{(k)}\}_{k=1}^{t\text{-}1}$ for Eq. 6. We only save the incrementally accumulated importance after training of each task.

For soft-masking, given the accumulated importance $\boldsymbol{I}_l^{(\leq t-1)}$ of layer l and the post-training loss $\mathcal{L}_{\text{post-train}}$ (typically the MLM loss; we also propose an additional loss in Eq. 11), we constrain (or soft-mask) its corresponding gradient (∇_l) flow as follows,

$$\hat{\nabla}_l = (1 - \boldsymbol{I}_l^{(\leq t-1)}) \otimes \nabla_l, \tag{7}$$

As mentioned in Sec. 3.1, we expand (by copying) the importance $\boldsymbol{I}_l^{(\leq t-1)}$ to match the dimensions of ∇_l to apply it to all associated parameters. This is *soft-masking* as each element in $\boldsymbol{I}_l^{(\leq t-1)}$ is a real number in $[0, 1]$ (not binary $\{0, 1\}$), which gives the model the flexibility to adjust any unit.

We note that the above soft-masks are only applied in the backward pass, but not in the forward pass, which encourages knowledge transfer as each domain training can leverage the knowledge learned from all past domains. To further encourage the model to learn a good representation from both the accumulated knowledge ($\boldsymbol{I}_l^{(\leq t-1)}$) and the full knowledge (both accumulated and current domain knowledge), we introduce a contrastive learning method to encourage complementary representation.

Contrasting the previously learned and new domain knowledge. We now present how to integrate the previously learned knowledge and the current domain knowledge by contrasting the previously learned knowledge and the full knowledge (both previously learned knowledge and the current domain knowledge). This is done based on the current domain data. Below we first introduce how to obtain the required types of knowledge for input $\boldsymbol{x}$, and then discuss how we contrast for integration.

(1) *Obtaining previously learned knowledge in the current LM using the input $\boldsymbol{x}$.* This is done by extracting the representation of $\boldsymbol{x}$ from the network learned from previous domains by combining the units in the layer and their importance scores $\boldsymbol{I}_l^{(\leq t-1)}$ in a *forward pass*. The intuition is that since the importance scores show how important each unit is to the previously learned knowledge (including the general knowledge in the *initialization* functions), the resulting representation reflects

the main previously learned knowledge used by $\boldsymbol{x}$. Formally, we use $\boldsymbol{I}_l^{(\leq t-1)}$ to gate the output of layer l (similar to Eq. 2),

$$\boldsymbol{o}_l^{\text{prev}} = \boldsymbol{I}_l^{(\leq t-1)} \otimes \boldsymbol{o}_l. \tag{8}$$

Given the units in layer l for the previously learned knowledge $\boldsymbol{o}_l^{\text{prev}}$, we can plug it into the whole language model to obtain the final learned knowledge or representation, taking the average of each token's output in the input sequence $\boldsymbol{x}$ (see $\boldsymbol{o}^{\text{prev}}$ in Figure 1 (B)),

$$\boldsymbol{o}^{\text{prev}} = f_{\text{LM}}(\boldsymbol{o}_l^{\text{prev}}). \tag{9}$$

(2) *Obtaining full (both learned domains and current domain) knowledge in $\boldsymbol{x}$.* This is similar to the above except that we extract the representation by using all units in the layer without considering their importance (the gates are removed) , i.e., $o_l^{\text{full}} = \boldsymbol{o}_l$.

Similarly, we can plug it into the Transformer (see $\boldsymbol{o}^{\text{full}}$ also in Figure 1 (B)),

$$\boldsymbol{o}^{\text{full}} = f_{\text{LM}}(o_l^{\text{full}}). \tag{10}$$

It is also possible to use $(1 - \boldsymbol{I}_l^{(\leq t-1)})$ as the importance of domain knowledge and contrast it with the previously learned knowledge, but this gives poorer results (Table 3) as explained in footnote 3.

(3) *Contrasting learned and full knowledge.* Contrastive learning helps learn a good isotropic representation that is good for down-stream tasks, with the help of positive $\boldsymbol{o}_m^+$ and negative $\boldsymbol{o}_m^-$ instances. In our case, such instances are representations of the input $\boldsymbol{x}$ for both the full knowledge ($\boldsymbol{o}^{\text{full}}$) and the previously learned domain knowledge ($\boldsymbol{o}^{\text{prev}}$) in the current LM. This enables us to contrast the two representations, which essentially makes the two representations *complementary* as they represent two aspects of the same input. It thus encourages the current domain representation of $\boldsymbol{x}$ in $\boldsymbol{o}^{\text{full}}$ to learn knowledge that is not already in the learned knowledge in previous domains and yet related to and integrated with the learned knowledge ($\boldsymbol{o}^{\text{prev}}$).

We construct the contrastive instances as follows: for input $\boldsymbol{x}_m$, three instances are produced. Anchor $\boldsymbol{o}_m$ and positive instance $\boldsymbol{o}_m^+$ are both the full knowledge from Eq. 10 obtained based on two independently sampled dropout masks in Transformer (recall this can be achieved by inputting $\boldsymbol{x}_m$ twice, see Sec. 3.1). $\boldsymbol{o}_m^+$ and $\boldsymbol{o}_m$ are positive instances as the dropout noise has been shown good positive instances in training sentence embedding (Gao et al., 2021a). Negative instance $\boldsymbol{o}_m^-$ is the representation of $\boldsymbol{x}_m$ in the previously learned knowledge obtained by Eq. 9. Contrastive learning pushes the positive and negative instances away, forcing them to be different and covering different aspects (full and previously learned knowledge) of the same input, resulting in knowledge integration.

Formally, with $\boldsymbol{o}_m$, $\boldsymbol{o}_m^+$, and $\boldsymbol{o}_m^-$, our contrastive loss is (sim($\cdot$) is the cosine similarity),

$$\mathcal{L}_{\text{contrast}} = -\log \frac{e^{\text{sim}(\boldsymbol{o}_m,\boldsymbol{o}_m^+)}/\tau}{\sum_{j=1}^N (e^{\text{sim}(\boldsymbol{o}_m,\boldsymbol{o}_j^+)/\tau} + e^{\text{sim}(\boldsymbol{o}_m,\boldsymbol{o}_j^-)/\tau})}. \tag{11}$$

Compared to Eq. 1, the second term is added in the denominator, i.e., representation in the previously learned knowledge as additional negative instances. Figure 1 (B) shows a red arrow pointed from $\boldsymbol{o}^{\text{full}}$ to itself, indicating the positive instances are from inputting twice. The dashed red arrow pointing to $\boldsymbol{o}^{\text{prev}}$ indicates the negative instances contrasting the full and previously learned knowledge.

Final Loss Function. The final post-training loss combines the Masked Language Model (MLM) loss after applying the proposed soft-masking for the general knowledge (we call $\mathcal{L}_{\text{MLM+SM}}$, where SM is for soft-masking) (Sec. 3.1) and the proposed contrastive loss (λ is a hyper-parameter),

$$\mathcal{L}_{\text{post-train}} = \mathcal{L}_{\text{MLM+SM}} + \lambda \mathcal{L}_{\text{contrast}} \tag{12}$$

3.3 COMPUTE IMPORTANCE OF UNITS TO THE CURRENT DOMAIN

After training the new/current domain t, we learn the units importance by applying Eq. 3 for the domain. We do not need any proxy to compute $\mathcal{L}_{\text{impt}}$ as in Eq. 4 because we can directly use the current domain data. Specifically, we randomly sample a subset (a hyper-parameter) of the current domain data $\{(\boldsymbol{x}_m^{\text{sub}}, y_m^{\text{sub}})\}$, where $\boldsymbol{x}_m^{\text{sub}}$ is the input and y_m^{sub} is the masked token as in MLM self-supervised loss. We can then easily compute the importance $\boldsymbol{I}_l^{(t)}$ by plugging $\mathcal{L}_{\text{MLM}}$ into $\mathcal{L}_{\text{impt}}$ in Eq. 3. The resulting $\boldsymbol{I}_l^{(t)}$ will be used in the next task by accumulating with the previously accumulated importance (Eq. 6) and soft-masking the learning (Eq. 7).

Unlabelde Domain Datasets			End-Task Classification Datasets				
Source	Dataset	Size	Dataset	Task	#Training	#Testing	#Classes
Reviews	Yelp Restaurant	758MB	Restaurant	Aspect Sentiment Classification (ASC)	3,452	1,120	3
	Amazon Phone	724MB	Phone	Aspect Sentiment Classification (ASC)	239	553	2
	Amazon Camera	319MB	Camera	Aspect Sentiment Classification (ASC)	230	626	2
Academic Papers	ACL Papers	867MB	ACL	Citation Intent Classification	1,520	421	6
	AI Papers	507MB	AI	Relation Classification	2,260	2,388	7
	PubMed Papers	989MB	PubMed	Chemical-protein Interaction Prediction	2,667	7,398	13

Table 1: Statistics of datasets for post-training. More details of their end-task supervised learning datasets are given in Appendix B.

4 EXPERIMENTS

We use RoBERTa (Liu et al., 2019)[6] as the LM. Following the standard evaluation setup (Lange et al., 2019) and, after a domain is trained, its training data is discarded. After all domains are incrementally learned, the final model is evaluated by fine-tuning the end-tasks in all domains.

4.1 DATASETS AND BASELINES

Datasets: Table 1 shows the statistics of the 6 *unlabeled domain corpora* for post-training and their 6 corresponding *end-task classification datasets*.[7] 3 of them are about reviews: *Yelp Restaurant* (Xu et al., 2019), *Amazon Phone* (Ni et al., 2019), *Amazon Camera* (Ni et al., 2019); 3 of them are academic papers: *ACL Papers* (Lo et al., 2020), *AI Papers* (Lo et al., 2020), and *PubMed Papers*[8]. Their corresponding *end-task classification datasets* are:[9] *Restaurant*[10], *Phone* (Ding et al., 2008; Hu & Liu, 2004), *Camera* (Ding et al., 2008; Hu & Liu, 2004), *ACL* (ACL-ARC in (Jurgens et al., 2018)), *AI* (SCIERC in (Luan et al., 2018)), and PubMed (CHEMPORT in (Kringelum et al., 2016)).

Baselines. We use 16 baselines, including non-continual learning (Non-CL) and continual learning (CL) baselines. All CL baselines are originally for learning supervised data except DEMIX. We adapt them and replace their backbone with RoBERTa. Details of each baseline is given in Appendix C.

Non-CL Baselines: Each baseline here builds a separate model for each task. **(1) Pool.** We pool the data of all domains together and train only one model for all domains. **(2) RoBERTa** (Liu et al., 2019) uses RoBERTa for end-task fine-tuning without post-training. **(3) Post (RoBERTa)** uses the existing post-training method (MLM) in (Gururangan et al., 2020) to posst-train each domain separately. **(4) Post (Adapter)** adds adapter[11] layers in Transformer for each domain for post-training (Jang et al., 2021; Madotto et al., 2020; Houlsby et al., 2019). Only the added adapters are trainable. In end-task fine-tuning, both RoBERTa and the adapters are trainable. **(5) Post (Prompt)** is from (Lester et al., 2021). In post-training, RoBERTa (the LM) is fixed and only the prompts are trained. In end-task fine-tuning, both the LM and the trained prompt are trainable.

CL Baselines: We use 2 naive baselines, which keep learning more domains with no mechanism to deal with CF or transfer. **(6) NCL** (Naive CL) continually post-trains the RoBERTa; and **(7) NCL (Adapter)** continually post-trains a set of adapters (Houlsby et al., 2019).

8 baselines are CL systems: **(8) DEMIX** (Gururangan et al., 2021) adds a new adapter for each new domain and initializes it with a previous adapter nearest to the new domain; **(9) BCL** (Ke et al., 2021b) uses capsule networks. **(10) CLASSIC** (Ke et al., 2021a) uses contrastive learning. **(11) KD** is knowledge distillation (Hinton et al., 2015). **(12) EWC** (Buzzega et al., 2020) is a popular regularization-based method. **(13) DER++** (Buzzega et al., 2020) is a replay method based on knowledge distillation. 16.4K tokens are saved for each domain in the replay memory, which is

---

[6] https://huggingface.co/roberta-base

[7] We down-sampled the *PubMed* due to its huge original size. In general, our datasets are much smaller than those used in (Gururangan et al., 2020) (which used more than 11GB of data for each domain). Our experiments showed that a smaller dataset is sufficient and more data does not help. It also requires less computing power.

[8] https://pubmed.ncbi.nlm.nih.gov/

[9] Our results are different from those presented in Table 5 of (Gururangan et al., 2020) because we observe very high variances due to very small test sets and thus enlarge the test set and reduce the training set slightly.

[10] https://alt.qcri.org/semeval2014/task4/

[11] We do not include other parameter-efficient methods, e.g. LoRA (Hu et al., 2022) because adapter is the most effective and representative. We also do not include different fine-tuning methods, e.g., AdapterFusion (Pfeiffer et al., 2020) because we focus on the post-training stage.

Category	Domain	Restaurant		ACL		AI		Phone		PubMed	Camera		Average		Forget R.	
	Model	MF1	Acc	MF1	Acc	MF1	Acc	MF1	Acc	MF1	MF1	Acc	MF1	Acc	MF1	Acc
	Pool	80.96	87.80	69.69	74.11	68.55	75.97	84.96	86.95	73.34	86.03	90.83	77.25	81.50	—	
Non-CL	RoBERTa	79.81	87.00	66.11	71.26	60.98	71.85	83.75	86.08	72.38	78.82	87.03	73.64	79.27	—	
	Post (RoBERTa)	80.84	**87.68**	68.75	73.44	68.97	75.95	82.59	85.50	72.84	84.39	89.90	76.40	80.89	—	
	Post (Adapter)	80.19	87.14	68.87	72.92	60.55	71.38	82.71	85.35	71.68	83.62	89.23	74.60	79.62	—	
	Post (Prompt)	79.00	86.45	66.66	71.35	61.47	72.36	84.17	86.53	**73.09**	85.52	90.38	74.98	80.03	—	
CL Post-train	NCL	79.52	86.54	68.39	72.87	67.94	75.71	84.10	86.33	72.49	85.71	90.70	76.36	80.77	1.14	1.05
	NCL (Adapter)	80.13	87.05	67.39	72.30	57.71	69.87	83.32	85.86	72.07	83.70	89.71	74.05	79.48	0.15	-0.02
	DEMIX	79.99	87.12	68.46	72.73	63.35	72.86	78.07	82.42	71.73	86.59	91.12	74.70	79.66	0.74	0.36
	BCL	78.97	86.52	**70.71**	**74.58**	66.26	74.55	81.70	84.63	71.99	85.06	90.51	75.78	80.46	-0.06	-0.19
	CLASSIC	79.89	87.05	67.30	72.11	59.84	71.08	84.02	86.22	69.83	86.93	91.25	74.63	79.59	0.44	0.25
	KD	78.05	85.59	69.17	73.73	67.49	75.09	82.12	84.99	72.28	81.91	88.69	75.17	80.06	-0.07	0.01
	EWC	**80.98**	87.64	65.94	71.17	65.04	73.58	82.32	85.13	71.43	83.35	89.14	74.84	79.68	0.02	-0.01
	DER++	79.00	86.46	67.20	72.16	63.96	73.54	83.22	85.61	72.58	87.10	91.47	75.51	80.30	2.36	1.53
	HAT	76.42	85.16	60.70	68.79	47.37	65.69	72.33	79.13	69.97	74.04	85.14	66.80	75.65	-0.13	-0.29
	HAT-All	74.94	83.93	52.08	63.94	34.16	56.07	64.71	74.43	68.14	65.54	81.44	59.93	71.33	3.23	1.83
	HAT (Adapter)	79.29	86.70	68.25	72.87	64.84	73.67	81.44	84.56	71.61	82.37	89.27	74.63	79.78	-0.23	-0.18
	CPS	80.34	87.16	69.36	74.01	**70.93**	**77.46**	**85.99**	**87.70**	72.80	**88.16**	**92.30**	**77.93**	**81.91**	**-1.09**	**-0.60**

Table 2: End-task macro-F1 (MF1), accuracy and forgetting rate results for all domains *after the continual post-training of all domains*, except for CHEMPORT in the PubMed domain, for which we use micro-F1 following (Gururangan et al., 2020; Dery et al., 2021; Beltagy et al., 2019). The results are averages of 5 random seeds (the domain training order is as they appear in the first row). Due to space limits, the results for *different domain orders* and the *standard deviations* are reported in Appendix D and Appendix E, respectively). Non-CL baselines have no forgetting.

Category	Domain	Restaurant		ACL		AI		Phone		PubMed	Camera		Average		Forget R.	
	Model	MF1	Acc	MF1	Acc	MF1	Acc	MF1	Acc	MF1	MF1	Acc	MF1	Acc	MF1	Acc
Non-CL	RoBERTa	79.81	87.00	66.11	71.26	60.98	71.85	83.75	86.08	72.38	78.82	87.03	73.64	79.27	—	
	Post (RoBERTa)	80.84	**87.68**	68.75	73.44	68.97	75.95	82.59	85.50	72.84	84.39	89.90	76.40	80.89	—	
	Post (Adapter)	80.19	87.14	68.87	72.92	60.55	71.38	82.71	85.35	71.68	83.62	89.23	74.60	79.62	—	
	Post (Prompt)	79.00	86.45	66.66	71.35	61.47	72.36	84.17	86.53	**73.09**	85.52	90.38	74.98	80.03		
CL Post-train	CPS (random)	79.79	86.84	68.34	73.02	68.62	76.17	84.92	87.02	72.73	85.92	91.15	76.72	81.15	0.45	0.26
	CPS (w/o contrast)	81.06	87.55	**70.39**	**74.39**	67.60	75.32	83.53	86.00	72.01	84.48	90.06	76.51	80.89	-0.54	-0.23
	CPS (w/o softmask)	80.48	87.27	69.92	74.39	67.73	75.73	84.00	86.37	73.03	87.96	92.08	77.19	81.48	-0.25	-0.12
	CPS (w/o initialization)	**81.30**	87.79	68.35	73.10	67.82	75.73	85.13	86.98	71.82	87.25	91.57	76.95	81.16	0.70	0.48
	CPS (domain-specific)	80.95	**87.68**	69.18	73.21	68.92	76.27	83.89	86.26	72.46	86.74	91.53	77.02	81.23	-0.07	0.08
	CPS	80.34	87.16	69.36	74.01	**70.93**	**77.46**	**85.99**	**87.70**	72.80	**88.16**	**92.30**	**77.93**	**81.91**	**-1.09**	**-0.60**

Table 3: Ablation results - averages of 5 random seeds. See *standard deviations* in Appendix E.

the largest memory we can use for the system to run. **(14) HAT** (Serrà et al., 2018) is an effective *parameter-isolation* method. HAT is applied to Transformer layers (i.e., self-attention, intermediate and output layers). **(15) HAT-All** is a HAT variant using the same post-training, but all features *from the LM* are used to do end-tasks (instead of only features from its domain sub-network as in HAT). **(16) HAT (Adapter)** (Ke et al., 2021b) uses HAT within adapters. ELLE (Qin et al., 2022a) is not included as we tried to adapt it for our purpose by learning from RoBERTa, but it fails to converge.

4.2 RESULTS ANALYSIS AND ABLATION STUDY

Due to space limits, ***Implementation Details*** are given in Appendix A. Table 2 reports the end-task fine-tuning results of all 15 systems on the 6 datasets. We can see that the proposed CPS outperforms all baselines on average and also achieve the best knowledge transfer (negative forgetting rate).

(1) CPS is slightly better than Pool on average. This may be because (a) some domains are quite different (e.g. camera reviews and ACL papers), which results in some negative transfer in Pool. (b) CPS can learn with the general and previous domain knowledge protected by soft-masks.

(2). CPS achieves both forgetting prevention and knowledge transfer. Those baselines (KD, EWC, DER++) focusing only on forgetting prevention give poorer performance as they sacrifice accuracy to avoid CF. Those baselines (BCL, CLASSIC and DEMIX) perform knowledge transfer achieve better results but still poorer than CPS. DEMIX has very weak transfer. BCL, which can avoid CF while also achieving some transfer, is weaker than NCL. In general, CL baselines are all poorer than CPS as they don't have methods to encourage knowledge transfer or they have to rely on adapters.

(3). Directly learning the domains within the LM helps CPS achieve better results than adapter and prompt based methods. CPS is better than adapter-based systems (Post(Adapter), NCL (Adapter) and HAT (Adapter)) and prompt-based system (Post(Prompt)). This is because adapters and prompts do not have sufficient trainable parameters, which are also randomly initialized and can be hard to train.

(4). Using the full LM to learn all tasks rather than using sub-networks (of HAT-based methods) makes CPS more effective. HAT performs poorly, indicating that it is unsuitable for post-training as discussed in Sec. 1. Even if we use all features (not only the feature from the corresponding

sub-network), we still get poor results (HAT-All) because the features used in post-training (in an LM sub-network) are different from features used in end-task fine-tuning (features from the whole LM).

Knowledge transfer and forgetting avoidance. To see how the models fare on CF and knowledge transfer, we compare the forgetting rates (**forget R.**) (Liu et al., 2020), $\frac{1}{t-1} \sum_{k=1}^{t-1} A_{k,k} - A_{t,k}$, where $A_{k,k}$ is the end-task accuracy right after its domain k is post-trained, and $A_{t,k}$ is the accuracy of the end-task of domain k after post-training the last domain t. We average over all end-tasks except the last as the last domain has no forgetting. The higher the forgetting rate is, the more forgetting it has. Negative rates indicate positive knowledge transfer. Clearly, CPS has the strongest negative forgetting rate, indicating it does well on both forgetting prevention and knowledge transfer. NCL, NCL (Adapter), DEMIX, EWC, KD and DER++ all suffer from some forgetting. HAT has no forgetting but it cannot learn well. HAT and BCL have no forgetting but are weak in transfer.

Effectiveness of the proxy KL-divergence loss. We use proxy KL-divergence loss in the *initialization* function (Sec. 3.1) to compute the importance of units for general knowledge. We are interested in how good the proxy is. Since we don't have the data that pre-trains RoBERTa, it is not obvious how to assess the quality of the proxy directly. Here, we provide some indirect evidences to show the effectiveness of the proxy for computing the importance of units to the general knowledge in the LM.

We conduct a separate experiment (none CL) to compare the attention heads' [12] importance score vectors after applying the proxy using the data from different domains. For each domain i, we compare its importance vector with the importance vector of every other domain, and then average the cosine similarities to get the value for domain i. We get 0.92 for Restaurant, the same 0.91 for ACL, AI, and Phone, 0.89 for PubMed and 0.92 for Camera. We see that different domains give similar importance values, indirectly showing that our proxy can identify the common general knowledge.

We also compute the importance score distributions of the proxy. For each of the 6 domains, after applying the proxy, around 20% of the attention heads are heavily protected ($0.8 \leq I_{l,i}^{\text{gen}} \leq 1.0$) and another 20% moderately protected ($0.6 \leq I_{l,i}^{\text{gen}} < 0.8$), which indicate the general knowledge. While Phone, AI, Camera and Restaurant share a similar distribution, ACL and PubMed protect slightly less. This is understandable as PubMed and ACL (medical or NLP publications) are probably less common than the other domains and the general knowledge in the LM covers them less.

Ablation. We want to know if the proposed (1) initialization (Sec. 3.1), (2) soft-masking, and (3) contrastive learning are helpful. To answer (1), we conduct the ablation **CPS (w/o initialization)**, where we remove the initialization and directly do the continual learning given no consideration to the general knowledge in the LM. To answer (2), we conduct the ablations (1) **CPS (w/o softmask)**, where we remove the soft-masks, and only use contrastive learning based on Eq. 11 (with the second term in the denominator removed); and (2) **CPS (random)** with randomly generated importance scores to do soft-masking and contrastive learning. To answer (3), we conduct two ablations: **(i) CPS (w/o contrast)** where we remove the contrastive loss and only soft-mask according to the importance; **(ii) CPS (domain-specific)** where we contrast domain-specific and learned knowledge (Sec. 3.2). Table 3 shows that the full CPS is the best on average and for most domains, indicating that every component contributes. Additional observations are: (1) CPS's gain is partially from the preserved general knowledge. We can see CPS (w/o initialization) is poorer on average; (2) Soft-masking helps as CPS (w/o softmask) is poorer than CPS. This is reasonable because soft masking can preserve learned domains. Besides, our gradient-based mask is informative as CPS (random) is worse than CPS; (3) Contrastive learning is effective as CPS (w/o contrast) and CPS (domain-specific) are both poorer, indicating the contrastive learning in CPS can help learn good representations

5 CONCLUSION

This paper proposed a novel method for the continual post-training of an LM. It has two key ideas: (1) Preserving the important previous knowledge by soft-masking units according to their importance to overcome CF and to facilitate knowledge transfer. (2) Learning complementary representations for knowledge integration. A set of techniques is proposed to achieve them. Extensive experiments showed the effectiveness of the proposed method. The current proposed approach involves two functions in learning. We will study how to combine them to further improve the results in the future.

---

[12] We use attention heads instead of other units because they are arguably the most important component in a Transformer (Michel et al., 2019; Voita et al., 2019; McCarley et al., 2019).

REFERENCES

Iz Beltagy, Kyle Lo, and Arman Cohan. SciBERT: A pretrained language model for scientific text. In *EMNLP-IJCNLP*, 2019.

Christopher Brix, Parnia Bahar, and Hermann Ney. Successfully applying the stabilized lottery ticket hypothesis to the transformer architecture. In *ACL*, July 2020.

Pietro Buzzega, Matteo Boschini, Angelo Porrello, Davide Abati, and Simone Calderara. Dark experience for general continual learning: a strong, simple baseline. *arXiv preprint arXiv:2004.07211*, 2020.

Tianlong Chen, Jonathan Frankle, Shiyu Chang, Sijia Liu, Yang Zhang, Zhangyang Wang, and Michael Carbin. The lottery ticket hypothesis for pre-trained bert networks. *Advances in neural information processing systems*, 33:15834–15846, 2020a.

Ting Chen, Simon Kornblith, Mohammad Norouzi, and Geoffrey Hinton. A simple framework for contrastive learning of visual representations. In *International conference on machine learning*, pp. 1597–1607. PMLR, 2020b.

Yung-Sung Chuang, Shang-Yu Su, and Yun-Nung Chen. Lifelong language knowledge distillation. *arXiv preprint arXiv:2010.02123*, 2020.

Lucio M Dery, Paul Michel, Ameet Talwalkar, and Graham Neubig. Should we be pre-training? an argument for end-task aware training as an alternative. *arXiv preprint arXiv:2109.07437*, 2021.

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. BERT: pre-training of deep bidirectional transformers for language understanding. In Jill Burstein, Christy Doran, and Thamar Solorio (eds.), *NAACL-HLT*, 2019.

Xiaowen Ding, Bing Liu, and Philip S Yu. A holistic lexicon-based approach to opinion mining. In *Proceedings of the 2008 international conference on web search and data mining*, 2008.

Tianyu Gao, Xingcheng Yao, and Danqi Chen. Simcse: Simple contrastive learning of sentence embeddings. *arXiv preprint arXiv:2104.08821*, 2021a.

Yang Gao, Nicolo Colombo, and Wei Wang. Adapting by pruning: A case study on bert. *arXiv preprint arXiv:2105.03343*, 2021b.

Aidan N Gomez, Ivan Zhang, Siddhartha Rao Kamalakara, Divyam Madaan, Kevin Swersky, Yarin Gal, and Geoffrey E Hinton. Learning sparse networks using targeted dropout. *arXiv preprint arXiv:1905.13678*, 2019.

Claudio Greco, Barbara Plank, Raquel Fernández, and Raffaella Bernardi. Psycholinguistics meets continual learning: Measuring catastrophic forgetting in visual question answering. *arXiv preprint arXiv:1906.04229*, 2019.

Yiwen Guo, Anbang Yao, and Yurong Chen. Dynamic network surgery for efficient dnns. *NIPS*, 29, 2016.

Pankaj Gupta, Yatin Chaudhary, Thomas Runkler, and Hinrich Schuetze. Neural topic modeling with continual lifelong learning. In *International Conference on Machine Learning*, pp. 3907–3917. PMLR, 2020.

Suchin Gururangan, Ana Marasovic, Swabha Swayamdipta, Kyle Lo, Iz Beltagy, Doug Downey, and Noah A. Smith. Don't stop pretraining: Adapt language models to domains and tasks. In *ACL*, 2020.

Suchin Gururangan, Mike Lewis, Ari Holtzman, Noah A Smith, and Luke Zettlemoyer. Demix layers: Disentangling domains for modular language modeling. *arXiv preprint arXiv:2108.05036*, 2021.

Song Han, Jeff Pool, John Tran, and William Dally. Learning both weights and connections for efficient neural network. *Advances in neural information processing systems*, 28, 2015.

Kaiming He, Haoqi Fan, Yuxin Wu, Saining Xie, and Ross Girshick. Momentum contrast for unsupervised visual representation learning. In *CVPR*, pp. 9729–9738, 2020.

Xu He and Herbert Jaeger. Overcoming catastrophic interference using conceptor-aided backpropagation. In *ICLR*, 2018.

Geoffrey Hinton, Oriol Vinyals, Jeff Dean, et al. Distilling the knowledge in a neural network. *arXiv preprint arXiv:1503.02531*, 2(7), 2015.

Neil Houlsby, Andrei Giurgiu, Stanislaw Jastrzebski, Bruna Morrone, Quentin de Laroussilhe, Andrea Gesmundo, Mona Attariyan, and Sylvain Gelly. Parameter-efficient transfer learning for NLP. In Kamalika Chaudhuri and Ruslan Salakhutdinov (eds.), *ICML*, 2019.

Edward J Hu, yelong shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Lu Wang, and Weizhu Chen. LoRA: Low-rank adaptation of large language models. In *International Conference on Learning Representations*, 2022. URL https://openreview.net/forum?id=nZeVKeeFYf9.

Minqing Hu and Bing Liu. Mining and summarizing customer reviews. In *Proceedings of ACM SIGKDD*, 2004.

Yufan Huang, Yanzhe Zhang, Jiaao Chen, Xuezhi Wang, and Diyi Yang. Continual learning for text classification with information disentanglement based regularization. *arXiv preprint arXiv:2104.05489*, 2021.

Joel Jang, Seonghyeon Ye, Sohee Yang, Joongbo Shin, Janghoon Han, Gyeonghun Kim, Stanley Jungkyu Choi, and Minjoon Seo. Towards continual knowledge learning of language models, 2021.

Xisen Jin, Dejiao Zhang, Henghui Zhu, Wei Xiao, Shang-Wen Li, Xiaokai Wei, Andrew Arnold, and Xiang Ren. Lifelong pretraining: Continually adapting language models to emerging corpora. *arXiv preprint arXiv:2110.08534*, 2021.

David Jurgens, Srijan Kumar, Raine Hoover, Daniel A. McFarland, and Dan Jurafsky. Measuring the evolution of a scientific field through citation frames. *TACL*, 2018.

Zixuan Ke, Bing Liu, Hu Xu, and Lei Shu. Classic: Continual and contrastive learning of aspect sentiment classification tasks. In *EMNLP*, 2021a.

Zixuan Ke, Hu Xu, and Bing Liu. Adapting bert for continual learning of a sequence of aspect sentiment classification tasks. In *NAACL*, pp. 4746–4755, 2021b.

James Kirkpatrick, Razvan Pascanu, Neil C. Rabinowitz, Joel Veness, Guillaume Desjardins, Andrei A. Rusu, Kieran Milan, John Quan, Tiago Ramalho, Agnieszka Grabska-Barwinska, Demis Hassabis, Claudia Clopath, Dharshan Kumaran, and Raia Hadsell. Overcoming catastrophic forgetting in neural networks. *CoRR*, 2016.

Jens Kringelum, Sonny Kim Kjaerulff, Søren Brunak, Ole Lund, Tudor I Oprea, and Olivier Taboureau. Chemprot-3.0: a global chemical biology diseases mapping. *Database*, 2016, 2016.

Cheng-I Jeff Lai, Yang Zhang, Alexander H Liu, Shiyu Chang, Yi-Lun Liao, Yung-Sung Chuang, Kaizhi Qian, Sameer Khurana, David Cox, and Jim Glass. Parp: Prune, adjust and re-prune for self-supervised speech recognition. *NeurIPS*, 34, 2021.

Matthias De Lange, Rahaf Aljundi, Marc Masana, and Tinne Tuytelaars. Continual learning: A comparative study on how to defy forgetting in classification tasks. *CoRR*, 2019.

Brian Lester, Rami Al-Rfou, and Noah Constant. The power of scale for parameter-efficient prompt tuning. In Marie-Francine Moens, Xuanjing Huang, Lucia Specia, and Scott Wen-tau Yih (eds.), *EMNLP*, 2021.

Jiaoda Li, Ryan Cotterell, and Mrinmaya Sachan. Differentiable subset pruning of transformer heads. *Transactions of the Association for Computational Linguistics*, 9:1442–1459, 2021.

Yuanpeng Li, Liang Zhao, Kenneth Church, and Mohamed Elhoseiny. Compositional language continual learning. In *International Conference on Learning Representations*, 2019.

Zi Lin, Jeremiah Zhe Liu, Zi Yang, Nan Hua, and Dan Roth. Pruning redundant mappings in transformer models via spectral-normalized identity prior. *arXiv preprint arXiv:2010.01791*, 2020.

Yaoyao Liu, Yuting Su, An-An Liu, Bernt Schiele, and Qianru Sun. Mnemonics training: Multi-class incremental learning without forgetting. In *CVPR*, 2020.

Yinhan Liu, Myle Ott, Naman Goyal, Jingfei Du, Mandar Joshi, Danqi Chen, Omer Levy, Mike Lewis, Luke Zettlemoyer, and Veselin Stoyanov. Roberta: A robustly optimized BERT pretraining approach. *CoRR*, 2019.

Kyle Lo, Lucy Lu Wang, Mark Neumann, Rodney Kinney, and Daniel S. Weld. S2ORC: the semantic scholar open research corpus. In Dan Jurafsky, Joyce Chai, Natalie Schluter, and Joel R. Tetreault (eds.), *ACL*, 2020.

Yi Luan, Luheng He, Mari Ostendorf, and Hannaneh Hajishirzi. Multi-task identification of entities, relations, and coreference for scientific knowledge graph construction. In Ellen Riloff, David Chiang, Julia Hockenmaier, and Jun'ichi Tsujii (eds.), *ACL*, 2018.

Andrea Madotto, Zhaojiang Lin, Zhenpeng Zhou, Seungwhan Moon, Paul Crook, Bing Liu, Zhou Yu, Eunjoon Cho, and Zhiguang Wang. Continual learning in task-oriented dialogue systems. *arXiv preprint arXiv:2012.15504*, 2020.

JS McCarley, Rishav Chakravarti, and Avirup Sil. Structured pruning of a bert-based question answering model. *arXiv preprint arXiv:1910.06360*, 2019.

Paul Michel, Omer Levy, and Graham Neubig. Are sixteen heads really better than one? *Advances in neural information processing systems*, 32, 2019.

Jianmo Ni, Jiacheng Li, and Julian J. McAuley. Justifying recommendations using distantly-labeled reviews and fine-grained aspects. In Kentaro Inui, Jing Jiang, Vincent Ng, and Xiaojun Wan (eds.), *EMNLP*, pp. 188–197. Association for Computational Linguistics, 2019.

Jonas Pfeiffer, Aishwarya Kamath, Andreas Rücklé, Kyunghyun Cho, and Iryna Gurevych. Adapter-fusion: Non-destructive task composition for transfer learning. In *EACL*, 2020.

Yujia Qin, Jiajie Zhang, Yankai Lin, Zhiyuan Liu, Peng Li, Maosong Sun, and Jie Zhou. ELLE: efficient lifelong pre-training for emerging data. In Smaranda Muresan, Preslav Nakov, and Aline Villavicencio (eds.), *Findings of the Association for Computational Linguistics: ACL 2022, Dublin, Ireland, May 22-27, 2022*, pp. 2789–2810. Association for Computational Linguistics, 2022a. URL https://aclanthology.org/2022.findings-acl.220.

Yujia Qin, Jiajie Zhang, Yankai Lin, Zhiyuan Liu, Peng Li, Maosong Sun, and Jie Zhou. Elle: Efficient lifelong pre-training for emerging data. *arXiv preprint arXiv:2203.06311*, 2022b.

Sylvestre-Alvise Rebuffi, Alexander Kolesnikov, Georg Sperl, and Christoph H. Lampert. icarl: Incremental classifier and representation learning. In *CVPR*, 2017.

Ari Seff, Alex Beatson, Daniel Suo, and Han Liu. Continual learning in generative adversarial nets. *CoRR*, abs/1705.08395, 2017.

Joan Serrà, Didac Suris, Marius Miron, and Alexandros Karatzoglou. Overcoming catastrophic forgetting with hard attention to the task. In *ICML*, 2018.

Yilin Shen, Xiangyu Zeng, and Hongxia Jin. A progressive model to enable continual learning for semantic slot filling. In *EMNLP-IJCNLP*, November 2019.

Hanul Shin, Jung Kwon Lee, Jaehong Kim, and Jiwon Kim. Continual learning with deep generative replay. In *NIPS*, 2017.

Lei Shu, Hu Xu, and Bing Liu. Lifelong learning CRF for supervised aspect extraction. In *ACL*, 2017.

Chi Sun, Xipeng Qiu, Yige Xu, and Xuanjing Huang. How to fine-tune bert for text classification? In *China national conference on Chinese computational linguistics*, pp. 194–206. Springer, 2019.

Fan-Keng Sun, Cheng-Hao Ho, and Hung-Yi Lee. Lamol: Language modeling is all you need for lifelong language learning. In *ICLR*, 2020. URL `https://openreview.net/forum?id=Skgxcn4YDS`.

Elena Voita, David Talbot, Fedor Moiseev, Rico Sennrich, and Ivan Titov. Analyzing multi-head self-attention: Specialized heads do the heavy lifting, the rest can be pruned. *arXiv preprint arXiv:1905.09418*, 2019.

Zirui Wang, Sanket Vaibhav Mehta, Barnabás Póczos, and Jaime Carbonell. Efficient meta lifelong-learning with limited memory. In *EMNLP*, 2020.

Mitchell Wortsman, Vivek Ramanujan, Rosanne Liu, Aniruddha Kembhavi, Mohammad Rastegari, Jason Yosinski, and Ali Farhadi. Supermasks in superposition. In H. Larochelle, M. Ranzato, R. Hadsell, M. F. Balcan, and H. Lin (eds.), *NeurIPS*, 2020.

Hu Xu, Bing Liu, Lei Shu, and Philip S. Yu. BERT post-training for review reading comprehension and aspect-based sentiment analysis. In Jill Burstein, Christy Doran, and Thamar Solorio (eds.), *NAACL-HLT*, 2019.

Random Sequence Order	NCL		KD		CPS	
	MF1	Acc	MF1	Acc	MF1	Acc
Restaurant → ACL → AI → Phone → PubMed → Camera	76.36	80.77	75.17	80.06	**77.93**	**81.91**
Phone → AI → PubMed → Camera → Restaurant → ACL	76.06	80.69	75.49	80.39	76.90	81.10
PubMed → Camera → ACL → Restaurant → AI → Phone	76.49	80.84	75.80	80.51	76.86	81.09
Camera → ACL → Phone → Restaurant → PubMed → AI	76.28	80.83	74.67	79.91	77.52	81.65
AI → PubMed → Camera → Phone → ACL → Restaurant	76.17	80.68	75.32	80.45	**78.18**	**82.10**

Table 4: CPS performance averaged over all domains after the final post-trained (averaged over 5 random seeds).

A IMPLEMENTATION DETAILS

Architecture. We adopt RoBERTa$_{\text{BASE}}$ as our backbone LM. A masked language model head is applied for post-training. The end-task fine-tuning of RoBERTa follows the standard practice. For the three ASC tasks (see Table 1), we adopt the ASC formulation in Xu et al. (2019), where the aspect (e.g., "*sound*") and review sentence (e.g., "*The sound is great*") are concatenated via .

Hyperparameters. Unless otherwise stated, the same hyper-parameters are used in all experiments. The maximum input length is set to 164 which is sufficient for all datasets. Adam optimizer is used for both post-training and end-task fine-tuning. The max sequence length is also set to 164.

Post-training. The learning rate is set to 1e-4 and batch size to 256. We train 2.5K steps for each domain, roughly a full pass through the domain data, following Gururangan et al. (2020); Xu et al. (2019). The subset of data $\{x_m^{\text{sub}}\}$ for computing $\mathcal{L}^{\text{impt}}$ to determine head importance in Secs. 3.1 and 3.3 is set to 1.64 Million tokens, which is sufficient in our experiments. λ in Eq. 12 is set to 1 and τ in Eq. 11 is set to 0.05.

End-task fine-tuning. The learning rate is set to 1e-5 and batch size to 16. We train on end-task fine-tuning datasets for 5 epochs for Restaurant; 10 epochs for ACL, AI and PubMed; and 15 epochs for Phone and Camera. We simply take the results for the last epoch, assuming no validation sets. We empirically found that the above number of epochs gives us stable and convergence results.

B DATASETS DETAILS

Table 1 in the main paper has already showed the number of examples in each dataset. Here we provide additional details about the 4 types of end-tasks.

(1) **(Phone, Camera and Restaurant) Aspect Sentiment Classification (ASC)** is defined as follows: given an aspect or product feature (e.g., *picture quality* in a camera review) and a review sentence containing the aspect in a domain or product category (e.g., camera), classify if the sentence expresses a positive, negative, or neutral (no opinion) sentiment or polarity about the aspect (for the Phone and Camera datasets, there are only negative and positive polarities in the data).

(2) **(ACL) Citation intent classification** is defined as follows: given a citing sentence (a sentence contains a citation), classify if the sentence expresses a citation function among "background", "motivation", "uses", "extension" and "comparison or contrast future".

(3) **(AI) Relation classification** is defined as follows: given a within-sentence word sequence span containing a pair of entities, classify if the span expresses a relation among "feature of", "conjunction", "evaluate for", "hyponym of", "used for", "part of" and "compare".

(4) **(PubMed) Chemical-protein interaction classification** is defined as follows: given a span containing a pair of chemical and protein, classify if the span expresses a chemical-protein interaction among "downregulator", "substrate", "indirect-upregulator", "indirect-downregulator", "agnonist", "activator", "product of", "agonist-activator", "inhibitor", "upregulator", "substrate product of", "agonist-inhibitor"and "antagonist".

Category	Domain Model	Restaurant MF1	Acc	ACL MF1	Acc	AI MF1	Acc	Phone MF1	Acc	PubMed MF1	Camera MF1	Acc	Average MF1	Acc
Non-CL	Pool	±0.0070	±0.0032	±0.0177	± 0.0103	±0.0137	±0.0087	±0.0190	±0.0142	±0.0088	±0.0345	±0.0209	±0.0127	±0.0085
	RoBERTa	±0.0117	±0.0049	±0.0192	±0.0096	±0.0646	±0.0347	±0.0210	±0.0154	±0.0071	±0.0403	±0.0179	±0.0119	±0.0070
	Post (RoBERTa)	±0.0096	±0.0056	±0.0218	±0.0118	±0.0117	±0.0086	±0.0165	±0.0103	±0.0035	±0.0479	±0.0298	±0.0118	±0.0075
	Post (Adapter)	±0.0102	±0.0068	±0.0142	±0.0099	±0.0551	±0.0288	±0.0265	±0.0181	±0.0055	±0.0165	±0.0110	±0.0132	±0.0087
	Post (Prompt)	±0.0060	±0.0035	±0.0068	±0.0108	±0.0301	±0.0124	±0.0126	±0.0087	±0.0028	±0.0243	±0.0138	±0.0049	±0.0019
CL Post-train	NCL	±0.0064	±0.0035	±0.0168	±0.0084	±0.0164	±0.0099	±0.0126	±0.0104	±0.0073	±0.0449	±0.0247	±0.0116	±0.0073
	NCL (Adapter)	±0.0090	±0.0060	±0.0063	±0.0065	±0.0835	±0.0405	±0.0196	±0.0124	±0.0086	±0.0312	±0.0152	±0.0117	±0.0058
	DEMIX	±0.0065	±0.0029	±0.0118	±0.0094	±0.0376	±0.0218	±0.0731	±0.0428	±0.0069	±0.0099	±0.0071	±0.0121	±0.0064
	BCL	±0.0106	±0.0059	±0.0050	±0.0054	±0.0433	±0.0229	±0.0191	±0.0130	±0.0069	±0.0290	±0.0164	±0.0097	±0.0055
	CLAASSIC	±0.0071	±0.0039	±0.0337	±0.0171	±0.0227	±0.0084	±0.0187	±0.0124	±0.0085	±0.0140	±0.0094	±0.0114	±0.0065
	KD	±0.0352	±0.0197	±0.0096	±0.0107	±0.0164	±0.0088	±0.0149	±0.0115	±0.0075	±0.0277	±0.0128	±0.0072	±0.0042
	EWC	±0.0161	±0.0085	±0.0136	±0.0076	±0.0178	±0.0089	±0.0205	±0.0140	±0.0069	±0.0725	±0.0424	±0.0172	±0.0098
	DER++	±0.0081	±0.0042	±0.0156	±0.0089	±0.0355	±0.0160	±0.0402	±0.0272	±0.0090	±0.0367	±0.0215	±0.0158	±0.0088
	HAT	±0.0182	±0.0091	±0.0271	±0.0206	±0.0369	±0.0126	±0.0834	±0.0474	±0.0038	±0.1082	±0.0408	±0.0323	±0.0155
	HAT-All	±0.0257	±0.0140	±0.0643	±0.0273	±0.1355	±0.0991	±0.0428	±0.0217	±0.0125	±0.0526	±0.0163	±0.0175	±0.0145
	HAT (Adapter)	±0.0093	±0.0061	±0.0048	±0.0053	±0.0289	±0.0168	±0.0277	±0.0195	±0.0037	±0.0760	±0.0370	±0.0129	±0.0074
	CPS	±0.0090	±0.0063	±0.0186	±0.0103	±0.0142	±0.0086	±0.0160	±0.0135	±0.0067	±0.0289	±0.0154	±0.0099	±0.0060

Table 5: Standard deviations of the corresponding metrics of the proposed CPS model and the baselines

Category	Domain Model	Restaurant MF1	Acc	ACL MF1	Acc	AI MF1	Acc	Phone MF1	Acc	PubMed MF1	Camera MF1	Acc	Average MF1	Acc
Non-CL	RoBERTa	±0.0117	±0.0049	±0.0192	±0.0096	±0.0646	±0.0347	±0.0210	±0.0154	±0.0071	±0.0403	±0.0179	±0.0119	±0.0070
	Post (RoBERTa)	±0.0096	±0.0056	±0.0218	±0.0118	±0.0117	±0.0086	±0.0165	±0.0103	±0.0035	±0.0479	±0.0298	±0.0118	±0.0075
	Post (Adapter)	±0.0102	±0.0068	±0.0142	±0.0099	±0.0551	±0.0288	±0.0265	±0.0181	±0.0055	±0.0165	±0.0110	±0.0132	±0.0087
	Post (Prompt)	±0.0060	±0.0035	±0.0068	±0.0108	±0.0301	±0.0124	±0.0126	±0.0087	±0.0028	±0.0243	±0.0138	±0.0049	±0.0019
CL Post-train	CPS (random)	±0.0074	±0.0055	±0.0110	±0.0102	±0.0201	±0.0112	±0.0184	±0.0128	±0.0042	±0.0483	±0.0247	±0.0119	±0.0067
	CPS (w/o contrast)	±0.0104	±0.0055	±0.0090	±0.0063	±0.0205	±0.0124	±0.0321	±0.0216	±0.0037	±0.0527	±0.0286	±0.0119	±0.0073
	CPS (w/o softmask)	±0.0064	±0.0046	±0.0121	±0.0088	±0.0193	±0.0113	±0.0245	±0.0175	±0.0096	±0.0322	±0.0183	±0.0104	±0.0059
	CPS (w/o initialization)	±0.0124	±0.0075	±0.0054	±0.0048	±0.0134	±0.0078	±0.0135	±0.0104	±0.0118	±0.0460	±0.0261	±0.0093	±0.0058
	CPS (domain-specific)	±0.0067	±0.0045	±0.0151	±0.0127	±0.0192	±0.0129	±0.0277	±0.0182	±0.0061	±0.0419	±0.0226	±0.0120	±0.0077
	CPS	±0.0090	±0.0063	±0.0186	±0.0103	±0.0142	±0.0086	±0.0160	±0.0135	±0.0067	±0.0289	±0.0154	±0.0099	±0.0060

Table 6: Standard deviations of the corresponding metrics of the proposed CPS model and the ablation

C BASELINE DETAILS

Non-Continual Learning Baselines: Each of these baselines builds a separate model for each task independently. It thus has no knowledge transfer or CF.

(1) **Non-post-training (RoBERTa)** Liu et al. (2019) uses the original RoBERTa for the end-task fine-tuning without any post-training. This is the only one without any post-training. All the following baselines use the masked language model loss (MLM) for post-training.

(2) **Post-training using masked language model loss (Post (RoBERTa))** is the existing post-training method in Gururangan et al. (2020). To our knowledge, the existing post-training systems are all based on the MLM loss.

(3) **Post-training using adapter-tuning** Madotto et al. (2020); Houlsby et al. (2019) adds small adapter layers between layers of Transformer for post-training. We follow the adapter design in Madotto et al. (2020); Houlsby et al. (2019): An adapter is simply a 2 layers of fully connected network. During post-training, the Transformer is fixed, only the added adapters are trainable. The bottleneck size (adapter size) is set to 128. During end-task fine-tuning, both RoBERTa and the adapters are trainable to ensure fair comparison.

(4) **Post-training using prompt-tuning** Lester et al. (2021) adds a sequence of real vector tokens (called virtual tokens or prompt tokens) to the end of the original sequence. In post-training, RoBERTa (the LM) is fixed and only the prompt tokens are trained. In end-task fine-tuning, both LM and the trained prompt are trainable. We initialize 100 tokens and set the learning rate of the prompt token to 0.3 in post-training, following the setting in Lester et al. (2021).

Continual Learning (CL) Baselines.

(5) **Naive continual learning (NCL)** is a naive extension of Gururangan et al. (2020), which continually/incrementally post-trains the LM to learn all domains using MLM loss with no mechanism to deal with CF.

(6) **Continual learning with adapter (NCL (Adapter))** Houlsby et al. (2019) is similar to the adapter based system. The only difference is that the same set of adapters is shared across all domains, rather than using a new adapter for each new domain.

(7) **DEMIX (DEMIX)** Gururangan et al. (2021) is a recent model to adapt pre-trained LM with new domains. It adds a new adapter once a new domain arrives (network expansion is needed) and initializes the new adapter with the parameters of the previous trained adapter nearest to the new domain data. They use the perplexity on a held-out sample to choose the most probable adapter. For fair comparison, we use the same size as $\{x_m^{sub}\}$ as the held-out samples.

(8) **Hard attention to overcome forgetting (HAT (Adapter))** Ke et al. (2021b) is derived from HAT Serrà et al. (2018), the state-of-the-art parameter-isolation based method with almost no forgetting. However, HAT requires task id information in end-task fine-tuning (CPS works in *domain-agnostic* manner and does not need the task id information; see Sec. 1). HAT also needs to train an addition task embedding to mask each layer of the network which makes the post-training inefficient.

(9) **Continual learning plugin with capsule(BCL)** Ke et al. (2021b) is a continual learning model that can avoid forgetting and encourage knowledge transfer. It is similar to NCL (Adapter). The difference is that its adapters consist of two modules, one is a capsule network (a new capsule is added once a new domain arrives) to encourage transfer and the other one is similar to HAT to avoid forgetting. Similar to HAT, task/domain information is needed in end-task fine-tuning. We replace the backbone network from BERT with RoBERTa for fair comparison.

(10) **Continual learning plugin with contrastive transfer (CLASSIC)** Ke et al. (2021a) is a continual learning model that can avoid forgetting and encourage knowledge transfer via contrasting loss. It is similar to HAT. but 3 additional contrastive loss are used for distillation, knowledge transfer and supervised contrast. Since CPS is working on unsupervised data, we remove the supervised contrastive loss. Similar to HAT, task information is needed in end-task fine-tuning. We replace the backbone network from BERT with RoBERTa for fair comparison.

(11) **Knowledge distillation (KD)** Hinton et al. (2015) minimizes the representational deviation between the learned representation and the new representation in post-training. We compute the KL divergence between the representations (the output before the masked language model prediction head) of each token of the previous post-trained LM and current LM as the distillation loss.

(12) **EWC** Buzzega et al. (2020) is a popular regularization-based method which adopts elastic weights consolidation to add L_2 regularization to parameter changes.

(13) **DER++** Buzzega et al. (2020) is a recent replay method using distillation to regularize the new task training. We store 16.4K tokens for each learned domain as the memory, which is the largest memory we can use for the system to run.

(14) **HAT** Serrà et al. (2018) is used in the Transformer layers (including self-attention, intermediate and output layers) rather than the added adapter layers. Additional task embedding and task information for end-task fine-tuning are needed.

D   POST-TRAINING IN DIFFERENT ORDERS

Table 2 in the main paper reported the results for the order `Restaurant` → `ACL` → `AI` → `Phone` → `PubMed` → `Camera`. We now look at how the order affects the results. Due to the computation intensive nature of post-training, we only report the best baseline (NCL) and CPS results with different domain orders. Table 4 shows NCL and CPS's results of 5 different orders. We can see CPS is always better than NCL, demonstrating the effectiveness of CPS.

E   STANDARD DEVIATIONS

Table 5 reports the standard deviations of the corresponding results in Table 2 (in the main paper) of CPS and the considered baselines over 5 runs with random seeds. We can see the results of CPS are stable. Some baselines (e.g., RoBERTa in AI, Post (RoBERTa) in Camera) can have quite large standard deviations.

Table 6 reports the standard deviations of the corresponding results in Table 3 (in the main paper) of CPS and the considered baselines over 5 runs with random seeds. We can see the results of CPS and its variants are stable.