LEARNING OBJECT-LANGUAGE ALIGNMENTS FOR OPEN-VOCABULARY OBJECT DETECTION

ABSTRACT

Existing object detection methods are bounded in a fixed-set vocabulary by costly labeled data. When dealing with novel categories, the model has to be retrained with more bounding box annotations. Natural language supervision is an attractive alternative for its annotation-free attributes and broader object concepts. However, learning open-vocabulary object detection from language is challenging since image-text pairs do not contain fine-grained object-language alignments. Previous solutions rely on either expensive grounding annotations or distilling classification-oriented vision models. In this paper, we propose a novel open-vocabulary object detection framework directly learning from image-text pair data. We formulate object-language alignment as *a set matching problem* between a set of image region features and a set of word embeddings. It enables us to train an open-vocabulary object detector on image-text pairs in a much simple and effective way. Extensive experiments on two benchmark datasets, COCO and LVIS, demonstrate our superior performance over the competing approaches on novel categories, e.g. achieving 32.0% mAP on COCO and 21.7% mask mAP on LVIS. Code will be released.

1 INTRODUCTION

In the past few years, significant breakthroughs of visual models have been witnessed on close-set recognition, where the object categories are pre-defined by the dataset (Johnson-Roberson et al., 2016; Sakaridis et al., 2018; Geiger et al., 2013; Yu et al., 2018). Such achievements are not the final answer to artificial intelligence, since human intelligence can perceive the world in an open environment. This motivates the community moving towards the open-world setting, where visual recognition models are expected to recognize arbitrary novel categories in a zero-shot manner. Towards this goal, learning visual models from language supervisions becomes more and more popular due to their open attributes, rich semantics, various data sources and nearly-free annotation cost. Particularly, many recent image classification works (Yu et al., 2022; Yuan et al., 2021; Zhai et al., 2021; Jia et al., 2021; Radford et al., 2021; Zhou et al., 2021a; Rao et al., 2021; Huynh et al., 2021) successfully expand their vocabulary sizes by learning from a large set of image-text pairs and demonstrate very impressive zero-shot ability. Following the success in open-vocabulary image classification, a natural extension is to tackle the object detection task, i.e., open-vocabulary object detection (OVOD).

Object detection is a fundamental problem in computer vision aiming to localize object instances in an image and classify their categories (Girshick, 2015; Ren et al., 2015; Lin et al., 2017; He et al., 2017; Cai & Vasconcelos, 2018). Training an ordinary object detector relies on manually-annotated bounding box and category for each object (Fig. 1 Left). Similarly, learning object detection from language supervision requires elaborate object-language annotations. In fact, such annotations have been investigated in visual grounding task (Krishna et al., 2017; Yu et al., 2016; Plummer et al., 2015). Most of the existing open-vocabulary object detection works (Li et al., 2021; Kamath et al., 2021; Cai et al., 2022) depend in whole or in part on the grounding data, which however is not scalable because annotating grounding data is even more costly than annotating object detection data. To reduce the annotation cost for open-vocabulary object detection, a few recent works (Du et al., 2022; Gu et al., 2021) turn to distill the visual region feature from classification-oriented models by cropping images. Their performances are limited by the pre-trained model, which is trained for global image-text matching instead of region-word matching.

Figure 1: Left: conventional object detection. Right: our proposed open-vocabulary object detection, where we focus on using the corpus of image-text pairs to learn region-word alignments for object detection. By converting the image into a set of regions and the caption into a set of words, the region-word alignments can be solved as a *set-matching problem*. In this way, our method is able to directly train the object detector with image-text pairs covering a large variety of object categories.

In this paper, we propose a simple yet effective end-to-end vision-and-language framework for open-vocabulary object detection, termed **VLDet**, which directly trains an object detector from image-text pairs without relying on expensive grounding annotations or distilling classification-oriented vision models. Our key insight is that extracting region-word pairs from image-text pairs can be formulated as *a set matching problem* (Carion et al., 2020; Sun et al., 2021b;a; Fang et al., 2021), which can be effectively solved by finding a bipartite matching (Kuhn, 1955) between regions and words with minimal global matching cost. Specifically, we treat image region features as a set and word embedding as another set with the the dot-product similarity as region-word alignment score. To find the lowest cost, the optimal bipartite matching will force each image region to be aligned with its corresponding word under the global supervision of the image-text pair. By replacing the classification loss in object detection with the optimal region-word alignment loss, our approach can help match each image region to the corresponding word and accomplish the object detection task.

We conduct extensive experiments on open-vocabulary settings, where using the dataset of image-text pairs for unknown novel categories while using object detection dataset with localized object annotations for base categories. The results show that our method significantly improves the novel class detection performance. On open-vocabulary COCO, our method outperforms the SOTA result PB-OVD (Zhou et al., 2022) on the novel classes by 1.2% mAP with COCO Caption data (Chen et al., 2015). On open-vocabulary LVIS, our method surpasses the SOTA method DetPro (Du et al., 2022) on the novel classes by 1.9% mAP^{mask} with CC3M (Sharma et al., 2018) dataset.

The contributions of this paper can be summarized as follows: 1) We introduce an open-vocabulary object detector method to learn object-language alignments directly from image-text pair data. 2) We propose to formulate region-word alignments as a set-matching problem from a global perspective. 3) Extensive experiments on two benchmark datasets, COCO and LVIS, demonstrate our superior performance, particularly on novel-class detection.

2 RELATED WORK

Weakly-Supervised Object Detection (WSOD). WSOD aims to train an object detector using image-level labels as supervision without any bounding box annotation. Multi-instance learning (Dietterich et al., 1997) is a well studied strategy for solving this problem (Bilen et al., 2015; Bilen & Vedaldi, 2016; Cinbis et al., 2016). It learns each category label assignment based on the top-scoring strategy, i.e. assigning the top-scoring proposal to the corresponding image label. As no bounding box supervision in training, OICR (Tang et al., 2017) proposes to refine the instance classifier online using spatial relation, thereby improving the localization quality. Cap2Det (Ye et al., 2019) further utilizes a text classifier to convert captions into image labels. Based on the student-teacher framework, Omni-DETR (Wang et al., 2022) uses different types of weak labels to generate accurate pseudo labels through a bipartite matching as filtering mechanism. Different from WSOD, OVOD benefits from the fully-annotated base class data, resulting in accurate proposals to match with corresponding words for target classes not known in advance. Directly using WSOD methods for OVOD tends to assign a region proposal to the mostly matching class, which is likely to be a base class due to the full supervision for the bass classes.

Multi-Modal Object Detection. A recent line of work considers instance-wise vision-language tasks, where the free-form language from captions is required to align with the objects. GLIP (Li et al., 2021) unifies object detection and visual grounding into a grounded language-image pre-training model. MDETR (Kamath et al., 2021) develops an end-to-end text-modulated detection system derived from DETR (Carion et al., 2020). XDETR (Cai et al., 2022) independently trains the two streams, visual detector and language encoder, and align the region features and word embeddings via dot product operations. All these multi-modal detectors extend their vocabulary fully or partially relying on annotated grounding data, i.e. object-language pairs with ground truth bounding boxes. In contrast, our model directly learns the region-word alignments for the novel classes by bipartite matching from the image-text pairs without bounding box annotations.

Open-Vocabulary Object Detection (OVOD). Recently, there is a trend toward improving the generalization ability of object detectors to new categories via multi-modal knowledge. Open-vocabulary object detection aims to increase the vocabulary of object detection with image-text pairs. As the first work of OVOD, OVR-CNN (Zareian et al., 2021) uses a corpus of image-caption pairs to pretrain a vision-language model and transfers the visual backbone to the supervised object detector. With the huge progress in image-level open vocabulary recognition (Yu et al., 2022; Yuan et al., 2021; Zhai et al., 2021; Jia et al., 2021; Radford et al., 2021), distilling the knowledge from the off-the-shelf vision-language model like CLIP (Radford et al., 2021) has become a popular solution for OVOD tasks (Zhong et al., 2022; Minderer et al., 2022). For instance, Zhong (Zhong et al., 2022) and Gao (Gao et al., 2021) generate the pseudo region annotations from the pre-trained vision-language model and use them as training data for detectors. To get a better localization ability for generating pseudo region annotations, Zhao (Zhong et al., 2022) uses another two-stage detector as a strong region proposal network (RPN). In order to use the CLIP class embedding effectively, DePro (Du et al., 2022) designs a fine-grained automatic prompt learning. Different from these works, we scale up the vocabulary of object detection by using the annotation-free data of image-text pairs. *As it is easy to extract noun words from captions, our object vocabulary is easily to be extended and scaled.* Besides, some work focuses on improving image segmentation in open vocabulary settings. Ghiasi (Ghiasi et al., 2022) organizes pixels into groups first and then learns the alignments between captions and predicted masks. Another close work is Detic (Zhou et al., 2022) that focuses on increasing the performance on novel classes with image classification data by supervising the max-size proposal with all image labels. Unlike Detic, we try to align image regions and caption words by bipartite matching.

3 METHOD

3.1 OVERVIEW

A traditional object detector can be considered as trained with (o_i, g_i), where o_i denote the $i\text{-}th$ object/region/box feature of an input image I, and $g_i = (b_i, c_i)$ denote the corresponding labels with the bounding-box coordinates b_i and their associated categories $c_i \in \mathbb{C}^{base}$, where $\mathbb{C}^{base}$ is the set of base classes, or pre-defined classes. Open-vocabulary Object Detection (OVOD) (Zareian et al., 2021) aims to acquire a large vocabulary of knowledge from a corpus of image-caption pairs to generalize traditional object detection to novel classes. In other words, our goal is to train an object detector, using only base-class bounding box annotations and a corpus of image-caption pairs $\langle I, C \rangle$ with a large vocabulary $\mathbb{C}^{open}$, which can be generalized to detect novel classes $\mathbb{C}^{novel}$ during testing. Note that the vocabulary $\mathbb{C}^{base}$ and $\mathbb{C}^{novel}$ might or might not overlap with $\mathbb{C}^{open}$.

Fig. 2 gives an overview of our proposed VLDet framework. We propose to learn fine-grained region-word alignments with the corpus of image-text pairs, which is formulated as a set-matching problem, i.e., matching a set of object candidates with a set of word candidates. In the following, we first describe how to formulate the learning of region-word alignment from image-text pairs as a bipartite match problem in Section 3.2 and then depict the network architecture followed by some method details in Section 3.3

3.2 LEARNING OBJECT-LANGUAGE ALIGNMENTS BY BIPARTITE MATCHING

Recap on Bipartite Matching. The Bipartite Matching describes the following problem: supposing there are X workers and Y jobs. Each worker has a subset of jobs that he/she is capable to finish. Each job can only accept one worker and each worker can be appointed to only one job. Because each worker has different skills, the cost $d_{x,y}$ required to perform a job y depends on the worker

Figure 2: Overview of our proposed **VLDet** framework. We propose to learn fine-grained region-word alignments with the corpus of image-text pairs, which is formulated as a bipartite matching problem between image regions and word candidates.

x who is assigned to it. The goal is to determine the optimum assignment M^* such that the total cost is minimized or the team effectiveness is maximized. For this purpose, given a matching matrix **M**, if element $m_{i,j} = 1$, it indicates a matching; otherwise, not matching. We can formulate this matching problem as:

$$\min_{\mathbf{M}} \sum_{i=1}^{X} \sum_{j=1}^{Y} d_{i,j} m_{i,j} \tag{1}$$

The constraints is to ensure each job being assigned to one worker if there are more workers; otherwise, ensure each worker being assigned to one job. In our case, the jobs are object regions $\mathbf{r}_i$ from image I and the workers are words $\mathbf{w}_j$ from caption C.

Learning Object-Language Alignments from Image-Text Pairs. Due to the low cost of image-text pairs data, we are motivated to increase the vocabulary of the detector assuming the image-text dataset covers a larger variety of objects. However, object detection requires more fine grained region-word pairs for training. The key challenge is how to find the correspondences between the set of regions and the set of words. Instead of generating pseudo bounding boxes and labels for each image, we propose to formulate the region-word alignment as an optimal bipartite matching problem.

Given an image I, the candidate region features from the image encoder is defined as $\mathbf{R} = [\mathbf{r}_1, \mathbf{r}_2, \ldots, \mathbf{r}_m]$, where m is the number of the regions. Given a caption C, we extract all the nouns from the caption and embed each noun with the language encoder. The word embedding is defined as $\mathbf{W} = [\mathbf{w}_1, \mathbf{w}_2, \ldots, \mathbf{w}_{|\mathbf{W}|}]$, where the $|\mathbf{W}|$ is the number of nouns in the caption. Usually, we have $m > |\mathbf{W}|$, as the region proposal network provides sufficient candidate regions. We define each region as a "job" which tries to find the most suitable "worker" and each word as a "worker" who finds the most confident "job". In this context, our approach converts the region and word assignment task into a set-to-set bipartite matching problem from a global perspective. The cost between image regions and words is defined as the alignment scores $\mathbf{S} = \mathbf{W}\mathbf{R}^\top$. The bipartite matching problem can then be efficiently solved by the off-the-shelf Hungarian Algorithm (Kuhn, 1955). In this way, the classifier head of the detection model is optimized by a binary cross-entropy loss:

$$L_{region-word} = \sum_{i=1}^{|W|} - \left[\log \sigma(s_{ik}) + \sum_{j \in W'} log(1 - \sigma(s_{jk})) \right], \tag{2}$$

where σ is the sigmoid activation, s_{ik} is the alignment score of the i-th word embedding and its corresponding k-th region feature matched by the bipartite matching, and W' is the set of nouns from other captions in the same batch.

Besides, we further consider image-text pairs as special region-word pairs. Particularly, we extract the RoI feature of an image by considering the entire image as a special region and the entire caption feature from the text encoder as a special word. For an image, we consider its caption as a positive sample and other captions in the same minibatch as negative samples. We use a similar binary cross-entropy loss $L_{image-text}$ for image-text pairs as Eq. 2.

Object Vocabulary. The object vocabulary during the training can be the object labels $\{\mathbb{C}^{base}, \mathbb{C}^{novel}\}$ defined in the dataset, as many recent works (Zhou et al., 2022; Gao et al., 2021) do for LVIS and COCO. However, we notice that it is not strictly following the open-vocabulary setting. In our design, we set the object vocabulary as all nouns in the image captions in each training batch. From the perspective of the whole training process, our object vocabulary $\mathbb{C}^{open}$ size is much larger than the dataset label space. Our experiments show that this setting not only realizes the desirable open-vocabulary detection, but also achieves better performance than previous works. More details are discussed in the experiment section.

3.3 NETWORK ARCHITECTURE

Our VLDet network includes three components: a visual object detector, a text encoder, and an alignment between regions and words. We choose the two-stage framework Faster R-CNN (Ren et al., 2015; Cai & Vasconcelos, 2018; Zhou et al., 2021b) as our object detector component. The first stage in the object detector remains the same as Faster R-CNN, predicting object proposals by the region proposal network. To adapt the two-stage object detector into the open-vocabulary setting, we modify the second-stage in two aspects: (1) we use the class-agnostic localization head instead of the class-specific one. In this way, The localization head predicts bounding boxes regardless of their categories. (2) We replace the trainable classifier weights with the language embeddings to convert the detector to the open-vocabulary setting. We use a pretrained language model CLIP (Radford et al., 2021) as our text encoder. Noting that there is no specific design in the object detector architecture, it is easy to replace Faster R-CNN by any other detector like Transformer-based detectors (Carion et al., 2020; Zhu et al., 2020; Meng et al., 2021; Zhang et al., 2022).

Training and Inference. During training, the data is composited by base-class detection data and image-text pairs. For base-class detection data, it is trained in a classical two-stage detection pipeline including classification and localization. For an image-caption pair, the image encoder generates candidate regions by taking the image as input and the text encoder encodes nouns in the caption as word embeddings. After that, the region features and word embeddings are aligned by the bipartite matching. At inference, VLDet adopts inference process of two-stage object detector with the language embedding as classifer.

4 EXPERIMENTS

4.1 DATASETS

COCO and COCO Caption. Following open-vocabulary COCO setting (OV-COCO) (Zareian et al., 2021), the COCO-2017 dataset is manually divided into 48 base classes and 17 novel classes, which are proposed by the zero-shot object detection (Bansal et al., 2018). We keep 107,761 images with base class annotations as the training set and 4,836 images with base and novel class annotations as the validation set. For images-text pairs data, we use COCO Caption (Chen et al., 2015) training set, which contains 5 human-generated captions for each image. Following (Gu et al., 2021; Zareian et al., 2021), we report mean Average Precision (mAP) at an IoU of 0.5.

LVIS and Conceptual Captions. To study a large-scale generalized setting for open-vocabulary object detection, we conduct experiments on the LVIS (Gupta et al., 2019) benchmark with Conceptual Captions (CC3M) (Sharma et al., 2018) as the paired image-text training data. LVIS dataset with object detection and instance segmentation annotations has diverse categories, which is more suitable for the open-vocabulary object detection task. In this setting, we follow ViLD (Gu et al., 2021) with the common classes and frequency classes as base classes (866 categories) and rare classes as novel classes (337 categories). We remove novel class annotations in training and predict all categories in testing. Different from COCO Caption (Chen et al., 2015) using the same images as COCO-2017, CC3M (Sharma et al., 2018) collects 3 million image-text pairs from the web. Following the official LVIS setting, we train a mask head on base-class detection data and report the mask AP for all categories.

4.2 IMPLEMENTATION DETAILS

In each mini-batch, the ratio of base-class detection data and image-text pair data is 1:4. For better generalized ability, we use fixed CLIP text encoder to embed the caption and object words. To reduce

Table 1: Open-vocabulary object detection results on COCO dataset. We follow the OVR-CNN (Zareian et al., 2021) using the same training data of COCO Caption (Chen et al., 2015) and outperform the state-of-art method PB-OVD (Gao et al., 2021) on novel classes.

Method	Novel AP	Base AP	Overall AP
Base-only	1.3	52.8	39.3
OVR-CNN (Zareian et al., 2021)	22.8	46.0	39.9
Detic (Zhou et al., 2022)	27.8	47.1	42.0
RegionCLIP (Zhong et al., 2022)	26.8	54.8	47.5
ViLD (Gu et al., 2021)	27.6	59.5	51.3
PB-OVD (Gao et al., 2021)	30.8	46.1	42.1
Our	**32.0**	50.6	45.8

Table 2: Open-vocabulary object detection results on LVIS dataset for two different backbones ResNet50 (RN50) (He et al., 2016) and Swin-B (Liu et al., 2021). Base-only method only uses base class bounding box, which is considered as our baseline.

Method	Backbone	$\text{mAP}^{mask}_{Novel}$	mAP^{mask}_c	mAP^{mask}_f	mAP^{mask}_{all}
Base-only	RN50	16.3	31.0	35.4	30.0
ViLD (Gu et al., 2021)	RN50	16.6	24.6	30.3	25.5
RegionCLIP (Zhong et al., 2022)	RN50	17.1	27.4	34.0	28.2
DetPro (Du et al., 2022)	RN50	19.8	25.6	28.9	25.9
Detic (Zhou et al., 2022)	RN50	19.5	-	-	30.9
Our	RN50	**21.7**	29.8	34.3	30.1
Base-only	Swin-B	21.9	40.5	43.3	38.4
Detic (Zhou et al., 2022)	Swin-B	23.9	40.2	42.8	38.4
Our	Swin-B	**26.3**	39.4	41.9	38.1

training time, we always initialize the parameters from the detector trained by the fully supervised base-class detection data following (Zhou et al., 2022).

In the open-vocabulary COCO experiments, we basically follow the OVR-CNN (Zareian et al., 2021) setting without any data augmentation. Our model adopts Faster R-CNN (Ren et al., 2015) with ResNet50-C4 (He et al., 2016) as the backbone. For the warmup, we increase the learning rate from 0 to 0.002 for the first 1000 iterations. The model is trained for 90,000 iterations using SGD optimizer with batch size 8 and the learning rate is scaled down by a factor of 10 at 60,000 and 80,000 iterations.

In open-vocabulary LVIS experiments, we follow Detic (Zhou et al., 2022) to adopt Center-Net2 (Zhou et al., 2021b) with ResNet50 (He et al., 2016) as backbone. We use large scale jittering (Ghiasi et al., 2021) and repeat factor sampling as data augmentation. For the warmup, we increase the learning rate from 0 to 2e-4 for the first 1000 iterations. The model is trained for 90,000 iterations using Adam optimizer with batch size 16. All the expriments are conducted on 8 NVIDIA V100 GPUs.

4.3 OPEN-VOCABULARY COCO

Table 1 shows the performance comparisons of different methods for open-vocabulary COCO datasets. It can be seen that our model performs the best on novel classes, suggesting the superiority of using the bipartite matching loss with the image-text pairs. Base-only method indicates the Faster R-CNN trained with the fully supervised COCO base-category detection data with CLIP embeddings as the classifier head. Although CLIP has the generalized ability to the novel class, it only achieves 1.3 mAP. Although ViLD and RegionCLIP distills the region proposal features using the CLIP, their performances are inferior to ours on novel categories, which is the main metric in the open-vocabulary object detection setting. These distillation methods require both the image encoder and the text encoder from the pretrained CLIP model to learn the matching between the image regions and the vocabulary. Thus, their performances on novel classes are limited by the pretrained model, which is trained for global image-text matching instead of region-word matching. Compared with the state-of-the-art method PB-OVD (Gao et al., 2021) which leverages the COCO Caption (Chen et al., 2015), VG (Krishna et al., 2017) and SBU Caption dataset (Ordonez et al.,

Figure 3: Visualization of the bipartite matching results. Here we show how the proposed region matched with their corresponding words. Best viewed on screen.

2011) with about 1M training image-text pairs, our method still outperforms it on all metrics while we use only 10K images of COCO Caption as training data.

4.4 OPEN-VOCABULARY LVIS

Table 2 shows the performance comparisons on the open-vocabulary LVIS object detection. The "Based-only" method is only fully supervised on the base categories, which is the baseline of our method. As mentioned above, since we use fix CLIP embeddings as the classifier head, the base-only method has a certain generalization ability. The proposed model outperforms the state-of-the-art method DetPro (Du et al., 2022) by 1.9 % AP on novel classes. RegionCLIP (Zhong et al., 2022) uses a CLIP model to predict pseudo-labels for image regions and pretrains a visual model with the region-text pairs. We can see that it is effective to improve the generalization ability to novel classes. Similar strategy is used in recent works (Gao et al., 2021). However, such two-step pseudo-label method is easy to amplify false predictions and it relies on good initialization of the teacher model to generate good pseudo-labels. In contrast, our proposed method is assigning class labels from a global perspective and optimizing the object detection model without finetuning. To further explore the scalability of our model, we use Swin-B as our backbone, and our model outperforms the ResNet backbone with 4.5% mAP on novel classes. Compared with Detic, our model achieves 2.4% gain on OV-LVIS novel classes, suggesting the effectiveness of the label assignment from the global perspective.

Visualization. As shown in Figure 3, we visualize some cases of matching results of CC3M in open vocabulary LVIS setting. As we can see, the model can extract promising region-words pairs from image-text data, avoiding expensive annotations. The results of the matching include a variety of objects, such as "jar", "typewriter", and "camera", which indicates that our method significantly expands the vocabulary for object detection. It demonstrates the generalization ability of our method to novel classes.

4.5 ABLATION STUDIES

Object Vocabulary Size. In our VLDet, we follow the previous work (Zhong et al., 2022) using all nouns in COCO Caption and CC3M and filtering out low-frequency words, resulting in 4764/6250 concepts left. We notice that many works recently use the LVIS and COCO label spaces as the object vocabulary during training, which do not strictly follow the open-vocabulary setting. We further analyze the effect of training our model with different vocabulary sizes. In Table 3, we replace our object vocabulary with the category names in COCO and LVIS datasets, i.e. only using

Table 3: Ablation study on vocabulary size. We replace our object vocabulary with the category names of OV-COCO and OV-LVIS. The results show that training with a large vocabulary size enables better generalization.

Vocabulary	OV-COCO			OV-LVIS		
	Size	mAP_{novel}	mAP_{all}	Size	$\text{mAP}_{novel}^{mask}$	mAP_{all}^{mask}
Category names	65	28.2	42.8	1203	18.9	31.2
All nouns from caption	4764	30.0	44.6	6750	20.4	30.4

Table 4: Ablation study on matching strategy. We implement Hungarian algorithm (Kuhn, 1955) for one-to-one region-word matching and Sinkhorn algorithm (Cuturi, 2013) for one-to-many matching.

Matching Strategy	OV-COCO		OV-LVIS	
	mAP_{novel}	mAP_{all}	$\text{mAP}_{novel}^{mask}$	mAP_{all}^{mask}
One-to-Many	29.1	44.6	18.5	29.2
One-to-One	32.0	45.8	21.7	30.1

the category names in the captions. We can see from Table 3 that a larger vocabulary significantly boosts the unseen class performance. It achieves gains of 1.8% and 1.5% on the novel categories of OV-COCO and OV-LVIS, respectively, indicating that training with a large vocabulary size leads to better generalization. In other words, with a bigger vocabulary, the model can learn more object language alignments which benefits the novel-class performance during inference.

One-to-One vs. One-to-Many. The key to extract a set of image region-word pairs from an image-text pair is to optimize the assignment problem from a global perspective. To further investigate the impact of assignment algorithms, we implement two global algorithms, Hungarian (Kuhn, 1955) and Sinkhorn (Cuturi, 2013) algorithms, where the former does one-to-one region-word assignment, and the latter produces one word to-many regions. Considering that there may be multiple instances of the same category in an image, Sinkhorn algorithm is able to produce multiple regions to the same word, while it might also introduce more noisy region-word pairs. From Table 4, we observe that the one-to-one assignment achieves 32.0 AP and 21.7 AP for novel classes, both outperforming the one-to-many assignment of 29.1 AP and 18.5 AP. This is mainly because the one-to-one assignment provides each word with a high-quality image region.
Discussion on noisy image-text pairs. In VLDet, we employ the Hungarian algorithm to assign each word a unique region. When facing plural descriptions in a text, such as "a basket of oranges", we will align the most confident region-word pair and ignore other "oranges". Similarly, if the caption is incomplete (which is often the case, since the caption may not describe every instance in the image), we will ignore those unmatched regions as well. Note that those regions will not be optimized as background, and the loss is only computed with the regions in the matching result.

Different Strategies for Region-Word Alignment. Figure 4 shows a comparison to different strategies for the region-word alignment in weakly supervised methods (Zhou et al., 2022; Redmon & Farhadi, 2017; Yao et al., 2021). For fair comparison, we use the region-word alignment loss alone with different strategies for training. "Max-score" (Redmon & Farhadi, 2017; Yao et al., 2021) indicates each word selects the proposal with the largest similarity score, which is widely used in weakly-supervised object detection. However, it tends to assigns each region proposal to a base class due to the full supervision for the bass classes. In contrast, our formulated set-to-set matching aims to minimize the global matching cost to find each region proposal a distinguished corresponding word, where strongly matched base-class regions can push other region proposals to explore the matching with novel classes. "Max-size" (Zhou et al., 2022), assigns all nouns in a caption to the proposal with the max size. The results in Figure 4 show that our method achieves the best performance for the novel classes on both OV-COCO and OV-LVIS.

Image-Text Alignment. We conduct ablation experiments to evaluate the effectiveness of different training losses of our method in Table 5. We observe that using the region-word alignment loss alone achieves promising results. It demonstrates the effectiveness of the bipartite matching strategy for learning region-word alignment. Furthermore, we can find that using image-text pair as additional supervision can improve the performance. Intuitively, the image-text pairs data can provide contextual information which complements semantics beyond nouns. A similar conclusion can be found in (Zhou et al., 2022; Zhong et al., 2022).

Figure 4: We show a comparison of different alignment strategies in terms of novel-class mAP on both open-vocabulary COCO and LVIS. Different from the bipartite matching that learns the alignment from the global perspective, "max-score" (Redmon & Farhadi, 2017; Yao et al., 2021) does the alignment based on the highest similarity score and "max-size" (Zhou et al., 2022) assigns the max size proposal to the image labels.

Table 5: Ablation study on training losses. It performs best when both the region-word alignment loss and the image-text alignment loss are used, suggesting that they benefit from each other.

$L_{region-word}$	$L_{image-text}$	OV-COCO		OV-LVIS	
		mAP_{novel}	mAP_{all}	mAP_{novel}^{mask}	mAP_{all}^{mask}
✓		30.0	44.6	20.4	30.4
	✓	21.0	43.8	17.4	30.4
✓	✓	32.0	45.8	21.7	30.1

4.6 TRANSFER TO OTHER DATASETS.

To evaluate the generalization ability of our model, we conduct the experiments on transferring COCO-trained model to PASCAL VOC (Everingham et al., 2010) test set and LVIS validation set without re-training. We directly use the model trained with COCO Caption data for OV-COCO and replace the class embeddings of the classifier head. PASCAL VOC is a widely used object detection dataset that contains 20 object categories, where 9 of them are unseen classes in COCO. Directly transferring models without us-

Table 6: Transfer to other datasets. We evaluated COCO-trained model on PASCAL VOC (Everingham et al., 2010) test set and LVIS validation set without re-training. All results are box AP_{50}.

Method	PASCAL VOC	LVIS
OVRCNN	52.9	5.2
PB-OVD	59.2	8.0
Our	61.7	10.0

ing any training images is challenging due to the domain gap. What's more, LVIS includes 1203 object categories which is much larger than COCO label space. As shown in Table 6, our model achieves 2.5 % and 2.0% improvement on VOC test set and LVIS validation set, demonstrating the effectiveness of our method on diverse image domains and language vocabularies. While LVIS includes category names that do not appear in COCO Caption concepts, our model can learn close concepts during training, which facilitates the transfer to LVIS.

5 CONCLUSIONS AND LIMITATIONS

We have presented VLDet which aims to learn the annotation-free object-language alignment from the image-caption pairs for open-vocabulary object detection. Our key idea is to extract the region-word pairs from a global perspective using bipartite matching by converting images into regions and text into words. We only use a single object detection model supervised by the free image-text pairs without any object-language annotations for novel classes. The extensive experiments show that our detector VLDet achieves a new state-of-the-art performance on both open-vocabulary COCO and LVIS. We hope this work can push the direction of OVOD and inspire more work on large-scale free image-text pair data. The potential limitations of VLDet are: 1) it does not consider the bias of vision-and-language data; 2) we have not investigated even larger data volumes, e.g. Conceptual Captions 12M (Changpinyo et al., 2021). We leave them for future works.

REFERENCES

Ankan Bansal, Karan Sikka, Gaurav Sharma, Rama Chellappa, and Ajay Divakaran. Zero-shot object detection. In *Proceedings of the European Conference on Computer Vision (ECCV)*, pp. 384–400, 2018.

Hakan Bilen and Andrea Vedaldi. Weakly supervised deep detection networks. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 2846–2854, 2016.

Hakan Bilen, Marco Pedersoli, and Tinne Tuytelaars. Weakly supervised object detection with convex clustering. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 1081–1089, 2015.

Zhaowei Cai and Nuno Vasconcelos. Cascade r-cnn: Delving into high quality object detection. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 6154–6162, 2018.

Zhaowei Cai, Gukyeong Kwon, Avinash Ravichandran, Erhan Bas, Zhuowen Tu, Rahul Bhotika, and Stefano Soatto. X-detr: A versatile architecture for instance-wise vision-language tasks. *arXiv preprint arXiv:2204.05626*, 2022.

Nicolas Carion, Francisco Massa, Gabriel Synnaeve, Nicolas Usunier, Alexander Kirillov, and Sergey Zagoruyko. End-to-end object detection with transformers. In *European conference on computer vision*, pp. 213–229. Springer, 2020.

Soravit Changpinyo, Piyush Sharma, Nan Ding, and Radu Soricut. Conceptual 12M: Pushing web-scale image-text pre-training to recognize long-tail visual concepts. In *CVPR*, 2021.

Xinlei Chen, Hao Fang, Tsung-Yi Lin, Ramakrishna Vedantam, Saurabh Gupta, Piotr Dollár, and C Lawrence Zitnick. Microsoft coco captions: Data collection and evaluation server. *arXiv preprint arXiv:1504.00325*, 2015.

Ramazan Gokberk Cinbis, Jakob Verbeek, and Cordelia Schmid. Weakly supervised object localization with multi-fold multiple instance learning. *IEEE transactions on pattern analysis and machine intelligence*, 39(1):189–203, 2016.

Marco Cuturi. Sinkhorn distances: Lightspeed computation of optimal transport. *Advances in neural information processing systems*, 26, 2013.

Thomas G Dietterich, Richard H Lathrop, and Tomás Lozano-Pérez. Solving the multiple instance problem with axis-parallel rectangles. *Artificial intelligence*, 89(1-2):31–71, 1997.

Yu Du, Fangyun Wei, Zihe Zhang, Miaojing Shi, Yue Gao, and Guoqi Li. Learning to prompt for open-vocabulary object detection with vision-language model. *arXiv preprint arXiv:2203.14940*, 2022.

Mark Everingham, Luc Van Gool, Christopher KI Williams, John Winn, and Andrew Zisserman. The pascal visual object classes (voc) challenge. *International journal of computer vision*, 88(2): 303–338, 2010.

Yuxin Fang, Shusheng Yang, Xinggang Wang, Yu Li, Chen Fang, Ying Shan, Bin Feng, and Wenyu Liu. Instances as queries. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 6910–6919, 2021.

Mingfei Gao, Chen Xing, Juan Carlos Niebles, Junnan Li, Ran Xu, Wenhao Liu, and Caiming Xiong. Towards open vocabulary object detection without human-provided bounding boxes. *arXiv preprint arXiv:2111.09452*, 2021.

Andreas Geiger, Philip Lenz, Christoph Stiller, and Raquel Urtasun. Vision meets robotics: The kitti dataset. *The International Journal of Robotics Research*, 32(11):1231–1237, 2013.

Golnaz Ghiasi, Yin Cui, Aravind Srinivas, Rui Qian, Tsung-Yi Lin, Ekin D Cubuk, Quoc V Le, and Barret Zoph. Simple copy-paste is a strong data augmentation method for instance segmentation. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 2918–2928, 2021.

Golnaz Ghiasi, Xiuye Gu, Yin Cui, and Tsung-Yi Lin. Scaling open-vocabulary image segmentation with image-level labels. In *European Conference on Computer Vision*, pp. 540–557. Springer, 2022.

Ross Girshick. Fast r-cnn. In *Proceedings of the IEEE International Conference on Computer Vision*, pp. 1440–1448, 2015.

Xiuye Gu, Tsung-Yi Lin, Weicheng Kuo, and Yin Cui. Open-vocabulary object detection via vision and language knowledge distillation. *arXiv preprint arXiv:2104.13921*, 2021.

Agrim Gupta, Piotr Dollar, and Ross Girshick. Lvis: A dataset for large vocabulary instance segmentation. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pp. 5356–5364, 2019.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 770–778, 2016.

Kaiming He, Georgia Gkioxari, Piotr Dollár, and Ross Girshick. Mask r-cnn. In *Proceedings of the IEEE International Conference on Computer Vision*, pp. 2961–2969, 2017.

Dat Huynh, Jason Kuen, Zhe Lin, Jiuxiang Gu, and Ehsan Elhamifar. Open-vocabulary instance segmentation via robust cross-modal pseudo-labeling. *arXiv preprint arXiv:2111.12698*, 2021.

Chao Jia, Yinfei Yang, Ye Xia, Yi-Ting Chen, Zarana Parekh, Hieu Pham, Quoc Le, Yun-Hsuan Sung, Zhen Li, and Tom Duerig. Scaling up visual and vision-language representation learning with noisy text supervision. In *International Conference on Machine Learning*, pp. 4904–4916. PMLR, 2021.

Matthew Johnson-Roberson, Charles Barto, Rounak Mehta, Sharath Nittur Sridhar, Karl Rosaen, and Ram Vasudevan. Driving in the matrix: Can virtual worlds replace human-generated annotations for real world tasks? *arXiv preprint arXiv:1610.01983*, 2016.

Aishwarya Kamath, Mannat Singh, Yann LeCun, Gabriel Synnaeve, Ishan Misra, and Nicolas Carion. Mdetr-modulated detection for end-to-end multi-modal understanding. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 1780–1790, 2021.

Ranjay Krishna, Yuke Zhu, Oliver Groth, Justin Johnson, Kenji Hata, Joshua Kravitz, Stephanie Chen, Yannis Kalantidis, Li-Jia Li, David A Shamma, et al. Visual genome: Connecting language and vision using crowdsourced dense image annotations. *International journal of computer vision*, 123(1):32–73, 2017.

Harold W Kuhn. The hungarian method for the assignment problem. *Naval research logistics quarterly*, 2(1-2):83–97, 1955.

Liunian Harold Li, Pengchuan Zhang, Haotian Zhang, Jianwei Yang, Chunyuan Li, Yiwu Zhong, Lijuan Wang, Lu Yuan, Lei Zhang, Jenq-Neng Hwang, et al. Grounded language-image pre-training. *arXiv preprint arXiv:2112.03857*, 2021.

Tsung-Yi Lin, Piotr Dollár, Ross Girshick, Kaiming He, Bharath Hariharan, and Serge Belongie. Feature pyramid networks for object detection. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 2117–2125, 2017.

Ze Liu, Yutong Lin, Yue Cao, Han Hu, Yixuan Wei, Zheng Zhang, Stephen Lin, and Baining Guo. Swin transformer: Hierarchical vision transformer using shifted windows. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 10012–10022, 2021.

Depu Meng, Xiaokang Chen, Zejia Fan, Gang Zeng, Houqiang Li, Yuhui Yuan, Lei Sun, and Jingdong Wang. Conditional detr for fast training convergence. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 3651–3660, 2021.

Matthias Minderer, Alexey Gritsenko, Austin Stone, Maxim Neumann, Dirk Weissenborn, Alexey Dosovitskiy, Aravindh Mahendran, Anurag Arnab, Mostafa Dehghani, Zhuoran Shen, et al. Simple open-vocabulary object detection with vision transformers. *arXiv preprint arXiv:2205.06230*, 2022.

Vicente Ordonez, Girish Kulkarni, and Tamara Berg. Im2text: Describing images using 1 million captioned photographs. *Advances in neural information processing systems*, 24, 2011.

Bryan A Plummer, Liwei Wang, Chris M Cervantes, Juan C Caicedo, Julia Hockenmaier, and Svetlana Lazebnik. Flickr30k entities: Collecting region-to-phrase correspondences for richer image-to-sentence models. In *Proceedings of the IEEE international conference on computer vision*, pp. 2641–2649, 2015.

Alec Radford, Jong Wook Kim, Chris Hallacy, Aditya Ramesh, Gabriel Goh, Sandhini Agarwal, Girish Sastry, Amanda Askell, Pamela Mishkin, Jack Clark, et al. Learning transferable visual models from natural language supervision. In *International Conference on Machine Learning*, pp. 8748–8763. PMLR, 2021.

Yongming Rao, Wenliang Zhao, Guangyi Chen, Yansong Tang, Zheng Zhu, Guan Huang, Jie Zhou, and Jiwen Lu. Denseclip: Language-guided dense prediction with context-aware prompting. *arXiv preprint arXiv:2112.01518*, 2021.

Joseph Redmon and Ali Farhadi. Yolo9000: better, faster, stronger. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 7263–7271, 2017.

Shaoqing Ren, Kaiming He, Ross Girshick, and Jian Sun. Faster r-cnn: Towards real-time object detection with region proposal networks. In *Advances in Neural Information Processing Systems*, pp. 91–99, 2015.

Christos Sakaridis, Dengxin Dai, and Luc Van Gool. Semantic foggy scene understanding with synthetic data. *International Journal of Computer Vision*, 126(9):973–992, 2018.

Piyush Sharma, Nan Ding, Sebastian Goodman, and Radu Soricut. Conceptual captions: A cleaned, hypernymed, image alt-text dataset for automatic image captioning. In *Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 2556–2565, 2018.

Peize Sun, Yi Jiang, Enze Xie, Wenqi Shao, Zehuan Yuan, Changhu Wang, and Ping Luo. What makes for end-to-end object detection? In *International Conference on Machine Learning*, pp. 9934–9944. PMLR, 2021a.

Peize Sun, Rufeng Zhang, Yi Jiang, Tao Kong, Chenfeng Xu, Wei Zhan, Masayoshi Tomizuka, Lei Li, Zehuan Yuan, Changhu Wang, et al. Sparse r-cnn: End-to-end object detection with learnable proposals. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 14454–14463, 2021b.

Peng Tang, Xinggang Wang, Xiang Bai, and Wenyu Liu. Multiple instance detection network with online instance classifier refinement. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 2843–2851, 2017.

Pei Wang, Zhaowei Cai, Hao Yang, Gurumurthy Swaminathan, Nuno Vasconcelos, Bernt Schiele, and Stefano Soatto. Omni-detr: Omni-supervised object detection with transformers. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 9367–9376, 2022.

Lewei Yao, Runhui Huang, Lu Hou, Guansong Lu, Minzhe Niu, Hang Xu, Xiaodan Liang, Zhenguo Li, Xin Jiang, and Chunjing Xu. Filip: Fine-grained interactive language-image pre-training. *arXiv preprint arXiv:2111.07783*, 2021.

Keren Ye, Mingda Zhang, Adriana Kovashka, Wei Li, Danfeng Qin, and Jesse Berent. Cap2det: Learning to amplify weak caption supervision for object detection. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 9686–9695, 2019.

Fisher Yu, Wenqi Xian, Yingying Chen, Fangchen Liu, Mike Liao, Vashisht Madhavan, and Trevor Darrell. Bdd100k: A diverse driving video database with scalable annotation tooling. *arXiv preprint arXiv:1805.04687*, 2(5):6, 2018.

Jiahui Yu, Zirui Wang, Vijay Vasudevan, Legg Yeung, Mojtaba Seyedhosseini, and Yonghui Wu. Coca: Contrastive captioners are image-text foundation models. *arXiv preprint arXiv:2205.01917*, 2022.

Licheng Yu, Patrick Poirson, Shan Yang, Alexander C Berg, and Tamara L Berg. Modeling context in referring expressions. In *European Conference on Computer Vision*, pp. 69–85. Springer, 2016.

Lu Yuan, Dongdong Chen, Yi-Ling Chen, Noel Codella, Xiyang Dai, Jianfeng Gao, Houdong Hu, Xuedong Huang, Boxin Li, Chunyuan Li, et al. Florence: A new foundation model for computer vision. *arXiv preprint arXiv:2111.11432*, 2021.

Alireza Zareian, Kevin Dela Rosa, Derek Hao Hu, and Shih-Fu Chang. Open-vocabulary object detection using captions. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 14393–14402, 2021.

Xiaohua Zhai, Xiao Wang, Basil Mustafa, Andreas Steiner, Daniel Keysers, Alexander Kolesnikov, and Lucas Beyer. Lit: Zero-shot transfer with locked-image text tuning. *arXiv preprint arXiv:2111.07991*, 2021.

Hao Zhang, Feng Li, Shilong Liu, Lei Zhang, Hang Su, Jun Zhu, Lionel M Ni, and Heung-Yeung Shum. Dino: Detr with improved denoising anchor boxes for end-to-end object detection. *arXiv preprint arXiv:2203.03605*, 2022.

Yiwu Zhong, Jianwei Yang, Pengchuan Zhang, Chunyuan Li, Noel Codella, Liunian Harold Li, Luowei Zhou, Xiyang Dai, Lu Yuan, Yin Li, et al. Regionclip: Region-based language-image pretraining. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 16793–16803, 2022.

Chong Zhou, Chen Change Loy, and Bo Dai. Denseclip: Extract free dense labels from clip. *arXiv preprint arXiv:2112.01071*, 2021a.

Xingyi Zhou, Vladlen Koltun, and Philipp Krähenbühl. Probabilistic two-stage detection. *arXiv preprint arXiv:2103.07461*, 2021b.

Xingyi Zhou, Rohit Girdhar, Armand Joulin, Phillip Krähenbühl, and Ishan Misra. Detecting twenty-thousand classes using image-level supervision. *arXiv preprint arXiv:2201.02605*, 2022.

Xizhou Zhu, Weijie Su, Lewei Lu, Bin Li, Xiaogang Wang, and Jifeng Dai. Deformable detr: Deformable transformers for end-to-end object detection. *arXiv preprint arXiv:2010.04159*, 2020.