BCDR: Betweenness Centrality-based Distance Resampling for Graph Shortest Distance Embedding

Abstract

Along with unprecedented development in network analysis such as biomedical structure prediction and social relationship analysis, Shortest Distance Queries (SDQs) in graphs receive an increasing attention. Approximate algorithms of SDQs with reduced complexity are of vital importance to complex graph applications. Among different approaches, embedding-based distance prediction has made a breakthrough in both efficiency and accuracy, ascribing to the significant performance of Graph Representation Learning (GRL). Embedding-based distance prediction usually leverages truncated random walk followed by Pointwise Mutual Information (PMI)-based optimization to embed local structural features into a dense vector on each node and integrates with a subsequent predictor for global extraction of nodes' mutual shortest distance. It has several shortcomings. Random walk as an unstrained node sequence possesses a limited distance exploration, failing to take into account remote nodes under graph's shortest distance metric, while the PMI-based maximum likelihood optimization of node embeddings reflects excessively versatile local similarity, which incurs an adverse impact on the preservation of the exact shortest distance relation during the mapping from the original graph space to the embedded vector space.

To address these shortcomings, we propose in this paper a novel graph shortest distance embedding method called Betweenness Centrality-based Distance Resampling (BCDR). First, we prove in a statistical perspective that Betweenness Centrality(BC)-based random walk can occupy a wider distance range measured by the intrinsic metric in the graph domain due to its awareness of the path structure. Second, we perform Distance Resampling (DR) from original walk paths before maximum likelihood optimization instead of the PMI-based optimization and prove that this strategy preserves distance relation with respect to any calibrated node via steering optimization objective to reconstruct a global distance matrix. Our proposed method possesses a strong theoretical background and shows much better performance than existing methods when evaluated on a broad class of real-world graph datasets with large diameters in SDQ problems. It should also outperform existing methods in other graph structure-related applications.

1 Introduction

Shortest Distance Queries (SDQs) in graphs focus on determining the minimum distance between arbitrary node pairs, defined as sum of related edge weights. Despite the fact that Shortest Path Queries (SPQs) (Wei, 2012; Sommer, 2014; Wang et al., 2021) are already renowned in graph structure exploration, SDQs play an essential role in increasing applications, such as social relationship analysis (Carlton, 2020; Melkonian et al., 2021; Chen et al., 2021; Zaki et al., 2021; Parveen & Varma, 2021), biomedical structure prediction (Yue et al., 2019; Galovičová et al., 2021; Sokolowski & Wasserman, 2021), learning theory (Yang et al., 2021; Yuan et al., 2021), optimization (Melkonian et al., 2021; Rahmad Syah et al., 2021; Jiang et al., 2021), etc. The key challenge in the SDQ problem is the prohibitive complexity in very large graphs. e.g., for an undirected dense graph with N nodes and k queries, the time complexity of A*(Hart et al., 1968) and Dijkstra Algorithm(Thorup & Zwick, 2004) are up to $O(kN^2)$ and $O(kN \log N)$ for unweighted and weighted graph, respectively.

Table 1: Overall comparison of approaches to shortest distance query.

Accuracy loss of approximate methods are evaluated on facebook(A.6.2) by mRE(2). N-number of nodes, T-walk length, K-window size, l-number of landmarks, d-dimension of embedding space, α, β, c-constant independent of N.

Objective	Method	Model	Off-Line Time	Space	Time	Accuracy Loss
Exact	Compress	-	$O(N^3)$	$O(N^2)$	$O(kN)$	0
Exact	Index	-	$O(N^2 \log N)$	$O(N^2)$	$O(kN \log N)$	0
Exact	Cache	-	—	$O(N)$	$O(N) \sim O(N^2)$	0
Approximate	Oracle	-	$O(\alpha N^{1+\frac{1}{\alpha}})$	$O(\alpha N^{1+\frac{1}{\alpha}})$	$O(k\alpha)$	$2(\alpha - 1)$
Approximate	Landmark	-	$O(lN \log N + lN)$	$O(lN)$	$O(kl)$	0.523
Approximate	Embedding	Orion	$O(\alpha N \log N + cN)$	$O(dN)$	$O(kd)$	0.688
		Rigel	$O(\alpha N \log N + cN)$	$O(dN)$	$O(kd)$	0.369
		DeepWalk	$O(TKN \log N + (T+c)N)$	$O(dN)$	$O(kd)$	0.329
		Node2Vec	$O(TKN \log N + (T+c)N)$	$O(dN)$	$O(kd)$	0.299
		DADL	$O(TKN \log N + (T+c)N)$	$O(dN)$	$O(kd)$	0.228
		BCDR(ours.)	$O(\alpha TKN \log N + (\beta T+c)N)$	$O(dN)$	$O(kd)$	**0.177**

| (a) | (b) | (c) | (d) |

Figure 1: Distance confusion of a conventional model in embedding. **(a)** random walks rooted at v_a have much difficulty in exploring beyond current community to v_c. **(b):** Weight decay on walks causes instability of shortest distance since walks rooted at v_a have large probability to steer clear of v_b for starters and back to v_b as the end, which results in a extremely weak correlation between v_a and v_b despite the fact that they have an immediate edge. **(c):** A sufficient number of 2-hop links between v_c and v_a induce a shorter distance in embedding space than that of v_b and v_a. **(d):** v_b and v_c sharing substantial connection deserve to be mapped closed to each other even if they have a large shortest distance gap, while the divergence of distance between v_b, v_c and v_a is also plagued with extraction.

To address this issue, a surging number of approximate algorithms in a wide range of fields have been proposed in the past a few years. They can be categorized into oracle-based (Thorup & Zwick, 2004; Baswana & Kavitha, 2006), landmark-based (Sarma et al., 2010; Gubichev et al., 2010), embedding-based distance prediction methods (Xiaohan et al., 2010; 2011; Rizi et al., 2018). Among these categories, embedding-based methods are of high accuracy with significantly reduced complexity (see Table1), owing much to rapid advances of representation learning in graphs (Perozzi et al., 2014; Grover & Leskovec, 2016). Embedding-based methods tackle the SDQ problem with two stages. First, they embed local structural features into a dense vector on each node, which preserves the essential information for indicating where the node is. Then, for arbitrary node pairs in the training set, subsequent predictor extracts mutual shortest distance globally via their embedding tuples and minimizes the mean of square loss between a predicted value and the real one. As predictors serve as a non-linear metric in the embedding space, the performance of embedding-based models depends highly on the first stage. These methods usually embed graph structures by leveraging truncated random walk to serialize node's neighborhood in a statistical perspective and maximize co-occurrence likelihood of nodes in one walk path to reflect their correlation, which is also proved to implicitly factorize a Pointwise Mutual Information (PMI) matrix (Levy & Goldberg, 2014; Shaosheng et al., 2015).

Although existing embedding-based methods have achieved a great success, they have several shortcomings. On one side, random walk is an unstrained node sequence from the root, possessing a limited distance exploration. This is because each transition on nodes is not implied for a specific direction to move towards or beyond the root, especially after several walk steps, which is backbreaking to accommodate correlation with remote nodes under graph's shortest distance metric (see Figure 1a). On the other side, the PMI-based optimization reflects excessively versatile local sim-

ilarity, which is not guaranteed for shortest distance-preserved mapping from the original graph space to the embedded vector space. As a matter of fact, it exerts a too-general metric over nodes' correlation, wherein the more links or paths exist between two nodes, the stronger correlation they share. That means we have many ways to claim a shorter distance for two nodes (e.g., by adding mutual edges, deleting links to other nodes) even if some of the operations do not change their actual shortest path distance (see Figures 1c and 1d).

In this paper, we address the above shortcomings by proposing a novel graph shortest distance embedding method called Betweenness Centrality-based Distance Resampling (BCDR). Here, random walk paths are simulated by considering nodes' betweenness centrality on each transition for covering a wider distance range of nodes. Then, a sampling process of nodes based on their mutual shortest distances is performed before optimization of co-occurrence likelihood to preserve pairwise distance relation during the mapping from graph to the embedding space.

We summarize our major contributions as follows.

- We propose a **Betweenness Centrality (BC)-based random walk** for **accommodating correlation** with nodes **of wider distance range** under the intrinsic graph metric (see Section 3.1). To the best of our knowledge, there is no existing method that combines betweenness centrality and random walk for the graph representation. We prove in a statistical perspective that the transition driven by nodes' BC value tends to explore high order proximity of the root due to the awareness of local path structure.

- We propose a **Distance Resampling (DR)** strategy to **preserve** nodes' mutual **shortest distance during the mapping** from graph to the embedding space (see Section 3.2). We prove that by sampling node sequences from original walk paths before maximum likelihood optimization instead of PMI-based optimization, the objective can be steered to reconstruct a global distance matrix, and for any calibrated node, it strictly preserves the shortest distance relation to other nodes on the graph.

- We evaluate BCDR and compare it with existing embedding-based methods with a broad class of **real-world graph datasets with divergent diameters**. BCDR shows a **much better empirical performance** in solving the SDQ problem than existing embedding-based methods (see Section 4).

2 NOTATION & PROBLEM DEFINITION

2.1 NOTATION

$G = (V, E)$ denotes an undirected graph, with $V = \{v_1, v_2, ..., v_{|V|}\}$ being the set of nodes and E being the set of edges. An edge $e_{ij} = (v_i, v_j)$ represents an undirected edge between nodes v_i and v_j. A node v_i's neighborhood $\mathcal{N}_i$ is a set of nodes with an edge with v_i, i.e., $\mathcal{N}_i = \{v_j | (v_i, v_j) \in E\}$. We use $Z_{|V| \times d}$ to represent an embedding matrix, where d is the embedding size. For any matrix B, the symbol $\mathbf{B}_i$ represents the i-th row of B, and B_{ij} represents the element at i-th row and j-th column. A truncated random walk $\mathcal{W}_i$ rooted at node v_i of length l is a random vector of $\langle \mathcal{W}_i^1, \mathcal{W}_i^2, \cdots, \mathcal{W}_i^l \rangle$, where $\mathcal{W}_i^k$ is a node chosen from the neighborhood of node $\mathcal{W}_i^{k-1}$ for $k = 1, ..., l$, with $\mathcal{W}_i^0 := v_i$. P_i is a finite set of walk paths sampled from $\mathcal{W}_i$, and W_i is the multiset of nodes on the walk paths in P_i.

2.2 PROBLEM DEFINITION

An arbitrary path p of length $l \in \mathbb{N}$ on graph G is an ordered sequence of nodes $(v_1, v_2, ...v_{l+1})$, where each node except the last one has an edge with the subsequent node, i.e., $(v_i, v_{i+1}) \in E$ for $1 \leq i \leq l$. The shortest path $\mathring{p}_{ij}$ is one of the paths with the minimum length $\mathring{l}$ between two nodes v_i and v_j, with the shortest distance D_{ij} defined as the length of $\mathring{p}_{ij}$. The global distance matrix D comprises $\{D_{ij}\}$.

An embedding-based model learns two mappings $\mathcal{F}$ and $\mathcal{G}$ for structure embedding and mutual distance extraction, respectively, as follows.

$$\mathcal{F} : G \to \mathbb{R}^d, \quad \mathcal{G} : \langle \mathbb{R}^d, \mathbb{R}^d \rangle \to \mathbb{R} \qquad (1)$$

A shortest distance query Q can be simply defined as a set of node pairs, i.e., $Q = \{(v_{11}, v_{12}), (v_{21}, v_{22}), ..., (v_{|Q|,1}, v_{|Q|,2})\}$. For each node pair (v_i, v_j), the model intends to find out approximation $\hat{D}_{ij} = \mathcal{G}(\mathcal{F}(v_i), \mathcal{F}(v_j))$ nearest to real D_{ij}. The commonly used metrics of approximation quality are mean of Relative Error (mRE) and mean of Absolute Error (mAE). mRE is defined as the relative loss of the prediction value with respect to the real value, while mAE measures the absolute gap between the prediction value and the real value, i.e.,

$$\text{mRE} := \frac{1}{|Q|} \sum_{(v_i, v_j) \in Q} \frac{|\hat{D}_{ij} - D_{ij}|}{D_{ij}}, \quad \text{mAE} := \frac{1}{|Q|} \sum_{(v_i, v_j) \in Q} |\hat{D}_{ij} - D_{ij}| \tag{2}$$

3 METHOD

Random walk as a serialization strategy of similarity measurement has been widely used in many graph representation and learning methods, aiming to model long-range dependency of nodes (Grover & Leskovec, 2016; Zhuang & Ma, 2018). The optimization of maximizing co-occurrence likelihood of nodes on walk paths also yields an impressive performance in network-structure extraction via approximating PMI matrix (Levy & Goldberg, 2014). But in terms of the shortest distance representation of a graph, we contend that this intuitive approach has several limitations on the performance. Consider a walk path $p = (v_a, v_{a_1}, v_{a_2}, \cdots, v_{a_l}) \in P_a$ sampled from a general random walk $\mathcal{W}_a$ from root node v_a. As an unstrained sequence of nodes, the distance measured along the walk path p is not consistent with that on the graph (see Figure 1b), i.e., for $v_{a_i}, v_{a_j} \in p$,

$$i \leq j \nLeftrightarrow D_{aa_i} \leq D_{aa_j} \tag{3}$$

where i and j are indexes of node v_{a_i} and v_{a_j} on p and $1 \leq i, j \leq l$.

Using the aforementioned unstrained walk paths for maximizing co-occurrence likelihood incurs two problems.

1. **Problem 1: Limited exploration range of walks**. Each transition on walks only considers a local structure of the current node, causing agnostic tendency to move towards or beyond the root node under the graph's shortest-distance metric after a few steps (see Figure 1a).

2. **Problem 2: Intractability of shortest distance on paths**. Distance measured on walk paths may not actually reflect the graph's shortest distance because of the unbalanced number of links between different nodes (see Figure 1c and 1d).

In this section, we describe in detail our proposed method, which is a decent way of encoding shortest distances using BC-based random walk plus a distance resampling strategy, and present a theoretical analysis for its interpretability and efficiency. More specifically, we first present BC-based random walks and distance resampling, and then an algorithm to integrate them. We provide an intuitive complexity explanation. Additionally, we discuss the connection between BCDR and conventional MDS methods as its partial theoretical basis in Appendix A.1.

3.1 BC-BASED RANDOM WALK

Definition 1. *(Betweenness Centrality) Define $G = (V, E)$ as undirected graph. v_i, v_s, v_t are arbitrary nodes in the node set V. $\sigma_{st}(v_i)$ represents the number of shortest paths between v_s and v_t that pass v_i, and σ_{st} is the total number of shortest paths between v_s and v_t. Then we say that BC of v_i is*

$$\text{BC}(v_i) = \sum_{s \neq i \neq t} \frac{\sigma_{st}(v_i)}{\sigma_{st}} \tag{4}$$

To address Problem 1, we propose a BC-based random walk. As defined in Definition 1, $\text{BC}(v_i)$ determines the probability of v_i located on shortest paths of arbitrary node pairs. Thus, we consider a node with large BC value vitally significant to drive the walk to move away from root node, since

it reveals a easy way of traveling to some nodes with minimal cost. And to leverage this property, in BC-based random walk $\mathcal{W}_a = \langle \mathcal{W}_a^1, \mathcal{W}_a^2, ... \mathcal{W}_a^j, ... \rangle$ on node v_a, we prefer choosing nodes with the largest BC values among their neighborhoods when simulating walk paths, i.e.,

$$p(\mathcal{W}_a^j | \mathcal{W}_a^{j-1} = v_{j-1}) = \frac{\text{BC}(\mathcal{W}_a^j)}{\sum_{v_k \in \mathcal{N}_{j-1}} \text{BC}(v_k)}, \; \mathcal{W}_a^j \in \mathcal{N}_{j-1} \tag{5}$$

where $\mathcal{N}_i$ is the neighborhood of v_i.

The following theorem, proved in Appendix A.2, indicates that a BC-based random walk tends to transit from $\mathcal{N}_a^{(h)}$ to $\mathcal{N}_a^{(h+1)}$, leading to a deeper exploration measured by the intrinsic graph's shortest distance. It also reveals that our method performs better when the number of final nodes $f_h(v_a)$ is larger or there are more links between final nodes $f_h(v_a)$ to connective nodes $e_h(v_a)$ at any h-order neighborhood of v_a.

Theorem 1. *Define $\mathcal{N}_a^{(h)} = \{v_j | D_{aj} = h\}$ as a set of nodes that are h-hops away from v_a and $N_h(v_a) = |\mathcal{N}_a^{(h)}|$ as the number of nodes in the set. Let the number of the nodes that have connection with nodes in $\mathcal{N}_a^{(h+1)}$ (called connective nodes) be $e_h(v_a)$ and the number of other nodes (called final nodes) be $f_h(v_a)$. The BC we use is an approximate value by considering only the shortest path of nodes within a range of k-hops locally. Let $p_R(N_h(v_a) \to N_{h+1}(v_a))$ represent the probability to transit from nodes of $N_h(v_a)$ to $N_{h+1}(v_a)$ by a general random walk, and $p_B(N_h(v_a) \to N_{h+1}(v_a))$ represent that by a BC-based random walk. Let $P_R(f_h(v_a) \to e_h(v_a))$ be a transition from $f_h(v_a)$ nodes to $e_h(v_a)$. Then, for any node v_a in graph G and any $h > 1$,*

$$\frac{p_B(N_h(v_a) \to N_{h+1}(v_a))}{p_R(N_h(v_a) \to N_{h+1}(v_a))} = 1 + B(k) + C \tag{6}$$

where $C \geq 0$, and

$$\lim_{k \to \infty} B(k) + C = \frac{A_2 - 1}{A_1} + C > 0$$
$$A_1 = \frac{e_h(v_a)}{f_h(v_a)}, \quad A_2 = \frac{1}{p_R(f_h(v_a) \to e_h(v_a))}. \tag{7}$$

3.2 DISTANCE RESAMPLING

To address Problem 2, we propose a Distance Resampling (DR) strategy, which is inspired by Sampling-Importance-Resampling (SIR) method (Smith & Gelfand, 1992). Let $\mathbf{v}_x(v_1, v_2)$ be a random vector of the node tuple. Define $p(\mathbf{v}_x)$ as the joint distribution reflecting the real shortest distance of v_1, v_2 on the graph. We have

$$\max_f \mathbb{E}_{\mathbf{v}_x \sim p}[f] = \sum_{v_1, v_2 \in V} f(v_1, v_2) p(v_1, v_2) \tag{8}$$

as a probabilistic objective for representing the shortest distance D_{12}, where f is a normalized learnable density function determined by nodes' mutual distance in the embedding space. According to the rearrangement inequality, the above equation arrives at the maximum when $f(v_1, v_2)$ varies consistent with $p(v_1, v_2)$, which means f indicates the shortest distance metric on the graph with respect to any v_1, v_2 as p does. Therefore, the critical issue is to extract accurate $p(v_1, v_2)$ in a graph. Let $q(\mathbf{v}_a)$ be the joint distribution reflecting distance relation on sampled walks. We try to leverage q on walk paths to approximate p. Here, we adopt a simple but effective resampling by considering both their mutual distance D_{12} as well as BC values.

Without loss of generality, let v_i represent the root node of walks and v_j be the j-th node on a walk path (i.e., sampled from $\mathcal{W}_i^j$). Our objective is thus to sample from $\mathcal{W}_i$ to generate a new random vector $\mathring{\mathcal{W}}_i = \langle \mathring{\mathcal{W}}_i^1, \mathring{\mathcal{W}}_i^2, ..., \mathring{\mathcal{W}}_i^{\mathring{l}} \rangle$ of length $\mathring{l}$. Then, each node v_j sampled from $\mathring{\mathcal{W}}_i^j$ can be described as a weighted resampling in original walk paths $\mathcal{W}_i$ based on D_{ij} and $\text{BC}(v_j)$, i.e.,

$$\mathbb{E}_{v_j \sim p(v_j|v_i)}[f|v_i] = \sum_{v_i, v_j \in V} f(v_i, v_j) p(v_j|v_i) = \sum_{v_i, v_j \in V} f(v_i, v_j) q(v_j|v_i) \frac{p(v_j|v_i)}{q(v_j|v_i)}$$
$$\approx \sum_{v_i \in V} \sum_{v_j \in W_i} f(v_i, v_j) q(v_j|v_i) \frac{\alpha^{D_{ij}} \text{BC}(v_j)}{\sum_{v_k \in W_i} \alpha^{D_{ik}} \text{BC}(v_k)} \tag{9}$$

where α is a hyper-parameter of the weight decay coefficient on paths.

Reminiscent of previous discussions on relating maximizing co-occurrence likelihood with matrix factorization, we demonstrate the connection between the above intuitive design and graph shortest distance metric. As we perform distance resampling for walk paths, the objective to learn an optimal node embedding is therefore interpreted as

$$
\begin{aligned}
\arg\max_{\mathbf{Z}} & \mathbb{E}_{\mathbf{v}_x \sim p}[f(\mathbf{Z}_i, \mathbf{Z}_j)] \\
& = \sum_{v_i \in V} p(v_i) \mathbb{E}_{v_j \sim p(\hat{\mathcal{W}}_i)}[p(v_j|v_i)(\log \sigma(\mathbf{Z}_i \mathbf{Z}_j^T) + \lambda \mathbb{E}_{v_k \sim p_N(v_k|v_i)}[\log \sigma(-\mathbf{Z}_i \mathbf{Z}_k^T)])]
\end{aligned}
\tag{10}
$$

Thereinto, $f(\mathbf{Z}_i, \mathbf{Z}_j) = \log \sigma(\mathbf{Z}_i \mathbf{Z}_j^T)$, $p_N(v_k|v_i)$ is the distribution of negative sampling. In our algorithm, p_N can be specified as a weighted random sampling over all occurred nodes in W_i (simulated based on Equation 5) by occurrence frequency, i.e.,

$$
p_N(v_k|v_i) = \frac{\#(v_k \text{ occurs in } W_i)}{\#(W_i)}
\tag{11}
$$

where $\#(\cdot)$ is a counting function indicating the number of occurrence times of specified nodes, i.e., the cardinality of a sampled set.

Proposition 1. *Define $G = (V, E)$ as an undirected graph. $Z_{|V| \times d}$ is the embedding matrix of V corresponding to maximizing likelihood objective $\mathbb{E}_{\mathbf{v}_x \sim p}[f(\mathbf{Z}_i, \mathbf{Z}_j)]$ defined in Equation 10. $p_N(v_b|v_a)$ is the negative sampling distribution of v_b from W_a simulated by Equation 11. Let the weight decay coefficient in distance resampling be α, $0 < \alpha < 1$. Then, the inner product of embedding matrix corresponds to a global distance matrix, i.e. $ZZ^T = \hat{D}$. For any v_a and any v_b that is n-hops away from v_a, the distance between them in the embedding space varies linearly with respect to distance n, namely,*

$$
\hat{D}_{ab} = n \log \alpha - \log A
\tag{12}
$$

where A is a constant independent of v_b.

Proposition 1 is proved in Appendix A.3.

Proposition 1 indicates that optimization of Equation 10 conforms to reconstruct a global distance matrix where nodes far away from each other in the graph under shortest distance metric(i.e., large D_{ab}) should be mapped with large distance in the embedding space(i.e., large $\hat{D}_{ab}$). We can also conclude that $\hat{D}_{ab}$ varies linearly with respect to the distance n between two nodes, while A is a constant independent of v_b but related to v_a, which means when we fix the source (or destination) node as v_a, any destination (or source) node v_b's distance with v_a could be compared with each other (we call that distance is measurable with respect to calibrated node v_a).

Consider the preservation of shortest distance relation. Some studies on metric learning (Hermans et al., 2017; Zeng et al., 2020) have revealed that a tuple of samples (v_a, v_b, v_c) being easy to learn means if v_b shares strong correlation with v_a, the distance between v_b and v_a in the embedding space should be shorter than that of v_c and v_a. With this property, we have the following theorem, which indicates that our method is consistent with distance relation under intrinsic graph metric. This will be used in the prediction task described next.

Theorem 2. *Each symbol here follows the definition in Proposition 1. Let D be a global distance matrix defined on graph G and D_{ab} be graph's shortest distance between node v_a and v_b. Then for any nodes $v_a, v_b, v_c \in G$,*

$$
(D_{ab} - D_{ac})(|\hat{D}_{ab}| - |\hat{D}_{ac}|) \geq 0
\tag{13}
$$

The proof is presented in Appendix A.4.

3.3 ALGORITHM

Our BCDR algorithm is presented in Algorithm 1. It contains three steps. First, pre-computation of the BC value (line 21) is required for each node on the graph. Second, for each node v_i, we sample a batch of walk paths P_i guided by the BC value according to Section 3.1 (line 1 to 20). Meanwhile,

Table 2: Statistics of graph datasets and their train & validation & test sets.

RoBC-range of BC, mBC-mean of BC, L-landmark nodes, $\mathcal{T}$-train set, $\mathcal{V}$-validation set, $\mathcal{E}$-test set.

	$|V|$	$|E|$	$|E|/|V|$	Diameter	RoBC	mBC	$|L|$	$|\mathcal{T}|$	$|\mathcal{V}|$	$|\mathcal{E}|$
Cora	$2,708$	$10,787$	3.9834	21	375.20	2.7174	100	$100 \times |V|$	800×30	$1,600 \times 10$
Facebook	$4,039$	$176,437$	21.846	8	$1,306.9$	0.89931	100	$100 \times |V|$	800×50	$1,600 \times 20$
GrQc	$5,242$	$30,042$	5.7310	17	148.43	2.7219	100	$200 \times |V|$	800×70	$1,600 \times 30$

distance relation of each node with v_i is also recorded for subsequent resampling. Third, for each node v_i, we resample nodes in W_i by their distances with v_i and BC values to formulate $\mathring{P}_i$ (line 25 to 34), which is optimized by maximizing pair-wise co-occurrence likelihood (line 37). This embedding algorithm takes $O(w_{out}l_{out}^2|V|\log|V|+(w_{in}l_{in}+w_{out}l_{out})|V|)$ of time complexity and $O((w_{in}l_{in}+w_{out}l_{out})|V|)$ of space complexity for any sparse graph (detailed analysis is presented in Appendix A.5). The above result reveals a feasible way of reducing time complexity by just taking larger $w_{in}l_{in}$ and smaller $w_{out}l_{out}$ in BCDR. This practice is applied in our experiments.

Algorithm 1: BCDR Embedding Algorithm

Input: input graph $G = (V, E)$, embedding size d, input sample size w_{in}, output sample size w_{out}, input walk length l_{in}, output walk length l_{out}, distance weight decay α, use smoothed normalization τ.

1 **Def** BC_Walk $(G, v_i, D_i, w_{in}, l_{in}, \tau)$:
2 **for** walk k from 0 to w_{in} **do**
3   visit sign set $S_i := \{v_i\}$, current node $v_c := v_i$, length $c_i := 0$, real length $c_i^r := 0$
4   **while** $c_i < l_{in}$ **do**
5          $\mathcal{N}_c^k := \{v_j|v_j \in \mathcal{N}_c \wedge v_j \notin S_i\}$
6   **if** τ is True **then**
7   normalize $p_{c \to j} \leftarrow \text{softmax}(\gamma_j + 1), v_j \in \mathcal{N}_c^k$
8   **else**
9   normalize $p_{c \to j} \leftarrow \frac{\gamma_j}{\sum_{v_m \in \mathcal{N}_c^k} \gamma_m}, v_j \in \mathcal{N}_i^k$
10   **end**
11   sample next v_n from $\mathcal{N}_c^k$ by $p_{c \to j}$
12   **if** $v_n \in D_i$ **then**
13             $D_i[v_n] = \min\{D_i[v_n], c_i^r + 1\}$
14             $c_i^r = \min\{D_i[v_n] - 1, c_i^r\}$
15   **else**
16             $D_i[v_n] = c_i^r + 1$
17   **end**
18         $v_c \leftarrow v_n$, $S_i \leftarrow v_n$, $c_i \leftarrow c_i + 1$, $c_i^r \leftarrow c_i^r + 1$
19   **end**
20 **end**

21 pre-compute BC of each node v_i as $\gamma_i \leftarrow \text{BC}(v_i)$.
22 Walk path set P
23 **for** v_i in G **do**
24   distance map $D_i := \{v_i : 0\}$
25     $D_i \leftarrow$ BC_Walk $(G, v_i, D_i, w_{in}, l_{in}, \tau)$
26   **for** $v_j \in D_i.keys$ **do**
27   **if** τ is True **then**
28             $\gamma_j' \leftarrow \text{softmax}(\gamma_j + 1)$
29             $p(v_j|v_i) := \alpha^{D_i[v_j]} \cdot \gamma_j'$
30   **else**
31             $p(v_j|v_i) := \alpha^{D_i[v_j]} \cdot \gamma_j$
32   **end**
33   **end**
34   sample walk paths $P_i = \{(v_i, v_{x_1}, v_{x_2}, \cdots, v_{x_j}, \cdots)\}$ of length l_{out} by
             $p(v_{x_j}|v_i)$, $v_{x_j} \in D_i.keys$ for w_{out} times.
35   append P_i into P
36 **end**
37 maximize Equation 10 by P.
38 **return** Z

---

4 EXPERIMENTAL EVALUATION

In this section, we evaluate our model's performance with several graph datasets and compare it with conventional embedding-based methods for SDQ tasks.

4.1 DATASETS

We test our model using three real-world graph datasets as well as some simulated datasets. As this paper focuses on the shortest distance prediction of connected and undirected graphs, we make a trivial change for some directed graphs by simply eliminating the direction of each edge. For graphs with multiple connected components, we repeatedly add one edge between two unconnected components until the whole graph is connected. The graphs we use are of complex inner connections and divergent diameters. The basic information of these datasets is outlined in Table 2 (columns 2 to 7). The detailed information is presented in Appendix A.6.

Since SDQ is a prediction problem requiring inputs of graph structures, we define $\mathcal{T}$, $\mathcal{V}$, and $\mathcal{E}$ as datasets for train, validation, and test, respectively. Each of them is composed of (v_i, v_j, D_{ij}). As simulations of the above sets in huge graphs have to be of $O(|V|)$ or less complexity, in our experiments, we initially select a group $\mathcal{S}$ of nodes as sources, and for each source $v_i \in \mathcal{S}$, a destination set $\mathcal{D}$ with their shortest distances to the source is randomly collected. Then, $|\mathcal{S}| \times |\mathcal{D}_i|$ input node pairs are simulated. The detailed setup for each dataset is presented in Table 2 (columns 8 to 11).

4.2 PARAMETER SETUP

We compare our method with conventional graph embedding models based on random walk as well as matrix factorization (see Appendix A.7). We simulate 40 walks on each node for random walk-based methods, and each walk is truncated at a length of 40. Sliding window size and negative

Table 3: Performance comparison of embedding-based models

	Cora		Facebook		GrQc	
	mAE	mRE	mAE	mRE	mAE	mRE
LLE	5.6265 ± 0.0490	0.8445 ± 0.0096	1.9921 ± 0.0731	0.6841 ± 0.0029	4.8849 ± 0.1034	0.7105 ± 0.0165
GF	5.6249 ± 0.0876	0.8440 ± 0.0142	1.8743 ± 0.0717	0.6383 ± 0.0284	4.8562 ± 0.0516	0.7125 ± 0.0084
LE	5.6393 ± 0.0782	0.8455 ± 0.0132	2.0312 ± 0.0625	0.6998 ± 0.0248	5.0046 ± 0.0242	0.7366 ± 0.0044
DeepWalk	1.5183 ± 0.0654	0.2425 ± 0.0101	0.9323 ± 0.0272	0.3289 ± 0.0137	2.8002 ± 0.1479	0.4169 ± 0.0227
Node2Vec	1.3072 ± 0.0236	0.2115 ± 0.0038	0.8541 ± 0.0436	0.2993 ± 0.0166	1.5156 ± 0.0691	0.2278 ± 0.0087
DADL	1.1349 ± 0.0180	0.1790 ± 0.0031	0.6150 ± 0.0325	0.2279 ± 0.0135	1.3624 ± 0.1366	0.2033 ± 0.0183
BCDR	$\mathbf{0.9768 \pm 0.0245}$	$\mathbf{0.1605 \pm 0.0043}$	$\mathbf{0.4804 \pm 0.0406}$	$\mathbf{0.1770 \pm 0.0156}$	$\mathbf{1.0490 \pm 0.0634}$	$\mathbf{0.1684 \pm 0.0058}$

| (a) | (b) | (c) | (d) |

Figure 2: Exploration distance of different random walk strategies tested on graph $TG(20, 1, 3, 10)$. **(a):** general random walk in DeepWalk. **(b):** Node2Vec. **(c):** Random Surfing. **(d)**: BC-based random walk(ours.).

sampling size are fixed at 20 and 5, respectively, for each dataset. Node2Vec takes hyper-parameter $p = q = 1$. Regularization r of GF is set to 1.0. DADL takes the Hadamard operator for embedding aggregation. Like previous research (Zhuang & Ma, 2018), linear regression is utilized as a predictor for general graph embedding models.

For our model, we take the same configuration as previous random walk-based models using input walk length $l_{in} = 40$ and input sample size $w_{in} = 40$. In order to keep complexity of parameters equal to or even less than that of baselines, the multiplication of output length l_{out} and output sample size w_{out} is fixed at 40, with $l_{out} = 10, w_{out} = 4$ for Cora and GrQc and $l_{out} = 40, w_{out} = 1$ for Facebook. Meanwhile, the weight decay coefficient α is set to 0.1 for Cora and GrQc datasets and 0.98 for Facebook. To avoid dramatically unbalanced values of BC, we also take smoothed normalization ($\tau = True$) in all datasets except Facebook. Finally, all of the above models use the Adam optimizer with a learning rate $\epsilon_r = 1e - 4$ for training, and embedding dimension d is fixed at 16 for every dataset.

4.3 PERFORMANCE OF PREDICTION ACCURACY

To compare embedding-based methods, we train each model on each dataset up to 500 iterations and save the results every 10 epochs. The best models are selected by their mAE and mRE scores on validation set $\mathcal{V}$. Each model is evaluated 5 times independently on each dataset, and their average performance is recorded. The resulting mAE and mRE are reported in Table 3. We can see from the table that our model outperforms previous models significantly for all the three datasets.

4.4 RESULT OF EXPLORATION DISTANCE

As stated in Section 3.1, exploration distance under intrinsic graph metric plays an indispensable role in modeling a wider range of node correlation. Here, we compare our BC-based random walk with existing renowned walk strategies, including DeepWalk (Perozzi et al., 2014; Zhuang & Ma, 2018), Node2Vec (Grover & Leskovec, 2016), and Random Surfing (Cao et al., 2016). We use $TG(20, 1, 3, 10)$ as a test graph of large diameters. We randomly sample 20 root nodes and, for each root, simulate 10 walks with length 10 to show how many nodes in different order proximity are visited. The ideal situation for a batch of walk paths with length l is to cover up to nodes $l - hop$ away from the current root. The results are shown in Figure 2. From the figure, we can see that our BC-based walk is much more competitive regarding exploration distance.

Figure 3: Distance relation during mappings when taking different random walk strategies. **(a):** general random walk in DeepWalk. **(b):** Node2Vec. **(c):** Random Surfing. **(d):** BCDR(ours.).

Figure 4: Distance preservation in the embedding spaces of different models. **(a):** general random walk in DeepWalk. **(b):** Node2Vec. **(c):** Random Surfing. **(d):** BCDR(ours.).

4.5 PRESERVATION OF DISTANCE RELATION

We have also evaluated the property of shortest distance preservation during the mapping from the original graph space into embedded vector space. First, we test distance variation in the embedding space when adjusting the shortest distance between nodes on the graph, taking the same configuration of simulation dataset as $\text{TG}(20, 1, 3, 10)$. Distance in the embedding space is measured by inner product $\mathbf{Z}_i\mathbf{Z}_j^T$ for any node v_i and v_j. We initially train embedding vectors using walks simulated by each model and randomly sample 20 source nodes with 100 destinations for each source. The results are shown in Figure 3, which indicates that our model has a better tendency to maintain a linear distance relation for the mapping.

Second, we try to find out how much the probability distance relation is violated in the embedding space. We randomly take 10000 node triple (v_a, v_b, v_c), and record if they violate Equation 13. The results are shown in Figure 4. The figure confirms that our model is much more satisfactory in preserving distance relation during mappings.

5 CONCLUSION

In this paper, we propose a novel graph shortest distance embedding method called Betweenness Centrality-based Distance Resampling (BCDR). It improves the graph embedding for the shortest distance representation with two components we propose in this paper. The first is Betweenness Centrality-based random walk to accommodate long-distance correlation on graphs by covering a wider range of nodes under the intrinsic graph metric. The second is a distance resampling strategy to preserve shortest distances during the mapping from graph to the embedding space via reconstructing a global distance matrix. The experimental evaluation indicates that BCDR possesses a better capacity than existing graph embedding methods to extract distance structure from original graphs. BCDR can be integrated into graph-based learning models (especially in graph neural networks), which should improve their performance on graph structure recognition. This will be our future work.

REFERENCES

Principal Component Analysis and Factor Analysis, pp. 150–166. Springer New York, New York, NY, 2002. ISBN 978-0-387-22440-4. doi: 10.1007/0-387-22440-8_7. URL https://doi.org/10.1007/0-387-22440-8_7.

A. Ahmed, N. Shervashidze, S. Narayanamurthy, V. Josifovski, and A. J. Smola. Distributed large-scale natural graph factorization. In *Proceedings of the 22nd international conference on World Wide Web*, pp. 37–48, 2013.

S. Baswana and T. Kavitha. Faster algorithms for approximate distance oracles and all-pairs small stretch paths. In *2006 47th Annual IEEE Symposium on Foundations of Computer Science (FOCS'06)*, pp. 591–602, Oct 2006. doi: 10.1109/FOCS.2006.29.

David M Blei, Andrew Y Ng, and Michael I Jordan. Latent dirichlet allocation. *the Journal of machine Learning research*, 3:993–1022, 2003.

Ulrik Brandes and Christian Pich. Centrality Estimation in Large Networks. *International Journal of Bifurcation and Chaos*, 17(7):2303, January 2007. doi: 10.1142/S0218127407018403.

Shaosheng Cao, Wei Lu, and Qiongkai Xu. Deep neural networks for learning graph representations. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 30, 2016.

Jason Carlton. The shortest distance between two people is a story: Storytelling best practices in digital and social media marketing. *Journal of Digital & Social Media Marketing*, 8(2):108–115, 2020.

Yu Chen, Hanchao Ku, and Mingwu Zhang. Pp-ocq: A distributed privacy-preserving optimal closeness query scheme for social networks. *Computer Standards & Interfaces*, 74:103484, 2021.

Mária Ercsey-Ravasz and Zoltán Toroczkai. Centrality scaling in large networks. *Physical review letters*, 105(3):038701, 2010.

Lucia Galovičová, Petra Borotová, Veronika Valková, Nenad L Vukovic, Milena Vukic, Jana Štefániková, Hana Ďuranová, Przemysław Łukasz Kowalczewski, Natália Čmiková, and Miroslava Kačániová. Thymus vulgaris essential oil and its biological activity. *Plants*, 10(9): 1959, 2021.

Rainer Gemulla, Erik Nijkamp, Peter J Haas, and Yannis Sismanis. Large-scale matrix factorization with distributed stochastic gradient descent. In *Proceedings of the 17th ACM SIGKDD international conference on Knowledge discovery and data mining*, pp. 69–77, 2011.

A. Grover and J. Leskovec. node2vec: Scalable feature learning for networks. In *the 22nd ACM SIGKDD International Conference*, 2016.

A. Gubichev, S. Bedathur, S. Seufert, and G. Weikum. Fast and accurate estimation of shortest paths in large graphs. In *Proceedings of the 19th ACM Conference on Information and Knowledge Management, CIKM 2010, Toronto, Ontario, Canada, October 26-30, 2010*, 2010.

Peter E Hart, Nils J Nilsson, and Bertram Raphael. A formal basis for the heuristic determination of minimum cost paths. *IEEE transactions on Systems Science and Cybernetics*, 4(2):100–107, 1968.

Alexander Hermans, Lucas Beyer, and Bastian Leibe. In defense of the triplet loss for person re-identification. *arXiv preprint arXiv:1703.07737*, 2017.

Shijie Jiang, Yang Wang, Guang Lu, and Chuanwen Li. Dlsm: Distance label based subgraph matching on gpu. In *Asia-Pacific Web (APWeb) and Web-Age Information Management (WAIM) Joint International Conference on Web and Big Data*, pp. 194–200. Springer, 2021.

Jure Leskovec and Andrej Krevl. SNAP Datasets: Stanford large network dataset collection. http://snap.stanford.edu/data, June 2014.

Omer Levy and Yoav Goldberg. Neural word embedding as implicit matrix factorization. *Advances in neural information processing systems*, 27:2177–2185, 2014.

Vardges Melkonian et al. Mathematical models for a social partitioning problem. *American Journal of Computational Mathematics*, 11(01):1, 2021.

Tomas Mikolov, Kai Chen, Greg Corrado, and Jeffrey Dean. Efficient estimation of word representations in vector space. *arXiv preprint arXiv:1301.3781*, 2013a.

Tomas Mikolov, Ilya Sutskever, Kai Chen, Greg S Corrado, and Jeff Dean. Distributed representations of words and phrases and their compositionality. In *Advances in neural information processing systems*, pp. 3111–3119, 2013b.

Ruksar Parveen and N Sandeep Varma. Friend's recommendation on social media using different algorithms of machine learning. *Global Transitions Proceedings*, 2021.

B. Perozzi, R. Al-Rfou, and S. Skiena. Deepwalk: Online learning of social representations. *Proceedings of the ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*, 03 2014. doi: 10.1145/2623330.2623732.

Bayu Rahmad Syah, Mahyuddin Nasution, Erna Nababan, and Syahril Efendi. Sensitivity of shortest distance search in the ant colony algorithm with varying normalized distance formulas. *TELKOMNIKA Indonesian Journal of Electrical Engineering*, 19:1251–1259, 08 2021. doi: 10.12928/TELKOMNIKA.v19i4.18872.

Fatemeh Salehi Rizi, Joerg Schloetterer, and Michael Granitzer. Shortest path distance approximation using deep learning techniques. In *2018 IEEE/ACM International Conference on Advances in Social Networks Analysis and Mining (ASONAM)*, pp. 1007–1014. IEEE, 2018.

S. T. Roweis and L. K. Saul. Nonlinear dimensionality reduction by locally linear embedding. *science*, 290(5500):2323–2326, 2000.

A. D. Sarma, S. Gollapudi, M. Najork, and R. Panigrahy. A sketch-based distance oracle for web-scale graphs. In *Proceedings of the Third International Conference on Web Search and Web Data Mining, WSDM 2010, New York, NY, USA, February 4-6, 2010*, 2010.

C. Shaosheng, L. Wei, and X. Qiongkai. Grarep: Learning graph representations with global structural information. In *Proceedings of the 24th ACM international on conference on information and knowledge management*, pp. 891–900, 2015.

A. F. M. Smith and A. E. Gelfand. Bayesian statistics without tears: A sampling–resampling perspective. *The American Statistician*, 46(2):84–88, 1992. doi: 10.1080/00031305.1992.10475856. URL https://doi.org/10.1080/00031305.1992.10475856.

Marcus Sokolowski and Danuta Wasserman. A candidate biological network formed by genes from genomic and hypothesis-free scans of suicide. *Preventive Medicine*, 152:106604, 2021.

Christian Sommer. Shortest-path queries in static networks. *ACM Computing Surveys (CSUR)*, 46 (4):1–31, 2014.

J. B. Tenenbaum, V. De Silva, and J. C. Langford. A global geometric framework for nonlinear dimensionality reduction. *science*, 290(5500):2319–2323, 2000.

M. Thorup and U. Zwick. Approximate distance oracles. *Journal of the Acm*, 52(1), 2004.

Ye Wang, Qing Wang, Henning Koehler, and Yu Lin. Query-by-sketch: Scaling shortest path graph queries on very large networks. In *Proceedings of the 2021 International Conference on Management of Data*, pp. 1946–1958, 2021.

Fang Wei. Tedi: efficient shortest path query answering on graphs. In *Graph Data Management: Techniques and Applications*, pp. 214–238. IGI global, 2012.

Z. Xiaohan, A. Sala, C. Wilson, Z. Haitao, and Z. Ben Y. Orion: Shortest path estimation for large social graphs. In *Proceedings of the 3rd Wonference on Online Social Networks*, WOSN'10, pp. 9, USA, 2010. USENIX Association.

Z. Xiaohan, A. Sala, Z. Haitao, and Z. Ben. Fast and scalable analysis of massive social graphs. *CoPR*, 07 2011.

Yiding Yang, Xinchao Wang, Mingli Song, Junsong Yuan, and Dacheng Tao. Spagan: Shortest path graph attention network. *arXiv preprint arXiv:2101.03464*, 2021.

Huilin Yuan, Jianlu Hu, Yufan Song, Yanke Li, and Jie Du. A new exact algorithm for the shortest path problem: An optimized shortest distance matrix. *Computers & Industrial Engineering*, 158: 107407, 2021.

Xiang Yue, Zhen Wang, Jingong Huang, Srinivasan Parthasarathy, Soheil Moosavinasab, Yungui Huang, Simon M Lin, Wen Zhang, Ping Zhang, and Huan Sun. Graph embedding on biomedical networks: methods, applications and evaluations. *Bioinformatics*, 36(4):1241–1251, 10 2019. ISSN 1367-4803. doi: 10.1093/bioinformatics/btz718. URL https://doi.org/10.1093/bioinformatics/btz718.

Abeer A Zaki, Nesma A Saleh, and Mahmoud A Mahmoud. Performance comparison of some centrality measures used in detecting anomalies in directed social networks. *Communications in Statistics-Simulation and Computation*, pp. 1–15, 2021.

Kaiwei Zeng, Munan Ning, Yaohua Wang, and Yang Guo. Hierarchical clustering with hard-batch triplet loss for person re-identification. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 13657–13665, 2020.

Chenyi Zhuang and Qiang Ma. Dual graph convolutional networks for graph-based semi-supervised classification. In *Proceedings of the 2018 World Wide Web Conference*, pp. 499–508, 2018.

A APPENDIX

A.1 CONNECTIONS TO MDS

Our algorithm also shares some connection with conventional MDS methods in global distance metric. Take a view of original MDS. Input data X distributes in agnostic high-dimensional euclidean space and mutual distance between samples is extractable as a global distance matrix D^X. A approximate distance matrix D^Y calculated by embedding matrix Y endeavor to be optimized closest t oD^X by Frobenius norm, i.e.,

$$\min_Y \|D^X - D^Y\|_F^2 = \|D^X - YY^T\|_F^2 \tag{14}$$

Here, we suppose D^X and Y have been double-centered for stability, and finally, Y could be deduced as the group of top-d leading eigenvectors in D^X. Then, as a non-linear version of MDS, Isomap(Tenenbaum et al., 2000) generalizes D^X as distribution on a manifold and utilizes short hops to measure the mutual distance between samples. Deriving from the above idea, we regard the global distance matrix D^X as a canonical metric on graphs and exert embedding matrix $Z_{|V|\times d}$ to reconstruct it. Different from previous work, we encounter prohibitive complexity to acquire all elements in D^X and leverage an iterative process to approximately minimize the accuracy loss between D^Z and D^X.

A.2 PROOF OF THEOREM 1

Proof. We simplify symbols $N_h(v_a), e_h(v_a), f_h(v_a)$ as N_h, e_h, f_h for short. Define the eccentricity of v_a in graph G is $\mathcal{E}(v_a) = \max_{v_b \in G} D_{ab}$ and

$$\begin{aligned}
\overrightarrow{N}_h &= \#\left(\bigcup_{i=h}^{\min\{\mathcal{E}(v_a), h+k-1\}} \{v_j | v_j \in \mathcal{N}_a^{(i)}\} \right) \\
\overleftarrow{N}_h &= \#\left(\bigcup_{i=\max\{0, h-k+1\}}^{h} \{v_j | v_j \in \mathcal{N}_a^{(i)}\} \right)
\end{aligned} \tag{15}$$

According to definition in the theorem, we have $N_h = e_h + f_h$. Since only e_h nodes could travel from N_h to N_{h+1}, We firstly consider $P_R(e_h \rightarrow e_{h+1} | e_h \rightarrow N_{h+1})$ and $P_B(e_h \rightarrow e_{h+1} | e_h \rightarrow N_{h+1})$.

For general random walk, the choice of destination is based on uniform sampling, thus causing

$$P_R(e_h \rightarrow e_{h+1} | e_h \rightarrow N_{h+1}) = \frac{e_{h+1}}{N_{h+1}} \tag{16}$$

For BC-based random walk, we need calculate BC value of e_{h+1} and f_{h+1} nodes for starters. Let $BC(e_{h+1})$ and $BC(f_{h+1})$ represent the BC value of nodes in e_{h+1} and f_{h+1} respectively, and the correspond legal shortest path counts comes from 4 sources as $\{\overleftarrow{N}_h \rightarrow \overrightarrow{N}_{h+2}\}$, $\{\overleftarrow{N}_h \rightarrow N_{h+1}\}$, $\{N_{h+1} \rightarrow \overrightarrow{N}_{h+2}\}$ and $\{N_{h+1} \rightarrow N_{h+1}\}$. And we use $BC(\{\cdot \rightarrow \cdot\})$ as the BC gain from the specified source, then

$$
\begin{aligned}
BC(\{\overleftarrow{N}_h \rightarrow \overrightarrow{N}_{h+2}\}) &= \overleftarrow{N}_h \overrightarrow{N}_{h+2} \\
BC(\{\overleftarrow{N}_h \rightarrow N_{h+1}\}) &= \overleftarrow{N}_h(f_{h+1} \cdot 0 + e_{h+1}\beta_e^{(1)}) \\
BC(\{N_{h+1} \rightarrow \overrightarrow{N}_{h+2}\}) &= \overrightarrow{N}_{h+2}(f_{h+1} \cdot 1 + e_{h+1}\beta_e^{(1)}) \\
BC(\{N_{h+1} \rightarrow N_{h+1}\}) &= N_{h+1}^2 \beta_e^{(2)}
\end{aligned}
\tag{17}
$$

where $\beta_e^{(1)}$ means average BC gain between nodes in e_{h+1} and $\overrightarrow{N}_{h+2}$, and $\beta_e^{(2)}$ means average BC gain between nodes both in e_{h+1}, which are constantly related with G. Therefore, we have

$$BC(e_{h+1}) = \overleftarrow{N}_h \overrightarrow{N}_{h+2} + (\overleftarrow{N}_h + \overrightarrow{N}_{h+2})e_{h+1}\beta_e^{(1)} + \overrightarrow{N}_{h+2}f_{h+1} + N_{h+1}^2\beta_e^{(2)} \tag{18}$$

Likewise, we calculate

$$
\begin{aligned}
BC(f_{h+1}) &= \overleftarrow{N}_h \overrightarrow{N}_{h+2} \cdot 0 + \overleftarrow{N}_h(f_{h+1}\beta_f^{(1)} + e_{h+1} \cdot 0) + \overrightarrow{N}_{h+2}(f\beta_f^{(1)} + e_{h+1} \cdot 0) + N_{h+1}^2\beta_e^{(2)} \\
&= (\overleftarrow{N}_h + \overrightarrow{N}_{h+2})\beta_f^{(1)} + N_{h+1}^2\beta_f^{(2)}
\end{aligned}
\tag{19}
$$

To compare the above $BC(e_{h+1})$ and $BC(f_{h+1})$,

$$\frac{BC(f_{h+1})}{BC(e_{h+1})} = \frac{(\overleftarrow{N}_h + \overrightarrow{N}_{h+2})\beta_f^{(1)} + N_{h+1}^2\beta_f^{(2)}}{\overleftarrow{N}_h \overrightarrow{N}_{h+2} + (\overleftarrow{N}_h + \overrightarrow{N}_{h+2})e_{h+1}\beta_e^{(1)} + \overrightarrow{N}_{h+2}f_{h+1} + N_{h+1}^2\beta_e^{(2)}} \tag{20}$$

note that for any N_j and $N_{(x,y)} = \overrightarrow{N}_0 - \overleftarrow{N}_x - \overrightarrow{N}_y$ where $j, x, y \in \{0, \mathcal{E}(v_a)\}$,

$$\lim_{k \rightarrow \infty} \frac{N_j}{N_{(x,y)}} = \lim_{k \rightarrow \infty} \epsilon(k) = 0 \tag{21}$$

Equation 19 is reduced to

$$\frac{BC(f_{h+1})}{BC(e_{h+1})} = \frac{2\epsilon(k)\beta_f^{(1)} + \epsilon(k^2)\beta_f^{(2)}}{1 + 2\epsilon(k)ne_{h+1}\beta_e^{(1)} + \epsilon(k)f_{h+1} + \epsilon(k^2)\beta_e^{(2)}} = 2\beta_f^{(1)}\epsilon(k) \tag{22}$$

Then, we perform weighted random sampling based on BC and get

$$p_B(e_h \rightarrow e_{h+1} | e_h \rightarrow N_{h+1}) = \frac{e_{h+1}}{e_{h+1} + 2f_{h+1}\beta_f^{(1)}\epsilon(k)} \tag{23}$$

Now, we consider the relation between $P_R(N_h \to e_{h+1}|N_h \to N_{h+1})$ and $P_B(N_h \to e_{h+1}|N_h \to N_{h+1})$.

$$
\begin{aligned}
\frac{p_B(N_h \to N_{h+1})}{p_R(N_h \to N_{h+1})} &= \frac{p_B(e_h)p_B(e_h \to N_{h+1})}{p_R(e_h)p_R(e_h \to N_{h+1})} \\
&= \frac{p_B(N_{h-1} \to e_h) + p_B(N_{h-1} \to f_h)p_B(f_h \to e_h)}{p_R(N_{h-1} \to e_h) + p_R(N_{h-1} \to f_h)p_R(f_h \to e_h)} \\
&= 1 + \frac{[p_B(N_{h-1} \to e_h) - p_R(N_{h-1} \to e_h)][1 - p_R(f_h \to e_h)]}{p_R(N_{h-1} \to e_h) + p_R(N_{h-1} \to f_h)p_R(f_h \to e_h)} \\
&\quad + \frac{p_R(f_h \to e_h)\epsilon}{p_R(N_{h-1} \to e_h) + p_R(N_{h-1} \to f_h)p_R(f_h \to e_h)} \\
&= 1 + \frac{f_h[1 - 2f_h\beta_f^{(1)}\epsilon(k)][1 - p_R(f_h \to e_h)]}{(1 + \frac{f_h}{e_h})[e_h + 2f_h\beta_f^{(1)}\epsilon(k)]p_R(f_h \to e_h)} \\
&\quad + \frac{p_R(f_h \to e_h)\epsilon}{p_R(N_{h-1} \to e_h) + p_R(N_{h-1} \to f_h)p_R(f_h \to e_h)}
\end{aligned}
\tag{24}
$$

Let $C = \frac{p_R(f_h \to e_h)\epsilon}{p_R(N_{h-1} \to e_h) + p_R(N_{h-1} \to f_h)p_R(f_h \to e_h)}$, $B(k) = \frac{f_h[1 - 2f_h\beta_f^{(1)}\epsilon(k)][1 - p_R(f_h \to e_h)]}{(1 + \frac{f_h}{e_h})[e_h + 2f_h\beta_f^{(1)}\epsilon(k)]p_R(f_h \to e_h)}$. Since C is a non-negative value independent of k, finally we get

$$
\frac{p_B(N_h \to N_{h+1})}{p_R(N_h \to N_{h+1})} = 1 + B(k) + C
\tag{25}
$$

where

$$
\lim_{k \to \infty} B(k) + C = \frac{A_2 - 1}{A_1} + C.
\tag{26}
$$

$\square$

A.3 PROOF OF PROPOSITION 1

Proof. Initially, we rewrite the negative sampling item of Equation 10 as

$$
\begin{aligned}
\mathbb{E}_{v_k \sim p_N(v_k|v_i)}[\log \sigma(-\mathbf{Z}_i\mathbf{Z}_k^T)]) &= \sum_{v_k \in W_i} p_N(v_k|v_i)[\log \sigma(-\mathbf{Z}_i\mathbf{Z}_k^T)] \\
&= p_N(v_j|v_i)[\log \sigma(-\mathbf{Z}_i\mathbf{Z}_j^T)] + \sum_{v_k \in W_i \setminus \{v_j\}} p_N(v_k|v_i)[\log \sigma(-\mathbf{Z}_i\mathbf{Z}_k^T)]
\end{aligned}
\tag{27}
$$

Then, for each pair of $v_i \in V$ and $v_j \in W_i$, we get independent objective by combing similar items in overall likelihood expression $\mathbb{E}_{\mathbf{v}_x \sim p}[f(\mathbf{Z}_i, \mathbf{Z}_j)]$, and get

$$
\begin{aligned}
\mathbb{E}_{\mathbf{v}_x \sim p}[f(\mathbf{Z}_i, \mathbf{Z}_j)] &= \sum_{v_i \in V} \sum_{v_j \in W_i} \mathcal{L}(v_i, v_j) \\
\mathcal{L}(v_i, v_j) &= p(v_i, v_j) \log \sigma(-\mathbf{Z}_i\mathbf{Z}_j^T) + \lambda p(v_i)p_N(v_j|v_i) \log \sigma(-\mathbf{Z}_i\mathbf{Z}_j^T)
\end{aligned}
\tag{28}
$$

Let $\hat{D} = ZZ^T$, for each node pair (v_a, v_b) with mutual shortest distance $\hat{D}_{ab}$, consider

$$
\hat{D}_{ab} = \mathbf{Z}_a\mathbf{Z}_b^T = \arg\max_{\mathbf{Z}_a, \mathbf{Z}_b} \mathcal{L}(v_a, v_b)
\tag{29}
$$

Suppose v_b is n-hops away from v_a, and denote $BC(v_b)$ by γ_b, according to Equation 5,

$$
p(v_a, v_b) = p(v_a) \cdot p(v_b|v_a) = p(v_a) \cdot \alpha^n \gamma_b
\tag{30}
$$

Note that $p_N(v_b|v_a)$ is a negative sampling in walk set W_a(Equation 11) which is selected by BC-based random walk locally restricted to v_a according to Equation 5, we have

$$
p_N(v_b|v_a) = \kappa(v_a)\gamma_b
\tag{31}
$$

where $\kappa(v_a)$ is related with the neighbor structure of v_a. Then, Equation 29 could be described as

$$\hat{D}_{ab} = \arg\max_{\hat{D}_{ab}} p(v_a)\alpha^n\gamma_b \log\sigma(\hat{D}_{ab}) + \lambda p(v_a)\kappa(v_a)\gamma_b \log\sigma(-\hat{D}_{ab}) \tag{32}$$

Solve the above problem by just let $\frac{\partial\mathcal{L}(v_a,v_b)}{\partial\hat{D}_{ab}}$ be equal to zero, i.e.,

$$\frac{\partial\mathcal{L}(v_a,v_b)}{\partial\hat{D}_{ab}} = p(v_a)\alpha^n\gamma_b\sigma(1-\hat{D}_{ab}) - \lambda p(v_a)\kappa(v_a)\gamma_b\sigma(1+\hat{D}_{ab}) = 0 \tag{33}$$

After some simplification, we get

$$\hat{D}_{ab} = n\log\alpha - \log\lambda\kappa(v_a) \tag{34}$$

Let $A = -\lambda\kappa(v_a)$ and there holds

$$\hat{D}_{ab} = n\log\alpha - \log A \tag{35}$$

$\square$

A.4 Proof of Theorem 2

Proof. Let v_b and v_c in graph be n and m-hops away from v_a respectively. In terms of node pair (v_a, v_b), as proved in Proposition 1, their mutual distance D_{ab} in the embedding space varies linear with respect to the graph shortest distance n, i.e.,

$$|\hat{D}_{ab}| = |n\log\alpha - \log A| = -n\log\alpha + \log A \tag{36}$$

Likewise, we have for (v_a, v_c)

$$|\hat{D}_{ac}| = |m\log\alpha - \log A| = -m\log\alpha + \log A \tag{37}$$

where $0 < \alpha < 1$ and A is independent of v_b and v_c. Then, consider the distance relation of v_a, v_b and v_c, there holds

$$(D_{ab} - D_{bc})(|\hat{D}_{ab}| - |\hat{D}_{bc}|) = (n-m)(m-n)\log\alpha = -\log\alpha \cdot (n-m)^2 \geq 0 \tag{38}$$

$\square$

A.5 Complexity Analysis of BCDR Embedding Algorithm

We analyze the complexity of Algorithm 1 as follows.

The first step depends on the algorithm used for BC calculation, wherein some approximation methods could reduce complexity to $O(|V|)$ or $O(|V|\log|V|)$(Brandes & Pich, 2007; Ercsey-Ravasz & Toroczkai, 2010). Then, in the second step, for each walk rooted at each node v_i(line 23), we use a loop(line 2 to 20) up to w_{in} times for generating nodes on the walk. Normalization of $p_{i\rightarrow j}$(line 5 to 18) is calculated for l_{in} times for each node, and summation of γ is up to $O(|E|)$ during the whole routine. Therefore, it takes totally $O(w_{in}l_{in}|V| + |E|)$ time complexity. Finally, as for the third step, line 26 to 33 re-weights explored area of every node v_i which need loops up to $w_{in}l_{in}|V|$ times. For the sake of resampling $w_{out}l_{out}$ nodes, line 34 also requires normalization by $O(w_{out}l_{out}|V|)$. Line 37 use a maximum likelihood optimization which occupies $O(w_{out}l_{out}^2|V|\log|V| + w_{out}l_{out}|V| + |E|)$ time complexity(Mikolov et al., 2013a). As for space complexity, distance map D_i and $p(v_j|v_i)$ are stored temporarily up to $O(w_{in}l_{in})$, while visit sign set S_i is up to $O(w_{in})$. For dumped and resampled walk paths, $O((w_{in}l_{in} + w_{out}l_{out})|V|)$ space is required. Finally, our embedding algorithm takes $O(w_{out}l_{out}^2|V|\log|V| + (w_{in}l_{in} + w_{out}l_{out})|V| + |E|)$ time complexity and $O((w_{in}l_{in} + w_{out}l_{out})|V|)$ space complexity. Especially, for sparse graph, time complexity is reduced to $O(w_{out}l_{out}^2|V|\log|V| + (w_{in}l_{in} + w_{out}l_{out})|V|)$.

A.6 Complementary Information of Datasets

This part provides detailed information about graph datasets we used, and presents some visualization result in Figure 5.

Figure 5: Visualization of graph datasets. **(a):** Cora. **(b):** Facebook. **(c):** GrQc. **(d), (e), (f):** TG$(20, 1, 3, 10)$.

A.6.1 CORA

Cora graph dataset describes the citation relationship of papers, which contains 2708 nodes and 10556 directed edges among them. Each node also has a predefined feature with 1433 dimensions.

A.6.2 FACEBOOK

Facebook dataset(Leskovec & Krevl, 2014) describes the relationship among Facebook users by their social circles(or friend lists), which is collected from a group of test users. Facebook has also encoded each user with a reindexed user ID to protect their privacy.

A.6.3 GRQC

Arxiv GR-QC (General Relativity and Quantum Cosmology) collaboration network(Leskovec & Krevl, 2014) is recorded from the e-print arXiv in the period from January 1993 to April 2003, which used to represent co-author relationship based on their submission. We suppose an undirected edge (v_i, v_j) if an author v_i co-authored a paper with another author v_j. If one paper is owned by k authors, a complete graph of k nodes is generated correspondingly.

A.6.4 TEST GRAPH (TG)

We define TG(cls, c, r, n) as a parameterized graph simulation for SDQ tasks. cls is the number of sub-graphs to represent communities, and n is the number of nodes in each community. c and r determine the inner and outer connectivity of each community, respectively. TG is guaranteed to be an undirected and connected graph in our experiment, which is also expected to be sparse and of large diameter. Some simulation results of TG$(20, 1, 3, 10)$ that we used in Section 4.4 and 4.5 are presented in Figure 5 (d), (e), (f).

A.7 BASELINE ALGORITHM

We outline all of the baseline models used in performance comparison as follows.

A.7.1 LLE

Locally Linear Embedding(LLE)(Roweis & Saul, 2000) is an effective method of dimensional reduction that preserves the local linear combination property of nodes. In contrast with previous PCA(Jol, 2002) and LDA(Blei et al., 2003) which are guaranteed to discover an optimal reduction in euclidean space, LLE that addresses local distance relation gives a more compact representation for non-linear manifolds.

A.7.2 LE

Analog to Laplace-Beltrami operator on manifolds, Laplacian Eigenmap(LE)(Roweis & Saul, 2000) leverages graph Laplacian matrix to generate embedding vectors. The objective of LE is to minimize mutual distance on edges by L_2 loss, which maps nodes with more first-order links closer to each other.

A.7.3 GF

Graph Factorization(GF)(Ahmed et al., 2013) utilize matrix factorization methods(Gemulla et al., 2011) to deal with graph structure exploration. By approximating graph adjacency matrix on a bundle of random nodes, GF is of high efficiency for large graphs.

A.7.4 DEEPWALK

DeepWalk(Perozzi et al., 2014) is a random walk-based embedding method of sub-linear complexity to represent graph structure. This method derives from skip-gram(Mikolov et al., 2013a) and negative sampling(Mikolov et al., 2013b) to learn each node representation by predicting its context.

A.7.5 NODE2VEC

Node2Vec(Grover & Leskovec, 2016) improves DeepWalk by performing a parametrized random walk. For each transition, Node2Vec considers second-order proximity to decide the next node be near or far from the previous node, which allows exploration both in local and global scopes.

A.7.6 DADL

DADL(Rizi et al., 2018) leverages conventional GRL methods to embed local structure on each node, which implies some similarities between the current node and its neighbors. Then, by considering different binary operations over node embeddings in deep learning techniques, this method outperforms conventional ones in the shortest distance prediction task.