On the Use of Self-Supervised Speech Representations in Spontaneous Speech Synthesis

Abstract

Self-supervised learning (SSL) speech representations are high-level yet expressive audio representations learned from large amounts of diverse, mixed-quality speech data without transcriptions, and are gaining ground in many speech-technology applications. These properties make SSL representations especially suitable for use in spontaneous text-to-speech (TTS). Prior work has shown that SSL is an effective intermediate representation in both read and spontaneous TTS. However, it is still not clear which SSL and which layer from each SSL is most suited for spontaneous TTS. We address this shortcoming by extending the scope of comparison for SSL in spontaneous TTS to 6 different SSLs and 3 layers within each SSL. Furthermore, SSL has also shown potential in predicting the mean opinion scores (MOS) of synthesized speech, but this has only been done in read-speech MOS prediction. We extend an SSL-based MOS prediction framework and evaluate its performance on spontaneous speech synthesis. Overall, we present comprehensive experimental results on the use of SSL in spontaneous TTS and MOS prediction to further quantify and understand how SSL can be used in spontaneous TTS.

Index Terms: spontaneous speech synthesis, self-supervised learning, automatic evaluation

1. Introduction

The availability of large amounts of data and computation has radically enhanced the capabilities of modern machine-learning systems. One way that these developments can benefit ordinary applications with smaller amounts of data and computation is via "foundation models" [1], publicly available pre-trained models created using self-supervised learning (SSL) on large amounts of unlabelled data. Models that integrate representations of speech audio learned via SSL have demonstrated impressive results in areas such as speech recognition, speaker recognition, and voice conversion [2]. Recently, these methods have also been considered for use as acoustic features two-stage text-to-speech (TTS) [3, 4], showing promising results in replacing conventional mel-spectrogram features.

However, integrating SSL-based representations into TTS is still a novel concept, and it is not clear which representations are preferred for use in TTS, why they are preferred, nor what trade-offs are involved. In addition to differences between different models, research into other applications has found that representations from different layers of the same model may be preferred for different applications [2, 5]. It is not even clear what TTS tasks these representations can be used for. Thus far, a handful of works have considered using SSL-based representations as TTS acoustic features [3, 4, 6, 7], demonstrating advantages in creating TTS systems from mixed-quality audio.

Outside of TTS, however, SSL models have found a wide range of different applications [8], including predicting mean opinion scores (MOS) for the audio quality of voice-conversion systems [9, 10]. Thus, SSL-based representations may be advantageous beyond acoustic representations in TTS, and we aim to explore a wider range of SSL uses in this work.

Another important shortcoming is that most prior applications of SSL in speech focuses on speech read aloud. This contrasts against the majority of in-the-wild human speech, which tends to be spontaneous and unscripted. Such speech involves unique verbal and nonverbal phenomena such as breathing [11, 12], disfluencies [13], and discourse markers, which are seldom included or transcribed in conventional speech corpora, making them a blind spot of contemporary TTS research [14].

In this paper, we compare representations derived from four different SSL speech models. We selected these models based on their high scores on the SUPERB benchmark [2], similar dimensionalities and frame rates, and the availability of pre-trained weights. (For some models, our comparisons consider multiple model versions.)

We study the utility of these models for two tasks in text-to-speech from spontaneous speech audio:

1. As intermediate feature representations ("acoustic features") in two-stage TTS.
2. As backbone models for automatic prediction of speech quality (MOS) of synthetic speech.

We perform comprehensive experiments on two corpora previously used for spontaneous TTS. In total, we train and evaluate 36 different TTS models (18 on each corpus) and 37 different MOS prediction models (18 on each corpus plus a pretrained model). Audio examples are enclosed as supplementary material with our submission.

2. Background

Self-supervised representations learned from large amounts of untranscribed speech audio have recently become a hot topic, finding a large number of applications all across speech technology [8]. In this section, we review the use of SSL representations in TTS and in speech-quality prediction. A particular focus of our survey (and, indeed, our entire paper) is spontaneous and conversational speech. Despite accounting for the lion's share of human speech, and being considered vital for creating more-human like and convincing TTS for, e.g., conversational systems, [15, 14], spontaneous speech and its challenges represent an underexplored topic in contemporary TTS research. On the one hand, spontaneous speech exhibits increased acoustic and prosodic diversity [16], and many spontaneous-speech databases rely on found or in-the-wild recordings, which may entail reduced audio quality, competing speakers, etc. [11]. (It

Figure 1: *Overview of this work. Two-stage TTS with SSL representations on the right and MOS prediction on the left.*

SSL model (version/versions)	Training data and loss	
	Pre-training	ASR fine-tuning
wav2vec 2.0 [19] (base & base-asr)	LibriSpeech 960 h (contrastive+diversity)	LibriSpeech 960 h
data2vec [25] (base & base-asr)	LibriSpeech 960 h (masked regression)	LibriSpeech 960 h
WavLM [26] (base-plus)	94k h mixed corpora (denoising+prediction)	N/A
Whisper [27] (small)	N/A	680k hours

Table 1: *Speech SSL models tested, with info about pre-training and ASR fine-tuning corpora used.*

has been argued [3, 7, 17] that SSL-based representations are especially useful for such data.) On the other hand, spontaneous speech cannot easily be partitioned into clean sentences, and the audio contains numerous phenomena that are difficult to transcribe. This includes breathing [11, 12], disfluencies such as repetitions and filled pauses (uh/um) [13], discourse markers ("like", "you know") [18]. These phenomena are often missing from the input text, but they need to be generated by the TTS system.

2.1. TTS Using SSL Models

The first systems using representations from modern self-supervised learning in TTS were likely WavThruVec [3] and VQTTS [4]. Both proposed to replace the acoustic representations in between the acoustic model and the vocoder with a speech feature representation from an SSL model. Compared to end-to-end TTS or traditional two-stage TTS based on mel-spectrogram features, this setup allows synthesizing high-quality audio even if the acoustic model is trained on mixed-quality audio material [3]. While VQTTS trained a custom, discrete acoustic representation (turning acoustic modelling into a classification problem), WavThruVec used a pre-trained wav2vec 2.0 model [19] as its intermediate acoustic representation. There has also been work exploring the use of audio SSL models as linguistic features instead of acoustic features [6].

Most relevant to the current work are MQTTS [7] and the analysis of Wang et al. [17], since both of these consider TTS with spontaneous speech audio. MQTTS trains multiple discrete representations on the GigaSpeech corpus [20], which is a very large corpus of in-the-wild speech that contains a lot of spontaneous speech. They find that, unlike conventional acoustic representations, SSL representations are more robust, in that they allow learning meaningful alignments. Meanwhile, a recent study [17] built a number of TTS systems from publicly

available speech SSL models, and contrasted these for synthesizing read versus spontaneous speech. They found that intermediate SSL layers are better for TTS than the final layers, and that SSL representations improved on both read-speech and spontaneous TTS systems, but with the difference being even more pronounced in the case of spontaneous TTS. Since that study already compared read and spontaneous TTS, we focus exclusively on spontaneous speech data and tasks in this work.

2.2. Quality Prediction Using SSL Models

Apart from synthesizing speech, SSL models have also been considered for predicting quality scores (specifically MOS values) of natural and synthetic speech. This was perhaps first done by [9] for predicting MOS values of different voice conversion systems. By building predictors from pre-trained SSL models and fine-tuning these end-to-end, they obtained a prediction accuracy surpassing previous state-of-the-art systems. SSLs have subsequently become a hot topic in quality prediction. The recent VoiceMOS Challenge considered predicting MOS scores of both voice conversion systems and of read-speech TTS [21], and saw a very large portion of entries that made use of SSL models. The main results saw pre-trained SSL models with fine-tuning outperform approaches that used such models without fine-tuning, in turn ahead of approaches that did not use SSL representations at all [21, 10].

Another recent challenge [22] focused on predicting speech quality in speech conferencing applications, and also saw several submissions, e.g., [23, 24], making use of SSL representations. This task does involve spontaneous speech audio, but the differences from clean, natural speech are not comparable to the artifacts expected to result from how TTS systems deal with complex spontaneous speech phenomena such as disfluencies. Thus, none of the above works considered the use of self-supervised representations to predict the perceived quality of spontaneous text-to-speech.

3. Method

The goal of this paper is to analyze the effect of using different SSL models in synthesizing and evaluating spontaneous speech; cf. Fig. 1. In this section we describe the SSL models studied, the data, how we build TTS systems on these data, and how we use SSL representations for subsequent MOS score prediction. Experimental results and discussion follow in Sec. 4.

3.1. Representations

Four speech SSL models were selected for our investigation. These are summarized in Table 1. All of these representations were investigated for spontaneous TTS, whereas only a subset were considered for the quality-prediction task.

Our main reason for choosing these specific models was that they rank high on the SUPERB benchmark [2] and have an official implementation with public weights available. Importantly, all models have same dimensionality (765), number of layers (12 transformer layers), and frame rate (50), making them highly comparable. The main differences between the models are the data and loss function/task used for training.

For each model, we considered the representations from three different layers (6, 9, and 12 out of 12), since prior work has shown that a middle layer of SSL models contains more prosodic information [28, 17] that could benefit synthesis. For some SSL models, we also found official ASR fine-tuned versions, which we include in the experiments in addition to any regular, pre-trained models. In total, we considered 18 different representations, 3 from each of 6 different SSL models.

3.2. Spontaneous Speech Corpora

We trained our TTS voices on two corpora previously used in several different studies on spontaneous TTS. The first corpus was created from the audio recordings of part 1 of the Trinity Speech-Gesture Dataset (TSGD) [29], comprising 25 monologues, each on average 10.6 minutes long, spoken by a male speaker of Hiberno English in an impromptu, colloquial style. During the recordings, the actor addresses a person seated behind the cameras, who is providing visual, but no verbal feedback. To prepare the dataset for TTS, we segmented the corpus into stretches of speech delineated by breath events following [12], and combined these segments in an overlapping fashion to form an utterance structure, with utterances no longer than 11 seconds, following [12].

The second spontaneous corpus used in this work is the ThinkComputers Corpus (TCC) [11, 14], which is a 9-hour long corpus created from the speech of one of the hosts of the ThinkComputers podcast, which is available in the public domain.[1] The podcast recordings are approximately 50 min each, and consist of two male speakers of American English discussing technology-related news and reviews. The speaking style can be described as extemporaneous, conversing freely around a prepared outline, meaning that the speakers use a prepared outline, but converse freely around the planned topics. Both corpora were transcribed using ASR and subsequently corrected manually. All discourse markers, laughter, and filled pauses (uh, um) were transcribed orthographically, breath events were marked with a semi-colon, while pauses were transcribed using a comma. Other spontaneous speech phenomena such as tongue clicks were not part of the transcription.

3.3. TTS System

We used a similar system and training setup as WavThruVec [3], with the difference that we omitted the multi-speaker embeddings in our system. We illustrate the system in Fig. 1.

The stage-1 model is adapted from a parallel TTS model, FastPitch [30], in which the alignment is learned automatically

---

[1] https://archive.org/details/podcasts_
miscellaneous Creator: ThinkComputers

[31].[2] We used identical hyperparameters as in [3] to train stage-1 models, only changing the batch size to 128. We first trained on a read-speech corpus, namely LJ Speech[3], for 200 epochs, and then on each of the two spontaneous corpus for 200 epochs. This transfer-learning method has shown to be effective in allowing neural TTS to be trained on smaller spontaneous corpora [14].

For the stage-2 model or the vocoder, we used HiFi-GAN [32],[4] trained with similar hyperparameters as in [3]. We used a batch size of 160, each datum being a 0.5 second random audio excerpt. All 18 stage-2 vocoders (for the 18 SSL representations) were trained for 80k steps for fair comparison. We used the original audio sampling rate of 22 kHz. Models of both stages were trained on 1–2 Nvidia A100 GPUs depending on batch size.

3.4. MOS-Prediction System

We followed [10] to build a simple wav2vec 2.0 based MOS predictor. The predictor consists of a wav2vec 2.0 base model with a mean-pooling head on top and a linear projection to a scalar MOS value. We adapted the implementation of [10][5] and followed their training procedure and hyperparameters. However, we tested different weight initializations and training-data configurations for this fixed architecture, to probe SSL MOS-predictor performance on spontaneous TTS.

4. Results

This section reports and discusses our three main experimental results, namely the validation-set losses achieved by the trained vocoders, the design and results of our spontaneous TTS listening test, and the performance of SSL-based predictors of MOS scores from our listening test.

4.1. Analysis of Vocoding Loss

The validation-set mel-spectrogram error achieved by the second-stage models (vocoders) we trained are graphed in Fig. 2, showing how these errors depend on the SSL model and representation layer. There are clear trends in that the later the layer, the greater the error, presumably because later layers are further removed from the original speech waveform. ASR fine-tuning also leads to increased error over corresponding pre-trained models, though the lowest error is attained by representations from Whisper, which is a dedicated ASR model. In informal listening, we were impressed with the copy-synthesis performance from the Whisper-derived representations. Except for WavLM, the plots are virtually identical across the two corpora.

4.2. Subjective Evaluation of TTS Systems

To evaluate the suitability of different SSL representations in two-stage TTS, we performed two MOS listening tests (ITU standard P.800 [33]), one for each corpus. Each evaluation used a pool of 20 utterances synthesised by each of the 18 different

---

[2] https://github.com/NVIDIA/
DeepLearningExamples/tree/master/PyTorch/
SpeechSynthesis/FastPitch. This model is called "Fast-Pitch 1.1" in this official implementation.

[3] https://keithito.com/LJ-Speech-Dataset/
[4] https://github.com/jik876/hifi-gan
[5] https://github.com/nii-yamagishilab/
mos-finetune-ssl.git

Figure 2: *Vocoding validation mel-spec error from different SSL representations on the two corpora: TSGD (left) and TCC (right).*

Figure 3: *MOS for the 18 different TTS systems compared. Results for TSGD on the left and TCC on the right. 95% confidence intervals of TSGD MOS range from ±0.17 (d2v_base_ssl-layer 6) to ±0.22 (w2v2_base_asr-layer 6), while TCC MOS confidence intervals range from ±0.16 (w2v2_base_asr-layer 9) to ±0.21 (d2v_base_asr-layer 6).*

systems, for a total of 320 stimuli per corpus (study). For each corpus we recruited 45 self-reported native English-speaking listeners via the Prolific crowdsourcing platform. Each listener rated 51 randomly chosen stimuli from the pool. Participants were asked to wear headphones, and they were requested to not take the test if they had a hearing impairment. Ratings were integer values given on a scale from 1 through 5 with labels as in [33]. Attention checks were included to filter out insincere test-takers. Test-takers who completed the test too quickly to have listened to all the audio were also disqualified.

Results of the two listening tests are visualized in Fig. 3. A number of general trends are visible. We observe two prominent trends in the layer-wise mean opinion scores: 1) the 9th layer outperforms the 12th (last) and 6th (middle) layers for 4 out of 6 SSL models on both corpora, and 2) MOS are quite spread out for layers 6 and 9, but converge to a similar level at the 12th layer across different models. The differences in MOS between layers are generally much wider than the confidence intervals on the individual scores, which are no wider than ±0.21. More often than not, we find that representations after ASR fine-tuning obtained better ratings than systems based on the corresponding representations prior to fine-tuning. For both corpora, the best performing TTS system was based on d2v-base-asr layer 9 (TSGD: 3.90±0.18, TCC: 3.77±0.17). The consistency of the trends between models and layers on the two corpora suggests that results are likely to generalize to other spontaneous corpora.

We also see that the vocoding errors in Fig. 2 do not correlate at all with perceived TTS quality. In fact, ASR fine-tuned data2vec, which was the best performing SSL model, consistently exhibited the worst vocoding errors, whereas Whisper underperformed for TTS despite having low objective vocoding errors.

4.3. Evaluation of Automated MOS Prediction

We probed two sets of factors that may affect the generalization ability of spontaneous-speech MOS prediction with SSL: 1) the starting weights used for fine-tuning and 2) the type of unseen data (dataset split), by specifically holding out either random audio samples, or data from specific utterances (input texts), or entire TTS models, or the full corpus (i.e., training on one corpus and predicting the scores on the other). Except for at the corpus level, we performed 5-fold cross-validation for each of these experiments. In addition to fine-tuning, we also tested the zero-shot performance of the predictor from [10].

Results from the experiments on automated MOS prediction are reported in Table 2. We make a number of observations from these results. First, the zero-shot model from [10] pretrained on read speech does not make meaningful predictions on this data. Fine-tuning improved performance, with fine-tuning on top of [10] or w2v2-base performing similarly and fine-tuning on top of w2v2-base-asr performing slightly worse. Finally, although prediction MSE is low, correlations are not as strong as the numbers achieved by MOS predictors on read-speech data [10]. Several factors may contribute to this, for example that the range of MOS values in our data is quite narrow,

		Zero-shot [10]	Fine-tuned from: [10]	w2v2-base	w2v2-base-asr
TSGD	Sample	2.77 ± 0.28	0.35 ± 0.08	0.32 ± 0.08	0.46 ± 0.08
		0.15 ± 0.08	0.47 ± 0.19	0.51 ± 0.17	0.30 ± 0.23
	Utt.	3.60 ± 0.00	0.37 ± 0.02	0.34 ± 0.03	0.34 ± 0.01
		-0.02 ± 0.00	0.36 ± 0.03	0.32 ± 0.06	0.15 ± 0.09
	Model	2.85 ± 0.00	0.40 ± 0.02	0.45 ± 0.01	0.45 ± 0.05
		0.43 ± 0.00	0.41 ± 0.04	0.22 ± 0.06	0.17 ± 0.17
	Corpus	3.07	0.60	0.44	0.50
		0.23	0.12	0.12	0.04
TCC	Sample	2.14 ± 0.15	0.38 ± 0.07	0.42 ± 0.11	0.50 ± 0.07
		0.19 ± 0.10	0.50 ± 0.10	0.58 ± 0.13	0.22 ± 0.10
	Utt.	2.14 ± 0.00	0.40 ± 0.03	0.38 ± 0.02	0.51 ± 0.07
		0.28 ± 0.00	0.19 ± 0.09	0.21 ± 0.18	-0.24 ± 0.18
	Model	2.19 ± 0.00	0.31 ± 0.04	0.32 ± 0.03	0.40 ± 0.02
		0.19 ± 0.00	0.53 ± 0.07	0.53 ± 0.03	0.04 ± 0.16
	Corpus	3.35	0.64	0.45	0.47
		-0.08	0.06	0.10	0.01

Table 2: *Results of MOS prediction experiments. The two numbers reported for each task and predictor are MSE (top) and linear correlation (below). The rows are unseen distribution categories. All categories except for corpus are 5-fold cross-validated, and thus report mean and standard deviation.*

that we have less data available than for read speech, and that predicting the scores of spontaneous TTS systems in general may be a more challenging task than for read speech.

5. Conclusion and Future Work

We have analyzed the effect of using self-supervised speech representations in spontaneous text-to-speech, as well as for objective evaluation of the same, on two different corpora. First, we conducted experiments on a total of 18 different same-dimensionality SSL representations used as intermediate acoustic features in two-stage TTS. We found that representations from layer 9 of the SSL models provided better subjective speech quality than layer 6 or layer 12 (the final layer), with best results were provided by data2vec with ASR fine-tuning. These results do not correlate at all with the vocoding losses obtained from different SSL representations, where the subjectively best-performing representations obtained some of the worst loss values, and vice versa. Vocoding loss thus cannot replace subjective evaluation.

Second, we studied the use of SSL models in predicting our subjective listening-test scores. We found fine-tuning on our spontaneous MOS data to be crucial for this approach to have any predictive value. Compelling future work includes studying more SSLs on larger corpora, well as improving SSL and TTS architectures for spontaneous speech.

6. References

[1] C. Zhou, Q. Li, C. Li, J. Yu, Y. Liu, G. Wang, K. Zhang, C. Ji, Q. Yan, L. He *et al.*, "A comprehensive survey on pretrained foundation models: A history from BERT to ChatGPT," *arXiv preprint arXiv:2302.09419*, 2023.

[2] S.-w. Yang *et al.*, "SUPERB: Speech processing Universal PER-formance Benchmark," in *Proc. Interspeech*, 2021, pp. 1194–1198.

[3] H. Siuzdak, P. Dura, P. van Rijn, and N. Jacoby, "WavThruVec: Latent speech representation as intermediate features for neural speech synthesis," in *Proc. Interspeech*, 2022, pp. 833–837.

[4] C. Du, Y. Guo, X. Chen, and K. Yu, "VQTTS: High-fidelity text-to-speech synthesis with self-supervised VQ acoustic feature," in *Proc. Interspeech*, 2022, pp. 1596–1600.

[5] Y. Li, Y. Mohamied, P. Bell, and C. Lai, "Exploration of a self-supervised speech model: A study on emotional corpora," in *Proc. SLT*, 2022.

[6] S.-H. Lee, S.-B. Kim, J.-H. Lee, E. Song, M.-J. Hwang, and S.-W. Lee, "HierSpeech: Bridging the gap between text and speech by hierarchical variational inference using self-supervised representations for speech synthesis," in *Advances in Neural Information Processing Systems*, 2023.

[7] L.-W. Chen, S. Watanabe, and A. Rudnicky, "A vector quantized approach for text to speech synthesis on real-world spontaneous speech," in *Proc. AAAI*, 2023.

[8] A. Mohamed, H.-y. Lee, L. Borgholt, J. D. Havtorn, J. Edin, C. Igel, K. Kirchhoff, S.-W. Li, K. Livescu, L. Maaløe *et al.*, "Self-supervised speech representation learning: A review," *IEEE J. Sel. Top. Signa.*, 2022.

[9] W.-C. Tseng, C. yu Huang, W.-T. Kao, Y. Y. Lin, and H. yi Lee, "Utilizing self-supervised representations for MOS prediction," in *Proc. Interspeech*, 2021, pp. 2781–2785.

[10] E. Cooper, W.-C. Huang, T. Toda, and J. Yamagishi, "Generalization ability of MOS prediction networks," in *Proc. ICASSP*, 2022, pp. 8442–8446.

[11] É. Székely, G. E. Henter, and J. Gustafson, "Casting to corpus: Segmenting and selecting spontaneous dialogue for TTS with a CNN-LSTM speaker-dependent breath detector," in *Proc. ICASSP*, 2019, pp. 6925–6929.

[12] É. Székely, G. E. Henter, J. Beskow, and J. Gustafson, "Breathing and speech planning in spontaneous speech synthesis," in *Proc. ICASSP*, 2020, pp. 7649–7653.

[13] E. Szekely, G. E. Henter, J. Beskow, and J. Gustafson, "How to train your fillers: uh and um in spontaneous speech synthesis," in *Proc. SSW*, vol. 10, 2019, pp. 245–250.

[14] É. Székely, G. E. Henter, J. Beskow, and J. Gustafson, "Spontaneous conversational speech synthesis from found data," in *Proc. Interspeech*, 2019, pp. 4435–4439.

[15] X. Tan, T. Qin, F. Soong, and T.-Y. Liu, "A survey on neural speech synthesis," *arXiv preprint arXiv:2106.15561*, 2021.

[16] H. Fujisaki, "Prosody, models, and spontaneous speech," *Computing prosody: Computational models for processing spontaneous speech*, pp. 27–42, 1997.

[17] S. Wang, G. E. Henter, J. Gustafson, and É. Székely, "A comparative study of self-supervised speech representations in read and spontaneous TTS," *arXiv preprint arXiv:2303.02719*, 2023.

[18] S. Wang, J. Gustafson, and É. Székely, "Evaluating sampling-based filler insertion with spontaneous TTS," in *Proc. LREC*, vol. 13, 2022, pp. 1960–1969.

[19] A. Baevski, Y. Zhou, A. Mohamed, and M. Auli, "wav2vec 2.0: A framework for self-supervised learning of speech representations," in *Proc. NeurIPS*, vol. 33, 2020, pp. 12 449–12 460.

[20] G. Chen, S. Chai, G. Wang, J. Du, W.-Q. Zhang, C. Weng, D. Su, D. Povey, J. Trmal, J. Zhang *et al.*, "GigaSpeech: An evolving, multi-domain ASR corpus with 10,000 hours of transcribed audio," *arXiv preprint arXiv:2106.06909*, 2021.

[21] W.-C. Huang, E. Cooper, Y. Tsao, H.-M. Wang, T. Toda, and J. Yamagishi, "The VoiceMOS Challenge 2022," in *Proc. Interspeech*, 2022, pp. 4536–4540.

[22] G. Yi, W. Xiao, Y. Xiao, B. Naderi, S. Möller, W. Wardah, G. Mittag, R. Culter, Z. Zhang, D. S. Williamson, F. Chen, F. Yang, and S. Shang, "ConferencingSpeech 2022 Challenge: Non-intrusive objective speech quality assessment (NISQA) challenge for online conferencing applications," in *Proc. Interspeech*, 2022, pp. 3308–3312.

[23] H. Becerra, A. Ragano, and A. Hines, "Exploring the influence of fine-tuning data on wav2vec 2.0 model for blind speech quality prediction," in *Proc. Interspeech*, 2022, pp. 4088–4092.

[24] B. Tamm, H. Balabin, R. Vandenberghe, and H. Van hamme, "Pretrained speech representations as feature extractors for speech quality assessment in online conferencing applications," in *Proc. Interspeech*, 2022, pp. 4083–4087.

[25] A. Baevski, W.-N. Hsu, Q. Xu, A. Babu, J. Gu, and M. Auli, "data2vec: A general framework for self-supervised learning in speech, vision and language," in *Proc. ICML*, 2022, pp. 1298–1312.

[26] S. Chen, C. Wang, Z. Chen, Y. Wu, S. Liu, Z. Chen, J. Li, N. Kanda, T. Yoshioka, X. Xiao *et al.*, "WavLM: Large-scale self-supervised pre-training for full stack speech processing," *IEEE Journal of Selected Topics in Signal Processing*, vol. 16, no. 6, pp. 1505–1518, 2022.

[27] A. Radford, J. W. Kim, T. Xu, G. Brockman, C. McLeavey, and I. Sutskever, "Robust speech recognition via large-scale weak supervision," *arXiv preprint arXiv:2212.04356*, 2022.

[28] A. Pasad, J.-C. Chou, and K. Livescu, "Layer-wise analysis of a self-supervised speech representation model," in *Proc. ASRU*, 2021, pp. 914–921.

[29] Y. Ferstl and R. McDonnell, "Investigating the use of recurrent motion modelling for speech gesture generation," in *Proc. IVA*, 2018, pp. 93–98. [Online]. Available: https://trinityspeechgesture.scss.tcd.ie

[30] A. Łańcucki, "FastPitch: Parallel text-to-speech with pitch prediction," in *Proc. ICASSP*, 2021, pp. 6588–6592.

[31] R. Badlani, A. Łańcucki, K. J. Shih, R. Valle, W. Ping, and B. Catanzaro, "One TTS alignment to rule them all," in *Proc. ICASSP*, 2022, pp. 6092–6096.

[32] J. Kong, J. Kim, and J. Bae, "HiFi-GAN: Generative adversarial networks for efficient and high fidelity speech synthesis," *Proc. NeurIPS*, pp. 17 022–17 033, 2020.

[33] International Telecommunication Union, Telecommunication Standardization Sector, "Methods for subjective determination of transmission quality," ITU Recommendation ITU-T P.800, 1996.