AutoOED: Automated Optimal Experimental Design Platform with Data- and Time-Efficient Multi-Objective Optimization

Abstract

We present AutoOED, an Automated Optimal Experimental Design platform powered by machine learning to accelerate discovering solutions with optimal objective trade-offs. To solve expensive multi-objective problems in a data-efficient manner, we implement popular multi-objective Bayesian optimization (MOBO) algorithms with state-of-the-art performance in a modular framework. To further accelerate the optimization in a time-efficient manner, we propose a novel strategy called Believer-Penalizer (BP), which allows batch experiments to be accelerated asynchronously without affecting performance. AutoOED serves as a testbed for machine learning researchers to quickly develop and evaluate their own MOBO algorithms. We also provide a graphical user interface (GUI) for users with little or no experience with coding, machine learning, or optimization to visualize and guide the experiment design intuitively. Finally, we demonstrate that AutoOED can control and guide real-world hardware experiments in a fully automated way without human intervention.

1 Introduction

Optimal Experimental Design (OED) problems in science and engineering often require satisfying several conflicting objectives simultaneously. These problems aim to solve a multi-objective optimization system and discover a set of optimal solutions, called Pareto optimal. Furthermore, the objectives are typically black-box functions whose evaluations are time-consuming and costly (e.g., measuring real experiments or running expensive numerical simulations). Thus, the budget that determines the number of experiments can be heavily constrained. Hence, an efficient strategy for guiding the experimental design towards Pareto-optimal solutions is necessary. Recent advances in machine learning algorithms have facilitated optimization of various design problems, including chemical design (Griffiths & Hernández-Lobato, 2017), material design (Zhang et al., 2020), resource allocation (Wu et al., 2013), environmental monitoring (Marchant & Ramos, 2012), recommender systems (Chapelle & Li, 2011) and robotics (Martinez-Cantin et al., 2009). A machine learning concept that enables automatic guidance of the design process is Bayesian optimization (Shahriari et al., 2016). This concept is extensively studied in the machine learning and optimization community from a theoretical aspect and in the single-objective case. However, its practical applications in other fields with multi-objective problems are still not widely explored due to the lack of intuitive, easy-to-use, open-source software.

In this paper, we present AutoOED, an open-source platform for efficiently optimizing multi-objective problems with a restricted budget of experiments. The platform automatically guides the design of experiments to be evaluated and quickly leads to the best performing designs. AutoOED is based on the concept of multi-objective Bayesian optimization (MOBO) and is entirely implemented in Python. The key features of this platform include:

- **Data-efficient experimentation**: As the platform aims to solve problems with expensive to evaluate or black-box objective functions, AutoOED employs state-of-the-art MOBO strategies that rapidly advances the Pareto front with a small set of evaluated experiments.

- **Time-efficient experimentation**: Apart from standard sequential optimization, the platform supports both synchronous and asynchronous batch optimization to accelerate the

discovery of optimal solutions. We propose a novel state-of-the-art asynchronous optimization strategy named Believer-Penalizer (BP), which is instrumental when multiple workers are running experiments in parallel, but their evaluations drastically vary in time.

- **Intuitive GUI**: An easy-to-use graphical user interface (GUI) is provided to directly visualize and guide the optimization progress and facilitate the operation for users with little or no experience with coding, optimization, or machine learning.

- **Modular structure**: A highly modular codebase enables easy extensions and replacements of MOBO algorithm components. The platform can serve as a testbed for machine learning researchers to easily develop and evaluate their own MOBO algorithms.

- **Automation of experimental design**: The platform is designed for straightforward integration into an automated experimental design optimization pipeline as long as the experiment evaluations (either in simulation or physical) can be controlled via computer programs.

We discuss related work in Section 2 and illustrate the optimization methodologies of AutoOED in Sections 3 and 4. We explain the workflow and features of AutoOED in Section 5 and present the experimental results in Section 6. Code, screenshots, detailed documentation and tutorials can be found at `https://sites.google.com/view/autooed`.

2 RELATED WORK

Bayesian optimal experimental design   Experiments can be expensive to perform either in time or cost. Therefore, optimal experimental design (OED) methods focus on designing the sequence of experiments to maximize specific objectives in a data- or time-efficient manner. Given that the experimental evaluations are usually expensive black-box functions, Bayesian optimization (BO) (Shahriari et al., 2016) can be applied to find optimal solutions with a minimal number of evaluations. Essentially, BO relies on *surrogate models* like the Gaussian process (GP) to accurately model the experimental process and proposes new experimental designs based on defined *acquisition functions* that trade-off between exploration and exploitation. Popular choices of the acquisition functions include Expected Improvement (EI) (Močkus, 1975), Upper Confidence Bound (UCB) (Srinivas et al., 2010), Thompson Sampling (TS) (Thompson, 1933). Bayesian OED has found success in a wide range of applications (Greenhill et al., 2020) and is the main methodology of AutoOED.

Multi-objective Bayesian optimization   MOBO is developed to optimize for a set of Pareto-optimal solutions while minimizing the number of experimental evaluations. ParEGO (Knowles, 2006) scalarizes the multi-objective problem to a single-objective one using a random weight and proposes the next design with maximum EI. Instead of scalarization, some acquisition functions are proposed to compute a single objective, e.g., entropy-based or hypervolume-based (Russo & Van Roy, 2014; Belakaria et al., 2019; Emmerich & Klinkenberg, 2008; Daulton et al., 2020a). Alternatively, MOBO can be solved by defining a separate acquisition function per objective, optimizing using cheap multi-objective solvers (usually evolutionary algorithms like NSGA-II (Deb et al., 2002)) and finally selecting one or a batch of designs to evaluate next. TSEMO (Bradford et al., 2018) utilizes Thompson Sampling (TS) as an acquisition function, optimizes multiple objectives with NSGA-II, and selects designs by maximizing hypervolume improvement. USeMO (Belakaria & Deshwal, 2020) uses maximum uncertainty as the selection criterion. DGEMO (Konakovic Lukovic et al., 2020) is one of the state-of-the-art approaches that approximates a piecewise-continuous Pareto set representation and selects next batch of designs based on hypervolume improvement and a carefully designed diversity criterion. AutoOED implements many of them in a modular way and allows easily changing modules in an unified MOBO framework (see Section 3.2).

Batch Bayesian optimization   Batch Bayesian optimization (i.e., parallel BO) applies to the scenario when the expensive evaluations can be carried out in parallel. The majority of work in this space focuses on the synchronous setting (Contal et al., 2013; Desautels et al., 2014; Shah & Ghahramani, 2015; González et al., 2016; Kathuria et al., 2016) while only a few methods can handle asynchronous evaluations (Ginsbourger et al., 2010; Kandasamy et al., 2018; Alvi et al., 2019). However, all of the previous literature focuses on single-objective BO rather than the multi-objective scenario. In this paper, we extend several single-objective asynchronous BO methods to multi-objective ver-

sions and propose a novel asynchronous method named Believer-Penalizer (BP) with the stablest performance on multi-objective benchmark problems.

Table 1: Feature comparison between different Bayesian optimization platforms.[1]

Name	GUI	Multiple objectives	Multiple domains	Asynchronous optimization	External evaluation	Modular framework	Built-in visualization
Spearmint			✓				
GPyOpt			✓		✓	✓	✓
GPflowOpt		∼				✓	
Dragonfly		∼	✓	✓			
BoTorch		✓		✓		✓	
AutoOED	✓	✓	✓	✓	✓	✓	✓

Open-source Bayesian optimization platform There are many existing Python libraries for Bayesian optimization including Spearmint (Snoek et al., 2012), GPyOpt (authors, 2016), GPflowOpt (Knudde et al., 2017), Dragonfly (Kandasamy et al., 2020) and BoTorch (Balandat et al., 2020). These Python libraries are designed for general applications and have different algorithmic features supported. The feature comparison between AutoOED and these libraries is shown in Table 1 and is further discussed in Section 5.2. However, they are all targeted for experts in coding without an intuitive GUI, which means that the users need to write hundreds lines of code defining the design space, performance space, surrogate models, acquisition functions, optimization solvers, etc. to finally start the optimization. In contrast, there are also software platforms designed for specific applications only, for example, Auto-QChem (Shields et al., 2021) for chemical synthesis and GeoBO (Haan, 2021) for geoscience. They provide intuitive user interface and visualization to specific domain experts but the platforms cannot be used for other general applications. Combining powerful Bayesian optimization algorithms and an intuitive GUI, AutoOED is designed to be a general optimization platform that can be easily used by anyone for applications in any field.

3 DATA-EFFICIENT MULTI-OBJECTIVE OPTIMIZATION

3.1 PROBLEM FORMULATION

Optimal experiment design problems involving multiple conflicting objectives can be formulated as a multi-objective optimization on design parameters as data- and time-efficient as possible. More formally, we consider a optimization problem over a set of design variables $\mathcal{X} \subset \mathbb{R}^d$, called *design space*. The goal is to simultaneously minimize $m \geq 2$ ob-

jective functions $f_1, ..., f_m : \mathcal{X} \to \mathbb{R}$. Representing the vector of all objectives as $\mathbf{f}(\mathbf{x}) = (f_1(\mathbf{x}), ..., f_m(\mathbf{x}))$, the *performance space* is then an m-dimensional image $\mathbf{f}(\mathcal{X}) \subset \mathbb{R}^m$. Conflicting objectives result in a set of optimal solutions rather than a single best solution. These optimal solutions are referred to as *Pareto set* $\mathcal{P}_s \subseteq \mathcal{X}$ in the design space, and the corresponding images in performance space are *Pareto front* $\mathcal{P}_f = \mathbf{f}(\mathcal{P}_s) \subset \mathbb{R}^m$.

To measure the quality of an approximated Pareto front, *hypervolume* (Zitzler & Thiele, 1999) is the most commonly used metric in multi-objective optimization (Riquelme et al., 2015). Let $\mathcal{P}_f$ be a Pareto front approximation in an m-dimensional performance space and given a reference point $\boldsymbol{r} \in \mathbb{R}^m$, the hypervolume $\mathcal{H}(\mathcal{P}_f)$ is defined as $\mathcal{H}(\mathcal{P}_f) = \int_{\mathbb{R}^m} \mathbb{1}_{H(\mathcal{P}_f)}(z)dz$, where $H(\mathcal{P}_f) = \{\boldsymbol{z} \in Z \mid \exists 1 \leq i \leq |\mathcal{P}_f| : \boldsymbol{r} \preceq \boldsymbol{z} \preceq \mathcal{P}_f(i)\}$. $\preceq$ is the relation operator of objective dominance and $\mathbb{1}_{H(\mathcal{P}_f)}$ is a Dirac delta function that equals 1 if $z \in H(P_f)$ and 0 otherwise. The higher the hypervolume, the better $\mathcal{P}_f$ approximates the true Pareto front.

---

[1]The comparison is based on AutoOED's core features. "∼" means the package only supports a single multi-objective algorithm rather than a modular multi-objective framework with several state-of-the-art algorithms.

3.2 MODULAR ALGORITHM FRAMEWORK

Figure 1: Algorithmic pipeline and core modules of multi-objective Bayesian optimization.

Multi-objective Bayesian optimization (MOBO) is a data-driven approach that attempts to learn the black-box objective functions $\mathbf{f}(\mathbf{x})$ from available data and find Pareto-optimal solutions in an iterative and data-efficient manner. MOBO typically consists of four core modules: (*i*) an inexpensive *surrogate model* for the black-box objective functions; (*ii*) an *acquisition function* that defines sampling from the surrogate model and trade-off between exploration and exploitation of the design space; (*iii*) a cheap *multi-objective solver* to approximate the Pareto set and front; (*iv*) a *selection strategy* that proposes a single or a batch of experiments to evaluate next. These four modules (see Figure 1) are implemented as core and independent building blocks of the AutoOEDs, making it highly modularized and easy to develop new algorithms and modules. The whole pipeline starts from a given small dataset or a set of random evaluated samples, then it works iteratively by proposing new design samples and evaluating them until the *stopping criterion* is met.

For each module in this framework, AutoOED supports following choices:

- **Surrogate model**: Gaussian process, neural network (multi-layer perceptron), Bayesian neural network (DNGO (Snoek et al., 2015))
- **Acquisition function**: Expected Improvement, Probability of Improvement, Upper Confidence Bound, Thompson Sampling, identity function
- **Multi-objective solver**: NSGA-II, MOEA/D, ParetoFrontDiscovery (Schulz et al., 2018)
- **Selection**: Hypervolume improvement, uncertainty, random, etc.
- **Stopping criterion**: Time, number of evaluations, hypervolume, convergence

```
class TSEMO(MOBO):              class USEMO_EI(MOBO):           class DGEMO(MOBO):
'''                             '''                             '''
[Bradford et al. 2018]          [Belakaria and Deshwal 2020]    [Lukovic et al. 2020]
'''                             '''                             '''
spec = {                        spec = {                        spec = {
    'surrogate': 'gp',              'surrogate': 'gp',              'surrogate': 'gp',
    'acquisition': 'ts',            'acquisition': 'ei',            'acquisition': 'identity',
    'solver': 'nsga2',              'solver': 'nsga2',              'solver': 'discovery',
    'selection': 'hvi',             'selection': 'uncertainty',     'selection': 'diversity',
}                               }                               }
```

Code Example 1: Creating algorithms in AutoOED by simply specifying module combinations.

Based on this framework, we implement several popular and state-of-the-art MOBO methods, including ParEGO (Knowles, 2006), MOEA/D-EGO (Zhang et al., 2009), TSEMO (Bradford et al., 2018), USeMO (Belakaria & Deshwal, 2020), DGEMO (Konakovic Lukovic et al., 2020). DGEMO exhibits state-of-the-art performance for data-efficient, multi-objective problems with batch evaluations to the best of our knowledge. With necessary modules of the MOBO framework implemented,

the algorithms can be easily composed by specifying the choice of each module and inheriting the base class MOBO, see Code Example 1. Supported choices of each module can be found in our documentation. Users can select an algorithm from this library that best fits the characteristics of their physical system or optimization goals, or they can easily create new algorithms by specifying novel combinations of existing modules in just a few lines of code.

4 TIME-EFFICIENT MULTI-OBJECTIVE OPTIMIZATION

4.1 BATCH OPTIMIZATION

While standard MOBO optimizes for the Pareto front in a data-efficient manner, often, when multiple experiment setups are available, evaluations can be executed in batch by parallel workers to further speed up the whole optimization process. To leverage this speed-up, all the algorithms in AutoOED are implemented to support batch evaluation.

However, if parallel workers evaluate in different speeds, some workers are left idle when they finish evaluations earlier than others. Therefore, asynchronous optimization is desired to maximize the utilization of workers and is able to evaluate many more designs than synchronous optimization in a fixed amount of time, as also illustrated by Kandasamy et al. (2018) and Alvi et al. (2019). Nevertheless, while some designs are being evaluated (i.e., busy designs), how to propose the next design that *(i)* avoids being similar to the busy designs and *(ii)* incorporates knowledge from busy designs to reach better regions in the performance space is the key question that we want to explore.

4.2 BELIEVER-PENALIZER STRATEGY

To develop efficient asynchronous strategy for multi-objective optimization, we borrow ideas from previous literature in the single-objective setting.

(a) The failure case of KB when believing overestimated busy designs.

(b) The sub-optimality of LP in multi-objective scenario when believing busy designs affects the selection result.

Figure 2: Analysis of KB and LP strategies for asynchronous optimization.

Kriging Believer (KB) (Ginsbourger et al., 2010) is a simple yet effective approach that believes the performance of busy designs is their posterior mean of the surrogate model when optimizing for new designs. In other words, it treats the mean prediction of the busy designs as their real performance and eliminates their posterior variance to prevent acquisition functions from preferring those regions. However, failure case happens when it believes an overestimated design, it might become difficult to find designs better than this overestimated one and make further improvement, see Figure 2a. Especially, when the posterior mean of the busy design is extremely small and even exceeds the lower bound of the objective, subsequent optimization can hardly find a better solution.

Local Penalization (LP) (González et al., 2016) is another widely used approach that directly penalizes the nearby region of the busy designs to prevent similar designs from being evaluated next. However, extending this approach to the multi-objective scenario sometimes leads to sub-optimal selection of new designs, as explained in Figure 2b. Consider when selecting the best design to evaluate from a set of candidate designs (A and B) proposed by the multi-objective solver using hypervolume improvement criterion, while a busy design is in evaluation. LP penalizes the nearby regions of the busy design in the design space but has no control over the performance space, which

means that designs with similar performance as the busy design could still be selected (design A). Ideally, if the surrogate prediction of the busy design is certain, we should be able to leverage this to avoid proposing designs with little performance gain. For example, simply believing the prediction of the busy design leads to selecting design B that has a higher overall hypervolume improvement.

In conclusion, we observe that the failure case of KB is due to the trust of uncertain predictions while the sub-optimality of LP comes from not believing the certain prediction. Therefore, we propose a novel strategy Believer-Penalizer (BP) that naturally combines KB and LP by applying KB to designs with certain predictions and LP to designs with uncertain predictions. Here, certainty of prediction is simply defined as the posterior standard deviation from the surrogate model which can be Gaussian processes, Bayesian neural networks or other type of model that computes standard deviation of predictions. Though the idea of BP is general and one can use any analytical expression to determine the certainty threshold for applying KB or LP, in practice, we find a simple probabilistic form which works well: $P_i(\mathbf{x}) = \max(1 - 2\sigma_i(\mathbf{x}), 0)$ where P_i is the probability of believing $\mathbf{x}$ for the i-th objective and σ_i is the posterior std of $\mathbf{x}$ from the surrogate model of the i-th objective. Because the objective data is normalized as zero with mean unit variance before fitting the surrogate models, $\sigma_i(\mathbf{x})$ is generally between 0 and 1. As a result, BP generalizes to most of the benchmark problems and outperforms both KB and LP as empirically demonstrated in Section 6.1.

5 THE AUTOOED PLATFORM

5.1 OVERALL WORKFLOW

Figure 3: The manual and automatic workflows of the platform design.

As a full-stack software, the overall workflows of AutoOED are presented in Figure 3. The manual mode and auto mode are distinguished by whether the experimental evaluations need to be done manually or can be done automatically through programs. Key components in this workflow include:

- **GUI**: An intuitive graphical interface between users and optimization, evaluation and database, with many powerful functionalities supported as described in Section 5.2.
- **Optimization**: Once the user sends the optimization request, the MOBO algorithm will be running in back-end and proposing next promising designs.
- **Evaluation**: AutoOED supports two different ways of performing evaluations: manually by hand and automatically by evaluation programs. The evaluation module receives designs proposed by the optimization algorithms and outputs the corresponding objective values.
- **Database**: The SQL database stores information of each design including design parameters, predicted and real objective values in a transactional manner which can be distributed.

Next, we illustrate how the workflows of AutoOED combine these individual components.

Manual mode   When the experimental evaluation must be performed by hand, the manual mode has to be selected. In this case, users need to interface with both the GUI and evaluation. When GUI receives the optimization request from the user, it launches the optimization worker to propose designs for the user to evaluate. Users will see the new proposed designs from the database GUI, then they can enter the evaluation results in the same interface. Once AutoOED receives the evaluation results, visualizations and statistics will be updated to inform users the latest status.

Auto mode   If the evaluation program is available (in Python/C/C++/Matlab), AutoOED can automatically guide the experiments by alternating between optimization and evaluation through a scheduler. In this case, upon receiving the optimization request and stopping criteria from the user, the scheduler will automatically repeat the optimization-evaluation cycle until one of the stopping criteria is met. The scheduler automatically launches evaluations after designs are proposed by optimization workers, and restarts optimization after evaluations are done, thus the whole loop of experimental design can be executed in an automated way without human intervention.

5.2 Feature comparison with other platforms

As shown in Table 1, we compare AutoOED with existing BO platforms according to the following important criteria. For other features and limitations of AutoOED, please refer to Appendix A.

Graphical user interface and visualization   The GUI guides the user through a set of simple steps to configure the problem, such as the number of design and performance parameters, the parameter bounds and constraints, parallelization settings, and selection of the optimization algorithm without the need of coding. The GUI also includes a real-time display of the design and performance space which allows users to easily understand the current status of optimization. We also support displaying and exporting the whole optimization history (including database and statistics). All previous platforms do not offer such a convenient GUI and even the visualizations need to be written by the user, except GPyOpt has a built-in tool for plotting the acquisition function and convergence.

Multiple objectives and multiple domains   For multi-objectivity, GPflowOpt implements HVPOI (Couckuyt et al., 2014) and Dragonfly implements MOORS (Paria et al., 2020) without the flexibility of incorporating other algorithms or modules. BoTorch supports MESMO (Belakaria et al., 2019), qEHVI (Daulton et al., 2020b) and qParEGO. Although algorithm implementations differ across platforms, AutoOED covers a wider range of algorithms and incorporates them into a more unified modular framework. Except continuous designs, AutoOED supports discrete, binary, categorical designs and a mix of them by applying discrete or one-hot transformation in fitting and evaluating the surrogate model, as suggested by (Garrido-Merchán & Hernández-Lobato, 2020).

Asynchronous optimization   As demonstrated in Section 4, AutoOED supports different asynchronous techniques including KB, LP and BP, while Dragonfly and BoTorch only implements KB and all other platforms do not support asynchronous optimization.

External evaluation   There are many real-world experimental design problems where the experimental evaluation must be performed by hand or external lab equipment thus it is hard to write an analytical objective function in code. Though simple to implement, surprisingly, among all of the existing platforms surveyed in this paper, only GPyOpt supports evaluating externally and suggesting designs to evaluate purely based on a given dataset. AutoOED allows users to see the suggested designs and enter the evaluation results easily in the database interface, as described in Section 5.1.

6 Experiments

We conduct experiments across 12 standard multi-objective benchmark problems: ZDT1-4 (Zitzler et al., 2000), DTLZ1-4 (Deb et al., 2005), OKA1-2 (Okabe et al., 2004) and VLMOP2-3 (Van Veldhuizen & Lamont, 1999). For each algorithm, we run experiments with 20 different random seeds and a budget of 100 samples. The initial 20 samples of each run are generated by Latin hypercube sampling (McKay et al., 1979). We measure as the performance criterion the log of the difference between the hypervolume of the ground-truth Pareto front and hypervolume of the best Pareto front

approximation found by the algorithms (thus lower is better). The curves are averaged over 20 random seeds and the variance is shown as shaded regions. Detailed problem information and hyperparameters are described in Appendix B. Additional ablation studies are included in Appendix C.

6.1 ASYNCHRONOUS MOBO ALGORITHMS

Figure 4: Performance comparison between variants of asynchoronous MOBO algorithms.

To test whether Believer-Penalizer is effective, we compare four asynchronous MOBO algorithms on all benchmark problems. *Async* simply ignores the busy designs while optimizing asynchronously and the remaining algorithms are described in Section 4. Figure 4 shows that *Async BP* consistently outperforms other methods and follows the best of *Async KB* and *Async LP*.

6.2 COMPARISON ACROSS PLATFORMS

We compare AutoOED against other open-source BO platforms with multi-objective optimization capabilities, including BoTorch, GPflowOpt, and Dragonfly, on the aforementioned benchmark problems. Our baseline implementation follows the default recommended settings in the original documentation and tutorials. For BoTorch, we use the qEHVI acquisition function. In Figure 5, we demonstrate the competitive performance of AutoOED against other BO platforms using our benchmark. AutoOED takes a major lead in several challenging problems such as ZDT1, ZDT3, and VLMOP3, which shows that our platform handles high-dimensional MOBO problems very well with the proposed asynchronous BP strategy. Besides, the performance of AutoOED is generally stable and ends up either the best or comparable on most benchmark problems.

6.3 REAL-WORLD OPTIMAL EXPERIMENT DESIGN

We further demonstrate the real-world applicability of AutoOED through applying to optimize a PID heater controller to have optimal response time and minimal overshoot in a fully automated way. Specifically, a PID controller is employed to regulate the temperature of the heater block with proportional, integral, and differential constants. To find the optimal set of constants a number of heating cycles are done asynchronously with the controller using AutoOED. The experiment is comprised of setting the PID constants, then heating the block up to a set temperature, and keeping them at the set duration for 2 minutes. During this time the response time and overshoot are measured. After the heating cycle, the heater is then cooled back down to a starting temperature to prepare for another test with new PID constants. More details can be found in Appendix B.3.

Figure 5: Performance of AutoOED on the benchmark problems compared to other BO platforms. The result of BoTorch on VLMOP3 is omitted as the algorithm fails to stop within 24 hours.

(a) Experiment setup.   (b) Discovered solutions.   (c) Hypervolume.

Figure 6: Physical setup, optimization process and solutions of the PID heater control experiment.

To automate the experiment, we simply link the Python evaluation program of this experiment setup to AutoOED through GUI then start the iterative optimization. Finally, the results are exported as shown in Figure 6, where a set of solutions are discovered with optimal trade-offs between minimal response time and minimal overshoot. Using MOBO algorithms provided by AutoOED is able to discover better designs compared to random sampling at the presence of evaluation noise.

7 CONCLUSION AND FUTURE WORK

We introduced an open-source platform for automated optimal experimental design of multi-objective problems. The platform is of modular structure, facilitating the implementation of different multi-objective Bayesian optimization (MOBO) algorithms and enabling both data- and time-efficient optimization. In addition, the platform includes a novel strategy for asynchronous batch optimization for improved time efficiency. We performed extensive experiments on standard benchmark to demonstrate the performance against other relevant methods. Furthermore, we conducted real-world physical experiments to showcase the automated usage of our platform.

Future work includes implementing additional features, such as expensive constraint handling, advanced noise handling and extending AutoOED's framework to incorporate a even wider range of MOBO algorithms. We are also interested in applying AutoOED to automate more real-world experimental design problems in science and engineering.

REFERENCES

Ahsan S Alvi, Binxin Ru, Jan Calliess, Stephen J Roberts, and Michael A Osborne. Asynchronous batch bayesian optimisation with improved local penalisation. *arXiv preprint arXiv:1901.10452*, 2019.

The GPyOpt authors. GPyOpt: A bayesian optimization framework in python. `http://github.com/SheffieldML/GPyOpt`, 2016.

Maximilian Balandat, Brian Karrer, Daniel R. Jiang, Samuel Daulton, Benjamin Letham, Andrew Gordon Wilson, and Eytan Bakshy. BoTorch: A Framework for Efficient Monte-Carlo Bayesian Optimization. In *Advances in Neural Information Processing Systems 33*, 2020. URL `https://proceedings.neurips.cc/paper/2020/hash/f5b1b89d98b7286673128a5fb112cb9a-Abstract.html`.

Syrine Belakaria and Aryan Deshwal. Uncertainty-aware search framework for multi-objective bayesian optimization. In *AAAI Conference on Artificial Intelligence (AAAI)*, 2020.

Syrine Belakaria, Aryan Deshwal, and Janardhan Rao Doppa. Max-value entropy search for multi-objective bayesian optimization. In *Advances in Neural Information Processing Systems*, pp. 7823–7833, 2019.

Eric Bradford, Artur M Schweidtmann, and Alexei Lapkin. Efficient multiobjective optimization employing gaussian processes, spectral sampling and a genetic algorithm. *Journal of global optimization*, 71(2):407–438, 2018.

Olivier Chapelle and Lihong Li. An empirical evaluation of thompson sampling. In J. Shawe-Taylor, R. S. Zemel, P. L. Bartlett, F. Pereira, and K. Q. Weinberger (eds.), *Advances in Neural Information Processing Systems 24*, pp. 2249–2257. Curran Associates, Inc., 2011. URL `http://papers.nips.cc/paper/4321-an-empirical-evaluation-of-thompson-sampling.pdf`.

Emile Contal, David Buffoni, Alexandre Robicquet, and Nicolas Vayatis. Parallel gaussian process optimization with upper confidence bound and pure exploration. In *Joint European Conference on Machine Learning and Knowledge Discovery in Databases*, pp. 225–240. Springer, 2013.

Ivo Couckuyt, Dirk Deschrijver, and Tom Dhaene. Fast calculation of multiobjective probability of improvement and expected improvement criteria for pareto optimization. *Journal of Global Optimization*, 60(3):575–594, 2014.

Samuel Daulton, Maximilian Balandat, and Eytan Bakshy. Differentiable expected hypervolume improvement for parallel multi-objective bayesian optimization. In H. Larochelle, M. Ranzato, R. Hadsell, M. F. Balcan, and H. Lin (eds.), *Advances in Neural Information Processing Systems*, volume 33, pp. 9851–9864. Curran Associates, Inc., 2020a. URL `https://proceedings.neurips.cc/paper/2020/file/6fec24eac8f18ed793f5eaad3dd7977c-Paper.pdf`.

Samuel Daulton, Maximilian Balandat, and Eytan Bakshy. Differentiable expected hypervolume improvement for parallel multi-objective bayesian optimization. *arXiv preprint arXiv:2006.05078*, 2020b.

Kalyanmoy Deb, Ram Bhushan Agrawal, et al. Simulated binary crossover for continuous search space. *Complex systems*, 9(2):115–148, 1995.

Kalyanmoy Deb, Mayank Goyal, et al. A combined genetic adaptive search (geneas) for engineering design. *Computer Science and informatics*, 26:30–45, 1996.

Kalyanmoy Deb, Amrit Pratap, Sameer Agarwal, and TAMT Meyarivan. A fast and elitist multiobjective genetic algorithm: Nsga-ii. *IEEE transactions on evolutionary computation*, 6(2):182–197, 2002.

Kalyanmoy Deb, Lothar Thiele, Marco Laumanns, and Eckart Zitzler. Scalable test problems for evolutionary multiobjective optimization. In *Evolutionary multiobjective optimization*, pp. 105–145. Springer, 2005.

Thomas Desautels, Andreas Krause, and Joel W Burdick. Parallelizing exploration-exploitation tradeoffs in gaussian process bandit optimization. *Journal of Machine Learning Research*, 15: 3873–3923, 2014.

Michael Emmerich and Jan-willem Klinkenberg. The computation of the expected improvement in dominated hypervolume of pareto front approximations. *Rapport technique, Leiden University*, 34:7–3, 2008.

Eduardo C Garrido-Merchán and Daniel Hernández-Lobato. Dealing with categorical and integer-valued variables in bayesian optimization with gaussian processes. *Neurocomputing*, 380:20–35, 2020.

Michael A Gelbart, Jasper Snoek, and Ryan P Adams. Bayesian optimization with unknown constraints. *arXiv preprint arXiv:1403.5607*, 2014.

David Ginsbourger, Rodolphe Le Riche, and Laurent Carraro. Kriging is well-suited to parallelize optimization. In *Computational intelligence in expensive optimization problems*, pp. 131–162. Springer, 2010.

Javier González, Zhenwen Dai, Philipp Hennig, and Neil Lawrence. Batch bayesian optimization via local penalization. In *Artificial intelligence and statistics*, pp. 648–657. PMLR, 2016.

Stewart Greenhill, Santu Rana, Sunil Gupta, Pratibha Vellanki, and Svetha Venkatesh. Bayesian optimization for adaptive experimental design: A review. *IEEE access*, 8:13937–13948, 2020.

Ryan-Rhys Griffiths and José Miguel Hernández-Lobato. Constrained bayesian optimization for automatic chemical design. *arXiv preprint arXiv:1709.05501*, 2017.

Sebastian Haan. Geobo: Python package for multi-objective bayesian optimisation and joint inversion in geosciences. *Journal of Open Source Software*, 6(57):2690, 2021. doi: 10.21105/joss. 02690. URL https://doi.org/10.21105/joss.02690.

Kirthevasan Kandasamy, Akshay Krishnamurthy, Jeff Schneider, and Barnabás Póczos. Parallelised bayesian optimisation via thompson sampling. In *International Conference on Artificial Intelligence and Statistics*, pp. 133–142. PMLR, 2018.

Kirthevasan Kandasamy, Karun Raju Vysyaraju, Willie Neiswanger, Biswajit Paria, Christopher R. Collins, Jeff Schneider, Barnabas Poczos, and Eric P. Xing. Tuning hyperparameters without grad students: Scalable and robust bayesian optimisation with dragonfly. *Journal of Machine Learning Research*, 21(81):1–27, 2020. URL http://jmlr.org/papers/v21/18-223.html.

Tarun Kathuria, Amit Deshpande, and Pushmeet Kohli. Batched gaussian process bandit optimization via determinantal point processes. *Advances in Neural Information Processing Systems*, 29: 4206–4214, 2016.

Joshua Knowles. Parego: a hybrid algorithm with on-line landscape approximation for expensive multiobjective optimization problems. *IEEE Transactions on Evolutionary Computation*, 10(1): 50–66, 2006.

Nicolas Knudde, Joachim van der Herten, Tom Dhaene, and Ivo Couckuyt. GPflowOpt: A Bayesian Optimization Library using TensorFlow. *arXiv preprint – arXiv:1711.03845*, 2017. URL https://arxiv.org/abs/1711.03845.

Mina Konakovic Lukovic, Yunsheng Tian, and Wojciech Matusik. Diversity-guided multi-objective bayesian optimization with batch evaluations. *Advances in Neural Information Processing Systems*, 33, 2020.

Roman Marchant and Fabio Ramos. Bayesian optimisation for intelligent environmental monitoring. pp. 2242–2249, 10 2012. ISBN 978-1-4673-1737-5. doi: 10.1109/IROS.2012.6385653.

Ruben Martinez-Cantin, Nando Freitas, Eric Brochu, Jose Castellanos, and Arnaud Doucet. A bayesian exploration-exploitation approach for optimal online sensing and planning with a visually guided mobile robot. *Auton. Robots*, 27:93–103, 08 2009. doi: 10.1007/s10514-009-9130-2.

Michael D McKay, Richard J Beckman, and William J Conover. Comparison of three methods for selecting values of input variables in the analysis of output from a computer code. *Technometrics*, 21(2):239–245, 1979.

Jonas Močkus. On bayesian methods for seeking the extremum. In *Optimization techniques IFIP technical conference*, pp. 400–404. Springer, 1975.

Tatsuya Okabe, Yaochu Jin, Markus Olhofer, and Bernhard Sendhoff. On test functions for evolutionary multi-objective optimization. In *International Conference on Parallel Problem Solving from Nature*, pp. 792–802. Springer, 2004.

Biswajit Paria, Kirthevasan Kandasamy, and Barnabás Póczos. A flexible framework for multi-objective bayesian optimization using random scalarizations. In Ryan P. Adams and Vibhav Gogate (eds.), *Proceedings of The 35th Uncertainty in Artificial Intelligence Conference*, volume 115 of *Proceedings of Machine Learning Research*, pp. 766–776. PMLR, 22–25 Jul 2020. URL https://proceedings.mlr.press/v115/paria20a.html.

Nery Riquelme, Christian Von Lücken, and Benjamin Baran. Performance metrics in multi-objective optimization. In *2015 Latin American Computing Conference (CLEI)*, pp. 1–11. IEEE, 2015.

Daniel Russo and Benjamin Van Roy. Learning to optimize via information-directed sampling. In *Advances in Neural Information Processing Systems*, pp. 1583–1591, 2014.

Adriana Schulz, Harrison Wang, Eitan Grinspun, Justin Solomon, and Wojciech Matusik. Interactive exploration of design trade-offs. *ACM Transactions on Graphics (TOG)*, 37(4):1–14, 2018.

Amar Shah and Zoubin Ghahramani. Parallel predictive entropy search for batch global optimization of expensive objective functions. *arXiv preprint arXiv:1511.07130*, 2015.

B. Shahriari, K. Swersky, Z. Wang, R. P. Adams, and N. de Freitas. Taking the human out of the loop: A review of bayesian optimization. *Proceedings of the IEEE*, 104(1):148–175, 2016.

Benjamin J Shields, Jason Stevens, Jun Li, Marvin Parasram, Farhan Damani, Jesus I Martinez Alvarado, Jacob M Janey, Ryan P Adams, and Abigail G Doyle. Bayesian reaction optimization as a tool for chemical synthesis. *Nature*, 590(7844):89–96, 2021.

Jasper Snoek, Hugo Larochelle, and Ryan P Adams. Practical bayesian optimization of machine learning algorithms. *Advances in neural information processing systems*, 25, 2012.

Jasper Snoek, Oren Rippel, Kevin Swersky, Ryan Kiros, Nadathur Satish, Narayanan Sundaram, Mostofa Patwary, Mr Prabhat, and Ryan Adams. Scalable bayesian optimization using deep neural networks. In *International conference on machine learning*, pp. 2171–2180. PMLR, 2015.

Niranjan Srinivas, Andreas Krause, Sham Kakade, and Matthias Seeger. Gaussian process optimization in the bandit setting: no regret and experimental design. In *Proceedings of the 27th International Conference on International Conference on Machine Learning*, pp. 1015–1022, 2010.

William R Thompson. On the likelihood that one unknown probability exceeds another in view of the evidence of two samples. *Biometrika*, 25(3/4):285–294, 1933.

David A Van Veldhuizen and Gary B Lamont. Multiobjective evolutionary algorithm test suites. In *Proceedings of the 1999 ACM symposium on Applied computing*, pp. 351–357, 1999.

J. Wu, W.Y. Zhang, S. Zhang, Y.N. Liu, and X.H. Meng. A matrix-based bayesian approach for manufacturing resource allocation planning in supply chain management. *International Journal of Production Research*, 51(5):1451–1463, 2013. doi: 10.1080/00207543.2012.693966. URL https://doi.org/10.1080/00207543.2012.693966.

Qingfu Zhang, Wudong Liu, Edward Tsang, and Botond Virginas. Expensive multiobjective optimization by moea/d with gaussian process model. *IEEE Transactions on Evolutionary Computation*, 14(3):456–474, 2009.

Yichi Zhang, Daniel W Apley, and Wei Chen. Bayesian optimization for materials design with mixed quantitative and qualitative variables. *Scientific Reports*, 10(1):1–13, 2020.

Eckart Zitzler and Lothar Thiele. Multiobjective evolutionary algorithms: a comparative case study and the strength pareto approach. *IEEE transactions on Evolutionary Computation*, 3(4):257–271, 1999.

Eckart Zitzler, Kalyanmoy Deb, and Lothar Thiele. Comparison of multiobjective evolutionary algorithms: Empirical results. *Evolutionary computation*, 8(2):173–195, 2000.

A PLATFORM DETAILS

A.1 ADDITIONAL FEATURES

Cross-platform AutoOED is a cross-platform software that can be installed as an executable on computers with either Windows/MacOS/Linux system. Installing from source code is also supported for extra flexibility.

Surrogate prediction Users may find AutoOED useful not only in optimization but also in prediction. In addition to the set of optimal solutions, our platform's final product is the learned prediction models of the unknown objectives, which can be used easily from GUI to predict the objectives for a given design from the user. The prediction provides the users with more insights into the potential outcomes of experiments. It helps them better understand the optimization problem to make informed decisions and guide the optimization process towards their preference.

Constraints Besides, AutoOED supports inexpensive black-box constraints on the design space in addition to the bounds. To handle expensive black-box design constraints or objective constraints, it is possible to learn a constraint model similar to learning the objective function, as implemented by Spearmint (Gelbart et al., 2014).

A.2 LIMITATIONS

Number of objectives First, AutoOED is designed to be a multi-objective experimental design platform, so single objective BO is not supported. Several other reasons for not supporting this include the difference between performance criterion of single- and multi-objective, different visualizations and different algorithmic pipeline. Though one can define two identical objectives to simulate single-objective optimization but this might be sub-optimal and we have not tested its performance. AutoOED works best when number of objectives equal 2 or 3, which is the case for most realistic multi-objective applications. We do not recommend solving problems having > 3 objectives if can be simplified because the performance space is *(i)* hard to visualize and *(ii)* exponentially difficult and expensive to explore.

B EXPERIMENT SETUP

B.1 BENCHMARK PROBLEMS

In this section, we briefly introduce the properties of each benchmark problem, including the dimensions of the design space $\mathcal{X} \subset \mathbb{R}^d$ and performance space $\mathbf{f}(\mathcal{X}) \subset \mathbb{R}^m$, and the reference points we use for calculating the hypervolume indicator, which are shown in Table 2. We perform 20 independent test runs with 20 different random seeds for each problem on each algorithm. For each test run of one problem, we use the same initial set of samples for every algorithm, which is generated by Latin hypercube sampling (McKay et al., 1979) using a same random seed. To have a fair comparison, we simply set the reference point $\mathbf{r} \in \mathbb{R}^m$ as a vector containing the maximum value of each objective over the initial set of samples $\{\mathbf{x}_1, ..., \mathbf{x}_k\}$:

$$\mathbf{r} = (\max_{1 \leq i \leq k} f_1(\mathbf{x}_i), ..., \max_{1 \leq i \leq k} f_m(\mathbf{x}_i)).$$

B.2 HYPERPARAMETERS

Here we present all the common hyperparameters that AutoOED uses in the experiments.

Surrogate model We use the same Gaussian process model as the surrogate for all experiments. We use zero mean function and anisotropic Matern 1/2 kernel, which empirically is numerically stable than popular Matern 5/2 kernel in our experiments. The corresponding hyperparameters are specified in Table 3, which are suggested by TSEMO.

Table 2: Basic descriptions of all the benchmark problems.

Name	d	m	$\mathbf{r}$
ZDT1	30	2	(0.9699, 6.0445)
ZDT2	30	2	(0.9699, 6.9957)
ZDT3	30	2	(0.9699, 6.0236)
ZDT4	10	2	(0.9699, 199.6923)
DTLZ1	6	2	(360.7570, 343.4563)
DTLZ2	6	2	(1.7435, 1,6819)
DTLZ3	6	2	(706.5260, 746.2411)
DTLZ4	6	2	(1.8111, 0.7776)
OKA1	2	2	(7.4051, 4.3608)
OKA2	3	2	(3.1315, 4.6327)
VLMOP2	6	2	(1.0, 1.0)
VLMOP3	2	3	(8.1956, 53.2348, 0.1963)

Table 3: GP hyperparameters.

parameter name	value
initial l	$(1, ..., 1) \in \mathbb{R}^d$
l range	$(\sqrt{10^{-3}}, \sqrt{10^3})$
initial σ_f	1
σ_f range	$(\sqrt{10^{-3}}, \sqrt{10^3})$
initial σ_n	10^{-2}
σ_n range	$(e^{-6}, 1)$

Multi-objective evolutionary algorithm The cheap NSGA-II solver employed in AutoOED's MOBO algorithms by default uses simulated binary crossover (Deb et al., 1995) and polynomial mutation (Deb et al., 1996) for finding the Pareto front of acquisition functions. The initial population is obtained from the best current samples determined by non-dominated sort (Deb et al., 2002). The other hyperparameters are specified in Table 4.

Table 4: NSGA-II hyperparameters.

parameter name	value
population size	100
number of generations	200
crossover η_c	15
mutation η_m	20

B.3 REAL-WORLD EXPERIMENT SETUP

The experimental setup is comprised of 3 heaters with identical dimensions and characteristics. Each heater is comprised of a heater block, heating element, temperature sensor, solid-state relay, power supply, and a controller, shown in Figure 7. To run an experiment, AutoOED sends the PID constants to a controller that is free. Next, the PID controller becomes active and starts regulating the temperature of the heater. The temperature sensor measures the temperature of the heater block. Depending on the constants of the PID controller and the temperautre of the heater block, the controller turns

the heating element on or off via the solid-state relay. After a period of 2 minutes where the PID controller is active, the controller stops actively regulating the temperature of the heater allowing the heater to cool. Next, the controller starts to monitor the cooling of the heater via the temperature sensor. It monitors it until the heater block cools to a temperature below a threshold. The amount of time it takes to cool the heater block depends on the temperature that the block was heated to during the active period. Once it sufficiently cools, the controller sends the calculated overshoot and response time to AutoOED and notifies that it is ready to run another experiment.

Figure 7: A schematic of the setup used for the real-world experiment.

C ABLATION STUDIES

C.1 SYNCHRONOUS AND ASYNCHRONOUS MOBO

Following the experiment settings in Section 6, we addtionally compare the performance of synchornous and asynchronous MOBO. As shown in Figure 8, they achieve similar hypervolumes whereas asynchronous MOBO spends less than half of the time of its synchronous counterpart.

C.2 BATCH SIZE

Ablation studies are also conducted on the batch size in asynchronous MOBO. For this category of experiments, we repeat our practice in Section 6.1 while changing the batch size to 4 and 16, respectively. The results are demonstrated in Figure 9 and 10. Our proposed BP strategy maintains its relative lead in VLMOP3 and performs comparably with other variants on the rest of the test problems.

C.3 ACQUISITION FUNCTION

Lastly, we evaluate the asynchronous MOBO variants using the EI acquisition function. Although the change in acquisition function has a clear influence on hypervolume growth, the proposed BP variant still performs favorably in problems such as ZDT2, DTLZ2, and VLMOP2. The performance of BP on the other problems remain comparable to the alternative strategies.

Figure 8: Performance comparison between synchronous and naive asynchronous MOBO algorithms.

Figure 9: Performance comparison between variants of asynchoronous MOBO algorithms with a batch size of 4.

Figure 10: Performance comparison between variants of asynchoronous MOBO algorithms with a batch size of 16.

Figure 11: Performance comparison between variants of asynchoronous MOBO algorithms with EI as acquisition function.