Self-Supervised Logit Adjustment

Abstract

Self-supervised learning (SSL) has achieved tremendous success on various well curated datasets in computer vision and natural language processing. Nevertheless, it is hard for existing works to capture transferable and robust features, when facing the long-tailed distribution in the real-world scenarios. The attribution is that plain SSL methods to pursue *sample-level uniformity* easily leads to the distorted embedding space, where head classes with the huge sample number dominate the feature regime and tail classes passively collapse. To tackle this problem, we propose a novel Self-Supervised Logit Adjustment (S^2LA) method to achieve the *category-level uniformity* from a geometric perspective. Specially, we measure the geometric statistics of the embedding space to construct the calibration, and jointly learn a surrogate label allocation to constrain the space expansion of head classes and avoid the passive collapse of tail classes. Our proposal does not alter the setting of SSL and can be easily integrated into existing works in an end-to-end and low-cost manner. Extensive results on a range of benchmark datasets show the effectiveness of S^2LA with high tolerance to the distribution skewness.

1 Introduction

Recent years have witnessed a great success of self-supervised learning (Doersch et al., 2015; Wang & Gupta, 2015; Chen et al., 2020; Caron et al., 2020). The rapid advances behind this paradigm benefit from the elegant training on data without annotations, which can be acquired in a large-volume and low-cost way. However, the real-world natural sources usually exhibit the long-tailed distribution (Reed, 2001), and directly applying existing self-supervised learning methods will lead to the distorted embedding space, where the majority dominates the feature regime (Zhang et al., 2021) and the minority collapses (Mixon et al., 2022). With the increasing attention on machine learning fairness in the recent years, it becomes a trend to explore self-supervised long-tailed learning (Yang & Xu, 2020; Liu et al., 2021; Jiang et al., 2021; Zhou et al., 2022).

Existing explorations for self-supervised learning in long-tailed context are from three perspectives: *data perspective*, *model perspective* and *loss perspective*. In the data perspective, BCL (Zhou et al., 2022) leverages the memorization effect of deep neural networks (DNNs) to drive an instance-wise augmentation, which learns a better trade-off between head classes and tail classes in representation learning. In the model perspective, SDCLR (Jiang et al., 2021) contrasts the feature encoder and its pruned counterpart to discover hard examples that mostly covers the samples from tail classes, and efficiently enhance the learning preference towards tail classes. In the loss perspective, the reweighting mechanism like rwSAM (Liu et al., 2021) that adopts a data-dependent sharpness-aware minimization scheme, can be applied to explicitly regularize the loss surface. However, in terms of the current performance to self-supervised long-tailed learning, the potential of the loss perspective has not been sufficiently set off, with which in comparison in supervised long-tailed learning, logit adjustment (Menon et al., 2021) of the same perspective has conquered a range of methods.

We dive into the loss perspective and explore to understand *"Why the conventional contrastive learning underperforms in self-supervised long-tailed learning?"* To answer this question, let us consider two types of representation uniformity: (1) *Sample-level uniformity*. As proof in (Wang & Isola, 2020), self-supervised learning targets to distribute the representation of data points uniformly in the embedding space. Then, the feature span of each category is proportional to their corresponding sample number. (2) *Category-level uniformity*. This uniformity pursues to split the region equally for different categories without considering their corresponding sample number (Papyan et al., 2020; Graf et al., 2021). In the case of the class-balanced scenarios, the former uniformity naturally implies

Figure 1: Comparison of S²LA and the plain SSL method on a 2-D imbalanced synthetic dataset. (Left) Visualization of the 2-D synthetic dataset. (Middle) The embedding distribution of each category learnt by the plain SSL method is approximately proportional to the sample number. (Right) S²LA reduces the adverse effect of class imbalance and approaches to the category-level uniformity.

the latter uniformity and induces the equivalent separability for classification. However, in the class-imbalanced cases, especially in long-tailed setting, sample-level uniformity leads to the undesired feature regime of head classes due to its dominant sample proportion. In comparison, category-level uniformity constrains the greedy expansion of head classes and prevents the passive collapse of tail classes, which is more benign to the downstream classification (Graf et al., 2021; Fang et al., 2021; Li et al., 2022). Unfortunately, there is no support regarding category-level uniformity in contrastive learning losses, which provides an answer to the question arisen at the beginning.

Inspired by logit adjustment (LA) for supervised long-tailed learning, we propose a novel method, termed as *Self-Supervised Logit Adjustment* (S²LA), to calibrate self-supervised long-tailed learning from the geometric perspective. Specially, unlike LA that requires the class distribution available, S²LA uses a constant Simplex ETF to measure the geometric characteristics of the embedding space for adjustment. Together with a surrogate label allocation to compute the target, we can then explicitly compress the greedy space expansion of head classes and avoid the passive collapse of tail classes. Their alternation refers to an ordinary balancing and an efficient optimal-transport problem, which dynamically approaches towards the category-level uniformity. In Figure 1, we give a toy experiment to compare the learnt representation without and with S²LA in the embedding space.

The contribution can be summarized as follows,

1. We are among the first attempts to study the drawback of the contrastive learning loss in self-supervised long-tailed context and point out that the resulting sample-level uniformity is an intrinsic limitation, driving our exploration for category-level uniformity (Section 4).

2. We develop a novel *Self-Supervised Logit Adjustment* (Figure 2), which dynamically adjusts the embedding distribution to calibrate the geometric statistics and conducts a surrogate label allocation for category-level uniformity in an efficient end-to-end manner.

3. Our method can be easily plugged into previous methods of self-supervised long-tailed learning (Eq. 7). Extensive experiments on a range of benchmark datasets demonstrate the consistent improvement of our S²LA with high tolerance to the distribution skewness.

2 RELATED WORKS

Self-Supervised Long-tailed Learning. There are several recent explorations devoted to this directions from data, model and loss perspectives. BCL (Zhou et al., 2022) leverages the memorization effect of DNNs to drive an instance-wise augmentation, which enhances the learning of tail samples. SDCLR (Jiang et al., 2021) constructs a self-contrast between model and its pruned counterpart to learn more balanced representation. Classic Focal loss (Lin et al., 2017) leverages the loss statistics to putting more emphasis on the hard examples, which has been applied to self-supervised long-tailed learning. rwSAM (Liu et al., 2021) proposes to penalize loss sharpness in a reweighting manner to similarly calibrate class-imbalance learning. However, the potential of the loss perspective has not been set-off due to the intrinsic limitation of the conventional contrastive learning loss.

Hyperspherical Uniformity. The distribution uniformity has been extensively explored from the physic area, *e.g.*, Thomson problem (Thomson, 1904; Smale, 1998), to machine learning area like

some kernel-based extensions *e.g.*, Riesz s-potential (Hardin & Saff, 2005; Liu et al., 2018) or Gaussian potential (Cohn & Kumar, 2007; Borodachov et al., 2019; Wang & Isola, 2020). Some recent explorations regarding features of DNNs (Papyan et al., 2020; Fang et al., 2021; Mixon et al., 2022) discover a terminal training stage when the embedding collapses to the geometric means of the classifier *w.r.t.* each category. Specially, these optimal class means specify a maximum separation structure, termed as Simplex Equiangular Tight Frame, and achieve the perfect uniform distribution under some dimensional constraints (Zhu et al., 2021; Yang et al., 2022; Kasarla et al., 2022). In this paper, we incorporate Simplex ETF into self-supervised learning and leverage the specific structure as a uniform prior to capture the geometric statistics for calibration of the embedding distribution.

3 PRELIMINARIES

3.1 PROBLEM FORMULATION

Given a dataset $\mathcal{D}$, for each $(\boldsymbol{x}, \boldsymbol{y}) \in \mathcal{D}$, the input $\boldsymbol{x} \in \mathbb{R}^m$ and the associated label $\boldsymbol{y} \in \{1, \ldots, L\}$. We define the imbalanced ratio as $\max_i p(\boldsymbol{y} = i)/\min_i p(\boldsymbol{y} = i)$. In SSL, the ground-truth $\boldsymbol{y}$ is not accessed and the goal is to transform an image to an embedding via DNNs $f_\theta : \mathbb{R}^m \to \mathbb{R}^d$. In the linear probing evaluation, we construct a supervised learning task with balanced datasets. A linear classifier g is built on top of the feature extractor f_θ to produce prediction, namely, $g \circ f_\theta(\boldsymbol{x})$, where $\circ$ represents the function composition operator.

3.2 LOGIT ADJUSTMENT IN SUPERVISED LONG-TAILED LEARNING

Logit adjustment manipulates the logits of prediction to remove the adverse effect of class-imbalance, which has shown efficiency in various supervised long-tailed explorations (Provost, 2000; Brodersen et al., 2010; Ren et al., 2020; Menon et al., 2021). Let $p(\boldsymbol{y}), p_{bal}(\boldsymbol{y})$ be the label distribution of the long-tailed training dataset and the balanced test set, we can derive $p(\boldsymbol{y}|\boldsymbol{x}) \propto p(\boldsymbol{x}|\boldsymbol{y})p(\boldsymbol{y})$ and $p_{bal}(\boldsymbol{y}|\boldsymbol{x}) \propto p(\boldsymbol{x}|\boldsymbol{y})p_{bal}(\boldsymbol{y})$ based on the Bayes' theorem. Assuming class-conditional probabilities $p(\boldsymbol{x}|\boldsymbol{y})$ are the same on training and test set, we have $p(\boldsymbol{y}|\boldsymbol{x}) \propto p_{bal}(\boldsymbol{y}|\boldsymbol{x})p(\boldsymbol{y})$. This indicates that learning under long-tailed data leads to a prediction shift proportional to $p(\boldsymbol{y})$ compared with the optimal classifier on the uniform test set. To this end, logit adjustment adds an offset on the logits to calibrate the statistical shift, namely,

$$p_{bal}(\boldsymbol{y}|\boldsymbol{x}) \propto p(\boldsymbol{y}|\boldsymbol{x})/p(\boldsymbol{y}) \propto \mathrm{softmax}(s(\boldsymbol{x}) - \log p(\boldsymbol{y})), \tag{1}$$

where $s(\boldsymbol{x})$ denotes the logits of the training samples and $\mathrm{softmax}(\cdot)$ is the Softmax function. Logit adjustment are well grounded to be Fisher consistent for minimising the balanced error (Menon et al., 2021), thus extended to a range of class-imbalanced scenarios (Ren et al., 2022).

3.3 SIMPLEX EQUIANGULAR TIGHT FRAME

Neural collapse (Mixon et al., 2022) describes a phenomenon that with the training, the geometric centroid of representation progressively collapses to the optimal classifier parameter *w.r.t.* each category. The collection of these points builds a special geometric structure, termed as Simplex Equiangular Tight Frame (ETF). Some study that shares the similar spirit is also explored regarding the maximum separation structure (Kasarla et al., 2022). We present its formal definition as follows.

Definition 3.1. A Simplex ETF is a collection of points in $\mathbb{R}^d$ specified by the columns of the matrix:

$$\mathbf{M} = \sqrt{\frac{K}{K-1}} \mathbf{U}(\mathbf{I}_K - \frac{1}{K} \mathbb{1}_K \mathbb{1}_K^{\mathrm{T}}) \tag{2}$$

where $\mathbf{I}_K \in \mathbb{R}^{K \times K}$ is the identity matrix and $\mathbb{1}_K$ is the K-dimensional ones vector. $\mathbf{U} \in \mathbb{R}^{d \times K}$ is the patial orthogonal matrix such that $\mathbf{U}^\top \mathbf{U} = \mathbf{I}_K$ and it satisfys $d \geq K$. All vectors in a Simplex ETF have the same pair-wise angle, *i.e.*, $\boldsymbol{m}_i \boldsymbol{m}_j = -\frac{1}{K-1}, i \neq j$. The pioneering work (Yang et al., 2022) shows Simplex ETF as a linear classifier combined with neural networks is robust to class-imbalanced learning in the supervised setting. In our self-supervised learning, we use the maximum separation property of Simplex ETF as a measure to characterize the representation uniformity.

4 SELF-SUPERVISED LOGIT ADJUSTMENT

Plain SSL methods encourage the sample-level uniformity in the embedding space, yielding the undesired property in long-tailed context. Specially, head classes will dominate the feature regime along with the collapse of tail classes. To solve this problem, one straightforward idea is to counteract the long-tailed effect like logit adjustment in supervised long-tailed learning. However, the core challenge in self-supervised learning is that there is no class-distribution prior available to characterize the imbalance degree. To address this issue, we propose to use Simplex ETF to measure the embedding space, and then the captured geometric statistics are used to properly adjust the embedding distribution alongside a surrogate label allocation. Concretely, we define an constant classifier $\mathbf{M} \in \mathbb{R}^{d \times K}$ following Eq. 2, and then compute the geometric label of each sample as follows:

$$\boldsymbol{t} = \arg\max_i h_i(\boldsymbol{x}), \quad \text{where} \quad h_i(\boldsymbol{x}) = \mathbf{M}_i^\top f_\theta(\boldsymbol{x}).$$

On the basis of such a positional indicator, we can further derive a group-level statistic to characterize the category-level uniformity, i.e., $p(\boldsymbol{t} = i) = \mathbb{E}_{\boldsymbol{x} \sim \mathcal{D}}[\mathbb{1}(\boldsymbol{t} = i)], i = 1, \ldots, K$, where $\mathbb{1}(\cdot)$ denotes the indicator function with the value 1 when its argument is true and 0 otherwise. In the balanced setting, we maintain an approximately uniform distribution while in long-tailed context, we face a more skewed geometric distribution for the category-level uniformity.

Logit Adjustment. Different from the ordinary logit adjustment that removes the class imbalance in $p(\boldsymbol{t})$ and exacerbates the space expansion, here we aim to shrink the feature span of head classes for the category-level uniformity, and thus reversely adjust the logits, namely:

$$\tilde{\boldsymbol{t}} = \arg\max p(\boldsymbol{t}|\boldsymbol{x})p(\boldsymbol{t})^\tau = \arg\max h(\boldsymbol{x}) + \tau \cdot \log p(\boldsymbol{t}) \tag{3}$$

where $p(\boldsymbol{t}|\boldsymbol{x}) = \text{softmax}(h(\boldsymbol{x}))$ denotes the output probabilities of the geometric classifier and τ is a hyper-parameter to temper the adjustment. We can derive $p(\tilde{\boldsymbol{t}}|\boldsymbol{x}) \propto p(\boldsymbol{x}|\boldsymbol{t})p(\boldsymbol{t})^{1+\tau}$ based on Bayes' theorem, which refers to an exponential growth over the original distribution $p(\boldsymbol{t}|\boldsymbol{x}) \propto p(\boldsymbol{x}|\boldsymbol{t})p(\boldsymbol{t})$. This fulfills an elastic adjustment on the embedding skewness. However, since there is no ground-truth annotation of each sample, naively using the geometric label tends to have trivial *unconstrained probabilities* with a low entropy. To handle these problems, we learn a surrogate label allocation together with logit adjustment here. Specifically, we propose the following objective:

$$\min_{p,q} -\frac{1}{|\mathcal{D}|} \sum_{x \sim \mathcal{D}} q(\boldsymbol{t}|\boldsymbol{x}) \log p(\boldsymbol{t}|\boldsymbol{x}), \quad \text{s.t.} \quad \mathbb{E}_{\boldsymbol{x} \sim \mathcal{D}}[q(\boldsymbol{t}|\boldsymbol{x})] = p(\tilde{\boldsymbol{t}}) \tag{4}$$

where $p(\tilde{\boldsymbol{t}} = i) = \mathbb{E}_{\boldsymbol{x} \sim \mathcal{D}}[\mathbb{1}(\tilde{\boldsymbol{t}} = i)], i = 1, \ldots, K$ and the constraint guarantees the adjusted group-level statistics. Since jointly optimizing Eq. 4 easily falls into a trivial solution, we resorts to solving an optimal transport problem for label allocation on $q(\boldsymbol{t}|\boldsymbol{x})$ and then optimize the model parameters.

Label Allocation. We first reformulate Eq. 4 as an optimal transport (OT) problem. Denote the assignments $Q \in \mathbb{R}^{K \times N}$ for distributing N samples to K classes with the minimal transportation cost and let $C = -\log P$ to retain the equivalent objective, where $P \in \mathbb{R}^{K \times N}$ are the joint probabilities derived from $q(\boldsymbol{t}|\boldsymbol{x})$. We can rewrite Eq. 4 as the following form:

$$\min_{Q \in \mathbb{R}^{K \times N}} \langle Q, C \rangle, \quad \text{s.t.} \quad Q \cdot \mathbb{1}_N = p(\tilde{\boldsymbol{t}}), \ Q^{\text{T}} \cdot \mathbb{1}_K = \mathbb{1}_N \tag{5}$$

This objective can be efficiently solved by adopting *Sinkhorn-Knopp algorithm* (Cuturi, 2013) with an additional entropy regularization to the objective, i.e., $\min_Q \langle Q, C \rangle - \frac{1}{\lambda} \text{H}(Q)$. Here, we define the entropy of Q as $\text{H}(Q) = -\sum_i \sum_j Q_{ij} \log Q_{ij}$. We can then obtain the solution as:

$$Q = \text{diag}(\boldsymbol{u}) \exp(-\lambda C) \text{diag}(\boldsymbol{v}) \tag{6}$$

where $\boldsymbol{u}, \boldsymbol{v}$ are two non-negative vectors of $\mathbb{R}^d$. We iteratively update $\boldsymbol{u}$ and $\boldsymbol{v}$ to reach the desired row and column marginals of Q. The coefficient λ controls the smoothness of the low-cost assignments. As $\lambda \to \infty$, we can approach the optimum of the OT problem at the cost of convergence speed. We keep λ at a relative high level to maintain good clustering results. To improve the efficiency, we estimate $p(\tilde{\boldsymbol{t}})$ over the whole training dataset and learn the label allocation $q(\boldsymbol{t}|\boldsymbol{x})$ in the mini-batch manner. Besides, we maintain a momentum update mechanism to track the output logits of each sample to stabilize the training, i.e., $h^m(\boldsymbol{x}) \leftarrow \beta h^m(\boldsymbol{x}) + (1-\beta)h(\boldsymbol{x})$. Given the surrogate labels $q(\boldsymbol{t}|\boldsymbol{x})$, we can directly optimize $p(\boldsymbol{t}|\boldsymbol{x})$ by minimising the cross-entropy loss, which can be

Figure 2: Illustration of S²LA on the top of SSL. We utilize the Simplex ETF structure to measure the embedding space, and the captured geometric statistics are used for the target calibration in logit adjustment. Simultaneously, an optimal transport optimization for label allocation is performed together with adjustment to avoid the trivial solutions. The additional model parameters introduced by S²LA are trained with SSL efficiently in an end-to-end manner.

considered as the alignment to the desired geometric distribution. We illustrate S²LA in Figure 2 and summarize the complete procedure in Algorithm 1 in the appendix.

Overall Objective. S²LA is compatible with the general self-supervised learning methods as it is constructed on the surrogate geometric analysis to rectify the distorted embedding space in long-tailed context. For example, if we build S²LA on SimCLR, the overall objective is defined as:

$$\mathcal{L} = \frac{1}{|\mathcal{B}|}\sum_{b\in\mathcal{B}}\frac{1}{|\mathcal{X}_b|}\sum_{\boldsymbol{x}\in\mathcal{X}_b}\left(-\log\frac{\exp\left(f_\theta(\boldsymbol{x})^\top f_\theta(\boldsymbol{x}^+)/\gamma\right)}{\sum_{x^-\in\mathcal{X}_b^-\cup\{\boldsymbol{x}^+\}}\exp\left(f_\theta(\boldsymbol{x})^\top f_\theta(\boldsymbol{x}^-)/\gamma\right)} - q(\boldsymbol{t}|\boldsymbol{x}^+)\log p(\boldsymbol{t}|\boldsymbol{x})\right)$$

(7)

where $\boldsymbol{x}, \boldsymbol{x}^+$ is set as different augmented view of the same input image and $\boldsymbol{x}^-$ denotes the rest images in the mini-batch. $\mathcal{X}_b$ is the sampled batch and $\mathcal{X}_b^-$ is the negative sample set with b as the batch index. γ represents the temperature hyper-parameter.

Remark 4.1. Although S²LA iteratively infers the surrogate labels and applies them for re-balanced training, it incurs only a small amount of computational or memory overhead. Specifically, the standard optimization of deep neural networks requires forward and backward step in each mini-batch update with the time complexity as $\mathcal{O}(M\Lambda)$, where M is the mini-batch size and Λ is the parameter size. At the parameter level, we add an additional classifier with the complexity as $\mathcal{O}(MKd)$, where K is the class number and d is the embedding dimension. Besides, Sinkhorn-Knopp algorithm only refers to a simple matrix-vector multiplication $u \leftarrow r./\exp(-\lambda C)v, v \leftarrow c./[\exp(-\lambda C)]^\top u$, whose complexity is $\mathcal{O}(L(M + K + MK))$ with the iteration step L. The complexity incurred in the momentum update is $\mathcal{O}(MK)$. Since K, d and L is significantly smaller than the model parameter Λ of a million scale, the computational overhead involved in S²LA is negligible compared to $\mathcal{O}(M\Lambda)$. The additional storage is the vector $h^m(\boldsymbol{x}) \in \mathbb{R}^{K\times M}$, which is also negligible to the memory usage. In total, our method incurs only a small computation or memory overhead and can thus be plugged into baseline methods in a low-cost manner.

4.1 DISCUSSION

Relation to Supervised Logit Adjustment. In supervised long-tailed learning, the optimal class-probabilities $p_{bal}(\boldsymbol{y}|\boldsymbol{x})$ follow the uniform distribution, which is aligned with the underlying ground-truth distribution $p_{bal}(\boldsymbol{y})$ on the test set. In contrast, the surrogate label distribution $p(\boldsymbol{t})$ in SSL encodes the positional information, which is better to be imbalanced. In our algorithm, we push away $p(\boldsymbol{t}|\boldsymbol{x})$ from $p_{bal}(\boldsymbol{t}|\boldsymbol{x})$ by replacing the division operation of Eq. 1 with multiplication, *i.e.*, $p_{imb}(\boldsymbol{t}|\boldsymbol{x}) \propto p(\boldsymbol{t}|\boldsymbol{x})p(\boldsymbol{t})^\tau$. Although it seems that we reversely enlarges the skewness of the geometric prediction, the surrogate supervised learning via Eq. 5 actually guarantees the space shrinking of head classes and the space expansion of tail classes.

Difference from Unsupervised Clustering. Compared with previous explorations (Asano et al., 2020; Caron et al., 2020), the uniqueness of our proposed S²LA lies in the following two aspects: (1) *Geometric Classifier.* The pioneering works mainly resort to a learnable classifier to perform clustering, which can easily be distorted in the long-tailed scenarios (Fang et al., 2021). Built on the

maximum separation classifier, our method is capable to provide clustering results with clear geometric interpretations. (2) *Adjustable Class Prior*. The class prior are assumed to be uniform among the previous attempts. When moving to the long-tailed case, this assumption will cause the undesired sample-level uniformity. In contrast, our methods can potentially cope with any distribution with a proper adjustment. In Section 5.4, we empirically demonstrate the priority of our S^2LA.

5 EXPERIMENTS

5.1 EXPERIMENTAL SETUP

Datasets. We conduct experiments on three benchmark datasets for long-tailed learning, including CIFAR-100-LT (Cao et al., 2019), ImageNet-LT (Liu et al., 2019) and Places-LT (Liu et al., 2019). For small-scale datasets, we adopt the widely-used CIFAR-100-LT with the imbalanced factor of 100, 50 and 10 (Cao et al., 2019). The statistics of all datasets are summarized in the appendix.

Baselines. We choose four representative state-of-the-art methods: one is a plain SSL method SimCLR (Chen et al., 2020) and the other three are Focal (Lin et al., 2017), SDCLR (Jiang et al., 2021) and BCL (Zhou et al., 2022) respectively from *loss*, *model* and *data* perspectives.

Implementation Details. Following previous works (Jiang et al., 2021; Zhou et al., 2022), we use ResNet-18 as the backbone for small-scale dataset (CIFAR-100-LT) and ResNet-50 for large-scale datasets (ImageNet-LT/Places-LT). For experiments on CIFAR-100-LT, we train model with the SGD optimizer for 1000 epochs with the batch size 512, momentum 0.9 and weight decay factor 5×10^{-4} and use the cosine annealing decay with the initial learning rate as 0.5. For experiments on ImageNet-LT and Places-LT, we only train for 500 epochs with the batch size 256 and decrease the weight decay factor to 1×10^{-4}. Other pre-training setups like the data augmentation and projector structure follow (Jiang et al., 2021; Zhou et al., 2022). For τ in S^2LA, we choose from [0.03,0.04,0.05,0.06,0.07] on CIFAR-100-LT and 0.02 for Places-LT and ImageNet-LT. We set the dimension K as 100 and the Sinkhorn iteration as 300. As S^2LA is combined with baselines, warmup of 500 epochs on CIFAR-100-LT and 400 epochs on ImageNet-LT and Places-LT is applied.

Evaluation Metrics. Following (Jiang et al., 2021; Zhou et al., 2022), *linear probing* on a balanced dataset is used for evaluation. We conduct full-shot evaluation on CIFAR-100-LT and few-shot evaluation on ImageNet-LT and Places-LT. We report the model performance and the standard deviation among three disjoint groups, *i.e.*, many/medium/few partitions (Liu et al., 2019).

5.2 SELF-SUPERVISED LONG-TAILED LEARNING PERFORMANCE

CIFAR-100-LT. In Table 1, we compare methods with and without S^2LA, and analyze as follows.

(1) *Overall performance.* S^2LA shows a consistent gain in many/medium/few groups, yielding a overall performance improvements averaging as 2.32%, 2.33% and 1.57% under different imbalance ratios. In particular, compared with previous state-of-the-art BCL, with S^2LA, BCL further achieves improvements by 1.20%, 1.82% and 1.22% on CIFAR-100-LT-R100/R50/R10.

(2) *Representation balancedness.* Previously, we claim S^2LA help compress the expansion of head classes and avoid the passive collapse of tail classes, yielding a more balanced representation distribution. To certify this aspect, we compute the difference in performance among many/medium/few groups, namely, their groupwise standard deviation. Our method provides 1.41%/2.32%/3.24%, 1.95%/2.45%/2.60% and 1.26%/1.55%/1.89% improvements *w.r.t.* many/medium/few group on CIFAR-100-LT-R100/R50/R10 with more preference to the tail classes. Therefore, S^2LA substantially improves the standard deviation by 0.72/0.41/0.44 on CIFAR-100-LT-R100/R50/R10.

(3) *Regarding skewness.* Our method can be generalized to practical distributions with varying levels of skewness as the algorithm does not refer to any information about the distribution prior.

ImageNet-LT and Places-LT. Table 2 shows the comparison of different methods on large-scale dataset ImageNet-LT and Places-LT, in which we have similar observations. As can be seen, on more challenging real-world data, S^2LA still outperforms other methods in terms of overall accuracy, averaging as 0.58%, 0.44% on ImageNet-LT and Places-LT. Specifically, our method provides 0.43%/2.30%/3.50% and 0.58%/0.83%/0.55% improvements in linear probing

Table 1: Linear probing on CIFAR-100-LT with different imbalanced ratios (100,50,10). Std means the group-level performance standard deviation and Avg is the average accuracy of full test set. Std represents a balancedness measure to quatify the variance among three specified groups. Here, Many/Med/Few indicate the fine-grained groups according to the class cardinality.

Method	CIFAR-100-LT-R100					CIFAR-100-LT-R50					CIFAR-100-LT-R10				
	Many	Med	Few	Std	Avg	Many	Med	Few	Std	Avg	Many	Med	Few	Std	Avg
SimCLR	54.97	49.39	47.67	3.82	50.72	56.00	50.48	50.12	3.30	52.24	57.85	55.06	54.03	1.98	55.67
+S^{2}LA	57.38	52.27	52.12	2.99	53.96	58.88	53.00	54.27	3.09	55.42	59.26	56.91	55.85	1.75	57.36
Improv.	**+2.41**	**+2.88**	**+4.45**	**-0.82**	**+3.24**	**+2.88**	**+2.52**	**+4.15**	**-0.20**	**+3.18**	**+1.41**	**+1.85**	**+1.82**	**-0.23**	**+1.69**
Focal	54.24	49.58	49.21	2.80	51.04	55.40	51.14	50.02	2.84	52.22	58.18	55.82	54.64	1.80	56.23
+S^{2}LA	57.01	52.93	51.74	2.76	53.92	57.97	53.55	53.58	2.54	55.06	60.06	56.79	57.24	1.77	58.05
Improv.	**+2.77**	**+3.35**	**+2.53**	**-0.04**	**+2.88**	**+2.57**	**+2.41**	**+3.56**	**-0.30**	**+2.84**	**+1.88**	**+0.97**	**+2.60**	**-0.03**	**+1.82**
SDCLR	57.32	50.70	50.45	3.90	52.87	57.50	51.85	52.15	3.18	53.87	58.47	54.79	52.97	2.80	55.44
+S^{2}LA	57.44	52.85	54.06	2.38	54.81	58.47	53.88	53.58	2.74	55.34	59.21	56.06	55.58	1.97	56.97
Improv.	**+0.12**	**+2.15**	**+3.61**	**-1.52**	**+1.94**	**+0.97**	**+2.03**	**+1.43**	**-0.44**	**+1.47**	**+0.74**	**+1.27**	**+2.61**	**-0.83**	**+1.53**
BCL	59.15	54.82	55.30	2.37	56.45	59.44	54.73	57.30	2.36	57.18	60.41	57.15	59.76	1.73	59.12
+S^{2}LA	59.50	55.73	57.67	1.89	57.65	60.82	57.58	58.55	1.66	59.00	61.41	59.27	60.30	1.07	60.34
Improv.	**+0.35**	**+0.91**	**+2.37**	**-0.49**	**+1.20**	**+1.38**	**+2.85**	**+1.25**	**-0.70**	**+1.82**	**+1.00**	**+2.12**	**+0.54**	**-0.66**	**+1.22**

Table 2: Linear probing on ImageNet-LT and Places-LT. Similarly, Std means the group-level performance standard deviation and Avg is the average accuracy of full test set. Std represents a balancedness measure to quatify the variance among three specified groups. Here, Many/Med/Few indicate the fine-grained partitions according to the class cardinality.

Method	ImageNet-LT					Places-LT				
	Many	Med	Few	Std	Avg	Many	Med	Few	Std	Avg
SimCLR	41.69	33.96	31.82	5.19	36.65	31.98	34.05	35.63	1.83	33.61
+S^{2}LA	41.53	36.35	35.84	3.15	38.28	32.46	35.03	36.14	1.89	34.33
Improv.	**-0.16**	**+2.39**	**+4.02**	**-2.04**	**+1.63**	**+0.48**	**+0.98**	**+0.51**	**+0.06**	**+0.72**
Focal	42.04	35.02	33.32	4.62	37.49	31.69	34.33	35.73	2.05	33.65
+S^{2}LA	42.55	36.75	36.28	3.49	38.92	32.40	35.14	36.49	2.08	34.42
Improv.	**+0.51**	**+1.73**	**+2.96**	**-1.13**	**+1.43**	**+0.71**	**+0.81**	**+0.76**	**+0.03**	**+0.77**
SDCLR	40.87	33.71	32.07	4.68	36.25	32.17	34.71	35.69	1.82	33.99
+S^{2}LA	41.92	36.53	36.04	3.26	38.53	32.78	35.60	36.18	1.82	34.70
Improv.	**+1.05**	**+2.82**	**+3.97**	**-1.42**	**+2.28**	**+0.61**	**+0.89**	**+0.49**	**0.00**	**+0.71**
BCL	42.92	35.89	33.93	4.73	38.33	32.69	35.37	37.18	2.26	34.76
+S^{2}LA	43.22	38.16	36.96	3.32	39.95	33.22	36.00	37.62	2.23	35.32
Improv.	**+0.30**	**+2.27**	**+3.03**	**-1.40**	**+1.62**	**+0.53**	**+0.63**	**+0.44**	**-0.03**	**+0.56**

w.r.t. many/medium/few group on ImageNet-LT and Places-LT. The consistent performance overhead indicates the robustness of our method to deal with long-tailed distribution with different characteristics. Moreover, the averaging improvement of standard deviation is 1.50 on ImageNet-LT, indicating the comprehensive merits on the tail classes towards representation balancedness. However, an interesting phenomenon is that the fine-grained performance exhibits a different trend on Places-LT. We observe that the standard deviation of our method does not significantly decrease on Places-LT. A possible explanation is that the head classes suffer from a severer over-expansion in the scene-centric scenario. As can be seen, the performance of head classes is even worse than that of tail classes, which requires more effort and exploration for improvement alongside S^{2}LA.

5.3 DOWNSTREAM SUPERVISED LONG-TAILED CLASSIFICATION

In supervised long-tailed learning, self-supervised learning has been proved to be beneficial as a pre-training stage to exclude the explicit bias from the class imbalance (Yang & Xu, 2020; Liu et al., 2021; Zhou et al., 2022). In order to validate the representation transferability of S^{2}LA, we conduct self-supervised pre-training as the initialization for downstream supervised classification tasks on CIFAR-100-LT-R100 and ImageNet-LT. The state-of-the-art logit adjustment (Menon et al., 2021) is chosen as the baseline. The combination of S^{2}LA + LA is interpreted as a method where S^{2}LA aims at the re-balanced representation extraction and LA copes with the debiased classifier learning. In Table 3, we can find that the superior performance improvements is achieved by self-supervised pre-training over the direct supervised learning baseline. We can also observe that our method consistently outperforms other methods, averaging as 0.81% and 0.35% on CIFAR-100-LT-R100

Table 3: Supervised long-tailed learning by finetuning on CIFAR-100-LT-R100 and ImageNet-LT. We compare the performance of four self-supervised learning methods as the pre-training stage for downstream supervised logit adjustment (Menon et al., 2021) method. Besides, the performance of logit adjustment via learning from scratch is also reported for comparisons.

Dataset	LA	Logit adjustment pretrained with the following SSL methods											
		SimCLR	+S²LA	**Improv.**	Focal	+S²LA	**Improv.**	SDCLR	+S²LA	**Improv.**	BCL	+S²LA	**Improv.**
CIFAR-100-LT	46.61	49.95	50.67	**+0.72**	49.87	50.98	**+1.11**	49.88	50.69	**+0.81**	50.38	50.99	**+0.61**
ImageNet-LT	48.27	51.10	51.64	**+0.54**	51.25	51.52	**+0.27**	51.01	51.33	**+0.32**	51.50	51.76	**+0.26**

and ImageNet-LT. These results demonstrate that S²LA are well designed to facilitate long-tailed representation learning and improve the generalization ability for downstream supervised tasks.

5.4 FURTHER ANALYSIS AND ABLATION STUDIES

On dimension of Maximum Separation Structure. For Simplex ETF, there is a hard dimension constraint in Eq. 2, *i.e.*, $d < K$. However, if this constraint violates, we do not have such a structure in the hyperspherical space. Alternatively, we can conduct the gradient descent to find an approximation of the maximum separation prototypes applied into S²LA. This refers to minimising the following loss function as demonstrated in (Li et al., 2022).

$$\mathcal{L}_{\text{uniform}} = \log \sum_i^K \sum_j^K e^{\tilde{\boldsymbol{m}}_i \cdot \tilde{\boldsymbol{m}}_j / \tau_{\text{u}}}, \quad \text{s.t.} \quad \sum_i^K \tilde{\boldsymbol{m}}_i = 0 \text{ and } \forall i \in K \ \|\tilde{\boldsymbol{m}}_i\| = 1 \qquad (8)$$

where the first term penalizes the pairwise similarity of different prototypes (Wang & Isola, 2020) under the constraints of Simplex ETF. Figure 3 shows the performance of S²LA equipped with different dimension of the geometric structure by analytical and approximate ways. Comparing the results of Simplex ETF with those of proxy weights, we can see that the comparable performance is achieved in both geometric structures. This indicates that our method is effective to two forms of the geometric structure, relaxing the hard dimensional constraints in Simplex ETF.

Figure 3: Linear probing performance w.r.t. the dimensionality d of the pre-defined classifier on CIFAR-100-LT-R100. We use simplex ETF structure when $d < K$ or otherwise the approximation learned via Eq. 8.

Diverse Pre-defined Skewed Constraints. To further validate the advantage of logit adjustment in S²LA , we alternate the estimated constraints in the OT problem with the fixed imbalanced prior based on the ground-truth label distribution. We explore the effect of the imbalanced prior by adding a temperature factor T, which softens the prior to various scale of skewness. As shown in Figure 4(a), we observe that S²LA outperforms all models pretrained with the imbalanced prior. A possible reason is that our method captures the inherent geometric statistics from the embedding space, which is different from the the label space. This is aligned with the empirical results that the model achieves the worst performance with the vanilla ground-truth prior ($T = 1$), whereas achieving the best performance with the prior closest to S²LA ($T = 0.6$). Moreover, we observe that the uniform prior ($T = 0$) adopted in (Asano et al., 2020; Caron et al., 2020) does not show the expected performance on the long-tailed data.

Clustering Quality. We track the normalized mutual information (Strehl & Ghosh, 2002) of the geometric predictions with the ground-truth label in the training stage on CIFAR-100-LT. As shown in Figure 4(b), we observe that S²LA significantly improves the NMI score across different methods, indicating that the distorted embedding space are calibrated to better capture the semantic information. Moreover, we find that the NMI improvements of the existing works are marginal compared with S²LA, which verifies the importance of calibrating the distorted embedding space.

(a) Pre-defined Prior	(b) NMI with GT Labels	(c) Embedding Statistics

Figure 4: (a) Linear probing performance *w.r.t.* the ground-truth prior served as the categorical constraints in the clustering stage. We soften the oracle distribution by T to obtain diverse imbalanced priors and report the corresponding imbalanced factor. (b) Normalized mutual information (NMI) between the geometric predictions and the ground-truth labels throughout training. (c) Histograms of geometric predictions at the end of the warm-up stage (vanilla) or at the end of training (adjusted).

Embedding Statistics. In Figure 4(c), we plot the geometric prediction histogram at two stages in the training process, *i.e.*, warm-up stage (vanilla) and the end of training stage (adjusted). We observe that the adjusted distribution are more imbalanced than the vanilla distribution. Specifically, it shows more samples are assigned to the instance-rich classes with the shrinking of instance-poor classes. This is aligned with the goal to compress the feature span of head classes and encourage the expansion of tail classes.

Hyper-parameter τ for S^{2}LA . We can adjust the coefficient τ to control the direction and strength of S^{2}LA , as shown in Figure 5. For each τ, we perform performance evaluation and skewness estimation, providing the inherent characteristics of our method. From the figure, the correlation between the coefficient τ and the embedding skewness indicates that we can adjust the skewness flexibly. Considering $\tau = 0$ as an anchor point, we can achieve the promising performance with a proper strength in the process of increasing skewness. In contrast, the model performance degenerates when

Figure 5: Linear probing performance and imbalanced factor of the geometric statistic w.r.t. τ on CIFAR-100-LT-R100.

we reversely adopt S^{2}LA (decrease skewness). These observations further confirm that our method can realize any desired skewness to deal with different levels of data imbalancedness.

6 CONCLUSION

In this paper, we study why the conventional contrastive learning loss underperforms in self-supervised long-tailed learning, motivating our exploration on category-level uniformity instead of sample-level uniformity. Inspired by the power of logit adjustment in supervised long-tailed learning, we correspondingly propose a Self-Superivsed Logit Adjustment algorithm to calibrate the learning in the self-supervised learning paradigm. On the geometric level, S^{2}LA gradually rectify the feature span by an alternation between the logit adjustment and the surrogate label allocation. Moreover, S^{2}LA is orthogonal to existing self-supervised long-tailed methods and can be easily plugged into these methods in an efficient end-to-end manner. Extensive experiments demonstrate the consistent efficacy of our proposed S^{2}LA. We believe that the geometric perspective has the more potential to understand self-supervised learning methods, especially when coping with the long-tailed scenarios. In the future, we will extend our work with several potential directions such as theoretical definition of the geometric structure over the training embeddings, and investigations of other clustering methods or regularization to edit the geometric statistics.

7 ETHICS STATEMENT

This paper does not raise any ethics concerns. This study does not involve any human subjects, practices to data set releases, potentially harmful insights, methodologies and applications, potential conflicts of interest and sponsorship, discrimination/bias/fairness concerns, privacy and security issues, legal compliance, and research integrity issues.

8 REPRODUCIBILITY STATEMENT

To ensure the reproducibility of experimental results, we will provide the anonymous repository about our codes in the discussion phase for reviewing purposes. The experimental setups for training and evaluation as well as the hyper-parameters are detailed in Section 5.1 and Appendix B.

REFERENCES

Yuki M. Asano, Christian Rupprecht, and Andrea Vedaldi. Self-labelling via simultaneous clustering and representation learning. In *International Conference on Learning Representations (ICLR)*, 2020.

Sergiy V Borodachov, Douglas P Hardin, and Edward B Saff. *Discrete energy on rectifiable sets*. Springer, 2019.

Kay Henning Brodersen, Cheng Soon Ong, Klaas Enno Stephan, and Joachim M Buhmann. The balanced accuracy and its posterior distribution. In *2010 20th international conference on pattern recognition*, pp. 3121–3124. IEEE, 2010.

Kaidi Cao, Colin Wei, Adrien Gaidon, Nikos Arechiga, and Tengyu Ma. Learning imbalanced datasets with label-distribution-aware margin loss. *Advances in Neural Information Processing Systems*, 32:1567–1578, 2019.

Mathilde Caron, Ishan Misra, Julien Mairal, Priya Goyal, Piotr Bojanowski, and Armand Joulin. Unsupervised learning of visual features by contrasting cluster assignments. *Advances in Neural Information Processing Systems*, 33:9912–9924, 2020.

Ting Chen, Simon Kornblith, Mohammad Norouzi, and Geoffrey Hinton. A simple framework for contrastive learning of visual representations. In *International Conference on Machine Learning*, pp. 1597–1607. PMLR, 2020.

Henry Cohn and Abhinav Kumar. Universally optimal distribution of points on spheres. *Journal of the American Mathematical Society*, 20(1):99–148, 2007.

Marco Cuturi. Sinkhorn distances: Lightspeed computation of optimal transport. *Advances in neural information processing systems*, 26, 2013.

Carl Doersch, Abhinav Gupta, and Alexei A Efros. Unsupervised visual representation learning by context prediction. In *Proceedings of the IEEE International Conference on Computer Vision*, pp. 1422–1430, 2015.

Cong Fang, Hangfeng He, Qi Long, and Weijie J Su. Exploring deep neural networks via layer-peeled model: Minority collapse in imbalanced training. *Proceedings of the National Academy of Sciences*, 118(43):e2103091118, 2021.

Florian Graf, Christoph Hofer, Marc Niethammer, and Roland Kwitt. Dissecting supervised constrastive learning. In *International Conference on Machine Learning*, pp. 3821–3830. PMLR, 2021.

DP Hardin and EB Saff. Minimal riesz energy point configurations for rectifiable d-dimensional manifolds. *Advances in Mathematics*, 193(1):174–204, 2005.

Ziyu Jiang, Tianlong Chen, Bobak J Mortazavi, and Zhangyang Wang. Self-damaging contrastive learning. In *International Conference on Machine Learning*, pp. 4927–4939. PMLR, 2021.

Tejaswi Kasarla, Gertjan J Burghouts, Max van Spengler, Elise van der Pol, Rita Cucchiara, and Pascal Mettes. Maximum class separation as inductive bias in one matrix. *arXiv preprint arXiv:2206.08704*, 2022.

Tianhong Li, Peng Cao, Yuan Yuan, Lijie Fan, Yuzhe Yang, Rogerio S Feris, Piotr Indyk, and Dina Katabi. Targeted supervised contrastive learning for long-tailed recognition. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 6918–6928, 2022.

Tsung-Yi Lin, Priya Goyal, Ross Girshick, Kaiming He, and Piotr Dollár. Focal loss for dense object detection. In *Proceedings of the IEEE International Conference on Computer Vision*, pp. 2980–2988, 2017.

Hong Liu, Jeff Z HaoChen, Adrien Gaidon, and Tengyu Ma. Self-supervised learning is more robust to dataset imbalance. *arXiv preprint arXiv:2110.05025*, 2021.

Weiyang Liu, Rongmei Lin, Zhen Liu, Lixin Liu, Zhiding Yu, Bo Dai, and Le Song. Learning towards minimum hyperspherical energy. *Advances in neural information processing systems*, 31, 2018.

Ziwei Liu, Zhongqi Miao, Xiaohang Zhan, Jiayun Wang, Boqing Gong, and Stella X Yu. Large-scale long-tailed recognition in an open world. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 2537–2546, 2019.

Aditya Krishna Menon, Sadeep Jayasumana, Ankit Singh Rawat, Himanshu Jain, Andreas Veit, and Sanjiv Kumar. Long-tail learning via logit adjustment. In *International Conference on Learning Representations*, 2021.

Dustin G Mixon, Hans Parshall, and Jianzong Pi. Neural collapse with unconstrained features. *Sampling Theory, Signal Processing, and Data Analysis*, 20(2):1–13, 2022.

Vardan Papyan, XY Han, and David L Donoho. Prevalence of neural collapse during the terminal phase of deep learning training. *Proceedings of the National Academy of Sciences*, 117(40): 24652–24663, 2020.

Foster Provost. Machine learning from imbalanced data sets 101. In *Proceedings of the AAAI'2000 workshop on imbalanced data sets*, volume 68, pp. 1–3. AAAI Press, 2000.

William J Reed. The pareto, zipf and other power laws. *Economics letters*, 74(1):15–19, 2001.

Jiawei Ren, Cunjun Yu, Xiao Ma, Haiyu Zhao, Shuai Yi, et al. Balanced meta-softmax for long-tailed visual recognition. *Advances in neural information processing systems*, 33:4175–4186, 2020.

Jiawei Ren, Mingyuan Zhang, Cunjun Yu, and Ziwei Liu. Balanced mse for imbalanced visual regression. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 7926–7935, 2022.

Steve Smale. Mathematical problems for the next century. *The mathematical intelligencer*, 20(2): 7–15, 1998.

Alexander Strehl and Joydeep Ghosh. Cluster ensembles—a knowledge reuse framework for combining multiple partitions. *Journal of machine learning research*, 3(Dec):583–617, 2002.

Joseph John Thomson. Xxiv. on the structure of the atom: an investigation of the stability and periods of oscillation of a number of corpuscles arranged at equal intervals around the circumference of a circle; with application of the results to the theory of atomic structure. *The London, Edinburgh, and Dublin Philosophical Magazine and Journal of Science*, 7(39):237–265, 1904.

Tongzhou Wang and Phillip Isola. Understanding contrastive representation learning through alignment and uniformity on the hypersphere. In *International Conference on Machine Learning*, pp. 9929–9939. PMLR, 2020.

Xiaolong Wang and Abhinav Gupta. Unsupervised learning of visual representations using videos. In *Proceedings of the IEEE International Conference on Computer Vision*, pp. 2794–2802, 2015.

Yibo Yang, Liang Xie, Shixiang Chen, Xiangtai Li, Zhouchen Lin, and Dacheng Tao. Do we really need a learnable classifier at the end of deep neural network? *arXiv preprint arXiv:2203.09081*, 2022.

Yuzhe Yang and Zhi Xu. Rethinking the value of labels for improving class-imbalanced learning. *Advances in neural information processing systems*, 33:19290–19301, 2020.

Yifan Zhang, Bingyi Kang, Bryan Hooi, Shuicheng Yan, and Jiashi Feng. Deep long-tailed learning: A survey. *arXiv preprint arXiv:2110.04596*, 2021.

Zhihan Zhou, Jiangchao Yao, Yan-Feng Wang, Bo Han, and Ya Zhang. Contrastive learning with boosted memorization. In *International Conference on Machine Learning*, pp. 27367–27377. PMLR, 2022.

Zhihui Zhu, Tianyu Ding, Jinxin Zhou, Xiao Li, Chong You, Jeremias Sulam, and Qing Qu. A geometric analysis of neural collapse with unconstrained features. *Advances in Neural Information Processing Systems*, 34:29820–29834, 2021.

APPENDIX

A ALGORITHM

We summarize the complete procedure of our S^2LA method in Algorithm 1.

Algorithm 1 Our proposed S^2LA.

Input: dataset $\mathcal{D}$, number of epochs E, number of warm-up epochs E_w, geometric classifier $\mathbf{M}$, a self-supervised learning method $\mathcal{A}$, logit anti-adjustment temper τ
Output: pretrained model parameter θ_E
Initialize: model parameter θ_0

  1: Warm up model θ for E_w epochs according to $\mathcal{A}$.
  2: **for** epoch $e = E_w, E_w + 1, \ldots, E$ **do**
  3:    Obtain the geometric prediction $\boldsymbol{t} = \arg\max_i h_i^m(\boldsymbol{x})$ for dataset $\mathcal{D}$.
  4:    Compute the surrogate class prior $p(\boldsymbol{t})$.
  5:    Compute $p\left(\hat{\boldsymbol{t}}\right)$ using logit adjustment according to Eq. 3.
  6:    **for** mini-batch $k = 1, 2, \ldots, B$ **do**
  7:      Update the output logits $h^m(\boldsymbol{x})$ for each sample.
  8:      Obtain the label $q(\boldsymbol{t}|\boldsymbol{x})$ using the optimal transport solutions according to Eq. 6.
  9:      Compute $\mathcal{L}_{\mathrm{SSL}}$ according to $\mathcal{A}$ and the proposed $\mathcal{L}_{S^2LA}$ according to Eq. 4.
 10:      Uptate model θ by minimizing $\mathcal{L}_{\mathrm{SSL}} + \mathcal{L}_{S^2LA}$.
 11:    **end for**
 12: **end for**

B EXPERIMENTAL SETUP

B.1 DATASET STATISTICS

In Table 4, we summarize the benchmark datasets used in this paper. Long-tailed versions of CIFAR-100 are constructed following the exponential distribution. For large-scale datasets, ImageNet-LT (Liu et al., 2019) has 115.8K images with 1000 categories, ranging from 1,280 to 5 in terms of class cardinality and Places-LT (Liu et al., 2019) contains 62,500 images with 365 categories, with the sample number per category ranging from 4,980 to 5. The large-scale datasets follow Pareto distribution.

Table 4: Statistics of long-tailed datasets.

Dataset	Class	Long Tail Type	Imbalanced Ratio	Train	Test
CIFAR-100-LT-R100	100	Exponential	100	10847	10000
CIFAR-100-LT-R50	100	Exponential	50	12608	10000
CIFAR-100-LT-R10	100	Exponential	10	19573	10000
ImageNet-LT	1000	Pareto	256	115846	50000
Places-LT	365	Pareto	996	62500	36500

B.2 COMPUTING INFRASTRUCTURE

Our codes are built on PyTorch. We trained all the experiments on NVIDIA GeForce RTX 3090.

B.3 EXPERIMENTAL DETAILS

Toy Experiments. (Figure 1) We use a 2-Layer ReLU network with 20 hidden units and 2 output units for visualization. The SimCLR algorithm (Chen et al., 2020) is adopted in the warm-up stage with proper Gaussian noise as augmentation. After the warm-up stage, we train S^2LA according to

Eq. 7. Due to the dimensional constraints, we use the orthogonal classifier [(1,1),(-1,1),(-1,-1),(1,-1)] as the suboptimal structure for maximum separation.

Linear Probing Evaluation. We follow (Zhou et al., 2022) to conduct Adam optimizer for 500 epochs based on batch size 128, weight decay factor 5×10^{-6} and the learning rate decaying from 10^{-2} to 10^{-6}. For few-shot evaluation on ImageNet-LT and Places-LT, we use the same sampled 100-shot subsets in (Zhou et al., 2022).