Generalisation Guarantees for Continual Learning with Orthogonal Gradient Descent

Abstract

In continual learning settings, deep neural networks are prone to catastrophic forgetting. Orthogonal Gradient Descent (Farajtabar et al., 2019) achieves state-of-the-art results in practice for continual learning, although no theoretical guarantees have been proven yet. We derive the first generalisation guarantees for the algorithm OGD for continual learning, for overparameterized neural networks. We find that OGD is only provably robust to catastrophic forgetting across a single task. We propose OGD+, prove that it is robust to catastrophic forgetting across an arbitrary number of tasks, and that it verifies tighter generalisation bounds. Our experiments show that OGD+ achieves state-of-the-art results on settings with a large number of tasks, even though the models are not overparameterized. Also, we derive a closed form expression of the learned models through tasks, as a recursive kernel regression relation, which captures the transferability of knowledge through tasks. Finally, we quantify theoretically the impact of task ordering on the generalisation error, which highlights the importance of the curriculum for lifelong learning.

1. Introduction

Continual learning is a setting in which an agent is exposed to multiples tasks sequentially (Kirkpatrick et al., 2016). The core challenge lies in the ability of the agent to learn the new tasks while retaining the knowledge acquired from previous tasks. Too much plasticity will lead to catastrophic forgetting, which means the degradation of the ability of the agent to perform the past tasks (McCloskey & Cohen 1989, Goodfellow et al. 2013, Ratcliff 1990). On the other hand, too much stability will hinder the agent from adapting

to new tasks. Continual learning is seeing a new surge of interest (Parisi et al. 2019, Nguyen et al. 2019).

Recent works on the Neural Tangent Kernel (Jacot et al., 2018) and on the convergence of Stochastic Gradient Descent for overparameterized neural networks (Arora et al., 2019) have unlocked powerful tools to analyze the training dynamics of over-parameterized neural networks. We leverage these theoretical findings in order to to prove guarantees on the convergence and the generalisation of the algorithm, Orthogonal Gradient Descent for Continual Learning (Farajtabar et al., 2019).

Our contributions are summarized as follows:

1. We provide closed form expressions of the functions learned across tasks. We find that they can be expressed as a linear combination of kernel regressors, over the previously seen tasks. The relationship also captures task similarity and the transferability of knowledge across tasks (Sec. 3, Theorem 1).

2. We prove the first generalisation bound for continual learning with OGD, to our knowledge. We derive bounds for within-task and outside-task generalisation. We find that generalisation through time depends on task similarity, which we quantify rigorously (Sec. 4, Theorem 2).

3. We prove that OGD is robust to forgetting with respect to the previous task only (Sec. 4, Lemma 1).

4. We build-up on this insight to propose OGD+ (Sec. 5, Alg. 1), an extension of OGD, which we prove robust to catastrophic forgetting across an arbitrary number of tasks (Sec. 5, Lemma 3). We also prove tighter generalisation bounds than OGD (Sec. 5, Theorem 3).

5. As a side result, we find that Lemma 2 also quantifies the impact of the learning curriculum on the generalisation error. We find that task dissimilarity impacts negatively generalisation, and that an ordering of tasks that minimises dissimilarity between neighbouring tasks leads to a tighter generalisation bound. (Sec. 2, Lemma 2).

[1]Anonymous Institution, Anonymous City, Anonymous Region, Anonymous Country. Correspondence to: Anonymous Author <anon.email@domain.com>.

Preliminary work. Under review by the International Conference on Machine Learning (ICML). Do not distribute.

Even though the analysis relies on the assumption that the neural network is overparametrised, the analysis leads to practical insights to improve OGD, which led us to OGD+. We run experiments in the non-overparametrised setting, and show that OGD+ achieves state-of-the-art results in settings with large number of tasks (Sec. 6).

2. Preliminaries

Notation We use bold-faced characters for vectors and matrices. We use $\|\cdot\|$ to denote the Euclidian norm of a vector or the spectral norm of a matrix, and $\|\cdot\|_F$ to denote the Frobenius norm of a matrix. We use $\langle\cdot,\cdot\rangle$ for the Euclidian dot product, and $\langle\cdot,\cdot\rangle_{\mathcal{H}}$ the dot product in the Hilbert space $\mathcal{H}$. We index the the task ID by τ. The $\leq$ operator if used with matrices, corresponds to the partial ordering over symetric matrices. We denote $\mathbb{N}$ the set of natural numbers, $\mathbb{R}$ the space of real numbers and $\mathbb{N}^\star$ for the set $\mathbb{N}\setminus\{0\}$. We use $\oplus$ to refer to the direct sum over Euclidian spaces.

2.1. Continual Learning

Continual learning considers a series of tasks $\{\mathcal{T}_1, \mathcal{T}_2, \ldots\}$, where each task can be viewed as a separate supervised learning problem. Similarly to online learning, data from each task is revealed only once. The goal of continual learning is to model each task accurately with a single model. The challenge is to achieve a good performance on the new tasks, while retaining knowledge from the previous tasks (Nguyen et al., 2018).

We assume the data from each task $\mathcal{T}_\tau$, $\tau \in \mathbb{N}^\star$, is drawn from a distribution $\mathcal{D}_\tau$. Individual samples are denoted $(\mathbf{x}_{\tau,i}, y_{\tau,i})$, where $i \in [n_\tau]$. Also, we only consider the binary classification setting for the sake of simplicity: $\mathbf{x}_{\tau,i} \in \mathbb{R}^d$ and $y_{\tau,i} \in \{-1, +1\}$. We note that it does not restrict the scope of the analysis, which can be easily extended to multiclass settings.

2.2. OGD for Continual Learning

Let $\mathcal{T}_T$ the current task, where $T \in \mathbb{N}^\star$. For all $i \in [n_T]$, let $\mathbf{v}_{T,i} = \nabla_\theta f^\star_{T-1}(\mathbf{x}_{T-1,i})$, which is the Jacobian of task $\mathcal{T}_T$. We define $\mathbb{E}_\tau = \mathrm{vec}(\{\mathbf{v}_{\tau,i}, i \in [n_\tau]\})$, which is the subspace induced by the Jacobian. The idea behind OGD is to update the weights along the projection of the gradient on the orthogonal space induced by the Jacobians over the previous tasks $\mathbb{E}_1 \oplus \ldots \oplus \mathbb{E}_{\tau-1}$. The update rule for the task $\mathcal{T}_T$ is as follows (Farajtabar et al., 2019):

$$\mathbf{w}_T(t+1) = \mathbf{w}_T(t) - \eta\Pi_{\mathbb{E}^\perp_{T-1}}\nabla_{\mathbf{w}}\mathcal{L}^T_\lambda(\mathbf{w}_T(t)).$$

The intuition behind OGD is to "preserve the previously acquired knowledge by maintaining a space consisting of the gradient directions of the neural networks predictions on previous tasks". (Farajtabar et al., 2019)

To prevent over-fitting and guarantee the uniqueness of the global minimum in the Neural Tangent Kernel (NTK) regime, we apply a ridge regularization with a parameter $\lambda \in \mathbb{R}^+$. For a task $\mathcal{T}_\tau$, we write the corresponding loss as follows:

$$\mathcal{L}^\tau_\lambda(\mathbf{w}) = \sum_{i=1}^{n_\tau}(f_\tau(\mathbf{x}_{\tau,i}) - y_{\tau,i})^2 + \lambda\|\mathbf{w} - \mathbf{w}_{\tau-1}\|^2.$$

2.3. Generalisation for Continual Learning

We define within-task generalisation as the ability of the agent to acquire new knowlege and outside-task generalisation as its ability to preserve the acquired knowledge.

Definition 1 (Within-task and outside-task generalisation) *Consider a loss function $l : \mathbb{R} \times \mathbb{R} \to \mathbb{R}$. The population loss over the distribution $\mathcal{D}$, and the empirical loss over n samples $D = \{(\mathbf{x}_i, y_i), i \in [n]\}$ from the same distribution $\mathcal{D}$ are defined as:*

$$L_D(f) = \mathbb{E}_{(\mathbf{x},y)\sim\mathcal{D}}[l(f(\mathbf{x}), y)],$$
$$L_S(f) = \frac{1}{n}\sum_{i=1}^{n} l(f(\mathbf{x}_i), y_i).$$

Let $\mathcal{T}_1, \ldots \mathcal{T}_T$ a sequence of tasks, and $\mathcal{D}_1, \ldots \mathcal{D}_T$ their corresponding distributions.
Let $f^\star_1, \ldots f^\star_T$ the trained models at each task. Let $\tau \in [T]$ fixed.
We define:

- *within-task generalisation of the task $\mathcal{T}_\tau$ as $L_{D_\tau}(f^\star_\tau)$.*

- *outside-task generalisation of the task $\mathcal{T}_\tau$ with respect to a task $\mathcal{T}_{\tau'}$, where $\tau' < \tau$ as $L_{D_\tau}(f^\star_{\tau'})$.*

In practice, several works also tracked these metrics in their experiments (Kirkpatrick et al. 2016, Farajtabar et al. 2019).

2.4. Neural Tangent Kernel

In their seminal paper, Jacot et al. (2018) established the connection between deep networks and kernel methods by introducing the Neural Tangent Kernel (NTK). They showed that at the infinite width limit, the kernel remains constant throughout training. Lee et al. (2019) also showed that a network evolves as a linear model in the infinite width limit when trained on certain losses under gradient descent.

Throughout our analysis, we make the assumption that the neural network is overparameterized, and consider the linear approximation of the neural network around its initialisation:

$$f^{(t)}(\mathbf{x}) \approx f^{(0)}(\mathbf{x}) + \nabla_{\mathbf{w}}f^{(0)}(\mathbf{x})^T(\mathbf{w}(t) - \mathbf{w}(0)).$$

3. Convergence of OGD for Continual Learning

In this section, we derive a closed form expression for the learned models across tasks. We find a recursive kernel ridge regression relationship between the models across tasks. The result is presented in Theorem 1, a stepping stone towards proving the generalisation bound for OGD in Sec. 4.

3.1. Convergence Theorem

Now, we state the main result of this section:

Theorem 1 (Convergence of SGD and OGD for Continual Learning) *Let $\mathcal{T}_1, \ldots, \mathcal{T}_T$ be a sequence of tasks. Fix a learning rate sequence $(\eta_\tau)_{\tau \in [T]}$. If, for all τ, the learning rate satisfies*

$$\eta_\tau < \frac{1}{\|k_\tau(\mathbf{X}_\tau, \mathbf{X}_\tau)\| + \lambda_\tau^2},$$

then for all τ, $\mathbf{w}_\tau(t)$ converges linearly to a limit solution $\mathbf{w}_\tau^\star$ such that

$$f_\tau^\star(\mathbf{x}) = f_{\tau-1}^\star(\mathbf{x}) + k_\tau(\mathbf{x}, \mathbf{X}_\tau)^T \mathbf{H}_{\tau,\lambda_\tau}^{-1} \tilde{\mathbf{y}}_\tau,$$

where

$$k_\tau(\mathbf{x}, \mathbf{x}') = \widetilde{\phi}_\tau(\mathbf{x})^T \widetilde{\phi}_\tau(\mathbf{x}'),$$
$$\tilde{\mathbf{y}}_\tau = \mathbf{y}_\tau - \mathbf{y}_{\tau-1 \to \tau},$$
$$\mathbf{y}_{\tau-1 \to \tau} = f_{\tau-1}^\star(\mathbf{X}_\tau),$$
$$\phi_\tau(\mathbf{x}) = \nabla_\mathbf{w} f_{\tau-1}^\star(\mathbf{x}),$$
$$\mathbf{H}_{\tau,\lambda} = k_\tau(\mathbf{X}_\tau, \mathbf{X}_\tau) + \lambda^2 \mathbf{I},$$
$$\widetilde{\phi}_\tau(\mathbf{x}) = \begin{cases} \phi_\tau(\mathbf{x}) & \text{for SGD,} \\ \mathbf{T}_\tau \phi_\tau(\mathbf{x}) & \text{for OGD.} \end{cases}$$

and $\{\mathbf{T}_\tau, \tau \in [T]\}$ are proxy matrices for the analysis.

The theorem describes how the model $f_\tau^\star$ evolves across tasks. The theorem is recursive because the learning is incremental. For a given task $\mathcal{T}_\tau$, $f_{\tau-1}^\star(\mathbf{x})$ is the knowledge acquired by the agent up to the task $\mathcal{T}_{\tau-1}$. At this stage, the model only fits the residual $\tilde{\mathbf{y}}_\tau = \mathbf{y}_\tau - \mathbf{y}_{\tau-1 \to \tau}$, which complements the knowledge acquired through previous tasks. This residual is also a proxy for task similarity. If the tasks are identical, the residual is equal to zero. The knowledge increment is captured by the term: $k_\tau(\mathbf{x}, \mathbf{X}_\tau)^T (k_\tau(\mathbf{X}_\tau, \mathbf{X}_\tau) + \lambda_\tau^2 \mathbf{I})^{-1} \tilde{\mathbf{y}}_\tau$. Finally, task similarity is computed with respect to the most recent feature map $\widetilde{\phi}_\tau$, and k_τ is the NTK with respect to the feature map $\widetilde{\phi}_\tau$.

Remark 1 *The recursive relation from Theorem 1 can also be written as a linear combination of kernel regressors as follows:*

$$f_\tau^\star(\mathbf{x}) = \sum_{k=1}^\tau \tilde{f}_k^\star(\mathbf{x}),$$

where

$$\tilde{f}_k^\star(\mathbf{x}) = k_k(\mathbf{x}, \mathbf{X}_k)^T (k_k(\mathbf{X}_k, \mathbf{X}_k) + \lambda_k^2 \mathbf{I})^{-1} \tilde{\mathbf{y}}_k.$$

Proof Sketch: We prove Theorem 1 by induction. We rewrite the loss function as a regression on the residual $\tilde{\mathbf{y}}_\tau$ instead of $\mathbf{y}_\tau$. Then, we rewrite the optimisation objective as an unconstrained strongly convex optimisation problem. Finally, we compute the unique solution in a closed form. The full proof is presented in App. A.1.

3.2. Distance from Initialisation

As described in Sec. 3.1, $\tilde{\mathbf{y}}_\tau$ is a residual. It is equal to zero if the model makes perfect predictions on the next task $\mathcal{T}_\tau$. The more the next task $\mathcal{T}_\tau$ is different, the further the neural network needs to move from its previous state in order to fit it. Corollary 1 tracks the distance from initialisation as a function of task similarity.

Corollary 1 *For SGD, and for OGD under the additional assumption that $\{\mathbf{T}_\tau, \tau \in [T]\}$ are orthonormal,*

$$\left\|\mathbf{w}_{\tau+1}^\star - \mathbf{w}_\tau^\star\right\|_\mathrm{F} = \sqrt{\tilde{\mathbf{y}}_\tau^T \mathbf{H}_{T,\lambda}^{-1} \mathbf{H}_{\tau,0} \mathbf{H}_{T,\lambda}^{-1} \tilde{\mathbf{y}}_\tau},$$

where

$$\mathbf{H}_{\tau,\lambda} = k_\tau(\mathbf{X}_\tau, \mathbf{X}_\tau) + \lambda^2 \mathbf{I}.$$

The proof is presented in App. A.2. The orthonormality assumption is not restrictive, since the set $\{\mathbf{T}_\tau, \tau \in [T]\}$ is only a proxy for the analysis; indeed we can choose any convenient basis to work with.

Remark 2 *Corollary 1 can be used to get a similar result to Theorem 3 by Liu et al. (2019). In this remark, we consider mostly their notations. Their theorem states that under some conditions, for 2-layer neural networks with a RELU activation function, with probability no less than $1 - \delta$ over random initialisation,*

$$\|\mathbf{W}(P) - \mathbf{W}(Q)\|_\mathrm{F} \le \sqrt{\tilde{\mathbf{y}}_{P \to Q}^T H_P^{\infty-1} \tilde{\mathbf{y}}_{P \to Q}} + \epsilon,$$

where, in their work:

$$\mathbf{y}_{P \to Q} = H_{PQ}^{\infty,T} H_P^{\infty-1} \mathbf{y}_P,$$
$$\tilde{\mathbf{y}}_{P \to Q} = \mathbf{y}_Q - \mathbf{y}_{P \to Q}.$$

Note that H_P^∞ is a Gram matrix, which also corresponds to the NTK of the neural network they consider. We see an analogy with our result, where we work directly with the NTK, with no assumptions on the neural network. One important observation is that, to our knowledge, since there are no guarantees for the invertibility of our Gram matrix, we add a ridge regularisation to work with a regularised matrix, which is then invertible. In our setting, by considering $\lambda \to 0$, and with the additional assumption of invertibility of $\mathbf{H}_{\tau,0}$, which is valid in the two-layer overparametrised RELU neural network considered in the setting of Liu et al. (2019), we can recover a similar approximation.

4. Generalisation of OGD for Continual Learning

In this section, we study the generalisation properties of OGD. First, we prove that OGD is robust to catastrophic forgetting with respect to the previous task (Lemma 1). Then, we present the the main generalisation theorem for OGD (Them. 2). The theorem provides several insights on the relation between task similarity and generalisation. Finally, we present how the Rademacher complexity relates to task similarity across a large number of tasks (Lemma 2). The lemma states that the more dissimilar tasks are, the larger the class of functions explored by the neural network, with high probability.

4.1. Memorisation property of OGD

The key to obtaining tight generalisation bounds for OGD is Lemma 1.

Lemma 1 (Memorisation Property of OGD) *Given a task $\mathcal{T}_\tau$, for all $\mathbf{x}_{\tau,i} \in D_\tau$, a sample from the training data of the task $\mathcal{T}_\tau$, it holds that*

$$f_{\tau+1}^\star(\mathbf{x}_{\tau,i}) = f_\tau^\star(\mathbf{x}_{\tau,i}). \tag{1}$$

As motivated by Farajtabar et al. 2019, the orthogonality of the gradient updates aims to preserve the acquired knowledge, by not altering the weights along relevant dimensions when learning new tasks. Lemma 1 states that the training error on the previous task is unchanged, when training with OGD. However, there are no guarantees that the knowledge from the tasks before the previous task is preserved.

The proof of Lemma 1 is presented in App. B.1.4

4.2. Generalisation of OGD for Continual Learning

Now, we state the main generalisation theorem for OGD, which provides within-task and outside-task generalisation bounds.

Theorem 2 (Generalisation of OGD for Continual Learning) *Let $\{\mathcal{T}_1, \ldots \mathcal{T}_T\}$ be a sequence of tasks. Let be $\{\mathcal{D}_1, \ldots, \mathcal{D}_T\}$ the respective distributions over $\mathbb{R}^d \times \{-1, 1\}$. Let $\{(\mathbf{x}_{\tau,i}, y_{\tau,i}), i \in [n_t], \tau \in [T]\}$ be i.i.d. samples from $\mathcal{D}_\tau, \tau \in [T]$. Denote $\mathbf{X}_\tau = (\mathbf{x}_{\tau,1}, \ldots, \mathbf{x}_{\tau,n_\tau})$, $\mathbf{y}_\tau = (y_{\tau,1}, \ldots, y_{\tau,n_\tau})$. Consider the kernel ridge regression solution $f_T^\star$. Suppose that the kernel matrices satisfy*

$$\mathrm{Tr}(k_\tau(\mathbf{X}_\tau, \mathbf{X}_\tau)) = \mathcal{O}(n_\tau),$$

then, for any loss function $\ell : \mathbb{R} \times \mathbb{R} \to [0, c]$ that is c-Lipchitz in the first argument, with probability at least $1 - \delta$, for within-task generalisation ($\mathcal{T}_T$),

$$\mathcal{L}_{D_T}(f_T^\star) \leq \frac{\lambda}{2}\sqrt{\frac{\tilde{\mathbf{y}}_T^T k_T(\mathbf{X}_T, \mathbf{X}_T)^{-1}\tilde{\mathbf{y}}_T}{n_T}} +$$
$$\sum_{k=1}^{T}(\mathcal{O}\left(\sqrt{\frac{\tilde{\mathbf{y}}_k^T \mathbf{H}_{k,\lambda}^{-1}\tilde{\mathbf{y}}_k}{n_k}}\right) + \Delta_k),$$

for outside-task generalisation ($\mathcal{T}_{T-1}$),

$$\mathcal{L}_{D_{T-1}}(f_T^\star) \leq \frac{\lambda}{2}\sqrt{\frac{\tilde{\mathbf{y}}_{T-1}^T k_T(\mathbf{X}_T, \mathbf{X}_T)^{-1}\tilde{\mathbf{y}}_{T-1}}{n_T}} +$$
$$\sum_{k=1}^{T}(\mathcal{O}\left(\sqrt{\frac{\tilde{\mathbf{y}}_k^T \mathbf{H}_{k,\lambda}^{-1}\tilde{\mathbf{y}}_k}{n_k}}\right) + \Delta_k),$$

and for outside-task generalisation ($\mathcal{T}_\tau, \tau < T - 1$),

$$\mathcal{L}_{D_\tau}(f_T^\star) \leq \sqrt{A_\tau + \sum_{k=\tau+1}^{T}\frac{1}{4\lambda^2}\frac{\tilde{\mathbf{y}}_k^T \tilde{\mathbf{K}}_{k,\tau}\tilde{\mathbf{y}}_k}{n_\tau}} +$$
$$\sum_{k=1}^{T}(\mathcal{O}\left(\sqrt{\frac{\tilde{\mathbf{y}}_k^T \mathbf{H}_{k,\lambda}^{-1}\tilde{\mathbf{y}}_k}{n_k}}\right) + \Delta_k),$$

where

$$\Delta_k = \mathcal{O}(\frac{1}{\sqrt{n_k}}) + 3c\sqrt{\frac{\log(2/\delta)}{2n_k}},$$
$$\mathbf{H}_{\tau,\lambda} = k_\tau(\mathbf{X}_\tau, \mathbf{X}_\tau) + \lambda^2\mathbf{I},$$
$$A_\tau = \frac{\lambda^2}{4}\frac{\tilde{\mathbf{y}}_\tau^T(k_\tau(\mathbf{X}_\tau, \mathbf{X}_\tau))^{-1}\tilde{\mathbf{y}}_\tau}{n_\tau}$$
$$\phi_\tau(\mathbf{x}) = \mathbf{T}_\tau\nabla_\mathbf{w}f_{\tau-1}^\star(\mathbf{x}),$$
$$\tilde{\mathbf{y}}_\tau = \mathbf{y}_\tau - \mathbf{y}_{\tau-1\to\tau},$$
$$\mathbf{y}_{\tau-1\to\tau} = f_{\tau-1}^\star(\mathbf{X}_\tau),$$
$$\mathbf{K}_{i,j,k} = k_i(\mathbf{X}_j, \mathbf{X}_k),$$
$$\tilde{\mathbf{K}}_{k,\tau} = \mathbf{K}_{k,k,k}^{-1}\mathbf{K}_{k,\tau,k}\mathbf{K}_{k,\tau,k}^T\mathbf{K}_{k,k,k}^{-1}.$$

The intution behind Theorem 2 is as follows:

- Within-task generalisation: The generalisation error on the most recent task leverages the information learned during training on the previous tasks. The bound is tighter compared to learning from scratch, since it depends on the residual $\tilde{\mathbf{y}}_\tau$. Therefore it captures the transferability of knowledge across tasks.

- Outside-task generalisation ($\mathcal{T}_{T-1}$): The generalisation bound increases only with respect to the Rademacher complexity when training with OGD. The tightness of this bound for OGD is due to Lemma 1. This lemma is valid for OGD and not for SGD, which implies that tighter generalisation is guaranteed compared to SGD.

- Outside-task generalisation ($\mathcal{T}_\tau, \tau \leq T - 2$): The upper bound depends on the similarity between the outside task and the latest task; the more dissimilar the subsequent tasks are, the more the upper bound diverges from the initial upper bound. This bound captures catastrophic forgetting as a function of the tasks dissimilarity. This bound is the same for OGD and SGD.

These bounds share some similarities with the bounds derived by Arora et al. (2019), Liu et al. (2019) and Hu et al. (2019), where in these works, the bounds were derived for supervised learning settings, and in some cases for two-layer RELU neural networks. Similarly, the bounds depend on the Gram matrix of the data, with the feature map corresponding to the NTK.

Proof Sketch: The proof is presented in App. B.1. One challenge is that the function class is the set of linear combinations of kernel regressors (Theorem 1). We state Lemma 4 to bound the Rademacher complexity for this function class. Then we derive bounds for the training error for each case in Theorem 2. The first case is straightforward. For the second case, we use Lemma 1, then derive a similar proof to the first case. The third case presents some additional technical challenges. In order to derive the upper bounds, we draw a strong inspiration from Hu et al. (2019), and leverage several of their proof techniques and mathematical tools.

4.3. Distance from Initialisation through Tasks

Now, we state Lemma 2, which tracks the Rademacher complexity through tasks.

Lemma 2 *Keeping the same notations and setting as Theorem 2, the Rademacher Complexity can be bounded as follows:*

$$
\hat{\mathcal{R}}(\mathcal{F}_{\mathbf{B}_T}) \leq \sum_{\tau=1}^{T} \mathcal{O}\left(\sqrt{\frac{\tilde{\mathbf{y}}_\tau^T (k_\tau(\mathbf{X}_\tau, \mathbf{X}_\tau) + \lambda^2 \mathbf{I})^{-1} \tilde{\mathbf{y}}_\tau}{n_\tau}} \right)
$$
$$
+ \sum_{\tau=1}^{T} \mathcal{O}(\frac{1}{\sqrt{n_\tau}}).
$$

The intuition behind Lemma 2 is that the upper bound on the Rademacher complexity increases when the tasks are dissimilar. The dissimilarity between two subsequent tasks is measured through $\tilde{\mathbf{y}}_\tau^T (k_t(\mathbf{X}_\tau, \mathbf{X}_\tau) + \lambda^2 \mathbf{I})^{-1} \tilde{\mathbf{y}}_\tau$. The knowledge from the previous tasks is implicitly encoded in the kernel k_τ, which is based on the feature map ϕ_τ. This feature map encodes the acquired knowledge. As an edge case, if two successive tasks are identical, this implies that the residual $\tilde{\mathbf{y}}_\tau = \mathbf{y}_\tau - \mathbf{y}_{\tau-1 \to \tau} = 0$, therefore, the upper bound on the Rademacher complexity does not increase.

Implications for Curriculum Learning We also observe that the upper bound depends on the task ordering, which may provide a theoretical explanation on the importance of learning with a curriculum (Bengio et al., 2009). In the following, we present an edge case which provided an intuition on how the bound captures the importance of the order. Consider two dissimilar tasks $\mathcal{T}_1$ and $\mathcal{T}_2$. A sequence of tasks alternating between $\mathcal{T}_1$ and $\mathcal{T}_2$ will lead to a large upper bound, as explained in the first paragraph. While, a sequence of tasks concatenating two sequences of $\mathcal{T}_1$ then $\mathcal{T}_2$ will lead to a lower upper bound.

Proof Sketch: The proof techniques for Lemma 2 are exactly the same as the ones for Theorem 2. The full proof is presented in Sec. B.1.6.

5. OGD+: Learning without Forgetting

In the previous section, we demonstrated the limits of OGD, in terms of robustness to catastrophic forgetting on the long run. Now, we present OGD+, an extension of OGD, which we prove robust to catastrophic forgetting, across an arbitrary number of tasks (Lemma 3). Then, we prove tighter generalisation bounds compared to OGD (Theorem 3).

5.1. The OGD+ Algorithm

Algorithm 1 presents the OGD+ algorithm, we highlight the differences with OGD in red. The main difference is that OGD+ stores the feature maps with respect to the samples from previous tasks, in addition to the feature maps with respect to the samples from the current task, as opposed to OGD. This small change unlocks the proof of Lemma 3 given below, which implies tighter bounds for Theorem 3.

The idea behind OGD+ comes from the convergence Theorem (Thm. 1, Sec. 3). After training on a task $\mathcal{T}_\tau$, the learned model is a linear combination of the previous models. For a given sample $\mathbf{x}$ from a task $\mathcal{T}_k$ where $k < \tau$, in order to keep the training error identical, the weights need to be updated along the directions that are orthogonal to *all the subsequent feature maps* of $\mathbf{x}$. OGD only considers the feature map of the source task of the sample. Storing all the feature maps implies that the learned model back from task $\mathcal{T}_k$, can be recovered even after training on an arbitrary number of tasks.

In order to compute the feature maps with respect to the previous samples, OGD+ saves these samples in a dedicated memory, we call this storage the *samples memory*. This memory comes in addition to the orthonormal *feature maps memory*. The only role of the *samples memory* is to compute the feature maps. While the proofs below are under the assumption that the memory size is infinite, in the experiments, we keep a limited size for both memories.

In practice, we split the memories uniformly across tasks. Also, we construct $\mathcal{S}$ from $\mathcal{S}_D$ by sampling uniformly without replacement. Finally, for the memory reduction step, we truncate the last elements of the storage to free-up the space for the next task's data.

Algorithm 1 OGD+

Input : A task sequence $\mathcal{T}_1, \mathcal{T}_2, \mathcal{T}_3 \ldots$, learning rate η
Output : The optimal parameter $\mathbf{w}^\star$

1. Initialize $S_J \leftarrow \{\}$; $S_D \leftarrow \{\}$; $\mathbf{w} \leftarrow \mathbf{w}_0$

2. **for** *Task ID* $\tau = 1, 2, 3, \ldots$ **do**
   repeat
   $\quad \mathbf{g} \leftarrow$ Stochastic Batch Gradient for $\mathcal{T}_\tau$ at $\mathbf{w}$
   $\quad \tilde{\mathbf{g}} = \mathbf{g} - \sum_{\mathbf{V} \in \mathcal{S}_J} \text{proj}_\mathbf{V}(\mathbf{g})$
   $\quad \mathbf{w} \leftarrow \mathbf{w} - \eta \tilde{\mathbf{g}}$

   until *convergence*;
   Sample $\mathcal{S} \subset \mathcal{S}_D$
   for $(\mathbf{x}, y) \in \mathcal{D}_\tau \bigcup \mathcal{S}$ and $k \in [1, c]$ *s.t.* $y_k = 1$ **do**
   $\quad \mathbf{u} \leftarrow \nabla f_\tau(\mathbf{x}; \mathbf{w}) - \sum_{\mathbf{V} \in \mathcal{S}_J} \text{proj}_\mathbf{V}(\nabla f_\tau(\mathbf{x}; \mathbf{w}))$
   $\quad \mathcal{S}_J \leftarrow \mathcal{S}_J \bigcup \{\mathbf{u}\}$
   end
   Sample $\mathcal{D} \subset \mathcal{D}_\tau$
   $\quad \mathcal{S}_D \leftarrow \mathcal{S}_D \bigcup \mathcal{D}$

   end

5.2. Memorisation Property of OGD+

The key to obtaining tight generalisation bounds for OGD+ is Lemma 3, presented below. It states that the training error across all previous tasks is unchanged, when training with OGD+.

Lemma 3 (Memorisation Property of OGD+) *Given a task $\mathcal{T}_\tau$, for all $\mathbf{x}_{k,i} \in D_k$, a sample from the training data of a previous task, it holds that:*

$$f_\tau^\star(\mathbf{x}_{k,i}) = f_k^\star(\mathbf{x}_{k,i}). \qquad (2)$$

The full proof of Lemma 3 is presented in App . C.1.

5.3. Generalisation Guarantees for OGD+

Now, we state the generalisation theorem for OGD+, which provides tighter generalisation bounds in comparison with Theorem 2.

Theorem 3 (Generalisation of OGD+ for Continual Learning) *Under the same conditions as Theorem 2, for OGD+, it holds that, for all tasks $\mathcal{T}_\tau$, within-task and outside-task generalisation error can be bounded as follows*

$$\mathcal{L}_{D_\tau}(f_T^\star) \leq \frac{\lambda}{2} \sqrt{\frac{\tilde{\mathbf{y}}_\tau^T k_T(\mathbf{X}_\tau, \mathbf{X}_\tau)^{-1} \tilde{\mathbf{y}}_\tau}{n_\tau}} +$$
$$\sum_{k=1}^T \mathcal{O}\left(\sqrt{\frac{\tilde{\mathbf{y}}_k^T (k_t(\mathbf{X}_k, \mathbf{X}_k) + \lambda^2 \mathbf{I})^{-1} \tilde{\mathbf{y}}_k}{n_k}} \right) + \Delta_k,$$

where

$$\Delta_k = \mathcal{O}(\frac{1}{\sqrt{n_k}}) + 3c \sqrt{\frac{\log(2/\delta)}{2n_k}},$$
$$\phi_\tau(\mathbf{x}) = \mathbf{T}_\tau \nabla_\mathbf{w} f_{\tau-1}^\star(\mathbf{x}),$$
$$\tilde{\mathbf{y}}_\tau = \mathbf{y}_\tau - \mathbf{y}_{\tau-1 \to \tau},$$
$$\mathbf{y}_{\tau-1 \to \tau} = f_{\tau-1}^\star(\mathbf{X}_\tau).$$

The generalisation bounds of Theorem 3 are tighter than the generalisation bounds for OGD. The tightness of the bounds is a consequence of Lemma 3. The term that corresponds to the Rademacher complexity is unchanged, while the term that bounds the training error is tighter. It is also tighter than a standard supervised learning bound, because it captures the transferability of knowledge across tasks through the residual $\tilde{\mathbf{y}}_\tau$, as opposed to the Supervised Learning only bounds, which would depend on $\mathbf{y}_\tau$ instead.

Proof Sketch The full proof is presented in App. C.2. The proof is based on Lemma 3 and Lemma 4. The proof techniques are the same as the ones for Theorem 2.

6. Experiments

We performed experiments on the continual learning benchmark Permuted Mnist. The setup is the same as the one de-

scribed in (Goodfellow et al. 2013, Kirkpatrick et al. 2017, Chaudhry et al. 2019, Farajtabar et al. 2019). However, in order to assess the robustness to catastrophic forgetting over a long sequence of tasks, we increase the size of the task sequence to 15. We generated 15 i.i.d. permutations of the MNIST pixels, then defined each task as a MNIST supervised learning problem with respect to each permutation, respectively. We trained the neural network sequentially on all tasks and tracked the validation loss on all previous tasks. We considered the same neural network architecture and mostly similar hyperparameters as (Farajtabar et al., 2019). The reproducibility details are presented in Appendix D.1.

We report the results in Figure 1, extended results are presented in App . D.2.1. The plot shows that OGD+ is more robust to catastrophic forgetting than OGD when the tasks occurrence difference is large. It also shows that OGD+ is equivalent to OGD when the tasks occurrence difference is small. These results concur with Lemma 6 which states that OGD is robust to catastrophic forgetting up to a single task ahead. They also concur with Lemma 3, which states that OGD+ is robust to catastrophic forgetting across any number of tasks. Two probable reasons that OGD+ is not perfectly prone to catastrophic forgetting in the experiment are the memory limit and the non-overparameterization of the neural network, while in Lemma 3, we assumed that the memory is unlimited and that the neural network is overparameterized.

We also observe that OGD+ slightly outperforms OGD for shorter term tasks, the probable reason is that OGD+ performs a uniform sampling across samples from all past tasks, considering the limited memory budget, we excpet an information loss with respect to the most recent tasks, since the corresponding storage is used by OGD+ to "remember" older tasks.

7. Related works

Continual Learning   Approaches to Continual Learning can be categorised into: regularization methods, memory based methods, and dynamic architectural methods. We refer the reader to the survey (Parisi et al., 2019) for an extensive overview on the existing methods. The idea behind memory-based methods is to store data from previous tasks in a buffer of fixed size, which can then be reused during training on the current task (Chaudhry et al. 2019, Van de Ven & Tolias 2018). Dynamic architectural methods rely on growing architectures which keep the past knowledge fixed and store new knowledge in new components, such as new nodes, layers ... (Lee et al. 2017, Schwarz et al. 2018) The idea behind regularization methods is to regularize the objective in order to preserve the knowledge acquired from the previous tasks (Kirkpatrick et al. 2016, Aljundi et al. 2017, Farajtabar et al. 2019, Zenke et al. 2017).

Figure 1. Test accuracy on the 4 first tasks of permuted MNIST, for SGD, OGD and OGD+. 15 different permutations are used, and the model is trained to classify MNIST digits for 5 epochs for each permutation. The y-axis is truncated for clarity. We report the dynamics of additional tasks in the appendix D.2.1. We report the mean and standard deviation over 5 independent runs. The test error is measured for every 50 mini-batch interval.

Catastrophic Forgetting   Catastrophic Forgetting refers to the tendency of agents to "forget" the previous tasks over the course of training. It has proven to be a challenging problem, several heuristics were developed in order to characterise it (Ans & Rousset 1997, Ans & Rousset 2000, Goodfellow et al. 2013, French 1999, McCloskey & Cohen 1989, Robins 1995, Nguyen et al. 2019).

Deep Learning Theory   Recent work have started to provide explanations about the mechanics of overparametrised Neural Networks. In their seminal work, Du et al. (2018) prove that Gradient Descent on multilayer overparametrised RELU neural networks achieve zero training error at the limit. These works have unlocked the analysis of several

properties of Deep Neural Networks, in the context of various applications, such as Transfer Learning (Liu et al., 2019), Noisy Supervision (Hu et al., 2019), Reinforcement Learning (Wang et al., 2020) ... Another line of works provide closed form expressions of the training dynamics of overparameterized neural networks, leveraging tools from statistical physics (Goldt et al. 2019, Goldt et al. 2020).

Also, Corrolary 1 in Sec. 3 can be seen as a generalisation of the Theorem 3 by Liu et al. (2019). While we don't make any assumptions on the neural network as opposed to Liu et al. (2019), which studies two-layer RELU neural networks, our analysis is based on less fine-grained approximations. Finally, as explained in Sec. 4.2, we used several proof techniques from Hu et al. (2019) to prove the Theorems 1 and 2.

Transfer Learning Several works have also recently started studying Transfer Learning from a theoretical perspective (Yu et al. 2020, Liu et al. 2019, Nguyen et al. 2019, Achille et al. 2019).

Statistical Learning Theory Alquier et al. (2017) define a compound regret for lifelong learning, as the regret with respect to the oracle who would have known the best common representation g for all tasks in advance.

Another line of works addresses lifelong learning and meta-learning from a statistical learning theory perspective, they define and provide regret bounds for lifelong learning (Alquier et al., 2017), or study the sample complexity and convergence of meta-learning algorithms (Denevi et al. 2018a, Du et al. 2020, Ji et al. 2020, Saunshi et al. 2020, Denevi et al. 2018b).

8. Discussion

In this section, we discuss some assumptions and limits of our analysis.

Linearization We considered a linear approximation of the neural network, which may not be valid in the non overparameterized regime. We find that the approximation leads to multiple insights on how to improve OGD, generalisation, knowledge transferability, curriculum learning and convergence. Also, our analysis is based solely on convex optimisation, which surprisingly leads us to results from other works, which considered other approximations for overparameterized neural networks. Also, the experiments with non-overparametrized neural networks concur with our theoretical findings.

How are the NTKs different between SGD and OGD ?
We note that the key difference comes from the feature map, which is projected with T to a feature space orthogonal to

$\mathbb{E}$. In practice, the size of the data is much smaller than the number of the parameters, therefore, the dimension of $\mathbb{E}$ is negligible in comparison with the d, the dimension of the parameter space of the neural net, independently of the NTK regime. It could be interesting to understand more in depth the difference between the kernels of SGD and OGD. Their formulation looks similar to Von Neumann Kernels, which may be a possible direction to investigate.

9. Conclusion

In this paper, we present an approach to study the properties of OGD for Continual Learning theoretically. Through this approach, we present in a closed-form how the model evolves through tasks. This result leads to a generalisation theorem for OGD and provides insights on the transferability of knowledge across tasks and on the importance of task ordering and how the curriculum impacts generalisation. We also present OGD+, an extension of OGD, for which we derive stronger guarantees in terms of robustness to catastrophic forgetting and generalisation error. Finally, we observe that OGD+ achieves state-of-the-art performance for settings with a large number of tasks.

There are multiple avenues for future investigation. First, similarly to Arora et al. (2019) and Liu et al. (2019), a lower bound over the number of parameters to fall in the overparameterization regime is an important problem, it would clarify the cases for which the theory is valid.

Another important direction to investigate is the theoretical properties of the other Continual Learning training methods and the catastrophic forgetting heuristics, such as the ones proposed by Nguyen et al. (2019). A theoretical understanding of these algorithms and heuristics, even for asymptotic cases, may provide insights on their limits and directions of improvements, similarly to OGD+.

We also observed in the experiments that uniform sampling across all tasks for OGD+ would be the optimal sampling strategy for an average performance balance across all past tasks. In order to favor remembering specific tasks, a direction would be to adapt the sampling distribution according to the past tasks' importance.

Finally, we found multiple connections to other fields such as Transfer Learning and Curriculum Learning. A promising direction for further investigation is to investigate how the theory could apply to neighbouring fields, such as meta-learning, multi-task learning ... We hope this work provides new keys to tackle these challenges.

References

à , J. S., dac Sur í s, D. i., Miron, M., and Karatzoglou, A. Overcoming catastrophic forgetting with hard attention to the task. *CoRR*, abs/1801.01423, 2018.

Achille, A., Lam, M., Tewari, R., Ravichandran, A., Maji, S., Fowlkes, C., Soatto, S., and Perona, P. Task2vec: Task embedding for meta-learning, 02 2019.

Aljundi, R., Babiloni, F., Elhoseiny, M., Rohrbach, M., and Tuytelaars, T. Memory aware synapses: Learning what (not) to forget. 11 2017.

Alquier, P., Mai, T. T., and Pontil, M. Regret Bounds for Lifelong Learning. In Singh, A. and Zhu, J. (eds.), *Proceedings of the 20th International Conference on Artificial Intelligence and Statistics*, volume 54 of *Proceedings of Machine Learning Research*, pp. 261–269, Fort Lauderdale, FL, USA, 20–22 Apr 2017. PMLR. URL http://proceedings.mlr.press/v54/alquier17a.html.

Ans, B. and Rousset, S. Avoiding catastrophic forgetting by coupling two reverberating neural networks. *Comptes Rendus de l'Académie des Sciences - Series III - Sciences de la Vie*, 320(12):989 – 997, 1997. ISSN 0764-4469. doi: https://doi.org/10.1016/S0764-4469(97)82472-9.

Ans, B. and Rousset, S. Neural networks with a self-refreshing memory: Knowledge transfer in sequential learning tasks without catastrophic forgetting. *Connection Science*, 12:1–19, 04 2000. doi: 10.1080/095400900116177.

Arora, S., Du, S. S., Hu, W., Li, Z., and Wang, R. Fine-grained analysis of optimization and generalization for overparameterized two-layer neural networks. *CoRR*, abs/1901.08584, 2019.

az Rodr í guez, N. D. i., Lomonaco, V., Filliat, D., and Maltoni, D. Don't forget, there is more than forgetting: new metrics for continual learning. *CoRR*, abs/1810.13166, 2018.

Bartlett, P. L. and Mendelson, S. Rademacher and gaussian complexities: Risk bounds and structural results. *J. Mach. Learn. Res.*, 3(null):463–482, March 2003. ISSN 1532-4435.

Ben-David, S. and Schuller, R. Exploiting task relatedness for multiple task learning. In Schölkopf, B. and Warmuth, M. K. (eds.), *Learning Theory and Kernel Machines*, pp. 567–580, Berlin, Heidelberg, 2003. Springer Berlin Heidelberg. ISBN 978-3-540-45167-9.

Bengio, Y., Louradour, J., Collobert, R., and Weston, J. Curriculum learning. In *Proceedings of the 26th Annual International Conference on Machine Learning*, ICML '09, pp. 41–48, New York, NY, USA, 2009. Association for Computing Machinery. ISBN 9781605585161. doi: 10.1145/1553374.1553380. URL https://doi.org/10.1145/1553374.1553380.

Bietti, A. and Mairal, J. On the inductive bias of neural tangent kernels, 2019.

Chaudhry, A., Ranzato, M., Rohrbach, M., and Elhoseiny, M. Efficient lifelong learning with a- GEM . In *International Conference on Learning Representations*, 2019.

Denevi, G., Ciliberto, C., Stamos, D., and Pontil, M. Incremental learning-to-learn with statistical guarantees, 2018a.

Denevi, G., Ciliberto, C., Stamos, D., and Pontil, M. Learning to learn around a common mean. In Bengio, S., Wallach, H., Larochelle, H., Grauman, K., Cesa-Bianchi, N., and Garnett, R. (eds.), *Advances in Neural Information Processing Systems 31*, pp. 10169–10179. Curran Associates, Inc., 2018b.

Dicker, L. H., Foster, D. P., and Hsu, D. Kernel ridge vs. principal component regression: Minimax bounds and the qualification of regularization operators. *Electron. J. Statist.*, 11(1):1022–1047, 2017. doi: 10.1214/17-EJS1258.

Du, S. S., Zhai, X., s P ó czos, B. a., and Singh, A. Gradient descent provably optimizes over-parameterized neural networks. *CoRR*, abs/1810.02054, 2018.

Du, S. S., Hu, W., Kakade, S. M., Lee, J. D., and Lei, Q. Few-shot learning via learning the representation, provably, 2020.

Ebrahimi, S., Elhoseiny, M., Darrell, T., and Rohrbach, M. Uncertainty-guided continual learning with bayesian neural networks. In *International Conference on Learning Representations*, 2020.

Fang, C., Dong, H., and Zhang, T. Over parameterized two-level neural networks can learn near optimal feature representations, 2019.

Farajtabar, M., Azizan, N., Mott, A., and Li, A. Orthogonal gradient descent for continual learning, 2019.

French, R. Catastrophic forgetting in connectionist networks. *Trends in cognitive sciences*, 3:128–135, 05 1999. doi: 10.1016/S1364-6613(99)01294-2.

Goldt, S., Advani, M., Saxe, A. M., Krzakala, F., and Zdeborov´ a , L. Dynamics of stochastic gradient descent for two-layer neural networks in the teacher-student setup. In Wallach, H., Larochelle, H., Beygelzimer, A., dAlché

Buc, F., Fox, E., and Garnett, R. (eds.), *Advances in Neural Information Processing Systems 32*, pp. 6979–6989. Curran Associates, Inc., 2019.

Goldt, S., zard, M. M. e., Krzakala, F., and á , L. Z. Modelling the influence of data structure on learning in neural networks, 2020.

Goodfellow, I., Mirza, M., Da, X., Courville, A., and Bengio, Y. An empirical investigation of catastrophic forgetting in gradient-based neural networks. 12 2013.

Hayou, S., Doucet, A., and Rousseau, J. Mean-field behaviour of neural tangent kernel for deep neural networks, 2019.

Hu, W., Li, Z., and Yu, D. Simple and effective regularization methods for training on noisily labeled data with generalization guarantee, 2019.

Jacot, A., Gabriel, F., and Hongler, C. e. m. Neural tangent kernel: Convergence and generalization in neural networks. In *Proceedings of the 32nd International Conference on Neural Information Processing Systems*, NIPS'18, pp. 8580–8589, Red Hook, NY, USA, 2018. Curran Associates Inc.

Ji, K., Yang, J., and Liang, Y. Multi-step model-agnostic meta-learning: Convergence and improved algorithms, 2020.

Kirkpatrick, J., Pascanu, R., Rabinowitz, N., Veness, J., Desjardins, G., Rusu, A., Milan, K., Quan, J., Ramalho, T., Grabska-Barwinska, A., Hassabis, D., Clopath, C., Kumaran, D., and Hadsell, R. Overcoming catastrophic forgetting in neural networks. *Proceedings of the National Academy of Sciences*, 114, 12 2016. doi: 10.1073/pnas.1611835114.

Kirkpatrick, J., Pascanu, R., Rabinowitz, N., Veness, J., Desjardins, G., Rusu, A. A., Milan, K., Quan, J., Ramalho, T., Grabska-Barwinska, A., Hassabis, D., Clopath, C., Kumaran, D., and Hadsell, R. Overcoming catastrophic forgetting in neural networks. *Proceedings of the National Academy of Sciences*, 114(13):3521–3526, 2017. ISSN 0027-8424. doi: 10.1073/pnas.1611835114.

Lee, J., Yoon, J., Yang, E., and Hwang, S. J. Lifelong learning with dynamically expandable networks. abs/1708.01547, 2017.

Lee, J., Xiao, L., Schoenholz, S. S., Bahri, Y., Novak, R., Sohl-Dickstein, J., and Pennington, J. Wide neural networks of any depth evolve as linear models under gradient descent, 2019.

Li, M., Soltanolkotabi, M., and Oymak, S. Gradient descent with early stopping is provably robust to label noise for overparameterized neural networks. *CoRR*, abs/1903.11680, 2019.

Liu, H., Long, M., Wang, J., and Jordan, M. I. Towards understanding the transferability of deep representations, 2019.

Masse, N., Grant, G., and Freedman, D. Alleviating catastrophic forgetting using context-dependent gating and synaptic stabilization. *Proceedings of the National Academy of Sciences*, 115, 02 2018. doi: 10.1073/pnas.1803839115.

McCloskey, M. and Cohen, N. J. Catastrophic interference in connectionist networks: The sequential learning problem. volume 24 of *Psychology of Learning and Motivation*, pp. 109 – 165. Academic Press, 1989. doi: https://doi.org/10.1016/S0079-7421(08)60536-8.

Nguyen, C., Achille, A., Lam, M., Hassner, T., Mahadevan, V., and Soatto, S. Toward understanding catastrophic forgetting in continual learning, 08 2019.

Nguyen, C. V., Li, Y., Bui, T. D., and Turner, R. E. Variational continual learning. In *International Conference on Learning Representations*, 2018. URL https://openreview.net/forum?id=BkQqq0gRb.

Pan, P., Immer, A., Swaroop, S., Eschenhagen, R., Turner, R. E., and Khan, M. E. Continual deep learning by functional regularisation of memorable past, 2020.

Parisi, G. I., Kemker, R., Part, J. L., Kanan, C., and Wermter, S. Continual lifelong learning with neural networks: A review. *Neural Networks*, 113:54 – 71, 2019. ISSN 0893-6080.

Ratcliff, R. Connectionist models of recognition memory: constraints imposed by learning and forgetting functions. *Psychological review*, 97 2:285–308, 1990.

Ritter, H., Botev, A., and Barber, D. Online structured laplace approximations for overcoming catastrophic forgetting. In *Proceedings of the 32nd International Conference on Neural Information Processing Systems*, NIPS'18, pp. 3742–3752, Red Hook, NY, USA, 2018. Curran Associates Inc.

Robins, A. Catastrophic forgetting, rehearsal and pseudorehearsal. *Connection Science*, 7:123–, 01 1995.

Saunshi, N., Zhang, Y., Khodak, M., and Arora, S. A sample complexity separation between non-convex and convex meta-learning, 2020.

Schwarz, J., Luketina, J., Czarnecki, W., Grabska-Barwinska, A., Teh, Y., Pascanu, R., and Hadsell, R. Progress and compress: A scalable framework for continual learning, 05 2018.

Smola, A. J., Schö lkopf, B., and Mü ller, K.-R. The connection between regularization operators and support vector kernels. *Neural Netw.*, 11(4):637–649, June 1998. ISSN 0893-6080. doi: 10.1016/S0893-6080(98)00032-X.

Van de Ven, G. M. and Tolias, A. S. Generative replay with feedback connections as a general strategy for continual learning. *arXiv preprint arXiv:1809.10635*, 2018.

Van de Ven, G. M. and Tolias, A. S. Three scenarios for continual learning. *arXiv preprint arXiv:1904.07734*, 2019.

Wang, R., Du, S. S., Yang, L. F., and Kakade, S. M. Is long horizon reinforcement learning more difficult than short horizon reinforcement learning?, 2020.

Wei, C., Lee, J. D., Liu, Q., and Ma, T. Regularization matters: Generalization and optimization of neural nets v.s. their induced kernel. In Wallach, H., Larochelle, H., Beygelzimer, A., dAlché Buc, F., Fox, E., and Garnett, R. (eds.), *Advances in Neural Information Processing Systems 32*, pp. 9709–9721. Curran Associates, Inc., 2019.

Yu, T., Kumar, S., Gupta, A., Levine, S., Hausman, K., and Finn, C. Gradient surgery for multi-task learning, 2020.

Zenke, F., Poole, B., and Ganguli, S. Continual learning through synaptic intelligence. In *Proceedings of the 34th International Conference on Machine Learning - Volume 70*, ICML'17, pp. 3987–3995. JMLR.org, 2017.

A. Missing proofs of section 3 - Convergence

A.1. Proof of Theorem 1

Orthogonal Gradient Descent   Proof

We prove the Theorem 1 by induction. Our induction hypothesis H_τ is the following :

H_τ : For all $k \le \tau$, Theorem 1 holds.

First, we prove that H_1 holds.

The proof is straightforward. For the first task, since there were no previous tasks $\mathbb{E}_1 = \emptyset$. Therefore, OGD on this task is equivalent to SGD.

Therefore, it is equivalent to minimising the following objective, where $\tau = 1$:

$$\underset{\mathbf{w} \in \mathbb{R}^d}{\arg\min} \left\| \phi_\tau(\mathbf{X}_\tau)^T (\mathbf{w}_{\tau+1}(t) - \mathbf{w}_\tau^\star) - \tilde{\mathbf{y}}_{\tau+1} \right\|_2^2 + \lambda_\tau \|\mathbf{w} - \mathbf{w}_0\|^2$$

The objective is quadratic and the Hessian is positive definite, therefore the minimum exists and is unique :

$$\mathbf{w}_\tau^\star - \mathbf{w}_0 = \phi_\tau(\mathbf{X}_\tau)(\phi_\tau(\mathbf{X}_\tau)^T \phi_\tau(\mathbf{X}_\tau) + \lambda_\tau^2 I)^{-1} \tilde{\mathbf{y}}_\tau$$

For $\tau = 1$, since there are no previous tasks $\tilde{\mathbf{y}}_\tau = \mathbf{y}_\tau$. Therefore :

$$\mathbf{w}_\tau^\star - \mathbf{w}_0 = k_\tau(\mathbf{x}, \mathbf{X}_\tau)(k_\tau(\mathbf{X}_\tau, \mathbf{X}_\tau) + \lambda_\tau^2 \mathbf{I})^{-1} \tilde{\mathbf{y}}_\tau$$

Which completes the proof of H_1.

Let $\tau \in \mathbb{N}^\star$, assume H_τ is true, we show $H_{\tau+1}$

On the task $\tau + 1$, we can write the loss $\mathcal{L}^{\tau+1}$ as :

$$\mathcal{L}^{\tau+1}(\mathbf{w}_{\tau+1}(t)) = \left\| \phi_\tau(\mathbf{X}_\tau)^T (\mathbf{w}_{\tau+1}(t) - \mathbf{w}_\tau^\star) - \tilde{\mathbf{y}}_{\tau+1} \right\|_2^2 + \lambda_{\tau+1} \|\mathbf{w}_{\tau+1} - \mathbf{w}_\tau\|^2$$

We recall that the optimisation problem at time $(\tau + 1)$:

$$\underset{\mathbf{w} \in \mathbb{R}^d}{\arg\min} \left\| \phi_\tau(\mathbf{X}_\tau)^T (\mathbf{w}_{\tau+1}(t) - \mathbf{w}_\tau^\star) - \tilde{\mathbf{y}}_{\tau+1} \right\|_2^2 + \lambda_{\tau+1} \|\mathbf{w}_{\tau+1} - \mathbf{w}_\tau\|^2$$
$$\text{u.c.} \quad \mathbf{V}_{\tau+1}(\mathbf{w} - \mathbf{w}_\tau^\star) = 0$$

Let $\mathbf{T}_{\tau+1} \in \mathbb{R}^{d \times (d-K_{\tau+1})}$ and $\tilde{\mathbf{w}}_{\tau+1} \in \mathbb{R}^{d-K_{\tau+1}}$ such as :

$$\mathbf{w} - \mathbf{w}_\tau^\star = \mathbf{T}_{\tau+1} \tilde{\mathbf{w}}_{\tau+1}$$
$$K_{\tau+1} = \dim(\mathbb{E}_{\tau+1})$$

We rewrite the objective by plugging in the variables we just defined. The two objectives are equivalent :

$$\underset{\tilde{\mathbf{w}} \in \mathbb{R}^{d-K_{\tau+1}}}{\arg\min} \left\| \phi_\tau(\mathbf{X}_\tau)^T \mathbf{T}_{\tau+1} \tilde{\mathbf{w}} - \tilde{\mathbf{y}}_{\tau+1} \right\|_2^2 + \lambda_{\tau+1}^2 \|\mathbf{T}_{\tau+1} \tilde{\mathbf{w}}\|_2^2$$

For clarity, we define $\mathbf{Z}_{\tau+1} \mathbb{R}^{n_{\tau+1} \times (d-K_{\tau+1})}$ as :

$$\mathbf{Z}_{\tau+1} = \phi_\tau(\mathbf{X}_\tau)^T \mathbf{T}_{\tau+1}$$

By plugging in $\mathbf{Z}_{\tau+1}$, we rewrite the objective as :

$$\underset{\tilde{\mathbf{w}} \in \mathbb{R}^{d-K_{\tau+1}}}{\arg\min} \left\| \mathbf{Z}_{\tau+1}\tilde{\mathbf{w}} - \tilde{\mathbf{y}}_{\tau+1} \right\|_2^2 + \lambda_{\tau+1}^2 \|\mathbf{T}_{\tau+1}\tilde{\mathbf{w}}\|_2^2$$

The optimisation objective is quadratic, unconstrainted, with a positive definite hessian. Therefore, an optimum exists and is unique :

$$\tilde{\mathbf{w}}_{\tau+1}^\star = \mathbf{Z}_{\tau+1}^T (\mathbf{Z}_{\tau+1}\mathbf{Z}_{\tau+1}^T + \lambda_{\tau+1}^2 I)^{-1} \tilde{\mathbf{y}}_{\tau+1}$$

We recover the expression of the optimum in the original space :

$$\mathbf{w}_{\tau+1}^\star - \mathbf{w}_\tau^\star = \mathbf{T}_{\tau+1}\mathbf{Z}_{\tau+1}^T (\mathbf{Z}_{\tau+1}\mathbf{Z}_{\tau+1}^T + \lambda_{\tau+1}^2 I)^{-1} \tilde{\mathbf{y}}_{\tau+1}$$

We define the kernel $k_{\tau+1} : \mathbb{R}^d \times \mathbb{R}^d \to \mathbb{R}$ as :

$$k_{\tau+1}(\mathbf{x}, \mathbf{x}') = \phi_\tau(\mathbf{x})^T \mathbf{T}_{\tau+1}\mathbf{T}_{\tau+1}^T \phi_\tau(\mathbf{x}') \quad \text{for all } \mathbf{x}, \mathbf{x}' \in \mathbb{R}^d$$

Now we rewrite $\mathbf{w}_{\tau+1}^\star - \mathbf{w}_\tau^\star$:

$$\mathbf{w}_{\tau+1}^\star - \mathbf{w}_\tau^\star = \mathbf{T}_{\tau+1}\mathbf{Z}_{\tau+1}^T (k_{\tau+1}(\mathbf{X}_\tau, \mathbf{X}_\tau) + \lambda_{\tau+1}^2 I)^{-1} \tilde{\mathbf{y}}_{\tau+1}$$

Finally, we recover a closed form expression for $f_{\tau+1}^\star$:

First, we use the induction hypothesis H_τ :

$$\begin{aligned} f_{\tau+1}^\star(\mathbf{x}) &= f_\tau^\star(\mathbf{x}) + \langle \nabla_\mathbf{w} f_\tau^\star(\mathbf{x}), \mathbf{w}_{\tau+1}^\star - \mathbf{w}_\tau^\star \rangle \\ &= f_\tau^\star(\mathbf{x}) + \phi_\tau(\mathbf{x})\mathbf{T}_{\tau+1}\mathbf{Z}_{\tau+1}^T (k_{\tau+1}(\mathbf{X}_\tau, \mathbf{X}_\tau) + \lambda_{\tau+1}^2 I)^{-1} \tilde{\mathbf{y}}_{\tau+1} \\ &= f_\tau^\star(\mathbf{x}) + k_{\tau+1}(\mathbf{x}, \mathbf{X}_\tau)(k_{\tau+1}(\mathbf{X}_\tau, \mathbf{X}_\tau) + \lambda_{\tau+1}^2 I)^{-1} \tilde{\mathbf{y}}_{\tau+1} \end{aligned}$$

At this stage, we have proven H_{t+1}.

We conclude.

Stochastic Gradient Descent   The proof is exactly the same as the proof for Orthogonal Gradient Descent, except that there are no equalities constraints.

A.2. Proof of the Corollary 1

Orthogonal Gradient Descent   Proof

In the lemma ..., we proved that :

$$\mathbf{w}_{\tau+1}^\star - \mathbf{w}_\tau^\star = \mathbf{T}_{\tau+1}\mathbf{Z}_{\tau+1}^T (k_{\tau+1}(\mathbf{X}_\tau, \mathbf{X}_\tau) + \lambda_{\tau+1}^2 I)^{-1} \tilde{\mathbf{y}}_{\tau+1}$$

Therefore :

$$\begin{aligned} \left\| \mathbf{w}_{\tau+1}^\star - \mathbf{w}_\tau^\star \right\|^2 &= \tilde{\mathbf{y}}_{\tau+1}^T (k_{\tau+1}(\mathbf{X}_\tau, \mathbf{X}_\tau) + \lambda_{\tau+1}^2 \mathbf{I})^{-1} \mathbf{Z}_{\tau+1}\mathbf{T}_{\tau+1}^T \mathbf{T}_{\tau+1}\mathbf{Z}_{\tau+1}^T (k_{\tau+1}(\mathbf{X}_\tau, \mathbf{X}_\tau) + \lambda_{\tau+1}^2 I)^{-1} \tilde{\mathbf{y}}_{\tau+1} \\ &= \tilde{\mathbf{y}}_{\tau+1}^T (k_{\tau+1}(\mathbf{X}_\tau, \mathbf{X}_\tau) + \lambda_{\tau+1}^2 \mathbf{I})^{-1} k_{\tau+1}(\mathbf{X}_\tau, \mathbf{X}_\tau)(k_{\tau+1}(\mathbf{X}_\tau, \mathbf{X}_\tau) + \lambda_{\tau+1}^2 I)^{-1} \tilde{\mathbf{y}}_{\tau+1} \end{aligned}$$

Stochastic Gradient Descent   The proof is exactly the same as for Orthogonal Gradient Descent.

B. Missing proofs of section 4 - Generalisation

B.1. Proof of Theorem 2

B.1.1. NOTATIONS

We recall that :

$$f_\tau^\star(\mathbf{x}) = \sum_{k=1}^{\tau-1} f_k^\star(\mathbf{x}) + k_\tau(\mathbf{x}, \mathbf{X}_\tau)^T (k_\tau(\mathbf{X}_\tau, \mathbf{X}_\tau) + \lambda_\tau^2 \mathbf{I})^{-1} \tilde{\mathbf{y}}_\tau$$

We define :

$$\tilde{f}_\tau^\star(\mathbf{x}) = k_\tau(\mathbf{x}, \mathbf{X}_\tau)^T \boldsymbol{\alpha}_\tau$$

where :

$$\boldsymbol{\alpha}_\tau = (k_\tau(\mathbf{X}_\tau, \mathbf{X}_\tau) + \lambda_\tau^2 \mathbf{I})^{-1} \tilde{\mathbf{y}}_\tau$$

Then :

$$f_\tau^\star(\mathbf{x}) = \sum_{k=1}^{\tau} \tilde{f}_\tau^\star(\mathbf{x})$$

Reminder on RKHS norm   Let k a kernel, and $\mathcal{H}$ the reproducing kernel Hilbert space (RKHS) corresponding to the kernel k. Recall that the RKHS norm of a function $f(x) = \alpha^T k(x, X)$ is : $\|f\|_{\mathcal{H}} = \sqrt{\alpha^T k(X, X)\alpha}$

Recap on Generalization and Rademacher Complexity   Consider a loss function $l : \mathbb{R} \times \mathbb{R} \to \mathbb{R}$. The population loss over the distribution $\mathcal{D}$, and the empirical loss over n samples $D = \{(\mathbf{x}_i, y_i), i \in [n]\}$ from the same distribution $\mathcal{D}$ are defined as :

$$L_D(f) = \mathbb{E}_{(\mathbf{x}, y) \sim \mathcal{D}}[l(f(\mathbf{x}), y)]$$

$$L_S(f) = \frac{1}{n} \sum_{i=1}^{n} l(f(\mathbf{x}_i), y_i)$$

Theorem 4 *Suppose the loss function is bounded in $[0, c]$ and is $\rho-$Lipchitz in the first argument. Then, with probability at least $1 - \delta$ over sample S of size n :*

$$\sup_{f \in \mathcal{F}} \{L_D(f) - L_S(f)\} \leq 2\rho\hat{\mathcal{R}}(\mathcal{F}) + 3c\sqrt{\frac{\log(2/\delta)}{2n}} \tag{3}$$

B.1.2. BOUNDING THE RADEMACHER COMPLEXITY

Lemma 4 (Rademacher Complexity of a linear combination of kernels) *Let $k_t : \mathcal{X} \times \mathcal{X} \to \mathbb{R}, t \in [T]$ kernels such that :*

$$\sup_{\mathbf{x} \in \mathcal{X}} \|k_t(\mathbf{x}, \mathbf{x})\| < \infty$$

To every kernel k_t, we associate a feature map $\phi_t : \mathcal{X} \to \mathcal{H}_t$, where $\mathcal{H}_t$ is a Hilbert space with inner product $\langle \cdot, \cdot \rangle_{\mathcal{H}_t}$, and for all $\mathbf{x}, \mathbf{x}' \in \mathcal{X}, k_t(\mathbf{x}, \mathbf{x}') = \langle \phi_t(\mathbf{x}), \phi_t(\mathbf{x}') \rangle_{\mathcal{H}_t}$

We define $\mathcal{F}$ as follows :

$$\mathcal{F} = \{\mathbf{x} \to \sum_{t=1}^{T} f_t(\mathbf{x}), \quad f_t(\mathbf{x}) = \alpha_t^T k_t(\mathbf{x}, \mathbf{X}_t) \quad \forall t \in [T], \|f_t\|_{\mathcal{H}_t} \leq B_t\} \tag{4}$$

Let $X_1, ..., X_n$ be random elements of $\mathcal{X}$. Then for the class $\mathcal{F}$, we have :

$$\hat{\mathcal{R}}(\mathcal{F}) \leq \sum_{t=1}^{T} \frac{2B_t}{n_t} (Tr(k_t(\mathbf{X}_t, \mathbf{X}_t)))^{1/2}$$

Proof

Let $f \in \mathcal{F}$, and let $\mathbf{x} \in \mathcal{X}$:

$$f(\mathbf{x}) = \sum_{t=1}^{T} \sum_{i=1}^{n_t} \alpha_i^t k_t(\mathbf{x}, \mathbf{x}_i^t) \tag{5}$$

For all $t \in [T]$, we associate a feature map $\phi_t : \mathbf{X} \to \mathcal{H}_t$

$$\forall \mathbf{x}, \mathbf{x}' \in \mathcal{X} \quad k_t(\mathbf{x}, \mathbf{x}') = \langle \phi_t(\mathbf{x}), \phi_t(\mathbf{x}') \rangle_{\mathcal{H}_t} \tag{6}$$

Therefore :

$$f(\mathbf{x}) = \sum_{t=1}^{T} \sum_{i=1}^{n_t} \alpha_i^t \langle \phi_t(\mathbf{x}_i^t), \phi_t(\mathbf{x}) \rangle_{\mathcal{H}_t} \tag{7}$$

$$= \sum_{t=1}^{T} \langle \sum_{i=1}^{n_t} \alpha_i^t \phi_t(\mathbf{x}_i^t), \phi_t(\mathbf{x}) \rangle_{\mathcal{H}_t} \tag{8}$$

On the other hand, the following holds $\forall t \in [T]$:

$$\left\| \sum_{i=1}^{n_t} \alpha_i^t \phi_t(\mathbf{x}_i^t) \right\|_{\mathcal{H}_t}^2 = \sum_{i,j} \alpha_i^t \alpha_j^t k_t(\mathbf{x}_i^t, \mathbf{x}_j^t) \leq B_t^2 \tag{9}$$

Therefore :

$$\mathcal{F} \subset \{ \mathbf{x} \to \sum_{t=1}^{T} \langle \mathbf{w}_t, \phi_t(\mathbf{x}) \rangle_{\mathcal{H}_t}, \|\mathbf{w}_t\|_2 \leq B_t \quad \forall t \in [T] \} := \tilde{\mathcal{F}} \tag{10}$$

Now, we derive an upper bound of the Rademacher complexity of $\mathcal{F}$:

$$\hat{\mathcal{R}}(\mathcal{F}) \leq \hat{\mathcal{R}}(\tilde{\mathcal{F}}) \tag{11}$$

$$= \mathbb{E}[\sup_{\|\mathbf{w}_t\|_2 \leq B_t, t \in [T]} \sum_{t=1}^{T} \langle \mathbf{w}_t, \frac{2}{n_t} \sum_{i=1}^{n_t} \epsilon_i \phi_t(\mathbf{x}_i^t) \rangle_{\mathcal{H}_t} | (\mathbf{X}_t)] \tag{12}$$

$$= \sum_{t=1}^{T} \mathbb{E}[\sup_{\|\mathbf{w}_t\|_2 \leq B_t} \langle \mathbf{w}_t, \frac{2}{n_t} \sum_{i=1}^{n_t} \epsilon_i \phi_t(\mathbf{x}_i^t) \rangle_{\mathcal{H}_t} | (\mathbf{X}_t)] \tag{13}$$

$$\leq \sum_{t=1}^{T} \frac{2B_t}{n_t} (Tr(k_t(\mathbf{X}_t)))^{1/2} \tag{14}$$

The last inequality is obtained by applying the upper bound from Lemma 22 in (Bartlett & Mendelson, 2003), on each function f_t

$$\tag{15}$$

B.1.3. BOUNDING $\left\|\tilde{f}_\tau^\star\right\|_{\mathcal{H}_\tau}$:

Lemma 5 *Let $\mathcal{H}_\tau$ the Hilbert space associated to the kernel k_τ .*

We recall that :

$$\tilde{f}_\tau^\star(\mathbf{x}) = k_\tau(\mathbf{x}, \mathbf{X}_\tau)^T \boldsymbol{\alpha}_\tau \tag{16}$$

$$\boldsymbol{\alpha}_\tau = (k_\tau(\mathbf{X}_\tau, \mathbf{X}_\tau) + \lambda_\tau^2 \mathbf{I})^{-1} \tilde{\mathbf{y}}_\tau \tag{17}$$

Then :

$$\left\|\tilde{f}_\tau^\star\right\|_{\mathcal{H}_\tau}^2 \leq \tilde{\mathbf{y}}_\tau^T (k_\tau(\mathbf{X}_\tau, \mathbf{X}_\tau) + \lambda^2 \mathbf{I})^{-1} \tilde{\mathbf{y}}_\tau \tag{18}$$

$$\tag{19}$$

Proof

$$\left\|\tilde{f}_\tau^\star\right\|_{\mathcal{H}_\tau}^2 = \boldsymbol{\alpha}_\tau^T k_\tau(\mathbf{X}_\tau, \mathbf{X}_\tau) \boldsymbol{\alpha}_\tau$$
$$= \mathbf{y}_\tau^T (k_\tau(\mathbf{X}_\tau, \mathbf{X}_\tau) + \lambda^2 \mathbf{I})^{-1} k_\tau(\mathbf{X}_\tau, \mathbf{X}_\tau)(k_\tau(\mathbf{X}_\tau, \mathbf{X}_\tau) + \lambda^2 \mathbf{I})^{-1} \tilde{\mathbf{y}}_\tau$$

Since $(k_\tau(\mathbf{X}, \mathbf{X}) + \lambda^2 \mathbf{I})^{-1} \leq k_\tau(\mathbf{X}, \mathbf{X})^{-1}$, we get :

$$\left\|\tilde{f}_\tau^\star\right\|_{\mathcal{H}_\tau}^2 \leq \tilde{\mathbf{y}}_\tau^T k_\tau(\mathbf{X}_\tau, \mathbf{X}_\tau)(k_\tau(\mathbf{X}_\tau, \mathbf{X}_\tau) + \lambda^2 \mathbf{I})^{-1} \tilde{\mathbf{y}}_\tau$$

B.1.4. PROOF OF LEMMA 1

The intuition behind the proof is : since the gradient updates were performed orthogonally to the feature maps of the training data of the source task, the parameters in this space are unchanged, while the remaining space, which was changed, is orthogonal to these features maps, therefore, the inference is the same and the training error remanis the same as at the end of training on the source task.

Proof

$$f_T^\star(\mathbf{x}_{T-1,i}) = f_{T-1}^\star(\mathbf{x}_{T-1,i}) + \langle \phi_T(\mathbf{x}_{T-1,i}), \mathbf{w}_T^\star - \mathbf{w}_{T-1}^\star \rangle$$
$$= f_{T-1}^\star(\mathbf{x}_{T-1,i}) + \langle \nabla_{\mathbf{w}} f(\mathbf{w}_{T-1}^\star, \mathbf{x}), \mathbf{w}_T^\star - \mathbf{w}_{T-1}^\star \rangle$$

Since we the training on task $\mathcal{T}_T$ is perfomed with OGD, we have :

$$\Pi_{\mathbb{E}_{T-1}}(\mathbf{w}_T^\star - \mathbf{w}_{T-1}^\star) = 0$$

Since $\nabla_{\mathbf{w}} f(\mathbf{w}_{T-1}^\star, \mathbf{x}) \in \mathbb{E}_{T-1}$ by definition, it follows that :

$$f_T^\star(\mathbf{x}_{T-1,i}) = f_{T-1}^\star(\mathbf{x}_{T-1,i})$$

B.1.5. BOUNDING THE TRAINING ERROR

Lemma 6 *The training errors on the source and target tasks can be bounded as follows :*

Let $T \in \mathbb{N}$ fixed. Then, for all $\tau \in [T]$

$$\frac{1}{n_T} \sum_{i=1}^{n_T} (f_T^\star(\mathbf{x}_{T,i}) - y_{T,i})^2 \leq \frac{1}{n_T} \frac{\lambda^2}{4} \tilde{\mathbf{y}}_T^T (k_T(\mathbf{X}_T, \mathbf{X}_T))^{-1} \tilde{\mathbf{y}}_T$$

$$\frac{1}{n_{T-1}} \sum_{i=1}^{n_{T-1}} (f_T^\star(\mathbf{x}_{T-1,i}) - y_{T-1,i})^2 \leq \frac{1}{n_{T-1}} \frac{\lambda^2}{4} \tilde{\mathbf{y}}_{T-1}^T (k_{T-1}(\mathbf{X}_{T-1}, \mathbf{X}_{T-1}))^{-1} \tilde{\mathbf{y}}_{T-1}$$

For all $\tau \in [T-2]$

$$\frac{1}{n_\tau} \|f_T^\star(\mathbf{X}_\tau) - \mathbf{y}_\tau\|_2^2 \leq \frac{1}{n_\tau} \left(\frac{\lambda^2}{4} \tilde{\mathbf{y}}_\tau^T (k_\tau(\mathbf{X}_\tau, \mathbf{X}_\tau))^{-1} \tilde{\mathbf{y}}_\tau + \right.$$

$$\left. \sum_{k=\tau+1}^{T} \frac{1}{4\lambda^2} \tilde{\mathbf{y}}_k^T k_k(\mathbf{X}_k, \mathbf{X}_k)^{-1} k(\mathbf{X}_\tau, \mathbf{X}_k) k(\mathbf{X}_\tau, \mathbf{X}_k)^T k_k(\mathbf{X}_k, \mathbf{X}_k)^{-1} \tilde{\mathbf{y}}_k \right)$$

Task $\mathcal{T}_T$ Proof

We start from the definition of the training error :

$$\sum_{i=1}^{n_T} (f_T^\star(\mathbf{x}_{T,i}) - y_{T,i})^2 = \left\| (k_T(\mathbf{X}_T, \mathbf{X}_T)^T (k_T(\mathbf{X}_T, \mathbf{X}_T) + \lambda^2 \mathbf{I})^{-1} - \mathbf{I}) \tilde{\mathbf{y}}_T \right\|_2^2$$

The expression is very similar to the previous norm, we can derive the same analysis as above to derive the following bound :

$$\sum_{i=1}^{n_T} (f_T^\star(\mathbf{x}_{T,i}) - y_{T,i})^2 \leq \frac{\lambda^2}{4} \tilde{\mathbf{y}}_T^T (k_T(\mathbf{X}_T, \mathbf{X}_T))^{-1} \tilde{\mathbf{y}}_T$$

Therefore :

$$\frac{1}{n_T} \sum_{i=1}^{n_T} (f_T^\star(\mathbf{x}_{T,i}) - y_{T,i})^2 \leq \frac{1}{n_T} \frac{\lambda^2}{4} \tilde{\mathbf{y}}_T^T (k_T(\mathbf{X}_T, \mathbf{X}_T))^{-1} \tilde{\mathbf{y}}_T$$

Task $\mathcal{T}_{T-1}$ Proof

We start with the definition of the training error, then applying Lemma 1 :

$$\sum_{i=1}^{n_{T-1}} (f_T^\star(\mathbf{x}_{T-1,i}) - y_{T-1,i})^2 = \sum_{i=1}^{n_{T-1}} (f_{T-1}^\star(\mathbf{x}_{T-1,i}) - y_{T-1,i})^2$$

$$= \left\| f_{T-1}^\star(\mathbf{X}_{T-1}) - \mathbf{y}_{T-1} \right\|_2^2$$

$$= \left\| k_{T-1}(\mathbf{X}_{T-1}, \mathbf{X}_{T-1})^T (k_{T-1}(\mathbf{X}_{T-1}, \mathbf{X}_{T-1}) + \lambda^2 \mathbf{I})^{-1} - \mathbf{I}) \tilde{\mathbf{y}}_{T-1} \right\|_2^2$$

$$= \left\| -\lambda^2 (k_{T-1}(\mathbf{X}_{T-1}, \mathbf{X}_{T-1}) + \lambda^2 \mathbf{I})^{-1} \tilde{\mathbf{y}}_{T-1} \right\|_2^2$$

$$= \lambda^4 \left\| (k_{T-1}(\mathbf{X}_{T-1}, \mathbf{X}_{T-1}) + \lambda^2 \mathbf{I})^{-1} \tilde{\mathbf{y}}_{T-1} \right\|_2^2$$

$$= \lambda^4 \mathbf{y}_{T-1}^T (k_{T-1}(\mathbf{X}_{T-1}, \mathbf{X}_{T-1}) + \lambda^2 \mathbf{I})^{-2} \tilde{\mathbf{y}}_{T-1}$$

Since :

$$(k_{T-1}(\mathbf{X}_{T-1}, \mathbf{X}_{T-1}) + \lambda^2 \mathbf{I})^{-2} \leq \frac{1}{4\lambda^2} k_{T-1}(\mathbf{X}_{T-1}, \mathbf{X}_{T-1})^{-1}$$

We get :

$$\sum_{i=1}^{n_{T-1}} (f_T^\star(\mathbf{x}_{T-1,i}) - y_{T-1,i})^2 \leq \frac{\lambda^2}{4} \tilde{\mathbf{y}}_{T-1}^T (k_{T-1}(\mathbf{X}_{T-1}, \mathbf{X}_{T-1}))^{-1} \tilde{\mathbf{y}}_{T-1}$$

Therefore :

$$\frac{1}{n_{T-1}} \sum_{i=1}^{n_{T-1}} (f_T^\star(\mathbf{x}_{T-1,i}) - y_{T-1,i})^2 \leq \frac{1}{n_{T-1}} \frac{\lambda^2}{4} \tilde{\mathbf{y}}_{T-1}^T (k_{T-1}(\mathbf{X}_{T-1}, \mathbf{X}_{T-1}))^{-1} \tilde{\mathbf{y}}_{T-1}$$

Task $\mathcal{T}_1, ..., \mathcal{T}_{T-2}$ **Proof**

Let $\tau \in [T-2]$ fixed.

We recall that :

$$f_T^\star(\mathbf{x}) = f_\tau^\star(\mathbf{x}) + \sum_{k=\tau+1}^{T} \tilde{f}_k^\star(\mathbf{x})$$

Then :

$$\|f_T^\star(\mathbf{X}_\tau) - \mathbf{y}_\tau\|_2^2 = \left\| f_\tau^\star(\mathbf{X}_\tau) + \sum_{k=\tau+1}^{T} \tilde{f}_k^\star(\mathbf{X}_\tau) - \mathbf{y}_\tau \right\|_2^2$$

$$\leq \|f_\tau^\star(\mathbf{X}_\tau) - \mathbf{y}_\tau\|_2^2 + \left\| \sum_{k=\tau+1}^{T} \tilde{f}_k^\star(\mathbf{X}_\tau) \right\|_2^2$$

$$\leq \underbrace{\|f_\tau^\star(\mathbf{X}_\tau) - \mathbf{y}_\tau\|_2^2}_{\text{A}} + \underbrace{\sum_{k=\tau+1}^{T} \left\| \tilde{f}_k^\star(\mathbf{X}_\tau) \right\|_2^2}_{\text{B}}$$

We can upper bound (A) similarly to the previous paragraphs, therefore we get :

$$\|f_\tau^\star(\mathbf{X}_\tau) - \mathbf{y}_\tau\|_2^2 \leq \frac{\lambda^2}{4} \tilde{\mathbf{y}}_\tau^T (k_\tau(\mathbf{X}_\tau, \mathbf{X}_\tau))^{-1} \tilde{\mathbf{y}}_\tau$$

Now, we upper bound (B). Let $k \in [\tau+1, T]$:

$$\left\| \tilde{f}_k^\star(\mathbf{X}_\tau) \right\|_2^2 = \tilde{\mathbf{y}}_k^T (k_k(\mathbf{X}_k, \mathbf{X}_k) + \lambda_k^2 \mathbf{I})^{-1} k(\mathbf{X}_\tau, \mathbf{X}_k) k(\mathbf{X}_\tau, \mathbf{X}_k)^T (k_k(\mathbf{X}_k, \mathbf{X}_k) + \lambda_k^2 \mathbf{I})^{-1} \tilde{\mathbf{y}}_k$$

$$= \frac{1}{4\lambda^2} \tilde{\mathbf{y}}_k^T k_k(\mathbf{X}_k, \mathbf{X}_k)^{-1} \underbrace{k(\mathbf{X}_\tau, \mathbf{X}_k) k(\mathbf{X}_\tau, \mathbf{X}_k)^T}_{\text{Captures the similarity between the tasks } \mathcal{T}_\tau \text{ and } \mathcal{T}_k} k_k(\mathbf{X}_k, \mathbf{X}_k)^{-1} \tilde{\mathbf{y}}_k$$

We conclude by plugging back the upper bounds of (A) and (B)

$$\|f_T^\star(\mathbf{X}_\tau) - \mathbf{y}_\tau\|_2^2 \leq \frac{\lambda^2}{4} \tilde{\mathbf{y}}_\tau^T (k_\tau(\mathbf{X}_\tau, \mathbf{X}_\tau))^{-1} \tilde{\mathbf{y}}_\tau + \sum_{k=\tau+1}^{T} \frac{1}{4\lambda^2} \tilde{\mathbf{y}}_k^T k_k(\mathbf{X}_k, \mathbf{X}_k)^{-1} k(\mathbf{X}_\tau, \mathbf{X}_k) k(\mathbf{X}_\tau, \mathbf{X}_k)^T k_k(\mathbf{X}_k, \mathbf{X}_k)^{-1} \tilde{\mathbf{y}}_k$$

Therefore :

$$\frac{1}{n_\tau} \|f_T^\star(\mathbf{X}_\tau) - \mathbf{y}_\tau\|_2^2 \leq \frac{1}{n_\tau} \left(\frac{\lambda^2}{4} \tilde{\mathbf{y}}_\tau^T (k_\tau(\mathbf{X}_\tau, \mathbf{X}_\tau))^{-1} \tilde{\mathbf{y}}_\tau + \sum_{k=\tau+1}^{T} \frac{1}{4\lambda^2} \tilde{\mathbf{y}}_k^T k_k(\mathbf{X}_k, \mathbf{X}_k)^{-1} k(\mathbf{X}_\tau, \mathbf{X}_k) k(\mathbf{X}_\tau, \mathbf{X}_k)^T k_k(\mathbf{X}_k, \mathbf{X}_k)^{-1} \tilde{\mathbf{y}}_k \right)$$

B.1.6. BOUNDING THE RADEMACHER COMPLEXITY

Proof

The proof strategy is exactly the same as sec. B.1. We generalize the previous proof, by applying the same lemmas.

$$\mathcal{F}_{\mathbf{B}_T} = \{\mathbf{x} \to \sum_{\tau=1}^{T} f_\tau(\mathbf{x}), \quad f_\tau(\mathbf{x}) = \boldsymbol{\alpha}_\tau^T k_\tau(\mathbf{x}, \mathbf{X}_\tau) \quad \forall \tau \in [T], \|f_\tau\|_{\mathcal{H}_\tau} \le B_\tau\}$$

It holds that :

$$f_T^\star \in \mathcal{F}_{\mathbf{B}_T}$$

where, for all $\tau \in [T]$:

$$B_\tau = \sqrt{(\mathbf{y}_\tau - \mathbf{y}_{\tau-1 \to \tau})^T (k_\tau(\mathbf{X}_\tau, \mathbf{X}_\tau) + \lambda_\tau^2 \mathbf{I})^{-1}(\mathbf{y}_\tau - \mathbf{y}_{\tau-1 \to \tau})}$$

$$\hat{\mathcal{R}}(\mathcal{F}_{\mathbf{B}_T}) \le \sum_{\tau=1}^{T} \frac{2(B_\tau + \epsilon)}{n_\tau}(Tr(k_\tau(\mathbf{X}_\tau, \mathbf{X}_\tau)))^{1/2}$$

We made the assumption that for all $\tau \in [T]$ $\text{tr}(k_\tau(\mathbf{X}_\tau, \mathbf{X}_\tau)) = \mathcal{O}(n_\tau)$, also, by setting $\epsilon = 1$:

$$\hat{\mathcal{R}}(\mathcal{F}_{\mathbf{B}_T}) \le \sum_{\tau=1}^{T} \frac{2(B_\tau + 1)}{n_\tau} \mathcal{O}(\sqrt{n_\tau})$$

$$\le \sum_{\tau=1}^{T} \mathcal{O}(\frac{B_\tau}{\sqrt{n_\tau}}) + \sum_{\tau=1}^{T} \mathcal{O}(\frac{1}{\sqrt{n_\tau}})$$

$$\le \sum_{\tau=1}^{T} \mathcal{O}\left(\sqrt{\frac{(\mathbf{y}_\tau - \mathbf{y}_{\tau-1 \to \tau})^T (k_\tau(\mathbf{X}_\tau, \mathbf{X}_\tau) + \lambda^2 \mathbf{I})^{-1}(\mathbf{y}_\tau - \mathbf{y}_{\tau-1 \to \tau})}{n_\tau}}\right) + \sum_{\tau=1}^{T} \mathcal{O}(\frac{1}{\sqrt{n_\tau}})$$

B.1.7. PROOF OF THE THEOREM 2

Proof

Using a union bound, we apply the generalisation bound simultanuously on $\mathcal{F}_{\mathbf{B}}$ for all $B \in \mathcal{N}$, with probability $1 - \delta/3$ we have :

$$\sup_{f \in \mathcal{F}_{\mathbf{B}}} \{L_D(f) - L_S(f)\} \le 2\rho\hat{\mathcal{R}}(\mathcal{F}_{\mathbf{B}}) + 3c\sqrt{\frac{\log(2/\delta)}{2n}} \quad \forall \mathbf{B} \in \mathcal{N}$$

$$\mathcal{L}_{D_\tau}(f_T^\star) \le \mathcal{L}_{S_\tau}(f_T^\star) + 2\rho\hat{\mathcal{R}}(\mathcal{F}_{\mathbf{B}_T}) + 3c\sqrt{\frac{\log(2/\delta)}{2n_T}}$$

$$\mathcal{L}_{D_\tau}(f_T^\star) \le \mathcal{L}_{S_\tau}(f_T^\star) + \sum_{\tau=1}^{T} \mathcal{O}\left(\sqrt{\frac{\tilde{\mathbf{y}}_\tau^T (k_\tau(\mathbf{X}_\tau, \mathbf{X}_\tau) + \lambda^2 \mathbf{I})^{-1} \tilde{\mathbf{y}}_\tau}{n_\tau}}\right) + \sum_{k=1}^{T} \mathcal{O}(\frac{1}{\sqrt{n_k}}) + 3c\sqrt{\frac{\log(2/\delta)}{2n_\tau}}$$

We get Theorem 2 by replacing into $\mathcal{L}_{S_\tau}(f_T^\star)$ using the inequalities from Lemma 6

C. Missing proofs of section 5 - OGD+ : Learning without forgetting

C.1. Memorisation property of OGD+ - Proof

Proof

In the proof of Theorem 1, App. A.1, we show that, for $\mathcal{T}_\tau$ a fixed task:

$$f^\star_{\tau+1}(\mathbf{x}) = f^\star_\tau(\mathbf{x}) + \langle \nabla_{\mathbf{w}} f^\star_\tau(\mathbf{x}), \mathbf{w}^\star_{\tau+1} - \mathbf{w}^\star_\tau \rangle.$$

We rewrite the recursive relation into a sum:

$$f^\star_{\tau+1}(\mathbf{x}) = \sum_{k=1}^{\tau} \langle \nabla_{\mathbf{w}} f^\star_k(\mathbf{x}), \mathbf{w}^\star_{k+1} - \mathbf{w}^\star_k \rangle.$$

We observe that, for all $k \in [T]$:

$$\mathbf{w}^\star_{k+1} - \mathbf{w}^\star_k \in \mathbb{E}_{k'}.$$

On the other hand, for OGD+, given a sample $\mathbf{x}$ from $\mathcal{D}_\tau$, for all $k' \in [\tau+1, T]$:

$$\nabla_{\mathbf{w}} f^\star_k(\mathbf{x}) \in \mathbb{E}_{k'}$$

Therefore, for all $k' \in [k+1, \tau]$:

$$\langle \nabla_{\mathbf{w}} f^\star_k(\mathbf{x}), \mathbf{w}^\star_{k+1} - \mathbf{w}^\star_k \rangle = 0$$

Therefore :

$$f^\star_\tau(\mathbf{x}) = f^\star_k(\mathbf{x})$$

We conclude.

C.2. OGD+ Generalisation Theorem - Proof

Proof

The proof is very similar to the proof of Theorem 2.

Let $\mathcal{T}_\tau$ a given task and $T \in \mathbb{N}^\star$ fixed

We start from the following result in Appendix B.1.

$$\mathcal{L}_{D_\tau}(f^\star_T) \le \mathcal{L}_{S_\tau}(f^\star_T) + \sum_{k=1}^{T} \mathcal{O}\left(\sqrt{\frac{\tilde{\mathbf{y}}^T_k (k_k(\mathbf{X}_k, \mathbf{X}_k) + \lambda^2 \mathbf{I})^{-1} \tilde{\mathbf{y}}_k}{n_k}} \right) + \sum_{k=1}^{T} \mathcal{O}(\frac{1}{\sqrt{n_k}}) + 3c\sqrt{\frac{\log(2/\delta)}{2n_\tau}}$$

We apply Lemma 3 for tasks $\mathcal{T}_\tau$ and $\mathcal{T}_T$:

$$f^\star_T(\mathbf{x}_{\tau,i}) = f^\star_\tau(\mathbf{x}_{\tau,i}).$$

Therefore :

$$\mathcal{L}_{S_\tau}(f^\star_T) = \mathcal{L}_{S_\tau}(f^\star_\tau)$$

We replace into the first inequality :

$$\mathcal{L}_{D_\tau}(f_T^\star) \leq \mathcal{L}_{S_\tau}(f_\tau^\star) + \sum_{k=1}^{T} \mathcal{O}\left(\sqrt{\frac{\tilde{\mathbf{y}}_k^T (k_k(\mathbf{X}_k, \mathbf{X}_k) + \lambda^2 \mathbf{I})^{-1} \tilde{\mathbf{y}}_k}{n_k}}\right) + \sum_{k=1}^{T} \mathcal{O}(\frac{1}{\sqrt{n_k}}) + 3c\sqrt{\frac{\log(2/\delta)}{2n_\tau}}$$

We recall the folowwing result from the proof of Theorem 2 in App. B.1

$$\frac{1}{n_\tau} \sum_{i=1}^{n_\tau} (f_\tau^\star(\mathbf{x}_{\tau,i}) - y_{\tau,i})^2 \leq \frac{1}{n_\tau} \frac{\lambda^2}{4} \tilde{\mathbf{y}}_\tau^\tau (k_\tau(\mathbf{X}_\tau, \mathbf{X}_\tau))^{-1} \tilde{\mathbf{y}}_\tau$$

By replacing into the previous inequality, we prove Theorem 3

D. Experiments :

D.1. Reproducibility

D.1.1. HYPERPARAMETERS

We use the same architecture and mostly the same hyperparameters as (Farajtabar et al., 2019). We also keep a small learning rate, in order to preserve the locality assumption of OGD, and in order to verify the conditions of the theorems.

The neural network is a three-layer MLP with 100 hidden units in two layers, each layer uses RELU activation function. The model has 10 logit outputs, which do not use any activation function. The optimiser is either SGD or OGD and the loss is Softmax cross-entropy. We report the hyperparameters in detail in Table 1.

Hyperparameter	Value
Learning rate	1e-02
Batch size	256
Epochs	5
Torch seeds	0 to 4
Memory size	1000
Activation	RELU

Table 1. Hyperparameters used across experiments

D.1.2. EXPERIMENT SETUP

We run each experiment 5 times, the seeds set is the same across all experiments sets. We report the mean and std of the measurements. Test error is measured every 50 mini-batch interval.

D.2. Additional experiments

D.2.1. OGD+ GENERALISATION

Figure 2. Test accuracy on the permuted MNIST tasks for SGD, OGD and OGD+. 15 different permutations are used, and the model is trained to classify MNIST digits for 5 epochs for each permutation. The y-axis is truncated for clarity. We report only a subset of the tasks.