EA-HAS-Bench: Energy-aware Hyperparameter and Architecture Search Benchmark

Abstract

The energy consumption for training deep learning models is increasing at an alarming rate due to the growth of training data and model scale, resulting in a negative impact on carbon neutrality. Energy consumption is an especially pressing issue for AutoML algorithms because it usually requires repeatedly training large numbers of computationally intensive deep models to search for optimal configurations. This paper takes one of the most essential steps in developing energy-aware (EA) NAS methods, by providing a benchmark that makes EA-NAS research more reproducible and accessible. Specifically, we present the first large-scale energy-aware benchmark that allows studying AutoML methods to achieve better trade-offs between performance and search energy consumption, named EA-HAS-Bench. EA-HAS-Bench provides a large-scale architecture/hyperparameter joint search space, covering diversified configurations related to energy consumption. Furthermore, we propose a novel surrogate model specially designed for large joint search space, which proposes a Bézier curve-based model to predict learning curves with unlimited shape and length. Based on the proposed dataset, we new energy-aware AutoML method that arms existing AutoML algorithms to consider the search energy consumption, and our experiments show that the modified energy-aware AutoML methods achieve a better trade-off between energy consumption and model performance.

1 Introduction

As deep learning technology progresses rapidly, its alarming increased rate of energy consumption causes growing concerns (Schwartz et al., 2020; Li et al., 2021a; Strubell et al., 2019). Neural architecture search (NAS) (Elsken et al., 2019), hyperparameter optimization (HPO) (Feurer & Hutter, 2019) lifted the manual effort of neural architecture and hyperparameter tuning but require repeatedly training large numbers of computationally intensive deep models, leading to significant energy consumption and carbon emissions. For instance, training 10K models on CIFAR-10 (Krizhevsky et al., 2009) for 100 epochs consume about 500,000 kWh of energy power, which is equivalent to the annual electricity consumption of about 600 households in China.

As a result, it is essential to develop search energy cost aware (EA) AutoML methods, which are able to find models with good performance while minimising the overall energy consumption throughout the search process. However, existing NAS studies mainly focus on the resource cost of the searched deep model, such as parameter size, the number of float-point operations (FLOPS) or latency (Tan et al., 2019; Wu et al., 2019; He et al., 2021). Exploiting the trade-off between model performance and energy cost during the searching process has been rarely studied (Elsken et al., 2019). In this paper, we propose to take one of the most essential steps in developing energy-aware (EA) NAS methods that make EA-NAS research more reproducible and accessible. Specifically, we provide a benchmark for EA-NAS called Energy Aware Hyperparameter and Architecture Search Benchmark (EA-HAS-Bench), where the researchers can easily obtain the training energy cost and model performance of a certain architecture and hyperparameter configuration, without actually training the model.

In order to support developing energy-aware HPO and NAS methods, the proposed EA-HAS-Bench should satisfy three requirements.

Table 1: Overview of NAS benchmarks related to EA-HAS-Bench

	Benchmark	Size	Bench. Type	Arch. Type	LCs	Query
NAS	NAS-Bench-101	423k	Tab.	Cell		Accuracy
	NAS-Bench-201	6k	Tab.	Cell	✓	Accuracy & Loss
	NAS-Bench-301	10^{18}	Surr.	Cell		Accuracy
	NATS-Bench	32K	Tab.	Macro	✓	Accuracy & Loss
	HW-NAS-Bench	15K/10^{21}	Tab./Esti.	Cell		Latency & Inference Energy
		423k	Surr.	Cell	✓	Accuracy
	NAS-Bench-x11	6k	Surr.	Cell	✓	Accuracy & Loss
		10^{18}	Surr.	Cell	✓	Accuracy
NAS+ HPO	NAS-HPO-Bench	62K	Tab.	MLP	✓	Accuracy
	NAS-HPO-Bench-II	192K	Surr.	Cell		Accuracy
	EA-HAS-Bench (Ours)	3×10^{10}	Surr.	Macro	✓	Accuracy & Inference and Total Search Energy

Search Energy Cost Our dataset needs to provide the total search energy cost of running a specific AutoML method, which is the sum of the training energy cost of all the hyperparameter and architecture configurations the search method traverses. As shown in Table 1, most of the existing conventional benchmarks (Ying et al., 2019; Dong & Yang, 2020; Siems et al., 2020) like NAS-Bench-101 do not directly provide training energy cost but use model training time as the training resource budget, which as verified by our experiments, is an inaccurate estimation of energy cost. HW-NAS-bench (Li et al., 2021b) provides the inference latency and inference energy consumption of different model architectures, but also does not provide the search energy cost.

Energy Related Joint Search Space The search space of EA-HAS-Bench should include the configurations that affect both the model training energy cost and performance. Since both model architectures (e.g., scales, width, depth) and training hyperparameters (e.g., number of epochs) are correlated to the training energy cost, designing a joint hyperparameter and architecture search (HAS) search space is essential. Most NAS benchmarks use a single fixed training hyperparameter configuration for all architectures. Existing HAS benchmarks (Klein & Hutter, 2019; Hirose et al., 2021) use small toy search space which does not cover enough critical factors affecting the search energy cost. As a result, EA-HAS-Bench provides the first dataset with a ten-billion-level architecture/hyperparameter joint space, covering diverse types of configurations related to search energy cost.

Surrogate Model for Joint Search Space Due to the enormous size of the proposed joint search space, a surrogate model is needed to fill out the entire search space with a subset of sampled configurations. Existing surrogate methods (Zela et al., 2022; Yan et al., 2021) are not applicable to our proposed large scale joint space. For instance, those methods do not consider the situation of maximum epoch variation and predict only a fixed length learning curve or final performance. Thus, we propose the Bézier Curve-based Surrogate (BCS) model to fit accuracy learning curves of unlimited shape and length.

We summarize the contribution of this paper as follows:

- EE-HAS-Bench is the first HAS dataset aware of the overall search energy cost. [1]. Based on this dataset, we further propose a *energy-aware AutoML* method with search energy cost related penalties, showing energy-aware AutoML achieves a better trade-off between model performance and search energy cost.

- We provide the first large-scale benchmark containing an architecture / hyperparameter joint search space with over 10 billion configurations, covering various configurations related to search energy cost.

- We develop a novel surrogate model suitable for more general and complex joint HAS search space, which outperforms NAS-Bench-X11 and other parametric learning curve-based methods.

---

[1]The dataset of EA-HAS-Bench will be released after paper publication

Table 2: Overview of EA-HAS-Bench's search space

Type	Hyperparameter	Range	Quantize	Space
RegNet	Depth d	[6,15]	1	10
	w_0	[48, 128]	8	10
	w_a	[8,32]	0.1	241
	w_m	[2.5, 3]	0.001	501
	Group Width	[1, 32]	8	5
Total of Network Architectures				$\approx 6 \times 10^7$
Optima	Learning rate	{0.001, 0.003, 0.005, 0.01, 0.03, 0.05, 0.1, 0.3, 0.5, 1.0}	-	10
	Max epoch	{50, 100, 200}	-	3
	Decay policy	{'cos', 'exp', 'lin'}	-	3
	Optimizer	{'sgd', 'adam','adamw'}	-	3
Training	Data augmentation	{None,Cutout}	-	2
Total of Hyperparameter Space				540

2 CREATING ENERGY AWARE BENCHMARKS

2.1 EA-HAS-BENCH SEARCH SPACE

Unlike the search space of existing mainstream NAS-Bench that focuses only on network architectures, our EA-HAS-Bench consists of a combination of two parts: the network architecture space-RegNet (Radosavovic et al., 2020) and the hyperparameter space for optimization and training, in order to cover a diversified configurations that affect both performance and energy consumption. The details of the search space are shown in Table 2.

RegNet Search Space. Our benchmark applies RegNet as the architecture search space because it contains several essential factors that control the scale and shape of the deep model, which corresponds to the training energy cost. Specifically, RegNet is a macro search space with the variation in width and depth explained by a quantized linear function. Specifically, for widths of residual blocks: $u_j = w_0 + w_a \times j$, where $0 \leq j \leq d$ and d denotes the depth. An additional parameter w_m is introduced to quantize u_j, i.e. $u_j = w_0 \times w_m^{s_j}$ and the quantized per-block widths w_j is computed by

$$w_j = w_0 \times w_m^{\lfloor s_j \rceil} \tag{1}$$

where $\lfloor s_j \rceil$ denotes round s_j. For different datasets (i.e., CIFAR-10 and TinyImageNet), we adjust this space accordingly via constraining parameters and FLOPs.

Training hyperparameter Search Space. Hyperparameter space (e.g., learning rate and maximum epoch) also has a great impact on energy consumption throughout the training phase. For example, training epochs is almost proportional to training time, which is also proportional to training energy cost. Different learning rate also causes different convergence rate and different total training time, resulting in different training energy cost. Thus, for hyperparameter search space, EA-HAS-Bench considers training epochs, and the most important factors in training schemes, i.e., base learning rate, decay policy of learning rate, optimizer and data augmentation.

As a result, the search space of EA-HAS-Bench contains a total of 3.26×10^{10} configurations, including 6×10^7 architectures and 540 training hyperparameter settings with variant training epochs.

2.2 EVALUATION METRICS

The EA-HAS-Bench dataset provides the following three types of metrics to evaluate different configurations.

Model Complexity. Metrics related to model complexity include parameter size, FLOPs, number of network activations (the size of the output tensors of each convolutional layer), as well as the inference energy cost of the trained model.

Figure 1: Overview of Bézier Curve-based Surrogate Model. HC denotes Hyperparameter configuration.

Model Performance. In order to support multi-fidelity NAS algorithms such as Hyperband (Li et al., 2017), EA-HAS-Bench provides the full training information including training and test accuracy learning curves for each hyperparameter and architecture configuration.

Search Cost. Firstly, the energy cost (in kWh) and time (in seconds) to train a model under a certain configuration for one epoch are obtained. Then, by accumulating the energy consumption and runtime at each epoch, we obtain the total search cost of a configuration, which allows NAS/HPO methods to search optimal models under a limited cost budget.

2.3 BÉZIER CURVE-BASED SURROGATE MODEL

Due to the large EA-HAS-Bench search space, directly training all configurations in the space is infeasible even for a small dataset like CIFAR10. As a result, some of the metrics can not be directly measured, including model performance curve, search energy cost and runtime. Thus, similar to other recent works (Zela et al., 2022; Yan et al., 2021), we develop a surrogate model that expands the entire search space from a sampled subset of configurations.

As for energy cost and training time, we follow the Surrogate NAS Benchmark (Zela et al., 2022) and train LGB models to predict these. However, for learning curve prediction, surrogate models proposed by the existing NAS-Bench are not applicable to EA-HAS-Bench. Since EA-HAS-Bench contains various maximum training epochs in the search space, non of the existing surrogate model can cope with dimensionally varying inputs and performs a dimensionality reduction operation on the learning curve. More importantly, it is not possible to directly constrain the learning curve after using the dimensionality reduction operation (e.g., the error rate should be between 0 and 1). In our early experiments, using the hyperparameter optimization algorithm on the NAS-Bench-X11 surrogate model would yield results with more than 100% accuracy. To design a surrogate model that is specially designed for EA-HAS-Bench search space, we propose a Bézier Curved-based Surrogate (BCS) Model to achieve learning curve prediction for arbitrary maximum epoch and direct constraint on final performance.

Convert Learning Curve to Bézier Curve Control Points. For each configuration of network architecture and training hyperparameters, the surrogate model outputs the learning curve containing the accuracy or error rate of each epoch. Previous methods are not very efficient and robust for predicting learning curves with arbitrary lengths. Inspired by the success of the Bézier curve in other areas (Liu et al., 2020), we choose the Bézier curve to fit learning curves of arbitrary length. The shape of a Bézier curve is entirely determined by its control points, and degree n control points correspond to a Bézier curve of order $n-1$. The Bézier curve can be formulated in a recursive way as follows:

$$P(t) = \sum_{i=0}^{n} P_i B_{i,n}(t), t \in [0, 1] \tag{2}$$

where P_i denotes control points, $B_{i,n}(t) = C_n^i t^i (1-t)^{n-i}$ and $i = 0, 1, \cdots, n$.

As a result, the task of regressing a learning curve of arbitrary length is simplified to predicting Bézier curve control points. Given a learning curve, $\{e_{x_i}, e_{y_i}\}_{i=1}^{m}$ where e_y is the error of the e_xth

epoch and m is the maximum epoch, we need to get the optimal control points to generate Quartic Bézier curves to fit the learning curve. The control points are learned with the standard least square method as follows:

$$
\begin{bmatrix}
B_{0,5}(t_0) & \cdots & B_{5,5}(t_0) \\
B_{0,5}(t_1) & \cdots & B_{5,5}(t_1) \\
\vdots & \ddots & \vdots \\
B_{0,5}(t_m) & \cdots & B_{5,5}(t_m)
\end{bmatrix}
\begin{bmatrix}
i_{x_{start}} & i_{y_{start}} \\
c_{x_1} & c_{y_1} \\
\vdots & \vdots \\
i_{x_{end}} & i_{y_{end}}
\end{bmatrix}
=
\begin{bmatrix}
e_{x_0} & e_{y_0} \\
e_{x_1} & e_{y_1} \\
\vdots & \vdots \\
e_{x_m} & e_{y_m}
\end{bmatrix}
\tag{3}
$$

Note that since the horizontal coordinates of the start and end points of the learning curve are fixed (i.e., $i_{x_{start}} = 1$ and $i_{x_{end}} =$ maximum epoch), the surrogate model only predicts the vertical coordinates of these two control points. An illustration of generated Bézier curves is shown in Figure 8 in Appendix B.3.

Surrogate Model Structure. Given a RegNet architecture and hyperparameter configurations, BCS estimates the Bézier curve control points with a neural network. As shown in Fig.1, the proposed Bézier curve-based Surrogate model is composed of a hyperparameter encoder E_h, architecture encoder E_a, and learning curve prediction network f. The training hyperparameter configurations are represented as one-hot vector v_h and then fed into E_h. The RegNet configuration parameters are normalized to values between 0 and 1, concatenated to a vector and fed into E_a. Finally, the hyperparameter representation and architecture representation are fed into the learning curve predictor to estimate Bézier curve starting/ending points and control points:

$$
\{i_{y_{start}}, i_{y_{end}}, c_{x_1}, c_{y_1}, \cdots, c_{x_3}, c_{y_3}\} = f(E_a(v_a), E_h(v_h))
\tag{4}
$$

The learning curve predictor consists of two branches. One predicts the vertical coordinates of the starting and ending points of the Bézier curve, and the other branch predicts the other control points. With the control points obtained, we can generate Bézier curves with equation (2), and then obtain the accuracy of each epoch based on the horizontal coordinates e_{x_i} of the curve.

2.4 DATASET COLLECTION

Some previous works (Eggensperger et al., 2015) propose to sample more training data from the high-performance regions of the search space because an effective optimizer spends most of its time in high-performance regions of the search space. However, this sampling strategy causes a distribution shift between the sampled training data and the actual search space, which hurts the prediction accuracy of the surrogate model. As discussed and verified in recent work (Zela et al., 2022), a search space containing hyper-parameters is more likely to produce dysfunctional models which are rarely covered in a sampled sub-set focusing on high-performance regions, and hence purely random sampled training data yields more satisfactory performance. In summary, for EA-HAS-Bench's search space that contains both model architectures and hyperparameters, we use random search (RS) to sample unbiased data to build a robust surrogate benchmark.

The sampled architecture and hyperparameter configurations are trained and evaluated on two of the most popular image classification datasets, namely CIFAR-10 (Krizhevsky et al., 2009) and MicroImageNet challenge's (Tiny ImageNet) dataset (Le & Yang, 2015).

2.5 SURROGATE BENCHMARK EVALUATION

Comparison Methods. We compare the proposed method with six parametric learning curve based model (Domhan et al., 2015) (Exp$_3$, ilog$_2$, pow$_2$, log power, log linear, vapor pressure) and three surrogate models (SVD-XGB, SVD-LGB, SVD-MLP) from NAS-Bench-X11 Yan et al. (2021). For a fair comparison, the parametric learning curve-based model applies the same network structure as our proposed BCS. For NAS-Bench-X11, we compress learning curves of different lengths (50, 100, and 200 epochs) into the hidden space with the same dimension with three different SVDs respectively (although this is not convenient to cope with learning curves of arbitrary length). Tree-of-Parzen-Estimators (TPE) (Bergstra et al., 2011) is adopted for BCS to search for the best hyperparameter configuration. The details of the experiments and ablation study are in Appendix B.

Table 3: Compare Bézier-based Surrogate model with NAS-Bench-X11 and parametric learning curve model on CIFAR-10 and TinyImageNet.

Methods	CIFAR10				TinyImageNet			
	Avg.R2	Final R2	Avg.KT	Final KT	Avg.R2	Final R2	Avg.KT	Final KT
Parametric learning curve neural network (Domhan et al., 2015)								
exp3	0.397	0.791	0.769	0.789	-1.128	0.935	0.807	0.849
ilog2	0.799	0.830	0.820	0.830	0.297	0.978	0.879	0.915
pow2	0.212	-0.056	0.564	0.506	0.321	0.396	0.571	0.547
log power	0.195	0.583	0.544	0.519	-1.933	0.872	0.807	0.873
logx linear	0.808	0.825	0.810	0.793	0.779	0.969	0.893	0.906
vapor	0.790	0.671	0.830	0.829	0.897	0.957	0.858	0.883
NAS-Bench-X11 (Yan et al., 2021)								
SVD-XGB	0.762	0.731	0.827	0.836	0.890	0.897	0.848	0.862
SVD-LGB	0.838	0.850	0.787	0.795	0.967	0.976	0.899	0.908
SVD-MLP	0.869	0.835	0.859	0.852	0.967	0.972	0.913	0.919
BCS(Ours)	**0.892**	**0.872**	0.860	0.841	0.968	**0.979**	0.922	0.928
GT (1 seed)	0.857	0.821	**0.928**	**0.931**	**0.979**	0.975	**0.961**	**0.962**

Testing Set. The proposed surrogate model and the comparison methods are evaluated on a separate testing set trained on two sets of random seeds. The sampled configurations on CIFAR10 and TinyImageNet are split into training, validation and testing sets containing 11597, 1288, and 1000 samples respectively.

Evaluation Metrics. Following Wen et al. (2020), White et al. (2021b) and Zela et al. (2022), we use the coefficient of determination R^2 and the Kendall rank correlation coefficient τ as the evaluation metrics. Since the prediction results may have anomalies that make the prediction performance much higher than the actual results, we introduce spike anomalies (Yan et al., 2021) to evaluate these anomalies.

Evaluation Results. The performance of surrogate models is shown in Table 3. First, the parametric learning curve-based models do not perform well, because the parametric learning curve function does not well fit the real learning curve in EA-HAS-Bench, some of the higher order functions even fail to fit, such as pow_3 $(c - ax^{-\alpha})$ and pow_4 $(c - (ax + b)^{-\alpha})$. On the other hand, the importance of the different parameters varies considerably, especially exponentially. We also show that the percentage of spike anomalies for real vs. BCS is 3.72% and 4.68% on CIFAR-10 and 0.83% and 1.31% on TinyImageNet, respectively. The energy cost surrogate models achieve 0.787 for R2 and 0.686 for KT on CIFAR-10 and 0.959 for R2 and 0.872 for KT on TinyImageNet.

3 DIFFERENCE WITH EXISTING NAS BENCHMARKS

Compared with existing NAS benchmarks such as NAS-Bench-101 (Ying et al., 2019), NAS-Bench-201 (Dong & Yang, 2020), NAS-Bench-301 (Dong & Yang, 2020) or Surrogate NAS Bench (Zela et al., 2022), EA-HAS-Bench has three significant differences.

Diverse and Large Scale Joint Search Space. EA-HAS-Bench is more diverse in terms of the types of configurations in the search space, which contains both model architectures and training hyperparameters. Although NAS-HPO-Bench (Klein & Hutter, 2019) and NAS-HPO-Bench-II (Hirose et al., 2021) also consider both architectures and hyperparameters, both benchmarks are based on small and homogeneous search spaces. Specifically, NAS-HPO-Bench focuses only on 2-layer feed-forward network training on tabular data, and the hyperparameters search space of NAS-HPO-Bench-II only contains learning rate and batch size. Besides the search space, diversity is also reflected in the evaluated performance ranges. As shown in Figure 2, the performance range of DARTS (Liu et al., 2019) used by NAS-Bench-301 is the smallest for the validation performance on CIFAR-10. Although DARTS contains more architectures, the performance of the models in this space is significantly less diverse (Yang et al., 2020). Compared with NAS-Bench-101/201, the configurations in EA-HAS-Bench cover a much larger performance range.

Figure 3: The empirical cumulative distribution (ECDF) of all real measured configurations on CIFAR-10 and TinyImageNet for 5 different splits.

Modeling Learning Curves for complex joint space. To the best of our knowledge, NAS-Bench-X11 (Yan et al., 2021) is the only existing surrogate model that provides the full training status over the entire training process. However, NAS-Bench-X11 is only available for learning curves with fixed maximum epochs. The number of training epochs required for convergence is not always the same for different architectures and it also directly affects the training energy cost. As a result, for a more realistic search space like EA-HAS-Bench, we propose BSC to predict learning curves with different maximum epochs.

Figure 2: Validation accuracy box plots for each NAS benchmark in CIFAR-10. The whiskers represent the minimum and maximum accuracies in each search space. The black hollow circles represent outliers

Full-cycle Energy Consumption. Most existing benchmarks use model training time as the training resource budget, which is not an accurate estimation of energy cost. Firstly, the GPU does not function at a stable level throughout the entire training process, or it may not even be working at all for a significant time period during training, and hence longer training time does not always mean more GPU usage and more energy cost. Secondly, energy cost not only corresponds to training time but also relates to the energy cost per unit time, which is affected by the architecture and hyperparameter configurations. Our experimental analysis in the next section also verifies that training time and energy cost are not equivalent. HW-NAS-Bench (Li et al., 2021b) also consider energy consumption, but its focus is on the model inference energy cost. On the other hand, EA-HAS-Bench provides a full-cycle energy consumption, both during training and inference. The energy consumption metric allows HPO algorithms to optimize for accuracy under an energy cost limit (Section 5).

4 ANALYSIS ON EA-HAS-BENCH

Impact of Hyperparameter Configurations. Since most existing large-scale computer vision NAS benchmarks focus solely on network architectures and apply the same hyperparameters for all models, we examine how different hyperparameters affect the searched model performance. We use a *empirical cumulative distribution* (ECDF) (Radosavovic et al., 2020) to assess the quality of search space. Specifically, we take a set of configurations from the search space and characterize its error distribution. Figure 3 shows the empirical cumulative distribution (ECDF) of different training hyperparameters on CIFAR-10 and TinyImageNet. We observe that the learning rate and the choice of optimizer may have the most significant impact on the search space quality. The size of the maximum number of epochs is almost proportional to the quality of the search space and increases the search cost linearly. In addition, through investigation of data augmentation, we found that cutout achieves opposite effects on different datasets.

Figure 4: **(left)** Training time vs. training energy consumption (TEC), colour-coded by test accuracy. **(middle)** Test Accuracy vs. TEC. **(right)** Test Accuracy vs. training time. TEC and training time are the GPU consumption (Kw*h) and runtime (seconds) of the model per epoch on the Tesla V100.

Correlation Between Training Energy Cost and Training time. Figure 4 investigates the relationship between the training energy consumption (TEC), training time and the test accuracy of models in TinyImageNet. Firstly, we observe that the points in the left figure of Figure 4 is rather scattered. This means *the correlation between training time and energy cost is not strong.* Although training the model for a longer period is likely to yield a higher energy cost, the final cost still depends on many other factors including power (i.e., consumed energy per hour). The middle and right plots of Figure 4 also verifies the conclusion, where the models in the Pareto Frontier on the accuracy-runtime coordinate (right figure) are not always in the Pareto Frontier on the accuracy-TEC coordinate (middle figure), showing that training time and energy cost are not equivalent.

Meanwhile, training a model longer (or with more energy) does not guarantee better accuracy. In the middle and right plots of Figure 4, we see that many models with high TECs, still fail to train, due to improper neural architectures or hyperparameter configurations. On the other hand, simply searching for the best accuracy might not be cost-efficient, since there are quite a few configurations with the same level of accuracy. The observation motivates finding the best trade-off between accuracy and energy consumption.

Figure 5: Correlation coefficient between RegNet+ HPO and Accuracy and TEC on TinyImageNet.

Configurations–Accuracy/Energy Correlation. Figure 5 shows the correlation between architecture/ hyperparameter configurations and accuracy/energy cost. We observe that hyperparameters like learning rate also have a high correlation with model performance, which further verifies the importance to consider hyperparameters in NASBench. Both network architecture like network depth and width and hyperparameter like training epoch have a relatively strong correlation with energy cost, showing the importance of considering both perspectives in our energy-aware Benchmark.

5 EA-HAS-BENCH AS A BENCHMARK

EA-HAS-Bench saves tremendous resources to train and evaluate the configurations for real. We demonstrate how to leverage the proposed dataset to conduct energy-aware AutoML research with two use cases. Firstly, we evaluate the trade-off between search energy cost and model performance of some of the existing AutoML methods (Li et al., 2017; White et al., 2021a; 2020; Falkner et al., 2018; Li & Talwalkar, 2019; Real et al., 2019) with the proposed EA-HAS-Bench dataset. Then, in the second sub-section, as the first step toward a long journey of energy-aware AutoML, we arm several existing AutoML algorithms with another energy-related objective and verify the effectiveness of energy-aware AutoML on our hyperparameter-architecture benchmark.

Figure 6: NAS results on CIFAR10 **(left)** and TinyImageNet **(middle)**. Energy-aware BANANAS and vs. origin BANANAS and LS on CIFAR10 **(right)**.

5.1 BENCHMARKING EXISTING ALGORITHMS

Experimental setup. Since EA-HAS-Bench focuses on the trade-off between model performance and search energy cost, in this experiment we use the total search energy cost as the resource limitation, instead of training time. As a result, we set the maximum search cost to roughly 40,000 kWh for CIFAR 10 and 250,000kWh for TinyImageNet, which is equivalent to running a single-fidelity HPO algorithm for about 1,000 iterations.

Results. In Figure 6 left and middle, we compare single- and multi-fidelity algorithms on the search space of EA-HAS-Bench. For single-fidelity algorithms, LS is the top-performing algorithm across two datasets. This shows that similar to NAS-Bench, HAS-Bench with a joint search space also has locality, a property by which "close" points in search space tend to have similar performance.

5.2 A NEW ENERGY-AWARE HPO BASELINE

Energy Aware HPO Most existing HPO methods do not directly consider the search energy cost. In order to verify the importance to consider the energy cost during the search process, we propose a new energy-aware HPO baseline by modifying existing HPO methods. Specifically, we modify the BANANAS (White et al., 2021a) and LS (White et al., 2020) by changing the optimization goal to a metric that considers both accuracy and energy cost: $ACC \times \left(\frac{TEC}{T}\right)^w$, where T is the target TEC. For CIFAR10, we set the T to 0.45 and w to -0.07.

Experimental Setup and Result We explore another important usage scenario, where the goal is to achieve a target model performance using as little energy cost as possible. As a result, we use model performance rather than energy consumption as a resource limitation, and stop the search when the model hits a target performance and compare the corresponding search energy cost. For CIFAR10, the target accuracy is set to 97%. As shown in Figure 6 right, EA algorithms that consider TEC save close to 20% of search energy consumption compared to the origin algorithms in achieving the target accuracy.

6 CONCLUSION

EA-HAS-Bench is the first large-scale energy-aware hyperparameter and architecture search benchmark. The search space of EA-HAS-Bench consists of both network architecture scale and training hyperparameters, covering diverse configurations related to energy cost. A novel Bézier curve-based surrogate model is proposed for the new joint search space. Furthermore, we analyse the difference between existing NAS benchmarks and EA-HAS-Bench and dataset statistics and correlation of the collected data. Finally, we provide use cases of EA-HAS-Bench to show that energy-aware algorithms can save significant energy in the search process. We expect that our EA-HAS-Bench expedites and facilitates the EA-NAS and HAS research innovations.

REFERENCES

James Bergstra, Rémi Bardenet, Yoshua Bengio, and Balázs Kégl. Algorithms for hyper-parameter optimization. In *Advances in Neural Information Processing Systems 24: 25th Annual Conference on Neural Information Processing Systems 2011. Proceedings of a meeting held 12-14 December 2011, Granada, Spain*, pp. 2546–2554, 2011.

Tobias Domhan, Jost Tobias Springenberg, and Frank Hutter. Speeding up automatic hyperparameter optimization of deep neural networks by extrapolation of learning curves. In *Proceedings of the Twenty-Fourth International Joint Conference on Artificial Intelligence, IJCAI 2015, Buenos Aires, Argentina, July 25-31, 2015*, pp. 3460–3468. AAAI Press, 2015.

Xuanyi Dong and Yi Yang. Nas-bench-201: Extending the scope of reproducible neural architecture search. In *8th International Conference on Learning Representations, ICLR 2020, Addis Ababa, Ethiopia, April 26-30, 2020*. OpenReview.net, 2020. URL `https://openreview.net/forum?id=HJxyZkBKDr`.

Xuanyi Dong, Mingxing Tan, Adams Wei Yu, Daiyi Peng, Bogdan Gabrys, and Quoc V Le. Auto-has: Efficient hyperparameter and architecture search. *arXiv preprint arXiv:2006.03656*, 2020.

Katharina Eggensperger, Frank Hutter, Holger H. Hoos, and Kevin Leyton-Brown. Efficient benchmarking of hyperparameter optimizers via surrogates. In Blai Bonet and Sven Koenig (eds.), *Proceedings of the Twenty-Ninth AAAI Conference on Artificial Intelligence, January 25-30, 2015, Austin, Texas, USA*, pp. 1114–1120. AAAI Press, 2015.

Thomas Elsken, Jan Hendrik Metzen, and Frank Hutter. Neural architecture search: A survey. *J. Mach. Learn. Res.*, 20:55:1–55:21, 2019.

Stefan Falkner, Aaron Klein, and Frank Hutter. BOHB: robust and efficient hyperparameter optimization at scale. In *Proceedings of the 35th International Conference on Machine Learning, ICML*, volume 80 of *Proceedings of Machine Learning Research*, pp. 1436–1445. PMLR, 2018.

Matthias Feurer and Frank Hutter. Hyperparameter optimization. In *Automated machine learning*, pp. 3–33. Springer, Cham, 2019.

Xin He, Kaiyong Zhao, and Xiaowen Chu. Automl: A survey of the state-of-the-art. *Knowledge-Based Systems*, 212:106622, 2021.

Yoichi Hirose, Nozomu Yoshinari, and Shinichi Shirakawa. Nas-hpo-bench-ii: A benchmark dataset on joint optimization of convolutional neural network architecture and training hyperparameters. In Vineeth N. Balasubramanian and Ivor W. Tsang (eds.), *Asian Conference on Machine Learning, ACML 2021, 17-19 November 2021, Virtual Event*, volume 157 of *Proceedings of Machine Learning Research*, pp. 1349–1364. PMLR, 2021.

Aaron Klein and Frank Hutter. Tabular benchmarks for joint architecture and hyperparameter optimization. *CoRR*, abs/1905.04970, 2019. URL `http://arxiv.org/abs/1905.04970`.

Alex Krizhevsky, Geoffrey Hinton, et al. Learning multiple layers of features from tiny images. 2009.

Ya Le and Xuan Yang. Tiny imagenet visual recognition challenge. *CS 231N*, 7(7):3, 2015.

Bo Li, Xinyang Jiang, Donglin Bai, Yuge Zhang, Ningxin Zheng, Xuanyi Dong, Lu Liu, Yuqing Yang, and Dongsheng Li. Full-cycle energy consumption benchmark for low-carbon computer vision. *CoRR*, abs/2108.13465, 2021a.

Chaojian Li, Zhongzhi Yu, Yonggan Fu, Yonan Zhang, Yang Zhao, Haoran You, Qixuan Yu, Yue Wang, Cong Hao, and Yingyan Lin. Hw-nas-bench: Hardware-aware neural architecture search benchmark. In *9th International Conference on Learning Representations, ICLR 2021, Virtual Event, Austria, May 3-7, 2021*. OpenReview.net, 2021b.

Liam Li and Ameet Talwalkar. Random search and reproducibility for neural architecture search. In *Proceedings of the Thirty-Fifth Conference on Uncertainty in Artificial Intelligence, UAI 2019, Tel Aviv, Israel, July 22-25, 2019*, volume 115 of *Proceedings of Machine Learning Research*, pp. 367–377. AUAI Press, 2019.

Lisha Li, Kevin G. Jamieson, Giulia DeSalvo, Afshin Rostamizadeh, and Ameet Talwalkar. Hyperband: A novel bandit-based approach to hyperparameter optimization. *J. Mach. Learn. Res.*, 18: 185:1–185:52, 2017.

Hanxiao Liu, Karen Simonyan, and Yiming Yang. DARTS: differentiable architecture search. In *7th International Conference on Learning Representations, ICLR 2019, New Orleans, LA, USA, May 6-9, 2019*. OpenReview.net, 2019.

Yuliang Liu, Hao Chen, Chunhua Shen, Tong He, Lianwen Jin, and Liangwei Wang. Abcnet: Real-time scene text spotting with adaptive bezier-curve network. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition, CVPR*, pp. 9806–9815, 2020.

Yash Mehta, Colin White, Arber Zela, Arjun Krishnakumar, Guri Zabergja, Shakiba Moradian, Mahmoud Safari, Kaicheng Yu, and Frank Hutter. Nas-bench-suite: NAS evaluation is (now) surprisingly easy. In *The Tenth International Conference on Learning Representations, ICLR , Virtual Event*. OpenReview.net, 2022.

Hieu Pham, Melody Y. Guan, Barret Zoph, Quoc V. Le, and Jeff Dean. Efficient neural architecture search via parameter sharing. In Jennifer G. Dy and Andreas Krause (eds.), *Proceedings of the 35th International Conference on Machine Learning, ICML 2018, Stockholmsmässan, Stockholm, Sweden, July 10-15, 2018*, volume 80 of *Proceedings of Machine Learning Research*, pp. 4092–4101. PMLR, 2018.

Ilija Radosavovic, Raj Prateek Kosaraju, Ross B. Girshick, Kaiming He, and Piotr Dollár. Designing network design spaces. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 10425–10433, 2020.

Esteban Real, Alok Aggarwal, Yanping Huang, and Quoc V. Le. Regularized evolution for image classifier architecture search. In *The Thirty-Third AAAI Conference on Artificial Intelligence, AAAI*, pp. 4780–4789. AAAI Press, 2019.

Michael Ruchte, Arber Zela, Julien Niklas Siems, Josif Grabocka, and Frank Hutter. Naslib: a modular and flexible neural architecture search library. 2020.

Roy Schwartz, Jesse Dodge, Noah A Smith, and Oren Etzioni. Green ai. *Communications of the ACM*, 63(12):54–63, 2020.

Julien Siems, Lucas Zimmer, Arber Zela, Jovita Lukasik, Margret Keuper, and Frank Hutter. Nas-bench-301 and the case for surrogate benchmarks for neural architecture search. *arXiv preprint arXiv:2008.09777*, 2020.

David R. So, Quoc V. Le, and Chen Liang. The evolved transformer. In *Proceedings of the 36th International Conference on Machine Learning, ICML 2019, 9-15 June 2019, Long Beach, California, USA*, volume 97 of *Proceedings of Machine Learning Research*, pp. 5877–5886. PMLR, 2019.

Emma Strubell, Ananya Ganesh, and Andrew McCallum. Energy and policy considerations for deep learning in nlp. *arXiv preprint arXiv:1906.02243*, 2019.

Mingxing Tan, Bo Chen, Ruoming Pang, Vijay Vasudevan, Mark Sandler, Andrew Howard, and Quoc V Le. Mnasnet: Platform-aware neural architecture search for mobile. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 2820–2828, 2019.

Wei Wen, Hanxiao Liu, Yiran Chen, Hai Helen Li, Gabriel Bender, and Pieter-Jan Kindermans. Neural predictor for neural architecture search. In *Computer Vision - ECCV 2020 - 16th European Conference, Glasgow, UK, August 23-28, 2020, Proceedings, Part XXIX*, volume 12374 of *Lecture Notes in Computer Science*, pp. 660–676. Springer, 2020.

Colin White, Sam Nolen, and Yash Savani. Local search is state of the art for NAS benchmarks. *CoRR*, abs/2005.02960, 2020.

Colin White, Willie Neiswanger, and Yash Savani. BANANAS: bayesian optimization with neural architectures for neural architecture search. In *Thirty-Fifth AAAI Conference on Artificial Intelligence, AAAI 2021, Thirty-Third Conference on Innovative Applications of Artificial Intelligence, IAAI 2021, The Eleventh Symposium on Educational Advances in Artificial Intelligence, EAAI 2021, Virtual Event, February 2-9, 2021*, pp. 10293–10301. AAAI Press, 2021a.

Colin White, Arber Zela, Robin Ru, Yang Liu, and Frank Hutter. How powerful are performance predictors in neural architecture search? In *Advances in Neural Information Processing Systems 34: Annual Conference on Neural Information Processing Systems 2021, NeurIPS 2021, December 6-14, 2021, virtual*, pp. 28454–28469, 2021b.

Bichen Wu, Xiaoliang Dai, Peizhao Zhang, Yanghan Wang, Fei Sun, Yiming Wu, Yuandong Tian, Peter Vajda, Yangqing Jia, and Kurt Keutzer. Fbnet: Hardware-aware efficient convnet design via differentiable neural architecture search. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 10734–10742, 2019.

Shen Yan, Colin White, Yash Savani, and Frank Hutter. Nas-bench-x11 and the power of learning curves. In *Advances in Neural Information Processing Systems 34: Annual Conference on Neural Information Processing Systems*, pp. 22534–22549, 2021.

Antoine Yang, Pedro M. Esperança, and Fabio Maria Carlucci. NAS evaluation is frustratingly hard. In *8th International Conference on Learning Representations, ICLR 2020, Addis Ababa, Ethiopia, April 26-30, 2020*. OpenReview.net, 2020.

Chris Ying, Aaron Klein, Eric Christiansen, Esteban Real, Kevin Murphy, and Frank Hutter. Nas-bench-101: Towards reproducible neural architecture search. In *Proceedings of the 36th International Conference on Machine Learning, ICML 2019, 9-15 June 2019, Long Beach, California, USA*, volume 97 of *Proceedings of Machine Learning Research*, pp. 7105–7114. PMLR, 2019.

Arber Zela, Julien Niklas Siems, Lucas Zimmer, Jovita Lukasik, Margret Keuper, and Frank Hutter. Surrogate nas benchmarks: Going beyond the limited search spaces of tabular nas benchmarks. In *International Conference on Learning Representations*, 2022.

Barret Zoph and Quoc V Le. Neural architecture search with reinforcement learning. *arXiv preprint arXiv:1611.01578*, 2016.

A RELATED WORK

A.1 EXISTING NAS BENCHMARKS

Tabular NAS Benchmarks. While neural architecture search (NAS) has succeeded in various practical tasks such as image recognition (Pham et al., 2018) and sequence modelling (So et al., 2019), the non-reproducibility of NAS has been contested (Li & Talwalkar, 2019). One of the main reasons that complicate NAS reproducibility studies is the high computational cost as well as the large carbon emissions that result(Li et al., 2021a). For the reproducibility of NAS research, NAS-Bench-101 (Ying et al., 2019) and NAS-Bench-201 (Dong & Yang, 2020) have been proposed. Due to the success of these tabular benchmarks in image classification, corresponding benchmarks have been proposed in areas such as NLP and speech recognition (Mehta et al., 2022).

Surrogate NAS Benchmarks. The recent Surrogate NAS Benchmarks (Zela et al., 2022) builds surrogate benchmarks on a realistic search space and shows strong generalization performance. To extend the surrogate model, NAS-Bench-X11 (Yan et al., 2021) uses singular value decomposition and noise modelling to output the learning curve.

NAS Benchmarks joint HPO Most NAS Benchmarks have fixed training hyperparameters, but the training hyperparameters strongly influence the performance of the model obtained by NAS (Dong et al., 2020). To alleviate this problem, NAS-HPO-Bench (Klein & Hutter, 2019) and NAS-HPO-Bench-II Hirose et al. (2021) are proposed. However, as shown in Table 1, the size of the two Benchmarks is small and the search spaces are simple. The architecture space of NAS-HPO-Bench is multi-layer perception (MLP) trained on the tabular datasets for regression tasks. NAS-HPO-Bench-II only really measure 12 epochs using the CIFAR-10 dataset Krizhevsky et al. (2009) and the training hyperparameters space only contains learning rate and batch size.

A.2 RESOURCE-AWARE NAS

Early NAS algorithms (Zoph & Le, 2016; Real et al., 2019) focused only on performance and ignored some of the associated hardware consumption. To this end, many resource-aware NAS algorithms are proposed to balance performance and resource budgets (He et al., 2021). These resource-aware NAS algorithms focus on the four types of computational costs that are included the FLOPs, parameter size, the number of Multiply-ACcumulate (MAC) operations and real latency. Among the NAS algorithms, two classic works are MnasNet (Tan et al., 2019) and FBNet (Wu et al., 2019). MnasNet proposes a multi-objective neural architecture search approach that optimizes both accuracy and real-world latency on mobile devices. Similar to MansNet, FBNet designs a loss function to trade off the cross-entropy loss and latency of architecture. However, none of the above on NAS algorithms focus on the huge energy consumption in search.

B MORE DETAILS OF EA-HAS-BENCH

B.1 **RegNet** vs **RegNet** + HPO

As shown in the figure 7, we compare the learning curves of one hundred samples actually measured from under two search spaces-RegNet and RegNet+HPO. The different architectures converge effectively under well-designed training hyperparameters. However, many architectures fail to converge under the search space of RegNet+HPO. But the latter may find a better combination to produce better performance. With a fixed training hyperparameter, the best model obtained by searching only in the network architecture space is not necessarily the true best model. At these fixed training hyperparameters, the sub-optimal model obtained by searching may get better performance under another set of training hyperparameters. In addition, the optimal hyperparameters are difficult to determine when facing a new dataset, while searching for training hyperparameters and model architecture is a more realistic scenario.

(a) RegNet

(b) RegNet + HPO

Figure 7: Comparing the learning curve under RegNet and RegNet+HPO search spaces. (a) The RegNet search space. (b) The RegNet + HPO search space.

Table 4: The formula of parametric learning curve

Reference name	Formula
$\exp_3$	$c - exp(-ax + b)$
ilog_2	$c - \frac{a}{\log x}$
pow_2	ax^α
log power	$\frac{a}{1+\left(\frac{x}{e^b}\right)^c}$
logx linear	$alog(x) + b$
vapor	$\exp\left(a + \frac{b}{x} + c\log(x)\right)$

B.2 DETAILS OF SURROGATE BENCHMARK EVALUATION

Parametric Learning Curves Based Models. We use the parametric models to fit the entire learning curve and the formula of those parametric models is shown in Table 4. Following Domhan et al. (2015), we first try the Levenberg-Marquardt algorithm and fall back to Broyden–Fletcher–Goldfarb–Shanno (BFGS) in case that fails. In the experiment, we found that the initial parameters are important in the fitting process. Some parametric models of a high order cannot be fitted to the learning curve in the training set because suitable initial parameters cannot be found. In contrast, the initial point of the BSC model is the starting and ending point of the learning curve.

Hyperparameters of Surrogate Models. For the optimal three surrogate models in Table 3 and the LGB energy cost model (LGB-E), the optimal parameters found using TPE and the search space are listed in Table 5. We used a fixed budget of 500 trials for all surrogate models and average R2 as the optimal target.

Models of Runtime Metrics Although our benchmark focuses on energy consumption, we also provide runtimes to allow NAS methods to use runtimes as budgets. We train an LGB model with

Table 5: Hyperparameters of the surrogate models and the optimal values found via TPE.

Model	Hyperparameter	Range	Type	Optime Value
SVD-LGB	Num. components	[1,20]	uniform int	4
	Num. rounds	-	constant	3000
	Early Stopping	-	constant	100
	Max. depth	[1,24]	uniform int	9
	Num. leaves	[10, 100]	uniform int	84
	Min. child weight	[0.001, 10]	log uniform	0.4622
	Lambda L1	[0.001, 1000]	log uniform	0.0056
	Lambda L2	[0.001, 1000]	log uniform	0.0054
	Boosting type	-	constant	gbdt
	Learning rate	[0.001, 0.1]	log uniform	0.5822
SVD-MLP	Num. components	[1,20]	uniform int	3
	Num. epochs	[5,200]	uniform int	190
	hidden dim	[32, 250]	constant	183
	Num. layers	-	constant	4
	Learning rate	[0.0001, 0.1]	log uniform	0.0008
	drop out	[0.0, 0.1, 0.2, 0.3, 0.4, 0.5]	uniform int	0.2
	batch size	[64, 128, 256]	uniform int	64
BSC	Num. epochs	[5,200]	uniform int	180
	hidden dim	[32, 250]	constant	247
	Num. layers	-	constant	4
	Learning rate	[0.0001, 0.1]	log uniform	0.0003
	drop out	[0.0, 0.1, 0.2, 0.3, 0.4, 0.5]	uniform int	0
	batch size	[64, 128, 256]	uniform int	64
LGB-E	Num. rounds	-	constant	3000
	Early Stopping	-	constant	100
	Max. depth	[1,100]	uniform int	31
	Num. leaves	[10, 1000]	uniform int	315
	Min. child weight	[0.001, 10]	log uniform	0.0046
	Lambda L1	[0.001, 1000]	log uniform	20.3216
	Lambda L2	[0.001, 1000]	log uniform	11.6866
	Boosting type	-	constant	gbdt
	Learning rate	[0.001, 0.1]	log uniform	0.0451

the average runtime of each epoch as a target and the model achieves 0.926 for R2 and 0.849 for KT on runtime prediction on CIFAR10.

B.3 ABLATION STUDY

In Table 6, we show the effect of different degrees of the Bézier curve on the prediction performance. The higher the degree, the better the Bézier curve fits the real learning curve, but it also leads to overfitting. As the degree increases, the prediction performance becomes worse instead. When the Degree is 4, the Quadratic Bézier curve achieves the best results.

Figure 8: Visualization of generated Bézier Curves and original learning curves (Ground Truth).

Table 6: The predicted performance of different degrees of the Bézier Curve on CIFAR-10

Method	Avg R2	Final R2	Avg KT	Final KT
Cubic Bézier (Degree = 3)	0.870	0.859	0.858	**0.855**
Quadratic Bézier (Degree = 4)	**0.892**	**0.872**	**0.860**	0.841
Quintic Bézier (Degree = 5)	0.891	0.862	0.855	0.834
Sextic Bézier (Degree = 6)	0.852	0.796	0.771	0.736

C   MORE ANALYSIS OF EA-HAS-BENCH

Distributions of Power.   The correlation between energy consumption and runtime is $energy = runtime \times Avg.power$. As shown in Figur9, since the power of different models trained on Tesla V100 is not a constant, the energy consumption is not linearly related to the runtime.

Figure 9: Visualization of distributions of power on CIFAR10 (left) and TinyImageNet (right).

D   MORE DETAILS OF SECTION 5

Details of NAS algorithms.   All algorithms we use in Section 5 are based on NASLib (Ruchte et al., 2020). For regularized evolution and local search, we modify them to suit our joint search space. The algorithm description and implementation details are as follows.

- **Random Search** is a classic baseline of HPO algorithms and is the basis for some complex algorithms (Li & Talwalkar, 2019). For EA-HAS-Bench, we sample randomly both the architecture and the hyperparameter space. The sampling type is the same as the dataset that we build for training the surrogate model.

- **Local search** iteratively evaluates all architectures in the neighbourhood of the current best architecture found so far (White et al., 2020). For the search space of EA-HAS-Bench, we define *neighbourhood* as having the same network architecture or the same training hyperparameters, i.e., points with the same subspace are neighbouring points.

- **Regularized evolution** mutates the best architecture from a sample of all architectures evaluated so far. For EA-HAS-Bench, we define a *mutation* as a random change of one dimension in the architecture or hyperparameters.

- **BANANAS** is based on Bayesian optimization and samples the next point by acquisition function (White et al., 2021a). We used a modified version from NAS-Bench-X11 to construct the candidate pool by mutating the best four points 10 times each.

- **Hyperband** is based on the random search with successive halving (Li et al., 2017). Since the space size of EA-NAS-Bench is 3×10^{10}, we expect to explore more points and set the maximum budget to 512 and the minimum budget to 4.

- **Bayesian optimization Hyperband** is based on Hyperband with Bayesian optimization (Falkner et al., 2018). We use the same parameters as Hyperhand.

Figure 10: Energy-aware BANANAS and vs. origin BANANAS and LS on TinyImaget.

EA algorithms on TinyImageNet. For TinyImageNet, we set T to 2.5 and target performance to 57%. The result is shown in Figure 10. Same as the experiment on CIFAR-10, compared with the baseline without the energy cost penalty, our EA algorithm cost a significantly lower search energy to reach the target accuracy.