MetaXLR - Mixed Language Meta Representation Transformation for Low-resource Cross-lingual Learning based on Multi-Armed Bandit

Abstract

Transfer learning for extremely low-resource languages is a challenging task as there is no large-scale monolingual corpora for pre-training or sufficient annotated data for fine-tuning. We follow the work of (Xia et al., 2021) which suggests using meta learning for transfer learning from a single source language to an extremely low resource one. We propose an enhanced approach which uses multiple source languages chosen in a data-driven manner. In addition, we introduce a sample selection strategy for utilizing the languages in training by using a multi armed bandit algorithm. Using both of these improvements we managed to achieve state-of-the-art results on the NER task for the extremely low resource languages even with the same amount of data, making the representations better generalized. Also, due to the method's ability to use multiple languages it allows the framework to use much larger amounts of data, while still having superior results over the former MetaXL method even with the same amounts of data.

1 Introduction

Multilingual pre-training such as XLM-R (Conneau et al., 2020) have presented great results on various NLP tasks for many languages. But in order to achieve that they require a large scale of monolingual data. Unfortunately, this is not the case for extremely low resource languages such Quechua or Ilocano where data for these languages barely exist. Therefore, in the case of a low resource language a way-to-go approach would be using transfer learning. We follow the work of (Xia et al., 2021) which uses a meta learning approach. In their work they used a high resource language to learn the task while learning concurrently how to convert representations to the low resource language.

However, the mentioned approach uses only one source language - missing the generalization that could be given using multiple languages. But moving to multi-language approach is not straight forward as different languages can have different effect on the learning process. Selecting languages can be done manually but it is a tedious process that requires linguistic knowledge that sometimes is not widely available. To overcome that, we suggest an approach which uses multiple languages, that are selected in a data driven manner and are balanced during training using a MAB algorithm.

In this paper we show how using multiple languages is more powerful than using a single source language even with the same amount of data. In addition, we propose utilizing multi armed bandit as a sampling strategy to balance the contribution of each language to the training process. Combining both we were able to achieve improved results on the downstream task of NER using languages that are never seen by the pretrained model before. In addition, the language selection is easy and can be done seamlessly.

2 Method

Using multiple source languages To select the source languages we took advantage of both LangRank (Lin et al., 2019) and the languages clusters present in Chiang et al. (2022). First, we chose a

Source / Target	qu	ilo	mhr	mi	tk	gn	Average
1. English 5k (Xia et al., 2021)	68.67	77.57	68.16	88.56	66.99	69.37	73.22
2. English 20k (Xia et al., 2021)	73.04	85.99	70.97	89.21	66.02	73.39	76.44
3. Related language 5k (Xia et al., 2021)	77.06	75.93	69.33	86.46	**73.15**	71.96	75.65
4. Related language (6k-8k)	76.47	82.3	73.78	**93.53**	71.07	74.07	78.54
5. Uniform selection	76.27	86.41	71.43	92.67	**72.9**	**79.65**	79.88
6. MetaXLR (ours)	**78.76**	**86.96**	**74.65**	92.67	**73.08**	79.44	**80.93**

Table 1: F1 for NER across six settings: (1) results for training on source data size of 5k with the English data source only. (2) results for training on source data size of 20k with the English data source only. (3) results using one source language with data size of 5k. (4) Training with MetaXL related source language using the exact same data size as we used in our method (varies between 6k-8k as in Table \ref{tab:langs-table}). (5) Choosing languages with uniform distribution. (6) Our method: training with the source languages defined in Table 2 with MetaXLR algorithm (Algorithm 1). We bold the numbers with a better average performance in each setting.

source language s_1 used in (Xia et al., 2021) using LangRank. Next, we used the language clusters and mapped s_1 's cluster c. Then, we chose $n-1$ arbitrary languages from c.

Multi armed bandit as sampling strategy Since the languages from the previous step are selected from a large cluster, they may have different effect on the training process as they are yet very varied. Thus, we would like to balance the training process - defining a sampling distribution for the source languages while training.

In our strategy we increase the weight of languages that are harder to learn. The intuition is that in order to generalize the representations properly across the different languages, we should train more with languages that the model struggles with. For making this weighting strategy adaptive to different languages without manual interference, we reduced the problem to a MAB problem where we consider each source language as an arm. Every training step, we select one language from the language distribution and get a reward, which in this case is the loss - as high as it gets it means the model struggles with this language. The multi armed bandit we used is EXP3 described in (Auer et al., 2002). We used it as part of the meta learning algorithm as can be seen in Algorithm 1.

3 EXPERIMENTS

Similarly to (Xia et al., 2021) we used XLM-R. The data that is used for our experiments is WikiAnn, which contain 282 different languages on the NER task. We present results in Table 1. We can see that our method outperform the baselines (1-4) by at least 2.4 F1 score in average by using the same amount of data. We can see the importance of the data size comparing method (1) and (2). We can also observe the importance of selecting related languages by comparing method (1) and (3). Our method allows us to leverage these two observations, by the fact that we are able to use related languages with limited data, and have a large amount of data size combining several related languages together. We can also see that the MetaXL (Xia et al., 2021) works well and improved even by using uniform language selection distribution, by presenting an improved result of at least 1.3 F1 in average. Our language selection algorithm further improves the result by 1.1 F1 score in average. Comparing the two methods (5) and (6), we can see that the language selection algorithm performs at least as well as the uniform selection and sometimes achieves better results.

4 CONCLUSION

In this paper, we study cross-lingual transfer learning for extremely low-resource languages. We broadened MetaXL (Xia et al., 2021), enabling it to use a set of source languages, while choosing from them in the training loop using a Multi Armed Bandit algorithm. We managed to both improve on the results of previous works while simultaneously increasing the pool of usable data and achieve state-of-the-art results for the extremely low resource languages.

URM STATEMENT

The authors acknowledge that at least one key author of this work meets the URM criteria of ICLR 2023 Tiny Papers Track.

REFERENCES

Peter Auer, Nicolo Cesa-Bianchi, Yoav Freund, and Robert E Schapire. The nonstochastic multi-armed bandit problem. *SIAM journal on computing*, 32(1):48–77, 2002.

Ting-Rui Chiang, Yi-Pei Chen, Yi-Ting Yeh, and Graham Neubig. Breaking down multilingual machine translation. In *Findings of the Association for Computational Linguistics: ACL 2022*, pp. 2766–2780, Dublin, Ireland, May 2022. Association for Computational Linguistics. doi: 10.18653/v1/2022.findings-acl.218. URL https://aclanthology.org/2022.findings-acl.218.

Alexis Conneau, Kartikay Khandelwal, Naman Goyal, Vishrav Chaudhary, Guillaume Wenzek, Francisco Guzmán, Edouard Grave, Myle Ott, Luke Zettlemoyer, and Veselin Stoyanov. Unsupervised cross-lingual representation learning at scale. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pp. 8440–8451, Online, July 2020. Association for Computational Linguistics. doi: 10.18653/v1/2020.acl-main.747. URL https://aclanthology.org/2020.acl-main.747.

Yu-Hsiang Lin, Chian-Yu Chen, Jean Lee, Zirui Li, Yuyan Zhang, Mengzhou Xia, Shruti Rijhwani, Junxian He, Zhisong Zhang, Xuezhe Ma, Antonios Anastasopoulos, Patrick Littell, and Graham Neubig. Choosing transfer languages for cross-lingual learning. In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pp. 3125–3135, Florence, Italy, July 2019. Association for Computational Linguistics. doi: 10.18653/v1/P19-1301. URL https://aclanthology.org/P19-1301.

Mengzhou Xia, Guoqing Zheng, Subhabrata Mukherjee, Milad Shokouhi, Graham Neubig, and Ahmed Hassan Awadallah. MetaXL: Meta representation transformation for low-resource cross-lingual learning. In *Proceedings of the 2021 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, pp. 499–511, Online, June 2021. Association for Computational Linguistics. doi: 10.18653/v1/2021.naacl-main.42. URL https://aclanthology.org/2021.naacl-main.42.

A   METAXLR ALOGRITHM

Algorithm 1 Training procedure for MetaXLR

Input: Input data from the target language data D_t and the source related languages $D_{s_1}...D_{s_K}$
Initialize base model parameters θ with pretrained XLM-R weights
Initialize parameters of the representation transformation network ϕ randomly
Initialize weights $w_0(0) = ... = w_0(K) = 1$
Initialize t = 0

while not converged **do**

   Define $p_t(i) = (1 - \gamma)\frac{w_t(i)}{\sum_{j=1}^{K}} + \frac{\gamma}{K}$

   Sample a source language s_i from $p_t(1)...p_t(K)$
   Sample a source batch (x_{s_i}, y_{s_i}) from D_{s_i} and   a target batch (x_t, y_t) from D_t
   $\theta^{(t+1)} = \theta^{(t)} - \alpha\nabla_\theta\mathcal{L}(f(x_{s_i};\theta^{(t)}, \phi^{(t)}), y_s)$
   $\phi^{(t+1)} = \phi^{(t)} - \beta\nabla_\phi\mathcal{L}(f(x_t;\theta^{(t+1)}), y_t)$
   $r_t = \frac{\mathcal{L}(f(x_t;\theta^{(t+1)}),y_t)}{p_t(i)}$
   $w_{t+1}(i) = w_t(i)e^{\frac{\gamma \cdot r_t}{K}}$
   $t = t + 1$
end while

The highlighted lines are the main differences between MetaXL and MetaXLR.

B   HYPER-PARAMETERS

We used $\gamma = 0.01$ and 12.5k training steps, with batch size of 4. The rest of the hyper-parameters remained the same as in MetaXL (Xia et al., 2021).

C   RELATED LANGUAGES CLUSTERS

Target Language	Related language in MetaXL	Related languages in our method
qu	es	es, pt, it, de, en, ar, he, fr
il	id	id, he, ar, de, fr, vi, en
mhr	ru	ru, he, ar, de, it, fr, ro, en
mi	id	id, he, ar, de, vi, en
tk	tr	tr, az, be, uk, sk, lt, sr, cs
gn	es	es, pt, it, de, en, ar, he, fr

Table 2: Target and source languages information on the NER task. The source data size per source language is 1k and the target language data size is 100

D   REWARD STRATEGIES

Meta loss as Loss	Uniform Selection	Meta loss as Reward
84.06	86.41	**86.96**

Table 3: F1 score for different reward strategies for the Ilocano target language