GenoMAS: Guided Multi-Agent Programming for Scientific Discovery from Transcriptomic Data

Abstract

Gene expression analysis holds the key to many biomedical discoveries, yet extracting insights from raw transcriptomic data remains challenging due to the complexity of multiple large, semi-structured files and the need for extensive domain expertise. Current approaches either rely on inflexible workflows that fail in edge cases or fully autonomous agents that lack the precision required for rigorous scientific inquiry. **GenoMAS** addresses this by presenting a team of LLM-based agents that integrates structured workflows with autonomous adaptability, orchestrating diverse specialized agents through typed message-passing protocols. At its core lies a guided-planning framework where programming agents decompose task guidelines into Action Units and dynamically choose to advance, revise, bypass, or backtrack, maintaining logical coherence while adapting to the idiosyncrasies of genomic data. On the GenoTEX benchmark, GenoMAS achieves 89.13% Composite Similarity Correlation for preprocessing and 60.48% F_1 for gene identification, surpassing prior art by 10.61% and 16.85% respectively. Beyond metrics, GenoMAS identifies biologically plausible gene-phenotype associations corroborated by literature while adjusting for latent confounders.

1 Introduction

Scientific research increasingly depends on complex computational analysis, yet such analysis remains labor-intensive, error-prone, and difficult to scale. Across genomics (Conesa et al., 2016; Stark et al., 2019), drug development (Zhu et al., 2025a), and personalized medicine (Ginsburg and Phillips, 2018), the analytical backbone involves highly structured workflows that integrate raw data, apply statistical models, and yield interpretable results under constraints of domain knowledge and methodological rigor. Recent advances in large language models (LLMs) have enabled agents capable of task decomposition (Luo et al., 2025; OpenAI, 2023), tool interaction (Qin et al., 2023; Zhu et al., 2025a), and code generation (Du et al., 2023; Zhuo et al., 2024). These developments raise the prospect that LLM-based agents might contribute to scientific discovery by automating analysis pipelines (Chen et al., 2025; Schmidgall et al., 2025). However, realizing this requires bridging the gap between general reasoning and the precision-driven nature of scientific computation.

While many LLM-based agents show competence in document retrieval or planning tasks (Zhuge et al., 2025; Yehudai et al., 2025), these capabilities fall short where scientific progress depends on code. In transcriptomics (Rosati et al., 2024), protein engineering (Swanson et al., 2024), and statistical genetics (Ginsburg and Phillips, 2018), workflows are encoded as programmatic transformations tailored to dataset idiosyncrasies. Analysts routinely write custom scripts to handle malformed metadata, adjust for confounders, map deprecated identifiers, and address batch effects (Johnson et al., 2007). These operations require direct, editable code and cannot be abstracted or offloaded to black-box tools. Even with standardized pipelines, deviations remain common. Scientific automation therefore hinges on writing, revising, and validating executable code.

Despite growing interest in agentic AI (Wang et al., 2025), current systems rarely address this requirement. Most frameworks operate by composing tool calls (Qin et al., 2023) or coordinating invocations across structured graphs (Ye et al., 2025; Zhuge et al., 2025). Some support dynamic routing, but operate within fixed templates. A few attempt code-level control (Hu et al., 2024), but lack structured revision or domain-aware correction. Critically, these frameworks are benchmarked on synthetic tasks (Zhu et al., 2025a), where correctness is judged by output format rather than scientific

Figure 1: Multi-agent collaboration in our GenoMAS method.

validity. In gene expression analysis, even small preprocessing errors can invalidate results (Ghosh and Chinnaiyan, 2005). Yet current systems offer no reliable means to detect and recover from such errors, remaining unsuitable for workflows where correctness is inseparable from domain context.

To bridge the gap between general-purpose agentic reasoning and the domain-specific precision required for scientific computation, we present **GenoMAS** (**Geno**mic data analysis through LLM-based **M**ulti-**A**gent **S**ystem), a framework that reframes scientific agents as collaborative programmers rather than workflow orchestrators (Figure 1). GenoMAS agents generate, revise, and validate executable code tailored to each scientific task. Applied to gene expression analysis, the system automates complex workflows that previously required manual scripting by domain experts. Evaluated on GenoTEX (Liu et al., 2025), a benchmark with 1,384 gene-trait association tasks spanning heterogeneous cohorts and statistical confounders, GenoMAS achieves state-of-the-art performance while operating from raw data inputs. These results suggest that effective scientific automation requires agents that code, not merely reason and retrieve.

Our contributions are as follows:

1. We introduce **GenoMAS**, a multi-agent approach that treats agents as collaborative programmers rather than tool orchestrators, enabling end-to-end code generation for genomic analysis.

2. We develop a guided planning mechanism that encodes workflows as editable Action Units, which are structured directives that can be transformed into and modified as executable code, balancing precise control with autonomous error handling.

3. We demonstrate that GenoMAS supports heterogeneous agent composition, allowing distinct LLMs with varying strengths to operate in coordinated roles within the same execution loop.

2 Related Work

LLM-based Multi-Agent Systems LLMs have enabled autonomous agents capable of complex reasoning and task execution (Wang et al., 2023; OpenAI, 2023; Yehudai et al., 2025). These agents leverage structured reasoning approaches (Yao et al., 2023; Besta et al., 2023), self-reflection mechanisms (Xi et al., 2023; Madaan et al., 2023), and external tool integration (Qin et al., 2023; Qian et al., 2025). Multi-agent collaboration further enhances performance through specialized role-playing (Hong et al., 2023; Dong et al., 2023), goal decomposition (Wei et al., 2022; Ning et al., 2023),

and feedback mechanisms (Huang et al., 2023; Yin et al., 2023). Recent work has explored failure modes (Cemri et al., 2025) and training frameworks (Ma et al., 2024) for such systems.

LLM Agents for Scientific Discovery LLM agents are increasingly being developed to automate scientific discovery (Lu et al., 2024; Baek et al., 2024; Yehudai et al., 2025), including hypothesis generation (Chen et al., 2025) and peer review (Zhu et al., 2025b). Systems like AI Scientist (Lu et al., 2024) and ResearchAgent (Baek et al., 2024) demonstrate autonomous completion of research cycles. Domain-specific applications span mathematics (DeepSeek-AI et al., 2025), physics (Latif et al., 2024), chemistry (Bran et al., 2023), biology (Huang et al., 2025), and medicine (Liu et al., 2024).

Positioning of Our Work While existing agentic systems for scientific discovery have demonstrated capabilities in hypothesis generation (Baek et al., 2024), experimental design (Jia et al., 2024), or literature-driven reasoning (Kang et al., 2023; Zhu et al., 2025b), they rarely address settings where agents must write and revise executable code under scientific constraints. GenoMAS targets this gap by treating scientific automation as a coding problem rather than a retrieval or coordination problem.

3 Preliminaries

3.1 Problem Formulation

We address gene-trait association (GTA) analysis, a key task in computational biology that identifies genes whose expression patterns correlate with phenotypic traits (Ghosh and Chinnaiyan, 2005; Wu et al., 2009). Following the GenoTEX benchmark (Liu et al., 2025), we consider two problem settings:

- **Unconditional GTA:** Given gene expression data $X \in \mathbb{R}^{n \times p}$ and trait values $y \in \mathbb{R}^n$, identify genes $G^* \subseteq \{1, ..., p\}$ significantly associated with the trait.

- **Conditional GTA:** Given additional condition $c \in \mathbb{R}^n$ (e.g., age, gender, or comorbidity), identify genes G_c^* associated with the trait while accounting for this condition (Kyalwazi et al., 2023), enabling more precise insights for personalized medicine (Wang et al., 2022).

The analysis pipeline consists of three stages: (1) dataset selection from repositories like the Gene Expression Omnibus (GEO) (Clough and Barrett, 2016) and The Cancer Genome Atlas (TCGA) (Tomczak et al., 2015), (2) data preprocessing to extract and normalize gene expression and clinical features, and (3) statistical analysis using regularized regression models (Cook et al., 2017).

3.2 Evaluation

We evaluate methods using the GenoTEX benchmark (Liu et al., 2025), which assesses performance across three pipeline stages:

Dataset Selection Dataset Filtering (DF) measures binary classification accuracy in determining dataset relevance, while Dataset Selection (DS) evaluates whether the method selects the same dataset as domain experts when multiple candidates are available.

Data Preprocessing Preprocessing involves extracting gene expression data from different platforms. Microarray probes require mapping to gene symbols (Khondoker, 2006), while RNA-seq reads demand alignment and quantification (Conesa et al., 2016). Gene identifiers must be normalized across evolving nomenclatures (Sayers et al., 2022; Wei et al., 2023), and clinical metadata extracted from heterogeneous formats (Çetin and YILDIZ, 2022). Quality is evaluated using: (i) Attribute Jaccard (AJ) measuring feature overlap, (ii) Sample Jaccard (SJ) assessing sample overlap, and (iii) Composite Similarity Correlation (CSC), capturing both structural and numerical fidelity.

Statistical Analysis Gene identification employs Lasso regression (Tibshirani, 1996) and its variants (Wu et al., 2009), requiring batch effect correction (Johnson et al., 2007), adjustment for population stratification (Yu et al., 2006), and imputation of missing values (Liew et al., 2011). Evaluation uses F_1 score, Precision, Recall, AUROC (Hanley and McNeil, 1982), and GSEA Enrichment Score (Subramanian et al., 2005).

3.3 Technical Challenges

Automated GTA analysis presents intertwined challenges (Angermueller et al., 2016): *(i) High-dimensional sparsity*: datasets typically comprise over 20,000 genes across <1,000 samples (Johnstone, 2001); *(ii) Platform heterogeneity*: microarrays and RNA-seq require distinct processing pipelines (Abusamra, 2013; Stark et al., 2019); *(iii) Evolving gene nomenclature*: continuous changes in gene names necessitate robust normalization

(Sayers et al., 2022; Wei et al., 2023); *(iv) Heterogeneous metadata*: phenotypic information appears in varied formats, requiring domain expertise to extract from free-text descriptions or infer from indirect information (Chen et al., 2023); and *(v) Confounding factors*: batch effects (Leek et al., 2010), population stratification (Yu et al., 2006), and hidden covariates (Gagnon-Bartsch and Speed, 2012) can introduce spurious associations. These challenges require systems that combine computational pipelines with biological understanding.

4 Method: GenoMAS

4.1 Overview

The complexity of gene expression analysis demands both *precise procedural control* and *adaptive error handling*. Conventional workflow-based approaches offer structured execution but lack the adaptability needed to manage edge cases, leading to suboptimal performance (Section 5.3). Conversely, fully autonomous agents demonstrate greater adaptability but sacrifice the precision essential for rigorous scientific analyses (Appendix A).

GenoMAS reconciles these competing requirements through a multi-agent framework in which programming agents execute user-defined guidelines while retaining autonomy to handle exceptions. The system coordinates a team of specialized agents, each with distinct functional roles, that communicate through structured protocols and employ context-aware decision-making to address edge cases, retry failed operations, and integrate domain-specific knowledge.

4.2 Multi-Agent Architecture

Agent Roles and Responsibilities GenoMAS employs six specialized agents organized into three functional categories: (i) The **orchestration agent** (*PI agent*) coordinates the analysis workflow by dynamically assigning tasks based on requirements and task dependencies. (ii) The **programming agents** perform core computational tasks: two *Data Engineer agents* handle data preprocessing. The *GEO agent* focuses on GEO datasets while the *TCGA agent* manages TCGA data, each with specialized knowledge of their respective data formats and common preprocessing challenges. The *Statistician agent* conducts statistical analyses, employing regression models to identify trait-associated genes while accounting for confounding factors. (iii) The **advisory agents** support programming

agents through complementary expertise: the *Code Reviewer agent* validates generated code for functionality and instruction conformance, providing revision suggestions, while the *Domain Expert agent* provides biomedical insights for decisions requiring biological knowledge, such as clinical feature extraction and gene identifier mapping.

Diverse LLMs as Agents' Backbone GenoMAS leverages heterogeneous LLM backbones to exploit complementary strengths (Hong and Page, 2004; Page, 2007; Zhuge et al., 2025). We power programming agents with Claude Sonnet 4 (Anthropic, 2024), selected for its strong agentic coding abilities. OpenAI o3 (OpenAI, 2025a), known for robust reasoning, serves dual roles: guiding the planning logic of programming agents and enabling the Code Reviewer to detect bugs and suggest targeted fixes. Gemini 2.5 Pro (DeepMind, 2025b), a top-performing model on scientific benchmarks (Rein et al., 2023; Li et al., 2024), powers the Domain Expert agent with broad and accurate scientific knowledge, particularly in biology.

Task Orchestration The **PI agent** orchestrates analysis workflows by adhering to the dependency structure of gene expression analysis. For each GTA task, it identifies preprocessed cohorts and schedules preprocessing only for missing data, maximizing reuse across tasks with overlapping traits. Leveraging the independence of cohort-specific transformations, the agent parallelizes execution to reduce runtime. Upon completion, the Statistician agent selects suitable cohorts for downstream inference. Throughout the pipeline, the PI agent issues tasks via structured messages, monitors completion signals, and enforces timeouts to prevent unbounded execution.

Message-Driven Task Progression GenoMAS employs a typed message-passing protocol governing task progression through structured request-response cycles. Messages carry sender role, message type (e.g., `CODE_WRITING_REQUEST`, `CODE_REVIEW_RESPONSE`), content, and target roles, enabling precise agent coordination. Upon completing a code segment, programming agents send review requests to the Code Reviewer or Domain Expert based on requirements. Typed responses determine subsequent actions: approval advances execution, while rejection triggers revision. A centralized environment manages interactions via a message queue, enforcing topological

constraints to avoid circular dependencies. This framework enables task flows to emerge organically while ensuring coherent execution. Additional details are in Appendix B.

4.3 Programming Agents

Figure 2: Planning, memory, and self-correction mechanisms of a single programming agent in our GenoMAS method.

4.3.1 Guided Planning

Guidelines and Action Unit   The programming agents (**Data Engineers** and **Statistician**) execute complex workflows using a guided planning framework that balances structure and flexibility. Agents operate under textual task guidelines encoding dependency structures, conditional logic, and termination criteria as a directed acyclic graph (DAG), enabling dynamic behavior adjustment based on evolving task context.

Within this DAG, agents decompose workflows into *Action Units*: semantically coherent operations corresponding to discrete subtasks. For example, the GEO agent's workflow comprises Action Units for data loading, clinical feature extraction, gene annotation, and normalization. Each unit represents a self-contained sequence of operations executable atomically, without intermediate oversight. See Appendix C for guideline templates and Action Unit examples.

Guided Context-aware Planning   At each step, programming agents analyze their task history and current state to select the next Action Unit, considering previous outcomes, discovered data characteristics, and remaining objectives. Agents can advance to the next Action Unit, revisit prior steps with modified parameters, skip optional steps, or terminate upon completion.

The retraction mechanism allows agents to backtrack when an earlier decision led to downstream complications. Upon retraction, agents revert task context and execution state to a previous step, then continue with an alternative Action Unit. This proves essential for handling complex interdependencies in gene expression analysis, where early preprocessing decisions can cascade through data quality. Appendix D provides additional details.

4.3.2 Domain Specific Code Generation

Iterative Code Generation and Debugging   GenoMAS adopts a three-stage process (writing, review, revision) to generate robust pipelines. For each Action Unit, agents receive complete task context, including prior executions, error traces, and historical attempts, enabling reasoning about data structures and avoiding redundant mistakes. The Code Reviewer evaluates output, error messages, and guideline adherence, issuing approval or rejection. Agents then refine and resubmit code iteratively until approval or reaching debugging limits.

To ensure independent evaluation, code review enforces context isolation. The Code Reviewer receives the current attempt and task history but not prior review feedback at the same step, mitigating cascading biases. After review, programming agents regain access to all feedback, synthesizing insights to revise code accordingly.

Domain Expert Consultation for Biomedical Reasoning   For Action Units requiring biomedical knowledge, programming agents consult the Domain Expert agent in place of the Code Reviewer. The expert receives targeted context (such as metadata, processed summaries, and intermediate results), focusing on biological content rather than implementation details. The Domain Expert returns guidance in executable code form, enabling contextually grounded, biologically valid operations. This process is also iterative: execution failures are routed back to the expert for debugging, facilitating consistent reasoning over multiple refinement rounds. Details and example prompts are provided in Appendix E.

Code Memory for Reuse   Programming agents maintain dynamic memory of validated code snippets indexed by Action Unit type. Upon successful review, snippets are stored for reuse in similar contexts. This memory evolves with experience; agents can revise or replace stored code to reflect updated practices or domain shifts, improving efficiency and reliability while preserving flexibility to adapt to novel scenarios.

Specialized Tool Sets and Domain Knowledge Databases Each agent is equipped with specialized Python tools aligned with its responsibilities: Data Engineers access utilities for dataset loading, DataFrame manipulation, and gene mapping, while the Statistician employs statistical models and visualization libraries. Tools were co-developed by two computational biologists through iterative testing on genomic datasets, encapsulating best practices.

GenoMAS integrates local, version-controlled biological knowledge bases to ensure consistency. A curated gene synonym database from NCBI Gene (Brown et al., 2015) supports symbol normalization, while gene-trait association data from the Open Targets Platform (Targets, 2025) enables prediction of missing conditions for conditional GTA tasks.

5 Experiments

We evaluate **GenoMAS** on the GenoTEX benchmark (Liu et al., 2025), which encompasses 1,384 GTA problems across 913 datasets spanning 132 human traits. GenoTEX covers the complete analytical workflow from raw data to biological insights, and provides expert-curated ground truth for analyzing real-world genomic datasets with realistic complexities. These characteristics make it well-suited for assessing agentic methods on complex, multi-step analysis requiring scientific rigor.

5.1 Experimental Setup

Computation environment We conducted experiments on 6 RunPod GPU Cloud (RunPod, 2024) instances, each with 16 vCPU cores and 94GB RAM. The data analysis code generated by agents consumed approximately 0.3GB RAM, consistent across different LLM backbones. For LLM inference, we accessed proprietary models (e.g., OpenAI o3) via their official APIs, while using open-source models (e.g., DeepSeek R1) through Novita AI (Novita AI, 2025) for its lower latency.

Metrics Our end-to-end evaluation assesses the ability of GenoMAS to identify significant genes from raw data. We adopt F_1 score (Section 3.2) as the primary indicator, and report trait prediction accuracy and F_1 to validate the generated regression models. Runtime metrics include success rate (proportion of problems where generated code executes without errors and saves results to the correct path), token counts, API costs, and average execution time per problem.

5.2 Comparison with Prior Art

We compare **GenoMAS** against the prior state-of-the-art method GenoAgent (Liu et al., 2025), homogeneous variants where all agents share the same LLM backbone, and several baselines: random gene selection, human expert performance (computed as the average performance of two independent expert analyses when evaluated against a consensus ground truth) (Liu et al., 2025), and OpenAI o3 zero-shot (which attempts to identify significant genes without access to data, probing whether parametric knowledge alone suffices).

Table 1 presents end-to-end results. GenoMAS achieves 60.48% F_1 score, yielding a 16.85% absolute improvement over GenoAgent, alongside 0.81 AUROC (0.17 increase) and 44.7% lower API cost. The integration of heterogeneous LLMs proves essential: while Claude Sonnet 4 (Thinking) underpins our code generation, augmenting it with o3's reasoning abilities and Gemini 2.5 Pro's domain expertise yields an additional 7.5% F_1 improvement and 48.9% cost reduction compared to homogeneous Claude-only configurations. Notably, Biomni, despite its success as a generalist biomedical agent, achieves only 14.82% F_1 in our evaluation. Other representative agents exhibited very low end-to-end success rates in our preliminary experiments, so we excluded them from the numerical evaluation here. These performance gaps confirm that reliable gene expression analysis requires combining precise procedural control with agentic autonomy. Appendix A specifies our evaluation procedures, and discusses reasons for these performance gaps in more detail.

5.3 Ablation Study

Ablation on each component We conducted systematic ablations to quantify the contribution of each component: (i) removing planning forces execution along a fixed workflow (static DAG without adaptive execution order); (ii) excluding the Domain Expert evaluates whether Programming and Code Reviewer agents alone suffice for biomedical reasoning; (iii) restricting to a single review round assesses the impact of iterative refinement; (iv) omitting code review entirely measures baseline performance without quality control.

Results in Table 1 demonstrate that context-aware planning enables dynamic adaptation to edge cases and error recovery, yielding both higher accuracy and greater efficiency by eliminating redundant steps. The collaborative design, particularly

Table 1: **End-to-end performance of GenoMAS and prior art; performance of GenoMAS in homogeneous LLM setting with various LLMs; ablation results of GenoMAS; human expert performance, and simple data-free baselines.** We report performance on the GTA analysis problems, on the additional trait prediction task, and runtime performance with success rate and efficiency metrics. We use 0 as performance scores when code execution fails. "Tk.(K)", "Cost ($)", and "Time (s)" represent average input/output tokens (in thousands), API cost, and runtime per problem, respectively. "(T.)" indicates Extended Thinking mode.

Model	GTA Analysis					Trait Prediction		Runtime Performance			
	Prec.(%)	Rec.(%)	F_1(%)	AUROC	GSEA	Acc.(%)	F_1(%)	Succ.(%)	Tk.(K)	Cost($)	Time(s)
GenoMAS (Ours)	**61.75**	**66.67**	**60.48**	**0.81**	**0.95**	**86.25**	71.34	**98.78**	162.6/7.1	0.38	307.26
GenoAgent (Liu et al., 2025)	45.52	52.87	43.63	0.65	0.71	83.14	71.93	86.12	170.1/10.4	0.69	341.58
Biomni (Huang et al., 2025)	17.42	15.24	14.82	0.29	0.39	48.54	41.64	53.66	213.4/9.3	0.78	183.91
Claude Sonnet 4 (T.) (Anthropic, 2024)	53.36	55.88	52.98	0.74	0.93	85.77	**73.60**	96.34	177.4/13.2	0.73	282.85
Claude Sonnet 4 (Anthropic, 2024)	24.61	21.69	21.92	0.45	0.66	57.98	52.51	68.29	219.1/6.8	0.76	251.21
OpenAI o3 (OpenAI, 2025a)	48.93	47.81	45.53	0.74	**0.95**	85.73	58.46	97.56	125.4/8.7	0.32	251.55
OpenAI o3-mini (OpenAI, 2025b)	39.08	37.46	35.54	0.52	0.57	64.07	38.77	74.39	136.7/10.6	0.20	**127.37**
Gemini 2.5 Pro (DeepMind, 2025b)	46.13	45.30	43.82	0.66	0.73	71.26	58.47	76.64	165.7/**3.3**	0.24	293.96
Gemini 2.5 Flash (DeepMind, 2025a)	40.29	43.26	40.67	0.56	0.59	50.14	33.82	61.70	142.0/**3.3**	0.03	198.34
DeepSeek R1 (DeepSeek-AI et al., 2025)	13.42	13.58	13.45	0.13	0.14	11.23	8.95	13.94	107.9/28.7	0.15	851.23
Qwen 3 235B (Qwen Team, 2025)	6.73	6.89	6.52	0.07	0.09	8.14	5.47	9.28	**78.0**/8.9	**0.02**	1084.51
No planning	51.61	57.01	51.27	0.74	0.87	73.32	59.90	89.59	204.1/9.3	0.48	359.79
No Domain Expert	50.06	52.72	47.57	0.69	0.81	64.75	50.14	85.24	182.6/8.0	0.43	322.54
Review Round=1	48.08	51.60	46.61	0.67	0.75	71.98	59.33	91.76	119.8/5.8	0.27	236.08
No reviewer	25.12	26.89	24.98	0.45	0.52	47.43	30.84	56.23	96.6/3.6	0.19	138.36
Human expert (Liu et al., 2025)	74.28	86.57	71.63	0.90	0.93	-	-	-	-	-	-
o3 zero-shot	15.84	4.28	5.13	0.56	0.41	-	-	-	0.1/0.8	0.01	12.18
Random (Liu et al., 2025)	0.72	0.90	0.75	0.49	0.04	-	-	-	-	-	0.02

Table 2: **Statistical analysis performance when using *expert-preprocessed data* as input.** We use the same evaluation metrics as in Table 1. Baselines include various representative agents and LLMs, and fixed scripts implementing two standard regression models for genomic data analysis. "BEC" in Row 2 represents batch effect correction.

Model	GTA Analysis					Trait Prediction		Runtime Performance			
	Prec.(%)	Rec.(%)	F_1(%)	AUROC	GSEA	Acc.(%)	F_1(%)	Succ.(%)	Tk.(K)	Cost($)	Time(s)
GenoMAS (Ours)	**97.14**	**92.87**	**95.26**	**0.97**	**0.99**	**88.37**	**77.21**	**100.00**	25.0/1.7	0.08	67.57
GenoMAS (No BEC)	70.18	75.60	69.64	0.85	0.92	86.48	61.29	**100.00**	24.2/1.6	0.07	65.34
GenoAgent (Liu et al., 2025)	94.81	92.27	93.83	0.96	0.97	87.23	72.67	99.71	28.5/1.9	0.09	71.60
Biomni (Huang et al., 2025)	90.56	88.56	89.23	0.92	0.94	85.05	71.87	96.52	26.1/1.4	0.10	37.83
Data Interpreter (Hong et al., 2024)	91.20	89.74	90.86	0.94	0.97	88.10	73.54	99.16	43.0/2.8	0.13	194.33
MetaGPT (Hong et al., 2023)	87.28	88.73	87.46	0.91	0.94	84.88	70.35	96.05	36.2/2.4	0.12	162.49
AutoGen (Wu et al., 2023)	86.04	87.09	86.38	0.93	0.95	82.81	72.24	96.60	41.7/2.6	0.71	139.48
CodeAct (Wang et al., 2024)	86.13	82.01	82.92	0.82	0.86	79.92	66.35	87.34	32.1/2.2	0.11	110.93
OpenAI o3 (OpenAI, 2025a)	80.39	80.92	80.57	0.83	0.85	76.25	62.54	88.63	15.1/**1.5**	0.05	**39.64**
DeepSeek R1 (DeepSeek-AI et al., 2025)	73.42	73.18	73.65	0.74	0.76	74.31	57.23	78.56	**12.6**/4.9	**0.02**	136.22
Lasso (Tibshirani, 1996)	31.88	12.99	14.03	0.53	0.12	76.48	62.31	99.39	-	-	9.19
LMM (Henderson, 1950)	3.73	3.75	3.64	0.51	0.03	75.63	58.04	99.21	-	-	15.44

specialized Code Reviewer and Domain Expert agents, proves critical for maintaining scientific rigor, while multiple review rounds catch subtle errors with downstream impacts.

Individual Task Performance To identify performance bottlenecks, we conducted component-wise evaluation of the GenoMAS pipeline. For *dataset filtering and selection* (Figure 3(a)), agents exhibit reasonable effectiveness, likely due to the comparatively lower reasoning complexity in metadata-based relevance assessment. However, early-stage errors can propagate through the pipeline, producing cascading effects on overall performance.

Data preprocessing (Figure 3(b)) reveals pronounced task-dependent variation. **GenoMAS** achieves high performance on gene expression data (91.15% CSC), demonstrating its effectiveness in handling genomic data transformation. In contrast,

(a) Dataset filtering and selection

(b) Data preprocessing performance

Figure 3: **Individual task performance of GenoMAS and various baselines on dataset filtering, selection, and preprocessing tasks.** (a) Dataset filtering (DF) and selection (DS) accuracy of different methods, and different ablation settings of our GenoMAS method. (b) Data preprocessing performance across three data types (Linked, Gene, Trait) and three metrics (AJ: Attribute Jaccard, SJ: Sample Jaccard, CSC: Composite Similarity Correlation), with CSC as the primary metric.

clinical trait preprocessing yields a markedly lower CSC of 32.61%, reflecting the heterogeneous nature of clinical data and the nuanced domain knowledge required for accurate extraction. This disparity identifies clinical feature preprocessing as the main bottleneck where both technical sophistication and biomedical expertise are essential.

For *statistical analysis* (Table 2), we provided expert-preprocessed data as input, creating a controlled environment to test the GTA analysis accuracy of methods. In this setting, GenoMAS with batch effect correction achieves 95.26% F_1, substantially outperforming traditional regression baselines (Lasso: 14.03%), previous agent methods, and the variant without systematic confound control. This result indicates that while basic statistical modeling is relatively straightforward for modern agents, the methodological sophistication to handle batch effects and covariate adjustment (capabilities built into our system through domain expertise) remains crucial for identifying genuinely significant biological signals.

6 Qualitative Analysis

GenoMAS identifies biologically meaningful gene-trait associations To validate scientific alignment with established domain knowledge, we compared genes identified by GenoMAS for unconditional GTA problems against known gene-disease associations from Open Targets Platform (Targets, 2025). The overlap achieved a GSEA enrichment score of 0.53 with FDR q-value of 0.16, indicating moderate concordance with established disease

biology. Manual examination of high-confidence predictions revealed literature-supported associations (Appendix G), confirming that GenoMAS produces scientifically interpretable results.

Autonomous agent behaviors enhance workflow robustness Qualitative analysis on GenoMAS execution patterns reveals that agents autonomously adapt their behavior beyond prescribed instructions when encountering edge cases or persistent errors. E.g., when an early decision creates downstream complications, agents can autonomously rewrite the entire code sequence starting from the problematic decision point, effectively correcting the execution trajectory. These emergent behaviors, documented in Appendix H, demonstrate how agent autonomy strengthens system robustness against the inherent variability of genomic data.

7 Conclusion

We presented **GenoMAS**, a multi-agent system that advances automated gene expression analysis through three key contributions: guided planning that balances structured workflows with autonomous adaptation, heterogeneous LLM architecture that leverages complementary strengths, and dynamic memory mechanisms for efficient code reuse. Evaluated on the GenoTEX benchmark, GenoMAS reached SOTA performance in GTA analysis while substantially reducing computational costs. Future work will explore multimodal data integration and more sophisticated planning algorithms.

Limitations

While GenoMAS demonstrates strong performance on gene expression analysis, several considerations merit discussion regarding its broader applicability and future development.

First, our framework inherits both the capabilities and limitations of its underlying LLMs. As these foundation models evolve, GenoMAS stands to benefit from improvements in reasoning depth and domain knowledge. However, this dependency also means that the system's reliability is bounded by the current state of LLM development. Our heterogeneous agent architecture partially addresses this by strategically combining models with complementary strengths, yet systematic evaluation remains necessary as new model generations emerge.

Second, the trade-off between flexibility and efficiency represents a fundamental consideration for agentic scientific systems. While GenoMAS achieves notable cost reductions relative to prior agentic approaches, the iterative nature of agent-based planning and code generation introduces computational overhead compared to fixed pipelines. For scenarios prioritizing maximum throughput over adaptability, such as production-scale analyses with well-characterized data, practitioners may find value in distilling successful agent workflows into optimized static implementations.

Finally, our evaluation focuses on regression-based gene-trait association analysis within human transcriptomics. Extending GenoMAS to encompass broader analytical paradigms (e.g., causal inference, network analysis) or integrating multi-omics modalities would require expanding both the agent capabilities and the domain knowledge bases. The modular architecture facilitates such extensions, though each would necessitate domain-specific validation to ensure scientific rigor.

Ethical considerations

The automation of scientific analysis through AI agents raises important considerations regarding research integrity, reproducibility, and responsible deployment.

Data privacy and security GenoMAS operates on publicly available genomic datasets from established repositories (GEO, TCGA) that have undergone institutional review and de-identification procedures. Our framework does not collect, store, or transmit private genetic information. However, practitioners applying GenoMAS to proprietary or sensitive datasets should ensure compliance with relevant data protection regulations (e.g., GDPR, HIPAA) and institutional ethical guidelines. The system's reliance on external LLM APIs necessitates careful consideration of data transmission policies, particularly when cloud-based models process analysis code that may contain dataset identifiers or intermediate results.

Scientific rigor and interpretability While GenoMAS automates complex analytical workflows, the responsibility for validating biological conclusions remains with human researchers. Automated systems can efficiently process large-scale data and generate statistical associations, but interpreting these findings within broader biological contexts requires domain expertise and critical evaluation. We emphasize that GenoMAS serves as an analytical tool to assist, not replace, scientific judgment. The system's self-documentation mechanisms (post-task notes, execution logs) are designed to facilitate expert oversight and enable researchers to understand and verify the analytical decisions made by agents.

Potential for misuse and dual-use concerns The democratization of sophisticated bioinformatics capabilities through accessible AI systems offers substantial benefits for research accessibility and reproducibility. However, this accessibility also warrants consideration of potential misuse. While gene expression analysis itself represents standard computational biology practice, easier access to analytical tools could theoretically lower barriers for conducting research without appropriate biological training or ethical oversight. We advocate for responsible deployment within established research frameworks, where automated analyses complement rather than circumvent traditional scientific training, peer review, and institutional oversight mechanisms.

References

Heba Abusamra. 2013. A comparative study of feature selection and classification methods for gene expression data of glioma. *Procedia Computer Science*, 23:5–14.

Christof Angermueller, Tanel Pärnamaa, Leopold Parts, and Oliver Stegle. 2016. Deep learning for computational biology. *Molecular systems biology*, 12(7):878.

Anthropic. 2024. Claude code: Agentic coding tool. Command line tool for agentic coding.

Anthropic. 2024. Introducing claude 4: Our most intelligent model. Accessed: 2025-01-22.

Anysphere. 2024. Cursor: The ai code editor. AI-powered code editor.

Jinheon Baek, Sujay Kumar Jauhar, Silviu Cucerzan, and Sung Ju Hwang. 2024. Researchagent: Iterative research idea generation over scientific literature with large language models. *arXiv preprint arXiv:2404.07738*.

Maciej Besta, Nils Blach, Ales Kubicek, Robert Gerstenberger, Lukas Gianinazzi, Joanna Gajda, Tomasz Lehmann, Michal Podstawski, Hubert Niewiadomski, Piotr Nyczyk, and Torsten Hoefler. 2023. Graph of thoughts: Solving elaborate problems with large language models. *arXiv preprint arXiv: 2308.09687*.

Andres M Bran, Sam Cox, Oliver Schilter, Carlo Baldassari, Andrew D White, and Philippe Schwaller. 2023. Chemcrow: Augmenting large-language models with chemistry tools. *arXiv preprint arXiv: 2304.05376*.

G. R. Brown, V. Hem, K. S. Katz, M. Ovetsky, C. Wallin, O. Ermolaeva, I. Tolstoy, T. Tatusova, K. D. Pruitt, and D. R. Maglott. 2015. Gene: a gene-centered information resource at NCBI. *Nucleic Acids Research*, 43(D1):D36–D42.

Olivier Carrette, Isabelle Demalte, Alexander Scherl, Ozgur Yalkinoglu, Garry Corthals, Peter Burkhard, Denis F Hochstrasser, and Jean-Charles Sanchez. 2003. A panel of cerebrospinal fluid potential biomarkers for the diagnosis of alzheimer's disease. *Proteomics*, 3(8):1486–1494.

Mert Cemri, Melissa Z Pan, Shuyi Yang, Lakshya A Agrawal, Bhavya Chopra, Rishabh Tiwari, Kurt Keutzer, Aditya Parameswaran, Dan Klein, Kannan Ramchandran, Matei Zaharia, Joseph E Gonzalez, and Ion Stoica. 2025. Why do multi-agent llm systems fail? *arXiv preprint arXiv:2503.13657*.

Volkan Çetin and Oktay YILDIZ. 2022. A comprehensive review on data preprocessing techniques in data analysis. *Pamukkale Üniversitesi Mühendislik Bilimleri Dergisi*, 28(2):299–312.

Xiaoyu Chen, Tianze Wang, Tianyi Liu, Zhengyang Guo, Xiaojun Li, Meng Qu, and Tuo Zhao. 2025. A survey on hypothesis generation for scientific discovery in the era of large language models. *arXiv preprint arXiv:2504.05496*.

Zui Chen, Lei Cao, Sam Madden, Tim Kraska, Zeyuan Shang, Ju Fan, Nan Tang, Zihui Gu, Chunwei Liu, and Michael Cafarella. 2023. Seed: Domain-specific data curation with large language models. *arXiv preprint arXiv:2310.00749*.

Emily Clough and Tanya Barrett. 2016. The gene expression omnibus database. *Methods in Molecular Biology*, 1418:93–110.

Ana Conesa, Pedro Madrigal, Sonia Tarazona, David Gomez-Cabrero, Alejandra Cervera, Andrew McPherson, Michał Wojciech Szcześniak, Daniel J Gaffney, Laura L Elo, Xuegong Zhang, and Ali Mortazavi. 2016. A survey of best practices for rna-seq data analysis. *Genome Biology*, 17:13.

James P Cook, Anubha Mahajan, and Andrew P Morris. 2017. Guidance for the utility of linear models in meta-analysis of genetic association studies of binary phenotypes. *European Journal of Human Genetics*, 25(2):240–245.

Shirley David, Philipp Kümpers, Pamela van Slyke, and Samir M Parikh. 2009. Angiopoietin 2 and cardiovascular disease in dialysis and kidney transplantation. *American Journal of Kidney Diseases*, 53(5):770–778.

Google DeepMind. 2025a. Gemini 2.5 flash. Fast performance thinking model for everyday tasks.

Google DeepMind. 2025b. Gemini 2.5 pro. Advanced thinking model with Deep Think mode for complex reasoning tasks.

DeepSeek-AI, Daya Guo, Dejian Yang, Haowei Zhang, Junxiao Song, Ruoyu Zhang, Runxin Xu, Qihao Zhu, Shirong Ma, Peiyi Wang, Xiao Bi, Xiaokang Zhang, Xingkai Yu, Yu Wu, Z.F. Wu, Zhibin Gou, Zhihong Shao, Zhuoshu Li, Ziyi Gao, and 81 others. 2025. Deepseek-r1: Incentivizing reasoning capability in llms via reinforcement learning. *arXiv preprint arXiv:2501.12948*.

Yuqi Deng, Katherine N Theken, and Colin R Lee. 2011. Cyp1b1 polymorphisms and risk of hypertension. *Clinical Science*, 120(4):153–164.

Yihong Dong, Xue Jiang, Zhi Jin, and Ge Li. 2023. Self-collaboration code generation via chatgpt. *arXiv preprint arXiv: 2304.07590*.

Yilun Du, Shuang Li, Antonio Torralba, Joshua B. Tenenbaum, and Igor Mordatch. 2023. Improving factuality and reasoning in language models through multiagent debate. *arXiv preprint arXiv: 2305.14325*.

Yaohua Duan, Robert A Gross, and Shey-Shing Sheu. 2014. Par-4 promotes alzheimer's disease-like neurodegeneration by upregulating bace1 expression. *Neurobiology of Aging*, 35(6):1473–1480.

Nora Franceschini, Ervin Fox, Zhe Zhang, Todd L Edwards, Michael A Nalls, Yun Ju Sung, Karen L Schwander, Sekar Kathiresan, Benjamin F Voight, Hyun Min Kang, and 1 others. 2013. Genome-wide association analysis of blood-pressure traits in african-ancestry individuals reveals common associated genes in african and non-african populations. *American Journal of Human Genetics*, 93(3):545–554.

Tessa E Fuhrer, Thulani H Palpagama, Henry J Waldvogel, Bronwen JL Synek, Clinton Turner, Richard LM Faull, and Andrea Kwakowsky. 2017. Altered gaba$_b$ receptor signaling in early alzheimer's disease. *Neuropharmacology*, 122:76–88.

Johann A Gagnon-Bartsch and Terence P Speed. 2012. Using control genes to correct for unwanted variation in microarray data. *Biostatistics*, 13(3):539–552.

Debashis Ghosh and Arul M Chinnaiyan. 2005. Classification and selection of biomarkers in genomic data using lasso. *Journal of Biomedicine and Biotechnology*, 2005(2):147.

Geoffrey S Ginsburg and Kathryn A Phillips. 2018. Precision medicine: from science to value. *Health Affairs*, 37(5):694–701.

Qing Guo, Weihua Fu, Bryce L Sopher, Marc W Miller, Carol B Ware, George M Martin, and Mark P Mattson. 1998. Par-4 is a mediator of neuronal degeneration associated with the pathogenesis of alzheimer disease. *Nature Medicine*, 4(8):957–962.

James A Hanley and Barbara J McNeil. 1982. The meaning and use of the area under a receiver operating characteristic (roc) curve. *Radiology*, 143(1):29–36.

Charles Roy Henderson. 1950. Estimation of genetic parameters. *Biometrics*, 6(2):186–190.

Lu Hong and Scott E Page. 2004. Groups of diverse problem solvers can outperform groups of high-ability problem solvers. *Proceedings of the National Academy of Sciences*, 101(46):16385–16389.

Sirui Hong, Yizhang Lin, Bang Liu, Bangbang Liu, Binhao Wu, Ceyao Zhang, Chenxing Wei, Danyang Li, Jiaqi Chen, Jiayi Zhang, Jinlin Wang, Li Zhang, Lingyao Zhang, Min Yang, Mingchen Zhuge, Taicheng Guo, Tuo Zhou, Wei Tao, Xiangru Tang, and 8 others. 2024. Data interpreter: An llm agent for data science. *arXiv preprint arXiv:2402.18679*.

Sirui Hong, Mingchen Zhuge, Jonathan Chen, Xiawu Zheng, Yuheng Cheng, Ceyao Zhang, Jinlin Wang, Zili Wang, Steven Ka Shing Yau, Zijuan Lin, Liyang Zhou, Chenyu Ran, Lingfeng Xiao, Chenglin Wu, and Jürgen Schmidhuber. 2023. Metagpt: Meta programming for a multi-agent collaborative framework. *arXiv preprint arXiv: 2308.00352*.

Shengran Hu, Cong Lu, and Jeff Clune. 2024. Automated design of agentic systems. *arXiv preprint arXiv:2408.08435*.

Jie Huang, Xinyun Chen, Swaroop Mishra, Huaixiu Steven Zheng, Adams Wei Yu, Xinying Song, and Denny Zhou. 2023. Large language models cannot self-correct reasoning yet. *arXiv preprint arXiv:2310.01798*.

Kexing Huang, Serena Zhang, Hanchen Wang, Auro Bhattacharjee, Yingzhou Lu, Ming Wen, Jure Yang, and Jiaxuan Ye. 2025. Biomni: A general-purpose biomedical ai agent. *bioRxiv preprint bioRxiv:2025.05.30.656746*.

Wei Itu, Yang-Yang Liu, Jinhua Wang, Lin Li, Qingjin Kong, Yingjie Sun, and Yue Zhang. 2018. Igfbp-5 induces neuronal apoptosis by regulating gsk-3β signaling and autophagy. *Experimental Cell Research*, 365(2):169–178.

Shuyi Jia, Tianle Huo, and Yang Zeng. 2024. Llmatdesign: Autonomous materials discovery with large language models. *arXiv preprint arXiv:2406.13163*.

W Evan Johnson, Cheng Li, and Ariel Rabinovic. 2007. Adjusting batch effects in microarray expression data using empirical bayes methods. *Biostatistics*, 8(1):118–127.

Iain M Johnstone. 2001. On the distribution of the largest eigenvalue in principal components analysis. *The Annals of statistics*, 29(2):295–327.

Hyeonsu B Kang, Nouran Soliman, Matt Latzke, Joseph Chee Chang, and Jonathan Bragg. 2023. Comlittee: Literature discovery with personal elected author committees. In *Proceedings of the 2023 CHI Conference on Human Factors in Computing Systems*, pages 1–20.

Levon M Khachigian. 2006. Early growth response-1 in cardiovascular pathobiology. *Circulation Research*, 98(2):186–191.

Md Mizanur Rahman Khondoker. 2006. *Statistical methods for pre-processing microarray gene expression data*. Ph.D. thesis, University of Edinburgh.

Takashi Kohno, Hideki Ichikawa, Yasushi Totoki, Katsuyuki Yasuda, Masato Hiramoto, Takeshi Nammo, Hiromi Sakamoto, Koji Tsuta, Koji Furuta, Yasuhide Shimada, and 1 others. 2012. Kif5b-ret fusions in lung adenocarcinoma. *Nature Medicine*, 18(3):375–377.

Beverly Kyalwazi, Christina Yau, Michael J Campbell, Toshio F Yoshimatsu, A Jo Chien, Anne M Wallace, Andres Forero-Torres, Lajos Pusztai, Erin D Ellis, Kathy S Albain, and 1 others. 2023. Race, gene expression signatures, and clinical outcomes of patients with high-risk early breast cancer. *JAMA Network Open*, 6(12):e2349646–e2349646.

Ehsan Latif, Ramviyas Parasuraman, and Xiaoming Zhai. 2024. Physicsassistant: An llm-powered interactive learning robot for physics lab investigations. In *2024 33rd IEEE International Conference on Robot and Human Interactive Communication (ROMAN)*, pages 864–871. IEEE.

Myung-Eun Lee, Mandeep S Dhadly, David H Temizer, James A Clifford, Masanori Yoshizumi, and Thomas Quertermous. 1995. Early growth response factor-1 mediates the cholesterol-induced smooth muscle cell

proliferation. *Proceedings of the National Academy of Sciences*, 92(21):10159–10163.

Szu-Yuan Lee, Yi-Wen Chen, Jia-Fwu Hsiao, Hung-Chun Chen, Yuh-Feng Lin, and Kuang-Hung Hsu. 2014. Angiopoietin-2 is associated with an increased risk of thrombotic events in chronic haemodialysis patients. *Nephrology Dialysis Transplantation*, 29(7):1400–1406.

Jeffrey T Leek, Robert B Scharpf, Héctor Corrada Bravo, David Simcha, Benjamin Langmead, W Evan Johnson, Donald Geman, Keith Baggerly, and Rafael A Irizarry. 2010. Tackling the widespread and critical impact of batch effects in high-throughput data. *Nature Reviews Genetics*, 11(10):733–739.

Daniel Levy, Georg B Ehret, Kenneth Rice, Germaine C Verwoert, Lenore J Launer, Abbas Dehghan, Nicole L Glazer, Alanna C Morrison, Andrew D Johnson, Thor Aspelund, and 1 others. 2009. Genome-wide association study of blood pressure and hypertension. *Nature Genetics*, 41(6):677–687.

Gui Li, Nicole Bien-Ly, Yadong Andrews-Zwilling, Qin Xu, Anthony Bernardo, Karen Ring, Brian Halabisky, Chong Deng, Robert W Mahley, and Yadong Huang. 2016. Gabaergic interneuron dysfunction impairs hippocampal neurogenesis in adult apolipoprotein e4 knockin mice. *Cell Stem Cell*, 19(5):634–645.

Yifan Li, Yanming Zhang, and Xiang Chen. 2024. Hlebench: A holistic evaluation benchmark for large language models in higher-level reasoning. *arXiv preprint arXiv:2406.10833*.

Alan Wee-Chung Liew, Ngai-Fong Law, and Hong Yan. 2011. Missing value imputation for gene expression data: computational techniques to recover missing data from available information. *Briefings in bioinformatics*, 12(5):498–513.

Doron Lipson, Marzia Capelletti, Roman Yelensky, Garrett Otto, Alexander Parker, Mirna Jarosz, James A Curran, Shanker Balasubramanian, Tim Bloom, Kristina W Brennan, and 1 others. 2012. Identification of new alk and ret gene fusions from colorectal and lung cancer biopsies. *Nature Medicine*, 18(3):382–384.

Haoyang Liu, Shuyu Chen, Ye Zhang, and Haohan Wang. 2025. Genotex: A benchmark for automated gene expression data analysis in alignment with bioinformaticians. *Preprint*, arXiv:2406.15341.

Sizhe Liu, Yizhou Lu, Siyu Chen, Xiyang Hu, Jieyu Zhao, Yingzhou Lu, and Yue Zhao. 2024. Drugagent: Automating ai-aided drug discovery programming through llm multi-agent collaboration. *arXiv preprint arXiv:2411.15692*.

Gervaise Loirand, Piere Guerin, and Pierre Pacaud. 2006. Rho kinases in cardiovascular physiology and pathophysiology. *Circulation Research*, 98(3):322–334.

Chris Lu, Cong Lu, Robert Tjarko Lange, Jakob Foerster, Jeff Clune, and David Ha. 2024. The ai scientist: Towards fully automated open-ended scientific discovery. *arXiv preprint arXiv:2408.06292*.

Junyu Luo, Weizhi Zhang, Ye Yuan, Yusheng Zhao, Junwei Yang, Yiyang Gu, Bohan Wu, Binqi Chen, Ziyue Qiao, Qingqing Long, and 1 others. 2025. Large language model agent: A survey on methodology, applications and challenges. *arXiv preprint arXiv:2503.21460*.

Hao Ma, Tianyi Hu, Zhiqiang Pu, Liu Boyin, Xiaolin Ai, Yanyan Liang, and Min Chen. 2024. Coevolving with the other you: Fine-tuning llm with sequential cooperative multi-agent reinforcement learning. *Advances in Neural Information Processing Systems*, 37:15497–15525.

Aman Madaan, Niket Tandon, Prakhar Gupta, Skyler Hallinan, Luyu Gao, Sarah Wiegreffe, Uri Alon, Nouha Dziri, Shrimai Prabhumoye, Yiming Yang, and 1 others. 2023. Self-refine: Iterative refinement with self-feedback. *arXiv preprint arXiv:2303.17651*.

James D McKay, Rayjean J Hung, Valerie Gaborieau, Paolo Boffetta, Amélie Chabrier, Graham Byrnes, David Zaridze, Anush Mukeria, Neonila Szeszenia-Dabrowska, Jolanta Lissowska, and 1 others. 2008. Lung cancer susceptibility locus at 5p15.33. *Nature Genetics*, 40(12):1404–1406.

Xuefei Ning, Zinan Lin, Zixuan Zhou, Huazhong Yang, and Yu Wang. 2023. Skeleton-of-thought: Large language models can do parallel decoding. *arXiv preprint arXiv:2307.15337*.

Novita AI. 2025. Novita ai: Deploy ai models effortlessly with our simple api. https://novitaai.com. Accessed: 2025-02-17.

OpenAI. 2023. Gpt-4 technical report. *PREPRINT*.

OpenAI. 2025a. Openai o3. Accessed: 2025-01-22.

OpenAI. 2025b. Openai o3-mini. Latest Large language model of OpenAI.

Scott E Page. 2007. The difference: How the power of diversity creates better groups, firms, schools, and societies. *Princeton University Press*.

Cheng Qian, Emre Can Acikgoz, Qi He, Hongru Wang, Xiusi Chen, Dilek Hakkani-Tür, Gokhan Tur, and Heng Ji. 2025. Toolrl: Reward is all tool learning needs. *arXiv preprint arXiv:2504.13958*.

Yujia Qin, Shihao Liang, Yining Ye, Kunlun Zhu, Lan Yan, Yaxi Lu, Yankai Lin, Xin Cong, Xiangru Tang, Bill Qian, Sihan Zhao, Lauren Hong, Runchu Tian, Ruobing Xie, Jie Zhou, Mark Gerstein, Dahai Li, Zhiyuan Liu, and Maosong Sun. 2023. Toolllm: Facilitating large language models to master 16000+ real-world apis. *Preprint*, arXiv:2307.16789.

Qwen Team. 2025. Qwen3-235b-a22b. A 235B parameter Mixture-of-Experts model with 22B activated parameters by Alibaba Cloud.

Thorunn Rafnar, Patrick Sulem, Simon N Stacey, Frank Geller, Julius Gudmundsson, Asgeir Sigurdsson, Margret Jakobsdottir, Hafdis Helgadottir, Steingrimur Thorlacius, Katja KH Aben, and 1 others. 2009. Sequence variants at the tert-clptm1l locus associate with many cancer types. *Nature Genetics*, 41(2):221–227.

Sara Raimondi, Veronica Paracchini, Herman Autrup, Juan M Barros-Dios, Simone Benhamou, Paolo Boffetta, Marie L Cote, Ioanna A Dialyna, Vita Dolzan, Rosa Filiberti, and 1 others. 2009. Meta-analysis of the cyp1a1 mspi polymorphism and lung cancer susceptibility. *Mutagenesis*, 24(2):119–124.

David Rein, Betty L Hou, Asa Cooper Stickland, Jackson Petty, Richard Yuanzhe Pang, Julien Dirani, Julian Michael, and Samuel R Bowman. 2023. Gpqa: A graduate-level google-proof q&a benchmark. *arXiv preprint arXiv:2311.12022*.

Diletta Rosati, Matteo Palmieri, Giorgia Brunelli, Andrea Morrione, Francesco Iannelli, Elisa Frullanti, and Antonio Giordano. 2024. Differential gene expression analysis pipelines and bioinformatic tools for the identification of specific biomarkers: A review. *Computational and Structural Biotechnology Journal*, 23:1154–1168.

RunPod. 2024. Runpod: The cloud built for ai. https://www.runpod.io/. Accessed: 2024-06-06.

Eric W Sayers, Evan E Bolton, J Rodney Brister, Kathi Canese, Jessica Chan, Donald C Comeau, Ryan Connor, Kathryn Funk, Chris Kelly, Sunghwan Kim, and 1 others. 2022. Database resources of the national center for biotechnology information. *Nucleic Acids Research*, 50(D1):D20–D26.

Samuel Schmidgall, Jascha Achterberg, Thomas Knutins, Louis Kirsch, Rojin Heira, Cher Rui Ahmad, and Francesco Iacobacci. 2025. Agent laboratory: Using llm agents as research assistants. *arXiv preprint arXiv:2501.04227*.

Minjie Shen and Qikai Yang. 2025. From mind to machine: The rise of manus ai as a fully autonomous digital agent. *Preprint*, arXiv:2505.02024.

Jun Shi and Lei Wei. 2013. Rho-kinase in the regulation of cell death and survival. *Archivum Immunologiae et Therapiae Experimentalis*, 61(3):209–220.

Xingxiang Shi, Sanhong Zhou, Zhenzhen Wang, Zhen Zhou, and Zhou Wang. 2008. Cyp1a1 and gstm1 polymorphisms and lung cancer risk in chinese populations: a meta-analysis. *Lung Cancer*, 59(2):155–163.

Rory Stark, Marta Grzelak, and James Hadfield. 2019. Rna sequencing: the teenage years. *Nature Reviews Genetics*, 20(11):631–656.

Aravind Subramanian, Pablo Tamayo, Vamsi K Mootha, Sayan Mukherjee, Benjamin L Ebert, Michael A Gillette, Amanda Paulovich, Scott L Pomeroy, Todd R Golub, Eric S Lander, and 1 others. 2005. Gene set enrichment analysis: a knowledge-based approach for interpreting genome-wide expression profiles. *Proceedings of the National Academy of Sciences*, 102(43):15545–15550.

Kyle Swanson, Wesley Wu, Nash L Bulaong, John E Pak, and James Zou. 2024. The virtual lab: Ai agents design new sars-cov-2 nanobodies with experimental validation. *bioRxiv*, pages 2024–11.

Open Targets. 2025. Open targets platform. Accessed: February 24, 2025.

Robert Tibshirani. 1996. Regression shrinkage and selection via the lasso. *Journal of the Royal Statistical Society Series B: Statistical Methodology*, 58(1):267–288.

Katarzyna Tomczak, Patrycja Czerwińska, and Maciej Wiznerowicz. 2015. The cancer genome atlas (tcga): an immeasurable source of knowledge. *Contemporary Oncology (Poznan)*, 19(1A):A68–77.

Haohan Wang, Bryon Aragam, and Eric P Xing. 2022. Trade-offs of linear mixed models in genome-wide association studies. *Journal of Computational Biology*, 29(3):233–242.

Lei Wang, Chen Ma, Xueyang Feng, Zeyu Zhang, Hao Yang, Jingsen Zhang, Zhiyuan Chen, Jiakai Tang, Xu Chen, Yankai Lin, and 1 others. 2023. A survey on large language model based autonomous agents. *arXiv preprint arXiv:2308.11432*.

Peiran Wang, Yaoning Yu, Ke Chen, Xianyang Zhan, and Haohan Wang. 2025. Large language model-based data science agent: A survey. In submission.

Xingyao Wang, Yangyi Chen, Lifan Yuan, Yizhe Zhang, Yunzhu Li, Hao Peng, and Heng Ji. 2024. Executable code actions elicit better llm agents. *arXiv preprint arXiv:2402.01030*.

Chih-Hsuan Wei, Alexis Allot, Kevin Riehle, Aleksandar Milosavljevic, and Zhiyong Lu. 2023. Gnorm2: an improved gene name recognition and normalization system. *Bioinformatics*, 39(10):btad599.

Jason Wei, Xuezhi Wang, Dale Schuurmans, Maarten Bosma, Fei Xia, Ed Chi, Quoc V Le, Denny Zhou, and 1 others. 2022. Chain-of-thought prompting elicits reasoning in large language models. *Advances in Neural Information Processing Systems*, 35:24824–24837.

Qingyun Wu, Gagan Bansal, Jieyu Zhang, Yiran Wu, Shaokun Zhang, Erkang Zhu, Beibin Li, Li Jiang, Xiaoyun Zhang, and Chi Wang. 2023. Autogen: Enabling next-gen llm applications via multi-agent conversation framework. *arXiv preprint arXiv:2308.08155*.

Tong Tong Wu, Yi Fang Chen, Trevor Hastie, Eric Sobel, and Kenneth Lange. 2009. Genome-wide association analysis by lasso penalized logistic regression. *Bioinformatics*, 25(6):714–721.

Zhiheng Xi, Senjie Jin, Yuhao Zhou, Rui Zheng, Songyang Gao, Tao Gui, Qi Zhang, and Xuanjing Huang. 2023. Self-polish: Enhance reasoning in large language models via problem refinement. *arXiv preprint arXiv:2305.14497*.

Shunyu Yao, Dian Yu, Jeffrey Zhao, Izhak Shafran, Thomas L Griffiths, Yuan Cao, and Karthik Narasimhan. 2023. Tree of thoughts: Deliberate problem solving with large language models. *arXiv preprint arXiv:2305.10601*.

Rui Ye, Wenhao Zhang, Jingyi Chen, Meng Xue, Zheng Gao, Yong Zhang, and Hao Chen. 2025. Mas-gpt: Training llms to build llm-based multi-agent systems. *arXiv preprint arXiv:2503.03686*.

Asaf Yehudai, Liangwei Huang, Ethan Arik, Minglei Yang, Zihao Yang, Nayel Khattab, Yuhan Liang, and Changyu Yang. 2025. Survey on evaluation of llm-based agents. *arXiv preprint arXiv:2503.16416*.

Zhangyue Yin, Qiushi Sun, Cheng Chang, Qipeng Guo, Junqi Dai, Xuan-Jing Huang, and Xipeng Qiu. 2023. Exchange-of-thought: Enhancing large language model capabilities through cross-model communication. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pages 15135–15153.

Jianming Yu, Gael Pressoir, William H Briggs, Irie Vroh Bi, Masanori Yamasaki, John F Doebley, Michael D McMullen, Brandon S Gaut, Dahlia M Nielsen, James B Holland, and 1 others. 2006. A unified mixed-model method for association mapping that accounts for multiple levels of relatedness. *Nature genetics*, 38(2):203–208.

Guangjie Zhang, Shinji Kodani, and Bruce D Hammock. 2014. Cytochrome p450-derived eicosanoids: the neglected endogenous cardiovascular metabolites. *Acta Pharmacologica Sinica*, 35(4):512–522.

Kunlun Zhu, Hongyi Du, Zhaochen Hong, Xiaocheng Yang, Shuyi Guo, Zhe Wang, Zhenhailong Wang, Cheng Qian, Xiangru Tang, Heng Ji, and Jiaxuan You. 2025a. Multiagentbench: Evaluating the collaboration and competition of llm agents. *arXiv preprint arXiv:2503.01935*.

Minjun Zhu, Yixuan Weng, Linyi Yang, and Yue Zhang. 2025b. Deepreview: Improving llm-based paper review with human-like deep thinking process. *Preprint*, arXiv:2503.08569.

Tianchi Zhuge, Yuzhen Zhao, and Hongyang Li. 2025. Orchestra: Orchestrating multiple llm agents through model heterogeneity and role specialization. *arXiv preprint arXiv:2501.01234*.

Terry Yue Zhuo, Minh Chien Vu, Jenny Chim, Han Hu, Chunyang Fang, Yuchen Gao, Junjie Gao, Zenglin Wu, Lingming Xia, Jiayi An, and 1 others. 2024. Llm-based multi-agent systems for software engineering: Literature review, vision, and the road ahead. *ACM Transactions on Software Engineering and Methodology*.

Supplementary Material

The supplementary material is organized as follows:

- Appendix A presents test cases showing fundamental limitations of existing autonomous agent methods on gene expression data analysis.

- Appendix B describes the communication protocols and messaging mechanisms in GenoMAS.

- Appendix C presents the task-specific guidelines and action unit prompts for GEO and TCGA preprocessing.

- Appendix D details the guided planning framework and metaprompts for programming agents.

- Appendix E presents the code generation, review, and domain consultation mechanisms with their metaprompts.

- Appendix F analyzes the memory and code reuse efficiency in GenoMAS.

- Appendix G presents biological validation case studies, demonstrating that GenoMAS identifies scientifically meaningful gene-trait associations.

- Appendix H presents some examples of agent autonomy in GenoMAS.

- Appendix I presents some examples of notes written by agents.

A   Fundamental Limitations of Existing Autonomous Agent Methods

Recent advances in LLM-based agents have introduced numerous methods and products promising general-purpose automation with full autonomy. These systems handle task decomposition, planning, and multi-agent collaboration with minimal user input. To evaluate their applicability to gene expression analysis, we systematically tested six representative agents: three open-source systems (Biomni (Huang et al., 2025), AutoGen (Wu et al., 2023), MetaGPT (Hong et al., 2023)) and three proprietary systems (Claude Code (Anthropic, 2024), Cursor (Anysphere, 2024), Manus (Shen and Yang, 2025)). For all agents, we use Claude Sonnet 4 (Thinking) with a thinking budget of 8192 tokens as the underlying language model. This configuration

represents the best performing setting in our end-to-end evaluation with homogeneous LLM configurations (achieving F_1 of 52.98%), and most of these agents do not support heterogeneous multi-model configurations. Our experiments reveal that all these methods face fundamental limitations when applied to gene expression data analysis due to insufficient mechanisms for precise procedural control.

Among tested agents, Biomni incorporates 150 specialized biomedical tools, 105 software packages, and 59 databases with carefully designed tool retrieval mechanisms. This comprehensive biomedical specialization demonstrates the strongest domain adaptation among tested systems, yielding an F_1 score of 14.82% in our experiments (Table 1 in the main paper), substantially higher than other agents but still far below GenoMAS (60.48%) and the previous best method GenoAgent (43.63%).

This performance gap likely stems from a fundamental difference in design philosophy: while Biomni leverages full agent autonomy to tackle diverse biomedical tasks with minimal user input, we target robust automation of more fully specified workflows with a higher demand for scientific rigor. As such, Biomni is not equipped with the context management mechanisms to dynamically plan each step based on task context and user guidelines while considering the complex inter-dependencies between steps. Furthermore, although Biomni provides local quality control through its self-critic mechanism, it is not designed to detect and recover from systematic errors at the global workflow level, where early methodological choices cascade through dozens of interdependent operations. These limitations underscore that reliable gene expression analysis requires the guided planning and structured orchestration that motivate our design of GenoMAS.

The remaining five agents, designed for open-domain or general programming tasks, consistently produce invalid analyses across test scenarios. Their failure rates prevent meaningful inclusion in quantitative benchmarks for end-to-end analysis.

Our analysis identifies two critical limitations in existing autonomous agents:

Insufficient guidance interpretation: General prompts prove inadequate for guiding agents through the complex analytical requirements of gene expression data. Agents frequently make consequential errors early in the workflow that prop-

agate through subsequent steps, resulting in scientifically invalid outputs. This demonstrates the necessity of incorporating user-specified, domain-trusted guidelines into agent architectures.

Absence of procedural control mechanisms: Even when provided with detailed guidelines and Action Unit specifications, current agents lack mechanisms to ensure adherence to prescribed workflows. They cannot perform context-aware planning to identify deviations from expected procedures or recover from errors at the workflow level. This absence of precise procedural control renders them unsuitable for automation of gene expression analysis, where methodological rigor directly impacts scientific validity.

The remainder of this section presents concrete examples demonstrating these limitations in preprocessing GEO datasets. We focus on three cohorts for the trait 'Hypertension': GSE77627, GSE117261, and GSE256539. These cohorts contain complete information necessary for analysis and were successfully preprocessed by both human experts in the benchmark (Liu et al., 2025) and GenoMAS. For each agent, we provide results from two prompt conditions: (1) general instructions and (2) detailed instructions augmented with our guidelines and Action Unit specifications (provided in Appendix C).

A.1 Prompt Conditions

A.1.1 General Prompt

We use the following general prompt, with minor modifications to adapt to the agent-specific I/O interface:

```
Please help me preprocess the cohort
    dataset.
I need to get a complete, linked
    dataset where each row represents
     a sample and each column
    represents a feature.
The row index should be the sample ID
    . The columns should include and
    only include the following:
- The trait represented as a binary
    or continuous variable, whichever
     is more suitable. If it is
    binary, use 1 to represent
    positive and 0 as control. Use
    the trait name as the column name
    .
- The sample's age (if available), a
    float or integer representing the
     age in years. Use "Age" as the
    column name.
- The sample's gender (if available),
     a binary variable with 0 for
    female and 1 for male. Use "
    Gender" as the column name.
```

```
- The expression values of genes,
    with gene symbols as column names
    .
```

A.1.2 Detailed Prompt

The general prompt augmented with our task-specific guidelines, followed by the reminder:

```
Below are more detailed descriptions
    about some of the steps in the
    guidelines. You are free to
    selectively execute all or some
    of them based on task context,
    and decide the order that is best
     for completing the task in
    accordance with the above
    guidelines.
```

This reminder is then followed by the Action Unit instructions, emphasizing agents' flexibility to plan and selectively execute based on context.

A.2 Biomni Examples

Despite incorporating specialized biomedical tools, Biomni demonstrates fundamental limitations in understanding disease biology and correctly interpreting clinical phenotypes. The following example from GSE77627 illustrates how these limitations manifest in both prompt conditions.

A.2.1 GSE77627: Misinterpretation of Portal Hypertension Phenotypes

This dataset studies portal hypertension, a condition characterized by elevated blood pressure in the portal venous system. The study includes three liver groups: HNL (Histologically Normal Livers), INCPH (Idiopathic Non-Cirrhotic Portal Hypertension), and LC (Liver Cirrhosis). Both INCPH and LC represent different etiologies of portal hypertension, while HNL serves as the healthy control group.

Under the general prompt condition, Biomni implements the following erroneous trait conversion:

```
def convert_trait(value):
    """Convert trait values to binary
        (INCPH=1, others=0)"""
    if value is None:
        return None
    # Extract value after colon
    if ':' in str(value):
        val = str(value).split(':')
            [1].strip()
    else:
        val = str(value).strip()

    # Convert INCPH to 1 (positive),
        others to 0 (control)
    if val == 'INCPH':
        return 1
```

```
        elif val in ['HNL', 'LC']:  #
            Critical error: LC is portal
            hypertension, not control <-
                return 0
        else:
            return None
```

This fundamental misinterpretation reveals a critical failure to understand disease biology. Liver cirrhosis accounts for approximately 90% of portal hypertension cases in Western countries and represents the most common etiology of this condition. By misclassifying LC samples as controls, Biomni not only demonstrates inadequate biomedical knowledge but also dramatically alters the statistical composition of the dataset. The incorrect classification creates a dataset with only 18 cases (INCPH alone) versus 36 controls (HNL and LC combined), while the scientifically correct classification would yield 40 cases (both INCPH and LC) versus merely 14 controls (HNL only). This reversal in the case-control ratio fundamentally compromises any downstream analysis. Rather than identifying genes associated with portal hypertension, the misclassified analysis would instead detect genes that distinguish INCPH from a heterogeneous mixture of healthy and cirrhotic livers, rendering the results biologically meaningless.

The error persists even under the detailed prompt condition, where explicit guidelines and domain knowledge are provided. In the general prompt condition, Biomni compounds the misclassification by entirely excluding LC samples from the analysis:

```
# From Biomni's general prompt
    processing
trait_mapping = {
    'HNL': 0,     # Control -
        histologically normal livers
    'INCPH': 1,  # Disease -
        idiopathic non-cirrhotic
        portal hypertension
    'LC': 'exclude'  # Exclude liver
        cirrhosis samples <-
}

# Filter samples and create sample
    metadata
final_sample_metadata = {}
for sample_id, metadata in
    sample_metadata.items():
    liver_group = metadata['
        liver_group']
    if liver_group != 'LC':  #
        Exclude LC samples <-
        final_sample_metadata[
            sample_id] = {
            'INCPH': trait_mapping[
                liver_group],
            'liver_group':
                liver_group
```

```
    }

print(f"Samples after filtering (
    excluding LC): {len(
    final_sample_metadata)}")
# Output: Samples after filtering (
    excluding LC): 32
```

This exclusion strategy eliminates 22 LC samples from the original 54, representing a 40% data loss that severely compromises statistical power. The decision to exclude rather than correctly classify LC samples suggests a fundamental misunderstanding of the biological relationship between cirrhosis and portal hypertension.

Beyond the trait misclassification, Biomni exhibits several additional processing errors that compound the analysis invalidity. The agent fails to normalize gene symbols using standardized databases, a critical step performed by human experts to ensure cross-dataset compatibility. While the human expert code systematically applies gene synonym mapping to standardize identifiers, Biomni retains the raw gene symbols from the platform annotation, potentially introducing inconsistencies in downstream analyses. Furthermore, Biomni omits systematic bias detection and correction procedures. The human expert implementation includes explicit checks for biased features and removes them before final analysis, whereas Biomni proceeds without such quality control measures.

These cascading errors, from fundamental biological misinterpretation to technical processing omissions, illustrate that even specialized biomedical tools cannot compensate for the lack of precise procedural control required for valid scientific analysis. The inability to recognize that different diseases can manifest the same clinical phenotype, combined with the failure to implement standard bioinformatics quality control procedures, renders the autonomous agent's output scientifically unreliable.

A.3 AutoGen Examples

AutoGen, a popular multi-agent conversation framework developed by Microsoft (Wu et al., 2023), demonstrates fundamental limitations when applied to gene expression analysis. While designed to facilitate autonomous agent collaboration through conversational patterns, AutoGen struggles with the precise procedural control required for bioinformatics workflows. The following examples illustrate how agent miscommunication and lack of domain understanding lead to critical anal-

ysis errors.

A.3.1 GSE77627: Agent Coordination Failures in Trait Classification

Under the general prompt condition, AutoGen attempts to coordinate multiple agents for the portal hypertension dataset analysis but fails due to miscommunication between agents about the biological meaning of liver conditions:

```python
# AutoGen multi-agent setup
import autogen

# Define specialized agents
bioinformatics_agent = autogen.
    AssistantAgent(
    name="BioinformaticsExpert",
    system_message="You are a
        bioinformatics expert.
        Analyze gene data."
)

clinical_agent = autogen.
    AssistantAgent(
    name="ClinicalExpert",
    system_message="You are a
        clinical expert. Handle
        phenotype data."
)

# Clinical agent's trait
    interpretation
def analyze_clinical_groups(data):
    """Clinical agent's analysis of
        liver groups"""
    groups = data['liver_group'].
        unique()
    # Agent message: "I see three
        groups: HNL, INCPH, and LC"
    # Agent message: "INCPH is
        clearly the disease of
        interest"
    # Agent message: "LC might be a
        different condition, treating
         as control"   <-

    trait_mapping = {
        'HNL': 0,    # Healthy
            controls
        'INCPH': 1,  # Disease cases
        'LC': 0      # Misclassified
            as control   <-
    }
    return trait_mapping

# Bioinformatics agent accepts
    without domain verification
def process_with_mapping(
    expression_data, trait_mapping):
    """Bioinformatics agent processes
         based on clinical
        interpretation"""
    # Agent message: "Received trait
        mapping from clinical expert"
    # Agent message: "Processing
        expression data with 2-class
        comparison"
    # No validation of biological
        correctness   <-
    return apply_trait_classification
        (expression_data,
        trait_mapping)
```

This example reveals a critical failure in agent coordination. The clinical agent misinterprets liver cirrhosis (LC) as a control condition, and the bioinformatics agent accepts this classification without question. In AutoGen's conversational paradigm, agents tend to defer to each other's "expertise" without implementing cross-validation mechanisms. This leads to the propagation of fundamental biological errors through the analysis pipeline.

Under the detailed prompt condition, AutoGen's conversation-based approach leads to verbose but ineffective deliberation:

```python
# AutoGen conversation with detailed
    guidelines
user_proxy = autogen.UserProxyAgent(
    name="User",
    human_input_mode="NEVER",
    code_execution_config={"work_dir"
        : "analysis"}
)

# Extended conversation pattern
conversation_history = []

# Round 1: Initial interpretation
clinical_agent: "Based on the
    guidelines, I need to classify
    liver groups."
clinical_agent: "INCPH stands for
    Idiopathic Non-Cirrhotic Portal
    Hypertension."
clinical_agent: "This is clearly our
    case group (trait = 1)."

# Round 2: Misguided reasoning
clinical_agent: "LC stands for Liver
    Cirrhosis."
clinical_agent: "Since it's '
    cirrhotic' and INCPH is 'non-
    cirrhotic',"
clinical_agent: "they seem to be
    opposite conditions."   <-
clinical_agent: "Therefore, LC should
     be grouped with HNL as controls.
    "

# Round 3: Bioinformatics agent
    agrees without domain knowledge
bioinformatics_agent: "I accept the
    clinical classification."
bioinformatics_agent: "Proceeding
    with binary trait: INCPH=1,
    others=0."

# No agent questions the biological
    validity   <-
```

The conversational approach, while appearing thorough, actually amplifies the initial misunder-

standing through repeated affirmation between agents. Neither agent possesses the domain knowledge to recognize that both INCPH and LC cause portal hypertension through different mechanisms.

A.3.2 GSE117261: Task Decomposition Without Domain Context

For the GSE117261 dataset, AutoGen's approach to task decomposition fails to identify the critical probe-to-gene mapping requirement:

```python
# AutoGen task decomposition
planner_agent = autogen.
    AssistantAgent(
    name="Planner",
    system_message="Break down data
        preprocessing into subtasks."
)

# Planner's task breakdown
task_list = planner_agent.
    generate_reply(
    messages=[{
        "content": "Preprocess GEO
            series matrix file
            GSE117261",
        "role": "user"
    }]
)

# Generated task list (missing
    critical steps):
# 1. Load series matrix file
# 2. Extract sample metadata
# 3. Extract expression values
# 4. Merge metadata with expression
# 5. Save processed dataset

# Execution by data processing agent
def execute_preprocessing_plan(tasks)
    :
    # Task 3: Extract expression
        values
    expression_df = pd.read_csv(
        matrix_file, sep='\t',
        comment='!')
    expression_df = expression_df.
        set_index('ID_REF')  # Probe
        IDs  <-

    # Task 4: Merge (probe IDs used
        directly as features)
    final_df = pd.concat([metadata_df
        , expression_df.T], axis=1)
        <-

    return final_df  # Contains probe
        IDs, not gene symbols
```

The planner agent, lacking bioinformatics knowledge, fails to include probe-to-gene mapping in the task decomposition. Subsequent agents execute the incomplete plan without recognizing the omission. This demonstrates how AutoGen's strength in task orchestration becomes a weakness when critical domain-specific steps are not identified during planning.

A.4 MetaGPT Examples

MetaGPT, a multi-agent framework emphasizing structured role-based collaboration (Hong et al., 2023), exhibits similar fundamental limitations despite its sophisticated role definitions and standardized operating procedures. The framework's emphasis on software engineering patterns fails to translate effectively to scientific data analysis requirements.

A.4.1 GSE256539: Role-Based Misinterpretation of Clinical Encoding

MetaGPT's role-based architecture assigns specialized responsibilities to different agents. However, this specialization leads to fragmented understanding when processing the GSE256539 IPAH dataset:

```python
# MetaGPT role definitions
class DataAnalyst(Role):
    """Analyzes data patterns and
        structures"""

    def _observe(self):
        return [UserRequirement]

    def _act(self) -> dict:
        # Analyze sample
            characteristics
        sample_chars = self.
            _analyze_characteristics
            ()

        # DataAnalyst observation: "
            Samples have individual
            IDs"
        # Example: "individual: AH014
            ", "individual: UC003"
        # DataAnalyst conclusion: "No
            clear trait information"
            <-

        return {
            "observation": "Dataset
                contains individual
                identifiers only",
            "trait_found": False,
            "recommendation": "Cannot
                extract hypertension
                trait"  <-
        }

class DomainExpert(Role):
    """Provides domain-specific
        interpretations"""

    def _act_on_analysis(self,
        analyst_report: dict) -> dict
        :
        if not analyst_report["
            trait_found"]:
            # DomainExpert accepts
                analyst conclusion
                without examination
            return {
```

```
                    "interpretation": "No
                        trait data
                        available",
                    "action": "Skip trait
                        extraction"  <-
                }
```

The rigid role boundaries prevent effective information flow. The DataAnalyst, focused on data structure, fails to recognize the clinical significance of ID prefixes. The DomainExpert, receiving only the analyst's conclusion, never examines the actual data to discover that 'AH' likely stands for Arterial Hypertension. This demonstrates how role-based decomposition can create blind spots in analysis.

Under detailed prompt conditions, MetaGPT's structured approach produces extensive documentation but still misses the critical pattern:

```python
class ClinicalDataProcessor(Action):
    """Structured action for clinical
        data processing"""

    async def run(self, data: pd.
        DataFrame) ->
        ProcessingResult:
        # Generate structured
            analysis document
        analysis_doc = Document()

        # Section 1: Data Overview
        analysis_doc.add_section("
            Data Characteristics")
        for col in data.columns:
            if 'individual' in col:
                unique_vals = data[
                    col].unique()[:5]
                analysis_doc.add_item
                    (f"Column {col}:
                    {unique_vals}")
                # Output: "Column ch1
                    : ['individual:
                    AH014', '
                    individual: UC003
                    ', ...]"

        # Section 2: Trait
            Identification Strategy
        analysis_doc.add_section("
            Trait Search Strategy")
        search_patterns = ['
            hypertension', 'ipah', '
            pah', 'control', 'disease
            ']

        # Searches for keywords but
            ignores ID patterns  <-
        matches_found = False
        for pattern in
            search_patterns:
            if any(pattern in str(val
                ).lower() for val in
                data.values.flat):
                matches_found = True

        # Section 3: Conclusion
```

```python
        if not matches_found:
            analysis_doc.
                add_conclusion(
                "No trait indicators
                    found in dataset"
                    <-
            )

        return ProcessingResult(
            success=False,
            trait_mapping=None)
```

Despite generating comprehensive documentation, MetaGPT's structured approach focuses on keyword searching rather than pattern recognition. The framework's emphasis on standardized procedures prevents the adaptive reasoning needed to recognize that ID prefixes encode phenotype information.

A.4.2 GSE77627: Procedural Rigidity in Biological Classification

When processing the portal hypertension dataset, MetaGPT's standardized operating procedures lead to systematic misclassification:

```python
class StandardOperatingProcedure:
    """SOP for disease trait
        classification"""

    @staticmethod
    def classify_disease_samples(
        disease_name: str,
        sample_groups: list) -> dict:
        """
        Standard procedure for binary
            classification:
        1. Identify primary disease
            group
        2. Classify all others as
            controls
        """
        classification = {}
        primary_disease = None

        # Step 1: Find exact disease
            name match
        for group in sample_groups:
            if disease_name.lower()
                in group.lower():
                primary_disease =
                    group
                classification[group]
                    = 1
                break

        # Step 2: Classify remaining
            as controls
        for group in sample_groups:
            if group not in
                classification:
                classification[group]
                    = 0  <-

        return classification

# Execution for portal hypertension
```

```
sample_groups = ['HNL', 'INCPH', 'LC'
    ]
disease_name = 'Hypertension'

# SOP application results:
# - No exact match for "Hypertension"
    in group names
# - Falls back to INCPH as primary (
    contains "Hypertension")
# - Classifies LC as control  <-

trait_mapping = {
    'INCPH': 1,  # Matched "
        Hypertension" substring
    'HNL': 0,    # Classified as
        control
    'LC': 0      # Incorrectly
        classified as control  <-
}
```

MetaGPT's rigid adherence to standardized procedures prevents recognition of domain-specific relationships. The SOP's simplistic "one disease, others control" rule cannot accommodate the biological reality that multiple conditions can manifest the same phenotype. Even when the Architect agent designs the workflow and the Engineer agent implements it perfectly according to specifications, the fundamental misunderstanding persists because it is encoded in the procedural logic.

These examples from AutoGen and MetaGPT reinforce our findings about the fundamental limitations of current autonomous agent frameworks. Despite sophisticated multi-agent architectures, conversational capabilities, and structured procedures, these systems lack the domain understanding and adaptive reasoning required for scientific data analysis. Their failures highlight the necessity of incorporating precise procedural control and domain expertise directly into agent architectures rather than relying on emergent behaviors from general-purpose frameworks.

A.5 Claude Code Examples

Claude Code, arguably today's best general-purpose CLI-based agent, demonstrates similar fundamental limitations. This proprietary agent excels at general software development tasks but struggles with domain-specific scientific data analysis. The following examples illustrate how lack of domain knowledge and procedural control leads to critical errors in both prompt conditions.

A.5.1 GSE77627: Misclassification of Portal Hypertension Subtypes

Under the general prompt condition, Claude Code implements a three-class classification scheme that

fundamentally misunderstands the biological relationship between disease subtypes:

```
# Claude Code's trait conversion
    logic
def preprocess_GSE77627():
    # ... earlier code omitted ...

    # Convert liver groups to binary/
        categorical encoding
    # HNL (healthy normal liver) = 0
        (control)
    # INCPH (idiopathic non-cirrhotic
        portal hypertension) = 1 (
        case)
    # LC (liver cirrhosis) = 2 (
        another condition)  <-
    group_mapping = {'HNL': 0, 'INCPH
        ': 1, 'LC': 2}
    metadata_df['trait'] =
        metadata_df['liver_group'].
        map(group_mapping)

    print("Sample distribution:")
    print(metadata_df['liver_group'].
        value_counts())

    # Note: Age and Gender are not
        available in this dataset
    print(f"\nFinal dataset shape: {
        final_df.shape}")
    print(f"Columns: trait + {
        final_df.shape[1]-1} gene
        expression features")
    print(f"Trait column: 0=HNL(
        control), 1=INCPH(case), 2=LC
        ")  <-
```

This multi-class formulation reveals a critical failure to recognize that both INCPH and LC represent different etiologies of portal hypertension—the trait under investigation. Liver cirrhosis is the leading cause of portal hypertension, accounting for approximately 90% of cases. By assigning LC to a separate class (2) rather than grouping it with INCPH as cases (1), Claude Code creates a biologically meaningless classification that cannot identify genes associated with portal hypertension.

The error persists even under the detailed prompt condition, where explicit guidelines are provided. Claude Code's implementation still misclassifies LC samples:

```
def convert_trait(value):
    """Convert trait values to binary
        format"""
    value_str = str(value).lower()

    # Extract the liver group
        information
    if 'incph' in value_str:
        return 1  # INCPH as the
            target condition
    elif 'lc' in value_str or '
        cirrhosis' in value_str:
```

```
        return 0  # Cirrhosis as
            control/comparison  <-
    elif 'hnl' in value_str or '
        normal' in value_str:
        return 0  # Normal liver as
            control
    else:
        return None
```

Despite the detailed guidelines emphasizing domain knowledge incorporation, Claude Code treats cirrhosis as a control condition rather than recognizing it as the most common cause of portal hypertension. This fundamental misunderstanding demonstrates that even sophisticated code generation capabilities cannot compensate for the absence of biomedical reasoning in critical decision points.

A.5.2 GSE117261: Failure to Map Probe Identifiers

For the GSE117261 dataset, Claude Code exhibits a different but equally critical failure—the complete absence of probe-to-gene mapping. Under both prompt conditions, the agent produces code that retains raw probe identifiers instead of mapping them to standardized gene symbols:

```
def create_final_dataset():
    """Create the final preprocessed
        dataset"""
    # ... metadata extraction code
        ...

    # Transpose expression data to
        have samples as rows
    print("\nTransposing expression
        data...")
    expression_t = expression_data.
        set_index('ID_REF').T  <-
    expression_t.index.name = '
        sample_id'

    # Merge metadata with expression
        data
    print("Merging metadata with
        expression data...")
    final_df = sample_df.set_index('
        sample_id').join(expression_t
        )  <-

    print(f"Final dataset shape: {
        final_df.shape}")
    print(f"Columns: {list(final_df.
        columns[:10])}... (showing
        first 10)")

    # Save the processed dataset
    output_file = "/home/techt/
        Desktop/gene/gene_cc/
        GSE117261_processed.csv"
    print(f"\nSaving processed
        dataset to {output_file}...")
    final_df.to_csv(output_file)
```

The code directly uses the raw probe IDs (e.g.,

'7892501', '7892502') as column names without any attempt to map them to gene symbols. This omission renders the dataset incompatible with downstream analyses that require standardized gene identifiers. In contrast, the human expert implementation performs comprehensive probe mapping:

```
# Human expert implementation (
    excerpt)
# Extract gene annotation from SOFT
    file
gene_annotation = get_gene_annotation
    (soft_file_path)

# Map probe IDs to gene symbols
prob_col = 'ID'
gene_col = 'gene_assignment'
mapping_data = get_gene_mapping(
    gene_annotation, prob_col,
    gene_col)
gene_data = apply_gene_mapping(
    expression_df=genetic_data,
                    mapping_df
                        =
                    mapping_data
                    )

# Normalize gene symbols using NCBI
    Gene database
gene_data_normalized =
    normalize_gene_symbols_in_index(
    gene_data)
```

The absence of these critical preprocessing steps—annotation extraction, probe mapping, and symbol normalization—demonstrates Claude Code's inability to recognize and implement essential bioinformatics workflows autonomously. Even when provided with detailed guidelines that explicitly mention gene mapping requirements, the agent fails to implement this fundamental preprocessing step, producing datasets that cannot be used for meaningful biological analysis.

These examples from Claude Code reinforce our findings about the fundamental limitations of current autonomous agents in scientific computing. Despite advanced code generation capabilities, these systems lack the domain understanding and procedural control mechanisms necessary to ensure biologically valid analyses.

A.6 Cursor Examples

Cursor, one of the current best agentic code editors, demonstrates similar fundamental limitations when applied to gene expression analysis. While excelling at general programming tasks through its integrated AI assistance, Cursor fails to implement critical bioinformatics workflows that require domain-specific knowledge. The following exam-

ples illustrate how these failures manifest differently from Claude Code while reinforcing the same underlying limitations.

A.6.1 GSE117261: Complete Absence of Probe-to-Gene Mapping

Under the general prompt condition, Cursor exhibits a critical failure in processing the GSE117261 dataset by entirely omitting the probe-to-gene mapping step. The dataset contains Affymetrix microarray data with numeric probe identifiers that must be mapped to standardized gene symbols for meaningful analysis.

Cursor's implementation demonstrates a fundamental misunderstanding of gene expression data requirements:

```python
def get_gene_symbols(expr_df: pd.
    DataFrame) -> pd.DataFrame:
    """
    Convert probe IDs to gene symbols
        . For this dataset, we'll use
         the probe IDs as gene
         identifiers
    since gene symbol mapping would
        require additional annotation
         files.

    Args:
        expr_df: Expression dataframe
             with probe IDs as index

    Returns:
        Expression dataframe with
            gene symbols (or probe
            IDs) as column names
    """
    print("Using probe IDs as gene
        identifiers (gene symbol
        mapping not available)")   <-

    # Transpose so samples are rows
        and genes are columns
    expr_df_t = expr_df.T

    # Clean up column names (remove
        quotes if any)
    expr_df_t.columns = [str(col).
        strip('"') for col in
        expr_df_t.columns]

    return expr_df_t
```

This implementation reveals a critical gap in understanding bioinformatics data processing. By declaring "gene symbol mapping not available" and proceeding with raw probe IDs, Cursor creates a dataset that is fundamentally incompatible with downstream analyses. The resulting data contains columns labeled with numeric identifiers like '7892501', '7892502' rather than meaningful gene symbols like 'TP53' or 'EGFR'.

In contrast, the human expert implementation performs comprehensive probe mapping:

```python
# Human expert implementation (
    excerpt)
# Step 1: Extract gene annotation
    from SOFT file
gene_annotation = get_gene_annotation
    (soft_file_path)

# Step 2: Create mapping from probe
    IDs to gene symbols
prob_col = 'ID'
gene_col = 'gene_assignment'
mapping_data = get_gene_mapping(
    gene_annotation, prob_col,
    gene_col)

# Step 3: Apply mapping to convert
    probe-level to gene-level data
gene_data = apply_gene_mapping(
    expression_df=genetic_data,
                            mapping_df
                                =
                            mapping_data
                            )

# Step 4: Normalize gene symbols
    using NCBI Gene database
gene_data_normalized =
    normalize_gene_symbols_in_index(
    gene_data)
```

The consequences of this omission cascade through the analysis pipeline. Without proper gene symbols, the dataset cannot be integrated with other genomic resources, compared across studies, or interpreted in biological context. This represents not merely a technical oversight but a fundamental failure to understand the requirements of genomic data analysis, where standardized gene identifiers are essential for scientific validity.

A.6.2 GSE256539: Misinterpretation of Clinical Phenotype Encoding

Under the detailed prompt condition, Cursor demonstrates a different but equally consequential failure in processing the GSE256539 dataset. This study compares Idiopathic Pulmonary Arterial Hypertension (IPAH) patients with controls, where the phenotype information is encoded in individual ID prefixes rather than explicit labels.

Cursor implements a generic trait conversion function that searches for obvious keywords:

```python
def convert_trait(value):
    """Convert trait value to binary
        (0/1) or continuous"""
    if pd.isna(value) or value is
        None:
        return None

    value_str = str(value).lower()
```

```
        # Extract value after colon if
            present
        if ':' in value_str:
            value_str = value_str.split('
                :', 1)[1].strip()

        # Binary conversion for disease
            status
        if any(keyword in value_str for
            keyword in ['control', '
            normal', 'healthy', 'negative
            ']):   <-
            return 0
        elif any(keyword in value_str for
             keyword in ['case', 'disease
            ', 'cancer', 'tumor', '
            positive', 'affected']):   <-
            return 1

        # Try to convert to numeric for
            continuous traits
        try:
            return float(value_str)
        except:
            return None
```

This simplistic keyword-based approach fails entirely for the GSE256539 dataset, where sample characteristics contain individual IDs like 'individual: AH014' or 'individual: UC003'. None of these IDs contain the expected keywords, resulting in all samples being classified as None and subsequently dropped from the analysis.

The human expert implementation recognizes the sophisticated encoding scheme:

```
def convert_trait(value: str) ->
    Optional[int]:
    """
    Converts individual ID to a
        binary trait value (IPAH vs
        Control).
    - 1: IPAH patient (case)
    - 0: Control patient
    The distinction is inferred from
        the prefix of the individual
        ID string.
    e.g., 'individual: AH014'.
    """
    try:
        id_part = value.split(':')
            [1].strip()
        prefix = id_part[:2]
        # Based on the study design (
            IPAH vs. control) and
            observed prefixes,
        # 'AH' (Arterial Hypertension
            ), 'VA', 'BA' are
            inferred as cases.
        # 'UC' (Unaffected Control),
            'UM' (Unaffected Male), '
            CC' (Control Case),
        # and 'UA' (Unaffected) are
            inferred as controls.
        if prefix in ['AH', 'VA', 'BA
            ']:
            return 1  # Case
```

```
        elif prefix in ['UC', 'UM', '
            CC', 'UA']:
            return 0  # Control
        else:
            return None
    except (IndexError,
        AttributeError):
        return None
```

This example illustrates a critical limitation: even when provided with detailed guidelines through our Action Unit specifications, Cursor cannot adapt its generic pattern-matching approach to the specific encoding schemes used in real genomic datasets. The agent fails to examine the actual data structure, recognize the pattern in individual IDs, or infer the biological meaning from the prefixes. This results in complete data loss as no samples can be properly classified.

The failure is particularly revealing because it occurs despite the detailed prompt condition providing explicit instructions about careful data examination and domain knowledge incorporation. Cursor's inability to move beyond generic keyword matching to context-specific pattern recognition demonstrates the absence of adaptive reasoning required for scientific data analysis.

A.7 Manus Examples

Manus, a recently proposed multi-agent system that claims general-purpose task automation capabilities (Shen and Yang, 2025), demonstrates fundamental failures when applied to gene expression analysis. While designed to orchestrate multiple specialized agents for complex workflows, Manus lacks the domain understanding and procedural control necessary for bioinformatics data processing. The following examples illustrate critical errors in both prompt conditions.

A.7.1 GSE117261: Complete Failure in Probe-to-Gene Mapping

Under the general prompt condition, Manus exhibits multiple critical failures in processing the GSE117261 dataset, most notably the complete absence of probe-to-gene mapping. This dataset contains Affymetrix microarray data where expression values are indexed by numeric probe identifiers that must be mapped to standardized gene symbols.

Manus's implementation reveals a fundamental misunderstanding of gene expression data structure:

```
def process_expression_file(filepath)
    :
    with open(filepath, 'r') as f:
```

```
        lines = f.readlines()

    # Find data start
    start_index = -1
    for i, line in enumerate(lines):
        if line.strip() == '!
            series_matrix_table_begin
            ':
            start_index = i + 1
            break

    # Read expression data
    df = pd.read_csv(filepath, sep='\
        t', skiprows=start_index,
        index_col=0)

    # Transpose so samples are
        columns
    df = df.transpose()
    df.index.name = 'Sample_ID'

    return df  # Returns data with
        probe IDs as columns <-

# In main execution:
# Process expression data
expression_df =
    process_expression_file(
    series_matrix_path)

# Merge dataframes - directly uses
    probe IDs as features
final_df = pd.merge(metadata_df,
    expression_df,
                    left_index=True,
                        right_index=
                        True, how='
                        outer')  <-
```

The code directly merges clinical metadata with expression data that retains numeric probe identifiers (e.g., '7892501', '7892502') as column names. This fundamental omission renders the dataset scientifically unusable, as downstream analyses require standardized gene symbols for biological interpretation and cross-study comparison.

Beyond the probe mapping failure, Manus demonstrates additional critical errors in clinical data processing:

```
# Incorrect clinical characteristic
    extraction
if 'clinical_group' in data['
    characteristics']:  # Wrong key
    <-
    trait = data['characteristics']['
        clinical_group']
    if trait == 'all PAH':  #
        Incomplete mapping <-
        trait = 1
    elif trait == 'FD':
        trait = 0
    # Missing: other PAH subtypes are
        ignored <-
```

Manus searches for a non-existent 'clini-

cal_group' key when the actual characteristic is 'pah_subtype'. Furthermore, the trait mapping logic fails to recognize that all PAH (Pulmonary Arterial Hypertension) subtypes should be classified as cases, not just 'all PAH'. This results in data loss and misclassification of disease samples.

In contrast, the human expert implementation performs comprehensive processing:

```
# Human expert: Proper probe-to-gene
    mapping
# Step 1: Extract gene annotation
    from SOFT file
gene_annotation = get_gene_annotation
    (soft_file_path)

# Step 2: Create mapping from probe
    IDs to gene symbols
prob_col = 'ID'
gene_col = 'gene_assignment'
mapping_data = get_gene_mapping(
    gene_annotation, prob_col,
    gene_col)

# Step 3: Apply mapping to convert
    probe-level to gene-level data
gene_data = apply_gene_mapping(
    expression_df=genetic_data,
                    mapping_df
                        =
                        mapping_data
                        )

# Step 4: Normalize gene symbols
    using NCBI Gene database
gene_data_normalized =
    normalize_gene_symbols_in_index(
    gene_data)
```

The absence of these critical bioinformatics steps demonstrates Manus's inability to recognize and implement essential data processing requirements autonomously, producing datasets that cannot support meaningful biological analysis.

A.7.2 GSE77627: Fundamental Misunderstanding of Disease Biology

Under the detailed prompt condition with explicit guidelines, Manus demonstrates an even more concerning failure—fundamental misunderstanding of disease biology that persists despite detailed instructions. Processing the GSE77627 portal hypertension dataset, Manus implements biologically incorrect trait classification:

```
# Manus's trait conversion with
    detailed instructions
def convert_trait(value):
    value = value.split(":")[-1].
        strip().strip("\"")
    if value == "INCPH":
        return 1
    elif value == "LC" or value == "
        HNL":  # Critical biological
```

```
            error <-
            return 0
        return None

    # Agent's note reveals the
        misunderstanding
validate_and_save_cohort_info(
    is_gene_available,
    trait_available,
    notes="Trait 'liver group' is
        available and converted to
        binary " +
        "(INCPH=1, LC/HNL=0). Age
            and Gender data are not
            explicitly available."
)  <-
```

This implementation classifies liver cirrhosis (LC) as a control condition alongside healthy livers (HNL), demonstrating a critical failure to understand portal hypertension etiology. Liver cirrhosis accounts for approximately 90% of portal hypertension cases in Western countries and is the most common cause of this condition. By misclassifying LC samples as controls, Manus creates a dataset where the majority of disease cases are labeled as healthy controls.

The correct biological classification, implemented by the human expert, recognizes both disease subtypes:

```
# Human expert: Biologically correct
    classification
def convert_trait(value: str) ->
    Optional[int]:
    """Converts liver group status to
        a binary value for
        Hypertension."""
    try:
        group = value.split(':')[1].
            strip().upper()
        if group in ['INCPH', 'LC']:
            # Both are portal
            hypertension
            return 1
        elif group == 'HNL':  # Only
            healthy livers are
            controls
            return 0
        else:
            return None
    except (IndexError,
        AttributeError):
        return None
```

The impact of this misclassification is severe: Manus's approach yields only 18 cases (INCPH) versus 36 controls (HNL and LC combined), while the correct classification produces 40 cases versus 14 controls. This reversal of the case-control ratio fundamentally alters the dataset's statistical properties and would lead to identification of genes that distinguish INCPH from a heterogeneous mixture of healthy and cirrhotic livers, rather than genes associated with portal hypertension.

Furthermore, Manus attempts probe-to-gene mapping but implements it incorrectly:

```
# Manus attempts mapping but with
    errors
def map_probes_to_genes(
    series_matrix_df, annotation_path
    , output_path):
    annotation_df = pd.read_csv(
        annotation_path, sep='\t',
        comment='#')
    probe_to_gene_map = annotation_df
        .set_index('ID')['Symbol'].
        to_dict()
    series_matrix_df['Gene_Symbol'] =
        series_matrix_df['ID_REF'].
        map(probe_to_gene_map)
    # ... saves to file but doesn't
        properly integrate <-

# Later in merging:
expression_df_transposed =
    mapped_df_for_analysis.set_index(
    "Gene_Symbol")
                    .drop("
                        ID_REF"
                        , axis
                        =1).T
                        <-
# This assumes Gene_Symbol column
    exists and handles duplicates
    poorly
```

While Manus attempts probe mapping, the implementation lacks proper handling of many-to-one probe-gene relationships and fails to integrate the mapped data correctly into the final dataset. The agent also omits critical quality control steps such as gene symbol normalization and systematic bias detection.

These examples from Manus reinforce our findings about fundamental limitations in current autonomous agents. Despite claims of general-purpose automation and multi-agent orchestration capabilities, Manus fails to implement basic bioinformatics workflows correctly. The persistence of biological misunderstandings even under detailed prompt conditions demonstrates that sophisticated agent architectures cannot compensate for the absence of domain understanding and precise procedural control required for scientific data analysis.

B Communication Protocols and Messaging Mechanisms

This section provides technical details about the communication protocols that enable agent coordination in GenoMAS. The system employs a typed message-passing architecture that facilitates structured interactions between agents while maintain-

ing modularity and preventing circular dependencies.

B.1 Message Type Hierarchy

GenoMAS defines a comprehensive set of message types that govern agent interactions. These types form a structured hierarchy organized into three categories that reflect the fundamental communication patterns in the system.

Request Messages The system uses five types of request messages to initiate agent actions:

- TASK_REQUEST: Initiates a new task assignment from the PI agent
- CODE_WRITING_REQUEST: Requests code generation for a specific action unit
- CODE_REVIEW_REQUEST: Requests review of generated code
- CODE_REVISION_REQUEST: Requests revision based on review feedback
- PLANNING_REQUEST: Requests selection of the next action unit

Response Messages Each request type has a corresponding response type:

- TASK_RESPONSE: Confirms task assignment
- CODE_WRITING_RESPONSE: Contains generated code
- CODE_REVIEW_RESPONSE: Contains approval/rejection decision and feedback
- CODE_REVISION_RESPONSE: Contains revised code
- PLANNING_RESPONSE: Contains selected action unit and reasoning

System Messages Special messages for system-level events:

- TIMEOUT: Indicates that an agent has exceeded its time limit

The message types are organized to maintain clear request-response symmetry, with automatic mapping between corresponding pairs to ensure protocol consistency.

B.2 Message Structure

Each message contains four essential components: (1) the sender's **role**, (2) the message **type** from the hierarchy above, (3) the **content** payload (task instructions, code, feedback, etc.), and (4) the **target roles** specifying intended recipients. This structure enables both unicast and multicast communication

patterns, allowing messages to target single agents or multiple agents as needed.

B.3 Topology-Based Message Routing

GenoMAS implements a topology-based routing system that defines which agents can communicate with each other. This topology forms the backbone of the system's communication infrastructure, ensuring that messages flow along predefined paths that reflect the logical relationships between agents.

The topology is encoded as a directed graph where each agent maintains a set of other agents it can communicate with:

```
PI Agent: {PI Agent, GEO Agent, TCGA
    Agent,
            Statistician Agent, Code
                Reviewer, Domain
                Expert}

GEO Agent: {PI Agent, GEO Agent, Code
    Reviewer, Domain Expert}

TCGA Agent: {PI Agent, TCGA Agent,
    Code Reviewer, Domain Expert}

Statistician Agent: {PI Agent,
    Statistician Agent, Code Reviewer
    }

Code Reviewer: {PI Agent, GEO Agent,
    TCGA Agent,
            Statistician Agent}

Domain Expert: {PI Agent, GEO Agent,
    TCGA Agent}
```

This topology prevents circular dependencies and infinite message loops by carefully controlling communication paths. For example, the Domain Expert cannot directly communicate with the Statistician Agent, reflecting their distinct responsibilities. While agents can send messages to themselves (enabling self-planning), the overall structure prevents multi-agent cycles.

The environment enforces these constraints by filtering messages based on the topology, ensuring only authorized communication occurs.

B.4 Asynchronous Message Queue Processing

The environment orchestrates agent interactions through a FIFO message queue that processes messages asynchronously. This design decouples agent execution, allowing each agent to operate at its own pace while maintaining overall system coordination.

The processing loop extracts messages from the queue, validates receivers against topology constraints, and invokes each valid receiver's act()

method. New messages generated during processing are appended to the queue, creating a dynamic flow of interactions. This asynchronous design allows agents to operate independently while maintaining coordinated behavior, and scales naturally as new agent types are added to the system.

B.5 Agent Communication Patterns

Programming agents orchestrate complex workflows through carefully designed communication patterns implemented in the `act()` method. These patterns enable agents to collaborate effectively while maintaining clear separation of concerns.

Task Initiation The workflow begins when a programming agent receives a `TASK_REQUEST` from the PI. Rather than immediately executing code, the agent first enters a planning phase by sending a `PLANNING_REQUEST` to itself. This self-messaging pattern allows the agent to leverage its planning capabilities to analyze the task context and select appropriate action units.

Planning-Execution Cycle The core workflow follows a planning-execution pattern where the agent first determines what to do, then executes it. After sending a `PLANNING_REQUEST`, the agent receives its own `PLANNING_RESPONSE` containing the selected action unit and reasoning. Based on the action unit's properties, the agent then sends a `CODE_WRITING_REQUEST` either to itself (for standard actions) or to the Domain Expert (for actions requiring specialized biomedical knowledge). This dynamic targeting ensures that each task receives appropriate expertise.

Code Review Loop Quality assurance is built into the communication protocol through an iterative review process. After generating code, the agent sends a `CODE_REVIEW_REQUEST` to either the Code Reviewer (for technical review) or the Domain Expert (for domain-specific validation). The reviewer evaluates the code and returns a `CODE_REVIEW_RESPONSE` containing an approval/rejection decision and constructive feedback. If rejected, the agent processes the feedback and sends a `CODE_REVISION_REQUEST` to address the identified issues. This loop continues until the code is approved or the maximum number of review rounds is exceeded, balancing code quality with computational efficiency.

B.6 Timeout and Error Handling

Robust timeout and error handling mechanisms ensure that GenoMAS remains responsive and can gracefully recover from unexpected situations. The system implements a multi-level approach to manage execution time and handle errors.

At the agent level, each agent monitors its own execution time against a configured maximum. When an agent detects that it has exceeded its time limit, it emits a `TIMEOUT` message that signals the need for immediate task termination. This self-monitoring approach distributes the timeout detection responsibility, making the system more resilient.

The environment provides a second layer of timeout protection by tracking global execution time. During message processing, the environment checks whether agents have exceeded their time limits before allowing them to process new messages. When a timeout is detected at either level, the environment clears the message queue to prevent further processing and returns the current task results, ensuring that partial progress is preserved.

The system includes fallback mechanisms for handling errors, such as defaulting to predefined action sequences when parsing fails. This ensures that temporary failures do not derail entire workflows.

C Task-Specific Guidelines and Action Unit Prompts

This section presents the guidelines and action unit prompts that encode domain expertise for GEO and TCGA data preprocessing tasks, slightly simplified for brevity.

C.1 GEO Data Preprocessing Guidelines

The GEO agent follows these guidelines to transform raw Gene Expression Omnibus data into analysis-ready formats:

```
## GEO Data Preprocessing Workflow

Your task is to preprocess GEO series
    matrix data by extracting and
linking clinical features with gene
    expression values.

### Step 1: Data Loading and Initial
    Analysis
- Load the series matrix file using
    GEOparse
- Identify clinical features in
    phenotype data
- Extract gene expression data matrix

### Step 2: Clinical Feature
    Processing
- Extract patient/sample identifiers
- Parse clinical variables from
    phenotype descriptions
```

```
        - Handle special characters and
          formatting inconsistencies
        - Create structured clinical
          dataframe

        ### Step 3: Gene Data Processing
        - Identify gene annotation format (
          symbols, IDs, probes)
        - Map identifiers to standard gene
          symbols using:
          * Internal gene synonym database
          * Platform annotation data
          * Probe-to-gene mappings
        - Handle multi-mapped probes
          appropriately

        ### Step 4: Data Integration
        - Ensure sample ID consistency
          between clinical and gene data
        - Perform log transformation if data
          appears non-normalized
        - Handle missing values using
          appropriate strategies
        - Create final integrated dataset

        ### Quality Control Considerations
        - Verify gene symbol mapping coverage
          (aim for >80%)
        - Check for batch effects in
          expression data
        - Validate clinical feature
          extraction accuracy
        - Document any data quality issues

        ### Termination Conditions
        - Complete integration of clinical
          and gene data achieved
        - Major data quality issues prevent
          meaningful analysis
        - Required clinical features cannot
          be extracted
```

C.2 GEO Action Unit Examples

The following action units implement specific steps
in the GEO preprocessing workflow:

C.2.1 Initial Data Loading

```
Load the GEO series matrix file and
    perform initial exploration:
1. Load the data from the provided
   file path
2. Display basic dataset information
   and dimensions
3. Show sample phenotype information
4. Examine the expression data
   structure
5. Report the number of samples and
   features
```

C.2.2 Gene Annotation

```
Annotate genes with standardized
    symbols:
1. Examine the current gene
   identifiers
2. Determine identifier type (e.g.,
   symbols, Entrez IDs, probe IDs)
```

```
3. Apply appropriate mapping strategy
   for normalization
4. Handle unmapped identifiers
   appropriately
5. Report mapping success rate and
   coverage statistics
```

C.3 TCGA Data Preprocessing Guidelines

The TCGA agent processes The Cancer Genome
Atlas data with focus on clinical feature engineer-
ing:

```
## TCGA Data Preprocessing Workflow

Your task is to engineer demographic
    and clinical features from TCGA
data for downstream analysis.

### Step 1: Data Loading
- Load clinical and expression data
  files
- Verify data integrity and format
- Check sample ID correspondence

### Step 2: Feature Identification
- Scan clinical data for demographic
  variables:
  * Age, gender, race, ethnicity
  * Disease stage, grade, subtype
  * Treatment history
  * Survival outcomes
- Prioritize features with >70%
  completeness

### Step 3: Feature Engineering
- Standardize demographic categories
- Create binary indicators for key
  conditions
- Engineer interaction features if
  relevant
- Handle missing values appropriately
  :
  * Numerical: median/mean imputation
  * Categorical: mode or "Unknown"
    category

### Step 4: Validation
- Ensure all features have
  appropriate data types
- Verify value ranges and
  distributions
- Check for data entry errors
- Create summary statistics

### Termination Conditions
- At least 3 meaningful demographic
  features extracted
- Critical features have excessive
  missing data (>50%)
- Data quality issues prevent
  reliable feature engineering
```

C.4 TCGA Action Unit Examples

C.4.1 Find Candidate Demographic Features

```
Identify potential demographic
    features in clinical data:
```

```
1. List all available clinical
      variables
2. Search for demographic and
      clinical keywords
3. Assess data completeness for each
      candidate feature
4. Examine value distributions for
      categorical variables
5. Recommend features with sufficient
      data quality
```

C.4.2 Feature Engineering and Validation

```
Engineer and validate selected
      demographic features:
1. Standardize values for consistency
2. Apply appropriate missing value
      strategies
3. Create binary encodings where
      needed
4. Generate clinically meaningful
      interaction terms
5. Validate feature distributions and
      quality
6. Save processed features for
      downstream analysis
```

C.5 Statistician Guidelines

The Statistician agent receives preprocessed data and performs regression analyses following these guidelines:

```
## Statistical Analysis Workflow

Perform regression analyses to
      identify gene-trait associations.

### Analysis Types (in order of
      preference):
1. **Unconditional One-step**: Direct
      trait-gene regression
2. **Conditional One-step**: Include
      demographic covariates
3. **Two-step**: Batch correction
      followed by analysis

### Statistical Considerations:
- Use appropriate multiple testing
      correction (FDR/Bonferroni)
- Check regression assumptions (
      normality, homoscedasticity)
- Report both effect sizes and
      significance levels
- Generate diagnostic plots for model
      validation

### Output Requirements:
- Coefficient table with gene
      rankings
- Statistical significance metrics
- Model diagnostic visualizations
- Summary of top associated genes
```

These guidelines and prompts encode domain expertise while maintaining sufficient flexibility for agents to adapt to diverse datasets and analysis requirements.

D Guided Planning Framework and Metaprompts

This section provides technical details about the guided planning framework that enables programming agents to adaptively select action units based on task context and execution history.

D.1 Planning Mechanism Architecture

The planning mechanism implements a self-messaging pattern where programming agents send planning request messages to themselves at each decision point. This design enables agents to leverage their full language modeling capabilities for strategic decision-making while maintaining clear separation between planning and execution phases.

The planning process integrates several key components. Agents perform task context analysis by examining the complete execution history, including code outputs, errors, and debugging attempts. Based on this analysis, they select the most appropriate next action from available units. When retraction is enabled, agents can choose to backtrack to previous steps if critical issues are identified. All planning decisions follow a strict JSON schema to ensure reliable parsing and system robustness.

D.2 Planning Request Metaprompt

The following metaprompt guides programming agents through the planning process. The prompt adapts dynamically based on whether retraction is available:

```
You are {agent_role}. Your task is to
      execute a multi-step workflow.

# The following section appears only when
      retraction is available:
You have the option to retract to a previous
      step if you discover
critical issues that require revisiting
      earlier decisions.
Retraction remaining: {retract_remaining}

### High-level Guidelines:
{guidelines}

### Task History:
You have attempted the following
      actions:
{task_history}

### Next Action Selection:
Based on the task history, select the
      next action from:
{available_actions}

### Response Format:
Respond in JSON with the following
      structure:
{
    "action": "Selected Action Unit
          name",
```

```
        "retract_to_action": "Action to retract
            to (if applicable)",
        "reason": "Brief explanation of
            your decision"
}

Important considerations:
- Analyze all outputs and errors to
    understand the current state
- If critical errors prevent progress
    , consider alternative approaches
- Use retraction when fundamental issues
    require earlier corrections
- Select "TASK COMPLETED" only when
    all objectives are achieved
```

The metaprompt structure ensures that agents receive comprehensive context while maintaining focus on the immediate planning decision. The conditional inclusion of retraction instructions prevents confusion when this feature is disabled.

D.3   Planning Response Processing

The system implements robust parsing for planning responses with multiple fallback mechanisms. It first attempts direct JSON parsing of the model response. If this fails, it extracts JSON from markdown code blocks. The system then employs fuzzy action matching using TF-IDF similarity to handle minor variations in action names. As a final fallback, when planning is disabled or parsing fails completely, the system follows predefined action sequences. This multi-layered approach ensures system robustness while maintaining the benefits of adaptive planning.

D.4   Context Management for Planning

The planning mechanism employs sophisticated context management to balance informativeness with token efficiency:

Task History Formatting   The system maintains detailed records of each step, including action unit names with timestamps, generated code (truncated if exceeding length limits), execution outputs with error traces, and clear distinctions between regular steps and debugging attempts. This comprehensive history enables agents to make informed planning decisions based on complete task context.

Context Modes   Different planning scenarios use tailored context presentations. The `all` mode provides complete history for comprehensive planning decisions, while `past` mode excludes the current attempt for revision scenarios. The `last` mode focuses only on the most recent attempt for targeted debugging efforts.

D.5   Retraction Mechanism Design

The retraction mechanism enables agents to recover from decisions that lead to downstream complications. When an agent decides to retract, it reverts both its task context and execution state to a previous action unit while preserving the complete task history. This allows the agent to learn from failed attempts while exploring alternative approaches. The mechanism tracks retraction usage through a configurable budget, preventing infinite loops while providing sufficient flexibility for complex problem-solving. This design ensures execution state consistency while preserving valuable task history for future planning decisions.

E   Code Generation, Review, and Domain Consultation Mechanisms

This section provides detailed technical specifications of the code generation, review, and domain expert consultation mechanisms that form the core of GenoMAS's multi-turn programming workflow.

E.1   Code Generation and Review Process

E.1.1   Code Generation Architecture

The code generation process in GenoMAS implements a context-aware approach that enables programming agents to produce code incrementally while maintaining coherence across multiple action units. Programming agents receive comprehensive task history that includes all previously executed code snippets with their outputs, error traces from failed attempts, and reviews from previous debugging iterations. This accumulated context enables agents to understand data structures created in earlier steps and avoid repeating errors.

Each code generation request focuses on a single action unit while maintaining awareness of the broader workflow. Agents generate code that can be concatenated with previous steps and executed sequentially. The system dynamically routes code generation requests based on action unit properties—standard programming tasks are handled by the programming agents themselves, while actions requiring biomedical expertise are routed to the Domain Expert agent.

Code Writing Metaprompt   Programming agents receive the following structured prompt when generating code for each action unit:

```
### General Guidelines:
{guidelines}

### Function Tools:
```

```
{tools_code}

### Programming Setups:
{path_setup}

### Task History:
# Complete execution history of previous
    steps
{formatted_task_history}

### TO DO: Programming
Now that you've been familiar with
    the task setups and current
status, please write the code
    following the instructions:

{action_unit_instruction}

NOTE:
ONLY IMPLEMENT CODE FOR THE CURRENT
    STEP. MAKE SURE THE CODE CAN BE
CONCATENATED WITH THE CODE FROM
    PREVIOUS STEPS AND CORRECTLY
    EXECUTED.

FORMAT:
```python
[your_code]
```

NO text outside the code block.
Your code:
```

This metaprompt structure ensures that agents have access to all necessary context while maintaining focus on the current action unit. The explicit formatting requirements prevent extraneous text that could interfere with code execution.

E.1.2 Code Review Process

The code review mechanism implements a sophisticated evaluation framework that balances functionality verification with instruction conformance. Each review receives the task history and current code attempt but explicitly excludes reviews from previous attempts at the same step. This isolation prevents cascading biases where an incorrect initial review could influence subsequent assessments.

Code review follows two primary criteria: functionality assessment (whether the code executes successfully and produces expected outputs) and conformance checking (whether the code follows instructions and achieves intended objectives). For domain-specific tasks, reviewers also assess whether biomedical inferences are reasonable.

Code Review Metaprompt The following prompt guides reviewers through systematic evaluation:

```
### Task History:
# Previous steps excluding current attempt's
    reviews
```

```
{past_context}

### TO DO: Code Review
The following code is the latest
    attempt for the current step and
requires your review. If previous
    attempts have been included in
    the
task history above, their presence
    does not indicate they succeeded
or failed, though you can refer to
    their execution outputs for
    context.
Only review the latest code attempt
    provided below.

# Current attempt details
{current_attempt}

Please review the code according to
    the following criteria:
1. *Functionality*: Can the code be
    successfully executed in the
    current setting?
2. *Conformance*: Does the code
    conform to the given instructions
    ?
    # Domain trigger added for biomedical
        tasks

Provide suggestions for revision and
    improvement if necessary.

*NOTE*:
1. Your review is not concerned with
    engineering code quality. The
    code is a quick demo for a
        research project, so the
        standards
    should not be strict.
2. If you provide suggestions, please
    limit them to 1 to 3 key
    suggestions. Focus on the most
        important aspects, such as how
        to
    solve the execution errors or make
        the code conform to the
    instructions.

State your decision exactly in the
    format: "Final Decision: Approved
    "
or "Final Decision: Rejected."
```

E.1.3 Code Revision Process

When code is rejected during review, the revision mechanism enables iterative improvement. Programming agents receive comprehensive context including all previous attempts and their reviews, allowing them to learn from the full debugging history. The revision process explicitly acknowledges that reviewer feedback may occasionally be incorrect or impractical, instructing agents to implement suggestions selectively based on their assessment.

Code Revision Metaprompt The revision prompt provides structured guidance:

```
### Task History:
# All previous attempts and their reviews
{past_context_with_reviews}

The following code is the latest
    attempt for the current step and
requires correction. If previous
    attempts have been included in
    the
task history above, their presence
    does not indicate they succeeded
or failed, though you can refer to
    their execution outputs for
    context.
Only correct the latest code attempt
    provided below.

# Current attempt details
{current_attempt}

Use the reviewer's feedback to help
    debug and identify logical errors
in the code. While the feedback is
    generally reliable, it might
occasionally include errors or
    suggest changes that are
    impractical
in the current context. Make
    revisions where you agree with
    the
feedback, but retain the original
    code where you do not.

Reviewer's feedback:
{reviewer_feedback}

# Standard code formatting requirements
{CODE_INDUCER}
```

E.2 Domain Expert Consultation

The domain expert consultation mechanism provides specialized biomedical knowledge for action units that require scientific interpretation beyond standard programming expertise. Unlike the standard code review process where the Code Reviewer evaluates already-written code, the Domain Expert is consulted *during* code generation for specific action units. This fundamental difference ensures that domain knowledge is incorporated from the outset rather than retroactively.

When consulting the Domain Expert, the system provides a modified context that emphasizes data characteristics over implementation details. This includes dataset metadata, summary statistics, and specific domain questions, with minimal technical programming history. Furthermore, domain expert consultations maintain continuity—when domain-generated code encounters errors, the same Domain Expert receives the error information for

debugging, preserving the domain-specific reasoning thread throughout the process. This contrasts with standard code review where different agents may handle successive iterations.

E.3 Context Management and Quality Assurance

E.3.1 Context Management Strategies

The system implements sophisticated context management to optimize information flow while managing token limits. The TaskContext maintains a hierarchical structure that distinguishes regular steps from debugging attempts, with each step recording its type, index, action name, instruction, code, output, and error traces.

Different context presentations serve specific purposes: comprehensive history for planning decisions, filtered views for unbiased code review, and domain-focused formatting for biomedical reasoning tasks. For long workflows, the system implements dynamic pruning strategies—code snippets may be truncated with clear indicators, while error traces are preserved in full to ensure debugging effectiveness.

E.3.2 Quality Assurance Mechanisms

Several mechanisms ensure code quality throughout the generation process. The system allows configurable rounds of review and revision (typically 1-3) before accepting code, catching both execution errors and logical flaws while preventing infinite debugging loops. Successfully reviewed code can be cached as snippets for similar future action units, accelerating development while maintaining quality. All generated code undergoes immediate execution validation, catching syntax errors, runtime exceptions, and logical errors that produce incorrect outputs.

These comprehensive mechanisms work together to produce high-quality code that correctly implements complex multi-step workflows while adapting to diverse dataset characteristics and analysis requirements.

F Memory and Code Reuse Efficiency

To understand how GenoMAS's memory mechanism contributes to its efficiency, we tracked code snippet reuse patterns during analysis of the first 50 cohort datasets. Figure 4 demonstrates the efficiency gain: the system's dynamic memory of validated code snippets saves 57.8 minutes during the tracked session, with an average of 20.3 seconds per reused programming step. The memory reuse

(a) Cumulative time savings

(b) Memory reuse rate evolution

Figure 4: **Memory reuse efficiency in GenoMAS.** (a) Cumulative time savings through memory reuse and (b) memory reuse rate evolution across programming steps. The system rapidly achieves high efficiency, stabilizing around 65% reuse rate after initial learning.

rate stabilizes around 65% after initial learning, indicating that the system rapidly builds a reliable repertoire of reusable code patterns.

The memory mechanism's effectiveness arises because certain steps in gene expression analysis, such as loading GEO files, mapping gene symbols, and normalizing expression values, follow consistent patterns across datasets. By capturing these patterns in reusable code snippets, GenoMAS transforms redundant code generation into efficient lookups, allowing the system to allocate computational resources to novel, cohort-specific challenges.

G Biological Validation: Case Studies

We present detailed case studies examining genes identified for three complex traits in the unconditional gene-trait association (GTA) problem. For each trait, we assess the biological plausibility of genes selected by GenoMAS against established literature.

G.1 Alzheimer's Disease

The analysis identified 22 significant genes for Alzheimer's Disease. Several genes show strong biological support:

GABBR1 (GABA$_B$ Receptor 1) This gene, encoding the GABA$_B$ receptor subunit 1, exhibited the third-highest coefficient (in absolute value). GABA$_B$ receptors play crucial roles in synaptic plasticity and cognitive function. Multiple studies have implicated GABAergic signaling dysfunction in Alzheimer's pathology (Li et al., 2016; Fuhrer et al., 2017). The observed negative association is consistent with evidence that GABA$_B$ receptor expression is altered in Alzheimer's brains, potentially contributing to cognitive decline.

IGFBP5 (Insulin-like Growth Factor Binding Protein 5) IGFBP5 was selected by GenoMAS and modulates IGF-1 signaling, which is critical for neuronal survival and synaptic maintenance. Experimental studies indicate that IGFBP5 can influence neuronal apoptosis and autophagy (Itu et al., 2018), consistent with potential involvement in neurodegenerative processes.

VGF (VGF Nerve Growth Factor Inducible) VGF, a neuropeptide precursor, showed negative association with disease risk. This gene is highly expressed in neurons and plays roles in synaptic plasticity and neurogenesis. Reduced VGF levels have been reported in Alzheimer's cerebrospinal fluid and brain tissue (Carrette et al., 2003), supporting its role as a protective factor.

PAWR (PRKC Apoptosis WT1 Regulator) PAWR, also known as Par-4, is a pro-apoptotic protein with documented involvement in neurodegenerative diseases. The observed positive association with Alzheimer's risk is supported by studies showing elevated PAWR expression in Alzheimer's brains and its role in mediating neuronal apoptosis in response to amyloid-beta toxicity (Guo et al., 1998; Duan et al., 2014).

The identified genes span key pathological mechanisms including GABAergic dysfunction, insulin signaling dysregulation, synaptic impairment, and apoptotic processes.

G.2 Lung Cancer

The analysis identified 1,269 significant genes for lung cancer, reflecting the complex genetic architecture of this malignancy. Several genes show particularly strong supporting evidence:

TERT (Telomerase Reverse Transcriptase) TERT is one of the most well-established lung cancer susceptibility genes. TERT encodes the catalytic subunit of telomerase, and polymorphisms in

the TERT locus are among the most robust genetic risk factors for lung cancer across multiple populations (McKay et al., 2008; Rafnar et al., 2009). TERT activation is a hallmark of cancer, enabling unlimited replicative potential.

CYP1A1 (Cytochrome P450 Family 1 Subfamily A Member 1) CYP1A1 metabolizes polycyclic aromatic hydrocarbons and other tobacco smoke carcinogens. CYP1A1 polymorphisms have been extensively studied in lung cancer susceptibility, particularly in smoking-related cancers (Shi et al., 2008; Raimondi et al., 2009). The enzyme's role in bioactivation of procarcinogens makes it a key determinant of individual cancer risk.

RET (Ret Proto-Oncogene) RET alterations, particularly fusions, are established oncogenic drivers in lung adenocarcinoma, occurring in approximately 1-2% of cases (Kohno et al., 2012; Lipson et al., 2012). RET-targeted therapies have shown clinical efficacy, validating its role as a therapeutic target.

The identified genes span diverse cancer-relevant processes: telomere maintenance, carcinogen metabolism, DNA repair, oncogenic signaling, and cell cycle control.

G.3 Hypertension

The analysis identified 108 significant genes for hypertension. Several show particularly strong biological relevance:

TGFB2 (Transforming Growth Factor Beta 2) TGFB2 exhibited negative association with hypertension risk. TGF-β signaling plays complex roles in vascular remodeling and blood pressure regulation. Genetic variants in TGFB2 have been associated with blood pressure in multiple genome-wide association studies (Levy et al., 2009; Franceschini et al., 2013), and the protein influences vascular smooth muscle cell differentiation and arterial stiffness.

RHOA (Ras Homolog Family Member A) RHOA, encoding a small GTPase, showed negative association with hypertension. RhoA/Rho kinase signaling is a well-established regulator of vascular tone and contractility. Enhanced RhoA activity increases vascular smooth muscle contraction and contributes to hypertension pathogenesis (Loirand et al., 2006; Shi and Wei, 2013). The negative coefficient suggests that lower expression or activity may be protective, consistent with therapeutic strategies targeting this pathway.

CYP1B1 (Cytochrome P450 Family 1 Subfamily B Member 1) CYP1B1 metabolizes endogenous compounds including estrogens and arachidonic acid, generating vasoactive metabolites. Genetic and experimental evidence implicates CYP1B1 in blood-pressure regulation and angiotensin II-driven hypertension (Deng et al., 2011; Zhang et al., 2014).

EGR1 (Early Growth Response 1) EGR1, a transcription factor, showed negative association in our analysis. EGR1 is rapidly induced by various stimuli and regulates genes involved in vascular inflammation, smooth muscle proliferation, and fibrosis (Lee et al., 1995; Khachigian, 2006). Its dysregulation contributes to vascular remodeling and end-organ damage.

ANGPT2 (Angiopoietin 2) ANGPT2 regulates angiogenesis and vascular stability. Elevated ANGPT2 levels have been associated with endothelial dysfunction and cardiovascular disease. The observed positive association with hypertension is consistent with evidence linking ANGPT2 to vascular inflammation and adverse cardiovascular outcomes (David et al., 2009; Lee et al., 2014).

The identified genes are involved in multiple hypertension-relevant pathways: vascular tone regulation, smooth muscle contractility, endothelial function, metabolic control, and inflammatory responses.

G.4 Summary

Across all three traits, the identified genes show strong literature support and span diverse pathophysiological mechanisms specific to each disease. These include neurotransmitter signaling and neurodegeneration for Alzheimer's Disease, carcinogenesis and DNA repair for lung cancer, and vascular biology and blood pressure regulation for hypertension. The results encompass both well-established disease genes (e.g., TERT for lung cancer) and biologically plausible candidates that merit further investigation, demonstrating the potential of computational approaches for hypothesis generation in genomic medicine.

H   Examples of Autonomous Behaviors by Agents

This appendix provides concrete examples of autonomous agent behaviors observed during GenoMAS execution, demonstrating how programming agents adaptively handle edge cases and errors beyond their prescribed instructions. These examples

illustrate the system's robustness in processing diverse genomic datasets.

H.1 Example 1: Autonomous Error Correction in Clinical Trait Extraction (GSE98578)

In processing the Acute Myeloid Leukemia dataset GSE98578, the GEO agent encountered persistent failures in clinical trait extraction despite multiple revision attempts. Rather than continuing failed approaches, the agent autonomously decided to re-implement the entire clinical data extraction logic.

H.1.1 Context and Initial Failure

The agent initially attempted to extract clinical features using the standard library functions:

```
# Initial attempt (Step 2) - Failed
    due to undefined function
selected_clinical_df =
    geo_select_clinical_features(
    clinical_df=clinical_data,
    trait=trait,
    trait_row=trait_row,
    convert_trait=convert_trait,
    age_row=age_row,
    convert_age=convert_age,
    gender_row=gender_row,
    convert_gender=convert_gender
)
```

This failed because the `convert_trait` function was defined but not properly accessible in the execution context. Multiple debugging attempts failed to resolve the scoping issue.

H.1.2 Autonomous Recovery Strategy

In Step 7, the agent autonomously decided to override the previous implementation entirely:

```
# Autonomous re-implementation in
    Step 7
# Agent's comment: "Need to recreate
    the clinical data extraction
# since it wasn't successfully
    executed in Step 2"

def convert_trait(value):
    """Convert AML subtype to binary
        format.
    AMKL = 1, non-AMKL = 0
    """
    if value is None:
        return None

    if ':' in value:
        value = value.split(':', 1)
            [1].strip()

    if value.lower() == 'amkl':
        return 1
    elif value.lower() == 'non-amkl':
        return 0
    else:
        return None
```

```
# Re-execute the entire clinical data
    extraction
selected_clinical_data =
    geo_select_clinical_features(
    clinical_df=clinical_data,
    trait=trait,
    trait_row=trait_row,
    convert_trait=convert_trait,
    age_row=age_row,
    convert_age=None,
    gender_row=gender_row,
    convert_gender=None
)
```

This autonomous decision to completely re-implement rather than patch the existing code demonstrates the agent's ability to recognize when incremental fixes are insufficient and a fresh approach is needed.

H.2 Example 2: Retroactive Clinical Rule Application (GSE123088)

When processing the Obesity dataset GSE123088, the agent implemented clinical trait extraction logic correctly but initially forgot to apply it to the raw clinical data. The agent later recognized this omission and autonomously corrected it.

H.2.1 Initial Oversight

In Step 2, the agent defined comprehensive conversion functions but failed to execute the clinical feature extraction:

```
# Step 2: Defined functions but
    skipped execution
def convert_trait(value):
    """Convert trait value to binary
        (0=No Obesity, 1=Obesity)"""
    if pd.isna(value):
        return None
    if ':' in value:
        value = value.split(':', 1)
            [1].strip()
    if value == 'OBESITY' or 'OBESITY
        ' in value:
        return 1
    elif value == 'HEALTHY_CONTROL'
        or value == 'Control':
        return 0
    else:
        return None

# Agent's reasoning: "Skip this step
    since we don't have the
# actual clinical data file"
print("Clinical data extraction would
    require the actual clinical data
    file.")
```

H.2.2 Autonomous Correction

Recognizing the oversight in Step 7, the agent autonomously applied the previously defined rules:

```
# Step 7: Autonomous correction
# Agent's comment: "Clinical Data
    Extraction (which was skipped in
    Step 2)"

clinical_df =
    geo_select_clinical_features(
    clinical_data,
    trait=trait,
    trait_row=trait_row,
    convert_trait=convert_trait,
    age_row=age_row,
    convert_age=convert_age,
    gender_row=gender_row,
    convert_gender=convert_gender
)

print(f"Extracted clinical data with
    shape: {clinical_df.shape}")
print("Clinical data preview:")
print(preview_df(clinical_df))

# Save the clinical data
os.makedirs(os.path.dirname(
    out_clinical_data_file), exist_ok
    =True)
clinical_df.to_csv(
    out_clinical_data_file)
print(f"Clinical data saved to {
    out_clinical_data_file}")
```

This behavior shows the agent's ability to maintain awareness of incomplete tasks across multiple steps and autonomously correct oversights without explicit instructions.

H.3 Example 3: Early Task Termination Discovery (GSE125771)

In processing the Stroke dataset GSE125771, the planning mechanism initially failed to recognize that clinical trait data was unavailable. The agent discovered this limitation during execution and appropriately terminated the preprocessing task.

H.3.1 Planning Oversight

The initial planning assumed stroke trait data would be available in the clinical characteristics:

```
# Step 2: Initial analysis
# For trait (Stroke):
# This is a study on atherosclerotic
    plaques in carotid arteries
# All samples are from carotid
    plaques
# However, there's no explicit
    indication about which patients
    had stroke

trait_row = None  # No explicit
    stroke data available
```

H.3.2 Autonomous Task Termination

Upon discovering the absence of trait data, the agent made the autonomous decision to properly document the limitation and terminate:

```
# Step 7: Autonomous termination
    decision
# Agent's reasoning: "Based on the
    exploration, we can see that
# clinical data doesn't have stroke
    information"

# Mark dataset as not having trait
    data available
is_trait_available = False
is_gene_available = True

# Initial validation with is_final=
    False since we don't have trait
    data
validate_and_save_cohort_info(
    is_final=False,
    cohort=cohort,
    info_path=json_path,
    is_gene_available=
        is_gene_available,
    is_trait_available=
        is_trait_available
)

print("Dataset processing complete.
    The dataset has gene expression "
    +
    "data but lacks stroke trait
        information.")
```

This demonstrates the agent's ability to recognize fundamental data limitations and make appropriate decisions about task continuation, preventing wasted computational effort on impossible analyses.

H.4 Key Insights from Autonomous Behaviors

These examples reveal several important patterns in agent autonomy:

1. **Strategic Re-implementation**: Agents can recognize when incremental debugging is insufficient and autonomously choose to re-implement functionality from scratch (Example 1).

2. **Cross-step Error Correction**: Agents maintain awareness of incomplete tasks across workflow steps and can retroactively apply corrections without explicit prompting (Example 2).

3. **Intelligent Task Termination**: Agents can identify fundamental data limitations and make appropriate decisions about workflow continuation, saving computational resources (Example 3).

4. **Context-aware Problem Solving**: All examples demonstrate agents' ability to reason about the broader workflow context when

making autonomous decisions, rather than focusing narrowly on immediate instructions and error messages.

These autonomous behaviors emerge from the combination of comprehensive task history, flexible planning mechanisms, and the agents' underlying language model capabilities. They significantly enhance GenoMAS's robustness in handling the inherent variability and complexity of genomic data analysis.

I Examples of Notes Written by Agents

Throughout GenoMAS execution, agents generate structured notes that document their observations, challenges encountered, and potential issues discovered during data preprocessing. These self-reported notes serve multiple purposes: they enable efficient human oversight of system decisions, facilitate debugging of complex workflows, and provide insights into data quality issues that may affect downstream analyses. This section presents representative examples from actual experiment runs, organized by severity level.

I.1 Note Generation Mechanism

GenoMAS implements a systematic note-taking protocol where each agent logs observations during task execution. Notes are categorized into three severity levels:

- **INFO**: Routine observations about data characteristics, successful operations, and standard processing decisions

- **WARNING**: Potential issues that may affect analysis quality but do not prevent execution, such as small sample sizes or missing covariates

- **ERROR**: Critical failures that prevent dataset processing, including missing trait data or irrecoverable technical issues

Each note includes the dataset identifier, severity level, and contextual information that enables rapid assessment of preprocessing outcomes.

I.2 INFO-Level Notes: Documenting Standard Processing

INFO notes constitute the majority of agent observations, documenting successful preprocessing steps and dataset characteristics. These notes provide audit trails for quality assurance and enable researchers to understand processing decisions.

I.2.1 Dataset Characteristics

Agents systematically document processed dataset dimensions and properties:

```
GSE 92538 (Bipolar disorder):
  INFO: Dataset contains 161 samples
    after preprocessing with 11741
    genes.

GSE 46449 (Bipolar disorder):
  INFO: Dataset contains 88 samples
    after preprocessing with 19845
    genes.

GSE 124283 (Gaucher Disease):
  INFO: Successfully processed; gene
    symbols normalised where
    synonym
      file present.
```

These dimension reports enable quick verification that preprocessing preserved sufficient samples and features for meaningful analysis.

I.2.2 Technical Processing Decisions

Agents document specific technical choices made during preprocessing:

```
GSE 123086 (Crohn's Disease):
  INFO: Dataset successfully
    processed with gene expression
    data from
      CD4+ T cells across multiple
        diseases including Crohn'
        s disease.
      Gene identifiers kept as
        Entrez IDs.

GSE 117261 (Multiple sclerosis):
  INFO: Processed; gene symbols
    normalised with synonym
    dictionary.

GSE 34788 (Heart rate):
  INFO: Gene-level matrix rebuilt;
    clinical trait consistent with
      STEP-2; proper normalisation
        applied.
```

These notes reveal how agents adapt to different identifier systems (Entrez IDs vs. gene symbols) and apply appropriate normalization strategies based on data characteristics.

I.2.3 Special Dataset Contexts

Agents provide contextual information about dataset origins and study designs:

```
GSE 77790 (Esophageal Cancer):
  INFO: Dataset contains esophageal
    cancer cell lines (TE8, TE9) as
      cases and other cancer cell
        lines as controls. Highly
      imbalanced with only 2
        esophageal cancer samples
          out of 32 total.
```

```
GSE100843 (Esophageal Cancer):
  INFO: Dataset from Barrett's
      esophagus vitamin D
      supplementation
        study with pre/post treatment
            samples from both
              Barrett's
        segment and normal mucosa.

GSE131027 (Esophageal Cancer):
  INFO: Dataset includes a wide range
      of cancer types to identify
      pathogenic germline variants.
          'Esophageal cancer' is
          treated
      as the case group.
```

These contextual notes help researchers understand potential limitations, such as severe class imbalance or indirect disease proxies.

I.3 WARNING-Level Notes: Identifying Potential Issues

WARNING notes alert researchers to conditions that may compromise analysis quality without preventing execution. These notes guide interpretation of results and highlight datasets requiring careful consideration.

I.3.1 Sample Size Limitations

Agents flag datasets with limited statistical power:

```
GSE186963 (Crohn's Disease):
  WARNING: Very small sample size
      after preprocessing.

GSE68950 (Mesothelioma):
  WARNING: Small sample size may
      limit statistical power.

GSE107754 (Mesothelioma):
  WARNING: Trait distribution is
      severely biased in this dataset
      .
```

I.3.2 Missing Covariate Data

Agents identify when important demographic or clinical covariates are unavailable:

```
GSE181339 (Hypertension):
  WARNING: Trait data not available;
      cohort unusable for association
          analysis.

GSE173263 (Large B-cell Lymphoma):
  WARNING: Trait data not available
      in this cohort.

GSE114022 (Large B-cell Lymphoma):
  WARNING: Trait data missing -
      cohort unusable for association
          analysis.
```

I.3.3 Data Distribution Issues

Agents detect problematic trait distributions:

```
GSE27597 (Von Willebrand Disease):
  WARNING: Von Willebrand Disease
      trait is severely biased - all
      samples
          have the same value (0) in
              this COPD/emphysema
          study.
```

These warnings enable researchers to exclude problematic datasets from meta-analyses or apply appropriate statistical corrections.

I.4 ERROR-Level Notes: Critical Processing Failures

ERROR notes document failures that prevent dataset integration into the analysis pipeline. These notes provide diagnostic information for troubleshooting and dataset exclusion decisions.

I.4.1 Gene Mapping Failures

Technical incompatibilities in gene annotation prevent successful preprocessing:

```
GSE93114 (Bipolar disorder):
  ERROR: Gene symbol mapping failed
      because no suitable gene symbol
          column could be identified
              in the platform
              annotation.

GSE158237 (Obesity):
  ERROR: No column containing gene
      symbols could be identified in
      the
          platform annotation; probe-
              to-gene mapping
              impossible.

GSE35661 (Heart rate):
  ERROR: Gene mapping failed due to
      an inconsistency between the
      probe
          IDs in the expression matrix
              (ENST-based) and the
              annotation
          in the SOFT file (Affymetrix
          -based).
```

I.4.2 Missing Trait Information

Absence of phenotype data prevents case-control analyses:

```
GSE67311 (Bipolar disorder):
  ERROR: Trait has only 0 distinct
      values

GSE65399 (Mitochondrial Disorders):
  ERROR: Dataset lacks trait
      information for Mitochondrial_
      Disorders.
          Only gene expression data is
              available.
```

```
GSE 203241 (Multiple sclerosis):
  ERROR: Dataset lacks Multiple
      Sclerosis case/control trait
      information
          required for association
                  study.
```

I.4.3 Data Structure Incompatibilities

Fundamental data organization issues prevent processing:

```
GSE 271700 (Obesity):
  ERROR: Gene mapping failed. The
      SOFT file does not contain the
      necessary probe-to-gene-
          symbol annotation table.

GSE 186963 (Crohn's Disease):
  ERROR: Preprocessing failed due to
      an unrecoverable mismatch in
      sample IDs between clinical
              and genetic data files.
```

I.5 Leveraging Notes for System Improvement

The structured note system enables several work-flows for continuous improvement:

Quality Assurance Workflow Researchers can filter notes by severity to prioritize review efforts. ERROR notes immediately identify datasets requiring exclusion or manual intervention. WARN-ING notes guide sensitivity analyses and robustness checks. INFO notes provide comprehensive audit trails for reproducibility.

Data Curation Insights Patterns in ERROR notes reveal common issues in public genomic databases. For instance, the frequency of gene mapping errors highlights the need for standard-ized annotation practices. Missing trait data errors suggest opportunities for enhanced metadata cura-tion in repository submissions.

System Enhancement Opportunities Recurring error patterns inform development priorities. For example, the prevalence of probe-to-gene mapping failures led to enhanced synonym dictionaries and platform-specific mapping strategies in subsequent GenoMAS versions.

I.6 Summary

The agent-generated notes demonstrate Geno-MAS's ability to provide transparent, interpretable preprocessing workflows. By systematically doc-umenting observations across severity levels, the system enables efficient human oversight while maintaining full automation. These notes not only

facilitate immediate quality control but also provide valuable insights for improving both the system and underlying data resources. The examples presented here, drawn from hundreds of preprocessing runs across diverse diseases and platforms, illustrate how structured self-reporting enhances the reliabil-ity and interpretability of automated genomic data analysis.

J Multi-agent Collaboration Patterns

(a) Agent collaboration network

(b) Message type distribution heatmap

Figure 5: **Agent collaboration patterns in GenoMAS.** (a) Network topology showing agent communication structure with node size proportional to message vol-ume. Edge thickness indicates interaction frequency. (b) Distribution of message types across agent pairs reveal-ing asymmetric communication patterns, with program-ming agents predominantly sending validation requests while advisory agents respond with feedback. GEO and TCGA agents are merged into Data Engineer for brevity.

Figure 5 visualizes GenoMAS's agent communi-cation structure during a representative 20-problem analysis session. The Data Engineer (merged GEO and TCGA agents) dominates with 56.9% of in-teractions (1,956 messages), reflecting its central role in processing gene expression data, while the

Statistician Agent accounts for 11.6% of interactions (398 messages) for analytical tasks. The PI agent's minimal 2.3% messaging efficiently orchestrates the workflow, with intensive bidirectional communication between programming and advisory agents enabling collaborative navigation of genomic complexities. These patterns highlight key insights for multi-agent systems: The Data Engineer's dominance emphasizes the benefits of role specialization, which centralizes intensive tasks while distributing expertise, mirroring organizational research on cognitive diversity (Hong and Page, 2004) as manifested in our heterogeneous LLM architecture. The PI's low involvement demonstrates the system's high degree of autonomy (97.7% self-coordinated interactions), which contributes to a 44.7% API cost reduction over prior methods.

The heatmap reveals that Planning Requests/Responses (634 each) dominate, validating the role of our guided planning framework at every juncture of task execution. Code validation (351 requests) ranks second, with low error messages (36 revisions) indicating effective error prevention through multi-turn advisory mechanisms and guided planning, correlating with our 98.78% success rate.

Overall, these metrics reveal design principles for computational biology agents: balancing centralized execution with distributed expertise minimizes overhead and boosts adaptability, ultimately enabling scalable analysis that outperforms prior art by 16.85% in F_1 score.