Improving Diffusion Models for Inverse Problems using Manifold Constraints

Abstract

Recently, diffusion models have been used to solve various inverse problems in an unsupervised manner with appropriate modifications to the sampling process. However, the current solvers, which recursively apply a reverse diffusion step followed by a projection-based measurement consistency step, often produce sub-optimal results. By studying the generative sampling path, here we show that current solvers throw the sample path off the data manifold, and hence the error accumulates. To address this, we propose an additional correction term inspired by the manifold constraint, which can be used synergistically with the previous solvers to make the iterations close to the manifold. The proposed manifold constraint is straightforward to implement within a few lines of code, yet boosts the performance by a surprisingly large margin. With extensive experiments, we show that our method is superior to the previous methods both theoretically and empirically, producing promising results in many applications such as image inpainting, colorization, and sparse-view computed tomography.

1 Introduction

Diffusion models have shown impressive performance both as generative models themselves [38, 11], and also as unsupervised inverse problem solvers [38, 7, 8, 23] that do not require problem-specific training. Specifically, given a pre-trained unconditional score function (i.e. denoiser), solving the reverse stochastic differential equation (SDE) numerically would amount to sampling from the data generating distribution [38]. For many different inverse problems (e.g. super-resolution [7, 8], inpainting [38, 8], compressed-sensing MRI (CS-MRI) [37, 8], sparse view CT (SV-CT) [37], etc.), it was shown that simple incorporation of the measurement process produces satisfactory conditional samples, even when the model was not trained for the specific problem.

Nevertheless, for certain problems (e.g. inpainting), currently used algorithms often produce unsatisfactory results when implemented naively (e.g. boundary artifacts, as shown in Fig. 1 (b)). The authors in [29] showed that in order to produce high quality reconstructions, one needs to iterate back and forth between the noising and the denoising step at least > 10 times *per iteration*. These iterations are computationally demanding and should be avoided, considering that diffusion models are slow to sample from even without such iterations. On the other hand, a classic result of Tweedie's formula [34, 39] shows that one can perform Bayes optimal denoising in one step, once we know the gradient of the log density. Extending such result, it was recently shown that one can indeed perform a single-step denoising with learned score functions for denoising problems from general exponential family noises [26].

In this work, we leverage the denoising result through Tweedie's formula and show that such denoised samples can be the key to significantly improve the performance of reconstruction using diffusion models across arbitrary inverse problems, despite the simplicity in the implementation. Moreover, we

Figure 1: Visual schematic of the MCG correction step. (a) ① Unconditional reverse diffusion generates $\boldsymbol{x}_i$; ② Q_i maps the noisy $\boldsymbol{x}_i$ to generate $\hat{\boldsymbol{x}}_0$; ③ Manifold Constrained Gradient (MCG) $\frac{\partial}{\partial \boldsymbol{x}_i}\|\boldsymbol{W}(\boldsymbol{y}-\boldsymbol{H}\hat{\boldsymbol{x}}_0)\|_2^2$ is applied to fix the iteration on manifold; ④ Takes the orthogonal complement; ⑤ Samples from $p(\boldsymbol{y}_i|\boldsymbol{y})$, then combines $\boldsymbol{A}\boldsymbol{x}_{i-1}'$ and $\boldsymbol{y}_i$. (b) Representative results of inpainting, compared with score-SDE [38]. Reconstructions with score-SDE produce incoherent results, while our method produces high fidelity solutions.

theoretically prove that if the score function estimation is globally optimal, the correction term from the manifold constraint enforces the sample path to stay on the plane tangent to the data manifold[1], so by combining with the reverse diffusion step, the solution becomes more stable and accurate.

2 Related Works

2.1 Diffusion Models

Continuous Form For a continuous diffusion process $\boldsymbol{x}(t) \in \mathbb{R}^n$, $t \in [0, 1]$, we set $\boldsymbol{x}(0) \sim p_0(\boldsymbol{x}) = p_{data}$, where p_{data} represents the data distribution of interest, and $\boldsymbol{x}(1) \sim p_1(\boldsymbol{x})$, with $p_1(\boldsymbol{x})$ approximating spherical Gaussian distribution, containing no information of data. Here, the forward noising process is defined with the following Itô stochastic differential equation (SDE) [38]:

$$d\boldsymbol{x} = \bar{\boldsymbol{f}}(\boldsymbol{x}, t)dt + \bar{g}(t)d\boldsymbol{w}, \tag{1}$$

with $\bar{\boldsymbol{f}} : \mathbb{R}^d \mapsto \mathbb{R}^d$ defining the linear drift function, $\bar{g}(t) : \mathbb{R} \mapsto \mathbb{R}$ defining a scalar diffusion coefficient, and $\boldsymbol{w} \in \mathbb{R}^n$ denoting the standard $n-$dimensional Wiener process. The forward SDE in (1) is coupled with the following reverse SDE by Anderson's theorem [1, 38]

$$d\boldsymbol{x} = [\bar{\boldsymbol{f}}(\boldsymbol{x}, t) - \bar{g}(t)^2 \nabla_{\boldsymbol{x}} \log p_t(\boldsymbol{x})]dt + \bar{g}(t)d\bar{\boldsymbol{w}}, \tag{2}$$

with dt denoting the infinitesimal negative time step, and $\bar{\boldsymbol{w}}$ defining the standard Wiener process running backward in time. Note that the reverse SDE defines the generative process through the score function $\nabla_{\boldsymbol{x}} \log p_t(\boldsymbol{x})$, which in practice, is typically replaced with $\nabla_{\boldsymbol{x}} \log p_{0t}(\boldsymbol{x}(t)|\boldsymbol{x}(0))$ to minimize the following denoising score-matching objective

$$\min_{\theta} \mathbb{E}_{t\sim U(\varepsilon,1),\boldsymbol{x}(t)\sim p(\boldsymbol{x}(t))} \left[\|\boldsymbol{s}_{\theta}(\boldsymbol{x}(t), t) - \nabla_{\boldsymbol{x}_t} \log p(\boldsymbol{x}(t)|\boldsymbol{x}(0))\|_2^2\right], \tag{3}$$

Once the parameter θ^* for the score function is estimated, one can replace the score function in (2) with $s_{\theta^*}(\boldsymbol{x}(t), t)$ to solve the reverse SDE.

Discrete Form Due to the linearity of $\bar{\boldsymbol{f}}$ and $\bar{g}$, the forward diffusion step can be implemented with a simple reparameterization trick [27]. Namely, the general form of the forward diffusion is

$$\boldsymbol{x}_i = a_i \boldsymbol{x}_0 + b_i \boldsymbol{z}, \quad \boldsymbol{z} \sim \mathcal{N}(0, \boldsymbol{I}), \tag{4}$$

where we have replaced the continuous index $t \in [0, 1]$ with the discrete index $i \in \mathbb{N}$. On the other hand, the discrete reverse diffusion step is implemented as

$$\boldsymbol{x}_{i-1} = \boldsymbol{f}(\boldsymbol{x}_i, \boldsymbol{s}_{\theta}) + g(\boldsymbol{x}_i)\boldsymbol{z}, \quad \boldsymbol{z} \sim \mathcal{N}(0, \boldsymbol{I}), \tag{5}$$

where we have replaced the ground truth score function with the trained one. We detail the choice of $a_i, b_i, \boldsymbol{f}, g$ in Section. B.

---

[1]We coin our method **M**anifold **C**onstrained **G**radient (MCG).

2.2 Conditional Generative models for Inverse problems

The main problem of our interest in this paper is the inverse problem, retrieving the unknown $\boldsymbol{x} \in \mathbb{R}^n$ from a measurement $\boldsymbol{y}$:

$$\boldsymbol{y} = \boldsymbol{H}\boldsymbol{x} + \boldsymbol{\epsilon}, \quad \boldsymbol{y} \in \mathbb{R}^m, \boldsymbol{H} \in \mathbb{R}^{m \times n}, \tag{6}$$

where $\boldsymbol{\epsilon} \in \mathbb{R}^m$ is the noise in the measurement. Accordingly, for the case of the inverse problems, our goal is to generate samples from a conditional distribution with respect to the measurement $\boldsymbol{y}$, i.e. $p(\boldsymbol{x}|\boldsymbol{y})$. Accordingly, the score function $\nabla_{\boldsymbol{x}} \log p_t(\boldsymbol{x})$ in (2) should be replaced by the conditional score $\nabla_{\boldsymbol{x}} \log p_t(\boldsymbol{x}|\boldsymbol{y})$. Unfortunately, this strictly restricts the generalization capability of the neural network since the conditional score should be retrained whenever the conditions change. To address this, recent conditional diffusion models [20, 38, 7, 8] utilize the unconditional score function $\nabla_{\boldsymbol{x}} \log p_t(\boldsymbol{x})$ but rely on a projection-based measurement constraint to impose the conditions. Specifically, one can apply the following:

$$\boldsymbol{x}'_{i-1} = \boldsymbol{f}(\boldsymbol{x}_i, s_\theta) + g(\boldsymbol{x}_i)\boldsymbol{z}, \quad \boldsymbol{z} \sim \mathcal{N}(0, \boldsymbol{I}), \tag{7}$$

$$\boldsymbol{x}_{i-1} = \boldsymbol{A}\boldsymbol{x}'_{i-1} + \boldsymbol{b}_i, \tag{8}$$

where $\boldsymbol{A}, \boldsymbol{b}_i$ are function of $\boldsymbol{H}, \boldsymbol{y}_0$, and $\boldsymbol{x}_0$. Note that (7) is identical to the unconditional reverse diffusion step in (5), whereas (8) effectively imposes the condition. It was shown in [8] that any general contraction mapping (e.g. projection onto convex sets, gradient step) may be utilized as (8) to impose the constraint.

Another recent work [23] advancing [24] establishes the state-of-the-art (SOTA) in solving *noisy* inverse problems with unconditional diffusion models, by running the conditional reverse diffusion process in the spectral domain achieved by performing singular value decomposition (SVD), and leveraging approximate gradient of the log likelihood term in the spectral space. The authors show that feasible solutions can be obtained with as small as 20 diffusion steps. Prior to the development of diffusion models, Plug-and-Play (PnP) models [44, 49, 41] were used in a similar fashion by utilizing a general-purpose unconditional denoiser in the place of proximal mappings in model-based reconstruction methods [5, 3]. Similarly, outside the context of diffusion models, iterative denoising followed by projection-based data consistency was proposed in [41]. In such view, diffusion models can be understood as generative variant of PnPs trained with multiple scales of noise. GAN-based solvers are also popular [4, 9, 18], where the pre-trained generators are tuned at test time by optimizing over the latent, the parameters, or jointly.

2.3 Tweedie's formula for denoising

In the case of Gaussian noise, a classic result of Tweedie's formula [34] tells us that one can achieve the denoised result by computing posterior expectation:

$$\mathbb{E}[\boldsymbol{x}|\tilde{\boldsymbol{x}}] = \tilde{\boldsymbol{x}} + \sigma^2 \nabla_{\tilde{\boldsymbol{x}}} \log p(\tilde{\boldsymbol{x}}), \tag{9}$$

when the noise is modeled by $\tilde{\boldsymbol{x}} \sim \mathcal{N}(\boldsymbol{x}, \sigma^2 I)$. If we consider a diffusion model of which forward step is modeled as $\boldsymbol{x}_i \sim \mathcal{N}(a_i \boldsymbol{x}_0, b_i^2 I)$ (discrete form), the Tweedie's formular is rewritten:

$$\mathbb{E}[\boldsymbol{x}_0|\boldsymbol{x}_i] = (\boldsymbol{x}_i + b_i^2 \nabla_{\boldsymbol{x}_i} \log p(\boldsymbol{x}_i))/a_i. \tag{10}$$

Tweedie's formula is in fact not only relevant to Gaussian denoising in the Bayesian framework, but have also been extended to be in close relation with kernel regression [31]. Moreover, it was shown that it can be applied to arbitrary exponential noise distributions beyond Gaussian [12, 26]. In the following, we use this key property to develop our algorithm.

3 Conditional Diffusion using Manifold Constraints

Although our original motivation of using the measurement constraint step in (8) was to utilize the unconditionally trained score function in the reverse diffusion step in (7), there is room for imposing additional constraints while still using the unconditionally trained score function.

Specifically, the Bayes rule $p(\boldsymbol{x}|\boldsymbol{y}) = p(\boldsymbol{y}|\boldsymbol{x})p(\boldsymbol{x})/p(\boldsymbol{y})$ leads to

$$\nabla_{\boldsymbol{x}} \log p(\boldsymbol{x}|\boldsymbol{y}) = \nabla_{\boldsymbol{x}} \log p(\boldsymbol{x}) + \nabla_{\boldsymbol{x}} \log p(\boldsymbol{y}|\boldsymbol{x}). \tag{11}$$

(a) Geometry of diffusion model (b) MCG correction

Figure 2: In both (a) and (b), the central manifolds represent data manifolds $\mathcal{M}$, encircled by manifolds of noisy data $\mathcal{M}_i$. The concentration on manifold of noisy data and the distance from the clean data manifold are prescribed by Proposition 1. In (a), the backward (resp. forward) step depicted by blue (resp. red) arrows can be considered as transitions from $\mathcal{M}_i$ to $\mathcal{M}_{i-1}$ (resp. $\mathcal{M}_{i-1}$ to $\mathcal{M}_i$). In (b), arrows refer to the directions of conventional projection onto convex sets (POCS) step (green arrow) and MCG step (red arrow) which can be predicted by Theorem 1.

Hence, the score function in the reverse SDE in (2) can be replaced by (11), leading to

$$\boldsymbol{x}'_{i-1} = \boldsymbol{f}(\boldsymbol{x}_i, \boldsymbol{s}_\theta) - \alpha \frac{\partial}{\partial \boldsymbol{x}_i} \|\boldsymbol{W}(\boldsymbol{y} - \boldsymbol{H}\boldsymbol{x}_i)\|_2^2 + g(\boldsymbol{x}_i)\boldsymbol{z}, \quad \boldsymbol{z} \sim \mathcal{N}(0, \boldsymbol{I}) \tag{12}$$

where α and $\boldsymbol{W}$ depend on the noise covariance, if the noise $\boldsymbol{\epsilon}$ in (6) is Gaussian.

Now, one of the important contributions of this paper is to reveal that the Bayes optimal denoising step in (10) from Tweedie formula leads to a preferred condition both empirically and theoretically. Specifically, we define the set constraint for $\boldsymbol{x}_i$, called the *manifold constraint gradient (MCG)*, so that the gradient of the measurement terms stays on the manifold (see Theorem 1):

$$\boldsymbol{x} \in \mathcal{X}_i, \quad \text{where} \quad \mathcal{X}_i = \{\boldsymbol{x} \in \mathbb{R}^n \mid \boldsymbol{x} = (\boldsymbol{x} + b_i^2 \boldsymbol{s}_\theta(\boldsymbol{x}, i))/a_i\} \tag{13}$$

To deal with the potential deviation from the measurement consistency, we again impose the data consistency step (8). Putting them together, the discrete reverse diffusion under the additional manifold constraint and the data consistency can be represented by

$$\boldsymbol{x}'_{i-1} = \boldsymbol{f}(\boldsymbol{x}_i, \boldsymbol{s}_\theta) - \alpha \frac{\partial}{\partial \boldsymbol{x}_i} \|\boldsymbol{W}(\boldsymbol{y} - \boldsymbol{H}\hat{\boldsymbol{x}}_0(\boldsymbol{x}_i))\|_2^2 + g(\boldsymbol{x}_i)\boldsymbol{z}, \quad \boldsymbol{z} \sim \mathcal{N}(0, \boldsymbol{I}), \tag{14}$$

$$\boldsymbol{x}_{i-1} = \boldsymbol{A}\boldsymbol{x}'_{i-1} + \boldsymbol{b}. \tag{15}$$

We illustrate our scheme visually in Fig. 1 (a), specifically for the task of image inpainting. The additional step leads to dramatic performance boost, as can be seen in Fig. 1 (b). Note that while the mapping (10) does not rely on the measurement, our gradient term in (14) incorporates the information of $\boldsymbol{y}$ so that the gradient of the measurement terms stays on the manifold. In the following, we articulate how the proposed MCG can be incorporated into each application, and study the theoretical properties of the method. Further algorithmic details and adaptations to the each problem that we tackle are presented in Section C.

We note that the authors of [17] proposed a similar gradient method for the application of temporal imputation and super-resolution. When combining (14) with (15), one can arrive at a similar gradient method proposed in [17], and hence our method can be seen as a generalization to arbitrary linear inverse problems.

4 Geometry of Diffusion Model and Manifold Constraint Gradient

In this section, we theoretically support the effectiveness of the proposed algorithm by showing the problematic behavior of the earlier algorithm and how the proposed algorithm resolves the problem.

125 We defer all proofs in the supplementary section. To begin with, we borrow a geometrical viewpoint
126 of the data manifold.

127 **Notation** For a scalar a, points $\boldsymbol{x}, \boldsymbol{y}$ and a set A, we use the following notations. $aA := \{a\boldsymbol{x} : \boldsymbol{x} \in$
128 $A\}; d(\boldsymbol{x}, A) := \inf_{\boldsymbol{y} \in A} \|\boldsymbol{x} - \boldsymbol{y}\|_2; B_r(A) := \{\boldsymbol{x} : d(\boldsymbol{x}, A) < r\}; T_{\boldsymbol{x}}\mathcal{M}$: the tangent space of to a
129 manifold $\mathcal{M}$ at $\boldsymbol{x}$; $\boldsymbol{J}_f$: the Jacobian matrix of a vector valued function f. We define $p_0 = p_{data}$.

130 To develop the theory, we need an assumption on the data distribution.

> **Assumption 1** (Strong manifold assumption: linear structure). *Suppose $\mathcal{M} \subset \mathbb{R}^n$ is the set of all
> data points, here we call the data manifold. Then, the manifold coincides with the tangent space with
> dimension $l \ll n$.*
> $$\mathcal{M} \cap B_R(\boldsymbol{x}_0) = T_{x_0}\mathcal{M} \cap B_R(x_0) \text{ and } T_{x_0}\mathcal{M} \cong \mathbb{R}^l.$$
131 *Moreover, the data distribution p_0 is the uniform distribution on the data manifold $\mathcal{M}$.*

132 We need to recall that the conventional manifold assumption is about the intrinsic geometry of data
133 points having a low dimensional nature. However, we assume more in this work: the manifold
134 is locally linear. Although this stronger assumption might narrow the practice of the theory, the
135 geometric approach may provide new insights on diffusion models. Under this assumption, the
136 following proposition shows how the data perturbed by noise lies in the ambient space, illustrated
137 pictorially in Fig. 2a.

138 **Proposition 1** (Concentration of noisy data). *Consider the distribution of noisy data $p_i(\boldsymbol{x}_i) =$
139 $\int p(\boldsymbol{x}_i|\boldsymbol{x})p_0(\boldsymbol{x})d\boldsymbol{x}, p(\boldsymbol{x}_i|\boldsymbol{x}) \sim \mathcal{N}(a_i\boldsymbol{x}, b_i^2\boldsymbol{I})$. Then $p_i(\boldsymbol{x}_i)$ is concentrated on $(n-1)$-dim manifold
140 $\mathcal{M}_i := \{\boldsymbol{y} \in \mathbb{R}^n : d(\boldsymbol{y}, a_i\mathcal{M}) = r_i := b_i\sqrt{n-l}\}$. Rigorously, $p(B_{\epsilon r_i}(\mathcal{M}_i)) > 1 - \delta$.*

141 **Remark 1** (Geometric interpretation of diffusion process). *Considering Proposition 1, the manifolds
142 of noise data can be interpreted as interpolating manifolds between the two: the hypersphere, where
143 pure noise $\mathcal{N}(\boldsymbol{x}_0, b_\infty^2)$ is concentrated, and the clean data manifold. In this regard, the diffusion
144 steps are mere transitions from one manifold to another and the diffusion process is a transport from
145 the data manifold to the hypersphere through interpolating manifolds. See Fig. 2a.*

146 **Remark 2.** *We can infer from the proposition that the score functions are trained only with the data
147 points concentrated on the noisy data manifolds. Therefore, inaccurate inference might be caused by
148 application of a score function on points away from the noisy data manifold.*

> **Proposition 2** (score function). *Suppose s_θ is the minimizer of the denoising score matching loss in
> (3). Let Q_i be the function that maps $\boldsymbol{x}_i$ to $\hat{\boldsymbol{x}}_0$ for each i,*
> $$Q_i : \mathbb{R}^d \to \mathbb{R}^d, \boldsymbol{x}_i \mapsto \hat{\boldsymbol{x}}_0 := \frac{1}{a_i}(\boldsymbol{x}_i + b_i^2 s_\theta(\boldsymbol{x}_i, i)).$$
149 *Then, $Q_i(\boldsymbol{x}_i) \in \mathcal{M}$ and $\boldsymbol{J}_{Q_i}^2 = \boldsymbol{J}_{Q_i} = \boldsymbol{J}_{Q_i}^T : \mathbb{R}^d \to T_{Q_i(\boldsymbol{x}_i)}\mathcal{M}$. Intuitively, Q_i is locally an
150 orthogonal projection onto $\mathcal{M}$.*

151 According to the proposition, the score function only concerns the normal direction of the data
152 manifold. In other words, the score function cannot discriminate two data points whose difference is
153 tangent to the manifold. In solving inverse problems, however, we desire to discriminate data points
154 to reconstruct the original signal, and the discrimination is achievable by measurement fidelity. In
155 order to achieve the original signal, the measurement plays a role in correcting the tangent component
156 near the data manifold. Furthermore, with regard to remark 2, diffusion model-based inverse problem
157 solvers should follow the tangent component. The following theorem shows how existing algorithms
158 and the proposed method are different in this regard.

159 **Theorem 1** (Manifold constrained gradient). *A correction by the manifold constrained gradient does
160 not leave the data manifold. Formally,*

$$\frac{\partial}{\partial \boldsymbol{x}_i}\|\boldsymbol{W}(\boldsymbol{y} - \boldsymbol{H}\hat{\boldsymbol{x}}_0)\|_2^2 = -2\boldsymbol{J}_{Q_i}^T\boldsymbol{H}^T\boldsymbol{W}^T\boldsymbol{W}(\boldsymbol{y} - \boldsymbol{H}\hat{\boldsymbol{x}}_0) \in T_{\hat{\boldsymbol{x}}_0}\mathcal{M},$$

161 *the gradient is the projection of data fidelity term onto $T_{\hat{\boldsymbol{x}}_0}\mathcal{M}$,*

162 This theorem suggests that in diffusion models, the naive measurement fidelity step (without consid-
163 ering the data manifold) pushes the inference path out of the manifolds and might lead to inaccurate
164 reconstruction. (To see this pictorially, see section. D, and Fig. 7.) On the other hand, our correction
165 term from the manifold constraint guides the diffusion to lie on the data manifold, leading to better
166 reconstruction. Such geometric views are illustrated in Fig. 2b.

Figure 3: Inpainting results on FFHQ (1st, 2nd row) and ImageNet (3rd, 4th row). (a) Measurement, (b) Ground truth, (c) IAGAN [18] for FFHQ, LaMa [40] for ImageNet, (d) DDRM [23], (e) Score-SDE [38], (f) RePAINT [29], (g) MCG (Ours). Out of 256×256 image, the 1st and the 3rd row is masked with size 128×128 box. 92% of pixels (all RGB channels) from the images in the 2nd and 4th row are blocked.

Remark 3. *One may concern that the suboptimality of the denoising score matching loss optimization may lead to inaccurate inference of the MCG steps. In practice, however, most of the error in denoising score matching is concentrated on $t \sim 1$[8], and in such region, the Tweedie's inference cannot make meaningful images. That is, the score function cannot detect the data manifold. Nonetheless, in this regime, the magnitudes of the MCGs are small when the denoising score is inaccurate, and hence the matters arising from suboptimality is minimal. As $t \to 0$, the estimation becomes exact, and subsequently leads to accurate implementation of the MCG.*

5 Experiments

For all tasks, we aim to verify the superiority of our method against other diffusion model-based approaches, and also against strong supervised learning-based baselines. Further details can be found in Section. F.

Datasets and Implementation For inpainting, we use FFHQ 256×256 [22], and ImageNet 256×256 [10] to validate our method. We utilize pre-trained models from the open sourced repository based on the implementation of ADM (VP-SDE) [11]. We validate the performance on 1000 held-out validation set images for both FFHQ and ImageNet dataset. For the colorization task, we use FFHQ, and LSUN-bedroom 256×256 [47]. We use pre-trained score functions from score-SDE [38] based on VE-SDE. We use 300 validation images for testing the performance with respect to the LSUN-bedroom dataset. For experiments with CT, we train our model based on ncsnpp as a VE-SDE from score-SDE [38], on the 2016 American Association of Physicists in Medicine (AAPM) grand challenge dataset, and we process the data as in [21]. Specifically, the dataset contains 3839 training images resized to 256×256 resolution. We simulate the CT measurement process with parallel beam geometry with evenly-spaced 180 degrees. Evaluation is performed on 421 held-out validation images from the AAPM challenge.

Inpainting Score-SDE [38], REPAINT [29], DDRM [23] were chosen as baseline diffusion models to compare against the proposed method. For a fair comparison, we use the same score function for all methods including MCG, and only differentiate the inference method that is used. Another class of generative models: GAN-based inverse problem solver, IAGAN [18] is considered as a comparison method for FFHQ specifically. We also include comparisons against supervised learning

Method	FFHQ (256 × 256) Box FID ↓	LPIPS ↓	Random FID ↓	LPIPS ↓	Extreme FID ↓	LPIPS ↓	Wide masks FID ↓	LPIPS ↓	ImageNet (256 × 256) Box FID ↓	LPIPS ↓	Random FID ↓	LPIPS ↓	Wide masks FID ↓	LPIPS ↓
MCG (ours)	**23.7**	0.089	**21.4**	**0.186**	**30.6**	**0.366**	**22.1**	0.099	**25.4**	0.157	**34.8**	**0.308**	**21.9**	0.148
Score-SDE [38]	30.3	0.135	109.3	0.674	48.6	0.488	29.8	0.132	43.5	0.199	143.5	0.758	25.9	0.150
RePAINT* [29]	25.7	0.093	38.1	0.240	35.9	0.398	24.2	0.108	26.1	0.156	59.3	0.387	37.0	0.205
DDRM [23]	28.4	0.109	111.6	0.774	48.1	0.532	27.5	0.113	88.8	0.386	99.6	0.767	80.6	0.398
LaMa [40]	27.7	**0.086**	188.7	0.648	61.7	0.492	23.2	**0.096**	26.8	**0.139**	134.1	0.567	**20.4**	**0.140**
AOT-GAN [48]	29.2	0.108	97.2	0.514	69.5	0.452	28.3	0.106	35.3	0.163	119.6	0.583	29.8	0.161
ICT [45]	27.3	0.103	91.3	0.445	56.7	0.425	26.9	0.104	31.9	0.148	131.4	0.584	25.4	0.148
DSI [32]	27.9	0.096	126.4	0.601	77.5	0.463	28.3	0.102	34.5	0.155	132.9	0.549	24.3	0.154
IAGAN [18]	26.3	0.098	41.5	0.279	56.1	0.417	23.8	0.110	-	-	-	-	-	-

Table 1: Quantitative evaluation (FID, LPIPS) of inpainting task on FFHQ and ImageNet. *: Re-implemented with our score function. MCG, Score-SDE, RePAINT, and DDRM all share the same score function and differ only in the inference method. **Bold**: Best, under: second best.

Figure 4: Colorization results on FFHQ / LSUN-bedroom, Sparse view CT reconstruction results on AAPM.

based baselines: LaMa [40], AOT-GAN [48], ICT [45], and DSI [32]. We use various forms of inpainting masks: box (128×128 sized square region is missing[2]), extreme (only the box region is existent), random (90-95% of pixels are missing), and LaMa-wide. Quantitative evaluation is performed with two metrics - Frechet Inception Distance (FID)-1k [15], and Learned Perceptual Image Patch Similarity (LPIPS) [50].

Our method outperforms the diffusion model baselines [38, 29, 23] by a large margin. Moreover, our method is also competitive with, or even better than the best-in-class fully supervised methods, as can be seen in Table 1. In Fig. 3, we depict representative results that show the superiority of the method, where we see in both the box-type and random dropping that MCG performs very well on all experiments.

Colorization We choose score-SDE [38], and DDRM [23] as diffusion-model based comparison methods, and also compare against cINN [2], and pix2pix [19]. Two metrics were used for evaluation: structural similarity index (SSIM), and LPIPS. Consistent with the findings from inpainting, we achieve much improved performance than score-SDE, and also is favorable against state-of-the-art (SOTA) superivsed learning based methods. In Table 2, we see that the

Data Method	FFHQ(256×256) SSIM ↑	LPIPS ↓	LSUN(256×256) SSIM ↓	LPIPS ↓
MCG (ours)	0.951	**0.146**	**0.959**	**0.160**
Score-SDE [38]	0.936	0.180	0.945	0.199
DDRM [23]	0.948	0.154	0.957	0.182
cINN [2]	**0.952**	0.166	0.952	0.180
pix2pix [19]	0.935	0.184	0.947	0.174

Table 2: Quantitative evaluation (SSIM, LPIPS) of colorization task. **Bold**: best, under: second best.

[2]The location of the box is sampled uniformly within 16 pixel margin of each side.

	LPIPS(↓)	MSE(MC)
Proj.	0.138	0
MCG	0.124	10.7
Both	0.089	0

(a) LPIPS & Measurement consistency (MC) vs. method	(b) LPIPS vs. NFE	(c) LPIPS vs. α

Figure 5: Ablation studies performed with box inpainting task on FFHQ 256×256 data.

proposed method outperforms all other methods in terms of both PSNR/LPIPS in LSUN-bedroom, and also achieves strong performance in the colorization of FFHQ dataset.

CT reconstruction To the best of our knowledge, [37] is the only method that tackles CT reconstruction directly with diffusion models. We compare our method against [37], which we refer to as score-CT henceforth. We also compare with the best-in-class supervised learning methods, cGAN [13] and SIN-4c-PRN [46]. As a compressed sensing baseline, FISTA-TV [3] was included, along with the analytical reconstruction method, FBP. We use two standard metrics - peak-signal-to-noise-ratio (PSNR), and SSIM for quantitative evaluation. From Table 3, we see that the newly proposed MCG method

	AAPM (256 × 256)			
Views	**18**		**30**	
Method	PSNR ↑	SSIM ↑	PSNR ↑	SSIM ↑
MCG (ours)	**33.57**	**0.956**	**36.09**	**0.971**
Score-POCS (ours)	30.77	0.907	32.68	0.923
Score-CT [37]	29.85	0.897	31.97	0.913
SIN-4c-PRN [46]	26.96	0.850	30.23	0.917
cGAN [13]	24.38	0.823	27.45	0.927
FISTA-TV [3]	21.57	0.791	23.92	0.861

Table 3: Quantitative evaluation (PSNR, SSIM) of CT reconstruction task. **Bold**: best.

outperforms the previous score-CT [37] by a large margin. We can observe the superiority of MCG over other methods more clearly in Fig. 4, where MCG reconstructs the measurement with high fidelity and detail. All other methods including the fully supervised baselines fall behind the proposed method.

Ablation studies We perform three ablation studies: 1) As both the MCG term and the projection term contain information about the measurement y, we observe the contribution of each term to the fixed solution. 2) As the performance of diffusion models depend heavily on the number of NFEs, we observe the trade-off of each diffusion model when varying the NFE from 20 to 1000. 3) Setting $\alpha = 0.0$ reduces our method to [8]. We show the difference in the performance by varying the values of α.

First, we see in Fig. 5a that using only the MCG step leads to improved performance in terms of LPIPS, but introduces error in the measurement consistency (measured with MSE). Combining both the projection and MCG leads to perfect data consistency along with further improved reconstruction.

Second, looking at Fig. 5b, we immediately see that the graph of MCG stays in the lowest (best) LPIPS regime across all NFEs by a large margin, except for when the NFE drops below 100. Here, DDRM [23] takes over the 1st place - allegedly due to the DDIM sampling strategy they take. The performance of RePAINT deteriorates rapidly as we decrease NFE. Furthermore, observe that the LPIPS of score-SDE [38] actually *increases* (i.e. worsen), as we increase the number of NFEs from a few hundred to one thousand. This suggests that the inference process that score-SDE takes (i.e. projection only) is inherently flawed, and cannot be corrected by taking small enough steps.

Lastly, seeing Fig. 5c, we see that α values within the range $[0.1, 1.0]$ produce satisfactory results. α values that are too low do not fully enjoy the advantages of MCG and collapses to the projection-only method, while using too high values of α results in exploding gradients, and the reconstruction saturates.

Properties of Our Method Our proposed method is fully unsupervised and is not trained on solving a specific inverse problem. For example, our box masks and random masks have very different forms of erasing the pixel values. Nevertheless, our method generalizes perfectly well to such different measurement conditions, while other methods have a large performance gap between the different mask shapes. We further note two appealing properties of our method as an inverse problem solver: 1) the ability to generate multiple solutions given a condition, and 2) the ability to maintain perfect measurement consistency. The former ability often lacks in supervised learning-based methods [40, 46], and the latter is often not satisfied for some unsupervised GAN-based solutions [9, 4].

6 Conclusion

In this work, we proposed a general framework that can greatly enhance the performance of the diffusion model-based solvers for solving inverse problems. We showed several promising applications - inpainting, colorization, sparse view CT reconstruction, and showed that our method can outperform the current state-of-the-art methods. We analyzed our method theoretically and show that MCG prevents the data generation process from falling off the manifold, thereby reducing the errors that might accumulate at every step. Further, we showed that MCG controls the direction tangent to the data manifold, whereas the score function controls the direction that is normal, such that the two components complement each other.

Limitations and Broader Impact The proposed method is inherently stochastic since the diffusion model is the main workhorse of the algorithm. When the dimension m is pushed to low values, at times, our method fails to produce high quality reconstructions, albeit being better than the other methods overall. For extreme cases of inpainting (e.g. Half masks) with the ImageNet model, we often observe artifacts in our reconstruction (e.g. generating perfectly symmetric images), which we discuss in further detail in Sec. E.We note that our method is slow to sample from, inheriting the existing limitations of diffusion models. This would likely benefit from leveraging recent solvers aimed at accelerating the inference speed of diffusion models. In line with the arguments of other generative model-based inverse problem solvers, our method is a solver that relies heavily on the underlying diffusion model, and can thus potentially create malicious content such as deepfakes. Further, the reconstructions could intensify the social bias that is already existent in the training dataset.

References

[1] Brian DO Anderson. Reverse-time diffusion equation models. *Stochastic Processes and their Applications*, 12(3):313–326, 1982.

[2] Lynton Ardizzone, Carsten Lüth, Jakob Kruse, Carsten Rother, and Ullrich Köthe. Guided image generation with conditional invertible neural networks. *arXiv preprint arXiv:1907.02392*, 2019.

[3] Amir Beck and Marc Teboulle. A fast iterative shrinkage-thresholding algorithm for linear inverse problems. *SIAM journal on imaging sciences*, 2(1):183–202, 2009.

[4] Ashish Bora, Ajil Jalal, Eric Price, and Alexandros G Dimakis. Compressed sensing using generative models. In *International Conference on Machine Learning*, pages 537–546. PMLR, 2017.

[5] Stephen Boyd, Neal Parikh, Eric Chu, Borja Peleato, Jonathan Eckstein, et al. Distributed optimization and statistical learning via the alternating direction method of multipliers. *Foundations and Trends® in Machine learning*, 3(1):1–122, 2011.

[6] Thorsten M Buzug. Computed tomography. In *Springer handbook of medical technology*, pages 311–342. Springer, 2011.

[7] Jooyoung Choi, Sungwon Kim, Yonghyun Jeong, Youngjune Gwon, and Sungroh Yoon. ILVR: Conditioning method for denoising diffusion probabilistic models. In *Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV)*, 2021.

[8] Hyungjin Chung, Byeongsu Sim, and Jong Chul Ye. Come-Closer-Diffuse-Faster: Accelerating Conditional Diffusion Models for Inverse Problems through Stochastic Contraction. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 2022.

[9] Giannis Daras, Joseph Dean, Ajil Jalal, and Alexandros G Dimakis. Intermediate layer optimization for inverse problems using deep generative models. In *International Conference on Machine Learning*, 2021.

[10] Jia Deng, Wei Dong, Richard Socher, Li-Jia Li, Kai Li, and Li Fei-Fei. Imagenet: A large-scale hierarchical image database. In *2009 IEEE conference on computer vision and pattern recognition*, pages 248–255. Ieee, 2009.

[11] Prafulla Dhariwal and Alexander Quinn Nichol. Diffusion models beat GANs on image synthesis. In A. Beygelzimer, Y. Dauphin, P. Liang, and J. Wortman Vaughan, editors, *Advances in Neural Information Processing Systems*, 2021.

[12] Bradley Efron. Tweedie's formula and selection bias. *Journal of the American Statistical Association*, 106(496):1602–1614, 2011.

[13] Muhammad Usman Ghani and W Clem Karl. Deep learning-based sinogram completion for low-dose ct. In *2018 IEEE 13th Image, Video, and Multidimensional Signal Processing Workshop (IVMSP)*, pages 1–5. IEEE, 2018.

[14] Richard Gordon, Robert Bender, and Gabor T Herman. Algebraic reconstruction techniques (art) for three-dimensional electron microscopy and x-ray photography. *Journal of theoretical Biology*, 29(3):471–481, 1970.

[15] Martin Heusel, Hubert Ramsauer, Thomas Unterthiner, Bernhard Nessler, and Sepp Hochreiter. Gans trained by a two time-scale update rule converge to a local nash equilibrium. In I. Guyon, U. Von Luxburg, S. Bengio, H. Wallach, R. Fergus, S. Vishwanathan, and R. Garnett, editors, *Advances in Neural Information Processing Systems*, volume 30. Curran Associates, Inc., 2017.

[16] Jonathan Ho, Ajay Jain, and Pieter Abbeel. Denoising diffusion probabilistic models. In *Advances in Neural Information Processing Systems*, volume 33, pages 6840–6851, 2020.

[17] Jonathan Ho, Tim Salimans, Alexey Gritsenko, William Chan, Mohammad Norouzi, and David J Fleet. Video diffusion models. *arXiv preprint arXiv:2204.03458*, 2022.

[18] Shady Abu Hussein, Tom Tirer, and Raja Giryes. Image-adaptive gan based reconstruction. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 34, pages 3121–3129, 2020.

[19] Phillip Isola, Jun-Yan Zhu, Tinghui Zhou, and Alexei A Efros. Image-to-image translation with conditional adversarial networks. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 1125–1134, 2017.

[20] Zahra Kadkhodaie and Eero Simoncelli. Stochastic solutions for linear inverse problems using the prior implicit in a denoiser. In *Advances in Neural Information Processing Systems*, volume 34, pages 13242–13254. Curran Associates, Inc., 2021.

[21] Eunhee Kang, Junhong Min, and Jong Chul Ye. A deep convolutional neural network using directional wavelets for low-dose x-ray ct reconstruction. *Medical physics*, 44(10):e360–e375, 2017.

[22] Tero Karras, Samuli Laine, and Timo Aila. A style-based generator architecture for generative adversarial networks. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 4401–4410, 2019.

[23] Bahjat Kawar, Michael Elad, Stefano Ermon, and Jiaming Song. Denoising diffusion restoration models. In *ICLR Workshop on Deep Generative Models for Highly Structured Data*, 2022.

[24] Bahjat Kawar, Gregory Vaksman, and Michael Elad. Snips: Solving noisy inverse problems stochastically. *Advances in Neural Information Processing Systems*, 34:21757–21769, 2021.

[25] Daniil Kazantsev, Edoardo Pasca, Martin J Turner, and Philip J Withers. Ccpi-regularisation toolkit for computed tomographic image reconstruction with proximal splitting algorithms. *SoftwareX*, 9:317–323, 2019.

[26] Kwanyoung Kim and Jong Chul Ye. Noise2score: Tweedie's approach to self-supervised image denoising without clean images. In A. Beygelzimer, Y. Dauphin, P. Liang, and J. Wortman Vaughan, editors, *Advances in Neural Information Processing Systems*, 2021.

[27] Diederik P. Kingma and Max Welling. Auto-encoding variational bayes. In *2nd International Conference on Learning Representations, ICLR*, 2014.

[28] Beatrice Laurent and Pascal Massart. Adaptive estimation of a quadratic functional by model selection. *Annals of Statistics*, pages 1302–1338, 2000.

[29] Andreas Lugmayr, Martin Danelljan, Andres Romero, Fisher Yu, Radu Timofte, and Luc Van Gool. RePaint: Inpainting using Denoising Diffusion Probabilistic Models. *arXiv preprint arXiv:2201.09865*, 2022.

[30] Xudong Mao, Qing Li, Haoran Xie, Raymond YK Lau, Zhen Wang, and Stephen Paul Smolley. Least squares generative adversarial networks. In *Proceedings of the IEEE international conference on computer vision*, pages 2794–2802, 2017.

[31] Frank Ong, Peyman Milanfar, and Pascal Getreuer. Local kernels that approximate bayesian regularization and proximal operators. *IEEE Transactions on Image Processing*, 28(6):3007–3019, 2019.

[32] Jialun Peng, Dong Liu, Songcen Xu, and Houqiang Li. Generating diverse structure for image inpainting with hierarchical VQ-VAE. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 10775–10784, 2021.

[33] Ali Razavi, Aaron Van den Oord, and Oriol Vinyals. Generating diverse high-fidelity images with vq-vae-2. *Advances in neural information processing systems*, 32, 2019.

[34] Herbert E Robbins. An empirical bayes approach to statistics. In *Breakthroughs in statistics*, pages 388–394. Springer, 1992.

[35] Simo Särkkä and Arno Solin. *Applied stochastic differential equations*, volume 10. Cambridge University Press, 2019.

[36] Karen Simonyan and Andrew Zisserman. Very deep convolutional networks for large-scale image recognition. In *3rd International Conference on Learning Representations, ICLR*, 2015.

[37] Yang Song, Liyue Shen, Lei Xing, and Stefano Ermon. Solving inverse problems in medical imaging with score-based generative models. In *International Conference on Learning Representations*, 2022.

[38] Yang Song, Jascha Sohl-Dickstein, Diederik P. Kingma, Abhishek Kumar, Stefano Ermon, and Ben Poole. Score-based generative modeling through stochastic differential equations. In *9th International Conference on Learning Representations, ICLR*, 2021.

[39] Charles M Stein. Estimation of the mean of a multivariate normal distribution. *The annals of Statistics*, pages 1135–1151, 1981.

[40] Roman Suvorov, Elizaveta Logacheva, Anton Mashikhin, Anastasia Remizova, Arsenii Ashukha, Aleksei Silvestrov, Naejin Kong, Harshith Goka, Kiwoong Park, and Victor Lempitsky. Resolution-robust large mask inpainting with fourier convolutions. In *Proceedings of the IEEE/CVF Winter Conference on Applications of Computer Vision*, pages 2149–2159, 2022.

[41] Tom Tirer and Raja Giryes. Image restoration by iterative denoising and backward projections. *IEEE Transactions on Image Processing*, 28(3):1220–1234, 2018.

[42] Github PK Tool, Nov Sun Mon Tue Wed Thu, and Fri Sat. dkazanc/tomobar.

[43] Aaron Van Den Oord, Oriol Vinyals, et al. Neural discrete representation learning. *Advances in neural information processing systems*, 30, 2017.

[44] Singanallur V Venkatakrishnan, Charles A Bouman, and Brendt Wohlberg. Plug-and-play priors for model based reconstruction. In *2013 IEEE Global Conference on Signal and Information Processing*, pages 945–948. IEEE, 2013.

[45] Ziyu Wan, Jingbo Zhang, Dongdong Chen, and Jing Liao. High-fidelity pluralistic image completion with transformers. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 4692–4701, 2021.

[46] Haoyu Wei, Florian Schiffers, Tobias Würfl, Daming Shen, Daniel Kim, Aggelos K Katsaggelos, and Oliver Cossairt. 2-step sparse-view ct reconstruction with a domain-specific perceptual network. *arXiv preprint arXiv:2012.04743*, 2020.

[47] Fisher Yu, Ari Seff, Yinda Zhang, Shuran Song, Thomas Funkhouser, and Jianxiong Xiao. Lsun: Construction of a large-scale image dataset using deep learning with humans in the loop. *arXiv preprint arXiv:1506.03365*, 2015.

[48] Yanhong Zeng, Jianlong Fu, Hongyang Chao, and Baining Guo. Aggregated contextual transformations for high-resolution image inpainting. *IEEE Transactions on Visualization and Computer Graphics*, 2022.

[49] Kai Zhang, Wangmeng Zuo, Shuhang Gu, and Lei Zhang. Learning deep cnn denoiser prior for image restoration. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 3929–3938, 2017.

[50] Richard Zhang, Phillip Isola, Alexei A Efros, Eli Shechtman, and Oliver Wang. The unreasonable effectiveness of deep features as a perceptual metric. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 586–595, 2018.

[51] Jun-Yan Zhu, Taesung Park, Phillip Isola, and Alexei A Efros. Unpaired image-to-image translation using cycle-consistent adversarial networks. In *Proceedings of the IEEE international conference on computer vision*, pages 2223–2232, 2017.