Transformers as Communication Systems: Controlling Information Flow with Bottlenecks

Kieran Murphy [1]

Abstract

We make the information communicated by attention between residual streams in vision transformers a measurable and controllable quantity. By inserting variational information bottlenecks on all attention-mediated writes to the residual stream—without other architectural changes—we train models with an explicit information cost and obtain a spectrum that interpolates between independent patch processing and fully expressive global attention. On ImageNet-100, we characterize how classification and self-supervised representation learning change across this spectrum, revealing how information flow is allocated across depth, heads, and patches as global visual representations emerge from local processing. We further inspect the first attention heads that transmit information, identifying simple visual computations that appear under tight communication constraints. By biasing learning toward solutions with constrained internal communication, our approach yields models that are more tractable for mechanistic analysis and more amenable to control.

1. Introduction

Transformers have emerged as a dominant architectural paradigm across machine learning, distinguished by their ability to aggregate information globally across the constitutive elements of an input (Vaswani et al., 2017). In vision transformers (Dosovitskiy et al., 2021), an image is decomposed into patches, and computation proceeds through repeated alternation between two modules: attention blocks, which enable information sharing across patches, and multilayer perceptron (MLP) blocks, which refine patch representations independently. Because communication and local refinement occur in distinct computational steps, information flow becomes an explicit and manipulable axis of the architecture, rather than being entangled with processing as in prior paradigms. This naturally raises a mechanistic question: when communication is restricted, what circuits of attention-mediated interaction emerge first (Olah et al., 2020; Elhage et al., 2021), and what do they reveal about how transformers build global understanding from local evidence?

Modern interpretability methods typically analyze models trained without explicit pressure toward simplicity (Rudin, 2019; Samek et al., 2021) or prescribed explanatory structure (e.g., prototype-based or concept-bottleneck constraints) (Chen et al., 2019; Koh et al., 2020), revealing internal mechanisms that are often rich but difficult to disentangle or control. A complementary approach is to bias learning toward solutions with constrained information flow (Alemi et al., 2017). However, properly reasoning about the movement of information requires going beyond the deterministic, point-valued transformations that dominate standard architectures, which make it difficult to assign meaning to "information" in an operational sense (Saxe et al., 2019). One must instead introduce stochastic or probabilistic representations that allow information to be measured and restricted.

Such information-theoretic modifications to bottleneck the flow of information can be applied either post-hoc or during training. Post-hoc bottleneck methods (Schulz et al., 2020; Jiang et al., 2020; Hong et al., 2025) enable the study of pretrained models, but necessarily probe them under perturbations that differ from the conditions under which they were optimized, raising concerns about faithfulness. In contrast, training-time information restriction directly shapes the solutions that optimization discovers (Alemi et al., 2017; Achille & Soatto, 2018), yielding models whose internal computations are intrinsically biased toward limited communication. In this work, we pursue this second approach, using vision transformers as a natural setting in which to study restricted information routing in a clean and controlled way.

Our goal is a minimal modification to the transformer ar-

[1] Department of Computer Science, New Jersey Institute of Technology, Newark, NJ, USA 97102. Correspondence to: <kieran.murphy@njit.edu>.

Mechanistic Interpretability Workshop at the 43^{rd} International Conference on Machine Learning, Seoul, South Korea, 2026. Copyright 2026 by the author(s).

Figure 1. **Limiting information written by attention to the residual stream.** **(a)** We insert a variational information bottleneck after every attention head, just before its message is written to the patch residual stream. The resulting KL penalty upper bounds the information written by attention; scaling the summed penalty by β yields models ranging from independent patch processing to standard ViT attention. **(b)** For a ViT-tiny trained on ImageNet-100, this produces a continuous spectrum trading accuracy for information, where information is reported as total KL per patch. Models smoothly interpolate between a no-attention ViT and an unmodified ViT; stochastic IB error bars show standard deviation across 10 validation runs. **(c)** With global average pooling as the final readout, each patch contributes uniformly to the final prediction, allowing patch logits to be interpreted as votes. Patch voting behavior changes continuously along the information spectrum: with less attention-written information, patches show larger logit ranges and more diverse top-class votes, measured by the inverse Simpson effective count of voted classes. Each dot is one image, colored by β as in **b**; medians and interquartile ranges summarize overlapping point clouds.

chitecture that allows attention-mediated communication to be smoothly controlled, producing a spectrum of models that interpolates between fully expressive transformer computation and attention-less independent patch processing. We achieve this by inserting variational information bottlenecks (Alemi et al., 2017) on the writes to the residual stream performed by attention blocks, without otherwise altering the attention mechanism or transformer structure. This yields a family of models in which communication capacity becomes a tunable parameter.

At the zero-communication limit, the architecture reduces to independent per-patch processing followed by permutation-invariant aggregation, closely related to the DeepSets formulation (Zaheer et al., 2017). This provides a well-defined and interpretable endpoint. As communication capacity increases, global visual representations emerge progressively from local patch computations. By analyzing performance, patch-level information updates, and the first attention heads that become active, we obtain a mechanistic picture of how transformers begin to integrate information across space under constrained bandwidth.

Contributions. Concretely, we: (i) introduce a controllable family of vision transformers with variational bottlenecks on every attention-mediated write to the residual stream; (ii) characterize how task performance trades off with routed information across a continuous spectrum from independent patch processing to standard global attention,

showing consistent structure on ImageNet-100 under both supervised training and DINO self-supervision (Caron et al., 2021); and (iii) analyze the first attention heads that transmit nontrivial information, illustrating how global computation emerges from restricted local processing. Overall, our results establish information restriction as a practical tool for making transformer communication measurable, tunable, and more amenable to mechanistic analysis.

2. Related work

Mechanistic interpretability and transformer circuits. This work aligns with mechanistic interpretability: understanding and ultimately controlling the internal computations of trained models. Prior work has traced attention-mediated information flow through transformer circuits (Olah et al., 2020; Elhage et al., 2021), decomposed representations into interpretable features using sparse dictionary learning and related tools (Bricken et al., 2023; Huben et al., 2024), and developed mechanistic accounts in simplified settings such as small transformers or narrowly defined tasks (Akyürek et al., 2023; Nanda et al., 2023; Wang et al., 2023; Dutta et al., 2024). Extending these ideas to vision transformers remains challenging because image patches are continuous, attention is dense rather than causally masked, and semantic units are less discrete than language tokens. Recent work has therefore studied ViT representations across depth, training objectives, and architectures (Raghu et al., 2021; Caron et al.,

2021; Park et al., 2023; Dorszewski et al., 2026), including feature-decomposition approaches applied to ViT activations (Stevens et al., 2025). Our work contributes a complementary simplification: rather than restricting model size, task complexity, or analyzing a fixed pretrained model, we restrict internal communication capacity during training, yielding a tunable spectrum of transformer computations.

Information bottleneck methods for interpretability. Our method builds on the information bottleneck principle (Tishby et al., 2000; Alemi et al., 2017), which formalizes a tradeoff between predictive sufficiency and compression. Beyond its use as a regularizer or robustness tool (Hu et al., 2024), the information bottleneck has also been used to identify which information is important to a model's computation. Post-hoc bottleneck methods, such as Information Bottleneck Attribution and its extensions (Schulz et al., 2020; Jiang et al., 2020; Hong et al., 2025), probe pretrained models by restricting information after training. Training-time bottleneck methods instead shape the solutions learned by optimization; for example, distributed information bottleneck approaches quantify feature importance by restricting communication about input dimensions (Murphy & Bassett, 2023; 2024). We extend this training-time perspective from input features to transformer internals by placing variational bottlenecks on attention-mediated residual writes.

Communication restriction and structured simplification in transformers. Several lines of work simplify transformer computation by pruning or restricting attention heads, sparsifying attention, or removing tokens (Michel et al., 2019; Voita et al., 2019; Pan et al., 2021; Rao et al., 2021; Liang et al., 2022). These methods primarily target efficiency. Our goal is interpretability: by making attention-mediated communication costly during training, we obtain a spectrum from independent patch processing to fully expressive attention and can analyze which heads and messages emerge first as capacity increases. **TODO:** Related is (Gao et al., 2025) – they explicitly target interpretability via weight-sparse transformers, though a followup on lesswrong makes a great point, that you can find masked sub-networks that do tasks inside randomly initialized (untrained) networks.

3. Method

We begin with a brief review of the vision transformer architecture, then introduce our training-time information restriction mechanism, and finally describe how we characterize the resulting spectrum of information routing behaviors.

3.1. Vision transformers as residual stream communication

We adopt the residual stream framing of transformer computation developed in Elhage et al. (2021). A vision transformer (ViT) processes an image as a sequence of patch embeddings, $\mathcal{S} = \{x_i\}_{i=1}^N$, where each patch maintains its own residual stream representation throughout the network. Each transformer block alternates between two update mechanisms: (i) an attention block, which computes context-dependent interactions across patches, and (ii) an MLP block, which refines each patch representation independently.

Crucially, only attention enables information exchange between sequence elements (Fig. 1a). MLP blocks operate pointwise on each residual stream and introduce no new cross-patch information. Thus, attention-mediated writes to the residual stream constitute the natural pathway through which global visual representations emerge from local patch features. Our approach directly monitors and restricts this communication channel.

3.2. Bottlenecking attention-mediated residual writes

Within an attention block, there are several possible points at which information flow could be restricted. We intervene at the final attention update, immediately before it is written back into the residual stream. This leaves the attention computation itself intact while limiting the information transmitted through the resulting update. To resolve communication at the level of individual heads, we instantiate a separate variational bottleneck on every attention head in every layer, yielding 36 independently regularized channels in ViT-Tiny.

Let $\Delta_i^{\ell,h} \in \mathbb{R}^{d_h}$ denote the attention update for patch i from head h in layer ℓ, before the output projection. In a standard transformer block, these head updates are concatenated, projected, and added deterministically to the residual stream. We instead route each head update through a head-specific variational bottleneck:

$$\Delta_i^{\ell,h} \to z_i^{\ell,h} \sim q_{\phi_{\ell,h}}(z \mid \Delta_i^{\ell,h}) \to \hat{\Delta}_i^{\ell,h} = g_{\theta_{\ell,h}}(z_i^{\ell,h}), \tag{1}$$

where each layer-head pair has its own encoder $q_{\phi_{\ell,h}}$ and decoder $g_{\theta_{\ell,h}}$. The decoded head updates are then concatenated, projected, and written to the residual stream as usual. Because attention-mediated residual writes are the mechanism by which patches exchange information, this intervention isolates inter-patch communication while otherwise preserving the ViT computation.

3.3. Training objective and information restriction

The communication bottlenecks are implemented using the variational information bottleneck (VIB) principle (Tishby

Figure 2. **Communication allocation across layers and across patches. (a)** Total transmitted information $I(\Delta; Z)$, summed over heads in each layer and averaged across three seeds, shifts from late to early layers as β decreases. **(b)** For a random sample of validation images correctly classified by the unmodified ViT, we visualize total KL per patch, summed over all attention heads, for selected models near the Pareto front in Fig. 1b. Panel **a** quantifies layerwise information transmission, while panel **b** shows the spatial distribution of the corresponding KL-based communication cost within individual images. Colormaps are normalized separately for each model (row).

et al., 2000; Alemi et al., 2017). Each layer-head bottleneck uses a diagonal Gaussian encoder,

$$q_{\phi_{\ell,h}}(z \mid \Delta) = \mathcal{N}\big(\mu_{\phi_{\ell,h}}(\Delta), \mathrm{diag}(\sigma^2_{\phi_{\ell,h}}(\Delta))\big), \quad (2)$$

and is regularized toward an isotropic unit Gaussian prior on its latent space, denoted $p(z) = \mathcal{N}(0, I)$. The resulting KL divergence upper bounds the mutual information between Δ and z, yielding a tractable proxy for transmitted information.

For a general task loss $\mathcal{L}_{\text{task}}$, we optimize

$$\mathcal{L} = \mathcal{L}_{\text{task}} + \beta \sum_{\ell,h,i} D_{\mathrm{KL}}\big(q_{\phi_{\ell,h}}(z_i^{\ell,h} \mid \Delta_i^{\ell,h}) \,\|\, p(z_i^{\ell,h})\big),$$

$$(3)$$

where $\mathcal{L}_{\text{task}}$ can be any differentiable objective; in this work, we use cross-entropy for supervised classification and the DINO loss for self-supervised training (Caron et al., 2021). The coefficient β sets the cost of transmitting attention-mediated information, thereby tuning the capacity of each head-level communication channel.

This is not a single-bottleneck compression objective in the classical IB sense. Rather, it defines a distributed information budget over the attention-mediated messages that carry information between patches. Each bottleneck penalizes the information retained in a local write, while the task loss selects messages that remain useful to downstream computation. The summed KL penalty is therefore a decomposable communication cost, allowing information flow to be measured by head and by patch.

Comparing probabilistic head updates via normalized mutual information. To compare probabilistic head updates across seeds and β values, we use the probabilistic representation-space normalized mutual information (NMI) estimator of Murphy et al. (2025), treating each head's bottleneck posterior as a soft clustering over patch instances. Details are in Appx. C.

3.4. Implementation details

All experiments use the ViT-Tiny backbone from `timm` (12 blocks, embedding dimension 192, 3 attention heads per block). We adopt this lightweight backbone to enable extensive sweeps over information budgets and detailed mechanistic analysis, while preserving the canonical transformer computation pattern. We insert variational information bottlenecks on the attention-mediated residual writes in every block, instantiating a separate encoder–decoder bottleneck for each head in each layer (36 bottlenecks total). All bottlenecks share the same architecture and latent dimensionality, differing only in their learned parameters. For ViT-tiny, the unmodified architecture contains approximately 5.5M parameters, while the bottlenecked variant contains approximately 7.6M parameters, corresponding to a roughly 40% parameter overhead from the bottleneck modules.

For supervised classification, we use global average pooling over patch representations followed by a linear classifier head (Zhai et al., 2022), ensuring that the zero-communication limit remains well-defined. We train on

ImageNet-100, a 100-class subset of ImageNet (Deng et al., 2009) introduced by Tian et al. (2020), using AdamW with learning rate 6×10^{-4} and weight decay 0.05 for 1000 epochs. Training uses a cosine learning-rate schedule with 10 epochs of warmup, and the information penalty coefficient β is fixed over the course of training. We apply RandAugment for standard appearance-level augmentation, but omit patch-mixing strategies such as Mixup and Cut-Mix since these distort patch-level statistics and complicate interpretation.

For self-supervised experiments, we train the same bottlenecked ViT-Tiny models with the DINO objective (Caron et al., 2021) on the same ImageNet-100 subset. To preserve the communication-limited readout, we remove the CLS token and replace DINO's projection head with global average pooling followed by a single linear projection to a 256-dimensional representation before the prototype layer. We use 2^{16} prototypes and train for 800 epochs with batch size 256, learning rate 5×10^{-4}, teacher-temperature warmup over 30 epochs, and weight decay ramped from 0.04 to 0.4. Additional optimization and augmentation details are provided in Appendix B.

4. Results

We present results in two stages. Our primary analysis uses supervised ImageNet-100 models, where the classification objective and GAP readout allow us to study the full information-accuracy spectrum, patch voting behavior, and the individual attention heads that first transmit nontrivial messages. We then ask whether the same communication-restriction framework extends beyond supervised classification by applying it to DINO self-supervised training. Together, these experiments test both the mechanistic value of the low-information regime and the broader applicability of attention-written information as a tunable constraint.

Within the supervised models, we analyze the system at two complementary scales. First, we characterize the continuum induced by the information cost β, demonstrating systematic changes in attention-mediated communication, predictive performance, and patch voting behavior. Second, we exploit the sparsity of the low-information regime to perform fine-grained mechanistic analyses of individual attention heads.

4.1. Properties of the spectrum of models

The entire spectrum from independent patch processing (attention blocks are removed from the ViT) to freely flowing information as in an unmodified ViT, spans $69.2\% \pm 0.3$ to $78.2\% \pm 0.3$ top-1 validation accuracy (mean and standard deviation over three random seeds) (Fig. 1b). That the attention-less baseline remains competitive underscores that substantial visual recognition can be achieved from simple

pooling of local patch evidence alone, consistent with the strong performance of local-feature-based image representations prior to deep networks (Lowe, 2004; Sánchez et al., 2013).

Intuitively, as information communicated by attention increases, so too does classification performance. With only around one nat of KL for every ten patches, accuracy increases by $1 - 2\%$. When around one nat of KL is communicated per patch, it further increases by $\sim 2\%$. Empirically, accuracy increases approximately linearly with $\log$ KL over much of the spectrum. The least restricted models ($\beta = 0$) approach, though do not fully reach, the accuracy of an unmodified ViT (within $\sim 1\%$ top-1), suggesting a small residual effect of the IB parameterization even in the weakly constrained regime.

Without attention to pass information between patches, there can clearly be no consensus between patch representations. How does patch independence give way to consensus as attention becomes less restricted? We show in Fig. 1c characteristics of patch voting behaviors for several models close to the Pareto front. These patch-level measures provide a complementary view of global integration: rather than only tracking top-1 accuracy, they quantify how communication induces consensus among local predictions. The spectrum therefore captures not just performance gains, but a qualitative transition from diverse independent patch hypotheses to coordinated global representations.

We summarize patch consensus using two quantities: the inverse Simpson effective count of top-class votes across patches (Simpson, 1949; Hill, 1973), $1/\sum_c p_c^2$, and the range of patch logit contributions. Independent patch processing yields many distinct patch-level class votes (effective counts often exceeding 50 different classes per image) and large logit ranges (total logit range $\gtrsim 100$), while increasing communication progressively drives consensus. Importantly, we are able to smoothly and controllably interpolate between these extremes by tuning the information cost coefficient β.

We visualize aspects of the processing of a handful of images by different models in Fig. 2 and in Appx. D. For the IB models, we display a heatmap of the information penalty (in terms of KL divergence) summed across all attention heads for each patch in the image. Because each bottleneck yields a per-patch KL cost, we obtain a direct, quantitative map of where attention allocates its limited communication budget. For large β, update KL tends to be insignificant for most of the image and then concentrated on patches in the foreground. As β decreases and communication is more plentiful, significant KL is spent on all patches. In Appx. D, we show samples of images randomly selected based on other criteria (e.g., large difference between classification assignments by the two ViT baselines) and additionally vi-

Figure 3. **Head update behavior.** For the single active attention head in the $\beta = 10$ model (head 11.0), and for one of the four active heads of the $\beta = 4$ model (head 10.0), we randomly sample positive and negative activations from patches in the top 0.1% of KL cost. The patch is indicated by a red square in both the original image (top of each pair of rows) and the head's attention map (bottom of each pair of rows).

sualize examples of patch voting behavior.

4.2. Update behavior of individual attention heads

The low-information regime provides a natural entry point for mechanistic analysis because the KL penalty causes most headwise channels to collapse to the prior. At $\beta = 10$, only a single head transmits nontrivial information; at $\beta = 4$, four heads do so. Thus, instead of analyzing dense attention across all layers and heads, we can inspect the first communication channels that optimization finds worth paying for.

Active heads in this regime often use only one or two latent dimensions, making their messages directly visualizable. When a head is effectively one-dimensional, its update reduces to a signed scalar message, allowing patches to be grouped by whether the head transmits a positive or negative signal. In Fig. 3, we show high-update patches and corresponding attention maps for the single active head in the $\beta = 10$ model, as well as a representative active head from the $\beta = 4$ model. The earliest active head appears to encode a coarse contextual statistic: whether the current patch is part of a repeated or redundant pattern elsewhere in the image. Across three random seeds, each $\beta = 10$ model contains an active head with qualitatively similar repetition-sensitive behavior (Appendix E).

We test this hypothesis with a controlled copy-paste augmentation (Fig. 4a). For each of 1024 randomly sampled images, we select a patch and paste copies of it at random locations elsewhere in the same image, increasing within-image redundancy while preserving the local content of the

queried patch. For the repetition-sensitive heads, the latent message shifts systematically as the number of copies increases from 4 to 16 to 64. This effect is pronounced for $\beta = 10$ head 11.0 and $\beta = 4$ head 11.0, but absent for $\beta = 4$ head 10.0, supporting the interpretation that these heads transmit information about repeated visual structure rather than merely responding to local patch content.

To assess whether this message is reproducible across seeds and persists as the communication budget increases, we compare head update distributions using normalized mutual information for probabilistic representation spaces (Murphy et al., 2025). We treat each head's bottleneck posterior as a soft clustering of patch instances conditioned on image context, allowing comparison across heads even when their latent dimensionalities differ. As shown in Fig. 4b, the active heads of the three $\beta = 10$ models have high mutual agreement, indicating that the same repetition-sensitive message emerges reliably across seeds. Related information also appears in less constrained models, most clearly in $\beta = 4$ head 11.0 and $\beta = 1$ head 6.0. Moreover, the NMI comparisons mirror the copy-paste perturbation results: heads that respond similarly to repeated patches have high NMI, while visually distinct heads, such as $\beta = 4$ head 10.0, have low NMI.

These results suggest that the first attention-mediated messages to emerge under strong information pressure encode simple, high-value global context. Coarse redundancy signals are cheap to communicate, recur across seeds, and remain partially identifiable as the communication budget increases, providing a concrete example of how restricted transformers can expose early-forming attention circuits.

Figure 4. **Controlled perturbations and cross-model similarity reveal repeated-pattern messaging. (a)** We test whether selected heads encode within-image redundancy by copy-pasting a queried patch to N random locations before passing the augmented image through the model. For 1024 randomly selected patches, we compare the bottleneck posterior mean for the original image, μ_0, with the signed displacement induced by augmentation, $\mu_{\text{aug}} - \mu_0$. Repetition-sensitive heads show systematic displacement as the number of copies increases, while other active heads do not. **(b)** Pairwise similarity between active attention-head messaging channels, measured by NMI between probabilistic representation spaces. For $\beta = 10$ head 11.0 (*top*), we compare against the active heads from two other $\beta = 10$ seeds, the four active heads at $\beta = 4$, and the 14 active heads at $\beta = 1$. We also compare each active $\beta = 4$ head against all active $\beta = 1$ heads (*bottom*). Error bars show propagated uncertainty from Monte Carlo estimates of mutual information using 2×10^7 samples.

4.3. Communication-restricted self-supervised learning

Finally, we test whether attention-written information can be restricted in a training objective that does not directly optimize class labels. We train the same bottlenecked ViT-Tiny architecture with the DINO self-supervised objective on ImageNet-100, using GAP followed by a single linear projection so that the final representation remains communication-limited rather than being aggregated by a large projection head.

Communication restriction again induces a structured performance spectrum, but with dynamics that differ from supervised classification. As measured by kNN accuracy, the gap between the attention-less and unmodified ViTs is larger under DINO than in the supervised setting (Fig. 5a), indicating that self-supervised representation learning places greater demand on global attention-mediated communication. The IB models interpolate across this range, with peak performance at $\beta = 0.003$ before degrading at still lower values of β. This non-monotonicity suggests that, in the weakly constrained regime, the IB parameterization can affect optimization or representation geometry even when the explicit information penalty is small.

To compare the resulting representation spaces, we compute linear CKA (Kornblith et al., 2019) between the

communication-restricted models and the two endpoint ViTs (Fig. 5b). High-β models closely align with the attention-less baseline. As communication increases, representations initially move toward the unmodified ViT, with similarity peaking near the same β that maximizes kNN accuracy before declining in the weakest-constraint regime. Thus, the best-performing DINO models are not simply those closest to the unmodified ViT endpoint; instead, the information budget traces a distinct path through representation space.

We also visualize how semantic localization emerges along the DINO spectrum. For each image, we compute the dot product between each patch representation and the global image representation obtained by averaging over patches. In the attention-less regime, these patch–image alignment maps remain largely local and diffuse. As communication becomes less restricted, object-aligned structure emerges, with clearer semantic localization appearing below approximately $\beta = 0.03$ (Fig. 5c). Thus, the same intervention that controls supervised patch voting also modulates the emergence of globally organized self-supervised representations.

Together, the DINO experiments show that communication bottlenecks are not tied to supervised classification losses. Across both supervised and self-supervised training, restricting attention-mediated residual writes yields an interpretable axis along which performance, representation geometry, and

Figure 5. **Restricted communication in SSL. (a)** DINO kNN accuracy interpolates between the attention-free and unmodified ViT endpoints, peaking at $\beta = 0.003$. **(b)** CKA similarity (Kornblith et al., 2019) compares image representations from bottlenecked models to the unmodified ViT (purple) and the independent-patch-processing ViT (green). Error bars show the standard deviation across cross-seed comparisons. **(c)** Patch-image alignment maps for random validation images, computed as the dot product between each patch representation and the final global image representation.

spatial organization change systematically.

The DINO results also separate two roles of the bottlenecked spectrum. In the supervised setting, GAP and patch logits make the transition from local voting to global consensus directly measurable. In the self-supervised setting, the same communication constraint instead organizes representation geometry and patch-image alignment, suggesting that the information budget controls a broader property of transformer computation rather than a peculiarity of supervised classification.

5. Discussion

Our results suggest that strong communication pressure exposes simple, high-value forms of global integration. In the lowest-information regimes, most attention heads collapse to the prior, leaving only a handful of active channels that can be inspected directly. The first active heads are sparse, low-dimensional, and reproducibly sensitive to patch repetition or redundancy across random seeds (Figs. 3,4). This indicates that coarse global texture statistics may be among the most information-efficient messages available to the model: cheap to transmit, but useful for coordinating otherwise independent patch representations.

Several limitations remain. We study ViT-Tiny models on

ImageNet-100, and the most interpretable circuits occur far from the dense communication patterns of models approaching the performance of an unrestricted ViT (Fig. 1b). Because the bottleneck modules add parameters and stochasticity, weakly constrained models need not exactly recover the unmodified ViT endpoint, even when the explicit KL penalty is small. Global average pooling provides a clean zero-communication endpoint but also constrains the class of readouts we study. In addition, each information budget requires training a separate model, making dense sweeps computationally expensive. Extending the framework to larger backbones, richer datasets, alternative aggregation structures, and more efficient ways of traversing the information spectrum will be important for testing the generality of the observed circuits.

More broadly, this work treats attention as a measurable communication channel rather than only as an architectural primitive. By restricting attention-mediated residual writes during training, we obtain models whose internal communication is intrinsically constrained, sparse, and tunable. This provides a complementary route to mechanistic interpretability: instead of only analyzing fully expressive models after training, we can bias optimization toward lower-bandwidth solutions and study how global computation emerges as that constraint is relaxed.

References

Achille, A. and Soatto, S. Information dropout: Learning optimal representations through noisy computation. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 40(12):2897–2905, 2018.

Akyürek, E., Schuurmans, D., Andreas, J., Ma, T., and Zhou, D. What learning algorithm is in-context learning? investigations with linear models. In *The Eleventh International Conference on Learning Representations*, 2023. URL https://openreview.net/forum?id=0g0X4H8yN4I.

Alemi, A. A., Fischer, I., Dillon, J. V., and Murphy, K. Deep variational information bottleneck. In *International Conference on Learning Representations*, 2017. URL https://openreview.net/forum?id=HyxQzBceg.

Bricken, T., Templeton, A., Batson, J., Chen, B., Jermyn, A., Conerly, T., Turner, N., Anil, C., Denison, C., Askell, A., Lasenby, R., Wu, Y., Kravec, S., Schiefer, N., Maxwell, T., Joseph, N., Hatfield-Dodds, Z., Tamkin, A., Nguyen, K., McLean, B., Burke, J. E., Hume, T., Carter, S., Henighan, T., and Olah, C. Towards monosemanticity: Decomposing language models with dictionary learning. *Transformer Circuits Thread*, 2023. https://transformer-circuits.pub/2023/monosemantic-features/index.html.

Caron, M., Touvron, H., Misra, I., Jégou, H., Mairal, J., Bojanowski, P., and Joulin, A. Emerging properties in self-supervised vision transformers. In *Proceedings of the IEEE/CVF international conference on computer vision*, pp. 9650–9660, 2021.

Chen, C., Li, O., Tao, D., Barnett, A., Rudin, C., and Su, J. K. This looks like that: deep learning for interpretable image recognition. *Advances in neural information processing systems*, 32, 2019.

Cubuk, E. D., Zoph, B., Shlens, J., and Le, Q. Randaugment: Practical automated data augmentation with a reduced search space. In Larochelle, H., Ranzato, M., Hadsell, R., Balcan, M., and Lin, H. (eds.), *Advances in Neural Information Processing Systems*, volume 33, pp. 18613–18624. Curran Associates, Inc., 2020. URL https://proceedings.neurips.cc/paper_files/paper/2020/file/d85b63ef0ccb114d0a3bb7b7d808028f-Paper.pdf.

Deng, J., Dong, W., Socher, R., Li, L.-J., Li, K., and Fei-Fei, L. Imagenet: A large-scale hierarchical image database. In *2009 IEEE conference on computer vision and pattern recognition*, pp. 248–255. Ieee, 2009.

Dorszewski, T., Tětková, L., Jenssen, R., Hansen, L. K., and Wickstrøm, K. K. From colors to classes: Emergence of concepts in vision transformers. In Guidotti, R., Schmid, U., and Longo, L. (eds.), *Explainable Artificial Intelligence*, pp. 28–47. Springer Nature Switzerland, 2026.

Dosovitskiy, A., Beyer, L., Kolesnikov, A., Weissenborn, D., Zhai, X., Unterthiner, T., Dehghani, M., Minderer, M., Heigold, G., Gelly, S., Uszkoreit, J., and Houlsby, N. An image is worth 16x16 words: Transformers for image recognition at scale. In *International Conference on Learning Representations*, 2021. URL https://openreview.net/forum?id=YicbFdNTTy.

Dutta, S., Singh, J., Chakrabarti, S., and Chakraborty, T. How to think step-by-step: A mechanistic understanding of chain-of-thought reasoning. *Transactions on Machine Learning Research*, 2024. ISSN 2835-8856. URL https://openreview.net/forum?id=uHLDkQVtyC.

Elhage, N., Nanda, N., Olsson, C., Henighan, T., Joseph, N., Mann, B., Askell, A., Bai, Y., Chen, A., Conerly, T., DasSarma, N., Drain, D., Ganguli, D., Hatfield-Dodds, Z., Hernandez, D., Jones, A., Kernion, J., Lovitt, L., Ndousse, K., Amodei, D., Brown, T., Clark, J., Kaplan, J., McCandlish, S., and Olah, C. A mathematical framework for transformer circuits. *Transformer Circuits Thread*, 2021. https://transformer-circuits.pub/2021/framework/index.html.

Gao, L., Rajaram, A., Coxon, J., Govande, S. V., Baker, B., and Mossing, D. Weight-sparse transformers have interpretable circuits. *arXiv preprint arXiv:2511.13653*, 2025.

Hill, M. O. Diversity and evenness: a unifying notation and its consequences. *Ecology*, 54(2):427–432, 1973.

Hong, J.-H., Kim, H.-J., Jeon, K.-S., and Lee, S.-W. Comprehensive information bottleneck for unveiling universal attribution to interpret vision transformers. In *2025 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 25166–25175, 2025. doi: 10.1109/CVPR52734.2025.02343.

Hu, S., Lou, Z., Yan, X., and Ye, Y. A survey on information bottleneck. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 46(8):5325–5344, 2024.

Huben, R., Cunningham, H., Smith, L. R., Ewart, A., and Sharkey, L. Sparse autoencoders find highly interpretable features in language models. In *The Twelfth International Conference on Learning Representations*, 2024. URL https://openreview.net/forum?id=F76bwRSLeK.

Jiang, Z., Tang, R., Xin, J., and Lin, J. Inserting Information Bottlenecks for Attribution in Transformers. In *Findings of the Association for Computational Linguistics: EMNLP 2020*, pp. 3850–3857, Online, November 2020. Association for Computational Linguistics. URL https://www.aclweb.org/anthology/2020.findings-emnlp.343.

Koh, P. W., Nguyen, T., Tang, Y. S., Mussmann, S., Pierson, E., Kim, B., and Liang, P. Concept bottleneck models. In *International conference on machine learning*, pp. 5338–5348. PMLR, 2020.

Kornblith, S., Norouzi, M., Lee, H., and Hinton, G. Similarity of neural network representations revisited. In *International conference on machine learning*, pp. 3519–3529. PMLR, 2019.

Liang, Y., Ge, C., Tong, Z., Song, Y., Wang, J., and Xie, P. Not all patches are what you need: Expediting vision transformers via token reorganizations. *arXiv preprint arXiv:2202.07800*, 2022.

Lowe, D. G. Distinctive image features from scale-invariant keypoints. *International journal of computer vision*, 60 (2):91–110, 2004.

Michel, P., Levy, O., and Neubig, G. Are sixteen heads really better than one? *Advances in neural information processing systems*, 32, 2019.

Murphy, K. A. and Bassett, D. S. Interpretability with full complexity by constraining feature information. In *International Conference on Learning Representations (ICLR)*, 2023. URL https://openreview.net/forum?id=R_OL5mLhsv.

Murphy, K. A. and Bassett, D. S. Information decomposition in complex systems via machine learning. *Proceedings of the National Academy of Sciences*, 121(13): e2312988121, 2024.

Murphy, K. A., Dillavou, S., and Bassett, D. S. Comparing the information content of probabilistic representation spaces. *Transactions on Machine Learning Research*, 2025. ISSN 2835-8856. URL https://openreview.net/forum?id=adhsMqURI1.

Nanda, N., Chan, L., Lieberum, T., Smith, J., and Steinhardt, J. Progress measures for grokking via mechanistic interpretability. In *The Eleventh International Conference on Learning Representations*, 2023. URL https://openreview.net/forum?id=9XFSbDPmdW.

Olah, C., Cammarata, N., Schubert, L., Goh, G., Petrov, M., and Carter, S. Zoom in: An introduction to circuits. *Distill*, 5(3):e00024–001, 2020.

Pan, B., Panda, R., Jiang, Y., Wang, Z., Feris, R., and Oliva, A. Ia-red^2: Interpretability-aware redundancy reduction for vision transformers. *Advances in neural information processing systems*, 34:24898–24911, 2021.

Park, N., Kim, W., Heo, B., Kim, T., and Yun, S. What do self-supervised vision transformers learn? In *The Eleventh International Conference on Learning Representations*, 2023. URL https://openreview.net/forum?id=azCKuYyS74.

Raghu, M., Unterthiner, T., Kornblith, S., Zhang, C., and Dosovitskiy, A. Do vision transformers see like convolutional neural networks? *Advances in neural information processing systems*, 34:12116–12128, 2021.

Rao, Y., Zhao, W., Liu, B., Lu, J., Zhou, J., and Hsieh, C.-J. Dynamicvit: Efficient vision transformers with dynamic token sparsification. *Advances in neural information processing systems*, 34:13937–13949, 2021.

Rudin, C. Stop explaining black box machine learning models for high stakes decisions and use interpretable models instead. *Nature Machine Intelligence*, 1(5):206–215, 2019.

Samek, W., Montavon, G., Lapuschkin, S., Anders, C. J., and Müller, K.-R. Explaining deep neural networks and beyond: A review of methods and applications. *Proceedings of the IEEE*, 109(3):247–278, 2021.

Sánchez, J., Perronnin, F., Mensink, T., and Verbeek, J. Image classification with the fisher vector: Theory and practice. *International journal of computer vision*, 105 (3):222–245, 2013.

Saxe, A. M., Bansal, Y., Dapello, J., Advani, M., Kolchinsky, A., Tracey, B. D., and Cox, D. D. On the information bottleneck theory of deep learning. *Journal of Statistical Mechanics: Theory and Experiment*, 2019(12):124020, dec 2019. doi: 10.1088/1742-5468/ab3985. URL https://doi.org/10.1088%2F1742-5468%2Fab3985.

Schulz, K., Sixt, L., Tombari, F., and Landgraf, T. Restricting the flow: Information bottlenecks for attribution. In *International Conference on Learning Representations*, 2020. URL https://openreview.net/forum?id=S1xWh1rYwB.

Simpson, E. H. Measurement of diversity. *nature*, 163 (4148):688–688, 1949.

Stevens, S., Chao, W.-L., Berger-Wolf, T., and Su, Y. Sparse autoencoders for scientifically rigorous interpretation of vision models. *arXiv preprint arXiv:2502.06755*, 2025.

Strehl, A. and Ghosh, J. Cluster ensembles—a knowledge reuse framework for combining multiple partitions. *Journal of machine learning research*, 3(Dec):583–617, 2002.

Tian, Y., Krishnan, D., and Isola, P. Contrastive multiview coding. In Vedaldi, A., Bischof, H., Brox, T., and Frahm, J.-M. (eds.), *Computer Vision – ECCV 2020*, pp. 776–794, Cham, 2020. Springer International Publishing. ISBN 978-3-030-58621-8.

Tishby, N., Pereira, F. C., and Bialek, W. The information bottleneck method. *arXiv preprint physics/0004057*, 2000.

Vaswani, A., Shazeer, N., Parmar, N., Uszkoreit, J., Jones, L., Gomez, A. N., Kaiser, Ł., and Polosukhin, I. Attention is all you need. *Advances in neural information processing systems*, 30, 2017.

Voita, E., Talbot, D., Moiseev, F., Sennrich, R., and Titov, I. Analyzing multi-head self-attention: Specialized heads do the heavy lifting, the rest can be pruned. *arXiv preprint arXiv:1905.09418*, 2019.

Wang, K. R., Variengien, A., Conmy, A., Shlegeris, B., and Steinhardt, J. Interpretability in the wild: a circuit for indirect object identification in GPT-2 small. In *The Eleventh International Conference on Learning Representations*, 2023. URL https://openreview.net/forum?id=NpsVSN6o4ul.

Zaheer, M., Kottur, S., Ravanbakhsh, S., Poczos, B., Salakhutdinov, R. R., and Smola, A. J. Deep sets. In Guyon, I., Luxburg, U. V., Bengio, S., Wallach, H., Fergus, R., Vishwanathan, S., and Garnett, R. (eds.), *Advances in Neural Information Processing Systems*, volume 30. Curran Associates, Inc., 2017. URL https://proceedings.neurips.cc/paper/2017/file/f22e4747da1aa27e363d86d40ff442fe-Paper.pdf.

Zhai, X., Kolesnikov, A., Houlsby, N., and Beyer, L. Scaling vision transformers. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pp. 12104–12113, 2022.

A. Declarations

Broader impacts. This work is foundational research on controlling and measuring information flow in vision transformers. Its potential positive impacts include improved interpretability, more transparent analysis of transformer computation, and better tools for understanding how models use attention-mediated communication. By making internal communication measurable and controllable, the method may help researchers identify simpler or more inspectable model behaviors and develop models whose internal mechanisms are easier to audit.

The potential negative impacts are indirect. Improved understanding of model internals could contribute to stronger models in domains where the models are later used harmfully. In addition, mechanistic analyses can be overinterpreted: sparse information flow or interpretable head behavior does not by itself guarantee that a model is safe, fair, or reliable under deployment. We therefore present the method as an analysis and control tool rather than as a guarantee of trustworthy behavior, and we support our claims with controlled experiments, quantitative measurements, and explicit limitations.

Compute resources. Experiments were conducted on an institutional high-performance computing cluster using NVIDIA A100 GPUs. As reported in Methods, the base ViT-tiny architecture has approximately 5.5M parameters, while the bottlenecked variant has approximately 7.6M parameters. For the supervised ImageNet-100 experiments, each bottlenecked ViT training run required approximately 3 days on a single A100 for 1000 epochs; the corresponding non-bottlenecked ViT baselines required roughly half this time. For the self-supervised DINO experiments, each bottlenecked ViT run required approximately 6 days on a single A100 for 800 epochs, with non-bottlenecked baselines again requiring roughly half this time. The reported experimental results include approximately 50 trained models spanning information-cost settings, random seeds, supervised baselines, and self-supervised runs. Beyond the experiments reported in the paper, the broader project involved approximately 50–100 additional preliminary exploratory runs used to tune hyperparameters, evaluate training schedules such as β-ramping, validate implementation choices, and select the final experimental protocol.

LLM usage. LLM-based programming assistance was used during implementation, including for code snippets related to architectural modifications for inserting variational information bottlenecks into the ViT attention blocks. The overall method design, integration into the codebase, experimental design, training, analysis, and interpretation were performed by the authors. The LLM was not used as a component of the proposed method, did not autonomously generate experimental results, and did not determine the scientific claims or conclusions. All implementation details, numerical results, figures, references, and manuscript content were reviewed and verified by the authors.

B. Implementation details

Accompanying code may be found on github.

All experiments are based on Vision Transformer (ViT) models implemented using the `timm` library. Unless otherwise stated, we use standard ViT architectures (e.g., patch size 16, image resolution 224) with modifications described below.

To study information-restricted attention, we wrap the attention module to bottleneck the per-head residual updates. For every head, the message passes through a variational information bottleneck (IB) module before being written to the residual stream. The IB is applied independently per attention head and per token, and returns both the transformed messages and a KL-divergence term used for regularization during training. For classification, we use global average pooling over the token representations and then apply the final projection to class logits. The remainder of the ViT architecture (patch embedding, positional embeddings, MLP blocks, normalization layers) follows the standard ViT design. All IB encoders and decoders had a single hidden layer with 256 dimensions, and the IB latent space was 32 dimensional.

DINO details. For DINO training, we follow the standard multi-crop augmentation protocol with global crop scale $(0.4, 1.0)$, local crop scale $(0.05, 0.4)$, and local crop size 96. We use warmup teacher temperature 0.04, final teacher temperature 0.07, student temperature 0.1, center momentum 0.9, teacher momentum 0.996, freeze the last layer for 1 epoch, use a 256-dimensional bottleneck projection space, and normalize the last layer.

Optimization. Models are trained using the AdamW optimizer with a base learning rate of 6×10^{-4} and a weight decay of 0.05, for 1000 epochs. Bias parameters, parameters with dimensionality one (e.g., LayerNorm scale parameters), and all parameters in the IB encoder and decoder are excluded from weight decay. All other parameters, including patch embeddings and positional embeddings, are subject to weight decay. Automatic mixed precision (AMP) is used with gradient scaling.

Training uses a cosine learning-rate schedule with linear warmup over the first 10 epochs. The coefficient β is fixed over the course of training.

Data and Augmentation. Experiments are conducted on the 100-class subset of Imagenet used in Tian et al. (2020) and specified in the accompanying github repository. Training images are augmented using random resized cropping, horizontal flipping, and RandAugment (Cubuk et al., 2020). We use a random resized crop with scale range [0.08, 1.0] and RandAugment with two augmentation operations of magnitude 9. Validation images are resized and center-cropped without stochastic augmentation. All images are normalized using standard ImageNet mean and standard deviation values.

C. Similarity assessments

Normalized mutual information. To compare the information content of two attention-head bottlenecks, we treat each head as inducing a soft clustering assignment over patches (Murphy et al., 2025). Let X denote a discrete index over all patch instances in the validation set, and let $Z^{\ell,h}$ denote the bottleneck latent variable for head h in layer ℓ. For a fixed head, the variational posterior defines a channel $q_{\ell,h}(z \mid x) \equiv q_{\phi_{\ell,h}}(z \mid \Delta_x^{\ell,h})$.

To quantify correspondence between two heads, let Z_1 and Z_2 denote their latent message variables. We form the joint channel by concatenating the two latent messages, equivalently using the product posterior $q(z_1, z_2 \mid x) = q_1(z_1 \mid x)q_2(z_2 \mid x)$. Using the identity

$$I(Z_1; Z_2) = I(X; Z_1) + I(X; Z_2) - I(X; Z_1, Z_2), \tag{4}$$

we estimate the information shared by the two headwise messages. Finally, we report the normalized mutual information (Strehl & Ghosh, 2002),

$$\mathrm{NMI}(Z_1, Z_2) = \frac{I(Z_1; Z_2)}{\sqrt{I(Z_1; Z_1')\, I(Z_2; Z_2')}}, \tag{5}$$

where Z_1' and Z_2' denote independent samples from the same corresponding headwise channels. Uncertainty is propagated from the standard errors of the Monte Carlo estimates of the constituent mutual informations.

JSD similarity of classification outputs. We compared the similarity of classification probability vectors for models across the spectrum, using the Jensen-Shannon divergence. The divergence values, grouped into five bins, are shown in Fig. 6.

D. Additional comparisons between model updates and patch voting

We show in Fig. 7 the survival function $\Pr(\mathrm{KL} \geq x)$ of per-patch information for all patches in the validation set and for all heads. We deem a head active if its KL exceeds 10^{-2} nats for at least one patch in the validation set. Only one attention head is 'active' at $\beta = 10$, and four heads are active for the $\beta = 4$ model. The heads that are active spend KL sparingly: 99% of patches receive an update costing less than 0.5 nats in the $\beta = 10$ case. For the low-information models ($\beta = 10, 4, 1$), the behavior is the same across heads, where the majority of patches get the same null update and the representation nearly mirrors the prior of the channel. As the information restriction loosens, $\beta = 0.01$ utilizes all 36 attention heads for non-trivial updates, and the distribution of KLs spent per patch shifts significantly, to where the majority deviate from the prior.

In Figs. 8, 9, and 10, we show how different models along the spectrum "vote" for different images, and for the information restricted models, how the KL budget is spent.

E. Additional attention head highly activating patches

In Figs. 11&12, we show top activating patches of both polarities for other seeds at $\beta = 10$ and for the four active heads of the $\beta = 4$ model.

Figure 6. **Jensen-Shannon divergence between classification outputs across the spectrum.** For all images in the validation set, we measure the similarity of model classification outputs across the spectrum to that of the independent patch processing model (ViT w/o attention, dark blue, top row) and to that of the unmodified ViT (yellow, bottom row).

Figure 7. **Attention head firing patterns.** Survival function $P(\text{KL} \geq x)$ of per-patch information across attention heads, showing that only a small fraction of patches carry significant routed information in the high-β regime. The grids on the right show which heads are active, starting with block 0 at the bottom.

Figure 8. **Patch voting and attention head update behavior for a random selection of images correctly classified by ViT (seed #1).**
Patches are colored according to the particular model's class assignments: dark blue for the patches whose top class matches that of the
full image prediction top class, light blue for ranks 2 through 5, and pink for ranks 6 through 10.

Figure 9. **Patch voting and attention head update behavior for a random selection of images correctly classified by ViT (seed #1) AND in the top 10% of images in terms of JSD between the ViT without attention and the unmodified ViT.**

Figure 10. **Patch voting and attention head update behavior for a random selection of images incorrectly classified by ViT (seed #1)**

Figure 11. **Additional top activation examples for heads with one active latent dimension: different $\beta = 10$ seeds.**

Figure 12. **Additional top activation examples for heads with one active latent dimension: different heads in the $\beta = 4$ model.**