Filtering Matters: Experiments in Filtering Training Sets for Machine Translation

Affiliation / Address line 1
Affiliation / Address line 2
Affiliation / Address line 3
email@domain

Anonymouser Author
Affiliation / Address line 1
Affiliation / Address line 2
Affiliation / Address line 3
email@domain

Anonymousest Author
Affiliation / Address line 1
Affiliation / Address line 2
Affiliation / Address line 3
email@domain

Abstract

We explore different approaches for filtering parallel data for MT training, whether the same filtering approaches suit different datasets and if separate filters should be applied to a dataset depending on translation direction. We evaluate the results of different approaches both manually and on a downstream NMT task. We find that it is beneficial to inspect how well different filtering approaches suit different dataset and that while MT systems trained on data prepared using different filters do not differ substantially in quality, there is indeed a statistically significant difference. We also find that the same training sets do not seem to suit different translation directions.

1 Introduction

In recent years, machine learning (ML) research has generally focused on creating better models rather than better datasets, where a focus on benchmarking model performance spur researchers into adapting the largest existing datasets without fully considering fidelity to the underlying problem the model should solve (Mazumder et al., 2022). The effectiveness of ML models, however, depends on both algorithms and data. Aroyo et al. (2021) argue that as the datasets define the world within which models exist and operate, more work is needed on how the data can be optimized for more effective use.

Filtering parallel data for machine translation (MT) is the task of removing possible detrimental segments from data used for training MT models. Filtering is usually carried out using a set of rules, scoring mechanisms and/or classifiers, to remove sentence pairs with the lowest perceived quality.

In this work, we experiment with filtering the raw data from two parallel corpora, ParaCrawl

(Bañón et al., 2020) and ParIce (Barkarson and Steingrímsson, 2019), for the English–Icelandic language pair. Our goal is to minimize detrimental data while losing little or no useful data from the texts, thus building a more accurate training set.

We investigate how shallow filters, four different scoring mechanisms and different classifiers based on them are suited to score and filter English–Icelandic sentence pairs. We compare these to Bicleaner and to the two corpora as they were filtered for publishing.

While recent literature on parallel corpus filtering has largely focused on filtering noisy data collected from the web, as discussed in Section 2, it is unclear how appropriate these approaches are to filtering cleaner parallel corpora compiled from document pairs where the documents are known to be mutual translations. Furthermore, although the same training data is usually used for training both translation directions, src→trg and trg→src, for a given dataset, we wonder if that is optimal.

Our aim is to find out how to filter parallel corpora so as to compile a training set that potentially gives the best results when used to train an MT system. We seek an answer to the following research questions: **1) Should the same filtering approaches be used for a given language pair, regardless of the datasets being filtered? 2) Should the intended translation direction of an MT system effect how the data used to train the system is filtered?** In order to answer these questions, we build MT models for both translation directions and multiple different filtering approaches for each one, and evaluate the results, both manually and automatically.

2 Related Work

In their paper, Khayrallah and Koehn (2018) show that incorrect translations, untranslated target text, misalignments and other noisy segments in a parallel corpus have a detrimental effect on

the output quality of NMT systems trained on that corpus, as measured using BLEU (Papineni et al., 2002). They specify five general classes of noise commonly found in the German-English Paracrawl corpus: misaligned sentences, disfluent text, wrong language, short segments, and untranslated sentences. As this classification is rather coarse, variation can be expected within each class; a misalignment in one sentence pair does not have to be equivalent to a misalignment in another sentence pair. Briakou and Carpuat (2021) focus on fine-grained divergences within mostly equivalent pairs (pairs of words, phrases or sentences that have similar meanings and connotations). They substitute words with their hypernyms or hyponyms, replace phrases with phrases of matching POS tags and delete subtrees from within sentences, and find that the divergences cause degradation, as expected, and that divergences impact model confidence in their predictions. Lexical substitution causes the largest degradation and subtree deletion the least. Nevertheless the impact on divergences seem to be smaller than that of noise. They argue that this suggests that noise-filtering techniques are suboptimal to deal with fine-grained divergences.

In early work on filtering web-scraped parallel corpora, Rarrick et al. (2011) filter out machine-translated content and show that removing large amounts of training data can improve performance of an MT system, challenging conventional wisdom at the time that more data is better.

Crosslingual word embeddings have been used to calculate distance between equivalences in different languages (Luong et al.; Artetxe et al., 2016). Defauw et al. (2019) treat filtering as a supervised regression problem and show that Levenshtein distance (Levenshtein, 1966) between the target and MT-translated source, as well as cosine distance between sentence embeddings of the source and target, are important features.

The Conference on Machine Translation, WMT, hosted three annual shared tasks on parallel corpus filtering (Koehn et al., 2018, 2019, 2020), focusing on filtering noisy web crawled corpora. Chaudhary et al. (2019) and Artetxe and Schwenk (2019a) introduced approaches based on crosslingual sentence embeddings trained from parallel sentences. Both papers tackle the inconsistencies of cosine similarity by investigating the neighbourhood of a given sentence pair, outperform-

ing systems using only cosine similarity. Bicleaner (Sánchez-Cartagena et al., 2018) uses a set of handcrafted rules to detect flawed sentences and then proceeds to use a random forest classifier based on lexical translations and several shallow features such as respective length, matching numbers and punctuation. It also scores sentences based on fluency using 5-gram language models. Bicleaner AI (Zaragoza-Bernabeu et al., 2022) is a fork of Bicleaner using a neural classifier. It has been shown to give significant improvements in translation quality as measured by BLEU when used for filtering training data for multiple language pairs, as compared to the previous version of the tool.

Herold et al. (2022) revisit the noise classes specified by Khayrallah and Koehn (2018) to investigate how accurately two of the strongest filtering approaches to date, according to them, cross entropy (Rossenbach et al., 2018) and LASER (Chaudhary et al., 2019) can filter out different noise classes. They find that for a common language pair, German→English, most types of noise can be detected with over 90% accuracy, although misalignments and poor synthetic translation can only be detected with an accuracy of less than 70%. For less common language pairs, the performance degraded significantly.

3 Experimental Setup

We compare a number of approaches and scoring mechanisms and apply them to a web-crawled corpus on the one hand, and a parallel corpus compiled from parallel documents on the other. We manually evaluate samples of the results using the taxonomy developed by Kreutzer et al. (2022) to gain an understanding of what sort of data each approach and scoring mechanism filters out. We then train MT systems on datasets filtered using the different approaches, as well as on previously published, filtered, versions of the corpora, and compare the quality of the resulting systems in terms of BLEU score. We measure BLEU scores on the test set provided for the English–Icelandic language pair in the WMT 2021 shared task (Akhbardeh et al., 2021), using Sacrebleu (Post, 2018).

3.1 Data Sets

The data sets we use for our experiments are the English–Icelandic part of ParaCrawl (Bañón et al., 2020) and the English–Icelandic parallel corpus

ParIce (Barkarson and Steingrímsson, 2019). We carry out the same experiments using both corpora and compare the results in order to answer our research question.

ParaCrawl is compiled from web-crawled data. Based on the evaluation by Kreutzer et al. (2022), approximately 76% of sentence pairs are acceptable mutual translations on average, in 21 language pairs from the ParaCrawl 7.1 datasets cleaned for publication. There is also high variance between languages and low-resource datasets tend to have lowest human-judged quality. Rikters (2018) inspects the quality of the first version of ParaCrawl and filters out 85% of the English–Estonian Paracrawl dataset. Although there may be differences in noise ratio between different versions of the corpus, for most language pairs ParaCrawl can likely be made more useful for training MT models by better filtering. This has been emphasized by the results of the WMT shared tasks on filtering parallel corpora. In our work, we start with the raw data from version 9 of the corpus, consisting of 65,373,727 sentence pairs in total. Our goal is to extract from the corpus sentence pairs useful for training MT systems on its own or to complement other data sets, and leave out sentence pairs likely to be detrimental.

The English-Icelandic parallel corpus ParIce differs from ParaCrawl in that it is compiled from known parallel documents, which have been aligned at the sentence level. When the corpus was compiled initially, the filtering process resulted in an estimated 20% reduction in corpus size. Out of what remained, manual evaluation of samples from the corpus indicated that approximately 3.5% was in some way faulty (Barkarson and Steingrímsson, 2019). The corpus is available unfiltered, accompanied with semantic similarity scores for each sentence pair and flags indicating whether it is recommended to filter out the pair or not. We work with the unfiltered data, version 21.10 (Steingrímsson and Barkarson).

3.2 Filters and Scoring

In order to find which sentence pairs are useful and which ones to filter out, we use an array of tools for scoring sentence pairs to find the highest-quality data within the corpora. We start with shallow filters to remove pairs that are very likely to be noise, and then proceed to run different tools, both made available by others and of our own device.

Shallow Filters

Our shallow filters are inspired by Pinnis (2018), who applies 17 different filters in his work. We do not use all his filtering approaches but select the ones likely to remove the highest portion of detrimental pairs as outlined by Khayrallah and Koehn (2018). They are:

1. Minimum sentence length of 3 tokens.

2. High overlap (60%) of tokens between source and target sentence.

3. At minimum, 70% of characters in both sentences should be alphabetical.

4. Both languages are in the top 2 prediction of a language filter. We use fasttext (Joulin et al., 2016) for language filtering.

5. Removal of near-duplicate pairs. We consider sentence pairs with all non-alphabetical symbols removed and if there are identical pairs in the corpus we keep the one with the highest score (Bicleaner score for ParaCrawl, LASER, LaBSE and WAScore for ParIce).

6. Removal of near-duplicate source or target sentence. We consider strings after removing all non-alphabetical symbols, and all tokens starting with a capital letter (removing possible named entities) from the sentences. If there are identical such strings in the same language we select the highest scoring pair.

Bicleaner Models

Bicleaner (Sánchez-Cartagena et al., 2018; Ramírez-Sánchez et al., 2020) is an open source noise filter and classification tool to clean parallel corpora, released as part of the ParaCrawl project and used to generate the filtered ParaCrawl datasets. Bicleaner uses a set of hard rules for pre-filtering, n-gram models for fluency scoring, and a random forest classifier to produce a probability score using features such as lexical similarity, sentence length, punctuation and capitalization. Bicleaner AI (Zaragoza-Bernabeu et al., 2022) is a fork that uses a fine-tuned XLM-RoBERTa classifier to produce probability scores.

We use two publicly available Bicleaner models for English–Icelandic, version 1.5 of the original Bicleaner and Bicleaner AI 1.0 full model. In addition, we train two new models using Bicleaner v0.15.2, one that classifies lemmatized

ParaCrawl shallow filtering					
Filter	Dataset Size	CC (%)	3C (%)	X (%)	3X (%)
0. ParaCrawl v9 Raw	65,373,727	14.40	69.20	8.00	30.80
0b. ParaCrawl v9 Clean	2,967,519	13.60	89.20	8.80	10.80
1.-3. Non-zero / low overlap (accepted)	31,094,385	23.60	94.80	4.40	5.20
1.-3. Non-zero / low overlap (discarded)	34,285,591	1.60	46.80	9.20	53.20
4.-5. Symbol+Language filter (accepted)	26,609,214	25.00	97.20	2.80	2.80
4.-5. Symbol+Language filter (discarded)	4,485,171	11.20	85.60	9.20	14.40
6. Similar pairs (accepted)	4,666,464	12.00	86.80	12.80	13.20
7. Similar segments (accepted)	2,081,354	14.80	95.60	3.60	4.40
ParIce shallow filtering					
0. ParIce 21.10 filtered	1,776,049	73.60	95.20	4.80	4.80

Table 1: Size and evaluation results for the shallow filtering approaches. For each dataset 250 random pairs are evaluated. 3C stands for all correct codes: CC, CB and CS. 3X stands for all error codes: X, WL and NL. For comparison, we also evaluate the clean version of the corpus as published by the ParaCrawl project. Note that we evaluated both accepted and discarded pairs for two of the filtering steps.

data and the other unlemmatized. For training each model, we used word frequency information from the Icelandic Gigaword Corpus (Steingríms-son et al., 2018) for Icelandic and News Crawl (Barrault et al., 2020) for English, a probabilistic dictionary (Steingrímsson et al., 2022) and for parallel training data, $250K$ highest-scoring sentence pairs from the 21.10 version of ParIce (Steingríms-son and Barkarson), based on the scores published with the corpus.

Scoring and Score-Based Classifiers

We used multiple scoring mechanisms to assess the quality of the bilingual sentence pairs.

LASER (Artetxe and Schwenk, 2019b) uses a single BiLSTM encoder with a shared byte-pair encoding (BPE) vocabulary (Sennrich et al., 2016) for all languages and is trained on parallel corpora.

LaBSE (Feng et al., 2022), is trained and optimized to produce similar representations for bilingual sentence pairs. It uses dual encoder models, with the encoder architecture following the BERT Base model, and additive margin softmax which improves the separation between translations and nearby non-translations (Yang et al., 2019). An available pre-trained model was trained on 109 languages, including Icelandic and English.

NMTScore (Vamvas and Sennrich, 2022) is based on translation cross-likelihood. It uses NMT to generate translations from source to target and target to source, for estimating the likelihood of one of the sentences being generated by the other. We use the M2M100 multilingual translation model (Fan et al., 2021) to calculate NMTScore.

WAScore is a word alignment-based score devised to measure word-level parallelism, intro-

duced in Steingrímsson et al. (2021) to help with identifying parallel bilingual sentence pairs in a comparable corpus.

The scores are used to train classifiers for determining acceptability of parallel sentence pairs. We adapt a training set compiled for a classifier used in mining comparable corpora (Steingríms-son et al., 2021). The dataset was compiled of 50,000 randomly sampled non-parallel pairs from two monolingual news corpora for negative examples and 1,000 parallel segments containing sentence pairs from news media. LASER, LaBSE, NMTScore and WAScore were calculated for all 51K sentence pairs, and used to train the classifiers. We used scikit-learn (Pedregosa et al., 2011) to train random forest (Breiman, 2001), support vector machine (Cortes and Vapnik, 1995) and logistic regression (Cox, 1958) classifiers.

Sentence Perplexity using GPT-2

We trained a classifier using a pre-trained GPT-2 model (Radford et al.) to recognize fluent and disfluent sentences. It is trained on 10,000 sentences selected randomly from WikiMatrix (Schwenk et al., 2021) and ParaCrawl v8, manually classified in two groups, *coherent* and *incoherent*. 6,570 sentences were classified as coherent and 3,430 sentences as incoherent.[1] The classifier sorts perplexity values and chooses potential thresholds as the average between two adjacent perplexity values. It then uses a maximization function to decide on a threshold that yields the most accurate prediction.

---

[1] https://anonymous.submission

3.3 Manual Evaluation

We manually annotated samples of the data sets compiled by each filtering approach. In our evaluation, we followed the taxonomy developed by Kreutzer et al. (2022), slightly amended to include partial misalignments. The taxonomy uses three codes for correct pairs and three error codes:

- CC – Correct translation.

- CB – Correct translation of low quality, or partly misaligned.

- CS – Correct translation, short.

- X – Incorrect translation.

- WL – Either sentence in wrong language.

- NL – Either sentence is non-linguistic content.

Shallow Filters: We annotated 250 randomly selected pairs from the datasets at different stages of shallow filtering. Table 1 shows the size of the datasets after applying shallow filters, and the percentage of sentence pairs in different categories. The evaluation indicates that almost 70% of the raw ParaCrawl data are potentially useful, while over 30% is in the best case useless and possibly detrimental. Note that this describes the dataset before any filtering or deduplication has been carried out. ParaCrawl also distributes a cleaned version of the corpus, containing approximately $3M$ sentence pairs. In that version, over 10% of sentence pairs are still erroneous and while almost

90% are potentially useful only 13.6% are evaluated to be good mutual translations. We filter the raw data and evaluate the changes after in between shallow filtering steps. All the filters discard some mutual translations but proportionally more inadequate pairs. While the 3C column indicates the ratio of all pairs in the correct category, it includes boilerplate and ungrammatical segments not necessarily useful for MT. We want our filters to keep as many sentence pairs from the CC category and remove all from the X-categories. After filters 1-7 (See Section 3.2) have been applied, we see the number of pairs annotated as correct, CC, is 14.8%. This is a reduced from 25% after filter 5, due to the fact that sentences that are identical except for numbers or other named entities have been reduced to one example.

For the ParIce corpus, we only manually evaluate after applying all the shallow filters and do not investigate the changes at each stage. This is because the data in the corpus all comes from known document sources and should not contain as much noisy data as ParaCrawl. We find that about 5% of sentence pairs in the corpus are erroneous, a number largely in line with the original ParIce paper, where the evaluation indicated that 3.5% of the alignments were bad, but we also find that only about three out of every four sentence pairs are mutual translations, with about 20% being accepted as correct while being imperfect in some way, usually due to misalignments.

Scores: After evaluating the shallow filters we evaluated the effectiveness of the scoring mecha-

	Laser								LaBSE							
	ParaCrawl				ParIce				ParaCrawl				ParIce			
	CC	3C	X	3X	CC	3C	X	3X	CC	3C	X	3X	CC	3C	X	3X
0.0 ⇒ 0.1	10	100	0	0	95	100	0	0	0	7	93	93	1	9	91	91
0.1 ⇒ 0.2	9	99	1	1	93	99	1	1	0	5	95	95	4	12	88	88
0.2 ⇒ 0.3	8	99	1	1	92	100	0	0	1	6	94	94	11	26	74	74
0.3 ⇒ 0.4	16	100	0	0	87	100	0	0	0	7	93	93	14	50	50	50
0.4 ⇒ 0.5	16	99	1	1	83	99	1	1	2	13	85	87	24	75	25	25
0.5 ⇒ 0.6	20	85	14	15	75	98	2	2	4	42	57	58	46	93	7	7
0.6 ⇒ 0.7	15	69	31	31	61	90	10	10	16	71	29	29	64	98	2	2
0.7 ⇒ 0.8	10	43	57	57	58	93	7	7	26	94	6	6	82	100	0	0
0.8 ⇒ 0.9	13	56	42	44	63	75	25	25	15	98	2	2	89	99	1	1
0.9 ⇒ 1.0	27	63	36	37	51	65	36	36	11	99	1	1	99	100	0	0
	NMTScore								WAScore							
	ParaCrawl				ParIce				ParaCrawl				ParIce			
	CC	3C	X	3X	CC	3C	X	3X	CC	3C	X	3X	CC	3C	X	3X
0.0 ⇒ 0.1	22	76	24	24	65	92	8	8	1	17	81	83	8	45	55	55
0.1 ⇒ 0.2	20	96	4	4	87	100	0	0	12	46	53	54	43	91	9	9
0.2 ⇒ 0.3	12	98	2	2	85	100	0	0	28	72	21	28	57	95	5	5
0.3 ⇒ 0.4	9	100	0	0	94	100	0	0	27	88	9	12	73	97	3	3
0.4 ⇒ 0.5	9	100	0	0	97	100	0	0	39	96	4	4	80	100	0	0
0.5 ⇒ 0.6	12	99	1	1	97	100	0	0	33	95	5	5	92	100	0	0
0.6 ⇒ 0.7	13	100	0	0	93	100	0	0	27	93	7	7	93	99	1	1
0.7 ⇒ 0.8	11	99	0	1	99	100	0	0	10	99	1	1	94	99	1	1
0.8 ⇒ 0.9	23	100	0	0	100	100	0	0	7	97	3	3	94	99	1	1
0.9 ⇒ 1.0	20	100	0	0	100	100	0	0	5	98	2	2	95	100	0	0

Table 2: Results of the manual evaluation of samples of 100 randomly selected sentence pairs from each of ten bands for the scoring mechanisms used.

Filter	ParaCrawl Filters									
	accepted (%)					rejected (%)				
	No. pairs	CC	3C	X	3X	No. pairs	CC	3C	X	3X
GPT-2	1,218,256	15.00	93.00	7.00	7.00	863.098	5.00	91.00	8.00	9.00
Logistic Regression	1,940,385	38.00	85.00	4.00	15.00	140,969	18.00	37.00	61.00	63.00
Random Forest	1,981,405	7.00	98.00	0.00	2.00	99,949	2.00	22.00	77.00	78.00
Support Vector Machine	1,991,924	12.00	98.00	2.00	2.00	89,430	0.00	22.00	78.00	78.00
Bicleaner baseline (0.50)	1,973,885	22.00	96.00	4.00	4.00	107,469	10.00	41.00	58.00	59.00
Bicleaner baseline (0.67)	1,705,042	15.00	98.00	2.00	2.00	376,312	20.00	80.00	20.00	20.00
Bicleaner retrained (0.50)	1,898,209	25.00	97.00	3.00	3.00	183,145	27.00	75.00	25.00	25.00
Bicleaner retrained (0.67)	1,615,913	20.00	98.00	2.00	2.00	465,441	24.00	81.00	18.00	19.00
Bicleaner lemmatized (0.50)	1,850,884	18.00	88.00	8.00	12.00	230,470	14.00	66.00	28.00	34.00
Bicleaner lemmatized (0.67)	1,512,437	30.00	93.00	5.00	7.00	568,917	21.00	70.00	29.00	30.00
Bicleaner AI (0.50)	1,235,771	**33.00**	**99.00**	1.00	1.00	845,583	6.00	85.00	13.00	15.00
Bicleaner AI (0.67)	1,096,288	25.00	97.00	3.00	3.00	985,066	8.00	92.00	8.00	8.00

Filter	ParIce filters									
	accepted (%)					rejected (%)				
	No. pairs	CC	3C	X	3X	No. pairs	CC	3C	X	3X
GPT-2	1,444,956	81.00	96.00	4.00	4.00	331,093	68.00	91.00	9.00	9.00
Logistic Regression	1,560,346	85.00	100.00	0.00	0.00	215,703	49.00	77.00	23.00	23.00
Random Forest	1,667,847	86.00	99.00	1.00	1.00	108,202	20.00	51.00	49.00	49.00
Support Vector Machine	1,646,183	91.00	100.00	0.00	0.00	129,866	28.00	58.00	42.00	42.00
Bicleaner baseline (0.50)	1,546,216	85.00	99.00	1.00	1.00	229,833	35.00	79.00	21.00	21.00
Bicleaner baseline (0.67)	1,242,258	86.00	100.00	0.00	0.00	533,791	48.00	86.00	14.00	14.00
Bicleaner retrained (0.50)	1,499,610	85.00	99.00	1.00	1.00	276,439	42.00	90.00	10.00	10.00
Bicleaner retrained (0.67)	1,244,412	94.00	100.00	0.00	0.00	531,637	55.00	95.00	5.00	5.00
Bicleaner lemmatized (0.50)	1,463,780	89.00	100.00	0.00	0.00	312,267	50.00	90.00	10.00	10.00
Bicleaner lemmatized (0.67)	1,117,814	88.00	100.00	0.00	0.00	604,235	69.00	98.00	2.00	2.00
Bicleaner AI (0.50)	1,262,313	**95.00**	**100.00**	0.00	0.00	513,736	60.00	86.00	13.00	14.00
Bicleaner AI (0.67)	1,152,319	91.00	100.00	0.00	0.00	623,730	77.00	95.00	5.00	5.00

Table 3: Manual evaluation of datasets generated by different filtering approaches. We both evaluate sentence pairs accepted by each filtering approach, and rejected by it.

nisms. We divided the scores for each scoring approach into 10 bands, and manually evaluated 100 pairs for each band. The evaluation results, shown in Table 2, indicate that all the scoring methods have some merit and could probably be useful to a classifier. On their own, the results usually differ depending on the parallel corpora used, with the accuracy of the same scoring mechanism varying for different corpora. For example, the LaBSE score has to be more than 0.7 for more than 90% of sentence pairs in a scoring band to be acceptable (3C) for ParaCrawl, but only 0.5 for ParIce.

The distribution of the scores differ between scoring approaches, which can effect their usefulness. While NMTScore seems to be very accurate when looking at the bands in the table, 83% of the ParaCrawl sentences have a score of less than 0.3, and 25% of the ParIce sentences have a score of less than 0.1, indicating that even though the results seem very good, using only this scoring method may not be enough for accurate filtering. It should also be noted that most approaches do not seem to be very good at discerning finer nuances such as whether a sentence pair contains only mutual translations or if there is additional content in at least one of the sentences. The ratio of CC usually does not change as consistently with rising scores as the 3C or 3X ratio. This may indicate that if some sentence pairs classified as CB are detrimental to MT training, we need other approaches to identify them and filter out.

Filters: We annotated 100 pairs from each group of stochastic filtering approaches. We use the classifiers and Bicleaner models described in section 3.2. We set cutoff score at two different levels for each Bicleaner model, 0.5 and a higher threshold of 0.67 to try to discover whether detrimental sentence pairs can still be found at such a high level.

As evident in Table 3, the filtering mechanisms are quite adept at removing erroneous sentence pairs. We can see that for both corpora, all but two filters return over 90% accepted sentence pairs, and a low rate of erroneous data, and for ParIce in particular almost all erroneous data is removed for 8 out of 12 filtering approaches. However, as it is important to keep as many of the good sentence pairs as possible, the most useful approaches may be the ones that remove the fewest mutual translations. We see that while the model having the highest proportion of CC, mutual translations, is Bicleaner AI, it has the drawback of filtering out the highest proportion of sentences compared to almost all other approaches. With almost half of the ParaCrawl data rejected, 985,066 out of 2,081,354 sentence pairs, when the threshold score is set to 0.67, of which 92% were rated in one of the correct categories. In order to investigate further what is best for MT training, we next train multiple models, using all the different data sets we have compiled, in order to see how the translations generated by these models compare to the results of our manual evaluation.

	ParaCrawl training experiments					ParIce training experiments				
Dataset	no. pairs	en→is	time	is→en	time	no. pairs	en→is	time	is→en	time
Baseline: ParaCrawl v9 clean	2,967,519	20.0	23h3m	30.6	11h14m					
Baseline: ParIce 21.10						1,864,679	19.1	22h54m	25.7	15h06m
Shallow filter 5 - Similar pairs	4,666,464	18.8	18h9m	30.4	29h56m					
Shallow filter 6 - Similar segments	2,081,354	19.7	13h3m	31.9	15h57m					
ParIce shallow filters						1,776,049	**19.6**	23h29m	25.5	14h31m
IS-perplexity (GPT-2)	1,218,256	**20.5**	5h50m	*32.4*	14h11m	1,444,956	18.4	22h33m	24.7	10h18m
SVM	1,991,924	19.3	13h41	*32.4*	15h56m	1,646,183	**19.6**	17h38m	**26.0**	13h04m
Logistic Regression	1,940,385	19.8	11h48	32.1	12h01m	1,560,346	19.1	16h51m	**26.1**	13h30m
Random Forest	1,981,405	19.2	6h37m	31.7	15h32m	1,667,847	18.5	20h07m	25.2	12h22m
Bicleaner 1.5 (0.50)	1,973,885	19.2	11h25m	*32.2*	15h33m	1,546,216	19.3	21h52m	*26.2*	12h5m
Bicleaner 1.5 (0.67)	1,705,042	19.0	8h29m	31.4	8h53m	1,242,258	**19.4**	12h06m	25.6	9h01m
Bicleaner retrained (0.50)	1,898,209	18.7	8h17m	31.9	15h41m	1,499,610	**19.5**	7h13m	25.6	12h22m
Bicleaner retrained (0.67)	1,615,913	19.3	7h36m	30.5	12h59m	1,244,412	**19.4**	10h16m	25.7	6h13m
Bicleaner lemmatized (0.50)	1,850,884	19.3	10h29m	31.6	17h19m	1,463,780	*19.7*	15h12m	**25.9**	11h56m
Bicleaner lemmatized (0.67)	1,512,437	19.1	6h27m	30.9	8h32m	1,171,814	*19.7*	7h29m	25.6	8h56m
Bicleaner AI (0.50)	1,235,771	20.2	8h26m	31.4	7h15m	1,262,313	**19.4**	7h07m	*26.2*	7h44m
Bicleaner AI (0.67)	1,096,288	*20.6*	4h50m	30.9	3h45m	1,152,319	18.8	7h11m	25.1	7h28m

Table 4: BLEU scores and training time for different filtering approaches.

3.4 Automatic evaluation

We evaluate the effect of different filtering approaches on a downstream NMT task, by training different MT models for each of the compiled datasets and evaluate them using BLEU. We use fairseq (Ott et al., 2019) to train Transformer$_{BASE}$ models, as described in Vaswani et al. (2017), except that we set dropout to 0.2 and use BPE with a shared vocabulary size of $32K$. We train each model on a single A100 GPU and use early stopping with the patience set to 10 epochs. We use the development and test sets provided for English–Icelandic news translation task at WMT 2021 (Akhbardeh et al., 2021) , using SacreBLEU (Post, 2018).[2] Following Koszowski et al. (2021) we apply regular expressions to fix quotation marks post-translation, making sure Icelandic quotation marks are used in the Icelandic translations and English quotation marks in the English translations.

---

[2]SacreBLEU Signature: BLEU+numrefs.1+case.mixed+tok.13a+smooth.exp+version.2.2.0

We train baseline models using the cleaned ParaCrawl dataset and the most recent published version of ParIce, and compare them to models trained on filtered datasets.Table 4 shows resulting BLEU scores. We used the pairwise bootstrap test (Koehn, 2004) to calculate statistical significance. Scores in italic are the highest, but not significantly higher than scores in bold. An effect of training with a cleaner dataset seems to be that the model reaches convergence faster, even though the quality is the same or better. We know from our manual evaluation that most of these training sets contain some erroneous pairs, and in order to try to reduce the number of these we select the dataset resulting in the highest BLEU score out of the datasets compiled by a Bicleaner model and the best resulting dataset compiled by a classifier. We do an ablation study to investigate whether combining these filters, and the filter looking at perplexity in Icelandic sentences, leads to a better training set. For each dataset and translation direction we combine the highest scoring

ParaCrawl en→is filters			
Dataset	no. pairs	BLEU	time
Bicleaner AI (0.67) + LogReg	1,071,802	20.2	3h51m
Bicleaner AI (0.67) + IS-pplx	776,984	*21.0*	4h17m
Bicleaner AI (0.67) + LogReg + IS-pplx	756,503	20.5	3h40m
ParaCrawl is→en filters			
Dataset	no. pairs	BLEU	time
Bicleaner 1.5 (0.50) + SVM	1,930,998	**32.3**	20h24m
Bicleaner 1.5 (0.50) + IS-pplx	1,147,961	31.9	9h02m
Bicleaner 1.5 (0.50) + SVM + IS-pplx	1,119,400	32.1	7h32m
ParIce en→is filters			
Dataset	no. pairs	BLEU	time
Bicleaner Lemmatized (0.50) + SVM	1,405,446	*20.0*	17h59m
Bicleaner Lemmatized (0.50) + IS-pplx	1,205,070	19.4	14h04m
Bicleaner Lemmatized (0.50) + SVM + IS-pplx	1,161,337	18.8	13h24m
ParIce is→en filters			
Dataset	no. pairs	BLEU	time
Bicleaner 1.5 (0.50) + LogReg	1,430,015	**26.1**	13h22m
Bicleaner 1.5 (0.50) + IS-pplx	1,269,808	25.7	9h30m
Bicleaner 1.5 (0.50) + LogReg + IS-pplx	1,179,158	25.7	10h46m
Best datasets from both corpora combined			
Dataset	no. pairs	BLEU	time
is→en: ParaCrawl SVM + ParIce Bicleaner 1.5 (0.50)	3,538,140	*33.2*	28h10m
en→is: ParaCrawl – Bicleaner AI (0.67) + IS-pplx + ParIce – Bicleaner Lemmatized (0.50) + SVM	2,182,430	*22.3*	18h57m

Table 5: BLEU scores and training time for combinations of different filtering approaches.

Bicleaner model with combinations of the highest scoring statistical classifier and the GPT-2 classifier. Table 5 shows the results for different combinations. For the English→Icelandic translation direction we obtain higher scores for both corpora using a combination, but for Icelandic→English the BLEU scores never exceed the best standalone filters. We speculate this may be due to noise being more common in the Icelandic texts instigating a need for more filtering when that is the target language, but further investigation is needed.

For our final models we concatenate the highest-scoring datasets from ParaCrawl and ParIce. These models obtain the highest BLEU scores, 33.2 for Icelandic→English and 22.3 for English→Icelandic. We compare these scores to the results of systems submitted to the WMT 2021 news translation task for the same language pair and directions. Koszowski et al. (2021) submitted a system trained on ParIce and ParaCrawl as well as WikiMatrix and wikititles. The model, based on Transformer$_{BIG}$ (Vaswani et al., 2017), using back-translation and forward-translation for data augmentation achieve 22.7 and 33.3 BLEU for en→is and is→en, respectively. Símonarson et al. (2021) train MT models using mBART-25, employing 16 V100 GPUs. They employ back-translations in their training and achieve 22.7 and 32.9 BLEU for en→is and is→en, respectively, after training for 4 days. Slightly higher than our best scores, we only filter, while they use data augmentation, larger models and more computing power for longer periods of time.

4 Conclusions and Future Work

In regards to our research questions, our results indicate that different filtering approaches suit different datasets and translation directions, even though we are working within the same language pair. Manual inspection of filtering results and scoring mechanisms seem to be helpful for making informed decisions on how best to filter a dataset. For best results, filtering approaches should be chosen for each translation direction. A limitation of our work is that it doesn't show which data are detrimental and which are beneficial. In future work we want to investigate if the differences between datasets used for training can give us an idea of which sentence pairs are most important to filter out. We intend to do this by investigating the pairs discarded by our filters, to compare the data that leads to rising BLEU scores and that which lowers them. This could lead to insights that help constructing filters that work on a more fine-grained level when that is needed.

Our manual evaluation shows that the scores generated by the automatic scoring systems we employ have different interpretations depending on the dataset. If scores are used for filtering parallel data, the optimal score should lead to a dataset that produces the best MT model. Feng et al. (2022) suggest a threshold of 0.6 for LaBSE when mining parallel text from CommonCrawl, stating that the threshold was selected by manually inspecting sampled data, but do not specify the language pair used when inspecting the data. In order for the scoring mechanism to be most effective, the user should inspect the results for their dataset before setting a threshold. While all our scoring mechanisms seem to be useful, none of the methods are very good at identifying mutual translations in particular, labelled CC in our taxonomy.

We trained two Bicleaner models for our experiments and our lemmatized model gave the best results for filtering ParIce for the en→is translation direction. The Bicleaner models could perhaps be improved. Bicleaner uses n-gram models and we only used a part of our parallel corpora to train these. If we would use larger corpora the n-gram models would likely give us more accurate scores. The bilingual probability dictionary we used only contained lemmas. By producing all wordforms for the lemmas and trying to estimate the prevalence of each wordform using a monolingual corpus, we could perhaps provide an unlemmatized model with more accurate information leading to better results. Furthermore, we only use 10K sentences to train our GPT-2 perplexity model for Icelandic. A larger dataset may increase its accuracy.

Two systems participating in the WMT 2021 news translation task, evaluated on the same data, obtain scores only slightly higher than ours, but while we only train a Transformer$_{BASE}$ model, they train larger models using more resources and much longer training time. In our experiments, it seems that models that have been filtered more tend to converge faster. We can deduce from this that training data that is better filtered, not only improves MT output quality, but is also in line with a call to greener and more sustainable models of AI, see e.g. Yusuf et al. (2021) and Jooste et al. (2022).

References

Farhad Akhbardeh, Arkady Arkhangorodsky, Magdalena Biesialska, Ondřej Bojar, Rajen Chatterjee, Vishrav Chaudhary, Marta R. Costa-jussa, Cristina España-Bonet, Angela Fan, Christian Federmann, Markus Freitag, Yvette Graham, Roman Grundkiewicz, Barry Haddow, Leonie Harter, Kenneth Heafield, Christopher Homan, Matthias Huck, Kwabena Amponsah-Kaakyire, Jungo Kasai, Daniel Khashabi, Kevin Knight, Tom Kocmi, Philipp Koehn, Nicholas Lourie, Christof Monz, Makoto Morishita, Masaaki Nagata, Ajay Nagesh, Toshiaki Nakazawa, Matteo Negri, Santanu Pal, Allahsera Auguste Tapo, Marco Turchi, Valentin Vydrin, and Marcos Zampieri. 2021. Findings of the 2021 conference on machine translation (wmt21). In *Proceedings of the Sixth Conference on Machine Translation*, pages 1–88, Online. Association for Computational Linguistics.

Lora Aroyo, Matthew Lease, Praveen K. Paritosh, and Mike Schaekermann. 2021. Data excellence for ai: Why should you care. *ArXiv*, abs/2111.10391.

Mikel Artetxe, Gorka Labaka, and Eneko Agirre. 2016. Learning principled bilingual mappings of word embeddings while preserving monolingual invariance. In *Proceedings of the 2016 Conference on Empirical Methods in Natural Language Processing*, Austin, Texas.

Mikel Artetxe and Holger Schwenk. 2019a. Margin-based parallel corpus mining with multilingual sentence embeddings. In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, Florence, Italy.

Mikel Artetxe and Holger Schwenk. 2019b. Massively Multilingual Sentence Embeddings for Zero-Shot Cross-Lingual Transfer and Beyond. *Transactions of the Association for Computational Linguistics*, 7:597–610.

Marta Bañón, Pinzhen Chen, Barry Haddow, Kenneth Heafield, Hieu Hoang, Miquel Esplà-Gomis, Mikel L. Forcada, Amir Kamran, Faheem Kirefu, Philipp Koehn, Sergio Ortiz Rojas, Leopoldo Pla Sempere, Gema Ramírez-Sánchez, Elsa Sarrías, Marek Strelec, Brian Thompson, William Waites, Dion Wiggins, and Jaume Zaragoza. 2020. ParaCrawl: Web-scale acquisition of parallel corpora. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, Online. Association for Computational Linguistics.

Starkaður Barkarson and Steinþór Steingrímsson. 2019. Compiling and Filtering ParIce: An English-Icelandic Parallel Corpus. In *Proceedings of the 22nd Nordic Conference on Computational Linguistics*, Turku, Finland.

Loïc Barrault, Magdalena Biesialska, Ondřej Bojar, Marta R. Costa-jussà, Christian Federmann, Yvette Graham, Roman Grundkiewicz, Barry Haddow, Matthias Huck, Eric Joanis, Tom Kocmi, Philipp Koehn, Chi-kiu Lo, Nikola Ljubešić, Christof Monz, Makoto Morishita, Masaaki Nagata, Toshiaki Nakazawa, Santanu Pal, Matt Post, and Marcos Zampieri. 2020. Findings of the 2020 conference on machine translation (WMT20). In *Proceedings of the Fifth Conference on Machine Translation*, pages 1–55, Online. Association for Computational Linguistics.

Leo Breiman. 2001. Random forests. *Machine Learning*, 45(1):5–32.

Eleftheria Briakou and Marine Carpuat. 2021. Beyond noise: Mitigating the impact of fine-grained semantic divergences on neural machine translation. In *Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing (Volume 1: Long Papers)*, Online. Association for Computational Linguistics.

Vishrav Chaudhary, Yuqing Tang, Francisco Guzmán, Holger Schwenk, and Philipp Koehn. 2019. Low-Resource Corpus Filtering Using Multilingual Sentence Embeddings. In *Proceedings of the Fourth Conference on Machine Translation (Volume 3: Shared Task Papers, Day 2)*, Florence, Italy.

Corinna Cortes and Vladimir Vapnik. 1995. Support-vector networks. *Machine learning*, 20(3):273–297.

David R Cox. 1958. The regression analysis of binary sequences. *Journal of the Royal Statistical Society: Series B (Methodological)*, 20(2):215–232.

Arne Defauw, Sara Szoc, Anna Bardadym, Joris Brabers, Frederic Everaert, Roko Mijic, Kim Scholte, Tom Vanallemeersch, Koen Van Winckel, and Joachim Van den Bogaert. 2019. Misalignment Detection for Web-Scraped Corpora: A Supervised Regression Approach. *Informatics*, 6(3):35.

Angela Fan, Shruti Bhosale, Holger Schwenk, Zhiyi Ma, Ahmed El-Kishky, Siddharth Goyal, Mandeep Baines, Onur Celebi, Guillaume Wenzek, Vishrav Chaudhary, Naman Goyal, Tom Birch, Vitaliy Liptchinsky, Sergey Edunov, Edouard Grave, Michael Auli, and Armand Joulin. 2021. Beyond english-centric multilingual machine translation. *J. Mach. Learn. Res.*, 22(1).

Fangxiaoyu Feng, Yinfei Yang, Daniel Cer, Naveen Arivazhagan, and Wei Wang. 2022. Language-agnostic BERT sentence embedding. In *Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, Dublin, Ireland. Association for Computational Linguistics.

Christian Herold, Jan Rosendahl, Joris Vanvinckenroye, and Hermann Ney. 2022. Detecting various types of noise for neural machine translation. In *Findings of the Association for Computational Linguistics: ACL 2022*, Dublin, Ireland. Association for Computational Linguistics.

Wandri Jooste, Rejwanul Haque, and Andy Way. 2022. Knowledge distillation: A method for making neural machine translation more efficient. *Information*, 13(2).

Armand Joulin, Edouard Grave, Piotr Bojanowski, and Tomas Mikolov. 2016. Bag of tricks for efficient text classification. *arXiv preprint arXiv:1607.01759*.

Huda Khayrallah and Philipp Koehn. 2018. On the impact of various types of noise on neural machine translation. In *Proceedings of the 2nd Workshop on Neural Machine Translation and Generation*, Melbourne, Australia.

Philipp Koehn. 2004. Statistical significance tests for machine translation evaluation. In *Proceedings of the 2004 Conference on Empirical Methods in Natural Language Processing*, Barcelona, Spain. Association for Computational Linguistics.

Philipp Koehn, Vishrav Chaudhary, Ahmed El-Kishky, Naman Goyal, Peng-Jen Chen, and Francisco Guzmán. 2020. Findings of the WMT 2020 shared task on parallel corpus filtering and alignment. In *Proceedings of the Fifth Conference on Machine Translation*, Online. Association for Computational Linguistics.

Philipp Koehn, Francisco Guzmán, Vishrav Chaudhary, and Juan Pino. 2019. Findings of the WMT 2019 shared task on parallel corpus filtering for low-resource conditions. In *Proceedings of the Fourth Conference on Machine Translation (Volume 3: Shared Task Papers, Day 2)*, Florence, Italy. Association for Computational Linguistics.

Philipp Koehn, Huda Khayrallah, Kenneth Heafield, and Mikel L. Forcada. 2018. Findings of the WMT 2018 shared task on parallel corpus filtering. In *Proceedings of the Third Conference on Machine Translation: Shared Task Papers*, Belgium, Brussels. Association for Computational Linguistics.

Mikołaj Koszowski, Karol Grzegorczyk, and Tsimur Hadeliya. 2021. Allegro.eu submission to WMT21 news translation task. In *Proceedings of the Sixth Conference on Machine Translation*, Online. Association for Computational Linguistics.

Julia Kreutzer, Isaac Caswell, Lisa Wang, Ahsan Wahab, Daan van Esch, Nasanbayar Ulzii-Orshikh, Allahsera Tapo, Nishant Subramani, Artem Sokolov, Claytone Sikasote, Monang Setyawan, Supheakmungkol Sarin, Sokhar Samb, Benoît Sagot, Clara Rivera, Annette Rios, Isabel Papadimitriou, Salomey Osei, Pedro Ortiz Suarez, Iroro Orife, Kelechi Ogueji, Andre Niyongabo Rubungo, Toan Q. Nguyen, Mathias Müller, André Müller, Shamsuddeen Hassan Muhammad, Nanda Muhammad, Ayanda Mnyakeni, Jamshidbek Mirzakhalov, Tapiwanashe Matangira, Colin Leong, Nze Lawson, Sneha Kudugunta, Yacine Jernite, Mathias Jenny, Orhan Firat, Bonaventure F. P. Dossou, Sakhile Dlamini, Nisansa de Silva, Sakine Çabuk Ballı,

Stella Biderman, Alessia Battisti, Ahmed Baruwa, Ankur Bapna, Pallavi Baljekar, Israel Abebe Azime, Ayodele Awokoya, Duygu Ataman, Orevaoghene Ahia, Oghenefego Ahia, Sweta Agrawal, and Mofetoluwa Adeyemi. 2022. Quality at a Glance: An Audit of Web-Crawled Multilingual Datasets. *Transactions of the Association for Computational Linguistics*, 10:50–72.

Vladimir Iosifovich Levenshtein. 1966. Binary codes capable of correcting deletions, insertions and reversals. *Soviet Physics Doklady*, 10(8):707–710.

Minh-Thang Luong, Hieu Pham, and Christopher D. Manning. Bilingual Word Representations with Monolingual Quality in Mind. In *NAACL Workshop on Vector Space Modeling for NLP*, Denver, Colorado.

Mark Mazumder, Colby R. Banbury, Xiaozhe Yao, Bojan Karlavs, William Gaviria Rojas, Sudnya Diamos, Gregory Frederick Diamos, Lynn He, Douwe Kiela, David Jurado, David Kanter, Rafael Mosquera, Juan Ciro, Lora Aroyo, Bilge Acun, Sabri Eyuboglu, Amirata Ghorbani, Emmett D. Goodman, Tariq Kane, Christine R. Kirkpatrick, Tzu-Sheng Kuo, Jonas Mueller, Tristan Thrush, Joaquin Vanschoren, Margaret J. Warren, Adina Williams, Serena Yeung, Newsha Ardalani, Praveen K. Paritosh, Ce Zhang, James Y. Zou, Carole-Jean Wu, Cody Coleman, Andrew Y. Ng, Peter Mattson, and Vijay Janapa Reddi. 2022. Dataperf: Benchmarks for data-centric ai development. *ArXiv*, abs/2207.10062.

Myle Ott, Sergey Edunov, Alexei Baevski, Angela Fan, Sam Gross, Nathan Ng, David Grangier, and Michael Auli. 2019. fairseq: A Fast, Extensible Toolkit for Sequence Modeling. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics (Demonstrations)*, Minneapolis, Minnesota. Association for Computational Linguistics.

Kishore Papineni, Salim Roukos, Todd Ward, and Wei-Jing Zhu. 2002. BLEU: A Method for Automatic Evaluation of Machine Translation. In *Proceedings of the 40th Annual Meeting of the Association for Computational Linguistics*, Philadelphia, PA.

F. Pedregosa, G. Varoquaux, A. Gramfort, V. Michel, B. Thirion, O. Grisel, M. Blondel, P. Prettenhofer, R. Weiss, V. Dubourg, J. Vanderplas, A. Passos, D. Cournapeau, M. Brucher, M. Perrot, and E. Duchesnay. 2011. Scikit-learn: Machine learning in Python. *Journal of Machine Learning Research*, 12:2825–2830.

Mārcis Pinnis. 2018. Tilde's Parallel Corpus Filtering Methods for WMT 2018. In *Proceedings of the Third Conference on Machine Translation: Shared Task Papers*, Belgium, Brussels.

Matt Post. 2018. A call for clarity in reporting BLEU scores. In *Proceedings of the Third Conference on*

Machine Translation: Research Papers, Brussels, Belgium. Association for Computational Linguistics.

Alec Radford, Jeffrey Wu, Rewon Child, David Luan, Dario Amodei, and Ilya Sutskever. Language models are unsupervised multitask learners.

Gema Ramírez-Sánchez, Jaume Zaragoza-Bernabeu, Marta Bañón, and Sergio Ortiz-Rojas. 2020. Bifixer and bicleaner: two open-source tools to clean your parallel data. In *Proceedings of the 22nd Annual Conference of the European Association for Machine Translation*, pages 291–298, Lisboa, Portugal. European Association for Machine Translation.

Spencer Rarrick, Chris Quirk, and Will Lewis. 2011. MT detection in web-scraped parallel corpora. In *Proceedings of Machine Translation Summit XIII: Papers*, Xiamen, China.

Matiss Rikters. 2018. http://arxiv.org/abs/1810.08392 Impact of corpora quality on neural machine translation. *CoRR*, abs/1810.08392.

Nick Rossenbach, Jan Rosendahl, Yunsu Kim, Miguel Graça, Aman Gokrani, and Hermann Ney. 2018. The RWTH aachen university filtering system for the WMT 2018 parallel corpus filtering task. In *Proceedings of the Third Conference on Machine Translation: Shared Task Papers*, Belgium, Brussels. Association for Computational Linguistics.

Víctor M. Sánchez-Cartagena, Marta Bañón, Sergio Ortiz-Rojas, and Gema Ramírez. 2018. Prompsit's submission to WMT 2018 Parallel Corpus Filtering shared task. In *Proceedings of the Third Conference on Machine Translation: Shared Task Papers*, Belgium, Brussels.

Holger Schwenk, Vishrav Chaudhary, Shuo Sun, Hongyu Gong, and Francisco Guzmán. 2021. WikiMatrix: Mining 135M parallel sentences in 1620 language pairs from Wikipedia. In *Proceedings of the 16th Conference of the European Chapter of the Association for Computational Linguistics: Main Volume*, Online. Association for Computational Linguistics.

Rico Sennrich, Barry Haddow, and Alexandra Birch. 2016. Neural machine translation of rare words with subword units. In *Proceedings of the 54th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 1715–1725, Berlin, Germany. Association for Computational Linguistics.

Haukur Barri Símonarson, Vésteinn Snæbjarnarson, Pétur Orri Ragnarson, Haukur Jónsson, and Vilhjalmur Thorsteinsson. 2021. Miðeind's WMT 2021 submission. In *Proceedings of the Sixth Conference on Machine Translation*, Online. Association for Computational Linguistics.

Steinþór Steingrímsson and Starkaður Barkarson. ParIce: English-icelandic parallel corpus (21.10).

Steinþór Steingrímsson, Sigrún Helgadóttir, Eiríkur Rögnvaldsson, Starkaður Barkarson, and Jón Guðnason. 2018. Risamálheild: A Very Large Icelandic Text Corpus. In *Proceedings of the Eleventh International Conference on Language Resources and Evaluation*, LREC 2018, Miyazaki, Japan.

Steinþór Steingrímsson, Pintu Lohar, Hrafn Loftsson, and Andy Way. 2021. Effective bitext extraction from comparable corpora using a combination of three different approaches. In *Proceedings of the 14th Workshop on Building and Using Comparable Corpora (BUCC 2021)*, pages 8–17, Online (Virtual Mode). INCOMA Ltd.

Steinþór Steingrímsson, Luke O'Brien, Finnur Ingimundarson, Hrafn Loftsson, and Andy Way. 2022. Compiling a highly accurate bilingual lexicon by combining different approaches. In *Proceedings of Globalex Workshop on Linked Lexicography within the 13th Language Resources and Evaluation Conference*, Marseille, France. European Language Resources Association.

Jannis Vamvas and Rico Sennrich. 2022. Nmtscore: A multilingual analysis of translation-based text similarity measures.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Ł ukasz Kaiser, and Illia Polosukhin. 2017. Attention is All you Need. In *Advances in Neural Information Processing Systems 30*, Long Beach, California.

Yinfei Yang, Gustavo Hernández Ábrego, Steve Yuan, Mandy Guo, Qinlan Shen, Daniel Matthew Cer, Yun-Hsuan Sung, Brian Strope, and Ray Kurzweil. 2019. Improving multilingual sentence embedding using bi-directional dual encoder with additive margin softmax. *ArXiv*, abs/1902.08564.

Mirza Yusuf, Praatibh Surana, Gauri Gupta, and Krithika Ramesh. 2021. Curb Your Carbon Emissions: Benchmarking Carbon Emissions in Machine Translation. *ArXiv*, abs/2109.12584.

Jaume Zaragoza-Bernabeu, Gema Ramírez-Sánchez, Marta Bañón, and Sergio Ortiz Rojas. 2022. Bicleaner ai: Bicleaner goes neural. In *Proceedings of the Language Resources and Evaluation Conference*, pages 824–831, Marseille, France. European Language Resources Association.