Sparsely Connected Layers for Financial Tabular Data

Abstract

While neural networks are the norm for unstructured data such as images and texts, their performance often lags behind more traditional machine learning models such as gradient boosted trees for tabular data, evidenced by academic studies, industrial practices, and Kaggle competitions. In particular, there is no easy way to increase the number of layers for neural networks applied on tabular data, which has been a key reason in their success on unstructured data. Deeper fully connected networks also suffer from the vanishing gradient problem, and convolutional layers and transformers are not directly applicable to tabular data in general. Special constructs such as skip layers and attentions have been adapted to tabular data models with limited success. In this paper, we show that for the consumer financial tabular data, while standard 2-layer neural networks fall behind gradient boosted trees as usual, sparsely connected layers can increase the network depth and reliably outperform gradient boosted trees. The superior performance seems to come from the ability of the sparse layers to reduce correlations from the input data, which is a common problem in high-dimensional tabular data. Therefore we are hopeful the method could be applicable to other domains with similar challenges.

1 Introduction

The past decade has witnessed the rapid progress of neural networks on unstructured data such as images and text, much of which are due to special network constructs that enable very deep architectures without suffering from the vanishing gradient problem. In particular, convolutional neural networks have dominated almost all vision tasks [15], and more recently transformers have dominated the language models [23].

On the other hand, while tabular data is arguably much simpler and easier to process, there is no generic deep neural architecture available for it. Standard 2-layer neural nets often fall behind modern gradient boosted tree models (GBDT) such as XGBoost [5], LightGBM [13], and CatBoost [18]. For example, the 2022 Kaggle competitions have been dominated by GBDTs, winning 7 out of the 10 challenges [7]. Another survey paper using academic datasets concluded that decision tree models are still state of the art, winning on 7 out of the 9 datasets [4].

Motivated by the performance gap, there is a significant amount of research on deep neural networks for tabular data, which can be largely divided into three categories. First, we can combine neural networks and tree-based methods. For example, [16] proposes a network structure that imitates a binary decision tree, while [20] argues that an ensemble of the two approaches works better. Second, the wide and deep network architecture [6] can be applicable for some datasets. Taking a step further, DeepFM [10] introduces a learned Factorization Machine [19] into a deep network. Finally, there is recent interest in using the attention mechanism to learn higher order interaction between features. TabNet [2] uses sequential attention for implicit feature selection, and each layer places importance on only a few features. Another method performs both inter-sample and inter-feature attention [21].

While working with our industrial scale financial tabular data, we also discover that XGBoost significantly outperforms the standard 2-layer neural networks. Adding additional fully connected layers hurts the performance even more. Other more sophisticated network architectures have difficulty meeting the baseline performance in our problem setting. However, a simple sparsely connected layer that groups the input data in meaningful ways surprisingly beats XGBoost by a reliable margin. Additional analysis shows that our high dimensional financial data, not surprisingly, has highly correlated features. The sparsely connected layer seems to be especially effective in eliminating the correlation automatically. Thus, we believe that this method could be applicable in other domains with high-dimensional tabular data.

2 Our Method

2.1 Financial tabular data

Machine learning is widely applied in the consumer finance domain, for example, propensity models to acquire customers and risk models for underwriting. A person's financial history is without doubt very useful in predicting their future financial behaviors. Therefore there are many data providers that featurize and standardize personal financial data for model-building purposes [9]. Example attributes of these datasets include how many inquiries in the past six months, how many credit cards are open, the maximal balance of the past three months, etc.

Because these datasets are designed for general purposes, there are many thousands of attributes that cover many financial industries, a range of time periods, and a variety of behaviors. For example, loans are grouped into auto, personal, mortgage, student, retail, etc, and inquiry attributes include the number of inquiries in 14-day, 1-month, 3-month, 6-month, etc. Derogatory behaviors include delinquency, charge-off, collection, bankruptcy, etc.

2.2 The data correlation problem

These thousands of financial attributes are usually correlated. For example, the 3-month inquiry count is a subset of the 6-month count, and charge-off accounts are often preceded by delinquency.

It is well known that correlated features can dramatically impair a model's performance, more so in neural networks than GBDTs because correlations incorrectly amplify the gradients while decision trees can ignore redundant features altogether. This is likely a big reason why GBDTs often outperform neural networks, as data correlation is very common in high-dimensional tabular data.

However, reducing data correlation is nontrivial. First of all, with large scale high-dimensional data, the correlation among attributes almost always has a smooth distribution so there is no clear cutoff threshold for feature removal, meaning correlation will always exist no matter how many features we remove. Second, with sparse labels, any subtle difference between two correlated features can have non-negligible impact on model performance. Finally, as business objectives or macro conditions change, feature reduction analysis has to be repeated, which is tedious and error prone. Ideally we would like the model to select features and eliminate correlations automatically.

2.3 Our model architecture

Figure 1: Our proposed model architecture.

Given information about correlated features, we can put those features beside each other in the neural network's input layer. The first layer of this model consists of small MLPs for each input feature

group whose output size is G, a hyperparameter we tune. We call this a sparse layer since only the group's neurons are connected in it. Figure 1 shows a visualization of our proposed model, with the special case that we only have 2 hidden layers. In practice, any number of fully connected hidden layers is possible, as this model becomes a regular MLP after the input layer.

3   Experiments

We evaluate all models on a proprietary dataset, and attempt to model consumer propensity. The dataset consists of tens of millions of samples and thousands of features, with a positive sample ratio in the single digits. For all neural networks, numerical features were scaled to 0 mean and 1 variance and categorical features were one-hot encoded. Missing values were mean imputed. Error bars were not reported due to the computational complexity of retraining models with datasets of this size. Experiments ran on a 30 GB RAM AWS ECS g2.2xlarge instance. Training time took an average of 2 hours per model.

Figure 2: Various models' validation AUCPR on proprietary classification dataset.

3.1   Results

To evaluate our model's goodness, we compare our model to many existing models that are commonly used in tabular data applications, such as GBDT methods (XGBoost, LightGBM, and CatBoost) [5, 13, 18], and specialized neural networks (TabNet, DeepFM, and AutoInt) [2, 10, 22]. Open source implementations were used for all of these models, and can be found here [8, 24, 5, 17, 25].

We can immediately see from Figure 2 that our approach, beats all the other methods compared. It is worth noting that both XGBoost and LightGBM perform quite well when compared to the other models, which continues to demonstrate the strength of GBDT models on tabular data.

We conduct ablation study to investigate the effect of increasing the number of layers of the model. Figure 2 shows the performance of our model compared to a (fully connected) 2- and 3-layer MLP. In the spirit of fairness, our model's second hidden layer has the same size as the first and second hidden layers in the 2- and 3-layer MLPs. The first hidden layer of the 3-layer MLP has the same number of neurons as the sparse layer in our model. Simply increasing the number of hidden layers clearly lowers the model's performance, yet our specialized architecture, even though it has the same number of neurons as the 3-layer MLP, is the clear winner here too. This demonstrates that our model's superior performance doesn't only come from widening/deepening the neural network.

3.2   The effect of the sparse layer

Figure 3 shows how the sparsely connected layer in our model removes the correlation in the input data. The left figure shows one input group, where there are lots of highly correlated feature clusters. The right figure shows that after the sparse layer, there is no visible correlation. The middle figure shows that there is still some leftover correlation when using fully connected layers, demonstrating that regular neural networks cannot remove the correlation as well as our model can.

Figure 3: The covariance matrices of the input features, output of a 3-layer MLP first hidden layer, and the output of the sparse layer in our model. Note activation here refers to the value computed after applying the activation function.

This also shows that grouping highly correlated features together is important, which is easy in our case as the financial features are naturally grouped by financial industries, e.g., automobile, mortgage, personal loan, etc. We also tried to group features in other reasonable fashions, and got similar results. Grouping features randomly drops the performance significantly, from 0.1794 to 0.1730.

The sparsely connected layer acts in a similar fashion as the embedding layer, which is also why we choose a fixed number G of output for each group, regardless of the group input size. Similarly to embedding, our sparsely connected layer can significantly reduce network complexity and the number of model parameters.

4 Related Works

Tabular data presents unique challenges for deep learning, as traditional neural networks have struggled to outperform GBDT methods like XGBoost, LightGBM, and CatBoost [5, 13, 18]. These tree-based methods excel at handling tabular data due to their ability to capture complex feature interactions and manage missing values. Despite their success, tree models do not naturally incorporate domain knowledge, which can be a limitation in scenarios where feature relationships are known but not explicitly provided to the model.

Recent efforts have explored adapting neural networks to work more effectively with tabular data. TabNet [2] leverages attention mechanisms to dynamically focus on relevant features. DeepFM [10] and AutoInt [22] attempt to model feature interactions explicitly, with the former combining factorization machines with deep neural networks to capture both first- and second-order interactions, and the latter using self-attention mechanisms to model higher-order feature interactions without manual engineering. While Group-Connected Multilayer Perceptron Networks (GMLP) [12] also focuses on exploiting feature groupings, they do so by dynamically learning groups during the training phase using techniques like temperature annealing and entropy loss to encourage sparsity. These models, however, rely on the network to discover feature groupings and relationships during training, rather than encoding domain-specific knowledge directly into the model.

Additionally, Sparsely-Connected Neural Networks (SCNN) [1] reduce the number of connections in neural networks to save memory and energy consumption while maintaining competitive accuracy. SCNN uses stochastic binary masks to generate sparsity. Our model shares the goal of introducing sparsity but differs in that its sparsity is driven by the natural structure of the data — specifically, by grouping related features — rather than relying on random mask generation or pruning.

5 Conclusion

Sparsely connected layers represent a new approach to dealing with high-dimensional tabular data by explicitly incorporating domain-driven feature groupings into the neural network architecture. This positions it as a simple yet effective solution compared to more complicated neural network architectures for tabular data. Since large-scale high-dimensional tabular data often exhibits similar behaviours as our consumer financial data, we hope to see more use cases of our proposed solution.

References

[1] Arash Ardakani, Carlo Condo, and Warren J. Gross. Sparsely-connected neural networks: Towards efficient vlsi implementation of deep neural networks, 2017. URL `https://arxiv.org/abs/1611.01427`.

[2] Sercan O. Arik and Tomas Pfister. Tabnet: Attentive interpretable tabular learning. In *Proceedings of the AAAI conference on artificial intelligence*, volume 35, pages 6679–6687, 2021.

[3] Jimmy Lei Ba, Jamie Ryan Kiros, and Geoffrey E. Hinton. Layer normalization, 2016. URL `https://arxiv.org/abs/1607.06450`.

[4] Vadim Borisov, Tobias Leemann, Kathrin Seßler, Johannes Haug, Martin Pawelczyk, and Gjergji Kasneci. Deep neural networks and tabular data: A survey. *IEEE Transactions on Neural Networks and Learning Systems*, 35(6):7499–7519, June 2024. ISSN 2162-2388. doi: 10.1109/tnnls.2022.3229161. URL `http://dx.doi.org/10.1109/TNNLS.2022.3229161`.

[5] Tianqi Chen and Carlos Guestrin. Xgboost: A scalable tree boosting system. In *Proceedings of the 22nd ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*, volume 11 of *KDD '16*, page 785–794. ACM, August 2016. doi: 10.1145/2939672.2939785. URL `http://dx.doi.org/10.1145/2939672.2939785`.

[6] Heng-Tze Cheng, Levent Koc, Jeremiah Harmsen, Tal Shaked, Tushar Chandra, Hrishi Aradhye, Glen Anderson, Greg Corrado, Wei Chai, Mustafa Ispir, et al. Wide & deep learning for recommender systems. In *Proceedings of the 1st workshop on deep learning for recommender systems*, pages 7–10, 2016.

[7] ML Contests. Tabular Data Competitions - Winning Strategies. `https://mlcontests.com/tabular-data/`, March 2023. Accessed 2 September, 2024.

[8] Dreamquark-AI. Tabnet, 2023. URL `https://github.com/dreamquark-ai/tabnet`.

[9] Experian. Premier Attributes. `https://www.experian.com/business/products/premier-attributes`, 2024. Accessed 2 September, 2024.

[10] Huifeng Guo, Ruiming Tang, Yunming Ye, Zhenguo Li, and Xiuqiang He. Deepfm: A factorization-machine based neural network for ctr prediction, 2017. URL `https://arxiv.org/abs/1703.04247`.

[11] Sergey Ioffe and Christian Szegedy. Batch normalization: Accelerating deep network training by reducing internal covariate shift, 2015. URL `https://arxiv.org/abs/1502.03167`.

[12] Mohammad Kachuee, Sajad Darabi, Shayan Fazeli, and Majid Sarrafzadeh. Group-connected multilayer perceptron networks, 2020. URL `https://arxiv.org/abs/1912.09600`.

[13] Guolin Ke, Qi Meng, Thomas Finley, Taifeng Wang, Wei Chen, Weidong Ma, Qiwei Ye, and Tie-Yan Liu. Lightgbm: A highly efficient gradient boosting decision tree. In I. Guyon, U. Von Luxburg, S. Bengio, H. Wallach, R. Fergus, S. Vishwanathan, and R. Garnett, editors, *Advances in Neural Information Processing Systems*, volume 30. Curran Associates, Inc., 2017. URL `https://proceedings.neurips.cc/paper_files/paper/2017/file/6449f44a102fde848669bdd9eb6b76fa-Paper.pdf`.

[14] Guolin Ke, Jia Zhang, Zhenhui Xu, Jiang Bian, and Tie-Yan Liu. TabNN: A universal neural network solution for tabular data, 2019. URL `https://openreview.net/forum?id=r1eJssCqY7`.

[15] Y. LeCun, B. Boser, J. S. Denker, D. Henderson, R. E. Howard, W. Hubbard, and L. D. Jackel. Backpropagation applied to handwritten zip code recognition. *Neural Computation*, 1(4): 541–551, 1989. doi: 10.1162/neco.1989.1.4.541.

[16] Haoran Luo, Fan Cheng, Heng Yu, and Yuqi Yi. Sdtr: Soft decision tree regressor for tabular data. *IEEE Access*, 9:55999–56011, 2021.

[17] Microsoft. Lightgbm, 2024. URL `https://github.com/microsoft/LightGBM`.

[18] Liudmila Prokhorenkova, Gleb Gusev, Aleksandr Vorobev, Anna Veronika Dorogush, and Andrey Gulin. Catboost: unbiased boosting with categorical features, 2019. URL `https://arxiv.org/abs/1706.09516`.

[19] Steffen Rendle. Factorization machines. In *2010 IEEE International conference on data mining*, pages 995–1000. IEEE, 2010.

[20] Ravid Shwartz-Ziv and Amitai Armon. Tabular data: Deep learning is not all you need. *Information Fusion*, 81:84–90, 2022.

[21] Gowthami Somepalli, Micah Goldblum, Avi Schwarzschild, C Bayan Bruss, and Tom Goldstein. Saint: Improved neural networks for tabular data via row attention and contrastive pre-training. *arXiv preprint arXiv:2106.01342*, 2021.

[22] Weiping Song, Chence Shi, Zhiping Xiao, Zhijian Duan, Yewen Xu, Ming Zhang, and Jian Tang. Autoint: Automatic feature interaction learning via self-attentive neural networks. In *Proceedings of the 28th ACM International Conference on Information and Knowledge Management*, CIKM '19. ACM, November 2019. doi: 10.1145/3357384.3357925. URL `http://dx.doi.org/10.1145/3357384.3357925`.

[23] Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. In *Advances in Neural Information Processing Systems*, volume 30, 2017. URL `https://proceedings.neurips.cc/paper_files/paper/2017/file/3f5ee243547dee91fbd053c1c4a845aa-Paper.pdf`.

[24] Shen Weichen, Zan Shuxun, Wang Ze, Zhang Wutong, Zhang Yuefeng, Huo Junyi, Zeng Kai, Chen K, Cheng Weiyu, and Tang. Deepctr-torch, 2022. URL `https://github.com/shenweichen/DeepCTR-Torch`.

[25] Yandex. Catboost, 2024. URL `https://github.com/catboost/catboost`.