FSL: FEDERATED SUPERMASK LEARNING

ABSTRACT

Federated learning (FL) allows multiple clients with (private) data to collaboratively train a common machine learning model without sharing their private training data. In-the-wild deployment of FL faces two major hurdles: robustness to poisoning attacks and communication efficiency. To address these concurrently, we propose *Federated Supermask Learning* (FSL). FSL server trains a global *subnetwork* within a *randomly initialized* neural network by aggregating local subnetworks of all collaborating clients. FSL clients share local subnetworks in the form of rankings of network edges; more useful edges have higher ranks. By sharing integer rankings, instead of float weights, FSL restricts the space available to craft effective poisoning updates, and by sharing subnetworks, FSL reduces the communication cost of training. We show theoretically and empirically that FSL is robust by design and also significantly communication efficient; all this without compromising clients' privacy. Our experiments demonstrate the superiority of FSL in real-world FL settings; in particular, **(1)** FSL achieves similar performances as state-of-the-art FedAvg with significantly lower communication costs: for CIFAR10, FSL achieves same performance as Federated Averaging while reducing communication cost by $\sim 35\%$. **(2)** FSL is substantially more robust to poisoning attacks than state-of-the-art robust aggregation algorithms.

1 INTRODUCTION

Federated Learning (FL) is an emerging AI technology, where mutually untrusted *clients* (e.g., Android devices) collaborate to train a shared model, called the *global model*, without explicitly sharing their local training data. FL training involves a *server* (e.g., Google) which collects model updates from selected FL clients in each round of training, and uses them to update the global model. FL, although highly promising, faces multiple challenges (Kairouz et al., 2019; Li et al., 2020b) to its practical deployment, in particular, communication efficiency and robustness, which are the focus of our work. Privacy preservation is another major challenge to FL, but is orthogonal to our work.

We present **F**ederated **S**upermask **L**earning (FSL), a novel approach to perform FL while concurrently achieving the two goals of robustness and communication efficiency. FSL is built on a novel learning paradigm called *supermasks* (Zhou et al., 2019; Ramanujan et al., 2020), which allows it to reduce communication costs while achieving significantly higher robustness. Specifically, in FSL, clients collaborate to find a *subnetwork* within a *randomly initialized* neural network which we call the *supernetwork* (this is in contrast to conventional FL where clients collaborate to *train* a neural network). The goal of training in FSL is to collaboratively identify a supermask, which is a binary mask of 1's and 0's, that is superimposed on the random neural network (the supernetwork) to obtain the final subnetwork. The subnetwork is then used for downstream tasks, e.g., image classification, hence it is equivalent to the global model in conventional FL. Note that in entire FSL training, weights of the supernetwork *do not* change.

More specifically, each FSL client computes the importance of the edges of the supernetwork based on their local data. The importance of the edges is represented as a ranking vector. Each FSL client will use the *edge popup* algorithm (Ramanujan et al., 2020) and their data to compute their local rankings (the edge popup algorithm aims at learning which edges in a supernetwork are more important over the other edges by minimizing the loss of the subnetwork on their local data). Each client then will send her local edge ranking to the server. Finally, the FSL server uses a novel *voting* mechanism to aggregate client rankings into a supermask, which represents which edges of the random neural network (the supernetwork) will form the global subnetwork.

Intuitions on FSL's robustness: In traditional FL algorithms, clients send large-dimension model updates $\in \mathbb{R}^d$ (real numbers) to the server, providing malicious clients a significant flexibility in fabricating malicious updates. By contrast, FSL clients merely share the rankings of the edges of the supernetwork, i.e., integers $\in [1, d]$, where d is the size of the supernetwork. Therefore, as we will show both theoretically and empirically, FSL provides robustness by design and reduces the impact of untargeted poisoning attacks. Furthermore, unlike most existing robust FL frameworks, FSL does not require any knowledge about the percentages of malicious clients.

Intuitions on FSL's communication efficiency: In FSL, the clients and the server communicate just the rankings of the edges in the supernetwork, i.e., a permutation of indices in $[1, d]$. Ranking vectors are generally significantly smaller than the global model. This, as we will show, significantly reduces the upload and download communication in FSL compared to Federated Averaging (FedAvg) (McMahan et al., 2017), where clients communicate model parameters, each of 32/64 bits.

Empirical results: We experiment with three datasets in real-world heterogeneous FL settings and show that: **(1)** FSL achieves similar performance (e.g., model accuracy) as state-of-the-art FedAvg but with significantly reduced communication costs: for CIFAR10, the accuracy and communication cost per client are 85.4% and 40.2MB for FedAvg, while 85.3% and 26.2MB for FSL. **(2)** FSL is highly robust to poisoning attacks as compared to state-of-the-art robust aggregation algorithms: from 85.4% in the benign setting, 10% malicious clients reduce the accuracy of FL to 56.3% and 58.8% with Trimmed-Mean (Xie et al., 2018; Yin et al., 2018) and Multi-Krum (Blanchard et al., 2017), respectively, while FSL's performance only decreases to 79.0%.

We also compare FSL with two communication reduction methods, SignSGD (Bernstein et al., 2019) and TopK (Alistarh et al., 2018a) and show that FSL produces comparable communication costs and model accuracies. For instance, on CIFAR10, FSL, SignSGD, and TopK achieve 85.3%, 79.1%, and 82.1% test accuracy, respectively, when the corresponding communication costs (download and upload) are 26.2MB, 20.73MB, and 30.79MB. On the other hand, FSL offers a significantly superior robustness. For instance, on CIFAR10, 10% (20%) malicious clients reduce the accuracy of SignSGD to 39.7% (10.0%), but FSL's accuracy decreases to only 79.0% (69.5%). TopK is incompatible with existing robust aggregation algorithms, hence uses Average aggregation and is as vulnerable as FedAvg, especially in the real-world heterogeneous settings.

2 RELATED WORKS

Supermask Learning: Modern neural networks have a very large number of parameters. These networks are generally overparameterized (Dauphin & Bengio, 2013; Denil et al., 2013), i.e., they have more parameters than they need to perform a particular task, e.g., classification. The *lottery ticket hypothesis* (Frankle & Carbin, 2019) states that a fully-trained neural network, i.e., *supernetwork*, contains sparse *subnetworks*, i.e., subsets of all neurons in supernetwork, which can be trained from scratch (i.e., by training randomly initialized weights of the subnetwork) and achieve performances close to the fully trained supernetwork. The lottery ticket hypothesis allows for massive reductions in the sizes of neural networks. (Ramanujan et al., 2020) offer a complementary conjecture that an overparameterized neural network with randomly initialized weights contains subnetworks which perform as good as the fully trained network.

Poisoning Attacks and Defenses for Federated Learning (FL): FL involves mutually untrusting clients. Hence, a *poisoning adversary* may own or compromise some of the FL clients, called *malicious clients*, with the goal of mounting a *targeted* or *untargeted* poisoning attack. In a targeted attack, the goal is to reduce the utility of the model on specific test inputs, while in the untargeted attack, the goal is to reduce the utility for all (or most) test inputs. It is shown (Blanchard et al., 2017) that even a single malicious client can mount an effective untargeted attack on FedAvg.

In order to make FL robust to the presence of such malicious clients, the literature has designed various *robust aggregation rules (AGR)* (Blanchard et al., 2017; Mhamdi et al., 2018; Yin et al., 2018), which aim to remove or attenuate the updates that are more likely to be malicious according to some criterion. For instance, Multi-krum (Blanchard et al., 2017) repeatedly removes updates that are far from the geometric median of all the updates, and Trimmed-mean (Xie et al., 2018; Yin et al., 2018) removes the largest and smallest values of each update dimension and calculates the mean of the remaining values. Unfortunately, these robust AGRs are not very effective in non-convex FL settings and multiple works have demonstrated strong targeted (Wang et al., 2020; Bhagoji et al., 2019) and untargeted attacks (Shejwalkar & Houmansadr, 2021; Fang et al., 2020) on them.

Communication Cost of FL: In many real-world applications of FL, it is essential to minimize the communication between FL server and clients. Especially in cross-device FL, the clients (e.g., mobile phones and wearable devices) have limited resources and communication can be a major bottleneck. There are two major types of communication reduction methods: (1) *Qunatization* methods reduce the resolution of (i.e., number of bits used to represent) each dimension of a client update. For instance, SignSGD (Bernstein et al., 2019) uses the sign (1 bit) of each dimension of model updates. (2) *Sparsification* methods propose to use only a subset of all the update dimensions. For instance, in TopK (Aji & Heafield, 2017; Alistarh et al., 2018a), only the largest K% update dimensions are sent to the server in each FL round. We note that, communication reduction methods primarily focus on and succeed at reducing upload communication (client $\rightarrow$ server), but they use the entire model in download communication (server $\rightarrow$ client).

3 PRELIMINARIES

3.1 FEDERATED LEARNING

In FL (McMahan et al., 2017; Kairouz et al., 2019; Konečný et al., 2016), N clients collaborate to train a global model without directly sharing their data. In round t, the service provider (server) selects n out of N total clients and sends them the most recent global model θ^t. Each client trains a local model for E local epochs on her data starting from the θ^t using stochastic gradient descent (SGD). Then the client send back the calculated gradients (∇_k for kth client) to the server. The server then aggregates the collected gradients and updates the global model for the next round. FL can be either cross-device or cross-silo (Kairouz et al., 2019). In cross-device FL, N is large (from few thousands to billions) and only a small fraction of clients is chosen in each FL training round, i.e., $n \ll N$. By contrast, in cross-silo FL, N is moderate (up to 100) and all clients are chosen in each round, i.e., $n = N$. In this work, we evaluate the performance of FSL and other FL baselines for cross-device FL under realistic production FL settings.

3.2 EDGE-POPUP ALGORITHM

The edge-popup (EP) algorithm (Ramanujan et al., 2020) is a novel optimization method to find supermasks within a large, randomly initialized neural network, i.e., a supernetwork, with performances close to the fully trained supernetwork. EP algorithm does not train the weights of the network, instead only decides the set of edges to keep and removes the rest of the edges (i.e., pop). Specifically, EP algorithm assigns a positive score to each of the edges in the supernetwork. On forward pass, it selects top k% edges with highest scores, where k is the percentage of the total number of edges in the supernetwork that will remain in the final subnetwork. On the backward pass, it updates the scores with the straight-through gradient estimator (Bengio et al., 2013). Algorithm 1 presents EP algorithm; we defer further details to Appendix D.

Algorithm 1 Edge-popup (EP) algorithm: it finds a subnetwork of size $k\%$ of the entire network θ

1: **Input:** number of local epochs E, training data D, initial weights θ^w and scores θ^s, sub-network size $k\%$, learning rate η
2: **for** $e \in [E]$ **do**
3:     $\mathcal{B} \leftarrow$ Split D in B batches
4:     **for** batch $b \in [B]$ **do**
5:         EP FORWARD $(\theta^w, \theta^s, k, b)$
6:         $\theta^s = \theta^s - \eta \nabla \ell(\theta^s; b)$
7:     **end for**
8: **end for**
9: **return** θ^s
10: **function** EP FORWARD$(\theta^w, \theta^s, k, b)$
11:     $m \leftarrow \text{sort}(\theta^s)$
12:     $t \leftarrow int((1 - k) * len(m))$
13:     $m[: t] = 0$
14:     $m[t :] = 1$
15:     $\theta^p = \theta^w \odot \mathbf{m}$
16:     **return** $\theta^p(b)$
17: **end function**

---

4 FEDERATED SUPERMASK LEARNING: DESIGN

In this section, we provide the design of our federated supermask learning (FSL) algorithm. FSL clients collaborate (without sharing their local data) to *find a subnetwork* within a randomly initialized, untrained neural network called the *supernetwork*. Algorithm 2 describes FSL's training. Training a global model in FSL means to first find a unanimous ranking of supernetwork edges and then use the subnetwork of the top ranked edges as the final output. We detail a round of FSL training and depict it in Figure 1, where we use a supernetwork with six edges $e_{i \in [0,5]}$ to demonstrate a

single FSL round and consider three clients $C_{j \in [1,3]}$ who aim to find a subnetwork of size k=50% of the original supernetwork.

Algorithm 2 Federated Supermask Learning (FSL)

1: **Input:** number of FL rounds T, number of local epochs E, number of selected users in each round n, seed SEED, learning rate η, subnetwork size k%
2: Server: Initialization
3: $\theta^s, \theta^w \leftarrow$ Initialize random scores and weights of global model θ using SEED
4: $R_g^1 \leftarrow$ ARGSORT(θ^s)   ▷ Sort the initial scores and obtain initial rankings
5: **for** $t \in [1, T]$ **do**
6:      $U \leftarrow$ set of n randomly selected clients out of N total clients
7:      **for** u in U **do**
8:          Clients: Calculating the ranks
9:          $\theta^s, \theta^w \leftarrow$ Initialize scores and weights using SEED
10:          $\theta^s[R_g^t] \leftarrow$ SORT(θ^s)   ▷ sort the scores based on the global ranking
11:          $S \leftarrow$ Edge-PopUp($E, D_u^{tr}, \theta^w, \theta^s, k, \eta$)   ▷ Client u uses Algorithm1 to train a supermask on its local training data
12:          $R_u^t \leftarrow$ ARGSORT(S)   ▷ Ranking of the client
13:      **end for**
14:      Server: Majority Vote
15:      $R_g^{t+1} \leftarrow$ VOTE($R_{u \in U}^t$)   ▷ Majority vote aggregation
16: **end for**
17: **function** VOTE($R_{\{u \in U\}}$):
18:      $V \leftarrow$ ARGSORT($R_{\{u \in U\}}$)
19:      $A \leftarrow$ SUM(V)
20:      **return** ARGSORT(A)
21: **end function**

4.1 SERVER: INITIALIZATION PHASE (ONLY FOR ROUND $t = 1$)

In the first round, the FSL server chooses a random seed SEED to generate initial random weights θ^w and scores θ^s for the global supernetwork θ; note that, θ^w, θ^s, and SEED remain constant during the entire FSL training. Next, the FSL server shares SEED with FSL clients, who can then locally reconstruct the initial weights θ^w and scores θ^s using SEED. Figure 1-① depicts this step.

Recall that, the goal of FSL training is to find the most important edges in θ^w without changing the weights. Unless specified otherwise, both server and clients use the Singed Kaiming Constant algorithm (Ramanujan et al., 2020) to generate random weights and the Kaiming Uniform algorithm (He et al., 2015) to generate random scores. However, in Appendix C.1, we also explore the impacts of different initialization algorithms on the performance of FSL. We use the same seed to initialize weights and scores.

At the beginning, the FSL server finds the global rankings of the initial random scores (Algorithm 2 line 4), i.e., $R_g^1 =$ ARGSORT(θ^s). We define *rankings of a vector* as the indices of elements of vector when the vector is sorted from low to high, which is computed using ARGSORT function (argsort).

4.2 CLIENTS: CALCULATING THE RANKS (FOR EACH ROUND t)

In the t^{th} round, FSL server randomly selects n clients among total N clients, and shares the global rankings R_g^t with them. Each of the selected n clients locally reconstructs the weights θ^w's and scores θ^s's using SEED (Algorithm 2 line 9). Then, each FSL client reorders the random scores based on the global rankings, R_g^t (Algorithm 2 line 10); we depict this in Figure 1-②a.

Next, each of the n clients uses reordered θ^s and finds a subnetwork within θ^w using Algorithm 1; to find a subnetwork, they use their local data and E local epochs (Algorithm 2 line 11). Note that, each iteration of Algorithm 1 updates the scores θ^s. Then client u computes their local rankings R_u^t using the final updated scores (S) and ARGSORT(.), and sends R_u^t to the server. Figure 1-②a shows how each of the selected n clients reorders the random scores using global rankings. For instance, the initial global rankings for this round are $R_g^t = [2, 3, 0, 5, 1, 4]$, meaning that edge e_4 should get the highest score ($s_4 = 1.2$), and edge e_2 should get the lowest score ($s_2 = 0.2$).

Figure 1: A single FSL round with three clients and network of 6 edges.

Figure 1-②b shows, for each client, the scores and rankings they obtained after finding their local subnetwork. For example, rankings of client C_1 are $R_1^t = [4, 0, 2, 3, 5, 1]$, i.e., e_4 is the least important and e_1 is the most important edge for C_1. Considering desired subnetwork size to be 50%, C_1 uses edges {3,5,1} in their final subnetwork.

4.3 Server: Majority Vote (for each round t)

The server receives all the local rankings of the selected n clients, i.e., $R_{\{u \in U\}}^t$. Then, it performs a majority vote over all the local rankings using VOTE(.) function. Note that, for client u, the index i represents the importance of the edge $R_u^t[i]$ for C_u. For instance, in Figure 1-②b, rankings of C_1 are $R_1^t = [4, 0, 2, 3, 5, 1]$, hence the edge e_4 at index=0 is the least important edge for C_1, while the edge e_1 at index=5 is the most important edge. Consequently, VOTE(.) function assigns reputation=0 to edge e_4, reputation=1 to e_0, reputation=2 to e_2, and so on. In other words, for rankings R_u^t of C_u and edge e_i, VOTE(.) computes the reputation of e_i as its index in R_u^t. Finally, VOTE(.) computes the total reputation of e_i as the sum of reputations from each of the local rankings. In Figure 1-②b, reputations of e_0 are 1 in R_1^t, 1 in R_2^t, and 0 in R_3^t, hence, the total reputation of e_0 is 2. We depict this in Figure 1-③; here, the final total reputations for edges $e_{\{i \in [0,5]\}}$ are $A = [2, 12, 3, 11, 8, 9]$. Finally, the server computes global rankings R_g^{t+1} to use for round $t + 1$ by sorting the final total reputations of all edges, i.e., $R_g^{t+1} = \text{ARGSORT}(A)$.

Note that, *all FSL operations that involve sorting, reordering, and voting are performed in a layer-wise manner*. For instance, the server computes global rankings R_g^t in round t for each layer separately, and consequently, the clients selected in round t reorder their local randomly generated scores θ^s for each layer separately.

5 Federated Supermask Learning: Salient Features

In this section, we discuss the two salient features of FSL that are instrumental for any distributed learning algorithm to be practical: *robustness to poisoning attacks* and *communication efficiency*.

5.1 Robustness of FSL to Poisoning Attacks

FSL is a distributed learning algorithm with mutually untrusting clients. Hence, a *poisoning adversary* may own or compromise some of FSL clients, called *malicious clients*, and mount a *targeted* or *untargeted* poisoning attack. In our work, we consider the untargeted attacks as they are more

severe than targeted attacks and can cause denial-of-service for all collaborating clients (Shejwalkar et al., 2021) and show that FSL is secure against such poisoning attacks by design.

Intuition on FSL's robustness: Existing FL algorithms, including robust FL algorithms, are shown to be vulnerable to targeted and untargeted poisoning attacks (Shejwalkar et al., 2021) where malicious clients corrupt the global model by sharing malicious model updates. One of the key reasons behind the susceptibility of existing algorithms is that their model updates can have arbitrary values. For instance, to manipulate vanilla FedAvg, malicious clients send very large updates (Blanchard et al., 2017), and to manipulate Multi-krum and Trimmed-mean, (Fang et al., 2020; Shejwalkar & Houmansadr, 2021) propose to perturb a benign update in a specific malicious direction. On the other hand, in FSL, clients must send a permutation of indices $\in [1, n_\ell]$ for each layer. Hence, FSL significantly reduces the space of the possible malicious updates that an adversary can craft. Majority voting in FSL further reduces the chances of successful attack. Intuitively, this makes FSL design robust to poisoning attacks. Below, we make this intuition more concrete.

The worst-case untargeted poisoning attack on FSL: Here, the poisoning adversary aims to reduce the accuracy of the final global FSL subnetwork on most test inputs. To achieve this, the adversary should replace the high ranked edges with low ranked edges in the final subnetwork. For the worst-case analysis of FSL, we assume a very strong adversary (i.e., threat model): 1) each of the malicious clients has some data from benign distribution; 2) malicious clients know the entire FSL algorithm and its parameters; 3) malicious clients can collude. Under this threat model we design a worst case attack on FSL (Algorithm 3 in Appendix A), which executes as follows: First, all malicious clients compute rankings on their benign data and use VOTE(.) algorithm to compute an aggregate rankings. Finally, each of the malicious clients uses the reverse of the aggregate rankings to share with the FSL server in given round.

Now we justify why the attack in Algorithm 3 is the worst case attack on FSL for the strong threat model we consider. Note that, FSL aggregation, i.e., VOTE(.), computes the reputations using clients' rankings and sums the reputations of each network edge. Therefore, the strongest poisoning attack would want to reduce the reputation of good edges. This can be achieved following the aforementioned procedure of Algorithm 3 to reverse the rankings computed using benign data.

Theoretical analysis of robustness of FSL algorithm:
In this section, we prove an upper bound on the failure probability of robustness of FSL, i.e., the probability that a good edge will be removed from the final subnetwork when malicious clients mount the worst case attack.

Following the work of Bernstein et al. (2019), we make two assumptions in order to facilitate a concrete robustness analysis of FSL: a) each malicious client has access only to its own data, and b) we consider a simpler VOTE(.) function, where the FSL server puts an edge e_i in the final subnetwork if more than half of the clients have e_i (a good edge) in their local subnetworks. In other words, the rankings that each client sends to the server is just a bit mask showing that each edge should or should not be in the final subnetwork. The server makes a majority vote on the bit masks, and if an edge has more than half votes, it will be in the global subnetwork. Our VOTE(.) mecha-

Figure 2: Upper bound on the failure probability of VOTE(.) function in FSL.

nism has more strict robustness criterion, as it uses more nuanced reputations of edges instead of bit masks. Hence, the upper bound on failure probability in this section also applies to the FSL VOTE(.) function.

The probability that our voting system fails is the probability that more than half of the votes do not include e_i in their subnetworks. The upper bound on the probability of failure would be $1/2\sqrt{\frac{np(1-p)}{(n(p+\alpha(1-2p)-1/2))^2}}$, where n is the number of clients being processed, p shows the probability that a benign client puts e_i in their top ranks, and α is the fraction of malicious clients. Due to space limitations, we defer the detailed proof to Appendix A.2. Figure 2 shows the upper bound on the failure of VOTE(.) for different values of α and p. We note that, the higher the probability p, the higher the robustness of FSL.

5.2 FSL's Communication Costs

In FL, and especially in the cross-device setting, clients have limited communication bandwidth. Hence, FL algorithms must be communication efficient. We discuss here the communication cost of FSL algorithm. In the first round, the FSL server only sends one seed of 32 bits to all the FSL clients, so they can construct the random weights (θ^w) and scores (θ^s). In a round t, each of selected FSL clients receives the global rankings R_g^t and sends back their local rankings R_u^t. The rankings are a permutation of the indices of the edges in each layer, i.e., of $[0, n_\ell - 1] \forall \ell \in [L]$ where L is the number of layers and n_ℓ is the number of parameters in ℓth layer.

We use the naive approach to communicate layer-wise rankings, where each FSL client exchanges a total of $\sum_{\ell \in [L]} n_\ell \times \log(n_\ell)$ bits. Because, for the layer ℓ, the client receives and sends n_ℓ ranks where each one is encoded with $\log(n_\ell)$ bits. On the other hand, a client exchanges $\sum_{\ell \in [L]} n_\ell \times 32$ bits in FedAvg, when 32 bits are used to represent each of n_ℓ weights in layer ℓ. In Appendix E, we compare theoretical communication costs of various FL algorithms.

Sparse-FSL: Here, we propose Sparse-FSL, a simple extension of FSL to further reduce the communication cost. In Sparse-FLS, a client sends only the most important ranks of their local rankings to the server for aggregation. For instance, in Figure 1, client C_1 sends $R_1^t = [4, 0, 2, 3, 5, 1]$ in case of FSL. But in sparse-FSL, with sparsity set to 50%, client C_1 sends just the top 3 rankings, i.e., sends $R_1'^t = [3, 5, 1]$. For each client, the sparse-FSL server assumes 0 reputation for all of the edges not included in the client's rankings, i.e., in Figure 1, sparse-FSL server will assign reputation=0 for edges e_4, e_0, and e_2. Then the server uses VOTE(.) to compute total reputations of all edges and then sort them to obtain the final aggregate global rankings, i.e., R_g^{t+1}, to use for subsequent rounds. We observe in out experiments, that sparse-FSL performs very close to FSL, even with sparsity as low as 10%, while also significantly reducing the communication cost. Due to space limitation, we defer the communication cost comparison of FSL with FedAvg, SingSGD, and LotteryFL (Li et al., 2020a) to Appendix E.

6 Experiments

In this section, we investigate the utility, robustness, and communication cost of our FSL framework. We use MNIST, CIFAR10, and FEMNIST data and distribute them in non-iid fashion among 1000, 1000, and 3400 clients respectively. We report the mean of all clients' test accuracies in our experiments. We provide further details of experimental setup in Appendix B. In addition to FSL, we also evaluate Sparse-FSL in different settings. We use SFSL top x% to denote a Sparse-FSL clients who sends top x% of ranks in each round.

6.1 Communication Cost Analysis

In FSL, both clients and server communicate just the edge ranks instead of weight parameters. Thus, FSL reduces both upload and download communication cost. Table 1 illustrates the utility, i.e., the accuracy on test data, and communication cost of FSL and state-of-the-art quantization, i.e., SignSGD (Bernstein et al., 2019), and sparsification, i.e., TopK (Alistarh et al., 2018b; Aji & Heafield, 2017) communication-reduction methods.

FSL versus SignSGD: We note that, FSL is significantly more accurate than SignSGD. For instance, on CIFAR10, distributed non-iid among 1000 clients, FSL achieves 85.3% while SignSGD achieves 79.1% , or on FEMNIST, FSL achieves 84.2% while SignSGD achieves 79.3%. This is because, FSL clients send more nuanced information via rankings of their subnetworks compared to SignSGD, where clients just send the signs of their model updates.

SignSGD in FL reduces only the upload communication, but for efficiency reasons, the server sends all of the weight parameters (each of 32 bits) to the newly selected clients. Hence, SignSGD has very efficient upload communication, but very inefficient download communication. For instance, on CIFAR10, for both upload and download, FSL achieves 13.1MB each while SignSGD achieves 0.63MB and 20.1MB, respectively.

FSL versus TopK: We compare FSL with TopK with $K \in \{10, 50\}$%. FSL is more accurate than Topk for MNIST and CIFAR10: on CIFAR10, FSL accuracy is 85.3%, while TopK accuracies

Table 1: Comparing the utility (test accuracy) and communication cost of FedAvg, FSL (in **bold**), SignSGD and, TopK and Sparse-FSL (SFSL) with different percentages of sparsity (in **bold**).

Dataset	Algorithm	Accuracy (STD)	Upload (MB)	Download (MB)
MNIST + LeNet 1000 clients	FedAvg	98.8 (3.1)	6.20	6.20
	FSL	**98.8 (3.2)**	**4.05**	**4.05**
	SFSL Top 50%	**98.2 (3.8)**	**2.03**	**4.05**
	SFSL Top 10%	**89.5 (9.2)**	**0.40**	**4.05**
	SignSGD	97.2 (4.6)	0.19	6.20
	TopK 50%	98.8 (3.2)	3.29	6.20
	TopK 10%	98.7 (3.2)	0.81	6.20
CIFAR10 + Conv8 1000 clients	FedAvg	85.4 (11.2)	20.1	20.1
	FSL	**85.3 (11.3)**	**13.1**	**13.1**
	SFSL Top 50%	**77.6 (13.0)**	**6.5**	**13.1**
	SFSL Top 10%	**27.5 (14.4)**	**1.3**	**13.1**
	SignSGD	79.1 (13.6)	0.63	20.1
	TopK 50%	82.1 (11.8)	10.69	20.1
	TopK 10%	77.8 (13.0)	2.64	20.1
FEMNIST + LeNet 3400 clients	FedAvg	85.8 (10.2)	6.23	6.23
	FSL	**84.2 (10.7)**	**4.06**	**4.06**
	SFSL Top 50%	**75.2 (12.7)**	**2.03**	**4.06**
	SFSL Top 10%	**59.2 (15.0)**	**0.40**	**4.06**
	SignSGD	79.3 (12.4)	0.19	6.23
	TopK 50%	85.7 (9.9)	3.31	6.23
	TopK 10%	85.5 (10.0)	0.81	6.23

are 82.1% and 77.8% with K=50% and K=10%, respectively. Similar to SignSGD, Topk is more efficiently reduces upload cost, but has very high download communication cost. Therefore, the combined upload and download communication cost per client per round is 26.2MB for FSL and 30.79MB for TopK with K=50%, and TopK still has worse performance.

Communication cost reduction due to Sparse-FSL (SFSL): We now evaluate SFSL explained in Section 5.2. In SFSL with top 50% ranks, clients send the top 50% of their ranks to the server, which reduces the bandwidth consumption by half. We note from Table 1 that, by sending fewer ranks, SFSL reduces both upload an download communication at a small cost of performance. For instance, on CIFAR10, SFLS with top 50% reduces the communication by 50% at the cost reducing accuracy from 85.4% to 77.6%.

6.2 SECURITY ANALYSIS

We compare FSL with state-of-the-art robust aggregation rules (AGRs): Mkrum (Blanchard et al., 2017), and Trimmed-mean (Xie et al., 2018; Yin et al., 2018). Table 2 gives the performances of robust AGRs, SignSGD, and FSL with different percentages of malicious clients. Here, we make a rather impractical assumption in favor of the robust AGRs: we assume that the server knows the exact % of malicious clients in each FL round. FSL does not require this knowledge.

FSL achieves higher robustness than state-of-the-art robust AGRs: We note from Table 2 that, FSL is more robust to the presence of malicious clients who try to poison the global model compared to Multi-Krum, Trimmed-mean, and SignSGD for both 10% and 20% malicious clients rates. For instance, on CIFAR10, 10% malicious clients can decrease the accuracy of FL models to 56.3%, 58.8%, and 39.8% for Trimmed-mean, Multi-Krum, and SignSGD respectively; 20% malicious clients can decrease the accuracy of the FL models to 20.5%, 25.6%, 10.0% for Trimmed-mean, Multi-Krum, and SignSGD respectively. On the other hand, FSL performance decreases to 79.0% and 69.5% for 10% and 20% attacking ratio respectively.

We make similar observations for MNIST and FEMNIST datasets: for FEMNIST, 10% (20%) malicious clients reduce accuracy of the global model from 85.8% to 72.7% (56.2%) for Trimmed-Mean, to 80.9% (23.7%) for Multi-krum, and 76.7% (55.1%) for SignSGD, while FSL accuracy decreases

Table 2: Comparing the robustness of various FL algorithms: FSL and SFSL (in **bold**) outperform state-of-the-art robust AGRs and SignSGD against strongest of untargeted poisoning attacks.

Dataset	AGR	No malicious	10% malicious	20% malicious
MNIST + LeNet 1000 clients	FedAvg	98.8 (3.2)	10.0 (10.0)	10.0 (10.0)
	Trimmed-mean	98.8 (3.2)	95.1 (7.7)	87.6 (9.5)
	Multi-krum	98.8 (3.2)	98.6 (3.3)	97.9 (4.1)
	SignSGD	97.2 (4.6)	96.6 (5.0)	96.2 (5.6)
	FSL	**98.8 (3.1)**	**98.8 (3.1)**	**98.7 (3.3)**
	SFSL Top 50%	**98.2 (3.8)**	**97.04 (4.4)**	**95.1 (7.8)**
CIFAR10 + Conv8 1000 clients	FedAvg	85.4 (11.2)	10.0 (10.1)	10.0 (10.1)
	Trimmed-mean	84.9 (11.0)	56.3 (16.0)	20.5 (13.2)
	Multi-krum	84.7 (11.3)	58.8 (15.8)	25.6 (14.4)
	SignSGD	79.1 (12.8)	39.7 (15.9)	10.0 (10.1)
	FSL	**85.3 (11.3)**	**79.0 (12.4)**	**69.5 (14.8)**
	SFSL Top 50%	**77.6 (13.0)**	**41.7 (15.4)**	**39.7 (15.2)**
FEMNIST + LeNet 3400 clients	FedAvg	85.8 (10.2)	6.3 (5.8)	6.3 (5.8)
	Trimmed-mean	85.2 (11.0)	72.7 (15.7)	56.2 (20.3)
	Multi-krum	85.2 (10.9)	80.9 (12.2)	23.7 (12.8)
	SignSGD	79.3 (12.4)	76.7 (13.2)	55.1 (14.9)
	FSL	**84.2 (10.7)**	**83.0 (10.9)**	**65.8 (17.8)**
	SFSL Top 50%	**75.2 (12.7)**	**70.5 (14.4)**	**60.39 (14.8)**

to 83.0% (65.8%). We omit evaluating TopK, because even a single malicious client (Blanchard et al., 2017) can jeopardize its accuracy.

6.3 MISCELLANEOUS DISCUSSIONS

Due to space limitations, we defer a detailed discussion of ablation studies of FSL to Appendix C and below give their important takeaways.

Initialization matters in FSL: In FSL, the weight parameters are randomly initialized at the start and remain fixed throughout the training. An appropriate initialization is instrumental to the success of FSL, since the clients are trying to find the most important weight parameters. We study efficacy of three initializing strategies that use three different distributions: Glorot Normal, Kaiming Normal, and Singed Kaiming Constant. Table 4 shows the results. We observe from Table 4 that, Singed Kaiming Constant initialization achieves the best results that are closest to FedAvg.

Varying the sparsity of edge-popup algorithm in FSL: Figure 3 illustrates how the performance of FSL varies with the sizes of local subnetworks that the clients share with the server. In other words, when we vary the sparsity $k\%$ of edge popup algorithm during local subnetwork search $k \in [10, 20, 30, 40, 50, 60, 70, 80, 90]\%$. Interestingly we note that, FSL performs the worst when clients use all (k=100%) or none (k=0%) of the edges. This is because, it is difficult to find a subnetwork with small number of edges. While using all of the edge essentially results in using a random neural network. As we can see FSL with $k \in [40, 70]\%$, gives the best performances for all the three datasets. Hence, we set k=50% by default in our experiments.

7 CONCLUSIONS

We designed a novel collaborative learning algorithm, called *Federated Supermask Learning* (FSL), to address the issues of robustness to poisoning and communication efficiency in existing FL algorithms. We argue that a core reason for the susceptibility of existing FL algorithms to poisoning is the use of arbitrary values in their model updates. Hence, in FSL, we use ranks of edges of a randomly initialized neural network contributed by collaborating clients to find a global ranking and then use a subnetwork based only on the top edges. Use of rankings in a fixed range restricts the space available to poisoning adversaries to craft malicious updates, and also allows FSL to use sophisticated communication reduction methods. We show, both theoretically and empirically, that ranking based collaborative learning can effectively mitigate the robustness issue as well as reduce the communication costs involved.

8 REPRODUCIBILITY STATEMENT

We have attached our implementation code and experiment notebooks as supplementary materials. There are separate experiment notebooks showing the process of FSL training for MNIST, CIFAR10, and FEMNIST (results that we used in Table 1 and Table 2). We have explained all the hyperparameters including optimizer, learning rate, momentum, weight decay, and batch size in Appendix B.1 for both FSL and FedAvg (including using robust AGRs) settings. We also explained the model architectures we used in our experiments in Table 3 explaining different layers with number of parameters inside each. We also explained how we distributed MNIST and CIFAR10 samples among 1,000 clients using Dirichlet distribution (Minka, 2000) to make them non-iid in Appendix B.2.

REFERENCES

Alham Fikri Aji and Kenneth Heafield. Sparse communication for distributed gradient descent. In *Proceedings of the 2017 Conference on Empirical Methods in Natural Language Processing, EMNLP*, 2017.

Dan Alistarh, Torsten Hoefler, Mikael Johansson, Nikola Konstantinov, Sarit Khirirat, and Cédric Renggli. The convergence of sparsified gradient methods. In *Advances in Neural Information Processing Systems 31: NeurIPS*, 2018a.

Dan Alistarh, Torsten Hoefler, Mikael Johansson, Nikola Konstantinov, Sarit Khirirat, and Cédric Renggli. The convergence of sparsified gradient methods. In *Advances in Neural Information Processing Systems*, pp. 5973–5983, 2018b.

argsort. Torch.argsort. URL https://pytorch.org/docs/stable/generated/torch.argsort.html.

Yoshua Bengio, Nicholas Léonard, and Aaron Courville. Estimating or propagating gradients through stochastic neurons for conditional computation. *arXiv preprint arXiv:1308.3432*, 2013.

Jeremy Bernstein, Jiawei Zhao, Kamyar Azizzadenesheli, and Anima Anandkumar. signsgd with majority vote is communication efficient and fault tolerant. In *7th International Conference on Learning Representations, ICLR*, 2019.

Arjun Nitin Bhagoji, Supriyo Chakraborty, Prateek Mittal, and Seraphin Calo. Analyzing federated learning through an adversarial lens. In *International Conference on Machine Learning*, pp. 634–643, 2019.

Peva Blanchard, Rachid Guerraoui, Julien Stainer, et al. Machine learning with adversaries: Byzantine tolerant gradient descent. In *Advances in Neural Information Processing Systems*, pp. 119–129, 2017.

Sebastian Caldas, Peter Wu, Tian Li, Jakub Konečný, H. Brendan McMahan, Virginia Smith, and Ameet Talwalkar. LEAF: A benchmark for federated settings. *CoRR*, abs/1812.01097, 2018. URL http://arxiv.org/abs/1812.01097.

Francesco Paolo Cantelli. Sui confini della probabilita. In *Atti del Congresso Internazionale dei Matematici: Bologna del 3 al 10 de settembre di 1928*, pp. 47–60, 1929.

Gregory Cohen, Saeed Afshar, Jonathan Tapson, and André van Schaik. EMNIST: extending MNIST to handwritten letters. In *2017 International Joint Conference on Neural Networks, IJCNN*, 2017.

Yann N Dauphin and Yoshua Bengio. Big neural networks waste capacity. *arXiv preprint arXiv:1301.3583*, 2013.

Jeffrey Dean, Greg Corrado, Rajat Monga, Kai Chen, Matthieu Devin, Mark Mao, Andrew Senior, Paul Tucker, Ke Yang, Quoc V Le, and Andrew Y Ng. Large scale distributed deep networks. *Advances in neural information processing systems*, 2012.

Misha Denil, Babak Shakibi, Laurent Dinh, Marc'Aurelio Ranzato, and Nando de Freitas. Predicting parameters in deep learning. In *Proceedings of the 26th International Conference on Neural Information Processing Systems-Volume 2*, pp. 2148–2156, 2013.

Minghong Fang, Xiaoyu Cao, Jinyuan Jia, and Neil Zhenqiang Gong. Local model poisoning attacks to byzantine-robust federated learning. In Srdjan Capkun and Franziska Roesner (eds.), *29th USENIX Security Symposium, USENIX Security*, 2020.

Jonathan Frankle and Michael Carbin. The lottery ticket hypothesis: Finding sparse, trainable neural networks. *ICLR*, 2019.

Xavier Glorot and Yoshua Bengio. Understanding the difficulty of training deep feedforward neural networks. In *Proceedings of the Thirteenth International Conference on Artificial Intelligence and Statistics, AISTATS*, 2010.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Delving deep into rectifiers: Surpassing human-level performance on imagenet classification. In *Proceedings of the IEEE international conference on computer vision*, pp. 1026–1034, 2015.

Peter Kairouz, H Brendan McMahan, Brendan Avent, Aurélien Bellet, Mehdi Bennis, Arjun Nitin Bhagoji, Keith Bonawitz, Zachary Charles, Graham Cormode, Rachel Cummings, et al. Advances and open problems in federated learning. *arXiv preprint arXiv:1912.04977*, 2019.

Jakub Konečný, H Brendan McMahan, Felix X Yu, Peter Richtárik, Ananda Theertha Suresh, and Dave Bacon. Federated learning: Strategies for improving communication efficiency. *arXiv preprint arXiv:1610.05492*, 2016.

Alex Krizhevsky and Geoffrey Hinton. Learning multiple layers of features from tiny images. 2009.

Ang Li, Jingwei Sun, Binghui Wang, Lin Duan, Sicheng Li, Yiran Chen, and Hai Li. Lotteryfl: Personalized and communication-efficient federated learning with lottery ticket hypothesis on non-iid datasets. *CoRR*, 2020a. URL https://arxiv.org/abs/2008.03371.

Tian Li, Anit Kumar Sahu, Ameet Talwalkar, and Virginia Smith. Federated learning: Challenges, methods, and future directions. *IEEE Signal Processing Magazine*, 37(3):50–60, 2020b.

Heiko Ludwig, Nathalie Baracaldo, Gegi Thomas, and Yi Zhou. IBM federated learning: an enterprise framework white paper V0.1. *CoRR*, abs/2007.10987, 2020.

H Brendan McMahan, Eider Moore, Daniel Ramage, Seth Hampson, and Blaise Aguera y Arcas. Communication-efficient learning of deep networks from decentralized data. *Proceedings of the 20 th International Conference on Artificial Intelligence and Statistics*, 2017.

El Mahdi El Mhamdi, Rachid Guerraoui, and Sébastien Rouault. The hidden vulnerability of distributed learning in byzantium. In *Proceedings of the 35th International Conference on Machine Learning, ICML*, 2018.

Thomas Minka. Estimating a dirichlet distribution, 2000.

Matthias Paulik, Matt Seigel, and Henry Mason and. Federated evaluation and tuning for on-device personalization: System design & applications. *CoRR*, abs/2102.08503, 2021. URL https://arxiv.org/abs/2102.08503.

Vivek Ramanujan, Mitchell Wortsman, Aniruddha Kembhavi, Ali Farhadi, and Mohammad Rastegari. What's hidden in a randomly weighted neural network? In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 11893–11902, 2020.

Virat Shejwalkar and Amir Houmansadr. Manipulating the byzantine: Optimizing model poisoning attacks and defenses for federated learning. In *Proceedings of the 28th Network and Distributed System Security Symposium, (NDSS)*, 2021.

Virat Shejwalkar, Amir Houmansadr, Peter Kairouz, and Daniel Ramage. Back to the drawing board: A critical evaluation of poisoning attacks on federated learning. *arXiv preprint arXiv:2108.10241*, 2021.

Hongyi Wang, Kartik Sreenivasan, Shashank Rajput, Harit Vishwakarma, Saurabh Agarwal, Jyyong Sohn, Kangwook Lee, and Dimitris Papailiopoulos. Attack of the tails: Yes, you really can backdoor federated learning. *arXiv preprint arXiv:2007.05084*, 2020.

Mitchell Wortsman, Vivek Ramanujan, Rosanne Liu, Aniruddha Kembhavi, Mohammad Rastegari, Jason Yosinski, and Ali Farhadi. Supermasks in superposition. In *Advances in Neural Information Processing Systems 33: NeurIPS*, 2020.

Cong Xie, Oluwasanmi Koyejo, and Indranil Gupta. Generalized byzantine-tolerant sgd. *arXiv preprint arXiv:1802.10116*, 2018.

Dong Yin, Yudong Chen, Kannan Ramchandran, and Peter L. Bartlett. Byzantine-robust distributed learning: Towards optimal statistical rates. In Jennifer G. Dy and Andreas Krause (eds.), *Proceedings of the 35th International Conference on Machine Learning, ICML*, 2018.

Hattie Zhou, Janice Lan, Rosanne Liu, and Jason Yosinski. Deconstructing lottery tickets: Zeros, signs, and the supermask. In *Advances in Neural Information Processing Systems 32: NeurIPS*, 2019.

A MISSING DETAILS OF ROBUSTNESS OF FSL

A.1 FSL POISONING ALGORITHM

Algorithm 3 shows the ranking poisoning attack.

Algorithm 3 FSL Poisoning

1: **Input:** number of malicious clients M, number of malicious local epochs E', seed SEED, global ranking R_g^t, learning rate η, subnetwork size $k\%$
2: **function** CRAFTMALICIOUSUPDATE(M, SEED, R_g^t, E', η, k):
3:     **for** $mu \in [M]$ **do**   ▷ For all the malicious clients
4:         Malicious Client Executes:
5:         $\theta^s, \theta^w \leftarrow$ Initialize scores and weights using SEED
6:         $\theta^s[R_g^t] \leftarrow$ SORT(θ^s)
7:         $S \leftarrow$ Edge-PopUp($E', D_u^{tr}, \theta^w, \theta^s, k, \eta$)
8:         $R_{mu}^t \leftarrow$ ARGSORT(S)   ▷ Ranking of the malicious client
9:     **end for**
10:     Aggregation:
11:     $R_m^t \leftarrow$ VOTE($R_{mu \in [M]}^t$)   ▷ Majority vote aggregation
12:     **return** REVERSE(R_m^t)   ▷ reverse the ranking
13: **end function**

A.2 THEORETICAL ANALYSIS OF ROBUSTNESS OF FSL ALGORITHM

Let Z be the random variable that represents the number of votes that say edge e_i should be in final subnetwork, i.e., the number of clients whose local subnetwork of size $k\%$ of the entire network (Algorithm 2 line 11) contains e_i. Therefore, $Z \in [0, n]$ where n is the number of clients being processed. Let G be the random variable that represents the number of good clients that vote for edge e_i and B be the random variable that represents the number of malicious clients that inadvertently put this edge in their top local ranks. There are total of αn malicious clients, where α is the malicious clients rate that B of them decides that e_i is a bad edge and should not be removed. Each malicious client is computing the subnetwork on its own training data, so B of them do not conclude that e_i is a good edge. Hence, $Z = G + B$. We can say that G and B have binomial distribution , i.e., $G \sim binomial([(1 - \alpha)n, p]$ and $B \sim binomial([\alpha n, 1 - p]$ where p shows the probability that a good client put this edge in top ranks and α is the attackers ratio. The probability that our voting system fails is $P[\text{failure}] = P[Z <= \frac{n}{2}]$, i.e., more than half of the votes do not include the e_i in their subnetworks. We can find the mean and variance of Z as follows:

$$E[Z] = (1 - \alpha)np + \alpha n(1 - p) \tag{1}$$

$$Var[Z] = (1 - \alpha)np(1 - p) + \alpha np(1 - p) = np(1 - p) \tag{2}$$

Cantelli (Cantelli, 1929) provides an inequality where for a random variable X with mean μ and variance σ^2 we have $P[\mu - X >= \lambda] <= \frac{1}{1 + \frac{\lambda^2}{\sigma^2}}$, so we will have:

$$P[Z <= \frac{n}{2}] = P[E[Z] - Z >= E[Z] - n/2] <= \frac{1}{1 + \frac{(E[z] - n/2)^2}{var[Z]}} \tag{3}$$

because $1 + x^2 >= 2x$, we have:

$$P[Z <= \frac{n}{2}] <= 1/2 \sqrt{\frac{Var[Z]}{(E[Z] - n/2)^2}} = 1/2 \sqrt{\frac{np(1 - p)}{(np - \alpha np + \alpha n - \alpha np - n/2)^2}}$$

$$= 1/2 \sqrt{\frac{np(1 - p)}{(n(p + \alpha(1 - 2p) - 1/2))^2}}$$

B MISSING DETAILS OF EXPERIMENTAL SETUP

B.1 DATASETS AND MODEL ARCHITECTURES

MNIST is a 10-class class-balanced classification task with 70,000 gray-scale images, each of size 28×28. We experiment with LeNet architecture, and 2 local epochs for selected clients in each round. For training weights (experiments for FedAvg), we optimize SGD as optimizer with learning rate 0.01, momentum 0.9, weight decay 1e-4, batch size 8. For training supermasks, we optimize SGD with learning rate of 0.4, momentum 0.9, weight decay 1e-4, and batch size 8.

CIFAR10 (Krizhevsky & Hinton, 2009) is a 10-class classification task with 60,000 RGB images (50,000 for training and 10,000 for testing), each of size 32×32. We experiment with a VGG-like architecture, which is identical to what Ramanujan et al. (2020) used, 5 local epochs for selected clients in each round. For training weights (experiments for FedAvg), we optimize SGD as optimizer with learning rate 0.1, momentum 0.9, weight decay 1e-4, batch size 8. For training supermasks, we optimize SGD with learning rate of 0.4, momentum 0.9, weight decay 1e-4, and batch size 8.

FEMNIST (Caldas et al., 2018; Cohen et al., 2017) is a character recognition classification task with 3,400 clients, 62 classes (52 for upper and lower case letters and 10 for digits), and 671,585 gray-scale images. Each client has data of her own handwritten digits or letters. We use LeNet architecture for this dataset, and 2 local epochs for selected clients. For training weights (experiments for FedAvg), we optimize SGD as optimizer with learning rate 0.15, momentum 0.9, weight decay 1e-4, batch size 10. For training supermasks, we optimize SGD with learning rate of 0.2, momentum 0.9, weight decay 1e-4, and batch size 10.

Table 3 shows the architecture and number of parameters in each layer of the models we use in our experiments.

B.2 NON-IID DATA DISTRIBUTION

Considering the heterogeneous data data in real-word cross-device FL, we distribute MNIST and CIFAR10 in non-iid parts using Dirichlet distribution (Minka, 2000) with $\alpha = 1$ among 1000 clients, where increasing the Dirichlet distribution parameter (i.e, α) results in more iid dataset. After this assignments, we split datasets to training (80%) and test (20%) among the clients. At the end of the FL rounds, we calculate the test accuracy of each client for its test data, and we report the mean of test accuracies in our experiments. We run all the experiments for 2000 global epochs, where 25 clients are selected in each round.

B.3 BASELINES

FedAVG In non-adversarial FL settings, dimension-wise average (Dean et al., 2012; Konečnỳ et al., 2016; McMahan et al., 2017) is an effective AGR. Due to its efficiency, Average is the only AGR implemented by FL applications in practice (Ludwig et al., 2020; Paulik et al., 2021). Multiple works have argued that, in theory, even a single compromised client can poison the global model of an Average-based FL.

SignSGD is a quntization method used in distributed learning that compress the gradients in 1 bit. In SignSGD (Bernstein et al., 2019) the workers just send the sign of the gradients to the server, and the server runs a majority vote on them. SignSGD is designed for distributed learning where all the clients are participating in each round, so all the clients are aware of the most updated weight parameters. However, using SignSGD in FL just provides benefit in upload bandwidth, and the server should send all the weight parameters (each 32 bits) to new selected clients as they are unaware of the global model. This make their design very efficient in upload cost, i.e., $\sum_{\ell \in [L]} n_\ell$ bits , but their download cost is similar to FedAvg, i.e, $\sum_{\ell \in [L]} 32 \times n_\ell$ bits.

TopK is a Sparsification method used in distributed learning that try to transmit only a few elements in each model update to the server. In TopK (Aji & Heafield, 2017; Alistarh et al., 2018a) , the clients sort all the gradients absolute values, and send the Top K largest gradients to the server for aggregation. Topk is suffering from the same problem that SignSGD has where the server should announce all the model updates (instead of portion of them) to the new selected clients as they are unaware of

Table 3: Model architectures. We use identical architecture to those Ramanujan et al. (2020); Wortsman et al. (2020) used.

Architecture	Layer Name	Number of parameters
LeNet + MNIST (Wortsman et al., 2020)	Convolution(32) + Relu	288
	Convolution(64) + Relu	18432
	MaxPool(2x2)	-
	FC(128) + Relu	1605632
	FC(10)	1280
Conv8 + CIFAR10 (Ramanujan et al., 2020)	Convolution(64) + Relu	1728
	Convolution(64) + Relu	36864
	MaxPool(2x2)	-
	Convolution(128) + Relu	73728
	Convolution(128) + Relu	147456
	MaxPool(2x2)	-
	Convolution(256) + Relu	294912
	Convolution(256) + Relu	589824
	MaxPool(2x2)	-
	Convolution(512) + Relu	1179648
	Convolution(512) + Relu	2359296
	MaxPool(2x2)	-
	FC(256) + Relu	524288
	FC(256) + Relu	65536
	FC(10)	2560
LeNet + FEMNIST (Wortsman et al., 2020)	Convolution(32) + Relu	288
	Convolution(64) + Relu	18432
	MaxPool(2x2)	-
	FC(128) + Relu	1605632
	FC(62)	7936

the global model. This make their design efficient in upload cost, i.e., $\sum_{\ell \in [L]} (32 \times k \, n_\ell + n_\ell)$ bits , but their download cost is similar to FedAvg, i.e, $\sum_{\ell \in [L]} 32 \times n_\ell$ bits.

We use FL poisoning attacks from (Shejwalkar & Houmansadr, 2021) in our experiments.

C MISSING EXPERIMENTS

C.1 FSL: INITIALIZATION MATTERS

Table 4: Comparing performance of FSL under different random initialization algorithms with vanilla FedAvg when cross-device FL is used. In all the datasets, using Singed Kaiming Constant initialization shows better performance.

Dataset	Metric	Algorithm			
		FedAvg	FSL		
	$W_{init} \sim$	-	$\mathcal{X}_N$	$\mathcal{N}_K$	U_K
MNIST LeNet N=1000	Mean	98.8	96.6	98.7	98.8
	STD	3.1	5.2	3.2	3.1
	Min	75.0	57.1	75.0	75.0
	Max	100	100	100	100
CIFAR10 Conv N=1000	Mean	85.4	63.6	82.0	85.3
	STD	11.2	15.6	11.9	11.3
	Min	33.3	0	0	33.3
	Max	100	100	100	100
FEMNIST LeNet N=3400	Mean	85.8	69.2	82.9	84.2
	STD	10.2	14.2	11.1	10.7
	Min	10.0	0	14.3	7.1
	Max	100	100	100	100

In FSL, the weight parameters are fixed through the protocol and they are initialized randomly at the beginning of the protocol. It is very important to how to initialize them since the clients are trying to find the importance of the weight parameters values. We use three different distribution for initializing the weight parameters as follows:

Glorot Normal (Glorot & Bengio, 2010) where we denote by $\mathcal{X}_N$. Previous work Zhou et al. (2019) used this initialization to demonstrate that subnetworks of randomly weighted neural networks can achieve impressive performance.

Kaiming Normal (He et al., 2015) where we denote by $\mathcal{N}_k$ defined as $\mathcal{N}_K = \mathcal{N}\left(0, \sqrt{2/n_{\ell-1}}\right)$ where $\mathcal{N}$ shows normal distribution. n_ℓ shows the number of parameters in the ℓth layer.

Singed Kaiming Constant (Ramanujan et al., 2020) where all the wights are a constant σ but they are assigned $\{+, -\}$ randomly. This constant, σ, is the standard deviation of Kaiming Normal. We show this initialization with U_K as we are sampling from $\{-\sigma, +\sigma\}$ where $\sigma = \left(\sqrt{2/n_{\ell-1}}\right)$.

Table 4 shows the results of running FSL for three datasets under different initialization algorithms. We compare FSL with FedAvg where we report mean, standard deviation, minimum and maximum of the accuracies for the clients after the protocol finishes. As we can see under three different random initialization, using Signed Kaiming Normal (U_K) results in better performance.

We can see from the Table 4, that FSL with U_K initialization can achieve very close results to the FedAVg. This is meaning that FSL just by sharing the ranks can produce good results as FedAVG where all the gradients are sent to the server.

Previous work Ramanujan et al. (2020) also consider these three initialization to find the best subnetwork in centralized machine learning setting. They also show that using Singed Kaiming Normal is producing the best supermasks. Our results are aligned with their results. We use Singed Kaiming Normal as the initialization method fro the weights and Kaiming Uniform for the scores for the rest of the experiments.

(a) MNIST (non-iid: 1000 clients)   (b) CIFAR10   (non-iid: 1000   (c) FEMNIST (3400 clients)
clients)

Figure 3: Comparing performance of FSL for different subnetwork sizes. k (x-axis) shows the % of weights that each client is including in its subnetwork, test accuracy (y-axis) shows the mean of accuracies for all the clients on their test data. The chosen clients in each round send all the ranks to the server. FSL with subnetworks of $\in [30\%, 70\%]$ result in better performances.

C.2   FSL: SIZE OF SUBNETWORKS

In FSL, each selected client learn a separate subnetwork in the randomly weight parameter network by applying Edge-Pop Algorithm (Ramanujan et al., 2020) using its local data. Edge-Pop algorithm has one associated parameter called k that it shows % of weights which remain in the subnetwork. For instance, $k = 50\%$ denotes that each client is searching for a subnetwork within random weight parameters that has half of the original weights by finding the top 50% top-ranks edges in the network and it is removing the other half.

Figure 3 illustrates how the performance of subnetwork that all the clients find in FSL varies with the size of subnetwork for different datasets. We trained FSL models with $k \in [10, 20, 30, 40, 50, 60, 70, 80, 90]$ and FedAvg model where it is shown as a horizontal line (i.e. it is updating 100% of the weights).

We can see that the worst performance of FSL happens when all the clients are approaching all (100%) or none (0%) of the weights as with small number of edges, it is difficult to find a subnetwork. Also a subnetwork with a large k is a random network that produce random results. As we can see FSL with $k \in [0.4, 0.7]$, result in better federated performances for all the three datasets. Previous work Ramanujan et al. (2020) also checked the effect of subnetwork size in the training of a supermask in centralized setting, and our results are in aligned with their results. We set k of the subnetworks in FSL as 50% for all the participating clients for the rest of the experiments.

D   MISSING DETAILS OF EDGE-POPUP ALGORITHM

Suppose in a fully connected neural network, there are L layers and layer $\ell \in [1, L]$ has n_ℓ neurons, denoted by $V^\ell = \{V_1^\ell, ..., V_{n_\ell}^\ell\}$. If I_v and Z_v denote the input and output for neuron v respectively, then the input of the node v is the weighted sum of all nodes in previous layer, i.e., $I_v = \sum_{u \in V^{\ell-1}} W_{uv} Z_u$. Here, W_{uv} is the weight of the edge connecting u to v. Edge-popup algorithm tries to find subnetwork E, so the input for neuron v would be: $I_v = \sum_{(u,v) \in E} W_{uv} Z_u$.

Updating scores. Consider an edge E_{uv} that connects two neurons u and v, W_{uv} be the weight of E_{uv}, and s_{uv} be the score assigned to the edge E_{uv} by Edge-popup algorithm. Then the edge-popup algorithm removes edge E_{uv} from the supermask if its score s_{uv} is not high enough. Each iteration of supermask training updates the scores of all edges such that, if having an edge E_{uv} in subnetwork reduces loss (e.g., cross-entropy loss) over training data, the score s_{uv} increases.

The algorithm selects top k% edges (i.e., finds a subnetwork with sparsity of k%) with highest scores, so I_v reduces to $I_v = \sum_{u \in V^{\ell-1}} W_{uv} Z_u h(s_{uv})$ where $h(.)$ returns 1 if the edge exists in top-k% highest score edges and 0 otherwise. Because of existence of $h(.)$, which is not differentiable, it is impossible to compute the gradient of loss with respect to s_{uv}. Recall that, the edge-popup algorithm use straight-through gradient estimator (Bengio et al., 2013) to compute gradients. In this approach, $h(.)$ will be treated as the identity in the backward pass meaning that the upstream gradient (i.e., $\frac{\partial L}{\partial I_v}$) goes straight-through $h()$. Now using chain rule, we can derive $\frac{\partial L}{\partial I_v} \frac{\partial I_v}{\partial s_{uv}} = \frac{\partial L}{\partial I_v} W_{uv} Z_u$ where L is the loss to minimize. Then we can SGD with step size η to update scores as $s_{uv} \leftarrow s_{uv} - \eta \frac{\partial L}{\partial I_v} Z_u W_{uv}$.

Figure 4: Communication cost Analysis

E   MISSING INFORMATION OF COMMUNICATION COST COMPARISON

If we use a compression algorithm, we know that $n_\ell!$ possible permutations exist for layer $\ell \in [L]$. In the best case, an FSL client needs to send and receive $\sum_{\ell \in [L]} \log(n_\ell!)$ bits. Therefore based on Stirling's approximation the download and upload bandwidth for each FSL client would be $\sum_{\ell \in [L]} \sqrt{2\pi n_\ell} \left(\frac{n_\ell}{e}\right)^{n_\ell}$ bits. In Section 6.1, we measure the performance and communication cost of FSL with other existing FL compressors signSGD (Bernstein et al., 2019) and TopK (Aji & Heafield, 2017; Alistarh et al., 2018a). In Figure 4, we compare the communication cost of one client per FL round for FedAvg, SignSGD, and different variant of FSL for different number of parameters.

Similar work in this domain is LotteryFL (Li et al., 2020a), a personalization framework that each FL client learns a lottery ticket network (LTN) by pruning the base model using Lottery Ticket hypothesis (Frankle & Carbin, 2019). In LotteryFL, each client sends and receives the update for its subnetwork, and at the end, they have an extra step for personalization. FSL is different from LotteryFL as the FSL clients find subnetworks within a random and fixed network and send the ranks of their subnetwork edges instead of what LotteryFL clients do that train their weights and find a subnetwork by freezing some weights and send their actual model update. LotteryFL is based on FedAvg that the clients can send any update to the server, which is vulnerable to the same attacks that existed for FedAVG. In terms of communication cost, FSL is very close to LotteryFL as they report 1.81x improvement over CIFAR10 which is close to FSL and SFSL(50%) which provide 1.53x, 3.09x improvement respectively over CIFAR10.