Similarity as Reward Alignment: Robust Preference-based Reinforcement Learning

Sara Rajaram   **R. James Cotton**   **Fabian H. Sinz**

Keywords: Reinforcement Learning, preference-based RL, PBRL, contrastive learning

Summary

Preference-based Reinforcement Learning (PbRL) entails a variety of approaches for aligning models with human intent to alleviate the burden of reward engineering. However, most previous PbRL work has not investigated the robustness to labeler errors, inevitable with labelers who are non-experts or operate under time constraints. We introduce Similarity as Reward Alignment (SARA), a simple contrastive framework that is both resilient to noisy labels and adaptable to diverse feedback formats. SARA learns a latent representation of preferred samples and computes rewards as similarities to the learned latent. On preference data with varying realistic noise rates, we demonstrate competitive and more stable performance on continuous control offline RL benchmarks, with statistically significant improvements over baselines (Wilcoxon signed-rank, $p < 0.01$). We compute correlation to the environment rewards as a proxy for measuring alignment to the underlying preference criteria. We show that the SARA computed rewards display higher correlation across noise rates compared to baselines.

Contribution(s)

1. SARA (Similarity as Reward Alignment) uses contrastive learning to encode preferred and non-preferred trajectory sets into latent representations, and computes per-timestep rewards via cosine similarity to the preferred set representation. SARA achieves robustness to labeler error by learning an attention-weighted representation of the entire preferred trajectory set, rather than fitting pairwise rankings as in the standard Bradley-Terry (BT) model.

   Context: The vast majority of prior PbRL methods rely on BT-modeled reward learning (Christiano et al., 2017; Lee et al., 2021a;b; Kim et al., 2023; Ouyang et al., 2022). Azar et al. (2024) showed BT reward models can overfit to relative rankings, and Sun et al. (2025) demonstrated that BT formulations degrade when label error rates exceed 10%.

2. SARA achieves consistent policy performance across labeling noise rates. While individual baselines may achieve higher returns on specific datasets at low error rates, SARA's policy evaluation returns remain stable from 0–20% error rates, whereas individual baselines can degrade by up to 73% on specific datasets. At 40% error, all methods degrade, but SARA generally remains competitive with baselines and outperforms them on several datasets. A Wilcoxon signed-rank test across 24 task-condition cells confirms SARA's advantage is statistically significant against all baselines ($p < 0.01$). Additionally, SARA-inferred transition rewards correlate better with environment rewards than baselines at all error rates tested.

   Context: Prior work showed that even 10% label error can significantly degrade RL performance (Lee et al., 2021a; Cheng et al., 2024), and realistic disagreement rates among human labelers are around 25% (Dubois et al., 2023; Coste et al., 2024).

3. We provide a mechanistic analysis of SARA's robustness to label noise. We support this mechanism in the through t-SNE visualization and an ablation study removing the set-based encoding.

   Context: We rely on mechanistic analysis because formal convergence proofs for preference learning under noise remain an open challenge across the PbRL literature. Sun et al. (2025) noted the BT model itself lacks a formal robustness proof in noisy settings despite widespread adoption.

Similarity as Reward Alignment: Robust Preference-based Reinforcement Learning

Sara Rajaram[1-3]   **R. James Cotton**[5]   **Fabian H. Sinz**[1,4]

`sara.rajaram@uni-goettingen.de`

[1]**Institute for Computer Science and Campus Institute for Data Science,**
University of Göttingen, Göttingen, Germany
[2]**University Hospital Tübingen, Tübingen, Germany**
[3]**International Max Planck Research School for Intelligent Systems, Tübingen, Germany**
[4]**CAIMed, Lower Saxony Center for AI & Causal Methods in Medicine, Germany** [5]**Shirley Ryan Ability Lab, Northwestern University, Chicago, USA**

Abstract

Preference-based Reinforcement Learning (PbRL) entails a variety of approaches for aligning models with human intent to alleviate the burden of reward engineering. However, most previous PbRL work has not investigated the robustness to labeler errors, inevitable with labelers who are non-experts or operate under time constraints. We introduce Similarity as Reward Alignment (SARA), a simple contrastive framework that is both resilient to noisy labels and adaptable to diverse feedback formats. SARA learns a latent representation of preferred samples and computes rewards as similarities to the learned latent. On preference data with varying realistic noise rates, we demonstrate competitive and more stable performance on continuous control offline RL benchmarks, with statistically significant improvements over baselines (Wilcoxon signed-rank, p < 0.01). We also compute correlation to the environment rewards as a proxy for measuring alignment to the underlying preference criteria. We show that the SARA computed rewards display higher correlation across noise rates compared to baselines.

1 Introduction

Reinforcement Learning (RL) algorithms rely on carefully engineered reward functions in order to produce the desired behaviors for a task of interest (Sutton & Barto, 2018; Dann et al., 2023). In complex real-world settings, reward engineering requires various sensors, such as motion trackers (Bin Peng et al., 2020) or computer visions systems (Devin et al., 2018), as well as tedious hand-crafting to fine-tune such functions (Zhu et al., 2020) and ensure safe behavior (Kim et al., 2023). To mitigate reward engineering challenges, Preference-based RL (PbRL) algorithms have garnered increased attention in recent years. In a PbRL setting, human labelers provide feedback on a dataset of agent behaviors, and the PbRL algorithms aim to learn agent models that produce behavior better aligned to the preferences. Prominent examples include Large Language Model (LLM) fine-tuning (Ziegler et al., 2020; OpenAI et al., 2024; Ouyang et al., 2022; DeepSeek-AI et al., 2025) as well as robotics and simulated control (Sadigh et al., 2017; Christiano et al., 2017).

PbRL methods can learn a reward function from human feedback to use in downstream RL, but they face the challenge of accurately representing preferences from limited data (Wirth et al., 2017). Many prior works leverage preference labels on trajectory pairs by applying the Bradley-Terry (BT) model (Bradley & Terry, 1952):

$$P[\sigma^1 \succ \sigma^0; \psi] = \frac{\exp\left(\sum_t \hat{r}(s_t^1, a_t^1; \psi)\right)}{\exp\left(\sum_t \hat{r}(s_t^1, a_t^1; \psi)\right) + \exp\left(\sum_t \hat{r}(s_t^0, a_t^0; \psi)\right)}$$

Figure 1: **SARA framework:** Step 1 (training): preferred and non-preferred trajectories ($\boldsymbol{\sigma}_{p,i}$ and $\boldsymbol{\sigma}_{n,i}$) are extracted from preference data. The first Transformer, Enc 1, encodes each trajectory into a single token to give us representations $\mathbf{u}_{p,i}$ and $\mathbf{u}_{n,i}$. We then divide the set of preferred $\{\mathbf{u}_{p,i}\}$ into 2 subsets (and likewise for $\{\mathbf{u}_{n,i}\}$). The second Transformer, Enc 2, allows attention between the $\mathbf{u}_i$ of the same subset. It encodes each subset into a single latent, so we then have $\mathbf{z}_p^1, \mathbf{z}_p^2, \mathbf{z}_n^1, \mathbf{z}_n^2$. The SimCLR contrastive loss pushes together the two $\mathbf{z}_p^k$ latents, pushes together the two $\mathbf{z}_n^k$, and pushes apart the $\mathbf{z}_p^k$ from $\mathbf{z}_n^k$. Step 2 (infer): all preferred trajectories pass through SARA encoder: ie first Encoder 1 (per-trajectory encoding) and then as a single set through Encoder 2. This produces one fixed vector $\mathbf{z}_p^*$. Step 3 (RL rewards): in RL training, sample trajectory $\boldsymbol{\sigma}_t$. Compute reward for $\boldsymbol{\sigma}_t$ as cosine similarity to preferred latent, $\mathbf{z}_p^*$.

where σ^1 and σ^0 are sampled preferred and non-preferred trajectories, respectively, and $\hat{r}_\psi$ is a learnable reward function. The BT model is often used to learn an explicit reward function $\hat{r}_\psi$ (Christiano et al., 2017; Lee et al., 2021a;b; III & Sadigh, 2022; Ouyang et al., 2022; Kim et al., 2023) or re-formulated to learn a policy without a reward model (Hejna et al., 2024; Hejna & Sadigh, 2023; An et al., 2023; Kang et al., 2023; Rafailov et al., 2023; Kuhar et al., 2023).

In both cases, the BT model formulations come with assumptions and limitations, discussed by previous works (Sun et al., 2025; Tang et al., 2024; Munos et al., 2024; Azar et al., 2024; Ye et al., 2024). The BT model assumes that human preferences are transitive, an assumption which has been undermined by psychology research (Ye et al., 2024; Tversky, 1969; May, 1954). Furthermore, prior works also argue that the BT model's transitivity assumption is unrealistic (Munos et al., 2024; Zhang et al., 2025). Azar et al. (2024) showed that the BT reward models can overfit to the relative rankings in the trajectory pairs, resulting in agent behavior that also overfits to the preferred ranked trajectory. Overfitting is particularly problematic when labels are noisy or behaviors are similar. Labeling errors occur when annotators are time-constrained or non-experts (Ye et al., 2024; Cheng et al., 2024). Realistic error rates are between 5-38% (Sun et al., 2025), as evidenced by an observed 25% disagreement rate among labelers (Dubois et al., 2023; Coste et al., 2024). Prior work demonstrated that even a 10% label error rate can significantly degrade RL performance (Lee et al., 2021a; Cheng et al., 2024). Sun et al. (2025) show that the BT-model is not a necessary choice for a reward modeling approach, and BT-based models result in underperforming behaviors when labeling error rates are above 10%.

In contrast to most previous work, we assume the presence of labeling mistakes and similar behaviors in ranked pairs, so we avoid learning BT-modeled rewards based on the relative labels. To this end, we introduce Similarity as Reward Alignment (SARA), a robust and flexible PbRL framework

(see Figure 1 for an overview). SARA acknowledges that even with noise, discerning patterns exist in the preferred set as a whole and employs contrastive learning to obtain a representation for this set. SARA then computes rewards at each timestep based on the encoded trajectory's similarity to the representation of the preferred trajectories. Despite its simplicity, it handles noisy or ambiguous preference data reliably, and to our knowledge, our framework is novel in the PbRL literature. Our contributions and findings are:

Strong performance and robustness. Compared to state-of-the-art baselines, SARA achieves competitive and stable performance using human-labeled preference datasets. We vary the preference data by injecting label noise (0%, 10%, 20%, 40% error rates). SARA results in consistent policy evaluation returns from 0–20% error rates, whereas individual baselines can degrade by up to 73% on specific datasets. At 40% error, all methods degrade, but SARA generally remains competitive with baselines and outperforms them on several datasets. A Wilcoxon signed-rank test confirms SARA's advantage is statistically significant against all baselines ($p < 0.01$). Moreover, we demonstrate that SARA inferred transition rewards correlate better with the environmental transition rewards (unknown at training time) compared to SOTA reward based methods. This is true at all error rates, indicating SARA's robustness to learning preference patterns.

2 Related work

Preference-based RL Enabling development and comparison of PbRL algorithms, Kim et al. (2023) provided both expert-human labeled and script-labeled preference datasets for D4RL offline benchmark tasks. They also proposed the Preference Transformer (PT) reward model trained with a BT-based loss function to learn from preference data. As reward models can fail to capture true underlying preferences with limited data, subsequent works developed methods that avoid learning a reward model (Hejna & Sadigh, 2023; Hejna et al., 2024; An et al., 2023; Kang et al., 2023; Kuhar et al., 2023; Kim et al., 2024; Zhang et al., 2024). Inverse Preference Learning (Hejna & Sadigh, 2023) reformulates the BT model in terms of the RL Q-function, and can be used both in online and offline learning. In a similar vein of avoiding reward modeling, Offline Preference-guided Policy Optimization (OPPO) learns a trajectory encoder, an optimal latent, and learns a Decision Transformer policy conditioned on the latents (Kang et al., 2023).

Contrastive learning in PbRL Contrastive Preference Learning (CPL) generalizes the BT model and uses contrastive learning on the discounted sum of log policy for preferred and non-preferred segments (Hejna et al., 2024). CPL reformulates policy learning as a supervised learning objective rather than RL. Direct Preference-based Policy Optimization (DPPO) learns a BT-based preference predictor network, infers preferences for a full offline dataset, and lastly conducts contrastive learning to align policy predictions with the inferred preferred trajectories (An et al., 2023). Learning to Discern (L2D) conducts contrastive learning between trajectories of different labels (Kuhar et al., 2023). They then train a network with a BT-based loss, and its output is mapped to labels to filter low quality trajectories for downstream Imitation learning (IL).

Robustness in PbRL Though robustness techniques have been studied extensively in supervised learning contexts (Wang et al., 2021; Zhang et al., 2018; Han et al., 2018; Lukasik et al., 2020; Song et al., 2023), relatively little attention has been given in PbRL to the effect of labeling noise. Cheng et al. (2024) developed a PbRL method to filter out noisy preferences by defining a time dependent threshold for KL-divergence between predicted preference and the provided label. However, this framework involves querying human preferences iteratively online during policy training; it is not straightforward to adapt to our setting, in which the preference set is fixed and new queries cannot be sampled. Sun et al. (2025) examine preference learning in an LLM context, and they showed theoretically that BT formulations are not necessary. Instead of a BT loss that predicts the probability of preferring one response over another, they propose a simple classifier approach of predicting binary response preference. Compared against BT based approaches, they showed improved performance on LLM human value metrics for label error rates above 10%.

Our work diverges from these previous works as follows: As discussed in Section 1, the vast majority of PbRL works rely on BT assumptions. Our work prioritizes representation learning and avoids BT-modeling due to the potential to overfit (Azar et al., 2024), especially problematic with noisy comparison labels (Sun et al., 2025). Unlike the methods that do not learn an explicit reward function (Kang et al., 2023; Hejna et al., 2024; An et al., 2023; Kuhar et al., 2023), we use our representations to provide rewards which enables versatility to off-the-shelf offline and online RL algorithms. Also, if the problem setup has a known task reward, as occurring in a robotics setting, our method allows easy reward shaping by adding task rewards to preference inferred rewards. The classifier approach proposed by Sun et al. (2025) lays out a theoretical foundation for a non-BT approach. However, they focus on the LLM bandit setting whereas we focus on RL environments, with multi-step state/action trajectories. Whereas they focus on label classification, we focus on representation learning and infer rewards cheaply afterwards.

3 Similarity as Reward Alignment (SARA)

We first review the PbRL setup. We then describe the SARA model, comprising a contrastive transformer encoder to learn a preferred set representation and a reward inference method. Supplement 12 provides details and hyperparameters.

Preliminaries In the RL paradigm, an agent at timestep t and state $\mathbf{s}_t$ interacts with the environment by choosing an action $\mathbf{a}_t$. The action is chosen via its policy $\mathbf{a}_t = \pi(\mathbf{s}_t)$ which is a mapping from state to action. The environment provides reward $r(\mathbf{s}_t, \mathbf{a}_t)$ and transitions the agent to the next state $\mathbf{s}_{t+1}$. RL algorithms aim to learn a policy that maximizes the discounted cumulative reward, $R_t = \sum_{k=0}^{\infty} \gamma^k r(\mathbf{s}_{t+k}, \mathbf{a}_{t+k})$ with discount factor γ.

To address the reward engineering problem (Sutton & Barto, 2018; Dann et al., 2023), PbRL leverages human labeled preferences to learn policies that align with human intent (Wirth et al., 2017). Several previous approaches (Christiano et al., 2017; Kim et al., 2023; Hejna & Sadigh, 2023; Hejna et al., 2024; An et al., 2023; Kang et al., 2023) assume that human feedback is given in the form of preferences over trajectory pairs. Each trajectory segment σ consists of H state-action transitions: $\sigma = \{(s_0, a_0), (s_1, a_1), \ldots, (s_{H-1}, a_{H-1})\}$. Given a pair of segments (σ^0, σ^1), a human annotator provides a preference label $y \in \{0, 0.5, 1\}$. The labels $y = 0$ and $y = 1$ indicate $\sigma^0 \succ \sigma^1$ and $\sigma^1 \succ \sigma^0$, respectively. The neutral preference $y = 0.5$ designates equal preference between the two trajectories.

SARA contrastive encoder The SARA encoder produces a single latent representation of all preferred labeled trajectories in the preference dataset. The SARA encoder addresses noisy preference learning by learning robust set-level representations that distinguish preferred from non-preferred behaviors, rather than relying on potentially unreliable pairwise comparisons.

We assume access to two sets of trajectories: a set of preferred trajectories and a set of non-preferred trajectories. In contrast to standard approaches, we do not require trajectories to be given in pairs, allowing the sets to have different sizes. When working with datasets that provide labeled pairs, we break apart the pairs to form these two sets, discarding the specific pairwise rankings. For pairs with neutral preference ($y = 0.5$), we include both trajectories in both sets.

Our contrastive encoder processes trajectories through a two-stage architecture. In the first stage, each trajectory passes through Transformer Encoder 1 (Figure 1) with positional encoding of time, followed by average pooling over timesteps to produce a single encoding per trajectory. This yields trajectory encodings $\mathbf{u}_{p,i}$ and $\mathbf{u}_{n,i}$ for preferred and non-preferred trajectories, respectively.

In the second stage, we randomly partition trajectory encodings within each category (preferred/non-preferred) into k subsets ($k = 2$ in Figure 1). The value k is a hyperparameter; we need a minimum of $k = 2$, so that we have at least one positive example for the contrastive loss. The model shows low sensitivity to the choice of k provided sufficient trajectories exist in each subset (Supplement 7). We fix $k = 2$ in our experiments. Each subset then passes through Transformer Encoder 2, allowing

u within the same subset to attend to each other. This produces set-level encodings $\mathbf{z}_p^k$ and $\mathbf{z}_n^k$ for each preferred and non-preferred subset, respectively.

We train the encoder using the SimCLR contrastive loss (Chen et al., 2020) to pull together preferred subset representations $\mathbf{z}_p^k$ while pushing apart preferred and non-preferred representations. Let the outputs of the SARA encoder be $P = \{z_p^1, ..., z_p^k\}$ and $N = \{z_n^1, ..., z_n^k\}$ and $\cos$ denote cosine similarity. Then SimCLR loss is given as:

$$\mathcal{L}_{\text{total}} = \frac{1}{2k} \left(\sum_{i=1}^{k} \mathcal{L}(z_p^i) + \sum_{i=1}^{k} \mathcal{L}(z_n^i) \right) \tag{1}$$

$$\mathcal{L}(z_p^i) = -\frac{1}{k-1} \sum_{j \neq i} \log \frac{\exp\big(\cos(z_p^i, z_p^j)/\tau\big)}{\sum\limits_{j \neq i} \exp\big(\cos(z_p^i, z_p^j)/\tau\big) + \sum\limits_{\ell=1}^{k} \exp\big(\cos(z_p^i, z_n^\ell)/\tau\big)}. \tag{2}$$

The $\mathcal{L}(z_n^i)$ is defined analogously.

We randomize the composition of trajectories in each subset at every training epoch. This randomization strategy forces the encoder to learn generalizable patterns that distinguish preferred from non-preferred behavior rather than overfitting to specific trajectory pairings.

This approach provides several key advantages. The transformer architecture naturally develops robustness to mislabeled or ambiguous trajectories by learning to downweight patterns that do not reliably distinguish preference categories. Additionally, the transformer handles variable numbers of trajectories within each set. This allows us to train on subsets and then feed in the full set of preferred trajectories at inference.

SARA reward inference At inference time, we encode the complete set of preferred trajectories to obtain $\mathbf{z}_p^*$, our fixed preference representation. This frozen preferred representation then serves as the basis for computing similarity rewards in downstream tasks, providing a stable reference point that captures the essential characteristics of preferred behavior patterns. For each trajectory up to time t, we get the latent $\mathbf{z}_t = \mathcal{E}(\sigma_t)$, where $\mathcal{E}$ is the trained and frozen encoder. Then we simply compute the reward at time t as: $r_t = \cos(\mathbf{z}_t, \mathbf{z}_p^*)$ using our frozen preferred latent (Figure 1, Step 3). This is a simple yet novel proposal for reward estimation from preferences.

SARA reward: theoretical justification Sun et al. (2025) examined preference learning in a LLM context, and they noted that BT formulations are not necessary. Instead of a BT loss that predicts the probability of preferring one response over another, they proposed a simple classifier approach of predicting preference (1 or 0 labeling) for the responses. They showed that such an approach preserves the ordering of the underlying true reward function, and that it is sufficient for downstream LLM alignment. Thus, instead of predicting the BT $P[\sigma^1 \succ \sigma^0; \psi]$ for a reward model parameterized by ψ, it is sufficient to predict the probability to be preferred $P[\sigma^i; \psi]$ with $i \in \{0, 1\}$ (Sun et al., 2025). In the next paragraph, we show that our approach implicitly does the same.

While our work focuses on representation learning followed by reward inference, their model focuses on classification for learning an explicit reward model. Nonetheless, their work provides theoretical grounding for our proposal that we learn based on individual trajectory labelings of preferred vs. non-preferred rather than learning the BT-based relative rankings. After training SARA, we pass σ_t through our frozen SARA encoder to get z_t. We then propose the following model to estimate the probability of the sampled trajectory σ_t being preferred, given its latent representation:

$$P\big(p \mid \mathbf{z}_t\big) = \frac{\exp\big(\cos(z_t, z_p^*)\big)}{\exp\big(\cos(z_t, z_p^*)\big) + \exp\big(\cos(z_t, z_n^*)\big)} = \frac{1}{1 + \exp\Big(-\big[\cos(z_t, z_p^*) - \cos(z_t, z_n^*)\big]\Big)}. \tag{3}$$

Such a probability function is a natural choice because the SimCLR loss aligns and separates latents using exponentiated cosine similarities. In RL we want to incentivize actions that have high probability of being preferred. Therefore, we simply set our reward equal to $r_t = \alpha \cos(\mathbf{z}_t, \mathbf{z}_p^*) - \beta \cos(\mathbf{z}_t, \mathbf{z}_n^*)$, where $\alpha \geq 0$ and $\beta \geq 0$ are hyperparameters to control the trade-off between the two terms. Empirically, we tuned these parameters and found $\alpha = 1$, $\beta = 0$ to work well in our experiments (Supplement 8). We state our reward function as such for simplicity.

Grounded by the work of Sun et al. (2025), we score trajectories on their alignment with preferred trajectories rather than relying on potentially noisy relative labels. Our approach represents a departure from pairwise modeling of the BT model. We provide mechanistic justifications in Section 5.

4   Offline RL experiments

In this section we address the following questions: First, how does SARA perform when labeling mistakes occur? Secondly, how do SARA inferred rewards compare to BT based algorithms?

We take preference datasets and randomly flip 10%, 20%, and 40% of the non-neutral labels. These error rates are in accordance with realistic error rates noted in prior literature, as discussed in Section 1 (page 2 top).

Setup Similar to past works (Kim et al., 2023; An et al., 2023), we evaluate our framework in the offline setting on the following D4RL benchmark datasets: Mujoco locomotion (4 datasets), Franka Kitchen (2 datasets), Adroit (2 datasets) (Fu et al., 2021; Gupta; Farama Foundation, 2024). For the Mujoco and Adroit tasks, we use the preference datasets provided by Kim et al. (2023). We use the datasets by An et al. (2023) for the Kitchen tasks. All preference datasets comprise a limited subset of labeled trajectory pairs (100-500 pairs, depending on the dataset) relative to the full number of offline trajectories. The Adroit and Kitchen tasks have high dimensional state/action spaces (69 state+action dimensions) relative to the Mujoco tasks (14-23 state+action dimensions). Thus, our experiments comprise a variety of task environments, labeler sources, and state-action dimensionalities. We did not experiment on AntMaze due to a critical bug noted by An et al. (2023) (Supplement 15). Additional details on the preference and full offline datasets can be found in Supplement 11.1. The policy evaluation rewards exhibit high variance and are quite similar across models for the Adroit tasks, so we defer the Adroit results to Supplement 9.1.

Evaluation Metrics After training on preference datasets, we infer the rewards r_t, for all transitions in the full offline dataset as discussed in Section 3. We then evaluate alignment of our learned rewards to the given preference criteria via two metrics: 1) Pearson correlation between inferred rewards and the environment rewards and 2) policy evaluation returns after offline RL training with the reward inferred offline dataset. The first metric, used also by Choi et al. (2024); Zhang et al. (2024); Liu et al. (2025), is valid because the preference criteria given to the human labelers closely aligns with the crafted environment reward functions (e.g., hopper Gym rewards velocity and stability, matching labeler instructions from Kim et al. (2023)). Thus, correlation with environment rewards serves as a proxy for adherence to preference labels.

For the policy evaluation returns, we conduct offline RL training with the state-of-the art Implicit Q-Learning (IQL) algorithm (Kostrikov et al., 2022), as in several prior PbRL works (Kim et al., 2023; Kostrikov et al., 2022). We adapt the OfflineRL-kit IQL implementation for our purposes (Sun, 2023), and we match preprocessing steps and hyperparameters to the recommended values in (Kostrikov et al., 2022; Kim et al., 2023) (Supplement 12). We train SARA+IQL and baselines on 8 seeds with multiple evaluation episodes (see Supplement 13.2 for reward normalization method and reward reporting method). We also provide our results for the oracle IQL, which uses the true environmental rewards rather than preference based rewards.

We compare against the following baselines. The first two baselines (PT, PT+ADT) learn a reward model from the preference dataset and then conduct IQL training. The last baseline does not learn an explicit reward model (DPPO).

Table 1: Average normalized policy evaluation rewards (8 seeds) under different human preference mistake rates. Oracle IQL results are constant across mistake rates and shown once in grey. Values in **bold** are the highest per row; underlined are within 1% of the best. The $\pm$ denotes standard deviation.

Task	Err Rate	Oracle	PT	PT+ADT	DPPO	SARA
hop-med-replay	0%	92.26 $\pm$13.6	74.48 $\pm$21.3	80.24 $\pm$16.1	68.98 $\pm$18.4	**84.68** $\pm$**3.1**
	10%		**86.31** $\pm$**7.9**	77.14 $\pm$18.5	70.76 $\pm$16.6	83.66 $\pm$3.5
	20%		49.77 $\pm$25.7	62.87 $\pm$24.0	68.67 $\pm$19.8	**82.94** $\pm$**5.8**
	40%		58.72 $\pm$17.9	53.87 $\pm$20.9	32.51 $\pm$23.2	**65.82** $\pm$**28.9**
hop-med-expert	0%	80.82 $\pm$44.5	89.64 $\pm$28.3	71.33 $\pm$40.6	**108.09** $\pm$**10.8**	80.45 $\pm$48.1
	10%		78.54 $\pm$30.1	80.69 $\pm$27.3	**100.32** $\pm$**20.4**	84.95 $\pm$32.4
	20%		68.14 $\pm$36.2	79.02 $\pm$21.0	28.92 $\pm$29.1	**85.16** $\pm$**17.0**
	40%		53.10 $\pm$24.9	70.00 $\pm$29.2	55.11 $\pm$8.2	**83.38** $\pm$**26.2**
walker2d-med-replay	0%	77.53 $\pm$15.5	74.43 $\pm$8.0	75.68 $\pm$8.3	47.21 $\pm$28.0	**78.21** $\pm$**5.8**
	10%		74.59 $\pm$6.7	64.42 $\pm$28.2	47.18 $\pm$27.0	**78.18** $\pm$**7.9**
	20%		71.73 $\pm$10.7	74.42 $\pm$12.6	41.00 $\pm$26.8	**76.29** $\pm$**13.2**
	40%		61.52 $\pm$19.3	67.86 $\pm$16.3	28.07 $\pm$27.9	**68.32** $\pm$**18.6**
walker2d-med-expert	0%	107.57 $\pm$8.5	109.74 $\pm$1.1	**109.98** $\pm$**1.0**	108.73 $\pm$0.4	108.35 $\pm$5.4
	10%		**109.89** $\pm$**1.1**	109.85 $\pm$3.5	108.75 $\pm$0.4	108.66 $\pm$3.6
	20%		109.37 $\pm$1.5	**109.53** $\pm$**1.6**	108.78 $\pm$0.4	108.37 $\pm$5.7
	40%		93.69 $\pm$16.9	89.83 $\pm$18.7	108.55 $\pm$0.5	**109.02** $\pm$**4.2**
kitchen-partial	0%	44.88 $\pm$31.4	59.45 $\pm$15.6	61.68 $\pm$15.2	40.39 $\pm$18.9	**64.84** $\pm$**13.2**
	10%		59.30 $\pm$18.2	60.27 $\pm$15.0	37.27 $\pm$17.5	**62.50** $\pm$**14.2**
	20%		58.55 $\pm$18.6	60.55 $\pm$16.7	38.44 $\pm$19.3	**64.18** $\pm$**15.4**
	40%		50.86 $\pm$21.7	**58.67** $\pm$**18.7**	36.84 $\pm$17.5	54.69 $\pm$23.8
kitchen-mixed	0%	54.02 $\pm$16.4	53.32 $\pm$9.8	**53.48** $\pm$**9.7**	43.63 $\pm$17.9	50.51 $\pm$6.4
	10%		**53.36** $\pm$**9.7**	48.71 $\pm$13.8	44.96 $\pm$20.1	50.27 $\pm$7.9
	20%		44.65 $\pm$16.9	41.60 $\pm$20.5	46.05 $\pm$18.4	**49.02** $\pm$**13.5**
	40%		**49.53** $\pm$**19.8**	46.41 $\pm$20.5	49.30 $\pm$14.8	42.73 $\pm$16.3

- **Preference Transformer (PT):** As in our model, PT uses a transformer backbone (Kim et al., 2023). Unlike our model, PT learns an explicit reward model with a BT based loss.

- **PT with Adaptive Denoising Training (PT+ADT):** We introduce this novel application of ADT as a baseline. In each training step, ADT drops a $\tau(t)$ fraction of queries with the largest cross-entropy loss, where $\tau(t) = \min(\gamma t, \tau_{max})$ (Wang et al., 2021). We set $\tau_{max} = 0.3$ and $\gamma = 0.003$ for our datasets. Prior works have considered ADT in the setting of iterative online human feedback (Cheng et al., 2024), but to our knowledge we are the first to apply ADT to learning the PT reward model.

- **Direct Preference-based Policy Optimization (DPPO):** As in our model, DPPO relies on contrastive learning and does not learn an explicit reward model. However, the contrastive learning is used to learn the policy directly and aims to align policy predictions with inferred preferred trajectories (An et al., 2023) (see Section 2 for additional details).

Preference data with labeling noise SARA shows competitive and stable performance across labeling noise rates (Table 1), statistically significant advantage over all baselines (Table 2), and superior correlations with environment rewards (Table 3).

Our method's robustness is evidenced by the consistency with error rate. As shown in Table 1, SARA's performance exhibits better stability across error rates while baselines degrade substantially

on specific datasets. For example, individual baselines can drop by up to 73% on specific datasets from 0% to 20% error, whereas SARA's degradation is minimal. Also, our novel implementation of PT+ADT provides significant improvement over PT.

Table 2: Wilcoxon signed-rank test comparing SARA against each baseline across 24 task-condition cells (6 tasks $\times$ 4 labeling error rates). W denotes the smaller of the positive and negative rank sums. Mean Diff is the average of (SARA $-$ baseline) over the 24 cells. All comparisons are statistically significant at $p < 0.01$.

Comparison	Wins / Losses	Mean Diff	W	p (two-sided)
SARA vs PT	16 / 8	$+5.5$	57	0.0065
SARA vs PT+ADT	18 / 6	$+4.9$	44	0.0016
SARA vs DPPO	18 / 6	$+14.9$	41	0.0011

To provide statistical support, we conduct a Wilcoxon signed-rank test across 24 task-condition cells (6 tasks $\times$ 4 labeling error rates). Table 2 confirms SARA's advantage is statistically significant against all baselines (p < 0.01).

Table 3: Pearson correlation coefficients between transition rewards and environment provided rewards (unknown at training). Each model was trained across 8 seeds; averages $\pm$ standard deviation are shown, with highest values in each row in bold.

Task	Error Rate	PT	PT+ADT	SARA
hop-medium-replay	0%	0.04 ($\pm$0.03)	0.08 ($\pm$0.06)	**0.39** ($\pm$**0.04**)
	10%	0.08 ($\pm$0.03)	0.06 ($\pm$0.08)	**0.19** ($\pm$**0.08**)
	20%	0.03 ($\pm$0.03)	0.04 ($\pm$0.05)	**0.36** ($\pm$**0.05**)
	40%	-0.04 ($\pm$0.02)	-0.03 ($\pm$0.06)	**0.02** ($\pm$**0.22**)
hop-medium-expert	0%	-0.09 ($\pm$0.09)	0.14 ($\pm$0.10)	**0.55** ($\pm$**0.14**)
	10%	-0.01 ($\pm$0.08)	0.16 ($\pm$0.08)	**0.28** ($\pm$**0.36**)
	20%	0.08 ($\pm$0.07)	0.02 ($\pm$0.13)	**0.14** ($\pm$**0.55**)
	40%	0.04 ($\pm$0.05)	0.06 ($\pm$0.14)	**0.13** ($\pm$**0.38**)
walk-medium-replay	0%	0.34 ($\pm$0.08)	0.50 ($\pm$0.06)	**0.73** ($\pm$**0.02**)
	10%	0.27 ($\pm$0.06)	0.36 ($\pm$0.06)	**0.70** ($\pm$**0.03**)
	20%	0.19 ($\pm$0.03)	0.36 ($\pm$0.07)	**0.56** ($\pm$**0.20**)
	40%	0.04 ($\pm$0.02)	0.12 ($\pm$0.08)	**0.32** ($\pm$**0.23**)
walk-medium-expert	0%	0.50 ($\pm$0.09)	0.73 ($\pm$0.01)	**0.84** ($\pm$**0.05**)
	10%	0.33 ($\pm$0.07)	0.65 ($\pm$0.05)	**0.86** ($\pm$**0.03**)
	20%	0.11 ($\pm$0.07)	0.48 ($\pm$0.10)	**0.81** ($\pm$**0.05**)
	40%	-0.14 ($\pm$0.03)	-0.09 ($\pm$0.05)	**0.51** ($\pm$**0.37**)
kitchen-partial	0%	0.22 ($\pm$0.09)	0.13 ($\pm$0.07)	**0.39** ($\pm$**0.36**)
	10%	0.07 ($\pm$0.08)	-0.01 ($\pm$0.07)	**0.36** ($\pm$**0.31**)
	20%	-0.10 ($\pm$0.06)	-0.15 ($\pm$0.11)	**0.30** ($\pm$**0.28**)
	40%	-0.15 ($\pm$0.09)	-0.18 ($\pm$0.13)	**0.22** ($\pm$**0.38**)
kitchen-mixed	0%	0.01 ($\pm$0.08)	-0.10 ($\pm$0.11)	**0.06** ($\pm$**0.35**)
	10%	-0.26 ($\pm$0.08)	-0.34 ($\pm$0.06)	**-0.14** ($\pm$**0.33**)
	20%	-0.26 ($\pm$0.17)	-0.44 ($\pm$0.06)	**0.03** ($\pm$**0.35**)
	40%	-0.24 ($\pm$0.08)	-0.49 ($\pm$0.07)	**0.02** ($\pm$**0.33**)

Correlation with environment transition rewards SARA demonstrates substantially better Pearson correlation with environment rewards compared to baselines at all error rates examined (Table 3). We conducted this analysis on full offline datasets at the transition level. Note that DPPO is excluded as it is a reward-free method.

This correlation advantage does not always translate to superior policy returns — on hopper-medium-expert at 0%, PT achieves better policy returns despite lower reward correlation, likely because high-quality BT rewards on expert-heavy data can outperform environment rewards for policy learning. SARA trades this potential upside for consistency: by focusing on consensus signals rather than fine-grained rankings, its performance does not degrade as annotation quality decreases. Thus, SARA does not displace BT reward models in high quality data scenarios, but offers a more robust alternative when labelers are non-experts.

5 A mechanistic analysis of SARA's robustness to noise

In the BT approach, a reward model is learned explicitly by maximizing likelihood of observed preferences: $\max_r \sum_{(i,j)} y_{ij} \log P[\sigma_i \succ \sigma_j; r]$. Then each mislabeled pair (i, j) causes direct corruption by making the gradient point in the opposite direction: $\nabla_r \log P[\sigma_j \succ \sigma_i; r] = -\gamma \nabla_r \log P[\sigma_i \succ \sigma_j; r]$. The coefficient $\gamma = \frac{\text{sigmoid}(r(\sigma_i) - r(\sigma_j))}{\text{sigmoid}(-(r(\sigma_i) - r(\sigma_j)))}$ is always positive and blows up for large reward differences.

In the SARA encoder, we have a first Transformer encoder which encodes each trajectory before the subset aggregation. The second Transformer then encodes subsets of each class. The contrastive objective drives the following:

- **Encoder 1** places low attention weight on portions of mislabeled trajectories that resemble the non-preferred set. It focuses instead on transitions shared by the majority of correctly labeled preferred trajectories.

Figure 2: T-SNE embedding of the latents for the hopper-medium-replay-v2 preference data, either colored by preference (left) or true reward (right).

- **Encoder 2** aggregates these per-trajectory latents into a consensus representation that maximally separates the two sets.

Figure 2 shows t-SNE embeddings of the SARA latents for the human-labeled hopper-medium-replay-v2 dataset, colored by preference label (left) and by true environment reward (right). SARA largely separates preferred from non-preferred trajectories. Importantly, a number of trajectories that are *labeled* preferred have low true reward. Comparing the two panels, these low-reward trajectories sit far from z_p^*, in the cluster at the top, even though the encoder never observes the environment reward. The encoder achieves this because such trajectories, despite their preferred label, share little similarity with the bulk of the other preferred trajectories, so the contrastive objective does not pull them toward the preferred set representation. As a result, z_p^* captures the consensus pattern of the high-quality preferred behavior and stays robust to, rather than corrupted by, these poor-quality trajectories.

Ablation To validate the set-based mechanism, we ablate it by performing contrastive learning on individual trajectory representations (BT Contrastive). Table 4 shows this leads to significantly lower and less stable returns, confirming that set-level encoding is key to SARA's robustness. BT Contrastive includes the following steps: 1) The transformer encodes the trajectories $\sigma_{p,i}$ and $\sigma_{n,i}$ to $\mathbf{u}_{p,i}$ and $\mathbf{u}_{n,i}$. The contrastive learning is done between all pairs of $\mathbf{u}$ individual trajectory encodings (not set encodings). Then 2) we learn a BT reward model, r_ψ, using the given preference set labels and their learned latents: $P[\sigma_{p,i} \succ \sigma_{n,i}; \psi] = P[\mathbf{u}_{p,i} \succ \mathbf{u}_{n,i}; \psi]$. In step 1 we match the encoder capacity to the original SARA encoder.

As an exception to the performance degradation, we see that BT Contrastive is on par with SARA on hopper-medium-expert at 20%. This is perhaps due to having many expert trajectories in this

Table 4: Comparison of SARA and BT Contrastive. Average normalized policy evaluation rewards (8 seeds) under different human preference mistake rates. Values in **bold** are the highest per row; underlined are within 1% of the best. The $\pm$ denotes standard deviation.

Task	Error Rate	SARA	BT Contrastive
hopper-med-replay	10%	**83.66** ($\pm$3.5)	65.21 ($\pm$22.3)
	20%	**82.94** ($\pm$5.8)	64.19 ($\pm$22.0)
	40%	**65.82** ($\pm$28.9)	60.03 ($\pm$25.8)
hopper-med-expert	10%	**84.95** ($\pm$32.4)	80.65 ($\pm$29.4)
	20%	85.16 ($\pm$17.0)	**86.93** ($\pm$21.8)
	40%	**83.38** ($\pm$26.2)	79.92 ($\pm$27.9)
walker2d-med-replay	10%	**78.18** ($\pm$7.9)	66.13 ($\pm$15.2)
	20%	**76.29** ($\pm$13.2)	57.17 ($\pm$23.0)
	40%	**68.32** ($\pm$18.6)	64.94 ($\pm$16.1)
walker2d-med-expert	10%	108.66 ($\pm$3.7)	**109.51** ($\pm$0.7)
	20%	108.37 ($\pm$5.7)	**109.34** ($\pm$1.3)
	40%	**109.02** ($\pm$4.2)	107.90 ($\pm$9.2)

dataset. This result consistent with analysis by Sun et al. (2025), who notes that BT models can still perform well when annotation quality is high.

6 Conclusion

Summary   SARA is a novel algorithm that prioritizes robustness by estimating preference-based rewards via similarity with a contrastively learned latent. Rather than relying on BT-based rewards, SARA assumes presence of noisy labeling and learns a representation of preferences. SARA shows comparable or improved performance over SOTA baselines on preference sets between 0–40% label error rate, with statistically significant advantages confirmed via Wilcoxon signed-rank test ($p < 0.01$). SARA outperforms BT based models on correlation with environmental rewards, indicating better alignment with the preference criteria given to labelers.

Future work   Our problem setup is one specific preference criteria per task; Kim et al. (2023); An et al. (2023) provide the criteria given to their labelers. However, SARA can be straight-forwardly applied towards the problem of heterogenous preference criteria. For our problem setup, we assumed two subset categories for Transformer Encoder 2, *preferred* and *non-preferred*. With multiple criteria, such as *preferred-fast*, *preferred-slow*, *non-preferred*, we would now have three categories which we train contrastively. Testing this would require creating multi-criteria RL preference datasets; we recommend this as a direction for future work.

Additionally, SARA has the advantage that it does not require preference pairs as in the BT model. This is particularly useful in scenarios where a human prefers some small subset of trajectories in a pool of samples. We suggest experiments on such potential datasets as another avenue to explore.

Limitations   Adapting SARA for online streaming preferences is an important direction for future work. Our exclusive use of D4RL environments is a limitation; evaluation on additional benchmarks is recommended. Unlike BT, SARA does not guarantee transitive preference orderings. However, this is mitigated by the well-documented intransitivity of human preferences, and prior works have argued that BT's transitivity is actually a BT limitation (page 2, top). We emphasize that SARA is not intended to displace BT in all scenarios; BT performs well on high-quality data with expert-heavy trajectories (Section 4). SARA's primary strength is consistency to labeler error whereas baselines fluctuate.

References

Hopper - Gym Documentation. URL https://www.gymlibrary.dev/environments/mujoco/hopper/.

TransformerEncoder — PyTorch 2.7 documentation. URL https://docs.pytorch.org/docs/stable/generated/torch.nn.TransformerEncoder.html.

Walker2D - Gym Documentation. URL https://www.gymlibrary.dev/environments/mujoco/walker2d/.

Gaon An, Junhyeok Lee, Xingdong Zuo, Norio Kosaka, Kyung-Min Kim, and Hyun Oh Song. Direct Preference-based Policy Optimization without Reward Modeling. In A. Oh, T. Naumann, A. Globerson, K. Saenko, M. Hardt, and S. Levine (eds.), *Advances in Neural Information Processing Systems*, volume 36, pp. 70247–70266. Curran Associates, Inc., 2023. URL https://proceedings.neurips.cc/paper_files/paper/2023/file/de8bd6b2b01cfa788e63f62e5b9a99b9-Paper-Conference.pdf.

Mohammad Azar, Zhaohan Daniel Guo, Bilal Piot, Remi Munos, Mark Rowland, Michal Valko, and Daniele Calandriello. A general theoretical paradigm to understand learning from human preferences. In Sanjoy Dasgupta, Stephan Mandt, and Yingzhen Li (eds.), *Proceedings of The 27th International Conference on Artificial Intelligence and Statistics*, volume 238 of *Proceedings of Machine Learning Research*, pp. 4447–4455. PMLR, 02–04 May 2024. URL https://proceedings.mlr.press/v238/gheshlaghi-azar24a.html.

Xue Bin Peng, Erwin Coumans, Tingnan Zhang, Tsang-Wei Lee, Jie Tan, and Sergey Levine. Learning Agile Robotic Locomotion Skills by Imitating Animals. In *Robotics: Science and Systems XVI*. Robotics: Science and Systems Foundation, July 2020. ISBN 978-0-9923747-6-1. DOI: 10.15607/RSS.2020.XVI.064. URL http://www.roboticsproceedings.org/rss16/p064.pdf.

Ralph Allan Bradley and Milton E. Terry. Rank Analysis of Incomplete Block Designs: I. The Method of Paired Comparisons. *Biometrika*, 39(3/4):324–345, 1952. ISSN 0006-3444. DOI: 10.2307/2334029. URL https://www.jstor.org/stable/2334029. Publisher: [Oxford University Press, Biometrika Trust].

Ting Chen, Simon Kornblith, Mohammad Norouzi, and Geoffrey Hinton. A Simple Framework for Contrastive Learning of Visual Representations. In *Proceedings of the 37th International Conference on Machine Learning*, pp. 1597–1607. PMLR, November 2020. URL https://proceedings.mlr.press/v119/chen20j.html. ISSN: 2640-3498.

Jie Cheng, Gang Xiong, Xingyuan Dai, Qinghai Miao, Yisheng Lv, and Fei-Yue Wang. RIME: robust preference-based reinforcement learning with noisy preferences. In *Proceedings of the 41st International Conference on Machine Learning*, volume 235 of *ICML'24*, pp. 8229–8247, Vienna, Austria, July 2024. JMLR.org.

Heewoong Choi, Sangwon Jung, Hongjoon Ahn, and Taesup Moon. Listwise reward estimation for offline preference-based reinforcement learning. In *Proceedings of the 41st International Conference on Machine Learning*, volume 235 of *ICML'24*, pp. 8651–8671, Vienna, Austria, July 2024. JMLR.org.

Paul F Christiano, Jan Leike, Tom Brown, Miljan Martic, Shane Legg, and Dario Amodei. Deep Reinforcement Learning from Human Preferences. In I. Guyon, U. Von Luxburg, S. Bengio, H. Wallach, R. Fergus, S. Vishwanathan, and R. Garnett (eds.), *Advances in Neural Information Processing Systems*, volume 30. Curran Associates, Inc., 2017. URL https://proceedings.neurips.cc/paper_files/paper/2017/file/d5e2c0adad503c91f91df240d0cd4e49-Paper.pdf.

Thomas Coste, Usman Anwar, Robert Kirk, and David Krueger. Reward model ensembles help mitigate overoptimization. In *The Twelfth International Conference on Learning Representations*, 2024. URL https://openreview.net/forum?id=dcjtMYkpXx.

Christoph Dann, Yishay Mansour, and Mehryar Mohri. Reinforcement learning can be more efficient with multiple rewards. In Andreas Krause, Emma Brunskill, Kyunghyun Cho, Barbara Engelhardt, Sivan Sabato, and Jonathan Scarlett (eds.), *Proceedings of the 40th International Conference on Machine Learning*, volume 202 of *Proceedings of Machine Learning Research*, pp. 6948–6967. PMLR, 23–29 Jul 2023. URL https://proceedings.mlr.press/v202/dann23a.html.

DeepSeek-AI, Daya Guo, Dejian Yang, and et al. DeepSeek-R1: Incentivizing Reasoning Capability in LLMs via Reinforcement Learning, January 2025. URL http://arxiv.org/abs/2501.12948. arXiv:2501.12948 [cs].

Coline Devin, Pieter Abbeel, Trevor Darrell, and Sergey Levine. Deep object-centric representations for generalizable robot learning. In *2018 IEEE International Conference on Robotics and Automation (ICRA)*, pp. 7111–7118, 2018. DOI: 10.1109/ICRA.2018.8461196.

Yann Dubois, Chen Xuechen Li, Rohan Taori, Tianyi Zhang, Ishaan Gulrajani, Jimmy Ba, Carlos Guestrin, Percy S Liang, and Tatsunori B Hashimoto. AlpacaFarm: A Simulation Framework for Methods that Learn from Human Feedback. In A. Oh, T. Naumann, A. Globerson, K. Saenko, M. Hardt, and S. Levine (eds.), *Advances in Neural Information Processing Systems*, volume 36, pp. 30039–30069. Curran Associates, Inc., 2023. URL https://proceedings.neurips.cc/paper_files/paper/2023/file/5fc47800ee5b30b8777fdd30abcaaf3b-Paper-Conference.pdf.

Alejandro Escontrela, Xue Bin Peng, Wenhao Yu, Tingnan Zhang, Atil Iscen, Ken Goldberg, and Pieter Abbeel. Adversarial Motion Priors Make Good Substitutes for Complex Reward Functions. In *2022 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, pp. 25–32, October 2022. DOI: 10.1109/IROS47612.2022.9981973. URL https://ieeexplore.ieee.org/document/9981973/. ISSN: 2153-0866.

Farama Foundation. MuJoCo environments – Gymnasium documentation, 2024. URL https://gymnasium.farama.org/environments/mujoco/. Accessed: 2025.

Justin Fu, Aviral Kumar, Ofir Nachum, George Tucker, and Sergey Levine. D4RL: Datasets for Deep Data-Driven Reinforcement Learning, February 2021. URL http://arxiv.org/abs/2004.07219. arXiv:2004.07219 [cs].

Ritwik Gupta. D4RL: Building Better Benchmarks for Offline Reinforcement Learning. URL http://bair.berkeley.edu/blog/2020/06/25/D4RL/.

Bo Han, Quanming Yao, Xingrui Yu, Gang Niu, Miao Xu, Weihua Hu, Ivor Tsang, and Masashi Sugiyama. Co-teaching: Robust training of deep neural networks with extremely noisy labels. In S. Bengio, H. Wallach, H. Larochelle, K. Grauman, N. Cesa-Bianchi, and R. Garnett (eds.), *Advances in Neural Information Processing Systems*, volume 31. Curran Associates, Inc., 2018. URL https://proceedings.neurips.cc/paper_files/paper/2018/file/a19744e268754fb0148b017647355b7b-Paper.pdf.

Donald Hejna, Lerrel Pinto, and Pieter Abbeel. Hierarchically decoupled imitation for morphological transfer. In Hal Daumé III and Aarti Singh (eds.), *Proceedings of the 37th International Conference on Machine Learning*, volume 119 of *Proceedings of Machine Learning Research*, pp. 4159–4171. PMLR, 13–18 Jul 2020. URL https://proceedings.mlr.press/v119/hejna20a.html.

Joey Hejna and Dorsa Sadigh. Inverse Preference Learning: Preference-based RL without a Reward Function. In A. Oh, T. Naumann, A. Globerson, K. Saenko,

M. Hardt, and S. Levine (eds.), *Advances in Neural Information Processing Systems*, volume 36, pp. 18806–18827. Curran Associates, Inc., 2023. URL https://proceedings.neurips.cc/paper_files/paper/2023/file/3be7859b36d9440372cae0a293f2e4cc-Paper-Conference.pdf.

Joey Hejna, Rafael Rafailov, Harshit Sikchi, Chelsea Finn, Scott Niekum, W. Bradley Knox, and Dorsa Sadigh. Contrastive preference learning: Learning from human feedback without reinforcement learning. In *The Twelfth International Conference on Learning Representations*, 2024. URL https://openreview.net/forum?id=iX1RjVQODj.

Donald Joseph Hejna III and Dorsa Sadigh. Few-shot preference learning for human-in-the-loop RL. In *6th Annual Conference on Robot Learning*, 2022. URL https://openreview.net/forum?id=IKC5TfXLuW0.

Yachen Kang, Diyuan Shi, Jinxin Liu, Li He, and Donglin Wang. Beyond Reward: Offline Preference-guided Policy Optimization. In *Proceedings of the 40th International Conference on Machine Learning*, pp. 15753–15768. PMLR, July 2023. URL https://proceedings.mlr.press/v202/kang23b.html. ISSN: 2640-3498.

Changyeon Kim, Jongjin Park, Jinwoo Shin, Honglak Lee, Pieter Abbeel, and Kimin Lee. Preference Transformer: Modeling Human Preferences using Transformers for RL, March 2023. URL http://arxiv.org/abs/2303.00957. arXiv:2303.00957 [cs].

Minu Kim, Yongsik Lee, Sehyeok Kang, Jihwan Oh, Song Chong, and Se-Young Yun. Preference Alignment with Flow Matching. In A. Globerson, L. Mackey, D. Belgrave, A. Fan, U. Paquet, J. Tomczak, and C. Zhang (eds.), *Advances in Neural Information Processing Systems*, volume 37, pp. 35140–35164. Curran Associates, Inc., 2024. URL https://proceedings.neurips.cc/paper_files/paper/2024/file/3df874367ce2c43891aab1ab23ae6959-Paper-Conference.pdf.

Ilya Kostrikov, Ashvin Nair, and Sergey Levine. OFFLINE REINFORCEMENT LEARNING WITH IMPLICIT Q-LEARNING. 2022.

Sachit Kuhar, Shuo Cheng, Shivang Chopra, Matthew Bronars, and Danfei Xu. Learning to Discern: Imitating Heterogeneous Human Demonstrations with Preference and Representation Learning. In *Proceedings of The 7th Conference on Robot Learning*, pp. 1437–1449. PMLR, December 2023. URL https://proceedings.mlr.press/v229/kuhar23a.html. ISSN: 2640-3498.

Michael Laskin, Denis Yarats, Hao Liu, Kimin Lee, Albert Zhan, Kevin Lu, Catherine Cang, Lerrel Pinto, and Pieter Abbeel. URLB: Unsupervised reinforcement learning benchmark. In *Thirty-fifth Conference on Neural Information Processing Systems Datasets and Benchmarks Track (Round 2)*, 2021. URL https://openreview.net/forum?id=lwrPkQP_is.

Kimin Lee, Laura Smith, Anca Dragan, and Pieter Abbeel. B-pref: Benchmarking preference-based reinforcement learning. In *Thirty-fifth Conference on Neural Information Processing Systems Datasets and Benchmarks Track (Round 1)*, 2021a. URL https://openreview.net/forum?id=ps95-mkHF_.

Kimin Lee, Laura M. Smith, and Pieter Abbeel. PEBBLE: Feedback-Efficient Interactive Reinforcement Learning via Relabeling Experience and Unsupervised Pre-training. In *Proceedings of the 38th International Conference on Machine Learning*, pp. 6152–6163. PMLR, July 2021b. URL https://proceedings.mlr.press/v139/lee21i.html. ISSN: 2640-3498.

Timothy P. Lillicrap, Jonathan J. Hunt, Alexander Pritzel, Nicolas Heess, Tom Erez, Yuval Tassa, David Silver, and Daan Wierstra. Continuous control with deep reinforcement learning. In Yoshua Bengio and Yann LeCun (eds.), *ICLR*, 2016. URL http://dblp.uni-trier.de/db/conf/iclr/iclr2016.html#LillicrapHPHETS15.

Runze Liu, Yali Du, Fengshuo Bai, Jiafei Lyu, and Xiu Li. PEARL: Zero-shot cross-task preference alignment and robust reward learning for robotic manipulation. In Ruslan Salakhutdinov, Zico Kolter, Katherine Heller, Adrian Weller, Nuria Oliver, Jonathan Scarlett, and Felix Berkenkamp (eds.), *Proceedings of the 41st International Conference on Machine Learning*, volume 235 of *Proceedings of Machine Learning Research*, pp. 30946–30964. PMLR, 21–27 Jul 2024. URL https://proceedings.mlr.press/v235/liu24o.html.

Ziang Liu, Junjie Xu, Xingjiao Wu, Jing Yang, and Liang He. Multi-type preference learning: Empowering preference-based reinforcement learning with equal preferences. In *2025 IEEE International Conference on Robotics and Automation (ICRA)*, pp. 1163–1169, 2025. DOI: 10.1109/ICRA55743.2025.11127694.

Michal Lukasik, Srinadh Bhojanapalli, Aditya Krishna Menon, and Sanjiv Kumar. Does label smoothing mitigate label noise? In *Proceedings of the 37th International Conference on Machine Learning*, volume 119 of *ICML'20*, pp. 6448–6458. JMLR.org, July 2020.

Kenneth O. May. Intransitivity, Utility, and the Aggregation of Preference Patterns. *Econometrica*, 22(1):1–13, 1954. URL https://onlinelibrary.wiley.com/doi/abs/0012-9682(195401)22:1<1:IUATAO>2.0.CO;2-P.

Takahiro Miki, Joonho Lee, Jemin Hwangbo, Lorenz Wellhausen, Vladlen Koltun, and Marco Hutter. Learning robust perceptive locomotion for quadrupedal robots in the wild. *Science Robotics*, 7(62):eabk2822, January 2022. DOI: 10.1126/scirobotics.abk2822. URL https://www.science.org/doi/10.1126/scirobotics.abk2822. Publisher: American Association for the Advancement of Science.

Rémi Munos, Michal Valko, Daniele Calandriello, Mohammad Gheshlaghi Azar, Mark Rowland, Zhaohan Daniel Guo, Yunhao Tang, Matthieu Geist, Thomas Mesnard, Côme Fiegel, Andrea Michi, Marco Selvi, Sertan Girgin, Nikola Momchev, Olivier Bachem, Daniel J. Mankowitz, Doina Precup, and Bilal Piot. Nash learning from human feedback. In *Proceedings of the 41st International Conference on Machine Learning (ICML)*, volume 235 of *Proceedings of Machine Learning Research*, pp. 36743–36768. PMLR, 2024.

OpenAI, Josh Achiam, Steven Adler, and et al. GPT-4 Technical Report, March 2024. URL http://arxiv.org/abs/2303.08774. arXiv:2303.08774 [cs].

Long Ouyang, Jeffrey Wu, Xu Jiang, and et al. Training language models to follow instructions with human feedback. In S. Koyejo, S. Mohamed, A. Agarwal, D. Belgrave, K. Cho, and A. Oh (eds.), *Advances in Neural Information Processing Systems*, volume 35, pp. 27730–27744. Curran Associates, Inc., 2022. URL https://proceedings.neurips.cc/paper_files/paper/2022/file/b1efde53be364a73914f58805a001731-Paper-Conference.pdf.

Rafael Rafailov, Archit Sharma, Eric Mitchell, Christopher D Manning, Stefano Ermon, and Chelsea Finn. Direct Preference Optimization: Your Language Model is Secretly a Reward Model. In A. Oh, T. Naumann, A. Globerson, K. Saenko, M. Hardt, and S. Levine (eds.), *Advances in Neural Information Processing Systems*, volume 36, pp. 53728–53741. Curran Associates, Inc., 2023. URL https://proceedings.neurips.cc/paper_files/paper/2023/file/a85b405ed65c6477a4fe8302b5e06ce7-Paper-Conference.pdf.

Dorsa Sadigh, Anca Dragan, Shankar Sastry, and Sanjit Seshia. Active Preference-Based Learning of Reward Functions. In *Robotics: Science and Systems XIII*. Robotics: Science and Systems Foundation, July 2017. ISBN 978-0-9923747-3-0. DOI: 10.15607/RSS.2017.XIII.053. URL http://www.roboticsproceedings.org/rss13/p53.pdf.

Hwanjun Song, Minseok Kim, Dongmin Park, Yooju Shin, and Jae-Gil Lee. Learning from noisy labels with deep neural networks: A survey. *IEEE Transactions on Neural Networks and Learning Systems*, 34(11):8135–8153, 2023. DOI: 10.1109/TNNLS.2022.3152527.

Hao Sun, Yunyi Shen, and Jean-Francois Ton. Rethinking reward modeling in preference-based large language model alignment. In *The Thirteenth International Conference on Learning Representations*, 2025. URL https://openreview.net/forum?id=rfdblE10qm.

Yihao Sun. Offlinerl-kit: An elegant pytorch offline reinforcement learning library. https://github.com/yihaosun1124/OfflineRL-Kit, 2023.

Richard S. Sutton and Andrew G. Barto. Reinforcement learning: An introduction. In *Reinforcement Learning: An Introduction*, chapter 17.6 Reinforcement Learning and the Future of Artificial Intelligence. MIT Press, Cambridge, MA, 2 edition, 2018. Chapter 17.6.

Yunhao Tang, Zhaohan Daniel Guo, Zeyu Zheng, Daniele Calandriello, Remi Munos, Mark Rowland, Pierre Harvey Richemond, Michal Valko, Bernardo Avila Pires, and Bilal Piot. Generalized preference optimization: A unified approach to offline alignment. In Ruslan Salakhutdinov, Zico Kolter, Katherine Heller, Adrian Weller, Nuria Oliver, Jonathan Scarlett, and Felix Berkenkamp (eds.), *Proceedings of the 41st International Conference on Machine Learning*, volume 235 of *Proceedings of Machine Learning Research*, pp. 47725–47742. PMLR, 21–27 Jul 2024. URL https://proceedings.mlr.press/v235/tang24b.html.

Saran Tunyasuvunakool, Alistair Muldal, Yotam Doron, Siqi Liu, Steven Bohez, Josh Merel, Tom Erez, Timothy Lillicrap, Nicolas Heess, and Yuval Tassa. dm_control: Software and tasks for continuous control. *Software Impacts*, 6:100022, 2020. ISSN 2665-9638. DOI: https://doi.org/10.1016/j.simpa.2020.100022. URL https://www.sciencedirect.com/science/article/pii/S2665963820300099.

Amos Tversky. Intransitivity of preferences. *Psychological Review*, 76(1):31–48, January 1969. ISSN 1939-1471, 0033-295X. DOI: 10.1037/h0026750. URL https://doi.apa.org/doi/10.1037/h0026750.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Ł ukasz Kaiser, and Illia Polosukhin. Attention is All you Need. In I. Guyon, U. Von Luxburg, S. Bengio, H. Wallach, R. Fergus, S. Vishwanathan, and R. Garnett (eds.), *Advances in Neural Information Processing Systems*, volume 30. Curran Associates, Inc., 2017. URL https://proceedings.neurips.cc/paper_files/paper/2017/file/3f5ee243547dee91fbd053c1c4a845aa-Paper.pdf.

Wenjie Wang, Fuli Feng, Xiangnan He, Liqiang Nie, and Tat-Seng Chua. Denoising Implicit Feedback for Recommendation. In *Proceedings of the 14th ACM International Conference on Web Search and Data Mining*, pp. 373–381, Virtual Event Israel, March 2021. ACM. ISBN 978-1-4503-8297-7. DOI: 10.1145/3437963.3441800. URL https://dl.acm.org/doi/10.1145/3437963.3441800.

Christian Wirth, Riad Akrour, Gerhard Neumann, and Johannes Fürnkranz. A Survey of Preference-Based Reinforcement Learning Methods. *Journal of Machine Learning Research*, 18(136):1–46, 2017. URL http://jmlr.org/papers/v18/16-634.html.

Chenlu Ye, Wei Xiong, Yuheng Zhang, Hanze Dong, Nan Jiang, and Tong Zhang. Online Iterative Reinforcement Learning from Human Feedback with General Preference Model. In A. Globerson, L. Mackey, D. Belgrave, A. Fan, U. Paquet, J. Tomczak, and C. Zhang (eds.), *Advances in Neural Information Processing Systems*, volume 37, pp. 81773–81807. Curran Associates, Inc., 2024. URL https://proceedings.neurips.cc/paper_files/paper/2024/file/94d13c2401fe119e57ba325b6fe526e0-Paper-Conference.pdf.

Hongyi Zhang, Moustapha Cisse, Yann N Dauphin, and David Lopez-Paz. mixup: BEYOND EMPIRICAL RISK MINIMIZATION. 2018.

Yifan Zhang, Ge Zhang, Yue Wu, Kangping Xu, and Quanquan Gu. Beyond bradley-terry models: A general preference model for language model alignment. In *Proceedings of the 42nd International Conference on Machine Learning (ICML)*, 2025. arXiv preprint arXiv:2410.02197.

Zhilong Zhang, Yihao Sun, Junyin Ye, Tian-Shuo Liu, Jiaji Zhang, and Yang Yu. Flow to better: Offline preference-based reinforcement learning via preferred trajectory generation. In *The Twelfth International Conference on Learning Representations*, 2024. URL https://openreview.net/forum?id=EG68RSznLT.

Henry Zhu, Justin Yu, Abhishek Gupta, Dhruv Shah, Kristian Hartikainen, Avi Singh, Vikash Kumar, and Sergey Levine. The ingredients of real world robotic reinforcement learning. In *International Conference on Learning Representations*, 2020. URL https://openreview.net/forum?id=rJe2syrtvS.

Daniel M. Ziegler, Nisan Stiennon, Jeffrey Wu, Tom B. Brown, Alec Radford, Dario Amodei, Paul Christiano, and Geoffrey Irving. Fine-Tuning Language Models from Human Preferences, January 2020. URL http://arxiv.org/abs/1909.08593. arXiv:1909.08593 [cs].

Supplementary Materials

The following content was not necessarily subject to peer review.

7 Sensitivity to Number of Subsets Per Category (parameter k)

As detailed in Section 5, our key innovation is to learn a representation for the **set** of preferred trajectories. The Transformer Encoder 2 of Figure 1 encodes a set of trajectories, where now trajectory representations within the set can attend to one another. We need at least one positive set encoding for each category (preferred and non-preferred) for the contrastive loss. This necessitates that we divide up the preferred trajectory encodings and non-preferred trajectory encodings in at minimum k=2 subsets. In each epoch, we shuffle the compositions of trajectories in each subset to avoid overfitting the representation to an exact subset composition. We used k=2 in all our experiments, but here we ablate the choice of k and show the model is not sensitive when k is low. We note that the k value is used as a training hyperparameter, not as an evaluation parameter. After training, we set k=1 (one set of preferred) and feed all preferred trajectories through the SARA encoder to infer $\mathbf{z}_\mathbf{p}^*$.

Table 5: Average normalized policy evaluation rewards (across 8 seeds), using human-labeled preference data (without mistakes). We vary the number of subsets k per category during training the SARA encoder. The $\pm$ denotes standard deviation.

Task	$k = 2$	$k = 3$	$k = 4$	$k = 16$
hopper-medium-replay-v2	84.68 (± 3.1)	85.00 (± 3.3)	84.48 (± 4.0)	76.78 (± 18.9)

When k is equal to the number of trajectories in each category (preferred or non-preferred), then one set is just a single trajectory. This is equivalent to contrastive learning on individual trajectories rather than sets of trajectories, as done in our ablation experiment in Section 5.

As we approach large k, we are approaching the regime of of contrastive learning between individual trajectories. Thus we see significant performance degradation at k=16. The results are not sensitive for lower values of k (i.e. 2,3,4).

8 Sensitivity to SARA reward parameters

We originally defined SARA rewards as follows: $r_t = \alpha \cos(z_t, z_p^*) - \beta \cos(z_t, z_n^*)$ with tunable weights α and β. We found that for the hopper-medium-replay-v2 dataset, the results are insensitive to these parameters as shown below.

Table 6: Performance comparison across different (α, β) settings. Here we show the average normalized policy evaluation rewards (across 8 seeds), using human-labeled preference data (without mistakes). The +- denotes standard deviation.

Task	$\alpha = 1, \beta = 0$	$\alpha = 0.5, \beta = 1$	$\alpha = 1, \beta = 0.5$	$\alpha = 0, \beta = 1$
hopper-medium-replay-v2	84.68 $\pm$ 3.1	83.96 $\pm$ 4.2	84.22 $\pm$ 3.5	83.90 $\pm$ 3.3

9 Additional offline RL results

9.1 Offline RL results on Adroit tasks

We also applied our framework to the Adroit tasks, with preference datasets for pen-cloned-v1 and pen-human-v1 provided by Kim et al. (2023). DPPO underperforms compared to other methods on pen-human-v1, but otherwise the mean evaluation policy rewards are similar across models (Tables

7, 8). Variance is also quite high for all models. This is explained by within seed variance among the 10 evaluation episodes at each epoch, presumably due to randomized initial start states, as opposed to across seed variance. Among the 10 evaluation episodes at each epoch, we acquire maximum normalized episode returns of 179 and minimum returns between -2 to -4.

Table 7: Average normalized policy evaluation rewards (across 8 seeds), using **human-labeled preference data with 20% label error rate**. Values in **bold** are best (highest reward) in each row. The $\pm$ denotes standard deviation.

Task	IQL (Oracle)	PT	PT+ADT	DPPO	SARA
pen-human-v1	85.19 (± 62.1)	81.91 (± 64.5)	79.42 (± 63.2)	71.99 (± 62.5)	**83.04** $(\pm \textbf{63.6})$
pen-cloned-v1	81.49 (± 62.6)	69.30 (± 63.8)	67.66 (± 64.1)	**72.64** $(\pm \textbf{64.4})$	69.78 (± 63.0)

Table 8: Average normalized policy evaluation rewards (across 8 seeds), using **human-labeled preference data**. Values in **bold** are best (highest reward) in each row. The $\pm$ denotes standard deviation.

Task	IQL (Oracle)	PT	PT+ADT	DPPO	SARA
pen-human-v1	85.19 (± 62.1)	80.84 (± 63.1)	**82.80** $(\pm \textbf{62.4})$	76.97 (± 64.3)	81.89 (± 63.2)
pen-cloned-v1	81.49 (± 62.6)	70.28 (± 64.6)	69.70 (± 63.8)	**72.13** $(\pm \textbf{64.5})$	69.72 (± 63.4)

10 Additional applications

Filtering low quality trajectories for downstream imitation learning As ground truth rewards may be unknown, we examine whether the SARA encoder can identify low quality trajectories from preference data. Human preference labels and ground truth rewards frequently do not align (Kim et al., 2023), so many poor quality trajectories may be labeled preferred ($y = 1$). Figure 2 shows a t-SNE plot of SARA learned latents for the human labeled hopper replay preference dataset from Kim et al. (2023). We exclude the neutral queries from the original preference dataset, but we otherwise do not corrupt or modify the dataset in any way. As encouraged by the constrastive learning objective, the encoder achieves good separation and clustering between *most* preferred and non-preferred trajectories, and the group embeddings $\mathbf{z}_p^*$ and $\mathbf{z}_n^*$ are centrally located within their respective clusters. However, some trajectories are not close to $\mathbf{z}_p^*$ nor $\mathbf{z}_n^*$, though they are labeled as such. Comparing the plots in Figure 2, we see that these separated trajectories exhibit a low ground truth reward. Therefore, the SARA encoder can learn overall patterns but it does not artificially align poor quality trajectories to the preferred set even when the human labelers designate them as preferred. We can further exploit the encoder results to filter low quality trajectories. After training the encoder, we merely need to filter out trajectories with large distance in latent space from both $\mathbf{z}_p^*$ and $\mathbf{z}_n^*$. Kuhar et al. (2023) notes that filtering should lead to a better policy in downstream IL. As IL is outside the scope of this work, we defer such analysis to future works.

Transfer of preferences to morphologically harder task We investigate whether the preference dataset for a morphologically simple task can be used to infer rewards for a harder task. We take the preference dataset from Kim et al. (2023) for trajectories from hopper-medium-replay-v2. Our goal is to learn the SARA encoder on this preference set and then infer rewards for the walker-medium-replay-v2 dataset. SARA reward inference relies on feeding walker trajectories into the learned encoder, so we map the state and action space dimensions of the hopper to that of the walker. We do so by crudely assuming that preferences for the hopper state-action trajectories can transfer to the additional degrees of freedom in the walker due to the symmetry of the joints (see Supplement 14 for details).

Figure 3: Walker2d IQL eval rewards, running average and 8 seeds (see Section 13.2). Shading indicates standard deviation. The policy is learned on the walker replay dataset. SARA rewards from training on hopper replay preferences perform almost as well as SARA rewards with training on the walker replay preferences.

After doubling the joint angles, velocities, and torques in the hopper replay preference set, we then train the SARA encoder with this modified set. Next we take the full offline walker replay set and infer rewards using this encoder learned from the hopper preferences. This cross-task transfer of preferences enables policy learning with these estimated rewards (Figure 3). Remarkably, the IQL learned policy from cross-task preferences performs only slightly worse than the SARA model using the walker replay preference set. Both exhibit lower variance than using the true task reward.

Hejna et al. (2020) investigated transfer learning of a policy from a simple agent to a more complex one with environment provided rewards, not preference aligned rewards. Liu et al. (2024) proposed an optimal transport method to transfer preferences, but their framework is limited to tasks with equivalent state-action space. To our knowledge, our cross-task preference transfer to a larger state-action space is novel, and we do so without any changes to the SARA architecture or hyperparameters.

Figure 4: Left: After training SARA encoder, we divide up the trajectories by their label (preferred vs non-preferred) and by the target location. Note that the training set has the extra hard target location for the non-preferred but not preferred. Target location is not explicitly fed into the model and many trajectories are the same between the two sets. Right: With task reward alone, the learned policy takes the shortest path going clockwise to the hard target location. Including the preference inferred award enables a learned policy traversing in counter-clockwise direction.

Online RL with reward shaping In contrast to previous sections, we now consider the scenario of some known but under-specified task reward. For instance, consider a robotics application in which a policy is trained to achieve some task, such as reaching an object. In many realistic applications,

such task-driven reward functions can result in policies that have undesirable patterns of movement, such as rapid or jerky actions (Escontrela et al., 2022). Such movements may not only be visually unappealing but can also damage the robot. Prior works employed complicated reward shaping techniques to overcome these issues (Miki et al., 2022). Here we test whether the SARA inferred rewards can shape the task reward in online RL learning.

We set up the following problem using the Deepmind Control Suite Reacher task (Tunyasuvunakool et al., 2020; Laskin et al., 2021). Let us assume a human labeler decided that counterclockwise movements are always preferable, perhaps due to a realistic engineering constraint or potential environmental obstructions limiting clockwise movement. The human labeler picks the preferred set of trajectories (all counterclockwise) for an easy target. The human labeler deems non-preferred any trajectories from the policy trained on the task reward. These are sometimes clockwise and sometimes counterclockwise depending on which has the fewest steps to target. Therefore, when the target is in the upper half, we have many trajectories for which the preferred and non-preferred sets overlap. This setup requires SARA to disentangle the preferred from non-preferred styles even when there are some strong similarities between the two groups.

The encoder is not explicitly given the counter-clockwise preference, so we evaluate what it implicitly learns by comparing with non-preferred movements. After training we split up trajectories by category (preferred vs non-preferred) and target location to view the similarity map shown in Figure 4. Despite overlaps between categories, SARA learns where preferred and non-preferred behaviors align or diverge. This result arises from the subset contrastive encoding and shuffling detailed in Section 3.

Next we test whether these learned patterns transfer to the harder task of the small target shown in Figure 4. We learn online using the Deep Deterministic Policy Gradient algorithm (Lillicrap et al., 2016). We add the known task reward to the SARA inferred reward. In the absence of our SARA inferred reward, the learned Reacher policy takes the most efficient path clockwise to the hard target (Figure 4). With our preference inferred reward, the policy takes the desired counterclockwise path even though it results in a lower task driven reward. The SARA framework achieves this even though the preferred set only includes the easy large target task.

This toy experiment illustrates our model's potential for the realistic preference driven goal of shaping an RL policy to conform with human desires. Such stylistic rewards may be both application specific and difficult to engineer, so inferring from preference data is a promising path forward.

11   Dataset details

Here we describe the details of the preference datasets and the full offline datasets used for our offline RL experiments (Section 4)

11.1   Preference datasets

For Mujoco locomotion and Adroit pen tasks, we use the preference datasets provided by Kim et al. (2023) from the PT human label repository. For the Franka Kitchen tasks, we use the preference datasets from An et al. (2023) from the DPPO human label repository. Both repositories are MIT licensed.

Kim et al. (2023) and An et al. (2023) created the preference datasets by sampling pairs of trajectories from the full offline datasets Fu et al. (2021). They named the preference datasets by the same name as the full offline datasets (e.g. hopper-medium-replay-v2 and so on). All trajectories are 100 timesteps in length. The replay datasets for hopper and walker have 500 trajectory pairs and all others have 100 pairs. The labelers are domain experts who are given specific criteria upon which to evaluate their preference for the trajectories. We refer the reader to the original works which state their preference criteria.

11.2   Full offline datasets

In our offline RL experiments, the policies for the SARA framework, all baselines, and the oracle are trained using the full offline D4RL datasets. The oracle uses the true environmental rewards provided in the datasets. In the case of the SARA framework and baseline models, each transition reward is computed using the respective models. Note all these models are non-Markovian, so each transition reward at time t is computed by feeding the trajectory up to and including time t into the models. For each model, we replace the dataset provided rewards with the computed transition rewards.

We refer to the work by Fu et al. (2021) for a thorough description of the full offline datasets. Here we summarize some key points as they relate to our work. Our experiments include hopper and walker2d locomotion tasks from Gym-Mujoco. The hopper has a 3 dimensional action space and 11 dimensional state space. The walker2d has a 6 dimensional action space and 17 dimensional state space. Franka Kitchen tasks are multi-task and high dimensional, requiring algorithms to "stitch" trajectories. The action space is 9 dimensional and the state space is 60 dimensional. The Adroit pen tasks are also high dimensional and contain a narrow distribution of expert or cloned expert data. The action space is 24-dimensional and the state space is 55-dimensional. By testing the methods on the 8 datasets from these three environments, we experiment on a range of task dimensionalities and difficulties.

12   SARA framework architecture and hyperparameters

First we provide the architecture of our contrastive encoder. Then we provide the hyperparameters used for acquiring the results in our main paper.

12.1   Transformer architecture

Here we briefly summarize architecture and hyperparameters for our contrastive encoder. Both Transformer Encoders use the standard Pytorch implementation pyt, which is based upon the originally proposed Transformer architecture by Vaswani et al. (2017). The Transformer Encoder 1 encodes each trajectory (state and action sequences), but it does not enable attention between trajectories. Information at different timesteps within each trajectory can attend to one another. We inject temporal information via positional encoding Vaswani et al. (2017). We experimented with causal masking in the encoder training, where state-actions can only attend to previous state-actions but not future. However, we found that this masking made either no difference or slightly degraded performance in downstream IQL learning.

We conduct average pooling over timesteps for each trajectory, resulting in one latent per trajectory: $\mathbf{u}_{p/n,i}$, where p or n indicates preferred or non-preferred and i indexes trajectory. Next we form k subsets within each category, *i.e.* k subsets within the set of $\{\mathbf{u}_{p,i}\}$ and k subsets within the set of $\{\mathbf{u}_{n,i}\}$. Each subset is comprised solely of trajectories for either preferred or non-preferred. Then we pass each subset $\{\mathbf{u}_p\}_k$ and $\{\mathbf{u}_n\}_k$ through Transformer Encoder 2, enabling encodings in the same subset to attend to each other. Note the time dimension was already removed prior to this encoder, so we do not have any positional encoding here. We then have single encoding $\mathbf{z}_{p/n,k}$ for each subset. This is trained with the SimCLR loss with a temperature hyperparameter Chen et al. (2020). The SimCLR loss does the following: pulls together latents within the same type (p or n) and repels each of the $\{\mathbf{z}_{p,k}\}$ from each of the $\{\mathbf{z}_{n,k}\}$. As noted in Section 3, we shuffle the composition of latents in each subset $\{\mathbf{u}_p\}_k$ and $\{\mathbf{u}_n\}_k$ to ensure robustness to mislabeling or existence of similar trajectories in the two sets.

As noted in the main paper, we conduct each experiments over 8 seeds. The seeding not only applies to the downstream IQL training but also the encoder training. We do this to align with our baseline models Kim et al. (2023); An et al. (2023), which also seed their Preference Transformer and DPPO Probability Predictor, respectively, with the same seed as their downstream policy training.

12.2   SARA encoder hyperparameters

Unless otherwise noted, all hyperparameters were kept the same for all preference datasets, even though the Kitchen and Adroit environments have higher dimensional action/state spaces than the locomotion tasks.

Here we provide hyperparameters for both Transformer Encoder 1 and Transformer Encoder 2

Table 9: Transformer Encoder 1 and 2 Hyperparameters

Hyperparameter	Value
Causal pooling	No
Model dimension (d_{model})	256
Feedforward network dimension	256
Embedding dimension ($\mathbf{z}_{p/n}$ dim)	16
Encoder dropout rate	0.0
Positional encoding dropout rate	0.0
Number of encoder layers	1
Number of attention heads	4
Avg pooling (after 1st encoder)	Yes

Here we provide additional training hyperparameters:

Table 10: Training Hyperparameters

Hyperparameter	Value
Batch size	256
Use cosine learning-rate schedule	Yes
Initial learning rate	1×10^{-5}
Min learning rate	1×10^{-6}
Optimizer	Adam
Number of epochs	2000 (hopper expert), 10^4 (walker replay), 4000 (all others)
Sets per category (k)	2
Temperature (SimCLR loss)	0.1

The sequence lengths in the preference sets are all 100. As done by the DDPO baseline An et al. (2023), we experimented with using subsequences of varying lengths in training. We passed in subsequence lengths of $[10, 20, 30, 40, 50, 60, 70, 80, 90, 100]$, and we used random start points in the sequences. We found that using random subsequences to train the encoder resulted in slightly reduced variance in the downstream IQL training on the hopper replay dataset. However, in general the asymptotic performance in IQL training was not sensitive to whether or not we used random subsequences of varying length.

13   Policy training and evaluation

We first provide details regarding policy training. We then detail the evaluation method.

13.1   Policy training hyperparameters

We train policies for oracle, SARA, PT, and PT+ADT using the IQL implementation in the publicly available OfflineRL-kit Sun (2023). We carefully match hyperparameters to those suggested by Kim et al. (2023), which also match the hyperparameters suggested for the offline datasets in Kostrikov et al. (2022). In these works, the Gym-Mujoco environments have different IQL hyperparameters,

namely for dropout and temperature, than the ones used for the Franka Kitchen and Adroit environments. We also use the same reward normalization functions provided by Kim et al. (2023). We also carefully match hyperparameters for DPPO policy training to the ones provided by An et al. (2023) in their appendices and code repository. We defer to Kim et al. (2023) and An et al. (2023) for exact hyperparameters. Upon acceptance, we will release our IQL training pipeline with the hyperparameters used for each offline dataset.

13.2 Policy evaluation method

To compare methods, we roll out multiple evaluation episodes for the method's learned policy and get the normalized trajectory reward provided by the environment, as done in prior PbRL works. We use the $get\_normalized\_score$ functions provided by each environment, which uses scaling factors unique to that environment. We scale the episode returns by 100 as done in prior works.

To avoid reporting overly optimistic values, we follow the method proposed by Hejna et al. (2024). We roll out 10 evaluation episodes every 5 epochs of training. We compute the average and the standard deviation of the true normalized episode rewards over the last 8 evaluations. Thus 80 total evaluation episode rewards are averaged at each epoch. This running mean is averaged over the 8 seeds. We report the maximum value achieved after averaging the running mean over the seeds. As noted in Hejna et al. (2024), this maximum of seed-averaged running mean mitigates effects of stochasticity. Past works either do not provide details on the metric computation or report the seed-averaged maximum, which can inflate performance. To report standard deviations that capture both within-seed and across-seed variability, we compute the total standard deviation as follows.

At each epoch of training a particular seed $s \in \{1, \ldots, S\}$, we have a set of $n = 80$ evaluation episodes. For each seed, we compute the standard deviation over episodes and apply Bessel's correction:

$$\sigma_s^{\text{corrected}} = \sigma_s \cdot \sqrt{\frac{n}{n-1}}.$$

The *within-seed variance* is the average of squared corrected standard deviations:

$$\sigma_{\text{within}}^2 = \frac{1}{S} \sum_{s=1}^{S} \left(\sigma_s^{\text{corrected}} \right)^2.$$

Let μ_s denote the mean return for seed s. The *across-seed variance* is the unbiased sample variance of the seed means:

$$\sigma_{\text{across}}^2 = \frac{1}{S-1} \sum_{s=1}^{S} (\mu_s - \bar{\mu})^2, \quad \bar{\mu} = \frac{1}{S} \sum_{s=1}^{S} \mu_s.$$

The total standard deviation used for error bars is then given by:

$$\sigma_{\text{total}} = \sqrt{\sigma_{\text{within}}^2 + \sigma_{\text{across}}^2}.$$

We use the same seeds and reporting methods for all reported values, including for SARA, baselines, and the oracle.

14 Cross-task transfer of preferences

As discussed in Section 10 we train on the hopper-medium-replay-v2 preference set, and we use the learned preferred latent to compute rewards for the full offline walker2d-medium-replay-v2 dataset. We then conduct IQL training on this walker2d dataset. In order to accomplish the SARA reward computation we must build an encoder based on the hopper data that can accept walker state-action space dimensions. The online Gym documentation provides a detailed description of the hopper and

Table 11: Hopper to walker2d action and observation dim mapping

Action Mapping		
hopper dims	**walker2d dims**	**actions in walker2d**
0–2	0–2	torques on thigh, leg, foot joints (right)
0–2	3–5	torques on thigh, leg, foot joints (left)
Observations Mapping		
hopper dims	**walker2d dims**	**observations in walker2d**
0–1	0–1	height and angle of top of torso
2-4	2-4	angle of thigh, leg, foot joints (right)
2–4	5–7	angle of thigh, leg, foot joints (left)
5–7	8–10	velocity of x coordinate, height coordinate, and angular velocity of top
8–10	11–13	angular velocities of thigh, leg, foot hinges (right)
8–10	14–16	angular velocities of thigh, leg, foot hinges (left)

walker2d state and action spaces hop; wal. We need to map the 3-dimensional hopper action space to the 6-dimensional walker2d action space. We also need to map the 11-dimensional hopper state space to the 17-dimensional walker2d state space. To do so we exploit the symmetries in the walker joints as shown in Table 11.

Of course this is not a physically realistic way to map the dimensions. In a well trained walker2d policy, the two legs are not moving symmetrically. Nonetheless, we train an encoder on the hopper replay data with dimensions mapped in this way, and subsequently we infer a preferred latent with this modified hopper replay data. Next, we take the full offline D4RL walker2d replay dataset, and we pass each trajectory through the encoder to get latents for each timestep in each trajectory. Next we compute rewards for each timestep in each trajectory in the walker2d replay dataset by computing cosine similarity with the preferred latent. Lastly we conduct IQL training and evaluate as we did with all other datasets. Though we based this method on physically unrealistic assumptions, we acquire normalized policy rewards that are only few points worse than the reward values attained using the walker2d replay preference set (Figure 3). We also result in lower evaluation reward variance compared to the oracle.

15 Antmaze bug

In their DPPO paper, An et al. (2023) found a critical bug in the Antmaze environment's goal randomization (Appendix F of original paper). After fixing the bug, the authors showed that state-of-the-art offline RL algorithms acquire trivially low policy returns (<12) even with the true environmental rewards. Therefore, we align with An et al. (2023) by deferring experiments on Antmaze until the offline-RL community can investigate further.

16 Compute resources

Our experiments involved training the following individual models on multiple seeds and datasets: SARA contrastive encoder, PT, PT+ADT, IQL policy training, DPPO preference predictor, and DPPO policy. Each individual model was trained on a single NVIDIA A100-SXM4-80GB GPU and 16 CPU cores. Compute resources needed were less than 20GB GPU per model. Training time for the SARA encoder, PT, PT+ADT, and DPPO preference predictor varies depending on size of dataset and number of epochs, but it was typically under 30 minutes per model. The walker2d-medium-replay-v2 dataset took up to 2 hours to train a SARA encoder for 10000 epochs when using additional random slices of trajectories. The DPPO policy training took approximately 2 hours to train on one model on the single GPU. The IQL policy training, using the open source OfflineRL-kit

Sun (2023), took about 3.5 hours to train one model. These computing resources were used for 8 datasets, each model, and 8 seeds per model+dataset. We used our university's computing cluster with access to multiple GPUs, but the models could also be trained on a single standalone GPU or with increased training time, on CPUs alone.