Composite Slice Transformer: An Efficient Transformer with Composition of Multi-Scale Multi-Range Attentions

Abstract

Since the introduction of Transformers, researchers have tackled the notoriously expensive quadratic complexity problem. While significant computational efficiency improvements have been achieved, they come at the cost of reduced accuracy trade-offs. In this paper, we propose Composite Slice Transformer (**CST**), a Transformer-based network equipped with a composition of multi-scale multi-range attentions, boosting both efficiency and modeling capability. After stacking fixed-length slices of the input sequence, each layer in **CST** performs a pair of fine-and-coarse-grained attentions with short-long ranges in a sequential manner, coupled with volatile instant positional embedding, enabling efficient token interactions *and* improving expressiveness of the model. In addition to significantly reduced $O(NL + N^2/L^2)$ complexity for sequence length N and slice length L, **CST** achieves superior performance on a variety of tasks. We show that **CST** surpasses recently published efficient Transformers on the Long Range Arena benchmark, demonstrating the bidirectional long-range dependency modeling capability of our model. It outperforms the standard Transformer by a margin of 6.9% in average accuracy across the five classification tasks of the benchmark, while being of complexity comparable to other efficient transformers. Furthermore, on the word-level autoregressive language modeling task with the WikiText-103 dataset, **CST** performs competitively against the Transformer model with only 2% gap in the test perplexity while outperforming other efficient Transformers.

1 Introduction

Transformers (Vaswani et al., 2017) and their variants are among the most pivotal contributions to recent advances in artificial intelligence (AI). Since they can be combined in a straightforward fashion with advanced training methods and auxiliary modules, Transformers have proven extremely effective as a versatile backbone architecture for achieving state-of-the-art performance in many domains such as natural language processing (Devlin et al., 2018; Yang et al., 2019; Brown et al., 2020; Raffel et al., 2020; Sanh et al., 2022), vision processing (Dosovitskiy et al., 2020; Liu et al., 2021b; Radford et al., 2021), visual language modeling (Alayrac et al., 2022), speech recognition (Dong et al., 2018; Gulati et al., 2020; Shi et al., 2021), and reinforcement learning (Chen et al., 2021b; Janner et al., 2021).

Despite this versatility and wide applicability, Transformers possess an expensive memory and computational complexity of $O(N^2)$ with respect to input length N; as a result of these complexity drawbacks, Transformers are often not applied to tasks with long sequence data. Since the introduction of Transformers in (Vaswani et al., 2017), significant research has concentrated on improving Transformer complexity through various approaches and techniques, achieving efficiency improvements in computation and memory (Tay et al., 2020c), even of $O(N)$ complexity (Wang et al., 2020; Katharopoulos et al., 2020; Ma et al., 2021). Unfortunately, despite these clear advances in complexity reduction, these accelerations come at the expense of decreased accuracy and simultaneously lack the modeling capability of fine-grained dependencies among all token pairs, hamstringing the ability to apply these recent techniques to practical problems.

Recent studies (Zhu et al., 2021; Ren et al., 2021; Nguyen et al., 2021; Zhu & Soricut, 2021; Han et al., 2021) show that combining efficient techniques for global sequence modeling with fine-grained

limited range attention *can* improve accuracy, maintain low complexity, and enable the longer-range context windows, allowing such models to outperform the standard, full-resolution Transformer on certain tasks. However, optimally combining sequence modeling at different levels of granularity remains an open problem.

Through the development of a technique for efficiently combining local and global token dependency modeling, we have observed better performance than the standard Transformers can be achieved. To this end, we propose the wider adoption of our *Composite Slice Transformer* (**CST**), an efficient and innovative Transformer-based network architecture, consisting of a composition of attentions applied to a stacked, slice representation of the input sequence at different scales, coupled with a multi-scale volatile instant positional embedding. For fixed slice length L, **CST** has a complexity of $O(NL + N^2/L^2)$, comparable to linear complexity in many practical settings (Section A.3). Since slicing restricts fine-grained token interaction across boundaries, **CST** also leverages extended attention (or overlapped attention), preventing context fragmentation (Dai et al., 2019b) and enabling seamless sequence modeling.

Similar to (Dosovitskiy et al., 2020), **CST** abstracts the input sequence into another with fewer tokens for low-resolution attention with longer range with fixed-size segment-wise embedding. When the segment length is L, as the sequence length becomes N/L, the quadratic complexity N^2 becomes a decimated quadratic one N^2/L^2. With a proper L, the model can benefit from a significant amount of complexity reduction while having comparable performance. Along with the segment-level abstractive attention, **CST** also leverages a full-resolution local attention to form a *multi-scale multi-range attention* (MSMRA) similar to (Zhu & Soricut, 2021; Zhu et al., 2021; Nguyen et al., 2021; Ren et al., 2021; Han et al., 2021). Additionally, **CST** extends the ideas of position-infused attention in (Press et al., 2021) and applies them to MSMRA, which we refer to as multi-scale volatile instant positional embedding (MS-VIPE). In addition to its effectiveness in embedding of positional information, MS-VIPE further provides parameter efficiency since it only requires storage for reduced lengths of local attention L and global attention N/L instead of the full length N.

We evaluate our model on bidirectional long-range dependency modeling tasks and an autoregressive language modeling task. In our experiments (Section 5), **CST** achieves state-of-the-art performance among all Transformer-based models (including the standard Transformer and recently proposed efficient Transformers) as well as demonstrates strong performance on a wide variety of tasks.

The paper is organized as follows. In Section 2 and Section 3, we discuss recent efficient Transformer developments within a single logical framework, discuss strengths and weaknesses, and outline the inspiration for **CST**. In Section 4, we present our model, Composite Slice Transformer, detailing its features. In Section 5, we show our experimental results on the Long Range Arena benchmark and WikiText-103 autoregressive language modeling benchmark demonstrating that **CST** is efficient in practice and applicable to a wide spectrum of different tasks. In Section 6, we conclude with a summary of our work and discuss about potential future works in this direction.

2 RELATED WORKS

Tay et al. (2020c) provides a comprehensive study of proposed approaches to accelerate the attention mechanism of Vaswani et al. (2017). The key differentiating factor among the approaches presented is the modeling assumptions used to approximate the original attention map. For example, common assumptions include sparsity (Child et al., 2019; Ho et al., 2019; Beltagy et al., 2020; Ainslie et al., 2020; Zaheer et al., 2020; Tay et al., 2020a; Kitaev et al., 2019) and low-rankness (Wang et al., 2020; Choromanski et al., 2020; Katharopoulos et al., 2020). Chen et al. (2021a) complementarily combines these two assumptions. Other architectures leverage additional memory for compressing the global context (Lee et al., 2019; Ma et al., 2021; Jaegle et al., 2021).

A group of approaches aim to reduce the dimensions of the operands involved in computing attention (Wang et al., 2020; Ma et al., 2021; Dosovitskiy et al., 2020) as *abstractive attention*. (**CST**) leverages a one-dimensional version of the token abstraction used in (Dosovitskiy et al., 2020) for the global attention, but with additional composition of local attention.

In order to capture fine-grained token interactions that might be missing in the abstractive attention, (Zhu & Soricut, 2021; Zhu et al., 2021; Nguyen et al., 2021; Ren et al., 2021) use a process akin to leverage a full-resolution local attention to form a *multi-scale multi-range attention* (MSMRA). These

approaches, however, do not compose the local full-resolution attention and global reduced-resolution attentions in a series. Absent from this literature, serial composition and positional embedding would improve accuracy while preserving the efficiency (see the following sections for how we address this enhancement).

(Press et al., 2021) propose the position-infused attention (PIA), which is an attention module with a layer-wise positional embedding applied only to queries and keys, to address token representation reusability issue in increasing window attention due to positional information draft, while avoiding expensive computation of relative position encoding (Dai et al., 2019b). Another study of adding positional embedding to values is conducted in (Tsai et al., 2019), concluding that positional embedding on value does not lead to performance improvement. We extends these ideas in (**CST**) and apply in MSMRA.

3 PRELIMINARIES

3.1 TRANSFORMERS AND MULTI-HEAD SELF-ATTENTION

A Transformer layer consists of a multi-head self-attention sublayer followed by a feed-forward network (Vaswani et al., 2017) with an optional cross-attention sublayer in case of the decoder. The multi-head self-attention is defined as the concatenation of the self-attention output of all attention heads:

$$\mathbf{Y} = [\mathbf{Y}_0, \mathbf{Y}_1, ..., \mathbf{Y}_{H-1}]_2, \tag{1}$$

where $[\cdot]_r$ denotes concatenation in the r^{th} dimension, and each of the outputs $\mathbf{Y}_h \in \mathbb{R}^{N \times d_h}$ is a scaled dot-product attention computed from the input $\mathbf{X} \in \mathbb{R}^{N \times D}$ as

$$\mathbf{Y}_h = \text{softmax}\left(\frac{\mathbf{Q}_h \mathbf{K}_h^\top}{\sqrt{d_h}}\right)\mathbf{V}_h = \mathbf{A}\mathbf{V}_h. \tag{2}$$

In Eq. equation 2, $\mathbf{Q}_h = \mathbf{X}\mathbf{W}_{q,h}$ are queries, $\mathbf{K}_h = \mathbf{X}\mathbf{W}_{k,h}$ are keys, and $\mathbf{V}_h = \mathbf{X}\mathbf{W}_{v,h}$ are values expressed as linear transformations of the input $\mathbf{X}$ as $\mathbf{W}_{\cdot,h} \in \mathbb{R}^{D \times d_h}$. We assume the queries, keys, and values have the same hidden dimension: $d_h = D/H$. For the rest of the paper, we omit the head index h and scaling factor $1/\sqrt{d}$ for simplicity. We denote the query, key and value at some position index i by $\mathbf{k}_i$, $\mathbf{v}_i$, $\mathbf{q}_i \in \mathbb{R}^{1 \times d}$, respectively. In this context, the attention output at the i^{th} token position $\mathbf{y}_i \in \mathbb{R}^{1 \times d_h}$ corresponds to

$$\mathbf{y}_i = \text{softmax}\left(\mathbf{q}_i \mathbf{K}^\top\right)\mathbf{V}. \tag{3}$$

Due to the nonlinearity and normalization property of the softmax function, $\mathbf{Q}\mathbf{K}^\top$ must be computed to obtain the attention weight, followed by value aggregation through the attention weights, $\mathbf{A}\mathbf{V}$, resulting in quadratic complexity with respect to the sequence length N for the self-attention; i.e., $O(N^2)$ computational and memory complexities.

3.2 ABSTRACTIVE ATTENTIONS AND MULTI-SCALE MULTI-RANGE ATTENTION (MSMRA)

Abstractive attentions are the family of efficient attention approaches in which the lengths of the attention operands are reduced to $M(< N)$ by applying an abstraction function $\phi(\cdot)$, resulting in reduced complexity of the attention while retaining the form of basic attention computation in Eq. 3. We focus on the cases that all the operands of attention, i.e., query, key, and value, are abstracted.

In such cases, the attention mechanism is reduced to

$$\overline{\mathbf{y}}_{i'} = \text{softmax}\left(\overline{\mathbf{q}}_{i'}\overline{\mathbf{K}}^\top\right)\overline{\mathbf{V}}, \tag{4}$$

where $\overline{\mathbf{Q}}$, $\overline{\mathbf{K}}$, and $\overline{\mathbf{V}}$ are queries, keys, and values, respectively, abstracted, $\overline{\mathbf{q}}_{i'}$ is i'^{th} row of $\overline{\mathbf{Q}}$, and $\overline{\mathbf{y}}_{i'}$ is the attention output token with the abstracted query token $\overline{\mathbf{q}}_{i'}$ obtained by

$$\overline{\mathbf{q}}_{i'} = \phi\left(\{\mathbf{q}_{i \in \Omega_{i'}}\}\right). \tag{5}$$

In order to restore the resolution of the output, we define a one-to-many mapping function $\psi_y(\cdot)$ as

$$\mathbf{y}_{i \in \Omega_{i'}} = \{\psi\left(\overline{\mathbf{y}}_{i'}\right)\}_i. \tag{6}$$

Detailed description of abstractive attention is presented in Section A.1.

Although many previous abstractive attention approaches have achieved sub-quadratic or linear complexities, they typically come at the cost of degraded benchmark performance. However, Transformer-based models that leverage multi-scale attention by combining local attention and global attention perform competitively against the standard Transformer. In fact, these models can outperform the standard Transformer on certain tasks, while still maintaining efficiency (Zhu & Soricut, 2021; Zhu et al., 2021; Nguyen et al., 2021; Ren et al., 2021). While other types of MSMRA are described in Section A.2, our proposed attention mechanism is essentially an MSMRA of the form

$$\mathbf{y}_i = \mathbf{y}_{1,i} + \psi\left(\overline{\mathbf{y}}_{\mathrm{g},i'}\right), \tag{7}$$

where $\mathbf{y}_{1,i}$ is the local attention output and $\overline{\mathbf{y}}_{\mathrm{g},i}$ is the global attention output.

4   COMPOSITE SLICE TRANSFORMER

We describe the key ideas of Composite Slice Attention (**CSA**) and **CST** network, a Transformer-based model with **CSA** replacing the full softmax dot-product attention in the standard Transformer. **CSA** leverages both full-resolution attention in limited ranges and abstracted attention to capture long-range interactions. Unlike previous approaches, the multi-scale, multi-range attentions are combined through function composition in a serial connection, which allows information routing across representations at different scales and improves expressiveness of the model. See Figure 1 for an illustration of the **CST** network and the **CSA** module.

While focusing on the core components of **CST** in this section, we expand on further details of **CSA** in various appendices. First, we present the extension of the local attention in Section A.4, to address the fine-grained contextual fragmentation problem (Dai et al., 2019b) caused by hard segmentation in the stacked slice representation of a sequence, and improve token-level dependency modeling. In Section A.5, we design a multi-scale causal mask and modify the **CSA** extension to prevent undesirable look-ahead due to the query abstraction, and guarantee true causality for autoregressive application. In Section A.6, we mathematically motivate **CSA** with approximation theory by arguing that a composition of attentions can express a larger functional space than common alternatives.

4.1   SEQUENCE REPRESENTATION AS STACKED SLICES AND **CSA**

In a high-level categorization, the multi-scale multi-range attention of the **CST** corresponds to the combination of block-wise local window attention (Beltagy et al., 2020) and patch-based global attention (Dosovitskiy et al., 2020) in a one-dimensional form. **CSA** layer starts with converting the input sequence $\mathbf{X} \in \mathbb{R}^{N \times D}$ into a stack of slices $\mathbf{S} \in \mathbb{R}^{N/L \times L \times D}$ by slicing it with a fixed length L, implemented simply as a `Reshape` operation. Two attentions with different granularity are then performed sequentially in each direction. First, the local attention is performed across the token within each slice while considering the number of slices as a batch, and then the number of slices N/L is combined with the batch size and parallelized together:

$$\mathbf{Y}_1 = \mathrm{softmax}\left(\mathbf{Q}_\mathrm{l}\mathbf{K}_\mathrm{l}^\top\right)\mathbf{V}_1, \tag{8}$$

where $\mathbf{Q}_\mathrm{l}$, $\mathbf{K}_\mathrm{l}$, and $\mathbf{V}_1 \in \mathbb{R}^{N/L \times L \times d}$ are the queries, keys, and values for each local attention head, computed as $\mathbf{SW}_{1,q}$, $\mathbf{SW}_{1,k}$, and $\mathbf{SW}_{1,v}$, respectively, with $\mathbf{W}_1 \in \mathbb{R}^{D \times d}$. Next, the dimension of length L in the local attention output is collapsed using an abstraction function ϕ_y to get the slice embedding $\overline{\mathbf{S}} \in \mathbb{R}^{N/L \times D}$. Specifically, we use a simple mean pooling $\overline{\mathbf{S}}_s = \phi_y(\mathbf{Y}_{1,s}) = \sum_{l=0}^{L-1} \mathbf{m}_{s,l}\mathbf{Y}_{s,l} / \sum_{l=0}^{L-1} \mathbf{m}_{s,l}$, where s and l denote the slice index and the token index, respectively, and $\mathbf{m} \in \mathbb{R}^{N/L \times L}$ is the stack of slices of the binary attention mask that is optionally given in the case that the input sequence is padded; e.g., when a data batch has samples with different lengths. Normalization with the sum of the binary mask, i.e., the number of nonzero mask values, instead of the slice length L, avoids biases in the mean computation induced by masked tokens. Then the second attention along the slice dimension is performed to model full-range slice-wise interaction in a reduced resolution:

$$\overline{\mathbf{Y}}_\mathrm{g} = \mathrm{softmax}\left(\overline{\mathbf{Q}}_\mathrm{g}\overline{\mathbf{K}}_\mathrm{g}^\top\right)\overline{\mathbf{V}}_\mathrm{g}, \tag{9}$$

(a) **CSA** Architecture   (b) Illustration of **CSA**

Figure 1: Composite Slice Attention. **CSA** consists of a full-resolution local attention with computational complexity $O(NL)$ and a low-resolution global attention with complexity $O(N^2/L^2)$. A shared multi-scale positional embedding is applied to all layers. **CSA** replaces self-attention sublayer in each Transformer block to form a *Composite Slice Transformer* (**CST**) network.

where $\overline{\mathbf{Q}}_g$, $\overline{\mathbf{K}}_g$, and $\overline{\mathbf{V}}_g$ is the abstracted queries, keys, and values for the global attention obtained by applying $\mathbf{W}_{g,q}$, $\mathbf{W}_{g,k}$, and $\mathbf{W}_{g,v}$ to $\overline{\mathbf{S}}$. Finally, the output of the global attention is interpolated to the original resolution followed by being added to the local output:

$$\mathbf{Y}_i = \mathbf{Y}_{l,i} + \mathbf{Y}_{g,i} = \mathbf{Y}_{l,i} + \psi\left(\overline{\mathbf{Y}}_{g,i'},\right) \tag{10}$$

where $\psi(\overline{\mathbf{Y}}_{g,i})$ is a broadcasting function that restores only the sequence length, i.e., $\mathbf{Y}_{g,i} = \overline{\mathbf{Y}}_{g,i'}$ for $i \in \Omega_{i'}$, since the output of the local attention still holds the full resolution. This process can be implemented as a simple broadcast-add operation as shown in Figure 1a.

4.2 Multi-scale volatile instant positional embedding (MS-VIPE)

Since we reduce the input lengths of both global and local attentions, the full positional embedding of the maximum input sequence length is no longer necessary. For the local attention, we can limit the positional embedding length to the attention range; i.e., the slice length L, sharing the embedding across slices. In addition, as we aggregate the tokens from each slice for the global attention resulting in different granularity, it is more natural to have a separate positional embedding of length N/L at the scale of slice embedding instead of aggregating the full-resolution full-length positional embedding by the same process for the token embedding.

To that end, **CST** utilizes the multi-scale positional embedding $\mathbf{P}_l \in \mathbb{R}^{1 \times L \times D}$ and $\mathbf{P}_g \in \mathbb{R}^{N/L \times D}$. Although it is similar to the positional embedding used in (Han et al., 2021), there are crucial differences. First, instead of adding the positional embedding to the stacked slices of token embedding at the embedding layer and having aggregated positional information as the layers stack up (Press et al., 2021), **CST** applies them instantly at the corresponding attentions in each layer before the linear transformations. Second, as the positional embedding in all layers are added, they can be accumulated over the layers and undesirably dominate the contextual information at top layers which potentially leads to performance degradation. In order to prevent this issue, **CST** does not add the positional embedding to values. Our experiments in Section A.7.2 show that the multi-scale volatile instant positional embedding (MS-VIPE) is more effective as compared to the conventional absolute full-length positional embedding. Equations 8 and 9 can now be rewritten as:

$$\mathbf{Y}_l = \text{softmax}\left(\{(\mathbf{S} + \mathbf{P}_l)\,\mathbf{W}_{l,q}\}\{(\mathbf{S} + \mathbf{P}_l)\,\mathbf{W}_{l,k}\}^\top\right)\mathbf{SW}_{l,v}, \tag{11}$$

$$\overline{\mathbf{Y}}_g = \text{softmax}\left(\{\left(\overline{\mathbf{S}} + \mathbf{P}_g\right)\mathbf{W}_{g,q}\}\{\left(\overline{\mathbf{S}} + \mathbf{P}_g\right)\mathbf{W}_{g,k}\}^\top\right)\overline{\mathbf{S}}\mathbf{W}_{g,v}. \tag{12}$$

4.3 COMPLEXITY AND PARAMETER REDUCTION IN CST

Compared to the *quadratic* $O(N^2)$ complexity of the standard Transformer, **CST** has *linear plus decimated quadratic* complexity $O(NL) + O(N^2/L^2)$. However, as shown in Section A.3, since the slice length L is typically less than the abstraction lengths M in other linear-complexity models, **CST** has comparable efficiency to other efficient Transformer models for practical lengths of input sequences. Since the global attention in **CST** takes the collapsed local attention outputs as inputs, it requires a slight increase in computation for linear transformers to get queries, keys, and values, corresponding to $3(N/L)d^2$.

Two sets of $\mathbf{W}_q, \mathbf{W}_k, \mathbf{W}_v$ transformations in **CST** may also affect the parameter count. While TNT (Han et al., 2021) reduces the hidden dimension for local attention to limit the network size increase, in **CST** we use the same dimension for representations at different scale *with tying the weights instead*, resulting in no increase parameter count.

Another benefit of having the stacked slice representation is the reduction in storage requirement for the positional embedding. Since the lengths for attentions are L and N/L for local and global attentions, respectively, **CST** has fewer parameters $((L + N/L) \cdot D)$ than that of the conventional positional embedding number $N \cdot D$. This benefit can be significant for tasks with very long sequences while it can be relatively small when the network size is very large.

5 EXPERIMENTS

To demonstrate the computational efficiency and sequence modeling capability of **CST**, we evaluate our model in three different contexts: (1) bidirectional long-range dependency modeling on classification tasks (2) word-level auto-regressive language modeling and (3) masked language modeling and natural language understanding on short sequences. Throughout this section, unless stated otherwise, it is implied that we train each model from scratch, reporting its test performance from a model with the best validation results.

5.1 BIDIRECTIONAL LONG-RANGE DEPENDENCY MODELING

Datasets and Baselines The Long Range Arena (LRA) benchmark (Tay et al., 2020b) is a suite of classification tasks that evaluate long-range dependency modeling capabilities with datasets from several different modalities with lengths ranging from 1k to 16k. We evaluate **CST** on the five tasks broadly used in literature, *ListOps, Text, Retrieval, Image*, and *Pathfinder*, where the maximum sequence length is 4k. We compare **CST**'s efficiency and performance against several state-of-the-art efficient Transformer models. Specifically, we evaluate our model and other Transformer models from a group of non-abstractive attention methods: FNet (Lee-Thorp et al., 2021), Linear Transformer (Katharopoulos et al., 2020), Performer (Choromanski et al., 2020), and another group of abstractive attention methods: Reformer (Kitaev et al., 2019), Linformer (Wang et al., 2020), Luna (Ma et al., 2021), Nyströmformer (Xiong et al., 2021), that of multi-scale multi-range attention

Figure 2: LRA score (y-axis), relative speed (x-axis), relative GPU memory usage (circle radius), and parameter count (color). With competitive efficiency and smaller model sizes, **CST**s outperform strong efficient Transformer baselines as well as the standard Transformer by significant margins. The speed and memory usage measurements can be different depending on devices and implementations.

methods: H-Transformer-1D (Zhu & Soricut, 2021), Long Short Transformer (Zhu et al., 2021), and Scatterbrain (Chen et al., 2021a), as well as the standard Transformer (Vaswani et al., 2017). We outline experimental setup for the Long Range Arena in Appendix A.7.1

Results   Our experimental results on the LRA benchmark are given in Table 1. We observe that **CST** surpasses the state-of-the-art efficient Transformers with large margins. The best performance is achieved using a slice length 8, outperforming the Transformer baseline by 4.23 points in average score across all tasks. The largest improvements are observed on the *Text, Retrieval*, and *Image* tasks, while a minimal degradation is observed on the *ListOps* task. In addition, as discussed in Section 4.1, **CST** has the added benefit of requiring fewer parameters for a given model size thanks to its positional embedding characteristics, although this benefit may be marginal as the network size increases.

Aside from the average score across all tasks, we measure relative speed, and relative GPU memory usage for each model under comparison on a `NVIDIA Tesla V100` GPU with 32GB memory on *Retrieval* dataset with the sequence length of 4k and report the results in Figure 2. Here, relative speed is computed as the number of training steps per second divided by that of Transformer, and GPU memory usage is measured using the PyTorch command, `torch.cuda.max_memory_allocated()`, both on the *Retrieval* task. It is clearly seen that **CST** outperforms all models while having competitive computation and memory efficiency to other efficient Transformer models. We note that these measures can be different according to implementation and hardware under test.

We present an ablation study on LRA benchamrk in Section A.7.2. As can be seen in Table 5 and Table 6, all variants of **CST** outperformed the baseline models, except that switching the MSMRA composition order, i.e. attentions in global-local order, performs slightly worse than Long Short Transformer (Zhu et al., 2021). We demonstrate that the composition of MSMRA in the local-global order and the proposed positional embedding are the most contributing components to the accuracy. While the best overall performance is achieved with $L = 8$, we find that the slice length L has less effect than other hyperparameters.

Table 1: Test accuracy on Long Range Arena (LRA) benchmark.

Model	ListOps	Text	Retrieval	Image	Pathfinder	Average
Transformer (ours)	**39.92**	64.20	82.11	44.25	74.79	61.05
Transformer (Tay et al., 2020b)	36.37	64.27	57.46	42.44	71.40	54.39
Transformer (Xiong et al., 2021)	37.10	65.02	79.35	38.20	74.16	58.77
FNet	36.74	64.37	74.29	44.08	50.22	53.94
Linear Transformer	37.40	65.16	82.73	43.81	74.74	60.77
Performer	37.25	64.65	81.69	41.73	72.91	59.65
Reformer	18.04	60.94	79.19	40.38	67.66	53.24
Linformer	38.71	58.73	79.88	45.31	70.11	58.55
Luna	38.36	65.20	81.88	43.16	74.04	60.53
Nyströmformer	37.50	65.01	80.42	51.13	69.73	60.76
H-Transformer-1D	38.21	66.09	**84.19**	46.03	72.45	61.39
Long Short Transformer	38.86	64.93	83.88	47.45	75.28	62.08
Scatterbrain	38.71	63.52	81.12	41.01	70.11	58.89
CST ($L = 8$)	37.45	**77.23**	84.15	51.27	76.32	**65.28**
CST ($L = 16$)	37.90	73.60	84.00	**51.39**	**76.97**	64.77

Table 2: Autoregressive language modeling perplexity on WikiText-103. Results for other models are taken from (Nguyen et al., 2021).

Model	Validation Perplexity	Test Perplexity
Transformer	33.15	34.29
Linear Transformer	37.27	38.40
FMMFormer (2-kernel + Band$_{20}$)	35.10	36.11
CST ($L = 32, \alpha = 3$)	34.18	34.98

5.2 AUTOREGRESSIVE LANGUAGE MODELING

In this section, to evaluate its extendability as practical language models, we conduct an autoregressive language modeling experiment on the word-level WikiText-103 dataset (Merity et al., 2016).

Dataset and Experimental Setup The WikiText-103 (Merity et al., 2016) dataset is a collection of featured articles on Wikipedia. It has 103M/218K/246K words in training/validation/test sets, respectively. The task in this experiment is to predict the next word given the history of past words. We follow the experimental setup in (Nguyen et al., 2021) and train **CST** and carefully match the network configuration and training hyperparameters to those given in (Nguyen et al., 2021) and compare with their reported results. Specifically, we train a small network with 16 layers, 8 attention heads, the model dimension of 128, and the hidden dimension of the feed-forward network of 2,048. We train the model for a total of 500K steps. While the dataset allows longer context, we used the 256 context window length to match with the baselines.

Results For **CST**, we report the perplexities of the best performing model of the slice length of 32 and the extension ratio α of 3. Results for other configurations can be found in Section A.8.2. As can be seen from Table 2, **CST** outperforms other efficient Transformer including Linear Transformer (Katharopoulos et al., 2020), a kernel method-based linear-complexity model, and FMMformer (Nguyen et al., 2021), an MSMRA with kernel method-based global attention. While methods for the baselines are limited, the results indicate that composite attention can be more effective than kernel method-based attention. Our model reduces the autoregressive language modeling perplexity gap between the standard Transformer and efficient Transformers to 2%. We further observe consistent 1.5x speed-ups across configurations, compared to the standard Transformer, as shown in Section A.8.2.

We also perform an ablation study for **CST** on the language modeling task. While the full results can be found in Section A.8.2, we observe that for smaller context lengths, larger slice length with

Table 3: Bidirectional MLM and NLU transfer learning evaluation on GLUE benchmark.

Model	MLM	COLA	MNLI	MRPC	QNLI	QQP	RTE	SST	STSB	GLUE Average
BERT$_{base}$	**4.84**	**60.63**	**83.35**	**91.17**	**90.04**	**87.67**	**69.68**	**92.89**	**87.43**	**82.86**
Nyströmformer (64)	6.77	39.39	78.75	87.23	87.35	85.64	54.87	90.48	84.28	76
Performer (64)	6.44	46.64	77.48	82.23	85.7	85.8	57.76	90.02	78.00	75.46
Luna (64)	5.63	42.63	78.26	82.94	85.78	84.18	59.21	90.94	75.89	74.98
FNet	8.62	44.58	75.15	84.00	84.15	84.61	63.18	89.33	82.84	75.98
CST ($L = 32, \alpha = 2$)	5.30	57.34	80.73	85.85	86.31	87.08	59.21	91.97	85.95	79.31
CST ($L = 64, \alpha = 1$)	5.56	56.50	81.17	89.42	88.07	87.44	60.65	92.66	87.41	80.41

smaller local attention extension is more effective and efficient than having smaller slice length with larger local attention extension. In addition, significant performance improvement is observed with increased context length to 1024, as shown in Table 8.

5.3 BIDIRECTIONAL LANGUAGE MODELING AND TRANSFER LEARNING

We further evaluate CST on bidirectional language modeling and transfer learning with relatively short input sequences, i.e., $N = 128$. Masked language modeling (MLM) was proposed in (Devlin et al., 2018) as a pretraining method of transformer encoder models and it greatly improves downstream natural language understanding (NLU) performances when fine-tuning the pretrained models. We follow the experimental setup of (Devlin et al., 2018) for conducting both pre-training and fine-tuning including datasets, masking rate, batch size, optimizer settings, and evaluation metrics with a few exceptions. We report the MLM validation perplexities and GLUE scores with accuracy on each task in Table 3. Further experimental details, more experimental results, and discussion can be found in A.9.

As can be seen in the table, CST consistently outperforms other efficient transformers and closes the gap to the baseline BERT model by 0.46 validation perplexity and 2.45 points in GLUE score. In the Section A.9, we discuss the sources of performance degradation compared to BERT and future research directions to address them.

6 CONCLUSION

In this paper, we present Composite Slice Transformer (**CST**), an efficient Transformer-based network equipped with composition of multi-scale multi-range attentions. Using stacked slice representation of input sequences, a **CST** layer performs a set of local fine-grained attention and global coarse-grained attention in a sequential manner at a low complexity cost of the sum of linear and decimated quadratic complexities $O(NL + N^2/L^2)$. In addition to the complexity benefit, we also show that **CST** improves performance on various sequence modeling tasks. On the Long Range Arena benchmark and word-level autoregressive language modeling benchmark on WikiText-103 dataset, **CST** significantly surpasses strong baselines including the standard Transformer and the recently proposed efficient Transformers.

After the observation that **CST** achieves superior modeling capability as well as relaxing the complexity bottleneck of Transformers, we observe some limitations of **CST** as summarized in A.10 and consider extending our research in several directions. First, we can easily generalize our work to multi-level slicing with a higher level than two. This will lead to more improvement in expressiveness of the model while adding more degree of freedoms for better efficiency while enabling its application to much longer sequences. Second, as discussed in Section A.5, more advanced design of autoregressive sequence modeling scheme will further improve the performance. Third, while **CST** is based on fixed-length slicing of the sequence, dynamic or semantic slicing would further improve applicability to non-stationary sequences. With end-to-end training, the model can learn the optimal slicing of the data for given tasks and provide layer-wise dynamic tokens. To this end, efficient realization of the dynamic slicing would be the most challenging task. Finally, as a meaningful next step, modification of **CST** to better fit vision tasks or training a **CST**-based large language model would provide general and practical impact.

7 REPRODUCIBILITY STATEMENT

Model Implementation We implemented the composite slice attention (CSA) and formed the composite slice transformer (CST) by replacing the self-attention block with the CSA block in the baseline transformer network. We are following our internal open-source policy and trying to open-source the code, at least the model implementation, to provide it to the reviewers in the rebuttal period. Nonetheless, since the implementation of CSA is straightforward in the sense that it does not involve any special kernels or operators, we believe any reader with a moderate knowledge and experience of deep learning would be able to implement it based on Section 4, especially, Figure 1a. For other models, we used the implementations from different github repositories, i.e., Linformer, Performer, Reformer from `https://github.com/NVIDIA/transformer-ls`), FNet from `https://github.com/huggingface/transformers`, Nyströmformer, Linear Transformer from `https://github.com/mlpen/Nystromformer`, H-Transformer-1D from `https://github.com/lucidrains/h-transformer-1d`, and Scatterbrain from `https://github.com/HazyResearch/fly`.

Benchmark Implementation and Hyperparameters To facilitate reproducibility, we used a well-established open-source code for each benchmark as below.

For Long Range Arena benchmark, we followed the training and evaluation pipeline in the open-source code of Long-Short Transformer (Zhu et al., 2021) (`https://github.com/NVIDIA/transformer-ls`, including the dataset preparation. The experimental setup including the training hyperparameters are described in A.7.1. As different models require different sets of hyperparameters, we described them in A.7.1 as well, mainly taken from the default or best settings from each paper.

For autoregressive language modeling task, we used the language modeling pipeline implementation from `https://github.com/IDSIA/lmtool-fwp`. Here, we swap in our CST implementation in place of the softmax transformers and applied autoregressive masking as described in section A.5 with the hyperparameters described in A.8.1.

For masked language modeling, we followed the training procedure and the training hyperparameter setting of BERT (Devlin et al., 2018) as described in A.9.1, up to the phase 1 pretraining, i.e., we only trained each model for 900k with the sequence length 128. We used the Huggingface MLM pretraining pipeline in huggingface transformers (`https://github.com/huggingface/transformers`) and BERT implementation (`https://github.com/huggingface/transformers/blob/main/src/transformers/models/bert/modeling_bert.py`) as the baseline transformer model to form different transformer variants by replacing the self-attention module.

For GLUE benchmark, with the MLM pretrained version of each transformer model, we mostly followed the evaluation procedure in Devlin et al. (2018) for GLUE benchmark, using the Jiant code (`https://github.com/nyu-mll/jiant`). As described in A.9.1, we used mean pooling of the model output sequence for classification input instead of using [CLS] token.

REFERENCES

Joshua Ainslie, Santiago Ontanon, Chris Alberti, Vaclav Cvicek, Zachary Fisher, Philip Pham, Anirudh Ravula, Sumit Sanghai, Qifan Wang, and Li Yang. Etc: Encoding long and structured inputs in transformers. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pp. 268–284, 2020.

Jean-Baptiste Alayrac, Jeff Donahue, Pauline Luc, Antoine Miech, Iain Barr, Yana Hasson, Karel Lenc, Arthur Mensch, Katie Millican, Malcolm Reynolds, et al. Flamingo: a visual language model for few-shot learning. *arXiv preprint arXiv:2204.14198*, 2022.

Iz Beltagy, Matthew E Peters, and Arman Cohan. Longformer: The long-document transformer. *arXiv preprint arXiv:2004.05150*, 2020.

Tom Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared D Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, et al. Language models are few-shot learners. *Advances in neural information processing systems*, 33:1877–1901, 2020.

Beidi Chen, Tri Dao, Eric Winsor, Zhao Song, Atri Rudra, and Christopher Ré. Scatterbrain: Unifying sparse and low-rank attention approximation. *arXiv preprint arXiv:2110.15343*, 2021a.

Lili Chen, Kevin Lu, Aravind Rajeswaran, Kimin Lee, Aditya Grover, Misha Laskin, Pieter Abbeel, Aravind Srinivas, and Igor Mordatch. Decision transformer: Reinforcement learning via sequence modeling. *Advances in neural information processing systems*, 34, 2021b.

Rewon Child, Scott Gray, Alec Radford, and Ilya Sutskever. Generating long sequences with sparse transformers. *arXiv preprint arXiv:1904.10509*, 2019.

Krzysztof Marcin Choromanski, Valerii Likhosherstov, David Dohan, Xingyou Song, Andreea Gane, Tamas Sarlos, Peter Hawkins, Jared Quincy Davis, Afroz Mohiuddin, Lukasz Kaiser, et al. Rethinking attention with performers. In *International Conference on Learning Representations*, 2020.

Zihang Dai, Zhilin Yang, Yiming Yang, Jaime Carbonell, Quoc V Le, and Ruslan Salakhutdi-nov. Transformer-xl: Attentive language models beyond a fixed-length context. *arXiv preprint arXiv:1901.02860*, 2019a.

Zihang Dai, Zhilin Yang, Yiming Yang, Jaime G Carbonell, Quoc Le, and Ruslan Salakhutdinov. Transformer-xl: Attentive language models beyond a fixed-length context. In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pp. 2978–2988, 2019b.

Zihang Dai, Guokun Lai, Yiming Yang, and Quoc Le. Funnel-transformer: Filtering out sequential redundancy for efficient language processing. *Advances in neural information processing systems*, 33:4271–4282, 2020.

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. Bert: Pre-training of deep bidirectional transformers for language understanding. *arXiv preprint arXiv:1810.04805*, 2018.

Linhao Dong, Shuang Xu, and Bo Xu. Speech-transformer: a no-recurrence sequence-to-sequence model for speech recognition. In *2018 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pp. 5884–5888. IEEE, 2018.

Alexey Dosovitskiy, Lucas Beyer, Alexander Kolesnikov, Dirk Weissenborn, Xiaohua Zhai, Thomas Unterthiner, Mostafa Dehghani, Matthias Minderer, Georg Heigold, Sylvain Gelly, et al. An image is worth 16x16 words: Transformers for image recognition at scale. *arXiv preprint arXiv:2010.11929*, 2020.

Anmol Gulati, James Qin, Chung-Cheng Chiu, Niki Parmar, Yu Zhang, Jiahui Yu, Wei Han, Shibo Wang, Zhengdong Zhang, Yonghui Wu, et al. Conformer: Convolution-augmented transformer for speech recognition. *Proc. Interspeech 2020*, pp. 5036–5040, 2020.

Kai Han, An Xiao, Enhua Wu, Jianyuan Guo, Chunjing Xu, and Yunhe Wang. Transformer in transformer. *Advances in Neural Information Processing Systems*, 34, 2021.

Jonathan Ho, Nal Kalchbrenner, Dirk Weissenborn, and Tim Salimans. Axial attention in multidi-mensional transformers. *arXiv preprint arXiv:1912.12180*, 2019.

Andrew Jaegle, Felix Gimeno, Andy Brock, Oriol Vinyals, Andrew Zisserman, and Joao Carreira. Perceiver: General perception with iterative attention. In *International Conference on Machine Learning*, pp. 4651–4664. PMLR, 2021.

Michael Janner, Qiyang Li, and Sergey Levine. Offline reinforcement learning as one big sequence modeling problem. In *Advances in Neural Information Processing Systems*, 2021.

Angelos Katharopoulos, Apoorv Vyas, Nikolaos Pappas, and François Fleuret. Transformers are rnns: Fast autoregressive transformers with linear attention. In *International Conference on Machine Learning*, pp. 5156–5165. PMLR, 2020.

Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014.

Nikita Kitaev, Lukasz Kaiser, and Anselm Levskaya. Reformer: The efficient transformer. In *International Conference on Learning Representations*, 2019.

Juho Lee, Yoonho Lee, Jungtaek Kim, Adam Kosiorek, Seungjin Choi, and Yee Whye Teh. Set transformer: A framework for attention-based permutation-invariant neural networks. In *International Conference on Machine Learning*, pp. 3744–3753. PMLR, 2019.

James Lee-Thorp, Joshua Ainslie, Ilya Eckstein, and Santiago Ontanon. Fnet: Mixing tokens with fourier transforms. *arXiv preprint arXiv:2105.03824*, 2021.

Hanxiao Liu, Zihang Dai, David So, and Quoc V Le. Pay attention to mlps. *Advances in Neural Information Processing Systems*, 34:9204–9215, 2021a.

Ze Liu, Yutong Lin, Yue Cao, Han Hu, Yixuan Wei, Zheng Zhang, Stephen Lin, and Baining Guo. Swin transformer: Hierarchical vision transformer using shifted windows. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 10012–10022, 2021b.

Ilya Loshchilov and Frank Hutter. Decoupled weight decay regularization. *arXiv preprint arXiv:1711.05101*, 2017.

Xuezhe Ma, Xiang Kong, Sinong Wang, Chunting Zhou, Jonathan May, Hao Ma, and Luke Zettlemoyer. Luna: Linear unified nested attention. *Advances in Neural Information Processing Systems*, 34, 2021.

Stephen Merity, Caiming Xiong, James Bradbury, and Richard Socher. Pointer sentinel mixture models. *arXiv preprint arXiv:1609.07843*, 2016.

Tan Nguyen, Vai Suliafu, Stanley Osher, Long Chen, and Bao Wang. Fmmformer: Efficient and flexible transformer via decomposed near-field and far-field attention. *Advances in Neural Information Processing Systems*, 34, 2021.

Ofir Press, Noah A Smith, and Mike Lewis. Shortformer: Better language modeling using shorter inputs. In *Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing (Volume 1: Long Papers)*, pp. 5493–5505, 2021.

Alec Radford, Jong Wook Kim, Chris Hallacy, Aditya Ramesh, Gabriel Goh, Sandhini Agarwal, Girish Sastry, Amanda Askell, Pamela Mishkin, Jack Clark, et al. Learning transferable visual models from natural language supervision. In *International Conference on Machine Learning*, pp. 8748–8763. PMLR, 2021.

Jack W Rae, Anna Potapenko, Siddhant M Jayakumar, Chloe Hillier, and Timothy P Lillicrap. Compressive transformers for long-range sequence modelling. In *International Conference on Learning Representations*, 2019.

Colin Raffel, Noam Shazeer, Adam Roberts, Katherine Lee, Sharan Narang, Michael Matena, Yanqi Zhou, Wei Li, and Peter J Liu. Exploring the limits of transfer learning with a unified text-to-text transformer. *Journal of Machine Learning Research*, 21:1–67, 2020.

Hongyu Ren, Hanjun Dai, Zihang Dai, Mengjiao Yang, Jure Leskovec, Dale Schuurmans, and Bo Dai. Combiner: Full attention transformer with sparse computation cost. *Advances in Neural Information Processing Systems*, 34, 2021.

Victor Sanh, Albert Webson, Colin Raffel, Stephen Bach, Lintang Sutawika, Zaid Alyafeai, Antoine Chaffin, Arnaud Stiegler, Teven Le Scao, Arun Raja, et al. Multitask prompted training enables zero-shot task generalization. In *The Tenth International Conference on Learning Representations*, 2022.

Imanol Schlag, Kazuki Irie, and Jürgen Schmidhuber. Linear transformers are secretly fast weight programmers. In *Proc. Int. Conf. on Machine Learning (ICML)*, Virtual only, July 2021.

Yangyang Shi, Yongqiang Wang, Chunyang Wu, Ching-Feng Yeh, Julian Chan, Frank Zhang, Duc Le, and Mike Seltzer. Emformer: Efficient memory transformer based acoustic model for low latency streaming speech recognition. In *ICASSP 2021-2021 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pp. 6783–6787. IEEE, 2021.

Yi Tay, Dara Bahri, Liu Yang, Donald Metzler, and Da-Cheng Juan. Sparse sinkhorn attention. In *International Conference on Machine Learning*, pp. 9438–9447. PMLR, 2020a.

Yi Tay, Mostafa Dehghani, Samira Abnar, Yikang Shen, Dara Bahri, Philip Pham, Jinfeng Rao, Liu Yang, Sebastian Ruder, and Donald Metzler. Long range arena: A benchmark for efficient transformers. In *International Conference on Learning Representations*, 2020b.

Yi Tay, Mostafa Dehghani, Dara Bahri, and Donald Metzler. Efficient transformers: A survey. *arXiv preprint arXiv:2009.06732*, 2020c.

Ilya O Tolstikhin, Neil Houlsby, Alexander Kolesnikov, Lucas Beyer, Xiaohua Zhai, Thomas Unterthiner, Jessica Yung, Andreas Steiner, Daniel Keysers, Jakob Uszkoreit, et al. Mlp-mixer: An all-mlp architecture for vision. *Advances in Neural Information Processing Systems*, 34: 24261–24272, 2021.

Lloyd Trefethen. Multivariate polynomial approximation in the hypercube. *Proceedings of the American Mathematical Society*, 145(11):4837–4844, 2017.

Yao-Hung Hubert Tsai, Shaojie Bai, Makoto Yamada, Louis-Philippe Morency, and Ruslan Salakhutdinov. Transformer dissection: A unified understanding of transformer's attention via the lens of kernel. *arXiv preprint arXiv:1908.11775*, 2019.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. *Advances in neural information processing systems*, 30, 2017.

Alex Wang, Amanpreet Singh, Julian Michael, Felix Hill, Omer Levy, and Samuel R Bowman. Glue: A multi-task benchmark and analysis platform for natural language understanding. *arXiv preprint arXiv:1804.07461*, 2018.

Sinong Wang, Belinda Z Li, Madian Khabsa, Han Fang, and Hao Ma. Linformer: Self-attention with linear complexity. *arXiv preprint arXiv:2006.04768*, 2020.

Ruibin Xiong, Yunchang Yang, Di He, Kai Zheng, Shuxin Zheng, Chen Xing, Huishuai Zhang, Yanyan Lan, Liwei Wang, and Tieyan Liu. On layer normalization in the transformer architecture. In *International Conference on Machine Learning*, pp. 10524–10533. PMLR, 2020.

Yunyang Xiong, Zhanpeng Zeng, Rudrasis Chakraborty, Mingxing Tan, Glenn Fung, Yin Li, and Vikas Singh. Nyströmformer: A nyström-based algorithm for approximating self-attention. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 35:16, pp. 14138–14148, 2021.

Jianwei Yang, Chunyuan Li, Pengchuan Zhang, Xiyang Dai, Bin Xiao, Lu Yuan, and Jianfeng Gao. Focal self-attention for local-global interactions in vision transformers. *arXiv preprint arXiv:2107.00641*, 2021.

Zhilin Yang, Zihang Dai, Yiming Yang, Jaime Carbonell, Russ R Salakhutdinov, and Quoc V Le. Xlnet: Generalized autoregressive pretraining for language understanding. *Advances in neural information processing systems*, 32, 2019.

Manzil Zaheer, Guru Guruganesh, Kumar Avinava Dubey, Joshua Ainslie, Chris Alberti, Santiago Ontanon, Philip Pham, Anirudh Ravula, Qifan Wang, Li Yang, et al. Big bird: Transformers for longer sequences. *Advances in Neural Information Processing Systems*, 33:17283–17297, 2020.

Chen Zhu, Wei Ping, Chaowei Xiao, Mohammad Shoeybi, Tom Goldstein, Anima Anandkumar, and Bryan Catanzaro. Long-short transformer: Efficient transformers for language and vision. *Advances in Neural Information Processing Systems*, 34, 2021.

Yukun Zhu, Ryan Kiros, Rich Zemel, Ruslan Salakhutdinov, Raquel Urtasun, Antonio Torralba, and Sanja Fidler. Aligning books and movies: Towards story-like visual explanations by watching movies and reading books. In *The IEEE International Conference on Computer Vision (ICCV)*, December 2015.

Zhenhai Zhu and Radu Soricut. H-transformer-1d: Fast one-dimensional hierarchical attention for sequences. In *Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing (Volume 1: Long Papers)*, pp. 3801–3815, 2021.

A APPENDIX

A.1 ABSTRACTIVE ATTENTIONS

Abstractive attentions are the family of efficient attention approaches in which the lengths of the attention operands are reduced to $M(< N)$ by applying an abstraction function, resulting in reduced complexity of the attention while retaining the form of basic attention computation in Eq. 3. Abstractive attentions can be further categorized to either *resolution preserving* or *non-preserving*, according to which operands are chosen to be abstracted. Resolution non-preserving attention is the result of abstracted queries, further producing abstracted output. This categorization is determined by the requirement of the given task. For example, tasks such as language modeling and machine translation require the full resolution at the output to be retained. In such cases, it is common to have only abstracted keys and values while the query resolution is retained; the abstractive attention can be expressed as

$$\mathbf{y}_i = \mathrm{softmax}\left(\mathbf{q}_i \overline{\mathbf{K}}^\top\right) \overline{\mathbf{V}}, \tag{13}$$

$$\overline{\mathbf{K}} = \left[\overline{\mathbf{k}}_0, ..., \overline{\mathbf{k}}_{j'}, ..., \overline{\mathbf{k}}_{M_k}\right]_1, \tag{14}$$

$$\overline{\mathbf{k}}_{j'} = \phi\left(\{\mathbf{k}_{j \in \Omega_{j'}}\}\right), \tag{15}$$

where $\Omega_{j'}$ denotes the abstraction range with the cardinality $|\Omega_{j'}| = M_k$ for the j'^{th} key abstraction $\overline{\mathbf{k}}_{j'}$ and $\phi(\cdot) : \mathbf{K}_{\Omega_{j'}} \in \mathbb{R}^{|\Omega_{j'}| \times d_h} \to \overline{\mathbf{k}}_{j'} \in \mathbb{R}^{1 \times d_h}$ is a many-to-one abstraction function. The abstracted values $\overline{\mathbf{V}}_{j'}$ can be expressed similarly. The queries $\mathbf{Q}$ can be similarly abstracted to $\overline{\mathbf{Q}}$ as

$$\overline{\mathbf{q}}_{i'} = \phi_q\left(\{\mathbf{q}_{i \in \Omega_{i'}}\}\right), \tag{16}$$

where $\overline{\mathbf{q}}_{i'}$ is the i'^{th} row of $\overline{\mathbf{Q}}$. The attention mechanism is reduced to

$$\overline{\mathbf{y}}_{i'} = \mathrm{softmax}\left(\overline{\mathbf{q}}_{i'} \overline{\mathbf{K}}^\top\right) \overline{\mathbf{V}}, \tag{17}$$

where an attention output vector $\overline{\mathbf{y}}_{i'}$ is obtained at each abstract position i'. In order to restore the resolution of the output, we define a one-to-many mapping function ψ_y as

$$\mathbf{y}_{i \in \Omega_{i'}} = \{\psi_y\left(\overline{\mathbf{y}}_{i'}\right)\}_i. \tag{18}$$

Resolution non-preserving abstraction is often used for the tasks where the full-resolution output is not needed such as sequence-level classification problem. However, in some cases, with additional processing leveraging representations at a lower layer, e.g., cross attention with input tokens, it is possible to restore the resolution (Dai et al., 2020; Jaegle et al., 2021).

A.2 MULTI-SCALE MULTI-RANGE ATTENTIONS (MSMRA)

Although many previous abstractive attention approaches have achieved sub-quadratic or linear complexities, they typically come at the cost of degraded benchmark performance. However, Transformer-based models that leverage multi-scale attention by combining local attention and global attention perform competitively against the standard Transformer; in fact, these models can outperform the standard Transformer on some benchmarks, while still maintaining efficiency (Zhu & Soricut, 2021; Zhu et al., 2021; Nguyen et al., 2021; Ren et al., 2021).

The local attention, also known as sliding window attention, limits the attention range to the vicinity of query locations. That is, the key abstraction with the whole abstraction range and the query location-dependent abstraction function becomes $\overline{\mathbf{K}}_{\mathrm{l},i} = \phi_{k,i}^{\mathrm{sliding}}(\mathbf{K}) = \mathbf{K} \odot (H(i-j-w/2) - H(i-j+w/2))$

for the i^{th} query token, where H is the Heaviside step function, w is the window length, and $\odot$ is the element-wise product. This results in the following equation:

$$\mathbf{y}_{1,i} = \text{softmax}\left(\mathbf{q}_i \overline{\mathbf{K}}_{1,i}^\top\right) \overline{\mathbf{V}}_{1,i} \tag{19}$$

For better computational efficiency, block-wise key abstraction in Equation equation 19 can be adopted as $\overline{\mathbf{K}}_{1,i} = \phi_{k,i}^{\text{block}}(\mathbf{K}) = \mathbf{K} \odot (H(t_i - j - w/2) - H(t_i - j + w/2))$ for a block-wise attention where $t_i = (b - 1/2)w$ for the block index b such that $(b-1)w \le i < bw$.

For the global attention, abstractive attention with either positional abstractions (Zhu & Soricut, 2021; Yang et al., 2021; Ren et al., 2021) or contextual abstractions (Ma et al., 2021; Zhu et al., 2021) can be employed. The former can be loosely seen as having patch embedding in ViT (Dosovitskiy et al., 2020).

MSMRAs can also be categorized according to how the two attentions are combined. While one approach involves concatenating the abstractions of multi-scale keys and values for a single attention operation (Zhu & Soricut, 2021; Zhu et al., 2021; Yang et al., 2021):

$$\mathbf{y}_i = \text{softmax}\left(\mathbf{q}_i \left[\overline{\mathbf{K}}_{1,i}, \overline{\mathbf{K}}_g\right]_1^\top\right) \left[\overline{\mathbf{V}}_{1,i}, \overline{\mathbf{V}}_g\right]_1, \tag{20}$$

another separates attentions at different scales and combining the outputs (Han et al., 2021) (possibly with some weighting coefficients):

$$\mathbf{y}_i = \mathbf{y}_{1,i} + \psi_y\left(\mathbf{y}_{g,i}\right). \tag{21}$$

In this case, other non-attentive methods such as kernel method (Nguyen et al., 2021) can also be used for the global attention.

CST belongs to the latter of the two approaches, where the local and global attentions are performed separately and their outputs are combined. This is closely related to Transformer-In-Transformer (**TNT**) (Han et al., 2021); however, since **TNT** has a path for the local attention that is independent of the global attention, information exchange between patches is not allowed for the features in the local attention path. Unlike **TNT**, the composition of multi-granular attentions in **CST** enables two-way information routing. This is more suitable for modeling highly non-stationary data, such as natural language text data for example, where the locality assumption does not hold.

A.3 CONSIDERATION ON PRACTICAL EFFICIENCY AND EFFECTIVENESS OF **CST**

In this section, we provide an intuition for how and why a multi-scale multi-range attention with $O(NL + N^2/L^2)$ complexity can be a better alternative to the vanilla self-attention than abstraction attentions with linear complexities in terms of both complexity and modeling capability. Improved expressiveness from composition of them is further discussed in Section A.6. A linear complexity can be easily considered to be more efficient than a quadratic complexity. A linear complexity often accompanies another variable; i.e., the abstraction length M in the case of abstractive attention such as (Wang et al., 2020; Ma et al., 2021), resulting in $O(NM)$ complexity. It is obvious that the quadratic complexity $O(N^2)$ is higher than the linear complexity whenever the abstraction length M is smaller than the sequence length, which is mostly true by the definition of *abstraction*. However, when a notion of sequence decimation comes into play, we come to a little different conclusion. Consider an attention on an abstracted sequence of patch embeddings in (Dosovitskiy et al., 2020) or slice embeddings in **CST**. Then the complexity of the abstractive attention becomes a decimated quadratic $O(N^2/L^2)$. In addition to this, if a full-resolution local attention is used as in **CST** or (Han et al., 2021) as a multi-scale multi-range attention, the complexity becomes $O(N^2/L^2 + N/L \cdot L^2) = O(N^2/L^2 + NL)$. We plot the comparison of the linear complexity $O(NM)$ and $O(N^2/L^2 + NL)$ in Figure 3a with several practical choices of the number of abstractions M and the decimation ratio, e.g., slice length, L. Here, one can find that a decimated quadratic complexity attention can have better efficiency a linear complexity attention, when the sequence length is less than a few tens of thousands which is considered as a practical range of sequence lengths in many tasks and data types.

Figures 3b shows effective number of tokens for each abstraction for both cases with the same choices of M and L. While a decimation, e.g., slicing, retains constant numbers of tokens in each abstraction, the linear complexity attention methods that uses fixed number of abstraction has linearly

(a) $O(NM)$ vs. $O(N^2/L^2 + NL)$

(b) Effective number of tokens/abstraction

Figure 3: Comparison between linear complexity attention and **CSA**. **CSA** with the complexity $O(N^2/L^2 + NL)$ is more efficient than linear complexity methods with $O(NM)$ for practical sequence lengths and choices of model-specific hyperparameters M and L. Due to increasing effective number of tokens per abstraction, performance of an abstractive attention with linear complexity can degrade as the sequence length gets large.

increasing effective number of tokens per abstraction with respect to the sequence length. Given a fixed hidden dimension, larger number of effective tokens per abstraction requires the abstraction process to compress more information, resulting in loss of potentially important information and negatively affecting the modeling capability.

Since the complexity of **CST** has a decimated quadratic term N^2/L^2, the efficiency benefit compared to linear-complexity method keeps closing as the sequence length becomes larger, and eventually the efficiency order is reversed, as it can be seen in 3a. However, we argue that our model can still be beneficial in two aspects. First, it is still more efficient than the standard Transformer. Second, it is possible to find an optimal set of hyperparameters such as the slice length L and the extension ratio α which result in comparably efficient and more effective in modeling capability to the linear-complexity counterpart, considering the discussion made in this section on the effective number of tokens per abstraction.

A.4 ADDRESSING FINE-GRAINED CONTEXT FRAGMENTATION

With the stacked slice representation of the sequence described in the previous section, the local attention is strictly bounded resulting in potential context fragmentation (Dai et al., 2019b). While the global attention models the slice-wise interaction to relax this issue, it may not be sufficient to capture the important fine-grained token dependencies.

A simple and intuitive way to allow token-level interaction between slices is to have overlaps in the local attention. The overlapped local attention (or extended local attention) can be computed by having keys $\mathbf{K}_{l,\,ext}$ and values $\mathbf{V}_{l,\,ext}$ transformed from extended stacked slices $\mathbf{S}_{ext} \in \mathbb{R}^{N/L \times \alpha L \times D}$, where $\alpha(\leq 3)$ denotes the extension ratio. The extension can be implemented by concatenating shifted-slices in keys and values as below

$$\mathbf{S}_{ext} = \left[\left[\mathbf{0}_{(\alpha-1)L/2}, \mathbf{S}_{:-1,(3-\alpha)L/2:L}\right]_1, \mathbf{S}, \left[\mathbf{S}_{1:,0:(\alpha-1)L/2}, \mathbf{0}_{(\alpha-1)L/2}\right]_1\right]_2, \quad (22)$$

where the Python notation of indices selection is used. As the local attention has longer range, the corresponding positional embedding P_l needs to have the extended length αL for $\mathbf{K}_{l,\,ext}$. Extended

local attention leads to the complexity increase to $O(\alpha N L)$ for the local attention and the parameter count increase to $\alpha L D$ for the local positional embedding.

A.5 Slice Extension and Multi-Scale Causal Mask for Autoregressive Sequence Modeling

For the use of **CST** in autoregressive sequence processing, e.g., autoregressive language modeling and generation, we additionally design causal masks and slice extension scheme. In the local token-level attention, it is sufficient to apply a $L \times L$ causal mask map to the score tensor $Q_l K_l^\top$, to guarantee causality where lower triangular including the diagonal elements to be zero and $-\infty$ elsewhere. However, since the leftmost tokens in each slice has no or very little tokens to attend, we extend the keys and values only on the left-hand side to encourage better fine-grained dependency modeling, i.e.,

$$\mathbf{S}_{\text{AR, ext}} = \left[\left[\mathbf{0}_{(\alpha-1)L/2}, \mathbf{S}_{:-1,(3-\alpha)L/2:L} \right]_1, \mathbf{S} \right]_2. \tag{23}$$

For the slice-wise global attention, extra care should be taken. First, to prevent leftward information leak during obtaining the slice embedding via mean pooling, the diagonal elements in the $N/L \times N/L$ mask map are set to be $-\infty$ in contrast to the local counterpart. Second, at the slice index (coarse time step) t, the time-shifted query $\mathbf{Q}_{g,t-1}$ is used for query instead of $\mathbf{Q}_{g,t}$ for the same reason. In our experiments on autoregressive language modeling, we use this approach.

Since, in the global attention, no information of tokens in current slice is taken into account because of the query shift and the attention mask excluding diagonal elements, there is missing information from coarse-grained modeling in the current design. We leave design of more advanced autoregressive modeling as a future work. As an alternative, one may consider using token-level accumulated query slice embedding at a larger computational cost, which is essentially equivalent to performing attention with abstraction in only keys and values.

A.6 Improved Expressiveness of **CST** Slice Attention

Recall from Eq.equation 10 that the attention mechanism under consideration takes the form,

$$\mathbf{Y} = \mathbf{Y}_l + \psi(\mathbf{Y}_g) \tag{24}$$

where $\mathbf{Y}_l$ represents local attention, $\mathbf{Y}_g$ represents global attention and $\psi(\cdot)$ is a (linear) one-to-many map. In this section, we will compare **CST** with the H-transformer described in Zhu & Soricut (2021). In particular, we argue that, for a given number of weights (degrees of freedom), our proposed attention mechanism, which involves the *composition* of attention mechanisms, is more expressive than the H-matrix-based approach proposed Zhu & Soricut (2021).Zhu & Soricut (2021) shares similar characteristics with **CST**, but does not involve composition, which explains our superior prediction performance (Section 5).

To explain why this is so, we first define

$$\gamma\left(\mathbf{X}; \mathbf{W}_q, \mathbf{W}_k, \mathbf{W}_v\right) = \text{softmax}\left((\mathbf{X}\mathbf{W}_q)(\mathbf{X}\mathbf{W}_k)^T\right)(\mathbf{X}\mathbf{W}_v), \tag{25}$$

which is the standard attention mechanism found in Eq.equation 2. Here, $\mathbf{X}$ is generally a matrix or a 3-tensor; in the latter case, we apply attention independently to each matrix slice along the third dimension. Expressing our local and global attention using this notation leads to,[1]

$$\mathbf{Y}_l^{CS} = \gamma\left(\mathbf{S}; \mathbf{W}_{1,q}, \mathbf{W}_{1,k}, \mathbf{W}_{1,v}\right) \in \mathbb{R}^{N/L \times L \times D} \tag{26}$$

$$\mathbf{Y}_g^{CS} = \gamma\left(\mathbf{Y}_l^{CS} \times_2 \mu; \mathbf{W}_{g,q}, \mathbf{W}_{g,k}, \mathbf{W}_{g,v}\right) \in \mathbb{R}^{N/L \times D} \tag{27}$$

where $\mu = \left[\frac{1}{L}, \frac{1}{L}, ..., \frac{1}{L}\right]^T$ is a fixed vector of mask values, $\mathbf{S}$ corresponds to the stack of L-length slices of $\mathbf{X}$ described in Section 4.1, and $\times_2$ indicates a tensor product along the second dimension, i.e.,

$$\left[\mathbf{Y}_l^{CS} \times_2 \mu\right]_{ij} = \sum_{k=1}^{L} [\mathbf{Y}_l^{CS}]_{ijk}\, \mu_k \tag{28}$$

---

[1]In practice, it is common to have equal weights at local and global scales, i.e., $W_{l,\cdot} = W_{g,\cdot}$. This is a special case of the analysis presented here and changes the conclusion in no significant way.

which corresponds to mean pooling within each slice. For the purpose of comparison, we focus on a 2-level H-transformer where each element at level 1 has L children at level 0.[2] In this case, it can be shown that the H-tranformer approximation takes the form of Eq. equation 24 with,[3]

$$\mathbf{Y}_1^H = \gamma\left(\mathbf{S}; \mathbf{W}_{1,q}, \mathbf{W}_{1,k}, \mathbf{W}_{1,v}\right) = \mathbf{Y}_1^M \in \mathbb{R}^{N/L \times L \times D} \tag{29}$$

$$\mathbf{Y}_g^H = \gamma\left(\mathbf{S} \times_2 \mu; \mathbf{W}_{g,q}, \mathbf{W}_{g,k}, \mathbf{W}_{g,v}\right) \in \mathbb{R}^{N/L \times D} \tag{30}$$

Note that the main difference between H-Transformer these and **CST** lies in Eq.equation 30 and Eq.equation 27; in the former, the argument to the global attention is $\mathbf{S} \times_2 \mu$, whereas it is $\mathbf{Y}_1^{CS} \times_2 \mu$ in the latter.

To demonstrate our claim, let us first introduce some quantities of interest, starting with the families of parameterized functions that the aforementioned attention mechanisms encompass. First, assume without loss of generality that all the weights are limited to the interval $[-1, 1]$.[4] Then, any attention function learned during the training process must belong to the following sets,

$$\mathcal{Y}_1^{CS} := \left\{ \mathbf{Y} \in \mathbb{R}^{N/L \times L \times D} \ : \ \mathbf{Y}_{ijk} = \gamma_{ijk}(\mathbf{S}; \mathbf{W}_{1,q}, \mathbf{W}_{1,k}, \mathbf{W}_{1,v}) \ \forall \ i, j, k \right\} \tag{31}$$

$$\mathcal{Y}_g^{CS} := \left\{ \mathbf{Y} \in \mathbb{R}^{N/L \times D} \ : \ \mathbf{Y}_{ij} = \gamma_{ij}(\sigma(\mathbf{S}) \times_2 \mu; \mathbf{W}_{g,q}, \mathbf{W}_{g,k}, \mathbf{W}_{g,v})), \ \sigma(\cdot) \in \mathcal{Y}_1^M \right\} \tag{32}$$

in the case of **CST** and,

$$\mathcal{Y}_1^H := \left\{ \mathbf{Y} \in \mathbb{R}^{N/L \times L \times D} \ : \ \mathbf{Y}_{ijk} = \gamma_{ijk}(\mathbf{S}; \mathbf{W}_{1,q}, \mathbf{W}_{1,k}, \mathbf{W}_{1,v}) \ \forall \ i, j, k \right\} = \mathcal{Y}_l^H \tag{33}$$

$$\mathcal{Y}_g^H := \left\{ \mathbf{Y} \in \mathbb{R}^{N/L \times D} \ : \ \mathbf{Y}_{ij} = \gamma_{ij}(\mathbf{S} \times_2 \mu; \mathbf{W}_{g,q}, \mathbf{W}_{g,k}, \mathbf{W}_{g,v}) \right\} \tag{34}$$

in the case of H-transformer. We want to show that $\mathcal{Y}_g^{CS}$ has more expressive set than $\mathcal{Y}_g^H$, which explains why **CST** exhibits better empirical prediction performance than its competitors. To this end, let us introduce the following quantities: Let $p(x)$, $q(x)$ be polynomials of Euclidean degree d from $\mathbb{R}^M$ to $\mathbb{R}$. We denote by $S_{M,d}$ the set of rational functions with numerator and denominator of Euclidean degree at most d, i.e.,

$$S_{M,d} := \left\{ \frac{p(\mathbf{x})}{q(\mathbf{x})} \ : \ \deg(p), \deg(q) \leq d, \ \mathbf{x} \in \mathbb{R}^M \right\}$$

imbued with the metric,[5]

$$d\left(\frac{p(\mathbf{x})}{q(\mathbf{x})}, \frac{a(\mathbf{x})}{b(\mathbf{x})} \right) := ||p(\mathbf{x}) - a(\mathbf{x})||_\infty + ||q(\mathbf{x}) - b(\mathbf{x})||_\infty \tag{35}$$

where $||f(\mathbf{x})||_\infty = \max_{\mathbf{x} \in [-1,1]^M} |f(\mathbf{x})|$. We also introduce $S_{M,\infty}$ to indicate the ratio of real analytic functions, which is a vector space. Further, given any fixed positive $\epsilon \in \mathbb{R}$, we define,

$$S_{M,d}^\epsilon := \left\{ \frac{p(\mathbf{x})}{q(\mathbf{x})} \in S_{M,\infty} \ : \ d\left(\frac{p(\mathbf{x})}{q(\mathbf{x})}, S_{M,d} \right) \leq \epsilon \right\} \tag{36}$$

as the ϵ-ball surrounding $S_{M,d}$ in the topology induced on $S_{M,\infty}$ by the metric. Clearly, for any fixed dimension M, $\epsilon > 0$ and Euclidean degrees $d' > d$, the family of functions $S_{M,d'}^\epsilon$ is more expressive than $S_{M,d}^\epsilon$, since the latter is a proper subset of the former, i.e., $S_{M,d} \subset S_{M,d'}$.

---

[2]More levels have little impact on our conclusion since H-transformers ultimately exhibit the same level of nonlinearity in the weights whatever the number of levels.

[3]Refer to Eq.(29) in Zhu & Soricut (2021) for two levels, i.e., $Y = Y^{(0)} + P^{(0)} \tilde{Y}^{(1)}$. In this case, $P^{(0)}$ corresponds to the one-to-many map $\psi(\cdot)$ whereas $\tilde{Y}^{(1)} = \tilde{A}^{(1)}(R^{(1)^T} V)$ corresponds to applying the level-1 matrix $\tilde{A}^{(1)}$ to the vector V after *averaging over slices* (i.e., applying $R^{(1)^T}$). In this context, this is analogous to applying a global attention to the averaged slices vector, namely, $\mathbf{S} \times_2 \mu$.

[4]Any finite bound may be use and has little impact as long as all expressions are subject to the same constraints.

[5]It can be shown that $d(\cdot, \cdot)$ is in fact a proper metric on $S_{M,d}$.

Next, we show that the families of functions $\mathcal{Y}_\mathrm{g}^{CS}$ and $\mathcal{Y}_\mathrm{g}^{H}$ are in fact subsets of $S_{M,d'}^\epsilon$ and $S_{M,d}^\epsilon$ respectively, for appropriately-chosen values of ϵ, d' and d with $d' > d$. To do so, we need the following result adapted from Trefethen (2017),

Let $f(\mathbf{x})$ be an analytic function from $\mathbb{R}^M$ to $\mathbb{R}$. Then for every fixed $\epsilon > 0$, there exists a polynomial $p(\mathbf{x})$ of Euclidean degree $d(\epsilon) = O(\log(\epsilon))$ such that,

$$||f(\mathbf{x}) - p(\mathbf{x})||_\infty = \max_{\mathbf{x} \in [-1,1]^D} |f(\mathbf{x}) - p(\mathbf{x})| \le \epsilon \tag{37}$$

We are now ready to demonstrate our main result, For any fixed $\epsilon > 0$, there exists some Euclidean degree $d(\epsilon) = O(\log(\epsilon))$ such that,

$$\mathcal{Y}_\mathrm{g}^{H} \subseteq S_{M,d(\epsilon)}^\epsilon, \tag{38}$$

and,

$$\mathcal{Y}_\mathrm{g}^{CS} \subseteq S_{M,4\,d(\epsilon)}^\epsilon, \tag{39}$$

where M corresponds to the total number of weights. First, recall that (assuming a single head) the parameterized functions $\gamma(\cdot)$ from Eq. equation 25 takes the following form

$$\gamma_{ij}\left(\mathbf{X};\, \mathbf{W}_q, \mathbf{W}_k, \mathbf{W}_v\right) = \frac{\sum_k e^{[(\mathbf{X}\mathbf{W}_q)(\mathbf{X}\mathbf{W}_k)^T]_{ik}}\,[\mathbf{X}\mathbf{W}_v]_{kj}}{\sum_{m,n} e^{[(\mathbf{X}\mathbf{W}_q)(\mathbf{X}\mathbf{W}_k)^T]_{mn}}}. \tag{40}$$

This should be recognized as the ratio of two analytic functions (because the exponential is analytic) paramatrized by the elements of the weight matrices. Following Theorem A.6, for every fixed set of weights $\mathbf{W}_g = [\mathbf{W}_q, \mathbf{W}_k, \mathbf{W}_v]$, there exists polynomials $\{p_{ij}^{\mathbf{W}_g}(\mathbf{x})\}$, $\{q_{ij}^{\mathbf{W}_g}(\mathbf{x})\}$ of Euclidean degree $d(\epsilon) = O(\log(\epsilon))$ such that

$$\max_{\mathbf{x} \in [-1,1]^D} \left| \sum_k e^{[(\mathbf{X}\mathbf{W}_q)(\mathbf{X}\mathbf{W}_k)^T]_{ik}}\,[\mathbf{X}\mathbf{W}_v]_{kj} - p_{ij}^{\mathbf{W}_g}(\mathbf{x}) \right| \le \frac{\epsilon}{2} \tag{41}$$

$$\max_{\mathbf{x} \in [-1,1]^D} \left| \sum_{m,n} e^{[(\mathbf{X}\mathbf{W}_q)(\mathbf{X}\mathbf{W}_k)^T]_{mn}} - q_{ij}^{\mathbf{W}_g}(\mathbf{x}) \right| \le \frac{\epsilon}{2}. \tag{42}$$

This means that

$$d\left(\gamma_{ij}\left(\mathbf{X};\, \mathbf{W}_q, \mathbf{W}_k, \mathbf{W}_v\right),\, \frac{p_{ij}^{\mathbf{W}}(\mathbf{x})}{q_{ij}^{\mathbf{W}}(\mathbf{x})} \right) \le \epsilon \tag{43}$$

and that $\gamma_{ij}(\,\cdot\,; \mathbf{W}_q, \mathbf{W}_k, \mathbf{W}_v) \in S_{M,d(\epsilon)}^\epsilon$. In particular, this shows that $\mathcal{Y}_\mathrm{g}^{H} \subset S_{M_g,d(\epsilon)}^\epsilon$ since every element of $\mathcal{Y}_\mathrm{g}^{H}$ has the form of Eq.equation 40. A similar conclusion can be reached for $\mathcal{Y}_\mathrm{l}^{H}$ and $\mathcal{Y}_\mathrm{l}^{CS}$ since elements of these families have the same functional form as those of $\mathcal{Y}_\mathrm{g}^{H}$.

All that remains is $\mathcal{Y}_\mathrm{g}^{CS}$. In this case, it suffices to note that the result of polynomial composition creates polynomials with Euclidean degree bounded by the sum of the degree of the polynomials involved in the composition. Indeed, the above analysis shows that elements of $\mathcal{Y}_\mathrm{g}^{CS}$ are within ϵ distance from rational functions of the form,

$$\frac{p_{ij}^{\mathbf{W}_g}\left(\frac{1}{L}\sum_{k=1}^{L} \frac{p_{ijk}^{\mathbf{W}_l}(\mathbf{x})}{q_{ijk}^{\mathbf{W}_l}(\mathbf{x})} \right)}{q_{ij}^{\mathbf{W}_g}\left(\frac{1}{L}\sum_{k=1}^{L} \frac{p_{ijk}^{\mathbf{W}_l}(\mathbf{x})}{q_{ijk}^{\mathbf{W}_l}(\mathbf{x})} \right)}, \tag{44}$$

for some polynomials $\{p_{ijk}^{W_l}(\mathbf{x})\}$, $\{q_{ijk}^{W_l}(\mathbf{x})\}$ of degree $d(\epsilon)$. Upon expanding the polynomials and expressing terms using a common denominator, this expression should be recognized as the ratio of two polynomials, each of which has degree $4d(\epsilon)$, following polynomial composition. Thus, we conclude that $\mathcal{Y}_\mathrm{g}^{CS} \subset S_{M,4\,d(\epsilon)}^\epsilon$. This proves our claim. In other words, Proposition A.6 shows that our proposed family of attention mechanisms belongs to $S_{M,4\,d(\epsilon)}^\epsilon$ which possesses more expressive power (since $4\,d(\epsilon) > d(\epsilon)$) than the family of functions $S_{M,d(\epsilon)}^\epsilon$ to which global attention mechanism without composition, such as H-transfomers ($\mathcal{Y}_\mathrm{l}^{H} + \psi\left(\mathcal{Y}_\mathrm{g}^{H}\right)$), belong.

We claim that this is the reason why our proposed approach performs better than the approach proposed by (Zhu & Soricut, 2021) and other similar mechanisms where linear combinations of attentions, rather than composition, are used. In other words, for the same number of parameters (weights), our proposed approach can capture more complex attentive interactions than that of (Zhu & Soricut, 2021) and related mechanisms, which leads to a richer set of attentions over which to train the network and, ultimately, better performance.

A.7 MORE INFORMATION AND DETAILS ON LRA BENCHMARK

A.7.1 EXPERIMENTAL SETUP

We follow the experimental setup described in (Xiong et al., 2021) with a few exceptions in hyperparameters. Specifically, we use the same Transformer encoder network backbone that consists of 2 transformer layers with pre-norm (Xiong et al., 2020) with 4 attention heads and the model dimension 256 across all tasks. Further, we replace the self-attention sub-layer by efficient attention alternatives including the slice attention of **CST**. To obtain label output for classification, we additionally use a classification head network with 2 fully-connected layers of the same hidden dimension with the feed-forward network in the backbone network and a ReLU layer between them. We aggregate the output sequence from the encoder by a mean pooling across the length dimension and feed it to the classification head. For a fair comparison between models with different characteristics, we optimize the learning rates for the baseline Transformer model on each task while keeping all other hyperparameters fixed. For the experimental setup, this allows for a strong baseline model, advantageous for the standard Transformer. We then evaluate each model with a learning rate search within a small bracket $[0.5l_0, l_0, 2l_0]$, where l_0 is the base learning rate providing the highest validation accuracy of the Transformer in each task, and report the test accuracy of the model trained with a learning rate that gives the highest validation accuracy among the bracket. We note that our experiments have stronger baselines than those found in literature (Tay et al., 2020b; Xiong et al., 2021) as highlighted in Table 1. For other efficient Transformer models, we perform a model-specific hyperparameter search as described below and report the test accuracy of the best models.

For the Long Range Arena benchmark, we performed experiments on our PyTorch version implementation of the original open-source JAX/Flax code (Tay et al., 2020b) where we followed its dataset preparation procedure and verified the results, and implemented our model on it. Since we found the performances of LRA tasks have relatively high variances, especially on certain tasks such as *ListOps*, we first performed a hyperparameter search with the standard Transformer with the base setup in (Xiong et al., 2021). The hyperparameters we used for the search include number of layers $\{2, 4\}$, number of attention heads $\{2, 4\}$, and model dimension $\{128, 256\}$, and learning rate $\{1, 2, 5\} \times 10^{\{-3, -4, -5, -6\}}$. In addition, for better convergence, we also increased the number of training steps in some tasks. The hyperparameters we determined after the search can be found in Table 4. As this step is essentially a hyperparameter tuning for the baseline Transformer, we note that we have stronger baseline Transformer model than those reported in (Tay et al., 2020b) and (Xiong et al., 2021), and compare them in Table 1. While fixing all other hyperparameters, we performed a learning rate sweep using a learning rate bracket as described in 5.1. For each model and task, we pick the best model on the validation dataset with early stopping, and report its accuracy on the test dataset. For the model training, we used AdamW optimizer (Loshchilov & Hutter, 2017) with linear learning rate warmup and decay, but without weight decay and other training hyperparameters as shown in Table 4.

Since each efficient Transformer has its own hyperparameters and they can affect the performance, we tried a few different values, around the default values used in each paper. Specifically, they are: the number of random features $\{64, 128, 256\}$ in Performer (Choromanski et al., 2020), the projection length $\{64, 128, 256\}$ in Linformer (Wang et al., 2020) and Luna (Ma et al., 2021), the number of landmarks $\{64, 128, 256\}$ in Nyströmformer (Xiong et al., 2021), the number of hashes $\{2, 4\}$ in Reformer (Kitaev et al., 2019), the numerical rank of off-diagonal blocks $\{16, 32, 64, 128\}$ in H-Transformer-1D (Zhu & Soricut, 2021), and the local window segment size $\{8, 16, 32\}$ and the rank of dynamic projection $\{32, 64\}$ in Long Short Transformer (Zhu et al., 2021). For Long Short Transformer, we optionally used additional 1D depth-wise convolution with the kernel 35 as described in (Zhu et al., 2021). For scatterbrain (Chen et al., 2021a), we follow the default setting for the model specific hyperparameters as in the official code release. Specifically, for text task, we have cluster size for query/key = 16, number of features = 16. For Listops task, we have cluster size

Table 4: Hyperparameters for LRA benchmark

Network Configuration						
D_{embed}	D_{model}	D_{FFN}	d_{h}	n_{head}	n_{layer}	p_{dropout}
256	256	1024	64	4	2	0.1

Task-Specific Training Configuration					
Task	N	Batch Size	LR_0	$n_{\mathrm{step,warmup}}$	$n_{\mathrm{step,train}}$
ListOps	2k	32	1×10^{-5}	1000	20k
Text	4k	32	2×10^{-5}	8000	20k
Retrieval	4k	32	5×10^{-5}	800	30k
Image	1k	256	2×10^{-4}	175	35k
Pathfinder	1k	256	1×10^{-4}	312	62k

Table 5: Performances of **CST** with various slice lengths L, extension ratios α, positional embeddings **P**, and combinations of local and global attentions, on LRA benchmark

L	α	**P**	Local-Global	ListOps	Text	Retrieval	Image	Pathfinder	Average
8	1	MS-VIPE	Composition	37.45	**77.23**	84.15	51.27	76.32	**65.28**
16	1	MS-VIPE	Composition	37.90	73.60	84.00	51.39	76.97	64.77
32	1	MS-VIPE	Composition	39.01	69.24	83.92	**54.21**	76.73	64.62
64	1	MS-VIPE	Composition	38.91	66.87	83.59	51.83	**78.12**	63.86
8	1	Conventional	Composition	38.26	69.39	83.21	47.77	70.46	61.82
16	1	Conventional	Composition	**39.31**	68.22	82.68	49.02	71.30	62.11
32	1	Conventional	Composition	38.81	66.09	82.16	47.81	71.16	61.21
64	1	Conventional	Composition	37.60	65.28	82.27	47.58	72.49	61.04
16	2	MS-VIPE	Composition	37.90	72.81	**84.62**	53.41	74.87	64.72
16	3	MS-VIPE	Composition	37.60	70.08	84.42	48.95	74.52	63.11
16	1	MS-VIPE	Parallel	37.85	71.15	84.02	46.05	75.13	62.84
16	1	MS-VIPE	Global First	36.19	73.09	84.16	43.36	71.30	61.62

for query/key = 32 and number of features = 32. For image and pathfinder task, we have cluster size = 16 and number of features = 16. For retrieval task, we have cluster size for query/key = 64 and number of features = 64. Additionally, we have number of hashes = 2 for all tasks. While each option produces different performances requiring different computation and memory costs, we found variants in each model have similar accuracy and report only the best accuracy among them and the corresponding complexity as comparing them is out of scope of this paper.

A.7.2 ABLATION STUDY ON LRA

We investigate the effect of each component in **CST** by performing an ablation study. We set the slice length of 16 without extension for local attention as the base configuration. Then, we train a **CST** variant from scratch where one component is changed. Specifically, we consider the variations in: 1) Slice length, 2) Extended local attention, 3) Positional embedding, and 4) Composition of MSMRA. The test accuracies of the variants are given in Table 5. We note that all variants of **CST** consistently outperforms other models, except for one case of the global first composition.

Slice Length   First, we vary the slice length L and test how the local attention range and abstraction length for the global attention affects the accuracy. Intuitively, one can expect a trade-off between fine-grained token interaction modeling and coarse-grained global context capturing, since in the extreme cases either local attention or global attention converges to the standard self-attention[6]. While each task has its own best L, shorter slice length tends to give better overall accuracy. One possible

---

[6]**CSA** converges to the standard self-attention with the global attention at $L = 1$ or the local attention at $L = N$ with $\mathbf{V} = \mathbf{X}\mathbf{W}_v^2$

Table 6: Performances of **CST** with different local modeling and slice aggregation methods, on LRA benchmark. (L=16, α=1)

Local Modeling	Aggregation	ListOps	Text	Retrieval	Image	Pathfinder	Average
Attention	Mean Pooling	37.90	73.60	84.00	51.39	76.97	64.77
MLP ($d_{\text{hidden}} = 16$)	Mean Pooling	37.65	66.12	81.66	45.47	74.51	61.08
MLP ($d_{\text{hidden}} = 32$)	Mean Pooling	37.25	69.70	83.63	46.79	74.19	62.31
Attention	Max Pooling	38.05	73.72	84.61	47.88	73.97	63.65
Attention	Linear Projection	37.70	73.36	82.33	50.24	72.79	63.28

interpretation is that $L = 8$ or 16 provides better-formed tokens to the global attention in a dynamic manner by the local attention.

Local Attention Extension Ratio   While slight improvements are observed on *Retrieval* and *Image* tasks, on the contrary to our expectation, extended local attention does not always improve the accuracy on LRA tasks. We conjecture it is because LRA datasets has tokens of very fine granularity, i.e., byte-level or pixel-level, and abstraction of the extended local attention output may result in redundant information for global attention. Thus, we evaluate the effect of the extension ratio on a dataset with a coarser-grained tokenization in the Section 5.2.

Position Embedding   We compare the MS-VIPE with the conventional learned positional embedding that is applied at the bottom embedding layer of the network. MS-VIPE shows consistent improvement over the conventional positional embedding except for the *ListOps* task where the fined-grained order of each token is essential in this particular task.

Combination of MSMRA   Instead of the proposed composition of MSMRA that has a serial connection of MSMRA in the local-global order, we try two different connections, i.e., parallel and global-local connection. Both of them degrade the accuracy compared to the local-global composition, supporting effectiveness of our design.

Local Modeling with MLP   As shown in (Tolstikhin et al., 2021) and (Liu et al., 2021a), a multilayer perceptron (MLP) can effectively replace the attention without loss of accuracy in some applications. In **CST**, since the slice length is fixed and relatively short, use of MLP instead of attention can be considered as another source of efficiency with a small increase of parameters. We evaluate a variant of **CST** with 2-layer MLP replacing the local attention, with 2 different hidden dimensions $d_{\text{hidden}} = 16$ or 32 while $L = 16$ and $\alpha = 1$. MLP in each slice is equivalent to 1D convolution with the kernel size and the stride set to the same with the slice length. We observe that using attention for local modeling module is still preferred in terms of accuracy.

Slice aggregation   We further evaluate use of different aggregation methods from the simple mean pooling. Similarly to (Rae et al., 2019), we try max pooling and linear projection. Again, a linear projection is equivalent to 1D convolution with the kernel size and stride set to L. While showing comparable results, they lead to degraded performances in Image and Pathfinder tasks. One can expect better accuracy from the linear projection as it is a general form of other pooling methods, but this result can be interpreted as limitation of a simple linear projection for modeling sequence translations. The mean pooling has already generalized well, and with better initialization, linear projection is expected to converge to the mean pooling or slightly better.

A.8   MORE ON AUTOREGRESSIVE LANGUAGE MODELING

A.8.1   EXPERIMENTAL DETAIL

For the autoregressive language modeling experiment, we use an open-source language modeling experiment framework (Schlag et al., 2021) and plug in our **CST** implementation. We follow all training setup including dataset preparation and hyperparameters given in (Dai et al., 2019a), and evaluate with the small-sized network configuration: 16 layers, 8 attention heads, 128 model dimension, and 2,048 hidden dimension. We train all models using the Adam optimizer (Kingma

Table 7: **CST** ablation study on WikiText-103

L	α	Context Length	Valid PPL	Test PPL	Relative Speedup
8	1	256	39.15	39.78	$1.50\times$
8	2	256	36.59	37.33	$1.51\times$
8	3	256	36.10	36.78	$1.49\times$
16	2	256	35.78	36.52	$1.52\times$
16	3	256	35.28	36.04	$1.47\times$
32	2	256	34.83	35.60	$1.54\times$
32	3	256	34.18	34.98	$1.51\times$

Table 8: **CST** ablation study on WikiText-103 with 1024 context length

Attention	Context Length	Test PPL
Full Attention	1024	25.258
Reformer	1024	27.68
Performer	1024	66
Scatterbrain	1024	26.72
CST($L = 32, \alpha = 3$)	1024	26.82
CST($L = 32, \alpha = 2$)	1024	29.48

& Ba, 2014), the cosine annealing learning rate scheduler with 2000 warmup steps while the base learning rate is 2.5×10^{-4} for 500K steps with the batch size of 96.

We also conduct autoregressive language modeling experiments with 1024 sequence length. Here, we roughly follow the experiment setup used in (Chen et al., 2021a). The larger model has 512 model dimension instead of 128, and we change the learning rate to 5×10^{-4}, number of steps to 90K, and batch size to 32, while keeping all the remaining hyperparameters same as that of the small model.

Different choices of slice length L and extension ratio α results in the same local attention range. For instance, the combination of $L = 8, \alpha = 3$ has the same key/value lengths with those in the $L = 16, \alpha = 1$ setting, i.e., $L \times (3-1)/2 = L$. However, since the abstraction length and the resulting granularity of the global attention only depends on L, the choices of these hyperparameters can affect the performance differently. We examine how the performance is affected by this configuration. To this end, we evaluate **CST** with combinations of a set of slice lengths $\{8, 16, 32\}$ and a set of extension ratios α $\{1, 2, 3\}$.

To ensure that the current query token has no interaction with the future key tokens, we design the causal mask and local attention extension scheme to better suit **CSA** as described in Section A.5, and use it throughout this experiment.

A.8.2 ABLATION STUDY

We show how different **CST** hyperparameters affects the performance on WikiText-103 autoregressive language modeling in Table 7. These results are computed using the MS-VIPE positional embedding. It can be observed that models with smaller slice length with local attention extension performs comparable to models with larger slice length without extension, while being more efficient than their non-extended counterparts.

We demonstrate the relative speedup obtained by dividing the training runtime of the regular transformer model with the runtime of **CST** on `NVIDIA RTX 2080` GPU with the batch size of 16. We report the average speed up over 100 training steps.

In Table 8 we compare the result for our training on 1024 context length with other models. It's seen that **CST** outperforms Reformer and Performer while achieveing competitive performance with Scatterbrain. We believe a better hyperparameter search will further improve the results here.

Table 9: Bidirectional MLM and NLU transfer learning evaluation on GLUE benchmark.

Model	MLM	COLA	MNLI	MRPC	QNLI	QQP	RTE	SST	STSB	GLUE Average
BERT$_{base}$	**4.84**	**60.63**	**83.35**	**91.17**	**90.04**	**87.67**	**69.68**	**92.89**	**87.43**	**82.86**
Nyströmformer (64)	6.77	39.39	78.75	87.23	87.35	85.64	54.87	90.48	84.28	76.00
Performer (64)	6.44	46.64	77.48	82.23	85.70	85.80	57.76	90.02	78.00	75.46
Luna (64)	5.63	42.63	78.26	82.94	85.78	84.18	59.21	90.94	75.89	74.98
FNet	8.62	44.58	75.15	84.00	84.15	84.61	63.18	89.33	82.84	75.98
CST ($L = 16, \alpha = 1$)	6.00	58.49	76.45	81.76	84.44	85.24	59.57	91.74	73.77	76.43
CST ($L = 16, \alpha = 2$)	5.42	58.87	78.04	82.39	85.52	85.70	60.29	92.20	75.59	77.33
CST ($L = 16, \alpha = 3$)	5.28	55.98	79.68	83.49	84.83	86.90	61.37	92.20	81.67	78.27
CST ($L = 32, \alpha = 1$)	5.77	60.34	78.47	83.06	85.17	86.36	59.93	91.74	78.26	77.92
CST ($L = 32, \alpha = 2$)	5.30	57.34	80.73	85.85	86.31	87.08	59.21	91.97	85.95	79.31
CST ($L = 64, \alpha = 1$)	5.56	59.69	81.12	89.42	88.21	87.42	61.37	92.43	87.76	80.93

A.9 MORE INFORMATION AND DETAILS ON BIDIRECTIONAL MASKED LANGUAGE MODELING AND GLUE BENCHMARK

In this section, we present more details about the experimental setup and results on the bidirectional masked language modeling (MLM) task Devlin et al. (2018) and the natural language understanding tasks in the GLUE benchmark Wang et al. (2018) with discussion.

A.9.1 EXPERIMENTAL SETUP

We pre-train transformer models with the masked language modeling (MLM) objective on Book-Corpus Zhu et al. (2015) and English Wikipedia. After pre-training, the models are fine-tuned on downstream natural language understanding tasks from GLUE benchmark Wang et al. (2018). We follow the experimental setup of Devlin et al. (2018) for conducting both pre-training and fine-tuning experiment, including datasets, masking rate, batch size, and optimizer settings, with several exceptions. We pre-train the models for 900k steps with sequences of 128 tokens. This corresponds to the first phase of BERT pre-training and we consider it to be enough for evaluating on GLUE tasks while expediting the experiment.

With the baseline network architecture of BERT$_{base}$ Devlin et al. (2018), we replace its self-attention layer with different types of efficient attentions such as Nyströmformer, Performer, Luna, and FNet.

For downstream NLU tasks, we also follow the setup of Devlin et al. (2018) with one minor change: instead of prepending [CLS] token in the input sequence, we use mean pooling to get the classifier input vector from the sequence output, as discussed in the following part of this section.

A.9.2 RESULTS AND DISCUSSION

As shown in Table 9, we can see that **CST** outperforms competing efficient transformers in terms of MLM perplexity. It can be seen that, while **CST**s achieve consistently lower perplexity than most of the efficient transformers, its perplexity decreases as slice length and extension ratio increases. However, **CST** does not outperform BERT$_{base}$ on contrary to our results on the LRA benchmark. We conjecture this is due to fine-grained masking strategy in the original MLM objective. The MLM pre-training stage involves replacing random tokens in the input sequence with a dummy token that the model must predict. After applying the positional embedding, replacing a standard token with a dummy token, i.e., [MASK], translates to injecting high-frequency noise into the input sequence. **CST** and other efficient attention alternatives are approximations to the full attention, which must truncate the high-frequency modes in exchange for faster evaluation. In MLM pre-training, all of the input sequences have high-frequency content that attention approximations have difficulty capturing. Meanwhile, the sequences in the LRA benchmark are long, low-frequency sequences which can be efficiently compressed. An alternative pre-training method could eventually be developed specifically for efficient transformers that circumvents this issue.

On downstream NLU classification tasks, **CST** also outperforms among the efficient transformers. But with under-performing pre-trained models compared to BERT, similar degradation trend is observed in evaluation on downstream tasks after fine-tuning them.

One drawback of the current version of **CST** in the original setting is that the use of [CLS] token is not trivial. [CLS] token can be seen as a global token that summarizes the sequence in the context of

the given classification task, and it is often prepended in the input sequence to summarize information from the sequence for the classification purpose. In **CST**, naively prepending it limits attention range in local attention part and also make the summarization in the global attention highly implicit. We believe this can be addressed by an additional well-designed architecture that uses global tokens and input them to classifier. We leave this as a future work and we instead use mean pooling for the experiment for all models.

While the efficiency gain is reduced due to the short sequence length, one can still expect reduction in total FLOPS from using **CST**. For instance, in the simple case of $N = 128$, $L = 64$ and $\alpha = 1$, the complexity of **CST** is $O(128 \cdot 64 + 128^2/64^2)$ which is almost half of that of the standard transformer $O(128^2)$.

A.10 LIMITATIONS

We summarize limitations of **CST** discussed in the previous sections.

As discussed in A.9, there is a mismatch of using token-wise random masking for MLM pretraining. In the abstraction of sequence slices for global attention, high-frequency modes are truncated, i.e., smoothed out, that leads to loss of information. While similar arguments can be made to other transformers with abstractive attention, we plan to carefully analyze it and address the issue by designing an alternative pretraining method.

In A.5, we discussed about the missing information of the latest slice in global attention step. This is only happening during the training phase, not in the testing, since the next token prediction with sliding window always has access to all tokens in the sequence up to the current time step. This mismatch may prohibits the full modeling capability of **CST**. To address the issue, we plan to design more suitable yet efficient training objective that allows full use of abstractions in the global attention during training.

Additional computation of the complexity $O(N/L)$ is required in **CST** for the Q, K, and V transformation from the local attention output. This increase in complexity is negligible compared to the overall computation, especially when N/L is small.