ScheduleNet: Learn to solve multi-agent scheduling problems with reinforcement learning

Abstract

We propose ScheduleNet, an RL-based decentralized constructive scheduler for coordinating multi-agent to finish tasks with minimum completion time. We formulate multi-agent scheduling problems (mSPs) as an event-based Markov decision process (MDP) with an episodic reward (e.g., makespan) and derive a decentralized decision-making policy using reinforcement learning. The decision making procedure of ScheduleNet includes: (1) representing the state of a scheduling problem with the agent-task graph, (2) extracting node embeddings for agent and tasks nodes by employing the type-aware graph attention (TGA), and (3) computing the assignment probability with the computed node embeddings. We validate the effectiveness of ScheduleNet on two types of mSPs: multiple traveling salesmen problem (mTSP) and job-shop scheduling problem (JSP). We empirically show that ScheduleNet can outperform other heuristic approaches and existing deep RL approaches, particularly validating its exceptional effectiveness in solving large and practical problems. Furthermore, we have demonstrated that ScheduleNet can effectively solve online vehicle routing problems where the new target customer appears dynamically during the course of scheduling.

1 Introduction

Optimal assignments of multiple autonomous agents for sequential completion of distributed tasks are necessary to solve various types of scheduling problems in logistics, transportation, and manufacturing. For example, finding the optimal delivery plans for vaccines, customer pickup orders for ride-sharing services, and machine operation sequence in modern manufacturing facilities are some examples of scheduling problems. As the size of the problems increases, solving large-scale scheduling problems using mathematical programming is infeasible or ineffective due to the expensive computational cost. Furthermore, the optimization approach cannot solve real-time scheduling problems where the new tasks appear dynamically.

Target Problem & Challenges. In this paper, we propose ScheduleNet, an RL-based decentralized constructive scheduler for coordinating multi-agent to finish tasks with minimum completion time. The followings specify objectives of the target problem and list technical challenges associated:

- *Min-Max vs Min-Sum*: ScheduleNet seeks to minimize the total completion time (i.e., makespan) to conduct the various time-critical distributed tasks (i.e., vaccine delivery). Most multi-agent routing problems are designed to minimize the sum of the traveling distance of all agents, which often results in unbalanced task assignments among the agents (Bakach et al., 2021). Although the makespan is the most direct and intuitive reward for inducing coordination, it is notoriously difficult to train decentralized policy with this sparse and delayed reward due to the temporal and spatial credit assignment issues.

- *Construction Heuristic vs Improvement heuristic*: ScheduleNet builds a solution sequentially by assigning an idle agent to one of the remaining tasks while considering the relationships among the remaining tasks and agents. This construction heuristic ensures that the learned policy can reschedule whenever a new event occurs, i.e., an agent finishes the assigned task or the new task appears. However, it is more challenging to find better planning due to its sequential solution construction; a wrong choice at the early stage can results in irreversible poor results at the end.

- **Decentralized** *vs Centralized*: ScheduleNet allows each agent to choose its destination independently while using its local observations and incorporating other agents' assignments. This decentralization ensures that the learned policy can solve a large-scale problem without having to search over the joint action space for all agents. However, to make the independently chosen routing decision produce excellent global performance, the sophisticated coordination mechanism should be implicitly incorporated into decentralized policy.

Proposed Decision-Making Scheme. We formulate multi-agent scheduling problems (mSPs) as an event-based Markov decision process (MDP) with an episodic reward (e.g., makespan) and derive a decentralized decision-making policy using reinforcement learning. At every step, ScheduleNet accepts the MDP state as an input and assigns an idle agent to one of the feasible tasks. The decision-making procedure of ScheduleNet is as follows:

- ScheduleNet first represents the MDP state as an agent-task graph, which effectively captures complex relationships among the entities and is general enough to apply to various mSPs.
- ScheduleNet then employs the type-aware graph attention (TGA) to extract important relational features among agents and tasks for making the best cooperative task assignment.
- Lastly, ScheduleNet computes the agent-task assignment probability by utilizing the computed node embeddings.

Training Method. Although makespan (shared team reward) is the most direct and general reward design for solving mSPs, training a decentralized scheduling policy using this reward is extremely difficult due to the credit assignment issues (Riedmiller et al., 2018; Hare, 2019). Additionally, makespan is highly volatile due to the combinatorial aspect of mSPs' solution space (min-max citation); a slight change in a solution can drastically alter the outcome. To overcome these issues, we employ the clipped reinforce algorithm with the normalized reward to effectively train the decentralized cooperative policy, even using a spare and delayed reward to overcome these difficulties.

Novelties. The proposed method to derive a decentralized constructive scheduler for coordinating multi-agents have the following novelties and the advantages:

- *Balance between Representability* & *Scalability*: ScheduleNet can effectively extract the crucial features using type-aware graph attention (TGA) to make the best cooperative task assignment (representability) in a computationally efficient manner. Computationally efficient representation scheme along with constructive decision-making scheme of ScheduleNet allow it to solve large-scale scheduling problems.
- *Transferability* & *Generalizability*: Type-aware graph representation allows the trained policy to solve problems with different numbers of agents and tasks (size transferability). Furthermore, this general state representation with the universal reward signal (i.e., makespan) allows ScheduleNet to be used to solve various multi-agent scheduling problems (generalizability). We validate this by showing that ScheduleNet can learn to solve a job-shop scheduling problem, different types of multi-agent scheduling problems with more complex constraints.

2 RELATED WORKS

RL approaches to solving vehicle routing problems. According to Mazyavkina et al. (2020), the RL approaches to solving vehicle routing problems can be categorized into: (1) improvement heuristics learns to rewrite the complete solution iteratively to obtain a better routing plan (Wu et al., 2020; da Costa et al., 2020; Chen & Tian, 2019; Lu et al., 2020); (2) construction approach learns to construct a solution by sequentially assigning idle vehicles to unvisited cities until the full routing schedule (sequence) is constructed (Bello et al., 2016; Nazari et al., 2018; Kool et al., 2018; Khalil et al., 2017), and (3) hybrid approaches blending both approaches (Joshi et al., 2020; Fu et al., 2021; Kool et al., 2021; Ahn et al., 2020). Typically, learning-based improvement have shown better performance than the learning-based construction heuristics because these iteratively revise the complete scheduling plan until reaching the best one when longer computational time is allowed. On the other hand, construction heuristic can be used more effectively than improvement heuristics for online vehicle routing problems where routes should be updated whenever new customers appear. These RL approaches have exclusively focused on static planning in a single agent perspective, which are far from the setting of real applications.

Figure 1: Solving mSP with ScheduleNet. At every event of the MDP, ScheduleNet constructs the agent-task graph $\mathcal{G}_\tau$ from s_τ, then computes the node embedding of $\mathcal{G}_\tau$ using TGA, and finally computes the agent-task assignment probabilities from the node embedding.

RL approaches to solve min-max mTSP. There are only few RL approaches for solving min-max mTSP, a problem of minimizing the makespan for multi agents to finish all tasks. Hu et al. (2020) applies RL to train the clustering algorithm that groups cities, and strong TSP heuristics (e.g., OR-Tool) to optimize the sub-tours of the city clusters. This approach is fundamentally different from ScheduleNet deriving a complete *end-to-end* learned heuristic that constructs a feasible solution from "scratch" without relying on any existing solvers. The most similar approach to our study is Cao et al. (2021) that proposes a transformer-based construction policy to solve min-max mTSP problem. We use these two algorithms as baselines to compare the performance of ScheduleNet.

RL approaches to solve Job-shop scheduling problems. There are only few RL approaches for solving job-shop scheduling problem, a problem of minimizing the makespan for multiple machines to finish the sequence of tasks required for completing jobs. For example, Gabel & Riedmiller (2012); Lin et al. (2019) have proposed to learn scheduling policy for each machine; hence, it requires an additional training to solve JSPs with a different number of machines. Recently, Park et al. (2021); Zhang et al. (2020) have proposed to learn a shared scheduling policy that can be used for all agents to minimize the makespan. Being similar to ScheduleNet, these studies utilize the disjunctive graph representation of JSP. However, these methods utilizing human-engineered dense reward, while ScheduleNet uses the makespan as sparse and delayed to train a policy. We use these algorithms as baseline to compare the performance of ScheduleNet.

3 PROBLEM FORMULATION

We formulate mSP as a MDP with sparse reward and aim to derive a decentralized scheduling decision-making policy that can be shared by all agents. The MDP is defined as:

State. We define state s_τ as the τ-th partial solution of mSP (i.e., the completed/uncompleted tasks, the status of agents, and the sequence of the past assignments). The initial s_0 and terminal state s_T are defined as an empty and a complete solution, respectively.

Action. We define action a_τ as the act of assigning an idle agent to one of the feasible tasks (unassigned tasks). We refer to a_τ as the *agent-to-task assignment*. When the multiple agents are idle at the same time t, we randomly choose one agent and assign an action to the agent and repeat the process until no agent is idle. Note that such randomness do not alter the resulting solutions, since the agents are considered to be homogeneous and the scheduling policy is shared.

Transition. The proposed MDP is formulated with an *event*-based transition. An event is defined as the the case where any agent finishes the assigned task (e.g., a salesman reaches the assigned city in mTSP). Whenever an event occurs, the idle agent is assigned to a new task, and the status of the agent and the target task are updated accordingly. We enumerate the event with τ to avoid confusion from the elapsed time of the problem; $t(\tau)$ is a function that returns the time of event τ.

Reward. The proposed MDP uses the minus of makespan (i.e. total completion time of tasks) as a reward, i.e., $r(s_T) = -t(T)$, that is realized only at s_T.

3.1 EXAMPLE: MDP FORMULATION OF MTSP

Let us consider the single-depot mTSP with two types of entities: m salesmen (i.e. m agents) and N cities (i.e. N tasks) to visit. All salesmen start their journey from the depot and come back to the depot after visiting all cities (each city can be visited by only one salesman). A solution to mTSP is considered to be *complete* when all the cities have been visited and all salesmen have returned to the depot. The MDP formulation for mTSP is similar to that of the general mSP. The specific definitions of the state and reward for mTSP are as follows:

State. We define $s_\tau = (\{s_\tau^i\}_{i=1}^{N+m}, s_\tau^{\text{env}})$ is composed of two types of states: entity state s_τ^i and environment state s_τ^{env}.

- $s_\tau^i = (p_\tau^i, \mathbf{1}_\tau^{\text{active}}, \mathbf{1}_\tau^{\text{assigned}})$ is the state of i-th entity. p_τ^i is the position of i-th entity at the τ-th event. $\mathbf{1}_\tau^{\text{active}}$ indicates whether the i-th worker/task is active (worker is working/ task is not visited) or not. Similarly, $\mathbf{1}_\tau^{\text{assigned}}$ indicates whether worker/task is assigned or not.
- s_τ^{env} contains the current time of the environment, and the sequence of cities visited by each salesman.

Reward. We use makespan of mTSP as a reward, which is sparse and episodic. The reward $r(s_\tau) = 0$ for all non-terminal events, and $r(s_\text{T}) = -t(\text{T})$, where T is the index of the terminal state.

4 SCHEDULENET

In this section, we explain how ScheduleNet recommends a scheduling action a_τ of an idle agent from input s_τ (partial solution) by (1) constructing the agent-task graph $\mathcal{G}_\tau$, (2) embedding $\mathcal{G}_\tau$ using TGA, and (3) computing the assignment probabilities. Figure 1 illustrates the decision-making process of ScheduleNet.

4.1 CONSTRUCTING AGENT-TASK GRAPH

ScheduleNet constructs the *agent-task graph* $\mathcal{G}_\tau$ that reflects the complex relationships among the entities in s_τ. Specifically, ScheduleNet constructs a directed complete graph $\mathcal{G}_\tau = (\mathbb{V}, \mathbb{E})$ out of s_τ, where $\mathbb{V}$ is the set of nodes and $\mathbb{E}$ is the set of edges. The nodes and edges, and their associated features are defined as:

- v_i denotes the i-th node representing either a agent or a task. v_i contains the node feature $x_i = (s_\tau^i, k_i)$, where s_τ^i is the state of entity i, and k_i is the type of v_i. For example, if the entity i is *agent* and its $\mathbf{1}_\tau^{active} = 1$, then the k_i becomes *active-agent* type. For the full list of the node features and types, refer to Appendix C.2.
- e_{ij} denotes the edge between the source node v_j and the destination node v_i. The edge feature w_{ij} is equal to the Euclidean distance between the two nodes.

In the following subsections, we omit the event iterator τ for notational brevity, since the action selection procedure is only associated with the current event index τ.

4.2 GRAPH EMBEDDING USING TGA

ScheduleNet computes the node embeddings from the agent-task graph $\mathcal{G}$ using the type-aware graph attention (TGA), which is designed to well capture the different relations among the graph entities by apply attention mechanisms per relational types. TGA performs three steps to compute the updated node/edge embedding as follows:

Type-aware edge update. Given the node embedding h_i and edge embedding h_{ij}, TGA computes the type-aware edge embedding h'_{ij} and the attention logit z_{ij} as follows:

$$h'_{ij} = \text{TGA}_{\mathbb{E}}([h_i, h_j, h_{ij}], k_j)$$
$$z_{ij} = \text{TGA}_{\mathbb{A}}([h_i, h_j, h_{ij}], k_j)$$

(1)

where $\text{TGA}_{\mathbb{E}}$ and $\text{TGA}_{\mathbb{A}}$ are the type-aware edge update function and the type-aware attention function, respectively. $\text{TGA}_{\mathbb{E}}$ and $\text{TGA}_{\mathbb{A}}$ are parameterized as Multilayer Perceptron (MLP).

Type-aware message aggregation. Each entity in the agent-task graph interacts differently with the other entities, depending on the type of the edge between them. To preserve the different relationships between the entities during the graph embedding procedure, TGA gathers messages h'_{ij} via the type-aware message aggregation.

First, TGA aggregates messages for each node type (*per-type*) and produces the *per-type* message m_i^k as follows:

$$m_i^k = \sum_{j \in \mathcal{N}_k(i)} \alpha_{ij} h'_{ij} \tag{2}$$

where $\mathcal{N}_k(i) = \{v_l | k_l = k, v_l \in \mathcal{N}(i)\}$ is the type k neighborhood of v_i, and α_{ij} is the attention score that is computed using z_{ij}:

$$\alpha_{ij} = \frac{\exp(z_{ij})}{\sum_{j \in \mathcal{N}_k(i)} \exp(z_{ij})} \tag{3}$$

TGA aggregates the per-type messages to compute the total aggregated message m_i for node v_i as:

$$m_i = \sum_{k \in \mathbb{K}} m_i^k \tag{4}$$

where $\mathbb{K}$ is the set of node types.

Type-aware node update. The total aggregated message m_i is then used to compute the updated node embedding h'_i as follows:
$$h'_i = \text{TGA}_{\mathbb{V}}([h_i, m_i], k_i) \tag{5}$$

where $\text{TGA}_{\mathbb{V}}$ is the type-aware node update function that is parametrized with MLP. The detailed architectures of $\text{TGA}_{\mathbb{E}}$, $\text{TGA}_{\mathbb{A}}$, and $\text{TGA}_{\mathbb{V}}$ are provided in Appendix A.

ScheduleNet computes the node embeddings from $\mathcal{G}$ using TGA. The embedding procedure first encodes the features of $\mathcal{G}$ into the initial node embeddings $\{h_i^{(0)} | v_i \in \mathbb{V}\}$, and the initial edge embeddings $\{h_{ij}^{(0)} | e_{ij} \in \mathbb{E}\}$. ScheduleNet then performs TGA H time simultaneously on all nodes to compute final node embeddings $\{h_i^{(H)} | v_i \in \mathbb{V}\}$, and edge embeddings $\{h_{ij}^{(H)} | e_{ij} \in \mathbb{E}\}$.

4.3 COMPUTING ASSIGNMENT PROBABILITY

Using the computed final node embeddings $\{h_i^{(H)} | v_i \in \mathbb{V}\}$ and edge embeddings $\{h_{ij}^{(H)} | e_{ij} \in \mathbb{E}\}$, ScheduleNet selects the best assignment action a_τ for the target agent.

ScheduleNet computes the assignment probability of the target *idle* agent i to the *unassigned* task j as follows:

$$l_{ij} = \text{MLP}_{actor}(h_i^{(H)}, h_j^{(H)}, h_{ij}^{(H)})$$
$$p_{ij} = \text{softmax}(\{l_{ij}\}_{j \in \mathbb{A}(\mathcal{G}_\tau)}) \tag{6}$$

where $h_i^{(H)}$ is the final node embedding for v_i, and $h_{ij}^{(H)}$ is the final edge embeddings for e_{ij}. In addition, $\mathbb{A}(\mathcal{G}_\tau)$ denote the set of feasible actions defined as $\{v_j | k_j = \textit{Unassigned-task}, v_j \in \mathbb{V}\}$.

Note that ScheduleNet allows an agent to process its local state information and make the assignment choice in a decentralized way, enabling ScheduleNet to solve mSPs with any number of agents and tasks even when agents or tasks appear dynamically.

5 TRAINING SCHEDULENET

We utilize sparse team reward (makespan) as the direct reward signal to train the decentralized scheduler (ScheduleNet) for having multiple agents to complete tasks as quickly as possible. Even though this team reward is the most direct signal that can be used for solving various types of mSPs, training a decentralized cooperative policy using a single sparse and delayed reward is notoriously difficult (Riedmiller et al., 2018; Hare, 2019). The high variance of the reward signal due to the combinatorial nature of mSPs' solution space adds an additional difficulty. To handle such difficulties, we employ two training stabilizers, reward normalization, and Clip-REINFORCE, while training ScheduleNet.

5.1 REWARD NORMALIZATION

We denote the makespan induced by policy π_θ as $M(\pi_\theta)$. We observe that $M(\pi_\theta)$ is highly volatile depending on the problem size (N, m) and π_θ. To reduce the variance of the reward incurred from the problem sizes, we propose to use the normalized makespan $\bar{M}(\pi_\theta, \pi_b)$ computed as:

$$\bar{M}(\pi_\theta, \pi_b) = \frac{M(\pi_\theta) - M(\pi_b)}{M(\pi_b)} \tag{7}$$

where π_b, a baseline policy, is the current policy π in greedy (test) mode.

A similar normalization scheme that only measures the performance difference between π and π_b has been investigated in RL applications for solving single-agent scheduling problems (Kool et al., 2018; Cao et al., 2021; Kwon et al., 2020). This normalization can provide consistent learning signals when the training instance sizes (i.e. N) are fixed, which is a common practice of training RL methods for solving single-agent scheduling problems. However, we observed that, even N is fixed, the (optimal) makespan of mTSP can be differ severely as m changes. To reduce the variability of makespan from the different m, we further divide the makespan difference by $M(\pi_b)$.

Using $\bar{M}(\pi_\theta, \pi_b)$, we compute the normalized return $G_\tau(\pi_\theta, \pi_b)$ as follows:

$$G_\tau(\pi_\theta, \pi_b) \triangleq -\gamma^{T-\tau} \bar{M}(\pi_\theta, \pi_b) \tag{8}$$

where T is the index of the terminal state, and γ is the discount factor of MDP. The minus sign is for minimizing the makespan. Note that, in the early phase of mSP (when τ is small), it is difficult to estimate the makespan. Thus, we place a smaller weight (i.e, $\gamma^{T-\tau}$) on $\bar{M}(\pi_\theta, \pi_b)$ evaluated when τ is small (early stage).

5.2 CLIP-REINFORCE

Even a small change in a single assignment can result in a dramatic change to make span due to the combinatorial nature of the solution. Hence, training value function that predicts the G_τ reliably is difficult. We thus propose to utilize the Clip-REINFORCE (CR), a variant of PPO (Schulman et al., 2017), *without* learning a value function for training ScheduleNet. The objective of the Clip-REINFORCE is given as follows:

$$\mathcal{L}(\theta) = \mathop{\mathbb{E}}_{(\mathcal{G}_\tau, a_\tau) \sim \pi_\theta} [\min(\text{clip}(\rho_\tau, 1 - \epsilon, 1 + \epsilon)G_\tau, \rho_\tau G_\tau)] \tag{9}$$

where G_τ is a shorthand notation for $G_\tau(\pi_\theta, \pi_b)$ and $\rho_\tau = \pi_\theta(a_\tau|\mathcal{G}_\tau)/\pi_b(a_\tau|\mathcal{G}_\tau)$ is the ratio between the target and baseline policy.

6 EXPERIMENTS

In this section, we evaluate the performance of ScheduleNet on mTSP and JSP. To calculate the inference time, we run all experiements on the server equipped with AMD Threadripper 2990WX CPU. we use single CPU core for evaluating all algorithms.

6.1 MTSP EXPERIMENTS

Training. We denote $(N \times m)$ as the mTSP with N cities (tasks) and m salesmen (agents). To generate a random mTSP instance, we sample N and m from $U(15, 30)$ and $U(3, 4)$, respectively. Similarly, the Euclidean coordinates of N cities are sampled uniformly at random from the unit square. ScheduleNet is trained on random mTSP instances that are generated on-the-fly. For all experimental results, we evaluate the performance of a single trained ScheduleNet model. Please refer to Appendix C.3 for more information regarding the training details.

Results on random mTSP datasets. To investigate the generalization capacity of ScheduleNet to various problem sizes, we evaluate ScheduleNet on the randomly generated mTSP datasets. Each $(N \times m)$ dataset consists of 100 random uniform mTSP instances.

We consider the four baseline algorithms to measure the performance of ScheduleNet. As the non-learning baselines, LKH3 (Helsgaun, 2017) and Google OR-Tools (Perron & Furnon) are used. It

Table 1: Random mTSP results. GNN-DisPN results are reproduced from Hu et al. (2020).

Figure 2: mTSP runtimes

N	30		50			100			200			Gap
m	3	5	5	7	10	5	10	15	10	15	20	
LKH3	2.17	1.94	2.00	1.95	1.91	2.20	1.97	1.98	2.04	2.00	1.97	1.00
OR-Tools	2.25	1.95	2.04	1.96	1.91	2.41	2.03	2.03	2.33	2.33	2.37	1.07
GNN-DisPN	-	-	2.12	-	1.95	2.48	2.09	-	-	-	-	-
DAN (g.)	2.32	2.02	2.29	2.11	2.03	2.72	2.17	2.09	2.40	2.20	2.15	1.13
DAN (s.64)	2.22	1.96	2.12	1.99	1.95	2.55	2.05	2.00	2.40	2.20	2.15	1.08
ScheduleNet (g.)	2.32	2.02	2.17	2.07	1.98	2.59	2.13	2.07	2.45	2.24	2.17	1.09
ScheduleNet (s.64)	2.22	1.96	2.07	1.99	1.92	2.43	2.03	1.99	2.25	2.08	2.05	1.04

Table 2: mTSPLib results. CPLEX results with $*$ are optimal solutions. Otherwise, the known-best upper bound of CPLEX results are reported.

Instance	eil51				berlin52				eil76				rat99				Gap
m	2	3	5	7	2	3	5	7	2	3	5	7	2	3	5	7	
CPLEX	222.7*	159.6	124.0	112.1	4110.2	3244.4	2441.4	2440.9	280.9*	197.3	150.3	139.6	728.8	587.2	469.3	443.9	1.00
LKH3	222.7	159.6	124.0	112.1	4110.2	3244.4	2441.4	2440.9	280.9	197.3	150.3	139.6	728.8	587.2	469.3	443.9	1.00
OR-Tools	243.3	170.5	127.5	112.1	4665.5	3311.3	2482.6	2440.9	318.0	212.4	143.4	128.3	762.2	552.1	473.7	442.5	1.03
DAN (g)	274.2	178.9	158.6	118.1	5,226.0	4,278.4	2,758.8	2,696.8	361.1	251.5	170.9	148.5	930.8	674.1	504.0	466.4	1.18
DAN (s. 64)	252.9	178.9	128.2	114.3	5,097.7	3,455.7	2,677.1	2,494.5	336.7	228.1	157.9	134.5	966.5	697.7	495.6	462.0	1.11
ScheduleNet (g.)	263.9	200.5	131.7	116.9	4,826.1	3,644.2	2,757.8	2,514.6	330.2	228.8	163.9	144.4	843.8	691.8	524.3	480.8	1.13
ScheduleNet (s.64)	239.3	173.5	125.8	112.2	4,591.6	3,276.1	2,517.3	2,441.4	317.7	220.8	153.8	131.7	781.2	627.1	502.3	464.4	1.05

is noteworthy that LKH3 is known to find the optimal solutions for the mTSP problems with the identified optimal solutions. Thus, we use the makespans computed by LKH3 as the proxies for the optimal solutions. As the RL baselines, GNN-DisPN (Hu et al., 2020) and DAN (Cao et al., 2021) are considered (To the best of our knowledge, these are the only RL-based algorithms tried to solve the min-max mTSP problems).

Table 1 shows the performance of ScheduleNet and the baseline algorithms on various sized of random mTSP instances. ScheduleNet generally shows leading performances compared to the baseline algorithms even though it is trained on the smallest test setup (30×3). In addition, Figure 2 compares the average computation time and the standard deviation per problem size, clearly indicating that ScheduleNet is significantly faster than traditional heuristic solvers (LKH3 and OR-Tools). The computational time difference among RL-approaches is almost not noticeable.

Results on Public Benchmarks. Next, to explore the generalization of ScheduleNet to problems that come from completely different distributions (i.e., real-world data), we present the results on the mTSPLib dataset defined by Necula et al. (2015). mTSPLib consists of four instances of size 51, 52, 76 and 99 from TSPLib (Reinelt, 1991), each of which extended to multi-agent setup where m equals to 2, 3, 5, and 7.

Table 2 shows the performance of algorithms. ScheduleNet still exhibits comparable performance to OR-tools, while the other RL method (DAN) shows significant performance drops. From this experiment, we can observe that ScheduleNet is effective in solving both randomly generated and real-world mTSPs problems (i.e., robust transferability over data distribution shift).

6.2 ABLATION STUDIES

In this paper, we propose TGA as the representation learning module and Clip-REINFORCE (CR) as the training method. Here, we provide the experimental results that shows the effect of proposed TGA and CR to the training and testing performance.

We train 3 variants of ScheduleNet models as the target of ablations. The variants are as follows:

- `TGA-REINFORCE`: the model using TGA and is trained by REINFORCE (Williams, 1992).
- `GN-CR`: the model using the graph network (GN) layer (Battaglia et al., 2018) is trained by Clip-REINFORCE.
- `TGA-CR`: the model using TGA and is trained by Clip-REINFORCE; the proposed ScheduleNet.

Figure 3: Training curves

N	m	TGA-R.	GN-CR	TGA-CR
	5	6.04	2.67	2.59
100	10	4.59	2.26	2.13
	15	3.56	2.36	2.07
	10	11.27	2.61	2.45
200	15	6.18	2.41	2.24
	20	4.55	2.52	2.17

Table 3: mTSP ablation results

Figure 4: Limited observation scenarios

Figure 5: Online routing scenarios

Figure 3 compares the performances of the three ablation models on the validation test instance (30×3) during training, and Table 3 shows the performances on the test problem instances.

- `TGA-REINFORCE` vs. `TGA-CR`: by comparing the learning curves of these two ablation models, we can see the effect of the proposed Clip-REINCORE learning algorithm. The REINFORCE algorithm without using clipped reward is not able to learn meaningful policy.

- `GN-CR` vs. `TGA-CR`: by comparing the learning curves of these two models, we can see the effect of TGA as a representation module; TGA induces more stabilized and faster performance improvement. In addition, as shown in Table 3, `TGA-CR` (ScheduleNet) consistently shows better performance than `GN-CR` in the test datasets. The performance differences between two models become severe as N and m increase. This again highlights the role of TGA in solving mTSP.

6.3 MTSP VARIANTS EXPERIMENTS

In this section, we further investigate the performance of ScheduleNet in a more practical scenarios of mTSP: (1) limited observation; (2) online routing.

limited observation scenarios. In a real-world application of mTSP, some salesmen may not gather all information about the other salesmen due to the limited communication capabilities (e.g., delivery trucks are located in distant). In such a scenario, the agent should be able to decide the next city to visit with local observations. To consider this realistic scenario, we limit the number N_r of observable salesmen from the global state $\mathcal{G}_\tau$ and investigate its performance.

We apply ScheduleNet to solve the test instances, whose sizes are (50×5), (100×10), and (200×20), by varying the number N_r of the salesmen to communicate. As shown in Figure 4, the performance improves as N_r increases because the extended communication scope can induce enhanced coordination among salesmen. Note that $N_r = 0$ indicates the case where each salesman makes an entirely independent action without considering other salesmen at all. This result implies that ScheduleNet is able to learn an effective cooperative policy for minimizing makespan. In addition, Schedule can robustly perform well even with the limited communication among salesmen.

Online routing scenario. ScheduleNet, as a decentralized constructive heuristic, can solve the dynamic scheduling problem in an online manner; it inherently reschedule whenever a new event occurs, i.e., an agent finishes the assigned task or the new task appears while considering the updated agent and task distribution. We evaluate this capability by solving online mTSP problem where the new cities arise dynamically during the course of scheduling problem.

Table 4: Taillard's 80 results. The gaps are measured w.r.t. the optimal (or the best-known) makespan.

	15×15	20×15	20×20	30×15	30×20	50×15	50×20	100×20	Gap
MOR	1.205	1.236	1.217	1.249	**1.173**	1.177	**1.092**	1.092	1.197
FIFO	1.239	1.314	1.275	1.319	1.310	1.206	1.239	1.136	1.255
SPT	1.258	1.329	1.278	1.349	1.344	1.241	1.256	1.144	1.275
Zhang et al. (2020)	1.259	1.300	1.316	1.319	1.336	1.224	1.264	1.136	1.269
Park et al. (2021)	1.171	1.202	1.228	1.189	1.254	1.159	1.174	1.070	1.181
ScheduleNet	**1.153**	**1.194**	**1.172**	**1.180**	1.187	**1.138**	1.135	**1.066**	**1.154**

We first randomly generate 100 (30×3) test instances. Then, while simulating these scenarios with the scheduling policies, we sequentially add $30 \times N_a$% cities to the simulation (the exact addition moment and locations are unknown to policies) and evaluate how the policies effectively replan the schedules according to online scenarios. We compare the performance of ScheduleNet with (1) oracle planning that plans once while knowing all future demands (its appearing locations and times), and (2) re-planing heuristics that re-plans the future actions whenever s_τ is updated. Please refer to Appendix C.4 for more details regarding the simulation and baselines.

Figure 5 shows the average performances computed using 100 random online scenarios. As shown in the left plot, ScheduleNet always produces a shorter makespan and shorter runtime than the re-planning heuristic for all N_a values, proving its effective adaptability and robustness to dynamically changing demand (cities). Note that as N_a increases, the makespan and the runtime increase for all methods due to the increased uncertainty and the number of re-plans required.

6.4 JSP EXPERIMENTS

We employ ScheduleNet to solve JSP, another important class of mSP, to evaluate its generalization capacity in terms of solving various types of mSPs. The goal of the JSP is to schedule machines (i.e. agents) in a manufacturing facility to complete the jobs that consist of a series of operations (tasks), while minimizing the total completion time (makespan). Solving JSP is considered to be challenging since it imposes additional constraints that scheduler must obey: precedence constraints and agent-sharing constraints.

Formulation. We formulate JSP as a MDP where s_τ is the partial solution of JSP, a_τ is agent-task assignment (i.e. assigning an idle machine to one of the feasible operations), and reward is the minus of makespan. Please refer to Appendix D.1 for the detailed formulation of MDP.

Training. We train ScheduleNet using the random JSP instances ($N \times m$) that have N jobs and m machines. We sample N and m from $U(7, 14)$ and $U(2, 5)$ respectively to generate the training JSP instances and randomly shuffle the order of the machines in a job to generate machine sharing constraints. Please refer to Appendix D.3 for more information.

Results on public benchmarks. We evaluate the scheduling performance to verify ScheduleNet's generalization capacity to unseen JSP distributions on the Taillard's 80 dataset (Taillard, 1993). We compare against two deep RL baselines (Park et al., 2021; Zhang et al., 2020), as well as three JSP heuristics that known to work well in practice, Most Operation Remaining (MOR), First-in-first-out (FIFO), and Shortest Processing Time (SPT). Both baseline RL methods were specifically designed to solve JSP by utilizing the well-known disjunctive JSP graph representation (Roy & Sussmann, 1964) and well-engineered dense reward functions. Nevertheless, we can observe that ScheduleNet outperforms all baselines in all of the cases while utilizing only a sparse episodic reward (see Table 4). Please refer to Appendix D.5 for the extended benchmark results.

7 CONCLUSION

In this work, we proposed ScheduleNet, which is a RL-based scheduler that can solve various types of multi-agent scheduling problems (mSPs) in a decentralized manner. Through the extensive experiments, we empirically verified that ScheduleNet is an effective *general scheduler* that can solve various mSPs, a *cooperative scheduler* that induces multi-agent coordination to achieve a common objective, and a *scalable scheduler* that can solve large scale static scheduling problems. Furthermore, we have validated that ScheduleNet can be used to solve online scheduling problems.

8 ETHICS STATEMENT AND REPRODUCIBILITY DISCUSSION

Ethics statement   The proposed method aims to learn a decentralized policy to solve practical large-scale multi-agent scheduling problems. With the recent advanced robotics and communication technologies, the proposed method can be considered and employed as a solver for real-life logistic problems. However, our method does not consider the subjective values (social protections for the underprivileged or expedited dispatching for life-threatening demands) in the process of decision-making or learning. Thus, our method may produce scheduling results that are not well aligned with human decision-makers in such cases.

reproducibility   As machine learning researchers, we consider the reproducibility of numerical results as one of the top priorities. Thus, we put a significant amount of effort into pursuing the reproducibility of our experimental results. As such efforts, we set and tracked the random seed used for our experiments and confirmed the experiments were reproducible. Furthermore, we also prepare to open-source our mTSP MDP environments so that the follow-up research can be assessed in a unified way.

REFERENCES

Sungsoo Ahn, Younggyo Seo, and Jinwoo Shin. Learning what to defer for maximum independent sets. In Hal Daumé III and Aarti Singh (eds.), *Proceedings of the 37th International Conference on Machine Learning*, volume 119 of *Proceedings of Machine Learning Research*, pp. 134–144. PMLR, 13–18 Jul 2020.

David Applegate and William Cook. A computational study of the job-shop scheduling problem. *ORSA Journal on computing*, 3(2):149–156, 1991.

Iurii Bakach, Ann Melissa Campbell, Jan Fabian Ehmke, and Timothy L Urban. Solving vehicle routing problems with stochastic and correlated travel times and makespan objectives. *EURO Journal on Transportation and Logistics*, 10:100029, 2021.

Peter W Battaglia, Jessica B Hamrick, Victor Bapst, Alvaro Sanchez-Gonzalez, Vinicius Zambaldi, Mateusz Malinowski, Andrea Tacchetti, David Raposo, Adam Santoro, Ryan Faulkner, et al. Relational inductive biases, deep learning, and graph networks. *arXiv preprint arXiv:1806.01261*, 2018.

Irwan Bello, Hieu Pham, Quoc V Le, Mohammad Norouzi, and Samy Bengio. Neural combinatorial optimization with reinforcement learning. *arXiv preprint arXiv:1611.09940*, 2016.

Yuhong Cao, Zhanhong Sun, and Guillaume Sartoretti. Dan: Decentralized attention-based neural network to solve the minmax multiple traveling salesman problem. *arXiv preprint arXiv:2109.04205*, 2021.

Xinyun Chen and Yuandong Tian. Learning to perform local rewriting for combinatorial optimization. In H. Wallach, H. Larochelle, A. Beygelzimer, F. d'Alché-Buc, E. Fox, and R. Garnett (eds.), *Advances in Neural Information Processing Systems*, volume 32. Curran Associates, Inc., 2019.

Paulo R d O da Costa, Jason Rhuggenaath, Yingqian Zhang, and Alp Akcay. Learning 2-opt heuristics for the traveling salesman problem via deep reinforcement learning. In Sinno Jialin Pan and Masashi Sugiyama (eds.), *Proceedings of The 12th Asian Conference on Machine Learning*, volume 129 of *Proceedings of Machine Learning Research*, pp. 465–480, Bangkok, Thailand, 18–20 Nov 2020. PMLR.

Henry Fisher. Probabilistic learning combinations of local job-shop scheduling rules. *Industrial scheduling*, pp. 225–251, 1963.

Zhang-Hua Fu, Kai-Bin Qiu, and Hongyuan Zha. Generalize a small pre-trained model to arbitrarily large tsp instances, 2021.

Thomas Gabel and Martin Riedmiller. Distributed policy search reinforcement learning for job-shop scheduling tasks. *International Journal of production research*, 50(1):41–61, 2012.

Joshua Hare. Dealing with sparse rewards in reinforcement learning. *arXiv preprint arXiv:1910.09281*, 2019.

Keld Helsgaun. An extension of the lin-kernighan-helsgaun tsp solver for constrained traveling salesman and vehicle routing problems. *Roskilde: Roskilde University*, 2017.

Yujiao Hu, Yuan Yao, and Wee Sun Lee. A reinforcement learning approach for optimizing multiple traveling salesman problems over graphs. *Knowledge-Based Systems*, 204:106244, 2020.

Chaitanya K. Joshi, Quentin Cappart, Louis-Martin Rousseau, Thomas Laurent, and Xavier Bresson. Learning tsp requires rethinking generalization, 2020.

Elias Khalil, Hanjun Dai, Yuyu Zhang, Bistra Dilkina, and Le Song. Learning combinatorial optimization algorithms over graphs. In *Advances in Neural Information Processing Systems*, pp. 6348–6358, 2017.

Wouter Kool, Herke Van Hoof, and Max Welling. Attention, learn to solve routing problems! *arXiv preprint arXiv:1803.08475*, 2018.

Wouter Kool, Herke van Hoof, Joaquim Gromicho, and Max Welling. Deep policy dynamic programming for vehicle routing problems, 2021.

Yeong-Dae Kwon, Jinho Choo, Byoungjip Kim, Iljoo Yoon, Youngjune Gwon, and Seungjai Min. Pomo: Policy optimization with multiple optima for reinforcement learning. *Advances in Neural Information Processing Systems*, 33, 2020.

S Lawrence. Resouce constrained project scheduling: An experimental investigation of heuristic scheduling techniques (supplement). *Graduate School of Industrial Administration, Carnegie-Mellon University*, 1984.

Chun-Cheng Lin, Der-Jiunn Deng, Yen-Ling Chih, and Hsin-Ting Chiu. Smart manufacturing scheduling with edge computing using multi-class deep q network. *IEEE Transactions on Industrial Informatics*, 2019.

Hao Lu, Xingwen Zhang, and Shuang Yang. A learning-based iterative method for solving vehicle routing problems. In *International Conference on Learning Representations*, 2020.

Nina Mazyavkina, Sergey Sviridov, Sergei Ivanov, and Evgeny Burnaev. Reinforcement learning for combinatorial optimization: A survey. *arXiv preprint arXiv:2003.03600*, 2020.

Mohammadreza Nazari, Afshin Oroojlooy, Lawrence Snyder, and Martin Takác. Reinforcement learning for solving the vehicle routing problem. In *Advances in Neural Information Processing Systems*, pp. 9839–9849, 2018.

Raluca Necula, Mihaela Breaban, and Madalina Raschip. Tackling the bi-criteria facet of multiple traveling salesman problem with ant colony systems. In *2015 IEEE 27th International Conference on Tools with Artificial Intelligence (ICTAI)*, pp. 873–880. IEEE, 2015.

Junyoung Park, Jaehyeong Chun, Sang Hun Kim, Youngkook Kim, and Jinkyoo Park. Learning to schedule job-shop problems: representation and policy learning using graph neural network and reinforcement learning. *International Journal of Production Research*, pp. 1–18, 2021.

Laurent Perron and Vincent Furnon. Or-tools.

Gerhard Reinelt. Tsplib—a traveling salesman problem library. *ORSA journal on computing*, 3(4): 376–384, 1991.

Martin Riedmiller, Roland Hafner, Thomas Lampe, Michael Neunert, Jonas Degrave, Tom Wiele, Vlad Mnih, Nicolas Heess, and Jost Tobias Springenberg. Learning by playing solving sparse reward tasks from scratch. In *International Conference on Machine Learning*, pp. 4344–4353. PMLR, 2018.

Bernard Roy and B Sussmann. Scheduling problems with disjunctive constraints. *Note ds*, 9, 1964.

John Schulman, Filip Wolski, Prafulla Dhariwal, Alec Radford, and Oleg Klimov. Proximal policy optimization algorithms. *arXiv preprint arXiv:1707.06347*, 2017.

David Silver, Aja Huang, Chris J Maddison, Arthur Guez, Laurent Sifre, George Van Den Driessche, Julian Schrittwieser, Ioannis Antonoglou, Veda Panneershelvam, Marc Lanctot, et al. Mastering the game of go with deep neural networks and tree search. *nature*, 529(7587):484–489, 2016.

Robert H Storer, S David Wu, and Renzo Vaccari. New search spaces for sequencing problems with application to job shop scheduling. *Management science*, 38(10):1495–1509, 1992.

Eric Taillard. Benchmarks for basic scheduling problems. *european journal of operational research*, 64(2):278–285, 1993.

Ronald J Williams. Simple statistical gradient-following algorithms for connectionist reinforcement learning. *Machine learning*, 8(3-4):229–256, 1992.

Yaoxin Wu, Wen Song, Zhiguang Cao, Jie Zhang, and Andrew Lim. Learning improvement heuristics for solving routing problems, 2020.

Takeshi Yamada and Ryohei Nakano. A genetic algorithm applicable to large-scale job-shop problems. In *PPSN*, volume 2, pp. 281–290, 1992.

Cong Zhang, Wen Song, Zhiguang Cao, Jie Zhang, Puay Siew Tan, and Chi Xu. Learning to dispatch for job shop scheduling via deep reinforcement learning. *arXiv preprint arXiv:2010.12367*, 2020.

ScheduleNet
Supplementary Material

Table of Contents

A DETAILS OF TYPE-AWARE GRAPH ATTENTION

In this section, we thoroughly describe the computation procedures of type-aware graph attention (TGA). Similar to the main body, We overload notations for the simplicity of notation such that the input node and edge feature as h_i and h_{ij}, and the embedded node and edge feature h'_i and h'_{ij}, respectively.

The proposed TGA performs graph embedding with the following three phases: (1) type-aware edge update, (2) type-aware message aggregation, and (3) type-aware node update.

Type-aware edge update The edge update scheme is designed to reflect the complex type relationship among the entities while updating edge features. First, the *context* embedding c_{ij} of edge e_{ij} is computed using the source and destination node type k_i, k_j such that:

$$c_{ij} = [\text{Emb}(k_i), \text{Emb}(k_j)] \tag{A.1}$$

where $\text{Emb}(\cdot)$ is a trainable lookup table function. Next, the type-aware edge encoding u_{ij} is computed using a multilayer perceptron (MLP) as follows:

$$u_{ij} = \text{MLP}_{etype}(h_i, h_j, h_{ij}, c_{ij}) \tag{A.2}$$

where $\text{MLP}_{etype}(\cdot)$ is the type-aware edge encoding MLP. u_{ij} can be seen as a dynamic edge feature which varies depending on the source and destination node type. Then, the updated edge embedding h'_{ij} and its attention logit z_{ij} are obtained as:

$$h'_{ij} = \text{MLP}_{edge}(u_{ij}) \tag{A.3}$$

$$z_{ij} = \text{MLP}_{attn}(u_{ij}) \tag{A.4}$$

where MLP_{edge} and MLP_{attn} is the edge updater and logit function, respectively. The edge updater and logit function produce updated edge embedding and logits from the type-aware edge.

The computation steps of equations A.1, A.2 and A.3 are defined as $\text{TGA}_{\mathbb{E}}$. Similarly, the computation steps of equations A.1, A.2 and A.4 are defined as $\text{TGA}_{\mathbb{A}}$.

Type-aware message aggregation We first define the type-k neighborhood of v_i as $\mathcal{N}_k(i) = \{v_l | k_l = k, \forall v_l \in \mathcal{N}(i)\}$, where $\mathcal{N}(i)$ is the in-neigborhood set of v_i. The proposed type-aware message aggregation procedure computes attention score α_{ij} for the e_{ij}, which starts from v_j and heads to v_i, such that:

$$\alpha_{ij} = \frac{\exp(z_{ij})}{\sum_{l \in \mathcal{N}_{k_j}(i)} \exp(z_{il})} \tag{A.5}$$

Intuitively speaking, The proposed attention scheme normalizes the attention logits of incoming edges over the types. Therefore, the attention scores sum up to 1 over each type-k neighborhood. Next, the type-k neighborhood message m_i^k for node v_i is computed as:

$$m_i^k = \sum_{j \in \mathcal{N}_k(i)} \alpha_{ij} h'_{ij} \tag{A.6}$$

In this aggregation step, the incoming messages of node i are aggregated per type. All incoming type neighborhood messages are concatenated to produce (inter-type) aggregated message m_i for v_i, such that:

$$m_i = \sum_{k \in \mathbb{K}} m_i^k \tag{A.7}$$

Type-aware node update Similar to the edge update phase, the context embedding c_i is computed first for each node v_i:

$$c_i = \text{Emb}(k_i) \tag{A.8}$$

where $\text{Emb}(\cdot)$ is a trainable lookup table function. Then, the updated hidden node embedding h'_i is computed as below:

$$h'_i = \text{MLP}_{node}(h_i, m_i, c_i) \tag{A.9}$$

where $\text{MLP}_{node}(\cdot)$ is the type-aware node updater. The computation steps of equations A.8, and A.9 are defined as $\text{TGA}_{\mathbb{V}}$.

B   EXTENDED DISCUSSION FOR REWARD NORMALIZATION SCHEME

In this section, we further discuss the effect of the proposed reward normalization scheme and its variants to the performance of ScheduleNet. The proposed reward normalization (i.e. normalized makespan) $m(\pi, \pi_b)$ is given as follows:

$$m(\pi, \pi_b) = \frac{M(\pi_\theta) - M(\pi_b)}{M(\pi_b)} \tag{A.10}$$

where π_b is the baseline policy.

Effect of the denominator $m(\pi, \pi_b)$ measures the relative scheduling supremacy of π to the π_b. Similar reward normalization scheme, but without $M(\pi_b)$ division, is employed to solve single-agent scheduling problems Kool et al. (2018). We empirically found that the division leads in much stable learning when the scale of makespan change (e.g. the area of map change from the unit square to different geometries or the size of training instances are varying).

Effect of the baseline selection   A proper selection of π_b is essential to assure stable and asymptotically better learning of ScheduleNet. Intuitively speaking, choosing too strong baseline (i.e. policy having smaller makespan such as LKH3 and OR-tools) can makes the entire learning process unstable since the normalized reward tends to have larger values. On the other hand, employing too weak baseline can leads in virtually no learning since the $m(\pi, \pi_b)$ becomes nearly zero.

We select π_b as Greedy(π) and this baseline selection has several advantages from selecting a fixed/pre-existing scheduling policy: (1) Entire learning process becomes independent from existing scheduling methods. Thus ScheduleNet is applicable even when the cheap-and-performing π_b for some target mSP does not exist. (2) Greedy(π) serves as an appropriate π_b (either not too strong or weak) during policy learning. We experimentally confirmed that the baseline section Greedy(π) results in a better scheduling policy as similar to the several literature Kool et al. (2018); Silver et al. (2016).

C   DETAILS OF MTSP EXPERIMENTS

In this section, we provide the details of mTSP exepriments.

C.1   MDP FORMULATION

The formulated mTSP MDP is event-based. Here we discuss the further details about the event-based transitions of mTSP MDP. Whenever all agents are assigned to cities, the environment transits in time, until any of the workers arrives to the city (i.e. completes the task). Arrival of the worker to the city triggers an event, meanwhile the other assigned salesman are still on the way to their correspondingly assigned cities. We assume that each worker transits towards the assigned city with unit speed in the 2D Euclidean space, i.e. the distance travelled by each worker equals the time past between two consecutive MDP events.

It is noteworthy that multiple events can happen at the same time, typically when time stamp $t = 0$. If the MDP has multiple available workers at the same time, we repeatedly choose an arbitrary idle agent and assign it to the one of an idle task until no agent is idle, while updating event index τ. This random selections do not alter the resulting solutions since we do not differentiate each agent (i.e. agents are homogeneous agents).

C.2   AGENT-TASK GRAPH FORMULATION

In this section, we present the list of all possible node types in $\mathcal{G}_\tau$:(1) assigned-agent, (2) unassigned-agent (i.e. idle), (3) assigned-task, (4) unassigned-task, (5) inactive-task (i.e. visited city) and (6) depot. Here, we do not include inactive-agent (i.e. salesmen already return to the depot) to the graph. For edge types, we don't define them explicitly rather we consider the combination of source and destination types as the edge type. All nodes in the $\mathcal{G}_\tau$ are fully connected.

C.3   TRAINING DETAILS

Network parameters.   ScheduleNet is composed of three components. The first components generates the initial node embedding $\{h_i^{(0)}\}$ and edge $\{h_{ij}^{(0)}\}$ by using linear projections. The second component (TGA), which utilizes MLP(64) as MLP_etype, MLP_edge, MLP_attn, and MLP_node, repeatedly updates the node and edge embedding 3 times to generate $\{h_i^{(3)}\}$ and edge $\{h_{ij}^{(3)}\}$. The last component MLP_actor, which is parametrized as MLP(64, 32), generates action logits from the set of node and edge embedding. All input and output dimensions of MLPs are 64 and hidden actions are LeakyReLU.

Training pseudocode.   We presents a pseudocode for training ScheduleNet.

Algorithm 2: ScheduleNet Training

input : Training policy π_θ, baseline policy π_ϕ
output: Optimized policy π_θ
1 Initialize the baseline policy with parameters $\phi \leftarrow \theta$
2 **for** *update step* **do**
3   **for** *number of episodes E* **do**
4   Generate a random mTSP instance I
5          $\pi_b \leftarrow \text{Greedy}(\pi_\phi)$
6   Construct mTSP MDP from the instance I
7   Collect samples with π_θ and π_b from the mTSP MDP
8   **end**
9   **for** *inner updates K* **do**
10         $\theta \leftarrow \theta + \alpha \nabla_\theta \mathcal{L}(\theta)$
11   **end**
12     $\phi \leftarrow \beta \phi + (1 - \beta)\theta$
13 **end**
14 **return** π_θ

Figure 6: Disjunctive graph representation of JSP

Figure 7: Precedence constraint

Figure 8: Agent-sharing constraint

We set the MDP discounting factor γ to 0.99, learning rate α to 0.0001, E to 128, K to 4, β to 0.01, and the clipping parameter ϵ of Clip-REINFORCE to 0.2. We set training seed as 1234.

C.4 ONLINE ROUTING SCENARIOS

Scenario generation In this paragraph, we thoroughly explain the online routing scenario generation scheme. To generate the scenarios, we first fix the number of cities added during the online routing. Once the number of cities is given, we then decide the locations of the cities by taking midpoints of cities. We assign the location of the city that will be first added as the midpoint between the first and second cities of the mTSP map. Similarly, the location of the second city is set as the midpoint between the second and third cities. Using the same logic, we decide all positions of the newly added cities. Lastly, we decide the timing of city addition by using (near) optimal solutions (e.g., LKH3) $M^*(\pi)$. We first compute divide $M^*(\pi)$ by $1.0 < s$ and then evenly allocate the timing of additions from 0.0 to $M^*(\pi)/s$. This ensures all "to be added" cities are added during the online routing simulation no matter what scheduling policies are evaluated. We set $s = 2$.

Baseline implementations In this paragraph, we explain the implementations of baseline algorithms. To implement the oracle planning, we reformulate the online routing problem as a vehicle routing problem with time constraints (VRP-TW). In the VRP-TW, we set the time window constraints for the originally existing cities as $(0, M)$, where M is a large number. For the newly added cities, the lower and upper bounds of the time window are set as their addition times and M. The re-planing heuristics are implemented with OR-tools (Perron & Furnon).

D DETAILS OF JSP EXPERIMENTS

Job-shop scheduling problem (JSP) is a mSP that can be applied in various industries including the operation of semi-conductor chip fabrication facility and railroad system. The objective of JSP is to find the sequence of machine (agent) allocations to finish the jobs (a sequence of operations; tasks) as soon as possible. JSP can be seen as an extension of mTSP with two additional constraints: (1) precedence constraint that models a scenario where an operation of a job becomes processable only after all of its preceding operations are done; (2) agent-sharing (disjunctive) constraint that confines the machine to process only one operation at a time. Due to these additional constraints, JSP is considered to be a more difficult problem when it is solved via mathematical optimization techniques. A common representation of JSP is the disjunctive graph representation. As shown in Figures 6, 7 and 8, JSP contains the set of jobs, machines, precedence constraints, and disjunctive constraints as its entities. In the following sections, we provide the details of the proposed MDP formulation of JSP, training details of ScheduleNet, and experiment results.

D.1 MDP FORMULATION

The MDP formulation of JSP is similar to that of mTSP. The specific definitions of the state and action for JSP are as follows:

State. We define $s_\tau = (\{s_\tau^i\}_{i=1}^{N+m}, s_\tau^{\text{env}})$ which is composed of two types of states: entity state s_τ^i and environment state s_τ^{env}.

- $s_\tau^i = (p_\tau^i, \mathbf{1}_\tau^{\text{processable}}, \mathbf{1}_\tau^{\text{assigned}}, \mathbf{1}_\tau^{\text{accessible}}, \mathbf{1}_\tau^{\text{waiting}})$ is the state of the i-th entity. p_τ^i is the processing time of the i-th entity at the τ-th event. $\mathbf{1}_\tau^{\text{processable}}$ indicates whether the i-th task is processable by the target agent or not. Similar to mTSP, $\mathbf{1}_\tau^{\text{assigned}}$ indicates whether an agent/task is assigned.

- s_τ^{env} contains the current time of the environment, the sequence of tasks completed by each agent (machine), and the precedence constraints of tasks within each job.

Action. We define the action space at the τ-th event as a set of oeprations that is both processable and currently available. Additionally, we define the *waiting* action as a reservation of the target agent (i.e. the unique idle machine) until the next event. Having *waiting* as an action allows the adaptive scheduler (e.g. ScheduleNet) to achieve the optimal scheduling solution (and also makespan) from the JSP MDP, where the optimal solution contains waiting (idle) time intervals.

D.2 AGENT-TASK GRAPH FORMULATION

ScheduleNet constructs the *agent-task graph* $\mathcal{G}_\tau$ that reflects the complex relationships among the entities in s_τ. ScheduleNet constructs a directed graph $\mathcal{G}_\tau = (\mathbb{V}, \mathbb{E})$ out of s_τ, where $\mathbb{V}$ is the set of nodes and $\mathbb{E}$ is the set of edges. The nodes and edges and their associated features are defined as:

- v_i denotes the i-th node and represents either an agent or a task. v_i contains the node feature $x_i = (s_\tau^i, k_i)$, where s_τ^i is the state of entity i, and k_i is the type of v_i (e.g. if the entity i is a *task* and its $\mathbf{1}_\tau^{processable} = 1$, then the k_i becomes a *processable-task* type.)

- e_{ij} denotes the edge between the source node v_j and the destination node v_i. The edge feature w_{ij} is a binary feature which indicates whether the destination node v_i is processable by the source node v_j.

All possible node types in $\mathcal{G}_\tau$ are: (1) assigned-agent, (2) unassigned-agent, (3) assigned-task, (4) processable-task, and (5) unprocessable-task. We do not include completed tasks in the graph. Thus, the currently active tasks are the union of the assigned tasks, processable-tasks, and unprocessable-tasks. The full list of node features are as follows:

- $\mathbf{1}_\tau^{\text{agent}}$ indicates whether the node is a agent or a task.
- $\mathbf{1}_\tau^{\text{target-agent}}$ indicates whether the node is a target-agent (unique idle agent that needs to be assigned).
- $\mathbf{1}_\tau^{\text{assigned}}$ indicates whether the agent/task is assigned.
- $\mathbf{1}_\tau^{\text{waiting}}$ indicates whether the node is an agent in *waiting* state.
- $\mathbf{1}_\tau^{\text{processable}}$ indicates whether the node is a task that is *processable* by the target-agent.
- $\mathbf{1}_\tau^{\text{accessible}}$ indicates whether the node is processable by the target-agent and is available.
- *Task wait time* indicates the amount of time passed since the operation became *accessible*.
- *Task processing time* indicates the processing time of the operation.
- *Time-to-complete* indicates the amount of time it will take to complete the task, i.e. the time-distance to the given task.
- *Remain ops.* indicates the number of remaining operations to be completed for the job where the task belongs to.
- *Job completion ratio* is the ratio of completed operations within the job to the total amount of operations in the job.

JSP graph connectivity. Figure 9 visualizes the proposed agent-task graph. From Figure 9, each agent is fully connected to the set of processable tasks by that agent, and vice versa. Each task is fully connected to the other tasks (operations) that belong to the same job. Each agent is fully connected to the other agents.

Figure 9: JSP agent-task graph representation

D.3 TRAINING DETAILS

We use the same training hyperparameters as in Appendix C.3.

D.4 BASELINE IMPLEMENTATIONS

Priority dispatching rules (PDR) is one of the most common JSP solving heuristics. PDR computes the priority of the feasible operations (i.e. the set of operations whose precedent operation is done and, at the same time, the target machine is idle) by utilizing the dispatching rules. As the JSP heuristic baselines, we consider the following three dispatching rules:

- Most Operation Remaining (MOR) sets the highest priority to the operation that has the most remaining operations to finish its corresponding job.
- First-in-first-out (FIFO) sets the highest priority to the operation that joins to the feasible operation set first.
- Shortest Processing Time (SPT) sets the highest priority to the operation that has the shortest processing time.

D.5 EXTENDED PUBLIC BENCHMARK JSP RESULTS

We provide the detailed JSP results for the following public datasets: TA (Taillard, 1993) (Tables 5 and 6), ORB Applegate & Cook (1991), FT Fisher (1963), YN Yamada & Nakano (1992) (Table 7), SWV Storer et al. (1992) (Table 8), and LA Lawrence (1984) (Table 9).

Table 5: Job-shop scheduling makespans on TA dataset (Part 1)

Instance	N × m	SPT	FIFO	MOR	Park et al. (2021)	Zhang et al. (2020)	ScheduleNet	OPT
Ta01	15 × 15	1462	1486	1438	1389	1443	1452	1231
Ta02	15 × 15	1446	1486	1452	1519	1544	1411	1244
Ta03	15 × 15	1495	1461	1418	1457	1440	1396	1218
Ta04	15 × 15	1708	1575	1457	1465	1637	1348	1175
Ta05	15 × 15	1618	1457	1448	1352	1619	1382	1224
Ta06	15 × 15	1522	1528	1486	1481	1601	1413	1238
Ta07	15 × 15	1434	1497	1456	1554	1568	1380	1227
Ta08	15 × 15	1457	1496	1482	1488	1468	1374	1217
Ta09	15 × 15	1622	1642	1594	1556	1627	1523	1274
Ta10	15 × 15	1697	1600	1582	1501	1527	1493	1241
Ta11	20 × 15	1865	1701	1665	1626	1794	1612	1357
Ta12	20 × 15	1667	1670	1739	1668	1805	1600	1367
Ta13	20 × 15	1802	1862	1642	1715	1932	1625	1342
Ta14	20 × 15	1635	1812	1662	1642	1664	1590	1345
Ta15	20 × 15	1835	1788	1682	1672	1730	1676	1339
Ta16	20 × 15	1965	1825	1638	1700	1710	1550	1360
Ta17	20 × 15	2059	1899	1856	1678	1897	1753	1462
Ta18	20 × 15	1808	1833	1710	1684	1794	1668	1396
Ta19	20 × 15	1789	1716	1651	1900	1682	1622	1332
Ta20	20 × 15	1710	1827	1622	1752	1739	1604	1348
Ta21	20 × 20	2175	2089	1964	2199	2252	1921	1642
Ta22	20 × 20	1965	2146	1905	2049	2102	1844	1600
Ta23	20 × 20	1933	2010	1922	2006	2085	1879	1557
Ta24	20 × 20	2230	1989	1943	2020	2200	1922	1644
Ta25	20 × 20	1950	2160	1957	1981	2201	1897	1595
Ta26	20 × 20	2188	2182	1964	2057	2176	1887	1643
Ta27	20 × 20	2096	2091	2160	2187	2132	2009	1680
Ta28	20 × 20	1968	1980	1952	2054	2146	1813	1603
Ta29	20 × 20	2166	2011	1899	2210	1952	1875	1625
Ta30	20 × 20	1999	1941	2017	2140	2035	1913	1584
Ta31	30 × 15	2335	2277	2143	2251	2565	2055	1764
Ta32	30 × 15	2432	2279	2188	2378	2388	2268	1784
Ta33	30 × 15	2453	2481	2308	2316	2324	2281	1791
Ta34	30 × 15	2434	2546	2193	2319	2332	2061	1829
Ta35	30 × 15	2497	2478	2255	2333	2505	2218	2007
Ta36	30 × 15	2445	2433	2307	2210	2497	2154	1819
Ta37	30 × 15	2664	2382	2190	2201	2325	2112	1771
Ta38	30 × 15	2155	2277	2179	2151	2302	1970	1673
Ta39	30 × 15	2477	2255	2167	2138	2410	2146	1795
Ta40	30 × 15	2301	2069	2028	2007	2140	2030	1669

Table 6: Job-shop scheduling makespans on TA dataset (Part 2)

Instance	N × m	SPT	FIFO	MOR	Park et al. (2021)	Zhang et al. (2020)	ScheduleNet	OPT
Ta41	30 × 20	2499	2543	2538	2654	2667	2572	2005
Ta42	30 × 20	2710	2669	2440	2579	2664	2397	1937
Ta43	30 × 20	2434	2506	2432	2737	2431	2310	1846
Ta44	30 × 20	2906	2540	2426	2772	2714	2456	1979
Ta45	30 × 20	2640	2565	2487	2435	2637	2445	2000
Ta46	30 × 20	2667	2582	2490	2681	2776	2541	2004
Ta47	30 × 20	2620	2508	2286	2428	2476	2280	1889
Ta48	30 × 20	2620	2541	2371	2440	2490	2358	1941
Ta49	30 × 20	2666	2550	2397	2446	2556	2301	1961
Ta50	30 × 20	2429	2531	2469	2530	2628	2453	1923
Ta51	50 × 15	3856	3590	3567	3145	3599	3382	2760
Ta52	50 × 15	3266	3365	3303	3157	3341	3231	2756
Ta53	50 × 15	3507	3169	3115	3103	3186	3083	2717
Ta54	50 × 15	3142	3218	3265	3278	3266	3068	2839
Ta55	50 × 15	3225	3291	3279	3142	3232	3078	2679
Ta56	50 × 15	3530	3329	3100	3258	3378	3065	2781
Ta57	50 × 15	3725	3654	3335	3230	3471	3266	2943
Ta58	50 × 15	3365	3362	3420	3469	3732	3321	2885
Ta59	50 × 15	3294	3357	3117	3108	3381	3044	2655
Ta60	50 × 15	3500	3129	3044	3256	3352	3036	2723
Ta61	50 × 20	3606	3690	3376	3425	3654	3202	2868
Ta62	50 × 20	3639	3657	3417	3626	3722	3339	2869
Ta63	50 × 20	3521	3367	3276	3110	3536	3118	2755
Ta64	50 × 20	3447	3179	3057	3329	3631	2989	2702
Ta65	50 × 20	3332	3273	3249	3339	3359	3168	2725
Ta66	50 × 20	3677	3610	3335	3340	3555	3199	2845
Ta67	50 × 20	3487	3612	3392	3371	3567	3236	2825
Ta68	50 × 20	3336	3471	3251	3265	3680	3072	2784
Ta69	50 × 20	3862	3607	3526	3798	3592	3535	3071
Ta70	50 × 20	3801	3784	3590	3919	3643	3436	2995
Ta71	100 × 20	6232	6270	5938	5962	6452	5879	5464
Ta72	100 × 20	5973	5671	5639	5522	5695	5456	5181
Ta73	100 × 20	6482	6357	6128	6335	6462	6052	5568
Ta74	100 × 20	6062	6003	5642	5827	5885	5513	5339
Ta75	100 × 20	6217	6420	6212	6042	6355	5992	5392
Ta76	100 × 20	6370	6183	5936	5707	6135	5773	5342
Ta77	100 × 20	6045	5952	5829	5737	6056	5637	5436
Ta78	100 × 20	6143	6328	5886	5979	6101	5833	5394
Ta79	100 × 20	6018	6003	5652	5799	5943	5556	5358
Ta80	100 × 20	5848	5763	5707	5718	5892	5545	5183

Table 7: Job-shop scheduling makespans on ABZ, FT, ORB, and YN datasets.

Instance	N × m	SPT	FIFO	MOR	Park et al. (2021)	ScheduleNet	OPT
abz5	10 × 10	1352	1467	1336	1353	1336	1234
abz6	10 × 10	1097	1045	1031	1043	981	943
abz7	20 × 15	849	803	775	887	791	656
abz8	20 × 15	929	877	810	843	787	665
abz9	20 × 15	887	946	899	848	832	678
ft06	6 × 6	88	65	59	71	59	55
ft10	10 × 10	1074	1184	1163	1142	1111	930
ft20	20 × 5	1267	1645	1601	1338	1498	1165
orb01	10 × 10	1478	1368	1307	1336	1276	1059
orb02	10 × 10	1175	1007	1047	1067	958	888
orb03	10 × 10	1179	1405	1445	1202	1335	1005
orb04	10 × 10	1236	1325	1287	1281	1178	1005
orb05	10 × 10	1152	1155	1050	1082	1042	887
orb06	10 × 10	1190	1330	1345	1178	1222	1010
orb07	10 × 10	504	475	500	477	456	397
orb08	10 × 10	1107	1225	1278	1156	1178	899
orb09	10 × 10	1262	1189	1165	1143	1145	934
orb10	10 × 10	1113	1303	1256	1087	1080	944
yn1	20 × 20	1196	1113	1045	1118	1027	884
yn2	20 × 20	1256	1148	1074	1097	1037	904
yn3	20 × 20	1042	1135	1100	1083	1046	892
yn4	20 × 20	1273	1194	1267	1258	1216	968

Table 8: Job-shop scheduling makespans on SWV datasets.

Instance	N × m	SPT	FIFO	MOR	Park et al. (2021)	ScheduleNet	OPT
swv01	20 × 10	1737	2154	1971	1761	1913	1407
swv02	20 × 10	1706	2157	2158	1846	1998	1475
swv03	20 × 10	1806	2019	1870	1892	1830	1398
swv04	20 × 10	1874	2015	2026	1908	1971	1464
swv05	20 × 10	1922	2003	2049	1796	1922	1424
swv06	20 × 15	2140	2519	2287	2068	2216	1671
swv07	20 × 15	2146	2268	2101	2194	2037	1594
swv08	20 × 15	2231	2554	2480	2191	2255	1752
swv09	20 × 15	2247	2498	2553	2278	2196	1655
swv10	20 × 15	2337	2352	2431	2141	2279	1743
swv11	50 × 10	3714	4427	4642	3989	4390	2983
swv12	50 × 10	3759	4749	4821	4136	4532	2977
swv13	50 × 10	3657	4829	4755	4008	4602	3104
swv14	50 × 10	3506	4621	4740	3758	4387	2968
swv15	50 × 10	3501	4620	4905	3860	4402	2885
swv16	50 × 10	3453	2951	2924	2924	2924	2924
swv17	50 × 10	3082	2962	2848	2840	2794	2794
swv18	50 × 10	3191	2974	2852	2852	2852	2852
swv19	50 × 10	3161	3095	3060	2961	2992	2843
swv20	50 × 10	3125	2853	2851	2823	2823	2823

Table 9: Job-shop scheduling makespans on LA datasets.

Instance	$N \times m$	SPT	FIFO	MOR	Park et al. (2021)	ScheduleNet	OPT
la01	10×5	751	772	763	805	680	666
la02	10×5	821	830	812	687	768	655
la03	10×5	672	755	726	862	734	597
la04	10×5	711	695	706	650	698	590
la05	10×5	610	610	593	593	593	593
la06	15×5	1200	926	926	926	926	926
la07	15×5	1034	1088	1001	931	1008	890
la08	15×5	942	980	925	863	863	863
la09	15×5	1045	1018	951	951	951	951
la10	15×5	1049	1006	958	966	958	958
la11	20×5	1473	1272	1222	1276	1254	1222
la12	20×5	1203	1039	1039	1039	1039	1039
la13	20×5	1275	1199	1150	1150	1150	1150
la14	20×5	1427	1292	1292	1292	1292	1292
la15	20×5	1339	1587	1436	1282	1395	1207
la16	10×10	1156	1180	1108	1134	1047	945
la17	10×10	924	943	844	953	888	784
la18	10×10	981	1049	942	1049	947	848
la19	10×10	940	983	1088	880	963	842
la20	10×10	1000	1272	1130	1042	989	902
la21	15×10	1324	1265	1251	1309	1261	1046
la22	15×10	1180	1312	1198	1158	1027	927
la23	15×10	1162	1354	1268	1085	1145	1032
la24	15×10	1203	1141	1149	1129	1088	935
la25	15×10	1449	1283	1209	1308	1117	977
la26	20×10	1498	1372	1411	1553	1458	1218
la27	20×10	1784	1644	1566	1624	1516	1235
la28	20×10	1610	1474	1477	1438	1357	1216
la29	20×10	1556	1540	1437	1582	1320	1152
la30	20×10	1792	1648	1565	1649	1490	1355
la31	30×10	1951	1918	1836	1817	1906	1784
la32	30×10	2165	2110	1984	1977	1850	1850
la33	30×10	1901	1873	1811	1795	1731	1719
la34	30×10	2070	1925	1853	1895	1784	1721
la35	30×10	2118	2142	2064	2041	1969	1888
la36	15×15	1799	1516	1492	1489	1449	1268
la37	15×15	1655	1873	1606	1623	1653	1397
la38	15×15	1404	1475	1455	1421	1444	1196
la39	15×15	1534	1532	1540	1555	1430	1233
la40	15×15	1476	1531	1358	1570	1357	1222