Deep Biological Pathway Informed Pathology-Genomic Multimodal Survival Prediction

Abstract

The integration of multi-modal data, such as pathological images and genomic data, is essential for understanding cancer heterogeneity and complexity for personalized treatments, as well as for enhancing survival predictions. Despite the progress made in integrating pathology and genomic data, most existing methods cannot mine the complex inter-modality relations thoroughly. Additionally, identifying explainable features from these models that govern preclinical discovery and clinical prediction is crucial for cancer diagnosis, prognosis, and therapeutic response studies. We propose PONET- a novel biological pathway informed pathology-genomic deep model that integrates pathological images and genomic data not only to improve survival prediction but also to identify genes and pathways that cause different survival rates in patients. Empirical results on six of The Cancer Genome Atlas (TCGA) datasets show that our proposed method achieves superior predictive performance and reveals meaningful biological interpretations. The proposed method establishes insight on how to train biological informed deep networks on multimodal biomedical data which will have general applicability for understanding diseases and predicting response and resistance to treatment.

1 Introduction

Manual examination of haematoxylin and eosin (H&E)-stained slides of tumour tissue by pathologists is currently the state-of-the-art for cancer diagnosis (Chan, 2014). The recent advancements in deep learning for digital pathology have enabled the use of whole-slide images (WSI) for computational image analysis tasks, such as cellular segmentation (Pan et al., 2017; Hou et al., 2020), tissue classification and characterisation (Hou et al., 2016; Hekler et al., 2019; Iizuka et al., 2020). While H&E slides are important and sufficient to establish a profound diagnosis, genomics data can provide a deep characterisation of the tumour on the molecular level potentially offering the chance for prognostic and predictive biomarker discovery.

Cancer prognosis via survival outcome prediction is a standard method used for biomarker discovery, stratification of patients into distinct treatment groups, and therapeutic response prediction (Cheng et al., 2017; Ning et al., 2020). WSIs exhibit enormous heterogeneity and can be as large as $150,000 \times 150,000$ pixels. Most approaches adopt a two-stage multiple instance learning-based (MIL) approach for representation learning of WSIs, in which: 1) instance-level feature representations are extracted from image patches in the WSI, and then 2) global aggregation schemes are applied to the bag of instances to obtain a WSI-level representation for subsequent supervision (Hou et al., 2016; Courtiol et al., 2019; Wulczyn et al., 2020; Lu et al., 2021). Therefore, multimodal survival prediction faces an additional challenge due to the large data heterogeneity gap between WSIs and genomics, and many existing approaches use simple multimodal fusion mechanisms for feature integration, which prevents mining important multimodal interactions (Mobadersany et al., 2018; Chen et al., 2022b;a).

The incorporation of biological pathway databases in a model takes advantage of leveraging prior biological knowledge so that potential prognostic factors of well-known biological functionality can be identified (Hao et al., 2018). Moreover, encoding biological pathway information into the neural networks achieved superior predictive performance compared with established models (Elmarakeby et al., 2021).

Based on the current challenges in multimodal fusion of pathology and genomics and the potential prognostic interpretation to link pathways and clinical outcomes in pathway-based analysis, we

Figure 1: Overview of PONET model.

propose a novel biological pathway informed pathology-genomic deep model, PONET, that uses H&E WSIs and genomic profile features for survival prediction. The proposed method contains four major contributions: 1) PONET formulates a biological pathway informed deep hierarchical multimodal integration framework for pathological images and genomic data; 2) PONET captures diverse and comprehensive modality-specific and cross modality relations among different data sources based on factorized bilinear model and graph fusion network; 3) PONET reveals meaningful model interpretations on both genes and pathways for potential biomarker and therapeutic target discovery; PONET also shows spatial visualization of the top genes/pathways which has enormous potential for novel and prognostic morphological determinants; 4) We evaluate PONET on six public TCGA datasets which showed superior survival prediction comparing to state-of-the-art methods. Fig. 1 shows our model framework.

2 RELATED WORK

Multimodal Fusion. Earlier works on multimodal fusion focus on early fusion and late fusion. Early fusion approaches fuse features by simple concatenation which cannot fully explore intra-modality dynamics (Wöllmer et al., 2013; Poria et al., 2016; Zadeh et al., 2016). In contrast, late fusion fuses different modalities by weighted averaging which fails to model cross-modal interactions (Nojavanasghari et al., 2016; Kampman et al., 2018). The exploitation of relations within each modality has been successfully introduced in cancer prognosis via bilinear model (Wang et al., 2021b) and graph-based model (Subramanian et al., 2021). Inspired from graph-style neural network (Zadeh et al., 2016; Garcia & Bruna, 2018), Adversarial Representation Graph Fusion (ARGF) (Mai et al., 2020) interprets multimodal fusion as a hierarchical interaction learning procedure where firstly bimodal interactions are generated based on unimodal dynamics, and then trimodal dynamics are generated based on bimodal and unimodal dynamics. Meanwhile, ARGF addresses the challenge of matching heterogeneous distributions before fusion and assign different importance to various inter-modality interactions, which can significantly narrow modality gap by matching multimodal distributions. Based on ARGF's graph fusion idea, we propose a new hierarchical fusion framework with modality-specific and cross-modality attentional factorized bilinear modules to mine the comprehensive modality interactions.

Multimodal Survival Analysis. There have been exciting attempts on multimodal fusion of pathology and genomic data for cancer survival prediction (Mobadersany et al., 2018; Cheerla & Gevaert, 2019; Wang et al., 2020). However, these multimodal fusion based methods fail to explicitly model the interaction between each subset of multiple modalities. Kronecker product considers pairwise interactions of two input feature vectors by producing a high-dimensional feature of quadratic expansion (Zadeh et al., 2017), and showed its superiority in cancer survival prediction (Wang et al., 2021b; Chen et al., 2022b;a). Despite of promising results, using Kronecker product in multimodal fusion may introduce a large number of parameters that may lead to high computational cost and a risk of overfitting (Kim et al., 2017; Liu et al., 2021), thus limiting its applicability and improvement in performance. To overcome this drawback, hierarchical factorized bilinear fusion for cancer survival prediction (HFBSurv) (Li et al., 2022) uses factorized bilinear model to fuse genomic and image

features which dramatically reduces computational complexity. PONET differs from HFBSurv in two ways: 1) PONET's multimodal framework has three levels of hierarchical fusion module including unimodal, bimodal, and trimodal fusion while HFBSurv only considers within-modality and cross-modality fusion which we argue it is not adequate for mining the comprehensive interactions; 2) PONET leverages biological pathway informed network for better prediction and meaningful interpretation purposes.

Pathway-associated Sparse Neural Network. The capabilities of high-level biological representation and interpretation of the prognosis are often more desired in biomedical research rather than merely improving predictive performance. Pathway-based analysis is an approach that a number of studies have been investigated to improve both predictive performance and biological interpretability (Jin et al., 2014; Cirillo et al., 2017; Hao et al., 2018; Elmarakeby et al., 2021). Moreover, pathway-based approaches have shown more reproducible analysis results than gene expression data analysis alone (Li et al., 2015; Mallavarapu et al., 2017). Unlike our proposed PONET can integrate pathology and genomic data, these pathway-based deep neural networks can only model genomic data which severely inhibits their applicability in current biomedical research.

3 BACKGROUND

3.1 MULTIMODAL LOW-RANK BILINEAR POOLING

Bilinear models (Tenenbaum & Freeman, 2000) provide richer representations than linear models. Given two feature vectors in different modalities, e.g., the visual features $x \in \mathbb{R}^m$ for an image and the genomic features $y \in \mathbb{R}^n$ for a genomic profile, bilinear model uses a quadratic expansion of linear transformation considering every pair of features:

$$z_i = x^T W_i y \tag{1}$$

where $W_i \in \mathbb{R}^{m \times n}$ is a projection matrix, $z_i \in \mathbb{R}$ is the output of the bilinear model. Fukui et al. (2016) first introduced the bilinear model to solve the problem of multi-modal feature fusion in visual question answering (VQA), they proposed the Multi-modal Compact Bilinear pooling (MCB) which uses the outer product of two feature vectors to produce a very high-dimensional feature for quadratic expansion. Such high-dimensional features could be a bottleneck for computationally complex models. To overcome this drawback, Kim et al. (2017) proposed the Multi-modal Low-rank Bilinear Pooling (MLB) approach based on the Hadamard product of two feature vectors in the common space with two low-rank projection matrices:

$$z_i = (U_i^T x \circ V_i^T y) \tag{2}$$

where $U_i = [u_1, ..., u_o] \in \mathbb{R}^{m \times o}$ and $V_i = [v_1, ..., v_o] \in \mathbb{R}^{n \times o}$, o is the dimensionality of the output feature, $\circ$ is the Hadmard product or the element-wise multiplication of two vectors.

3.2 FACTORIZED MULTI-MODAL BILINEAR POOLING

MLB has a slow convergence rate and is sensitive to the learned hyperparameters. To address these issues, Yu et al. (2017) develop the Multi-modal Factorized Bilinear pooling (MFB) method, which enjoys the dual benefits of compact output features of MLB and robust expressive capacity of MCB. The projection matrix W_i in Eq. (1) can be factorized as two low-rank matrices:

$$
\begin{aligned}
z_i &= x^T U_i V_i^T y = \sum_{d=1}^{k} x^T u_d v_d^T y \\
&= 1^T (U_i^T x \circ V_i^T y)
\end{aligned}
\tag{3}
$$

where k is the factor or the latent dimensionality of the factorized matrices $U_i = [u_1, ..., u_k] \in \mathbb{R}^{m \times k}$ and $V_i = [v_1, ..., v_k] \in \mathbb{R}^{n \times k}$, $1 \in \mathbb{R}^k$ is an all-one vector. To obtain the output feature $z \in \mathbb{R}^o$ by Eq. (3), the weights to be learned are two three-order tensors $U = [U_1, ..., U_o] \in \mathbb{R}^{m \times k \times o}$ and $V = [V_1, ..., V_d] \in \mathbb{R}^{n \times k \times o}$ accordingly. Without loss of generality, U and V can be reformulated as 2-D matrices $\tilde{U} \in \mathbb{R}^{m \times ko}$ and $\tilde{V} \in \mathbb{R}^{n \times ko}$ respectively with simple reshape operations. Accordingly, Eq. (3) can be rewritten as follows:

$$z = \text{SumPooling}(\tilde{U}^T x \circ \tilde{V}^T y, k) \tag{4}$$

where the function $\mathrm{SumPooling}(x, k)$ means using a one-dimensional non-overlapped window with the size k to perform sum pooling over x.

4 METHODOLOGY

4.1 PROBLEM FORMULATION AND NOTATIONS

The model architecture of PONET is presented in Fig. 1, where three modalities are included as input: gene expression $g \in \mathbb{R}^{d_g}$, pathological image $p \in \mathbb{R}^{d_p}$, and copy number (CNV) + mutation (MUT) $CNV + MUT \in \mathbb{R}^{d_c}$, with d_p being the dimensionality of p and so on. We define a hierarchical factorized bilinear fusion model for PONET. We build a sparse biological pathway-informed embedding network for gene expression (Han et al., 2018; Elmarakeby et al., 2021), and a fully connected (FC) embedding layer for both preprocessed pathological image feature (f_p) and the copy number + mutation (f_c) to map feature into similar embedding space for alleviating the statistical property differences between modalities, the three network architecture details are in Appendix C.1. We label the three modality embeddings as $h_m, m \in \{g, p, c\}$, the superscript/subscript u, b, and t represents unimodal fusion, biomodal fusion and trimodal fusion. After that, the embeddings of each modality is first used as input for unimodal fusion to generate the modality-specific representation $h_m^u = \omega^m \hat{h}_m$, ω^m represents the modality-specific importance, the feature vector of the unimodal fusion is the sum of all modality-specific representations $h_u = \sum_m h_m^u$. In the bimodal fusion, modality-specific representations from the output of unimodal fusion are fused to yield cross-modality representations $h_{m_1 m_2}^b = \omega_{m_1 m_2} \hat{h}_{m_1 m_2}, m_1, m_2 \in (p, c, g)$ and $m_1 \neq m_2$, $\omega_{m_1 m_2}$ represents the corresponding cross-modality importance. Similarly, the feature vector of bimodal fusion is calculated as $h_b = \sum_{m_1, m_2} h_{m_1 m_2}^b$. Motived by ARGF's (Mai et al., 2020) there level hierarchical graph fusion multimodal model for visual, language and acoustic data, we propose to build a trimodal fusion to take each cross-modality representation from the output of bimodal fusion to thoroughly mine the interactions. Simiarly as the bimodal fusion architecture, trimodal fusion feature vector will be $h_t = \sum_{m_1, m_2, m_3} \omega_{m_1 m_2 m_3} \hat{h}_{m_1 m_2 m_3}, m_1, m_2, m_3 \in (p, c, g)$ and $m_1 \neq m_2 \neq m_3$, $\omega_{m_1 m_2 m_3}$ represents the corresponding trimodal importance.

Finally, PONET concatenates h_u, h_b, h_t to obtain the final comprehensive multimodal representation and pass it to the Cox porportional harzard model (Cox, 1972; Cheerla & Gevaert, 2019) for survival prediction. In the following sections we will describe our hierarchical factorized bilinear fusion framework, l, o, s represents the dimensionality of h_m, z_m, $\hat{h}_{m1m2}$.

4.2 UNIMODAL FUSION

We propose unimodal fusion to capture modality-specific representations and quantify their importance. Inspired by the factorized multi-modal bilinear pooling (Yu et al., 2017; Li et al., 2022), the unimodal fusion takes the embedding of each modality h_m as input and factorizes the projection matrix W_i in Eq. (1) as two low-rank matrices:

$$
\begin{aligned}
z_i &= h_m^T W_i h_m = \sum_{d=1}^{k} h_m^T u_{m,d} v_{m,d}^T h_m \\
&= 1^T (U_{m,i}^T h_m \circ V_{m,i}^T h_m), m \in \{p, c, g\}
\end{aligned}
\tag{5}
$$

According to Eq. (4), we get the output feature z_m:

$$
z_m = \mathrm{SumPooling}\left(\tilde{U}_m^T h_m \circ \tilde{V}_m^T h_m, k\right), m \in \{p, c, g\}
\tag{6}
$$

where k is the latent dimensionality of the factorized matrices. SumPooling (x, k) function performs sum pooling over x by using a 1-D non-overlapped window with the size k, $\tilde{U}_m \in \mathbb{R}^{l \times ko}$ and $\tilde{V}_m \in \mathbb{R}^{l \times ko}$ are 2-D matrices reshaped from U_m and V_m, $U_m = [U_{m,1}, \ldots, U_{m,h}] \in \mathbb{R}^{l \times k \times o}$ and $V_m = [V_{m,1}, \ldots, V_{m,h}] \in \mathbb{R}^{l \times k \times o}$. Each modality-specific representation $\hat{h}_m \in \mathbb{R}^{l+o}$ is obtained as:

$$
\hat{h}_m = h_m \copyright z_m, m \in \{p, c, g\}
$$

Figure 2: Overall framework of the visual representation extraction using pre-trained self-supervised vision transformer.

where © denotes vector concatenation. We also introduce an modality attention network $Atten \in \mathbb{R}^{l+o} \rightarrow \mathbb{R}^1$ to determine the weight for each modality-specific representation to quantify its importance:

$$\omega_m = Atten(\hat{h}_m; \Theta_{Atten}), m \in \{p, c, g\}$$

where ω_m is the weight of modality m. In practice, $Atten$ consists a sigmoid activated dense layer parameterized by Θ_{Atten}. Therefore, the output of each modality in unimodal fusion, h_m^u, is denoted as $\omega_m \hat{h}_m \in \mathbb{R}^{l+o}, m \in \{p, c, g\}$. Accordingly, the output of unimodal fusion, h_u, is the sum of each weighted modality-specific representation $\omega_m \hat{h}_m, m \in (p, c, g)$ which is different from ARGF (Mai et al., 2020) that used the weighted average of different modalities as the unimodal fusion output.

4.3 BIMODAL FUSION

The goal of bimodal fusion is to fuse diverse information of different modalities and quantify different importance for them. After receiving the modality-specific representations h_m^u from the unimodal fusion, we can generate the cross-modality representation $\hat{h}_{m_1 m_2} \in \mathbb{R}^s$ similar to Eq. (6):

$$\hat{h}_{m1,m2} = \mathrm{Sum\,Pooling}\left(\tilde{U}_{m_1}^T h_{m_1}^u \circ \tilde{V}_{m_2}^T h_{m_2}^u, k\right),$$

$$m_1, m_2 \in \{p, c, g\}, m_1 \neq m_2 \tag{7}$$

where $\tilde{U}_{m_1}^T \in \mathbb{R}^{(l+o) \times ks}$ and $\tilde{V}_{m_2}^T \in \mathbb{R}^{(l+o) \times ks}$ are 2-D matrices reshaped from U_{m_1} and V_{m_2} and $U_{m_1} = [U_{m_1,1}, \ldots, U_{m_1,s}] \in \mathbb{R}^{(l+o) \times k \times s}$ and $V_{m_2} = [V_{m_2,1}, \ldots, V_{m_2,s}] \in \mathbb{R}^{(l+o) \times k \times s}$. If two information vectors are close to each other, then little complementary information lies between them and their information has been well explored in the unimodal fusion. Borrow the idea from ARGF (Mai et al., 2020), we leverage a bimodal attention network to identify the importance of the cross-modality representation. The similarity $S_{m_1 m_2} \in \mathbb{R}^1$ of $h_{m_1}^u$ and $h_{m_2}^u$ is first estimated as follows:

$$S_{m_1,m_2} = \sum_{i=1}^{l+o} \left(\frac{e^{\omega_{m_1} h_{m_1,i}^u}}{\sum_{j=1}^{l+o} e^{\omega_{m_1} h_{m_1,j}^u}}\right)\left(\frac{e^{\omega_{m_2} h_{m_2,i}^u}}{\sum_{j=1}^{l+o} e^{\omega_{m_2} h_{m_2,j}^u}}\right)$$

where the computed similarity is in the range of 0 to 1. Then, the cross-modality importance $\omega_{m_1 m_2}$ is obtained by:

$$\omega_{m_1 m_2} = \frac{e^{\hat{\omega}_{m_i m_j}}}{\sum_{m_i \neq m_j} e^{\hat{\omega}_{m_i m_j}}}, \hat{\omega}_{m_1 m_2} = \frac{\omega_{m_1} + \omega_{m_2}}{S_{m_1 m_2} + S_0}$$

where S_0 represents a pre-defined term controlling the relative contribution of similarity and modality-specific importance, and here is set to 0.5. Therefore, the output of bimodal fusion, h_b, is the sum of each weighted cross-modality representation $\omega_{m_1 m_2} \hat{h}_{m_1 m_2}, m_1, m_2 \in (p, c, g)$ and $m_1 \neq m_2$.

4.4 TRIMODAL FUSION

In the trimodal fusion, all calculations are similar to the procedure of bimodal fusion. Each two bimodal fusion output are further fused using the MFB that generate the corresponding trimodal representation $\hat{h}_{m_1 m_2 m_3}$. In addition, a trimodal attention was applied to identify the importance of each trimodal representation, $\omega_{m_1 m_2 m_3}$. The output of the trimodal fusion, h_t, is the sum of each weighted trimodal representation $\omega_{m_1 m_2 m_3} \hat{h}_{m_1 m_2 m_3}, m_1, m_2, m_3 \in (p, c, g)$ and $m_1 \neq m_2 \neq m_3$.

4.5 SURVIVAL LOSS FUNCTION

We train the model through the Cox partial likelihood loss (Cheerla & Gevaert, 2019) with l_1 regularization for survival prediction, which is defined as:

$$\ell(\Theta) = - \sum_{i:E_i=1} \left(\hat{\mathfrak{h}}_\Theta\left(x_i\right) - \log \sum_{j:T_i>T_j} \exp\left(\hat{\mathfrak{h}}_\Theta\left(x_j\right)\right) \right) + \lambda\left(\|\Theta\|_1\right)$$

where the values E_i, T_i and x_i for each patient represent the survival status, the survival time and the feature, respectively. $E_i = 1$ means event while $E_i = 0$ represents censor. $\hat{\mathfrak{h}}_\Theta$ is the neural network model trained for predicting the risk of survival, Θ is the neural network model parameters, and λ is a regularization hyperparameter to avoid overfitting.

5 EXPERIMENTS

5.1 EXPERIMENTAL SETUP

Datasets. To validate our proposed method, we used six cancer datasets from The Cancer Genome Atlas (TCGA), a public cancer data consortium that contains matched diagnostic WSIs and genomic data with labeled survival times and censorship statuses. The genomic profile features (mutation status, copy number variation, RNA-Seq expression) are preprocessed by Porpoise [1] (Chen et al., 2022b). For this study, we used the following cancer types: Bladder Urothelial Carcinoma (BLCA) (n = 437), Kidney Renal Clear Cell Carcinoma (KIRC) (n = 350), Kidney Renal Papillary Cell Carcinoma (KIRP) (n = 284), Lung Adenocarcinoma (LUAD) (n = 515), Lung Squamous Cell Carcinoma (LUSC) (n = 484), Pancreatic adenocarcinoma (PAAD) (n = 180). We downloaded the same diagnostic WSIs from TCGA website [2] that used in Porpoise study to match the paired genomic features and survival times. The feature alignment table for all the cancer type is in Appendix A. For each WSI, automated segmentation of tissue was performed. Following segmentation, image patches of size 224×224 were extracted without overlap at the 20 X equivalent pyramid level from all tissue regions identified while excluding the white background and selecting only patches with at least 50% tissue regions. Subsequently, visual representation of those patches are extracted with a vision transformer (Wang et al., 2021a) pre-trained on the TCGA dataset through a self-supervised constructive learning approach, such that each patch is represented as a 1×2048 vector. Fig. 2 shows the framework for the visual representation extraction by vision transformer (VIT). Survival outcome information is available at the patient-level, we aggregated the patch level feature into slide level feature representations based on attention-based method (Lu et al., 2021; Ilse et al., 2018), please check the algorithm details in Appendix B.4.

Baselines. Using the same 5-fold cross-validation splits for evaluating PONET[3], we implemented and evaluated six state-of-the-art methods for survival outcome prediction. Additionally, we included three variations of PONET: a) PONET-O represents only genomic data and pathway architecture for the gene expression are included in the model; b) PONET-OH represents only genomic and pathological image data but without pathway architecture in the model; c) PONET is our full model. For all methods, we use the same VIT feature extraction pipeline for WSIs, as well as identical training hyperparameters and loss function for supervision. Training details and the parameters tuning can be found in the Appendix C.2.

CoxPH (Cox, 1972) represents the standard Cox proportional hazard models (Appendix B.1).
DeepSurv (Katzman et al., 2018) is the deep neural network version of CoxPH model.
Pathomic Fusion (Chen et al., 2022a) as a pioneered deep-learning based framework for predicting survival outcome by fusing pathology and genomic multimodal data, in which Kronecker product is taken to model pairwise feature interactions across modalities.
GPDBN (Wang et al., 2021b) adopts Kronecker product to model inter-modality and intra-modality relations between pathology and genomic data for cancer prognosis prediction.
HFBSurv (Li et al., 2022) extended GPDBN using factorized bilinear model to fuse genomic and

---

[1]https://github.com/mahmoodlab/PORPOISE

[2]https://www.cancer.gov/about-nci/organization/ccg/research/structural-genomics/tcga

[3]We will release our github repository after the paper accepted

Table 1: C-Index (mean $\pm$ standard deviation) of PONET and ablation experiments in TCGA survival prediction. Top two performers are highlighted in bold.

Model	TCGA-BLCA	TCGA-KIRC	TCGA-KIRP	TCGA-LUAD	TCGA-LUSC	TCGA-PAAD
CoxPH (Age + Gender) (Cox, 1972)	0.525 ± 0.130	0.550 ± 0.070	0.544 ± 0.050	0.531 ± 0.082	0.532 ± 0.094	0.539 ± 0.092
DeepSurv (Kampman et al., 2018)	0.580 ± 0.062	0.620 ± 0.043	0.560 ± 0.063	0.534 ± 0.077	0.541 ± 0.066	0.544 ± 0.076
GPDBN (Wang et al., 2021b)	0.612 ± 0.042	0.647 ± 0.073	0.669 ± 0.109	0.565 ± 0.057	0.545 ± 0.063	0.571 ± 0.060
HFBSurv (Li et al., 2022)	0.622 ± 0.043	0.667 ± 0.053	0.769 ± 0.109	0.581 ± 0.017	0.548 ± 0.049	0.591 ± 0.052
Pathomic Fusion (Chen et al., 2022a)	0.586 ± 0.062	0.598 ± 0.060	0.577 ± 0.032	0.543 ± 0.065	0.523 ± 0.045	0.545 ± 0.064
Porpoise (Chen et al., 2022b)	0.617 ± 0.048	$\mathbf{0.711 \pm 0.051}$	$\mathbf{0.811 \pm 0.089}$	0.586 ± 0.056	0.527 ± 0.043	0.591 ± 0.064
PONET-O (ours)	0.596 ± 0.056	0.664 ± 0.056	0.761 ± 0.093	$\mathbf{0.623 \pm 0.062}$	0.538 ± 0.037	$\mathbf{0.598 \pm 0.027}$
PONET-OH (ours)	$\mathbf{0.625 \pm 0.063}$	0.695 ± 0.043	0.776 ± 0.123	0.618 ± 0.049	$\mathbf{0.553 \pm 0.049}$	0.591 ± 0.050
PONET (ours)	$\mathbf{0.643 \pm 0.037}$	$\mathbf{0.726 \pm 0.056}$	$\mathbf{0.829 \pm 0.054}$	$\mathbf{0.646 \pm 0.047}$	$\mathbf{0.567 \pm 0.066}$	$\mathbf{0.639 \pm 0.080}$

pathology features in a within-modality and cross-modalities hierarchical fusion.

Porpoise (Chen et al., 2022b) applied discrete survival model and Kronecker product to fuse pathology and genomic data for survival prediction (Zadeh & Schmid, 2020).

Evaluation. For each cancer dataset, we used the cross-validated concordance index (C-Index) (Appendix B.2) (Harrell et al., 1982) to measure the predictive performance of correctly ranking the predicted patient risk scores with respect to overall survival.

5.2 RESULTS

Comparison with Baselines. In combing pathology image, genomics, and pathway network via PONET, our approach outperforms CoxPH models, unimodal networks, and previous deep learning based approaches on pathology-genomic-based survival outcome prediction (Table 1). From the results, deep learning-based approaches generally exhibit better performance than CoxPH model. PONET achieves superior C-index value in all six cancer types. All versions of PONET outperform Pathomic Fusion by a big margin which we think this is due to two main reasons: 1) Pathomic Fusion uses Kronecker product to fuse the two modalities and that's also the reason why other advanced fusion methods, like GPDBN and HFBSurv, achieves better performance: 2) The outperformed results showed in Pathomic Fusion paper is due to their graph convolutional network (GCN) for the image feature extraction while in this comparison we used the same image feature extracted by VIT. However, we argue that GCN is trained on the region of interest for feature extraction which might limit the understanding of the tumor microenvironment of the whole slide. HFBSurv shows better performance than GPDBN and Pathomic Fusion which is consistent with their findings, and these results further demonstrate that the hierarchical factorized bilinear model can better mine the rich complementary information among different modalities compare to Kronecker product. Porpoise performs similarly with PONET on TCGA-KIRC and TCGA-KIRP and outperformed HFBSurv in these two studies, this probably is due to Porpoise partitioned the survival time into different non-overlapping bins and parameterized it as a discrete survival model (Zadeh & Schmid, 2020) which works better for these two cancer types. In other cases, Porpoise performs similarly with HFBSurv. Note: the results of Porpoise are from their paper (Chen et al., 2022b).

Additionally, we can see that PONET consistently outperforms PONET-O and PONET-OH indicating that the effectiveness of the biological pathway-informed neural network and the contribution of pathological image for the overall survival prediction.

Ablation Studies. To assess the impact of hierarchical factorized bilinear fusion strategy is indeed effective, we compare PONET with four single-fusion methods: 1) Simple concatenation: concatenate each modality embeddings; 2) Element-wise addition: element-wise addition from each modality embeddings; 3) Decision fusion (Esteban et al., 2005): decision voting on the output of single modality embeddings; 4) Tensor fusion (Zadeh et al., 2017): Kronecker product from each modality embeddings. Table 2 shows the C-index values of different methods. We can see that PONET achieves the best performance and shows remarkable improvement over single-fusion methods on different cancer type datasets. For example, PONET outperforms the Simple concatenation by 8.4% (TCGA-BLCA), 27% (TCGA-KIRP), 15% (TCGA-LUAD), 8.0% (TCGA-LUSC), and 11.4% (TCGA-PAAD), etc.

Furthermore, we adopted four different configurations of PONET to evaluate each hierarchical component of the proposed method: 1) Unimodal: unimodal fusion output as the final feature representation; 2) Bimodal: bimodal fusion output as the final feature representation; 3) Unimodal +

Figure 3: Inspecting and interpreting PONET on TCGA-KIRP. **a**: Sankey diagram visualization of inner layers of PONET shows the estimated relative importance of different nodes in each layer. Nodes in the first layer represent genes; the next layers represent pathways; and the final layer represents the model outcome. Different layers are linked by weights. Nodes with darker colours are more important, while transparent nodes represent the residual importance of undisplayed nodes in each layer, H1 presents gene layer and H2-H4 represent pathway layers; **b**: Co-attention visualization of top 4 ranked pathways in one case of TCGA-KIRP.

Table 2: Evaluation of PONET on different fusion methods and configurations by C-index (mean ± standard deviation). Best performer is highlighted in bold.

Fusion strategy	Methods	TCGA-BLCA	TCGA-KIRP	TCGA-LUAD	TCGA-LUSC	TCGA-PAAD
Single	Simple concatenation	0.585 ± 0.045	0.652 ± 0.049	0.554 ± 0.065	0.525 ± 0.066	0.568 ± 0.075
	Element-wise addition	0.592 ± 0.047	0.655 ± 0.055	0.587 ± 0.065	0.522 ± 0.046	0.588 ± 0.055
	Decision fusion	0.583 ± 0.027	0.696 ± 0.048	0.605 ± 0.062	0.530 ± 0.042	0.583 ± 0.060
	Tensor fusion	0.605 ± 0.046	0.775 ± 0.053	0.595 ± 0.060	0.545 ± 0.045	0.592 ± 0.061
Hierarchical	Unimodal	0.596 ± 0.035	0.783 ± 0.063	0.611 ± 0.056	0.553 ± 0.073	0.595 ± 0.053
	Bimodal	0.602 ± 0.062	0.789 ± 0.053	0.601 ± 0.056	0.552 ± 0.051	0.598 ± 0.083
	Unimodal + Bimodal	0.614 ± 0.052	0.803 ± 0.061	0.631 ± 0.044	**0.578 ± 0.058**	0.615 ± 0.057
	PONET	**0.643 ± 0.037**	**0.829 ± 0.054**	**0.641 ± 0.046**	0.567 ± 0.066	**0.639 ± 0.070**

Bimodal: hierarchical (include both unimodal and bimodal feature representation) fusion; 4) PONET: our proposed hierarchical strategy by incorporating unimodal, bimodal and trimodal fusion output. As shown in Table 2, Unimodal + Bimodal performs better than Unimodal and Bimodal which demonstrates that Unimodal + Bimodal can capture the relations within each modality and across modalities. However, PONET outperforms Unimodal + Bimodal in 4 out of 5 cancer types indicating that three layers of hierarchical fusion can mine the comprehensive interactions among different modalities.

Model Interpretation. We discuss the model interpretation results for cancer type TCGA-KIRP here and the results for other cancer types are included in the Appendix C.3. To understand the interactions between different genes, pathways and biological processes that contributed to the predictive performance and to study the paths of impact from the input to the outcome, we visualized the whole structure of PONET with the fully interpretable layers after training (Fig. 3 a). To evaluate the relative importance of specific genes contributing to the model prediction, we inspected the genes layer and used the Integrated Gradients attribution (Sundararajan et al., 2017) method to obtain the total importance score of genes, and the modified ranking algorithm details are included in the Appendix B.5. Highly ranked genes included KRAS, PSMB6, RAC1, and CTNNB1 which are known kidney cancer drivers previously (Yang et al., 2017; Shan et al., 2017; Al-Obaidy et al., 2020; Guo et al., 2022).

GBN2, a member of the guanine nucleotide-binding proteins family, which has been reported that the decrease of its expression reduced tumor cell proliferation (Zhang et al., 2019). A recent study identified strong dependency on BCL2L1, which encodes the BCL-XL anti-apoptotic protein, in a subset of kidney cancer cells (Grubb et al., 2022). This biological interpretability revealed established and novel molecular features contributing kidney cancer. In addition, PONET selected a hierarchy of pathways relevant to the model prediction, including downregulation of TGF-beta receptor signaling, regulation of PTEN stability and activity, the NLRP1 inflammasome, and noncanonical activation of NOTCH3 by PSEN1, PSMB6, and BCL2L1. TGF-beta signaling is increasingly recognized as a key driver in cancer, and in progressive cancer tissues TGF-beta promotes tumor formation, and its increased expression often correlates with cancer malignancy (Han et al., 2018). Noncanonical activation of NOTCH3 was reported to limit tumour angiogenesis and plays vital roles in kidney disease (Lin et al., 2017).

To further inspect the pathway spatial association with WSI slide we adopted the co-attention survival method MCAT (Chen et al., 2021) between WSIs and genomic features on the top pathways of the second layer, visualized as a WSI-level attention heatmap for each pathway genomic embedding in Fig. 3 b (algorithm details are included in the Appendix B.6). Overall, we observe that high attention in different pathways showed different spatial pattern associations with the slide. This heatmap can reflect genotype-phenotype relationships in cancer pathology. The high attention regions (red) of different pathways in the heatmap have positive associations with the predicted death risk while the low attention regions (blue) have negative associations with the predicted risk. By further check the cell types in high attention patches we can gain insights of prognostic morphological determinants and have a better understanding about the complex tumor microenvironment.

Table 3: Comparison of model complexity

Methods	Number of Parameters	FLOPS
Pathomic Fusion	175M	168G
GPDBN	82M	91G
HFBSurv	0.3M	0.5G
PONET	2.8M	3.1G

Complexity Comparison. We compared PONET with Pathomic Fusion, GPDBN, and HFBSurv since both Pathomic Fusion and GPDBN are based on Kronecker product to fuse different modalities while GPDBN and HFBSurv modeled inter-modality and intra-modality relations which have similar consideration to our method. As illustrated in Table 3, PONET has 2.8M (M = Million) trainable parameters, which is approximately 1.6%, 3.4%, and 900% of the number of parameters of Pathomic Fusion, GPDBN, and HFBSurv. To assess the time complexity of PONET and the competitive methods, we calculate floating-point operations per second (FLOPS) of each method in testing. The results in Table 3 show that PONET needs 3.1G during testing, compared with 168G, 91G, and 0.5G in Pathomic Fusion, GPDBN, and HFBSurv. The main reason for fewer trainable parameters and number of FLOPS lies in that PONET and HFBSurv performs multimodal fusion using factorized bilinear model, and can significantly reduce the computational complexity and meanwhile obtain more favorable performance. PONET has one additional trimodal fusion which explains why it has more trainable parameters than HFBSurv.

6 CONCLUSION

In this study, we pioneer propose a novel biological pathway-informed hierarchical multimodal fusion model that integrates pathology image and genomic profile data for cancer prognosis. In comparison to previous works, PONET deeply mines the interaction from multimodal data by conducting unimodal, biomodal and trimodal fusion step by step. Empirically, PONET demonstrates the effectiveness of the model architecture and the pathway informed network for superior predictive performance. Our methods thus constitute valuable additions to the practical survival modeling toolkit. Specifically, PONET provides insight on how to train biological informed deep networks on multimodal biomedical data for biological discovery in clinic genomic contexts which will be useful for other problems in medicine that seek to combine heterogeneous data streams for understanding diseases and predicting response and resistance to treatment. While all experiments in this paper were limited to time-invariant features, extensions to time-varying features (longitudinal data) remain of interest. Longitudinal covariates will bring rich information to the study of disease progression and pathway dynamics.

REFERENCES

Khaleel I Al-Obaidy, John N Eble, Mehdi Nassiri, Liang Cheng, Mohammad K Eldomery, Sean R Williamson, Wael A Sakr, Nilesh Gupta, Oudai Hassan, Muhammad T Idrees, et al. Recurrent kras mutations in papillary renal neoplasm with reverse polarity. *Modern Pathology*, 33(6):1157–1164, 2020.

Laura Antolini, Patrizia Boracchi, and Elia Biganzoli. A time-dependent discrimination index for survival data. *Statistics in Medicine*, 24(24):3927–3944, 2005.

Norman Edward Breslow. Discussion of the paper by d.r. cox. *Journal of the Royal Statistical Society: Series B (Statistical Methodology)*, 34(2):216–217, 1972.

John KC Chan. The wonderful colors of the hematoxylin-eosin stain in diagnostic surgical pathology. *International Journal of Surgical Pathology*, 22(1):12–32, 2014.

Anika Cheerla and Olivier Gevaert. Deep learning with multimodal representation for pancancer prognosis prediction. *Bioinformatics*, 35:i446–i454, 2019.

Richard J Chen, Ming Y Lu, Wei-Hung Weng, Tiffany Y Chen, Drew FK Williamson, Trevor Manz, Maha Shady, and Faisal Mahmood. Multimodal co-attention transformer for survival prediction in gigapixel whole slide images. *IEEE/CVF International Conference on Computer Vision*, pp. 3995–4005, 2021.

Richard J Chen, Ming Y Lu, Jingwen Wang, Drew FK Williamson, Scott J Rodig, Neal I Lindeman, and Faisal Mahmood. Pathomic fusion: An integrated framework for fusing histopathology and genomic features for cancer diagnosis and prognosis. *IEEE Transactions on Medical Imaging*, 41(4):757–770, 2022a.

Richard J Chen, Ming Y Lu, Drew FK Williamson, Tiffany Y Chen, Jana Lipkova, Zahra Noor, Muhammad Shaban, Maha Shady, Mane Williams, Bumjin Joo, et al. Pan-cancer integrative histology-genomic analysis via interpretable multimodal deep learning. *arXiv:2108.02278*, 2022b.

Jun Cheng, Jie Zhang, Yatong Han, Xusheng Wang, Xiufen Ye, Yuebo Meng, Anil Parwani, Zhi Han, Qianjin Feng, and Kun Huang. Integrative analysis of histopathological images and genomic data predicts clear cell renal cell carcinoma prognosis. *Cancer Research*, 77(21):e91–e100, 2017.

Elisa Cirillo, Laurence D Parnell, and Chris T Evelo. A review of pathway-based analysis tools that visualize genetic variants. *Frontiers in Genetics*, 8(174), 2017.

Pierre Courtiol, Charles Maussion, Matahi Moarii, Elodie Pronier, Samuel Pilcer, Meriem Sefta, Pierre Manceron, Sylvain Toldo, Mikhail Zaslavskiy, Nolwenn Le Stang, et al. Deep learning-based classification of mesothelioma improves prediction of patient outcome. *Nature Medicine*, 25(10):1519–1525, 2019.

David R Cox. Regression models and life-tables. *Journal of the Royal Statistical Society: Series B (Statistical Methodology)*, 34(2):187–202, 1972.

Haitham A Elmarakeby, Justin Hwang, Rand Arafeh, Jett Crowdis, Sydney Gang, David Liu, Saud H AlDubayan, Keyan Salari, Steven Kregel, Camden Richter, et al. Biologically informed deep neural network for prostate cancer discovery. *Nature*, 598:348–352, 2021.

Jaime Esteban, Andrew Starr, Robert Willetts, Paul Hannah, and Peter Bryanston-Cross. A review of data fusion models and architectures: towards engineering guidelines. *Neural Computing and Applications*, 14:273–281, 2005.

Antonio Fabregat, Steven Jupe, Lisa Matthews, Konstantinos Sidiropoulos, Marc Gillespie, Phani Garapati, Robin Haw, Bijay Jassal, Florian Korninger, Bruce May, et al. The reactome pathway knowledgebase. *Nucleic Acids Research*, 48(D1):D498–D503, 2020.

Akira Fukui, Dong Huk Park, Daylen Yang, Anna Rohrbach, Trevor Darrell, and Marcus Rohrbach. Multimodal compact bilinear pooling for visual question answering and visual grounding. In *Proceedings of the 2016 Conference on Empirical Methods in Natural Language Processing*, pp. 457–468, 2016.

Victor Garcia and Joan Bruna. Few-shot learning with graph neural networkss. In *Proceedings of the International Conference on Learning Representations*, 2018.

Treg Grubb, Smruthi Maganti, John Michael Krill-Burger, Cameron Fraser, Laura Stransky, Tomas Radivoyevitch, Kristopher A. Sarosiek, Francisca Vazquez, William G. Kaelin Jr., and Abhishek A. Chakraborty. A mesenchymal tumor cell state confers increased dependency on the bcl-xl anti-apoptotic protein in kidney cancer. *bioRxiv*, 2022.

Jing-Yi Guo, Zuo-qian Jing, Xue-jie Li, and Li-yuan Liu. Bioinformatic analysis identifying psmb 1/2/3/4/6/8/9/10 as prognostic indicators in clear cell renal cell carcinoma. *International Journal of Medical Sciences*, 19(5):796–812, 2022.

Zhezhu Han, Dongxu Kang, Yeonsoo Joo, Jihyun Lee, Geun-Hyeok Oh, Soojin Choi, Suwan Ko, Suyeon Je, Hye Jin Choi, and Jae J Song. Tgf- downregulation-induced cancer cell death is finely regulated by the sapk signaling cascade. *Experimental and Molecular Medicine*, 50(12):162, 2018.

Jie Hao, Youngsoon Kim, Tae-Kyung Kim, and Mingon Kang. Pasnet: pathway-associated sparse deep neural network for prognosis prediction from high-throughput data. *BMC Bioinformatics*, 19: 510, 2018.

Frank E Harrell, Robert M Califf, David B Pryor, Kerry L Lee, and Robert A Rosati. Evaluating the yield of medical tests. *Journal of the American Medical Association*, 247(18):2543–2546, 1982.

Achim Hekler, Jochen S Utikal, Alexander H Enk, Wiebke Solass, Max Schmitt, Joachim Klode, Dirk Schadendorf, Wiebke Sondermann, Cindy Franklin, Felix Bestvater, et al. Deep learning outperformed 11 pathologists in the classification of histopathological melanoma images. *Europe Journal of Cancer*, 118:91–6, 2019.

Le Hou, Dimitris Samaras, Tahsin M Kurc, Yi Gao, James E Davis, and Joel H Saltz. Patch-based convolutional neural network for whole slide tissue image classification. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 2424–2433, 2016.

Le Hou, Rajarsi Gupta, John S Van Arnam, Yuwei Zhang, Kaustubh Sivalenka, Dimitris Samaras, Tahsin M Kurc, and Joel H Saltz. Dataset of segmented nuclei in hematoxylin and eosin stained histopathology images of ten cancer types. *Scientific Data*, 7(1):185, 2020.

Osamu Iizuka, Fahdi Kanavati, Kei Kato, Michael Rambeau, Koji Arihiro, and Masayuki Tsuneki. Deep learning models for histopathological classification of gastric and colonic epithelial tumours. *Scientific Report*, 10(1):1504, 2020.

Maximilian Ilse, Jakub Tomczak, and Max Welling. Attention-based deep multiple instance learning. In *Proceedings of the 35th International Conference on Machine Learning*, volume 80, pp. 2127–2136, 2018.

Lv Jin, Xiao-Yu Zuo, Wei-Yang Su, Xiao-Lei Zhao, Man-Qiong Yuan, Li-Zhen Han, Xiang Zhao, Ye-Da Chen, and Shao-Qi Rao. Pathway-based analysis tools for complex diseases: A review. *Genomics Proteomics Bioinformatics*, 12(5):210–220, 2014.

Onno Kampman, Elham J Barezi, Dario Bertero, and Pascale Fung. Investigating audio, video, and text fusion methods for end-to-end automatic personality prediction. In *Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics (Volume 2: Short Papers)*, pp. 606–611, 2018.

Jared L. Katzman, Uri Shaham, Alexander Cloninger, Jonathan Bates, Tingting Jiang, and Yuval Kluger. Deepsurv: personalized treatment recommender system using a cox proportional hazards deep neural network. *BMC Medical Research Methology*, 18(24):187–202, 2018.

Jin-Hwa Kim, Kyoung-Woon On, Woosang Lim, Jeonghee Kim, Jung-Woo Ha, and Byoung-Tak Zhang. Hadamard product for low-rank bilinear pooling. In *Proceedings of International Conference on Learning Representations*, pp. 1–14, 2017.

Ruiqing Li, Xingqi Wu, Ao Li, and Minghui Wang. Hfbsurv: hierarchical multimodal fusion with factorized bilinear models for cancer survival prediction. *Bioinformatics*, 38(9):2587–2594, 2022.

Yanming Li, Bin Nan, and Ji Zhu. Multivariate sparse group lasso for the multivariate multiple linear regression with an arbitrary group structure. *Biometrics*, 71(2):354–63, 2015.

Shuheng Lin, Ana Negulescu, Sirisha Bulusu, Benjamin Gibert, Jean-Guy Delcros, Benjamin Ducarouge, Nicolas Rama, Nicolas Gadot, Isabelle Treilleux, Pierre Saintigny, et al. Non-canonical notch3 signalling limits tumour angiogenesis. *Nature Communications*, 8:16074, 2017.

Zhun Liu, Ying Shen, Varun Bharadhwaj Lakshminarasimhan, Paul Pu Liang, Amir Zadeh, and Louis-Philippe Morency. Efficient low-rank multimodal fusion with modality-specific factors. In *Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics*, pp. 2247–2256, 2021.

Ming Y Lu, Drew FK Williamson, Tiffany Y Chen, Richard J Chen, Matteo Barbieri, and Faisal Mahmood. Data-efficient and weakly supervised computational pathology on whole-slide images. *Nature Biomedical Engineering*, 5:555–570, 2021.

Sijie Mai, Haifeng Hu, and Songlong Xing. Modality to modality translation: An adversarial representation learning and graph fusion network for multimodal fusion. In *Proceedings of the AAAI Conference on Artificial Intelligence*, pp. 164–172, 2020.

Tejaswini Mallavarapu, Youngsoon Kim, Jung Hun Oh, and Mingon Kang. R-pathcluster: Identifying cancer subtype of glioblastoma multiforme using pathway-based restricted boltzmann machine. In *2017 IEEE International Conference on Bioinformatics and Biomedicine*, pp. 1183–8, 2017.

Pooya Mobadersany, Safoora Yousefi, Mohamed Amgad, David A Gutman, Jill S Barnholtz-Sloan, José E Velázquez Vega, Daniel J Brat, and Lee AD Cooper. Predicting cancer outcomes from histology and genomics using convolutional networks. *Proceedings of the National Academy of Sciences*, 115(13):E2970–E2979, 2018.

Zhenyuan Ning, Weihao Pan, Yuting Chen, Qing Xiao, Xinsen Zhang, Jiaxiu Luo, Jian Wang, and Yu Zhang. Integrative analysis of cross-modal features for the prognosis prediction of clear cell renal cell carcinoma. *Bioinformatics*, 36(9):2888–2895, 2020.

Behnaz Nojavanasghari, Deepak Gopinath, Jayanth Koushik, Tadas Baltrušaitis, and Louis-Philippe Morency. Deep multimodal fusion for persuasiveness prediction. In *Proceedings of the 18th ACM International Conference on Multimodal Interaction*, pp. 284–288, 2016.

Xipeng Pan, Lingqiao Li, Huihua Yang, Zhenbing Liu, Jinxin Yang, Lingling Zhao, and Yongxian Fan. Accurate segmentation of nuclei in pathological images via sparse reconstruction and deep convolutional networks. *Neurocomputing*, 15:88–99, 2017.

Soujanya Poria, Iti Chaturvedi, Erik Cambria, and Amir Hussain. Convolutional mkl based multimodal emotion recognition and sentiment analysis. In *Proceedings of International Conference on Data Mining*, pp. 439–448, 2016.

Guang Shan, Tian Tang, Huijun Qian, and Yue Xia. Expression of tiam1 and rac1 proteins in renal cell carcinoma and its clinical-pathological features. *International Journal of Clinical and Experimental Pathology*, 10(11):11114–11121, 2017.

Vaishnavi Subramanian, Tanveer Syeda-Mahmood, and Minh N Do. Multimodal fusion using sparse cca for breast cancer survival prediction. In *Proceedings of IEEE 18th International Symposium on Biomedical Imaging (ISBI)*, pp. 1429–1432, 2021.

Mukund Sundararajan, Ankur Taly, and Qiqi Yan. Axiomatic attribution for deep networks. In *Proceedings of the 34th International Conference on Machine Learning*, volume 70, pp. 3319–3328, 2017.

Joshua B Tenenbaum and William T Freeman. Separating style and content with bilinear models. *Neural Computation*, 12(6):1247–1283, 2000.

Chunyu Wang, Junling Guo, Ning Zhao, Yang Liu, Xiaoyan Liu, Guojun Liu, and Maozu Guo. A cancer survival prediction method based on graph convolutional network. *IEEE Trans Nanobioscience*, 19(1):117–126, 2020.

Xiyue Wang, Sen Yang, Jun Zhang, Minghui Wang, Jing Zhang, Junzhou Huang, Wei Yang, and Xiao Han. Transpath: Transformer-based self-supervised learning for histopathological image classification. In *International Conference on Medical Image Computing and Computer-Assisted Intervention*, pp. 186–195. Springer, 2021a.

Zhiqin Wang, Ruiqing Li, Minghui Wang, and Ao Li. Gpdbn: deep bilinear network integrating both genomic data and pathological images for breast cancer prognosis prediction. *Bioinformatics*, 27(18):2963–2970, 2021b.

Martin Wöllmer, Felix Weninger, Tobias Knaup, Björn Schuller, Congkai Sun, Kenji Sagae, and Louis-Philippe Morency. Youtube movie reviews: Sentiment analysis in an audio-visual context. *IEEE Intelligent Systems*, 28(3):46–53, 2013.

Wing Hung Wong. Theory of partial likelihood. *The Annals of Statistics*, 14(1):88–123, 1986.

Ellery Wulczyn, David F Steiner, Zhaoyang Xu, Apaar Sadhwani, Hongwu Wang, Isabelle Flament-Auvigne, Craig H Mermel, Po-Hsuan Cameron Chen, Yun Liu, and Martin C Stumpe. Deep learning-based survival prediction for multiple cancer types using histopathology images. *Plos One*, 15(6):e0233678, 2020.

Chun-ming Yang, Shan Ji, Yan Li, Li-ye Fu, Tao Jiang, and Fan-dong Meng. B-catenin promotes cell proliferation, migration, and invasion but induces apoptosis in renal cell carcinoma. *OncoTargets and Therapy*, 10:711–724, 2017.

Zhou Yu, Jun Yu, Jianping Fan, and Dacheng Tao. Multi-modal factorized bilinear pooling with co-attention learning for visual question answering. In *IEEE International Conference on Computer Vision*, pp. 1839–1848, 2017.

Amir Zadeh, Rowan Zellers, Eli Pincus, and Louis-Philippe Morency. Multimodal sentiment intensity analysis in videos: Facial gestures and verbal messages. *IEEE Intelligent Systems*, pp. 82–88, 2016.

Amir Zadeh, Minghai Chen, Soujanya Poria, Erik Cambria, and Louis-Philippe Morency. Tensor fusion network for multimodal sentiment analysis. In *Proceedings of the 2017 Conference on Empirical Methods in Natural Language Processing*, pp. 1103–1114, 2017.

Shekoufeh Gorgi Zadeh and Matthias Schmid. Bias in cross-entropy-based training of deep survival networks. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 43(9):3126–3137, 2020.

Qiang Zhang, Xiujuan Yin, Zhiwei Pan, Yingying Cao, Shaojie Han, Guojun Gao, Zhiqin Gao, Zhifang Pan, and Weiguo Feng. Identification of potential diagnostic and prognostic biomarkers for prostate cancer. *Oncology Letters*, 18(4):4237–4245, 2019.

Table 4: **TCGA Data Feature Alignment Summary**

Cancer Type	WSI	CNV	MUT	RNA	WSI+CNV+MUT	WSI+MUT+RNA	ALL
BLCA	454	443	452	450	441	448	**437**
KIRC	517	509	357	514	352	355	**350**
KIRP	294	291	286	293	284	285	**284**
LUAD	528	522	523	522	519	519	**515**
LUSC	505	502	489	503	486	487	**484**
PAAD	208	201	187	195	187	180	**180**

A   DATA

Table 3 in Appendix A shows the number of patients with matched different data modalities: WSI (Whole slide image), CNV (Copy number), MUT (Muation), RNA (RNA-Seq gene expression). For each TCGA dataset and each patient we have preprocessed data dimensions $\mathbf{d}_g \in \mathbb{R}^{1 \times 2000}$ (RNA), $\mathbf{d}_c \in \mathbb{R}^{1 \times 227}$ (CNV + MUT), and $\mathbf{d}_p \in \mathbb{R}^{1 \times 32}$ (WSI) which will be used for our multimodal fusion.

B   METHODS

B.1   COX PROPORTIONAL HAZARD MODEL

In survival analysis, we are interested in modeling the continuous time T until some event of interest (i.e. survival time). The survival function $S(t) = \mathbb{P}(T > t_0) = 1 - \int_0^t f(s)ds$ is the probability of a individual surviving longer than time t_0, where f is the probability density function of survival times. We denote the probability that an event occurs in an infinitesimal interval after time t, given it has not yet occurred at time t as the hazard function $\lambda(t)$:

$$\lambda(t) = \lim_{\delta \to 0} \frac{\mathbb{P}(t \leq T < t + \delta \mid T \geq t)}{\delta} \tag{8}$$

This results in the relationship: $S(t) = exp - \lambda(t)$, where $\Lambda(t) = \int_0^t \lambda(s)ds$ is the cumulative hazard function. The most common semi-parametric approach for estimating the hazard function is the Cox proportion hazards model (Cox, 1972), which assumes that the hazard function can be parameterized as an linear exponential function $\lambda(t \mid X) = \lambda_0(t) \exp\left(\beta^\top X\right)$ where the baseline hazard function $\lambda_0(t)$ describes how the risk of an event changes over time, β are model parameters that describe how the hazard varies with features X. The baseline hazard $\lambda_0(t)$ is unspecified in the original model, making it difficult to estimate β, however, the Cox partial log-likelihood technique (Wong, 1986) can first estimate β by maximizing:

$$\mathcal{L}_n(\beta) = \frac{1}{n} \sum_{i=1}^n \Delta_i \left[\beta^\top X_i - \log\left(\sum_{j=1}^n Y_j\left(O_i\right) e^{\beta^\top X_j} \right) \right] \tag{9}$$

where n is the set of patients, for the i-th subject in the study, T_i and C_i denote, respectively, the event time and the potential censoring time; and $X_i \in \mathbb{R}^p$ denotes the observed features. Thus, the observed data from a typical survival study contain independent observations $\mathcal{D} = \{X_i, O_i, \Delta_i\}_{i=1}^n$, where the observed time $O_i = \min\left(T_i, C_i\right)$ and the event indicator $\Delta_i = 1$, if the observed time is T_i, i.e. $T_i \leq C_i$, otherwise $\Delta_i = 0$, the subject is censored at C_i. Once the parameter β has been estimated through the log partial likelihood, the cumulative baseline hazard function $\Lambda(t) = \int_0^t \lambda(s)ds$ can be estimated through the Breslow estimator (Breslow, 1972).

B.2   C-INDEX

Due to the presence of censoring in survival data, traditional performance measures such as mean squared error cannot be used to evaluate the accuracy of predictions. Instead, the concordance-index

(C-index) (Harrell et al., 1982) is one of the most widely used performance measures for survival models. It assesses how good a model is by measuring the concordance between the rankings of the predicted event times and the true event times. Specifically, if the predicted event time of the i-th individual is $\hat{T}_i$, the C-index is defined by $C = \mathbb{P}\left(\hat{T}_i < \hat{T}_j \mid O_i < O_j, \Delta_i = 1\right)$. However, it is difficult to obtain the predicted event time in most survival models, so the following C-index proposed in Antolini et al. (2005) is often used in practice:

$$C = \mathbb{P}\left(\hat{S}\left(O_i \mid X_i\right) < \hat{S}\left(O_i \mid X_j\right) \mid O_i < O_j, \Delta_i = 1\right) \tag{10}$$

If $\{X_i, O_i, \Delta_i\}_{i=1}^{n}$ and $\hat{S}(t \mid X_i)$ denote observations and predicted conditional probabilities, respectively, the C-index in Eq. (10) can be estimated empirically by

$$\hat{C} = \frac{\sum_{i=1}^{n}\sum_{j=1}^{n}\Delta_i I\left(\hat{S}\left(O_i \mid X_i\right) < \hat{S}\left(O_i \mid X_j\right)\right)}{\sum_{i=1}^{n}\sum_{j=1}^{n}\Delta_i I\left(O_i < O_j\right)}.$$

The range of the C-index is $[0, 1]$, and larger values indicate better performance with a random guess leading to a C-index of 0.5.

B.3 WSI REPRESENTATION LEARNING

It has been shown that the WSI visual representations extracted by self-supervised learning methods on histopathological images are more accurate and transferable than the supervised baseline models on domain-irrelevant datasets such as ImageNet. In this work, a pre-trained Vision Transformer (ViT) model (Wang et al., 2021a) that is trained on a large histopathological image dataset has been utilized for tile feature extraction. The model is composed of two main neural networks that learn from each other, i.e. student and teacher networks. Parameters of the teacher model θ_t is updated using the student network with parameter θ_s using update rule represented in Eq. (11).

$$\theta_t \leftarrow \tau\theta_t + (1 - \tau)\theta_s \tag{11}$$

Two different views of a given input H&E image x, uniformly selected from training set $\mathcal{I}$, are generated using random augmentations, i.e. u, v. Then, student and teacher models generate two different visual representations according to u and v as $y_1 = f^{\theta_s}(u)$ and $\hat{y}_2 = f^{\theta_t}(v)$, respectively. Finally, the generated visual representations are transformed into latent space using linear projection as $p_1 = g^{\theta_s}\left(g^{\theta_s}(y_1)\right)$ and $\hat{z}_2 = g^{\theta_t}(\hat{y}_2)$ for student and teacher networks, respectively. Similarly, feeding v and u to student and teacher networks leads to $y_2 = f^{\theta_s}(v)$, $\hat{y}_1 = f^{\theta_t}(u)$, $p_2 = g^{\theta_s}\left(g^{\theta_s}(y_2)\right)$ and $\hat{z}_1 = g^{\theta_t}(\hat{y}_1)$. Finally, the symmetric objective function L_{loss} is optimized through minimizing the $\ell_2 - $ norm distance between student and teacher as Eq. (12)

$$L_{loss} = \frac{1}{2}L\left(p_1, \hat{z}_2\right) + \frac{1}{2}L\left(p_2, \hat{z}_1\right) \tag{12}$$

where $L(p, z) = -\frac{p}{\|p\|_2} \cdot \frac{z}{\|z\|_2}$ and $\|\cdot\|_2$ represents $\ell_2 - $ norm.

B.4 AGGREGATE PATCH LEVEL FEATURE INTO SLIDE LEVEL FEATURE

Survival outcome information is available at the patient-level instead of for individual slides, we use the attention based strategy in Porpoise (Chen et al., 2022b) which was originally designed in CLAM (Lu et al., 2021) to aggregate the patch level feature into slide level representation for our model training. We treat all WSIs corresponding to a patient case as a single WSI bag during training and evaluation. If a patient has N WSIs with bag sizes $M_1, \cdots, M_N$ respectively, the WSI bag corresponding the patient is formed by concatenating all N bags, and has dimensions $M \times 2048$, where $M = \sum_{i=1}^{N} M_i$.

There are three components for the model: 1) the projection layer f_p; 2) the attention module f_{attn}; 3) the prediction layer f_{pred}. After the VIT feature extraction, each patch-level embeddings of WSI bag, $\mathbf{H} \in \mathbb{R}^{M \times 2048}$, are first mapped into a more compact, dataset-specific 512-dimensional feature

space by the fully-connected layer f_p with weights $\mathbf{W}_{\text{proj}} \in \mathbb{R}^{512 \times 2048}$ and bias $\mathbf{b}_{\text{bias}} \in \mathbb{R}^{512}$. Subsequently, the attention module f_{attn} learns to score each patch for its perceived relevance to patient-level prognostic prediction. Patches receives high attention scores will contribute more to the patient-level feature representation than patches assigned low attention scores, all the patches in one patient's WSIs are aggregated based on attention-pooling (Ilse et al., 2018). Specifically, f_{attn} has 3 fully-connected layers with weights $\mathbf{U}_a \in \mathbb{R}^{256 \times 512}$, $\mathbf{V}_a \in \mathbb{R}^{256 \times 512}$ and $\mathbf{W}_a \in \mathbb{R}^{1 \times 256}$. Given a patch embedding $\mathbf{h}_m \in \mathbb{R}^{512}$ (the m^{th} row entry of $\mathbf{H}$), its attention score a_m can be computed by:

$$a_m = \frac{\exp\left\{\mathbf{W}_a \left(\tanh\left(\mathbf{V}_a \mathbf{h}_m^\top\right) \odot \operatorname{sigm}\left(\mathbf{U}_a \mathbf{h}_m^\top\right)\right)\right\}}{\sum_{m=1}^{M} \exp\left\{\mathbf{W}_a \left(\tanh\left(\mathbf{V}_a \mathbf{h}_m^\top\right) \odot \operatorname{sigm}\left(\mathbf{U}_a \mathbf{h}_m^\top\right)\right)\right\}}$$

Then the patient-level representations $\mathbf{h}_{\text{patient}} \in \mathbb{R}^{512}$ are computed based on the attention-pooling operation from the patch-level feature representations by attention scores as weight coefficients, where $\mathbf{A} \in \mathbb{R}^M$ is the vector of attention scores:

$$\mathbf{h}_{\text{patient}} = \mathbf{Attn} - \mathbf{pool}(\mathbf{A}, \mathbf{H}) = \sum_{m=1}^{M} a_m \mathbf{h}_m$$

The last fully-connected layer is used to learn a representation $\mathbf{h}_{\text{WSI}} \in \mathbb{R}^{1 \times 32}$, which is then used as input to our multimodal fusion.

B.5 SPARSE NETWORK FEATURE INTERPRETATION

We use the Integrated Gradients attribution algorithm to rank the features in all layers. Inspired by PNET (Elmarakeby et al., 2021), to reduce the bias introduced by over-annotation of certain nodes (nodes that are member of too many pathways), we adjusted the Integrated Gradients scores using a graph informed function f that considers the connectivity of each node. The importance score of each node i, C_i^l is divided by the node degree d_i^l if the node degree is larger than the mean of node degrees plus 5σ where σ is the standard deviation of node degrees.

$$d_i^l = fan - in_i^l + fan - out_i^l$$

adjusted $C_i^l = f(x) = \begin{cases} \frac{C_i^l}{d_i^l}, & d_i^l > \mu + 5\sigma \\ C_i^l, & \text{otherwise} \end{cases}$

B.6 CO-ATTENTION BASED PATHWAY VISUALIZATION

After we get the ranking of top genes and pathways, we adopted the co-attention survival model (MCAT) (Chen et al., 2021) to show the spatial visualization of genomic features. MACT learns how WSI patches attend to genes when predicting patient survival. We define each WSI patch representation and pathway genomic features as H_{bag} and G_{bag}. The model uses $G_{bag} \in \mathbb{R}^{N \times d_g}$ to guide the feature aggregation of $H_{bag} \in \mathbb{R}^{N \times d_p}$ into a clustered set of gene-guided visual concepts $\widehat{H}_{\text{bag}} \in \mathbb{R}^{N \times d_p}$, d_g and d_p represents the dimension for the pathway (number of genes involved in the pathway) and patch. Through the following mapping:

$$\operatorname{CoAttn}_{G \rightarrow H}(G, H) = \operatorname{softmax}\left(\frac{QK^\top}{\sqrt{d_p}}\right)$$

$$= \operatorname{softmax}\left(\frac{\mathbf{W}_q G H^\top \mathbf{W}_s^\top}{\sqrt{d_p}}\right) \mathbf{W}_v H \rightarrow A_{\text{coattn}} \mathbf{W}_v H \rightarrow \widehat{H}$$

where $\mathbf{W}_q, \mathbf{W}_s, \mathbf{W}_v \in \mathbb{R}^{d_p \times d_p}$ are trainable weight matrices multiplied to the queries G_{bag} and key-value pair ($H_{\text{bag}}, H_{\text{bag}}$), and $A_{\text{coattn}} \in \mathbb{R}^{N \times M}$ is the co-attention matrix for computing the weighted average of H_{bag}. Here, M represents the number of patches in one slide and N represents number of pathways (We trained top five pathways, so $N = 5$ in our study).

Interpretation: For a single genomic pathway embedding $\mathbf{g}_n \in G$, the co-attention module scores the pairwise similarity for how much $\mathbf{h}_m$ attends to $\mathbf{g}_n$ for all $\mathbf{h}_m \in H_{\text{bag}}$, written as a row vector

$[a_{n1}, a_{n2}, \ldots, a_{nm}] \in A_{\text{coattn.}}$. These attention weights are then applied element-wise to H_{bag}, which constructs a new WSI-level feature embedding $\widehat{\mathbf{h}}_n \in \mathbb{R}^{n \times 1}$ that reflects the biological function of $\mathbf{g}_n$. For example, if g_n is a genomic embedding that expresses the underlying biological pathways responsible for tumor formation, A_{coattn} computed by the co-attention layer would saliently localize image patches containing tumor cells as high attention, which then aggregates $\widehat{\mathbf{h}}_n$ as a WSI-level representation primarily containing tumor cells. We describe the set of high attention image patches that attend to a single genomic embedding $\mathbf{g}_n$ as a "gene-guided visual concept", in which patches that are similar in feature space to $\mathbf{g}_n$ would share similar phenotypic information. For N pathway embeddings in G_{bag}, the co-attention module captures up to N different pathway-guided visual concepts, which we visualizes as attention heatmap in Fig. 3 b.

C EXPERIMENTS

C.1 NETWORK ARCHITECTURE

Sparse network for gene expression: We have one gene layer followed by three pathway layers, and one hidden layer. The architecture was built using the Reactome pathway datasets (Fabregat et al., 2020). The whole Reactome dataset was downloaded and processed to form a layered network of one layer of genes, three layers of pathway and biological processes, and one hidden layer. The first layer of PONET is connected to the next layer via a set of one-to-one connections, and each node in the next layer is connected to exactly one node of the input layer representing RNA-Seq expression. The connections are encoded by a mask matrix $\mathbf{M}$ that is multiplied by the weights matrix $\mathbf{W}$ to zero-out all the connections that do not exist in the Reactome pathway dataset. For the next layers, a similar scheme is devised to control the connection between consecutive layers to reflect the real parent–child relationships that exist in the Reactome dataset. The output of each layer is calculated as

$$y = f[(\mathbf{M} * \mathbf{W})^T \mathbf{X} + \epsilon] \tag{13}$$

where f is the activation function, $\mathbf{M}$ is the mask matrix, $\mathbf{W}$ is the weights matrix, $\mathbf{X}$ is the input matrix, ϵ is the bias vector, and $*$ is the Hadamard product. We use tanh for the activation of each node. The final gene expression embedding is $\mathbf{h}_{\text{g}} \in \mathbb{R}^{1 \times 50}$.

Pathology network: The slide level image feature representation is passed through an image embedding layer and encodes the embedding as $\mathbf{h}_{\text{p}} \in \mathbb{R}^{1 \times 50}$.

CNV + MUT network: Similarly as the pathology network, the patient level CNV + MUT feature representation is passed through an FC embedding layer and encodes the embedding as $\mathbf{h}_{\text{c}} \in \mathbb{R}^{1 \times 50}$.

C.2 EXPERIMENTAL DETAILS

PONET. The latent dimensionality of the factorized matrices k is a very important tuning parameter. We tune $k = [3, 5, 10, 20, 30, 50]$ based on the testing C-index value (Appendix Fig. 4) and the loss of training and testing plot (Appendix Fig. 5) for each dataset. We choose k to maximize the C-index value and also it should have stable convergence in both training and testing loss. For example, we choose $k = 10$ in TCGA-KIRP for the optimized results. We can see that in Appendix Fig. 4 the testing loss is quite volatile when k is less than 10. Similarly, we choose $k = [20, 10, 20, 20, 10]$ for TCGA-BLCA, TCGA-KIRC, TCGA-LUAD, TCGA-LUSC, TCGA-PAAD, respectively.

The learning rate and the regularization hyperparameter λ for the Cox partial likelihood loss are also tunable parameters. The model is trained with Adam optimizer. For each training/testing pair, we first empirically preset the learning rate to 1.2e-4 as a starting point for a grid search during training, the optimal learning rate is determined through the 5-fold cross-validation on the training set, C-index was used for the performance metric. After that, the model is trained on all the training set and evaluated on the testing set. We use 2e-3 through the experiments for λ. The batch size is set to 16, and epoch is 100. During the training process, we carefully observe the training and testing loss for convergence (Figure 4 in Appendix C.2). The server used for experiments is NVIDIA GeForce RTX 2080Ti GPU.

CoxPH. We only include the age and gender for the survival prediction. Using CoxPHFitter from lifelines [4].

---

[4]https://github.com/CamDavidsonPilon/lifelines

Figure 4: C-Index value under K = 3, 5, 10, 20, 30, 50 for TCGA-KIRP. The mean value and standard deviation for 5-fold cross-validation are plotted.

DeepSurv [5]. We concatenate preprocessed pathological images features, gene expression, and copy number + mutant data in a vector to train the DeepSurv model. L2 reg = 10.0, dropout = 0.4, hidden layers sizes = [25, 25], learning rate = 1e-05, lr decay = 0.001, momentum = 0.9.

Pathomic Fusion [6]. We use the pathomicSurv model which takes our preprocessed image feature, gene expression and copy number + mutation as model input. $k = 20$, Learning rate is 2e-3, weight decay is 4e-4. Batch size is 16 and epoch is 100. Drop out rate is 0.25.

GPDBN [7]. Learning rate is 2e-3, batch size is 16, weight decay is 1e-6, dropout rate is 0.3, epoch is 100.

HFBSurv [8]. The learning rate is set to 1e-3, batch size is 16, λ = 3e-3, weight decay is 1e-6, epoch is 100.

---

[5]https://github.com/czifan/DeepSurv.pytorch

[6]https://github.com/mahmoodlab/PathomicFusion

[7]https://github.com/isfj/GPDBN

[8]https://github.com/Liruiqing-ustc/HFBSurv

Figure 5: Train and test loss for TCGA-KIRP under K = 3, 5, 10, 20, 50 for 5-fold cross-validation.

C.3 ADDITIONAL RESULTS

Figure 6: Inspecting and interpreting PONET on TCGA-BLCA. Sankey diagram visualization of inner layers of PONET shows the estimated relative importance of different nodes in each layer. Nodes in the first layer represent genes; the next layers represent pathways; and the final layer represents the model outcome. Different layers are linked by weights. Nodes with darker colours are more important, while transparent nodes represent the residual importance of undisplayed nodes in each layer.

Figure 7: Co-attention visualization of top 4 ranked pathways in two cases of TCGA-BLCA.

Figure 8: Inspecting and interpreting PONET on TCGA-KIRC. Sankey diagram visualization of inner layers of PONET shows the estimated relative importance of different nodes in each layer. Nodes in the first layer represent genes; the next layers represent pathways; and the final layer represents the model outcome. Different layers are linked by weights. Nodes with darker colours are more important, while transparent nodes represent the residual importance of undisplayed nodes in each layer.

Figure 9: Co-attention visualization of top 4 ranked pathways in two cases of TCGA-KIRC.

Figure 10: Inspecting and interpreting PONET on TCGA-LUAD. Sankey diagram visualization of inner layers of PONET shows the estimated relative importance of different nodes in each layer. Nodes in the first layer represent genes; the next layers represent pathways; and the final layer represents the model outcome. Different layers are linked by weights. Nodes with darker colours are more important, while transparent nodes represent the residual importance of undisplayed nodes in each layer.

Figure 11: Co-attention visualization of top 4 ranked pathways in two cases of TCGA-LUAD.

Figure 12: Inspecting and interpreting PONET on TCGA-LUSC. Sankey diagram visualization of inner layers of PONET shows the estimated relative importance of different nodes in each layer. Nodes in the first layer represent genes; the next layers represent pathways; and the final layer represents the model outcome. Different layers are linked by weights. Nodes with darker colours are more important, while transparent nodes represent the residual importance of undisplayed nodes in each layer.

Figure 13: Co-attention visualization of top 4 ranked pathways in two cases of TCGA-LUSC.

Figure 14: Inspecting and interpreting PONET on TCGA-PAAD. Sankey diagram visualization of inner layers of PONET shows the estimated relative importance of different nodes in each layer. Nodes in the first layer represent genes; the next layers represent pathways; and the final layer represents the model outcome. Different layers are linked by weights. Nodes with darker colours are more important, while transparent nodes represent the residual importance of undisplayed nodes in each layer.

Figure 15: Co-attention visualization of top 4 ranked pathways in two cases of TCGA-PAAD.