CONTINUAL LEARNING BASED ON SUB-NETWORKS AND TASK SIMILARITY

ABSTRACT

Continual learning (CL) has two main objectives: preventing *catastrophic forgetting* (CF) and encouraging *knowledge transfer* (KT) across tasks. The existing literature mainly tries to overcome CF. Although some papers have focused on both CF and KT, they may still suffer from CF because of their ineffective handling of previous tasks and/or poor task similarity detection mechanisms to achieve KT. This work presents a new CL method that addresses the above issues. First, it overcomes CF by isolating the knowledge of each task via a learned mask that indicates a sub-network. Second, it proposes a novel technique to compute how important each mask is to the new task, which indicates how the new task is similar to an underlying old task. Similar tasks can share the same mask/sub-network for KT, while dissimilar tasks use different masks/sub-networks for CF prevention. Comprehensive experiments have been conducted using a range of NLP problems, including classification, generation, and extraction to show that the proposed method consistently outperforms prior state-of-the-art baselines. [1]

1 INTRODUCTION

This paper studies continual learning (CL) of a sequence of natural language processing (NLP) tasks in the task continual learning (Task-CL) setting. It deals with both *catastrophic forgetting* (CF) and *knowledge transfer* (KT) across tasks. CF refers to the phenomenon that the current task learning may cause the performance degradation for previous tasks due to parameter updates (McCloskey & Cohen, 1989). In Task-CL, the task ID is provided for each test case in testing. In learning, after a task is learned, its data is no longer accessible. Another CL setting is class continual learning (Class-CL), which provides no task ID in testing and it solves a different type of problems.

Existing research in CL has almost exclusively focused on overcoming CF (Kirkpatrick et al., 2016; Serrà et al., 2018; Wortsman et al., 2020). Limited work has being done on KT except (Ke et al., 2020; 2021; Wang et al., 2022). But KT is particularly important for NLP because many tasks in NLP share similar knowledge that can be leveraged to achieve better accuracy. We humans are also particularly good at leveraging prior knowledge to help learn new skills. To achieve KT in learning a new task, CAT (Ke et al., 2020) first detects previous tasks that are similar to the current task so that the current task learning can leverage the knowledge learned from the similar past tasks. CAT uses the hard-attention mechanism in HAT (Serrà et al., 2018) to deal with CF, which masks out those important neurons for each task so that the training of new tasks cannot change them in back-propagation. However, different tasks can share neurons. This approach has a major problem for KT that is very hard, if not impossible, to solve. After the similar previous tasks are detected, CAT opens the masks of these tasks so that the new task learning can modify their parameters to achieve both forward and backward KT. This clearly helps KT. But this can cause CF for dissimilar tasks that share parameters with those similar tasks. CAT's task similarity comparison method based on the transfer learning performance can be quite inaccurate too. The KT methods in (Ke et al., 2021; Wang et al., 2022) are based on instance-level feature similarity comparison using dot product or cosine, which can be inaccurate as well (see experiment results in Sec. 4.3).

To deal with these issues, we would like to have (1) a learning method that can isolate the knowledge of each task without parameter overlapping among tasks to deal with harmful interference in KT and

---

[1]The code has been uploaded as supplementary materials.

(2) a task similarity detection method that is directly related to the loss of previous tasks (even though we do not have their data) for more accurate similar task detection.

For (1), we draw inspiration from the sub-network masking idea in (Wortsman et al., 2020), where the underlying backbone network is fixed but a binary mask is learned to find a sub-network for each task, which encodes the model for the task. The mask is basically a set of binary gates that indicates which parameters in the backbone network should be used for a task model. Thus, different task models have no interference to cause CF although sub-networks of multiple tasks can share neurons and parameters because the underlying backbone network is fixed and shared by all tasks.

For (2), we propose to determine whether a previous task k is similar to the current task t by assessing the importance of the mask (which represents the model or sub-network of a task) for the previous task k to the current task t. To compute the importance score, we make use of an effective idea from the network pruning community (Michel et al., 2019). In Michel et al. (2019), the gradient on each parameter is serving as the importance of the parameter. The less important parameters (determined by a threshold) are regarded as unimportant and removed to reduce the network size. However, it is not obvious how we can compute the importance of each mask with its sub-network to the current task and how to determine whether the current task is similar enough to a previous task based on the importance so that they can perform KT. This paper proposes a novel method to perform the above two functions. A set of virtual gate variables are introduced to represent the mask/sub-network so that we can compute the gradient of each mask/sub-network. The gradient, based on the current task data and directly related to current task loss, serves as the importance of the mask/sub-network to the current task. The more important a mask/sub-network is, it is more likely that the previous task that has used the mask is similar to the current task. To mitigate the possible forgetting, a novel importance comparison mechanism is also proposed to take the previous task gradient into account.

Based on the proposed idea, a new Task-CL method, called **TST** (**T**ask-continual learning based on **S**ub-networks and **T**ask similarity), is proposed. TST is evaluated using datasets for classification, generation, and extraction. The datasets also include similar tasks and dissimilar tasks. The results demonstrate the high effectiveness of TST.

In summary, this paper makes two key contributions.

1. It proposes a new Task-CL method TST based on sub-networks and task similarity. TST not only overcomes CF but also enables effective KT. For KT, it learns the current task in the sub-network of a previous task without interference with any other tasks and thus will not cause any CF for the other tasks. This cannot be achieved by other existing methods.

2. It proposes a novel task similarity detection method based on gradients computed on masks. This method is simple and yet highly effective. It is instrumental for effective KT.

2 RELATED WORK

Continual learning. Existing CL work mainly focused on overcoming CF: (1) *Regularization-based approaches* (Kirkpatrick et al., 2016; Lee et al.; Seff et al., 2017; Zenke et al., 2017; Rusu et al., 2016) add a regularization in the loss to penalize changes to parameters that are important to previous tasks. A related approach is *gradient projection* (Zeng et al., 2019), which ensures the gradient updates occur only in the orthogonal direction to the input of old tasks. (2) *Parameter isolation-based approaches,* such as those in (Serrà et al., 2018; Ke et al., 2020; Mallya & Lazebnik, 2018; Fernando et al., 2017; Wortsman et al., 2020), learn a dedicated sub-network for each task and masks it out in learning new tasks. (3) *Replay-based approaches*, such as those in (Rebuffi et al., 2017; Lopez-Paz & Ranzato, 2017; Chaudhry et al., 2019; Wang et al., 2020), retain some training data of old tasks and use them in learning a new task. The methods in (Shin et al., 2017; Kamra et al., 2017; Rostami et al., 2019; He & Jaeger, 2018) learn data generators and generate old task data for learning a new task. These are clearly very different from our method as we don't use any replay data.

Continual learning in NLP. Above existing approaches usually do not use a pre-trained model. However, in NLP, almost all recent CL (or non-CL) techniques use pre-trained language models (LMs). We categorize them into 3 types based on which part in the pre-trained LM is trainable. The first one below belongs to replay or regularization families and last two types belong to parameter-isolation. (1). *Transformer-updating based* - this family updates the Transformer directly. IDBR (Huang et al., 2021) disentangles task-shared and task-specific knowledge in BERT via regularizations, which can

only work on classification problems. LAMOL (Sun et al., 2020) is a replay method based on GPT-2. It generates previous task samples before learning the new task. (2). *Prompt-based* - a prompt (Lester et al., 2021) is an added structure to the input layer.[2] C-PT (Zhu et al., 2022) learns a separate prompt for each task. L2P (Wang et al., 2022) learns a prompt pool for all tasks, preventing CF by only choosing the matched prompt and allowing transfer by sharing the same prompt pool. (3). *Adapter-based* - an adapter (Houlsby et al., 2019) is an added structure in each layer of the Transformer. In learning, the Transformer is fixed and only adapters are trainable. AdapterCL (Madotto et al., 2020) trains a separate adapter for each task. It thus has no CF or KT. CTR (Ke et al., 2021) trains a shared adapter for all tasks. It prevents CF via task masks (Serrà et al., 2018) and achieves KT via capsule networks (Sabour et al., 2017). Our method TST also belongs to this family but TST updates the mask instead of the adapter. It needs no replay samples or regularization and can effectively detect the task similarity based on the mask importance. We have discussed the advantages of TST in Sec. 1.

Network pruning as importance computation. It is known that many parameters in a neural network are redundant and can be pruned (Li et al., 2021; Lai et al., 2021). This has also been shown for pre-trained Transformer (Chen et al., 2020; Lin et al., 2020; Gao et al., 2021; Michel et al., 2019; Voita et al., 2019). One method is to discard the parameters with small absolute values (Han et al., 2015; Guo et al., 2016). Other methods prune at higher levels. In a Transformer-based model, these include pruning the attention head (Michel et al., 2019; Voita et al., 2019; McCarley et al., 2019) and pruning sub-layers in a standard Transformer layer (Fan et al., 2020; Sajjad et al., 2020). However, the above methods are not directly applicable to us as we need to compute the importance of mask to detect task similarity, while the above approaches are all for the importance of network parameters.

3 PROPOSED TST TECHNIQUE

TST is designed for both CF prevention and KT (knowledge transfer). This is achieved by selecting a mask from a shared mask pool based on the task similarity. In learning each new task, the system first computes the importance of each mask in the pool to the new task based on the gradient of a virtual gate variable representing the mask (Sec. 3.2). Based on the mask importance, if the mask of a previous task is likely to improve both the previous task and the current task, the mask and its underlying sub-network will be used to train the current new task for KT (Sec. 3.3). If such a mask is not found, the unused mask in the pool will be trained to find a new sub-network for the task so that it will not cause CF for any previous task. The whole process is illustrated in Figure 1.

3.1 SUB-NETWORK MASKING AND MASK POOL

Most of existing methods focus on forgetting/CF prevention and thus cannot meet our goal. The few methods that also do KT are based on the parameter-isolation method HAT, which, as we discussed in the introduction section, *cannot* completely isolates the parameters for different tasks. The shared parameters still cause forgetting when updating the sub-networks for similar tasks. This work borrows the idea of *sub-network masking* from (Wortsman et al., 2020), which trains a mask to isolate a sub-network for a task with the network parameters fixed. Thus, different tasks have no interference to cause CF. We start with a *mask pool* of K randomly initialized masks $\{\boldsymbol{M}^{(k)}\}_{k=1}^{K}$ (K is a hyper-parameter). To learn a task, a mask is selected from the pool and trained. Each mask $\boldsymbol{M}^{(k)}$ is of the same size as the weight or parameter set ($\boldsymbol{W}$) of the inserted adapter (Houlsby et al., 2019)[3]. During the training of a task, the Transformer and adapters are fixed, only the mask for the task is trained. To ensure the mask has a binary output and differentiable, we leverage the "straight-through" trick. We refer readers to the papers (Ramanujan et al., 2020; Wortsman et al., 2020) for the details of training the mask that can indicate a sub-network and the method that saves the mask efficiently. In short, a mask indicates a sub-network by element-wise multiplying with the adapter weight,

$$\boldsymbol{o}^{(k)} = f(\boldsymbol{x}, \boldsymbol{W} \otimes \boldsymbol{M}^{(k)}), \tag{1}$$

where $\otimes$ is element-wise multiplication, f refers to the adapter. $\boldsymbol{W}$ is fixed and shared by all tasks. Only $\boldsymbol{M}^{(k)}$ is trainable. $\boldsymbol{W} \otimes \boldsymbol{M}^{(k)}$ represents a sub-network and can be indicated by mask $\boldsymbol{M}^{(k)}$.

---

[2]The prompts used in CL are all randomly initialized, a.k.a, soft prompt. This is different from "hard prompt", where the prompt needs to be manually designed (Brown et al., 2020).

[3]One can also mask the whole Transformer. In our preliminary experiments, this and masking only the adapter give similar results. We choose to mask the adapter as it has a smaller mask size and thus more efficient.

Figure 1: Illustration of TST (from left to right). There are K masks in the mask pool, where each mask is of the same size as the adapter weight and randomly initialized before learning. When a new task t comes, TST first multiplies each mask with an virtual gate variable (with value of 1). The resulting gated masks are then combined via summation to produce the combined mask for importance computation (Eq. 2). **(A)** shows the mask importance computation (Sec. 3.2). We mask the adapter using the combined mask M^{impt} and compute the gradient of each virtual gate variable via cross-entropy loss ($\mathcal{L}^{\text{CE}}$). The normalized magnitude of the resulting gradient serves as the importance of each mask to the current task t (Eqs. 4 and 5). **(B)** shows the mask selection (Sec. 3.3). We take the mask with the highest importance as candidate mask a and select a mask using the saved importance of the previous task that used the mask. Only the mask of higher importance for the current task data is selected. Otherwise, we select an unused mask u. (Eqs. 6 and 7) **(C)** shows the mask training (Sec. 3.4). Using the selected mask q, we can mask the adapter and train the mask with cross-entropy. As a result, we share the same mask for similar tasks and isolate the mask from dissimilar tasks, achieving both forgetting prevention and knowledge transfer (KT).

3.2 COMPUTING MASK IMPORTANCE

Since the network weights are always fixed, a simple way to perform CL is to use a different mask for each task so that the resulting sub-networks for different tasks will not affect each other. This gives us a chance to safely update the masks of sub-networks of similar tasks without affecting any other tasks. However, this cannot achieve KT (knowledge transfer), which is a main goal of this paper. Thus, before learning a new task, we propose to select a mask for KT based on task similarity, where each task may use the same mask as a previous task (for KT) or a unused mask in the pool. The intuition is that if two tasks are similar, they can share the *same* mask from the pool to encourage knowledge transfer; otherwise, the new task should select a unused mask to avoid forgetting. We present how to compute the task similarity next.

Gate variables. Intuitively, if a mask is important for two different tasks, the two tasks are similar. This motivates us to compute the importance of each mask in the pool to the current task based on its data. To this end, we introduce a set of *gate variables*, $\{g^{(k)}\}_{k=1}^{K}$, where each variable corresponds to a mask in the pool. The variable serves as a proxy for computing the gradient on each mask, which is used to compute the importance of the mask to the current task. We first define the virtual network of masks for our importance computation (see Figure 1(A)),

$$M^{\text{impt}} = \sum_{k=1}^{K} (g^{(k)} * M^{(k)}), \qquad (2)$$

where $g^{(k)}$ is a scalar-valued gate variable and $M^{(k)}$ is a mask. Eq. 2 basically combines all masks ($g^{(k)} * M^{(k)}$) so that we can compute the gradient on each gate variable based on the current task

data. The resulting combined mask, $\boldsymbol{M}^{\text{impt}}$, is then used to mask the adapter, similar to Eq. 1

$$o^{\text{impt}} = f(\boldsymbol{x}, \boldsymbol{W} \otimes \boldsymbol{M}^{\text{impt}}), \quad (3)$$

o^{impt} can be used to compute the loss based on the current task data and the gradient on each gate variable $g^{(k)}$ gives us the importance of the corresponding mask $\boldsymbol{M}^{(k)}$.

Mask importance based on the gradients of gate variables. To compute the mask importance, we borrow the idea from neural network punning (Michel et al., 2019). Given the data from the current task t, $D_t = \{(\boldsymbol{x}_t^n, \boldsymbol{y}_t^n)\}_{n=1}^N$, the importance of a mask is estimated with a gradient-based score.

$$I_t^{(k)} = \frac{1}{N} \sum_{n=1}^N |\nabla_{g^{(k)}}|, \quad (4)$$

where $\nabla_{g^{(k)}}$ is the gradient on the gate variable $g^{(k)}$,

$$\nabla_{g^{(k)}} = \frac{\partial \mathcal{L}^{\text{impt}}(\boldsymbol{x}_t^n, \boldsymbol{y}_t^n)}{\partial_{g^{(k)}}}, \quad (5)$$

where $\mathcal{L}^{\text{impt}}$ (*impt* stands for *importance*) is a problem-specific loss function. Note that each gate variable $g^{(k)}$ is initialized to 1, and is not changed. This is because we only need its gradient to compute the importance of a mask and will not use the gradient to update the gate variable.

$\mathcal{L}^{\text{impt}}$ **for mask importance.** Eq. 4 offers a way to compute the mask importance w.r.t. a given loss $\mathcal{L}^{\text{impt}}$. A nature idea is to use the cross-entropy loss [4], $\mathcal{L}^{\text{CE}}$, as $\mathcal{L}^{\text{impt}}$. By doing so, we can easily get the importance scores of all masks in the mask pool to the current task [5]. Note that the resulting importance score $I_t^{(k)}$ is saved for each task.

3.3 SELECTING A MASK TO LEARN TASK t BASED ON MASK IMPORTANCE

Recall that the goal of computing mask importance is to find the task similarity and select a mask for the current task based on it. To achieve this, we propose a 2-step mechanism:

(1) Find the mask with highest importance as the candidate for knowledge transfer. We leverage the importance scores computed using the data of the current task t, $\{I_t^{(k)}\}_{k=1}^K$. Intuitively, the highest score indicates the most useful sub-network for task t. If this sub-network has been used by a previous task, it indicates the previous task's sub-network is helpful to task t and the two tasks are very likely to be similar. Formally, in learning task t, we first get the highest importance to task t,

$$I_t^{(a)} = \max(\{I_t^{(1)} ... I_t^{(K)}\}). \quad (6)$$

where a is the ID of the most useful/important mask (sub-network) to the current task t. The previous task that has used $\boldsymbol{M}^{(a)}$, denoted as task s [6], is then the candidate similar previous task to task t.

(2) Select a mask for task t. We cannot simply say that the previous task s is similar to current task t. We want to ensure that the update of the mask for s by t will not cause forgetting for s, and can result in improvement for both. Eq. 6 is only about whether a previous used sub-network $\boldsymbol{M}^{(a)}$ can help task t, it does not consider whether the updating of the $\boldsymbol{M}^{(a)}$ by t will cause forgetting for s. Therefore, we need one more step to be confident that forgetting is unlikely to occur due to the updating of $\boldsymbol{M}^{(a)}$ by t's data. Since task s's data is no longer accessible, we propose to use the saved importance score ($I_s^{(a)}$) computed using s's data for mask a to achieve the goal [7]. This is because

---

[4]Different problems in our experiments (generation, classification and extraction) all use cross-entropy loss.

[5]To facilitate the importance comparison, the importance scores for each mask k is normalized so that the importance scores for all masks have a mean of 0 and standard deviation of 1. To simplify the notation, we use the same $I_t^{(k)}$ to represent the normalized importance of mask $\boldsymbol{M}^{(k)}$ computed from current task t.

[6]If multiple tasks have selected mask a, we use the task with the highest importance as task s. We realize the mask has been updated if it is shared by multiple tasks and the importance needs to be updated as well, which we do not do. Our current simple approach works well in our experiments. We leave the issue to our future work.

[7]$I_s^{(a)}$ is computed and saved *after* training task s (to ease the notation, we still use the same $I_s^{(a)}$). This is to ensure that $I_s^{(a)}$ is computed based on the *trained* mask and is comparable to $I_t^{(a)}$.

$I_s^{(a)}$ is computed from the previous task s's data when we were in task s and is directly related to the previous task loss. For mask a, we now have two importance scores; $I_t^{(a)}$ computed from the current task t and $I_s^{(a)}$ computed from the previous task s which learned the mask a. We then compare their values and select the mask via,

$$q = \begin{cases} a, & I_t^{(a)} > I_s^{(a)} \\ u, & otherwise, \end{cases} \tag{7}$$

where u refers to any mask in the pool that has not been selected and used by a previous task. The above inequality can tell us whether the updating of the mask a by the current task is likely to help the previous task s. The rationale for Eq. 7 is that $I_s^{(a)}$ refers to the normalized magnitude of the gradient that can decrease the previous task loss most. Based on the concept of gradient-based importance in (Michel et al., 2019), since mask a is more important to the current task t than to the previous task s, the current task can potentially improve task s and vice versa to achieve KT. It is thus reasonable to use the mask a (and its associated sub-network) to also learn the current task t. If mask a is not as important to the current task t as to the previous task s, the current task data is unlikely to help the previous task s and vice versa, and a unused mask in the pool should be used to learn t to avoid CF on any previous task. Our empirical results show that Eq. 7 works well.

3.4 TRAINING THE SELECTED SUB-NETWORK

Using the selected mask $\boldsymbol{M}^{(q)}$ for the current task, we can train the task by plugging $\boldsymbol{M}^{(q)}$ in Eq. 1 with the cross-entropy loss $\mathcal{L}^{\text{CE}}$.

4 EXPERIMENTS

We now evaluate the proposed system TST. We first learn all tasks sequentially. After that, their task models are tested using their respective test sets. TST does not use any replay data.

4.1 DATASETS AND BASELINES

Datasets: We use the five datasets covering a wide range of NLP problems, including classification, generation, and extraction (token-level classification). We introduce each of them bellow. For detailed datasets statistics, please see Appendix A.

(1). ASC (*Aspect Sentiment Classification*). This dataset is from (Ke et al., 2021) and has 19 tasks. Each task classifies the opinion (*positive*, *negative*, or *neutral*) in a review sentence at the aspect-level of a product or service. For example, "*The picture is good but the sound is poor*" about a TV expresses a *positive* opinion about the aspect "picture" and a *negative* opinion about the aspect "sound."

(2). CCD (*Continual Classification Dataset*). This is a text classification dataset (de Masson d'Autume et al., 2019) that is popular in continual learning for NLP. It contains 5 tasks include AGNews (news classification), Yelp (sentiment analysis), Amazon (sentiment analysis), DBpedia (Wikipedia article classification) and Yahoo (questions and answers categorization). [8]

(3). SUM (*ConvoSum*). This is a conversational abstractive summarization dataset with 6 tasks or domains (Fabbri et al., 2021). Given conversation from a domain, the system generates its summary.

(4). DRG (*Dialogue Response Generation*). This is a popular task-oriented dialogue response dataset (Multi-WoZ2.0) (Ramadan et al., 2018) with 5 tasks/domains. Given the intent and dialogue state (slot-value pairs containing messages to express), the system is expected to generate a response.

(5). NER (*Named Entity Recognition*). This data consists of 5 tasks, including **conll03** (Sang & Meulder, 2003), **wikigold** (Balasuriya et al., 2009), **btc** (Derczynski et al., 2016), **re3d** (Laboratory, 2017), and **gum** (Zeldes, 2017). Each task needs to classify mentions into pre-defined entity types. [9]

Baselines. We setup 11 baselines, including both *non-continual* and *continual learning* (CL) methods.

---

[8] Since each of these datasets is quite large, we randomly sampled 500 samples from each class for each task due to our resource limitations.

[9] Due to resource limitations, we randomly sampled 200 samples for each task.

Non-CL baselines: **ONE** builds a separate model for each task by fine-tuning the LM, which clearly has no knowledge transfer (KT) or CF. **ONE (Adapter)** (Madotto et al., 2020) trains an adapter for each task separately (called AdapterCL in its original paper). **ONE (Prompt)** (Zhu et al., 2022) trains a prompt for each task (called C-PT in its original paper).

CL baselines. The CL setting includes an *naive continual learning* (NCL) method where the system learns the tasks one by one with no mechanism to deal with CF or to encourage transfer, and 7 state-of-the art *task continual learning* (Task-CL) methods.

The 7 CL baselines include: 4 adapter-based methods **CTR** (Ke et al., 2021), **HAT** (Serrà et al., 2018), **SupSup** (Wortsman et al., 2020) and **CAT** (Ke et al., 2020). They all train a shared adapter while SupSup trains a sub-network mask on the fixed adapter. HAT is one of the most effective Task-CL methods with little forgetting. CTR encourages transfer via capsule networks and transfer routing. SupSup uses the similar sub-network masking method as TST but without any consideration on knowledge transfer. CAT and CTR are two systems that deal with both CF and KT. 1 prompt-based method **L2P** (Wang et al., 2022), which trains a prompt pool to transfer task knowledge and a key-value pair prompt selection strategy to select the task-specific prompt (it thus deals with both KT and CF); 2 baselines that modify the Transformer: **LAMOL** (Sun et al., 2020) is a pseudo-replay method based on GPT-2. **EWC** (Kirkpatrick et al., 2016) is a popular regularization method.

4.2 HYPER-PARAMETERS

Architecture. Since we need a backbone LM that can do both classification and generation, we adopt $BART_{LARGE}$ (Lewis et al., 2020) as our LM. Fine-tuning of BART follows the standard practice. [10]

Hyperparameters. Unless otherwise stated, the same hyper-parameters are used in all experiments. The maximum input length is set to 128 for all datasets except for SUM which uses 1024 due to its longer sequences. `AdamW` optimizer is used. The learning rate is set to 5e-5 for Transformer (search within {5e-2,5e-3,5e-4,5e-5}), 3e-2 for prompt (search within {3e-1,3e-2,3e-3,3e-4,3e-5}), adapter and classifier. The prompt length is set to 20 (search within {10,20,50,80,100,150}) and adapter bottleneck size is 64, following the original papers (Houlsby et al., 2019). The batch size is set to 32 and the number of training epochs is set to 50 with early stopping. The number of mask K in the mask pool is set to the same as the number of task. For classification tasks, a separate classification head is used for each task in the sequence. For generation tasks, a shared LM head is used for all tasks in a sequence. we further set the number of beams to 4 for beam search and constrain the target length in between 30 to 200. For image-based (EWC, HAT, SupSup, CAT, L2P) and RoBERTa-based (CTR) systems, we adapt them for text classification and generation by replacing their feature extractors with BART. For LAMOL, we directly run the author provided code. Except for the aforementioned hyper-parameters, all baseline-specific hyper-parameters follow those in their original papers.

Since the order of the tasks in a sequence may impact the final results, we ran 5 randomly sampled task sequences. We compute different metrics for different types of tasks. Specifically, we use Macro-F1 and accuracy for the sequence-level classification tasks (ASC and CCD), where Macro-F1 (MF1) is the primary metric because highly imbalanced classes in ASC introduce biases in accuracy. We use Rouge score (R1, R2 and RL) for SUM, BLEU score for DRG and F1 for NER. Table 1 gives the average result of each system on all tasks of each dataset over the 5 random task sequences. [11]

4.3 EVALUATION RESULTS AND ANALYSIS

Superiority of TST. Table 1 shows that TST clearly outperforms all baselines for tasks with shared knowledge (ASC and NER), and has no forgetting for tasks with little shared knowledge (SUM, CCD and DRG). Below, we discuss additional observations.

(1). TST achieves both forgetting prevention and knowledge transfer (KT). Using ONE as control, we can clearly see TST outperforms ONE in two datasets (ASC and NER) with similar tasks, indicating effective knowledge transfer. TST achieves similar results to ONE in other datasets, indicating effective forgetting prevention.

---

[10]For the ASC tasks, we adopt the ASC formulation in (Xu et al., 2019), where the aspect term and sentence are concatenated via ``. The opinion is predicted using the average over all tokens.

[11]LAMOL for NER is not included as it is not obvious how to adapt LAMOL for token-level classification.

Scenario	Data Model	SUM			ASC		CCD		DRG	NER
		R1	R2	RL	MF1	Acc	MF1	Acc	BLEU	F1
Non-CL	ONE	39.0738	10.7076	35.2501	0.8555	0.9150	0.9107	0.9109	0.2414	0.5933
	ONE (Adapter)	38.9000	11.5449	35.2323	0.8395	0.9090	0.9078	0.9081	0.2342	0.5669
	ONE (Prompt)	30.6709	7.2285	27.5339	0.7646	0.8554	0.8623	0.8628	0.1267	0.4590
CL	NCL	32.6824	6.8418	29.1898	0.8925	0.9304	0.8508	0.8510	0.2231	0.4919
	EWC	32.6362	7.1160	29.0004	0.8836	0.9260	0.8727	0.8737	0.1830	0.5176
	HAT	37.1127	10.4009	33.5331	0.8933	0.9328	0.9021	0.9023	0.2147	0.5231
	SupSup	38.3660	11.6289	34.7497	0.8898	0.9335	0.9098	0.9100	**0.2471**	0.5893
	LAMOL	10.8817	1.3885	6.8711	0.8462	0.9017	0.5444	0.6704	0.1996	—
	CAT	37.2350	10.5304	33.7733	0.8431	0.8898	0.9082	0.9090	0.2172	0.5073
	CTR	37.3360	10.7305	33.6853	0.8886	0.9294	0.9054	0.9058	0.2139	0.5185
	L2P	26.6538	4.8220	23.8983	0.7481	0.8464	0.8535	0.8554	0.0852	0.4422
	TST	**38.7758**	**11.3652**	**34.9935**	**0.9161**	**0.9453**	**0.9104**	**0.9103**	0.2425	**0.6169**

Table 1: Performance for different type of tasks and the mixture of them, averaged over 5 random sequences (the standard deviation is reported in Appendix B). "—" means not applicable. We bold the best performance within CL baselines.

Scenario	Data Model	SUM			ASC		CCD		DRG	NER
		R1	R2	RL	MF1	Acc	MF1	Acc	BLEU	F1
CL	NCL	8.3709	5.5409	5.9023	-0.0044	0.0031	0.0567	0.0564	0.0301	0.1549
	EWC	2.5835	1.6784	2.0420	0.0781	0.0278	0.0894	0.0817	0.0078	0.0753
	HAT	1.0993	1.2171	0.7840	-0.0088	-0.0036	-0.0007	-0.0008	0.0148	-0.0344
	SupSup	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
	LAMOL	3.9017	1.4158	2.3189	-0.0188	-0.0152	0.3226	0.2730	0.0229	—
	CAT	1.8510	1.4146	1.3684	0.0205	0.0081	-0.0013	-0.0021	0.0226	0.0081
	CTR	1.4349	0.9002	0.8590	-0.0038	-0.0008	-0.0027	-0.0027	0.0191	0.0058
	L2P	7.2695	3.5268	4.6789	0.0030	0.0054	0.0094	0.0082	0.0342	0.0096
	TST	0.3456	0.3051	0.2469	-0.0097	-0.0026	0.0075	0.0078	0.0133	-0.0062

Table 2: Forgetting rate - averages over 5 random sequences. Positive forgetting rate indicates forgetting while negative forgetting rate indicates knowledge transfer.

(2). TST is more effective than the baseline CL systems (EWC, HAT, SupSup, LAMOL) that only deal with CF. These baselines give poorer performances because regularization-based EWC sacrifices accuracy for overcoming CF and parameter-isolation based SupSup prevents any possible knowledge transfer (KT) and is thus poorer in ASC and NER. HAT has little KT in classification tasks, which makes ASC poorer. It has forgetting in generation tasks because it cannot isolate parameters in the shared LM head. LAMOL has only weak CF prevention and KT as it highly relies on the replay data, which could be of low quality.

(3). TST is also more effective than the baseline CL systems that try to deal with both CF and KT (CAT, CTR and L2P). Among these systems, L2P performs the worst due to the poor prompt selection (we can see it is even poorer than ONE (prompt), indicating that its selection causes forgetting). CAT performs better, but still has a large gap compared to TST, due to its inaccurate similarity detection and ineffectiveness in handling previous tasks. CTR is the best one among the three, but it is still worse than TST because of the inaccurate instance-level similarity detection.

(4). Sub-network masking on adapters helps TST achieve good results. TST uses adapters and we can see ONE (Adapter) is much better than ONE (Prompt) and is similar to ONE. The performance of prompt-based CL baseline L2P is much worse than other baselines. This is because prompts do not have sufficient trainable parameters, which are also randomly initialized and can be difficult to train.

Knowledge transfer and forgetting prevention. To validate TST's effectiveness in dealing with forgetting with a sequence of dissimilar tasks, we compute the *Forgetting Rate* (Liu et al., 2020), $FR = \frac{1}{t-1} \sum_{i=1}^{t-1} A_{i,i} - A_{t,i}$, where $A_{i,i}$ is the forward performance of task i and $A_{t,i}$ is the performance of task i after training the last task t. We average over all tasks except the last one because the last task obviously has no forgetting. We report the forgetting rate FR (averaged over 5 random task sequences) for all datasets in Table 2. In general, we can see that TST has only slight forgetting. We also note negative forgetting rates in ASC and NER, indicating there is some positive backward transfer (the training of a new task helps some old tasks). We can also see that the baselines have much larger forgetting comparing to TST. One exception is SupSup, which has no forgetting because it trains different masks/sub-networks for different tasks. This is certainly good for forgetting prevention but makes knowledge transfer impossible.

| Scenario | Data | SUM | | | ASC | | CCD | | DRG | NER |
	Model	R1	R2	RL	MF1	Acc	MF1	Acc	BLEU	F1
Non-CL	ONE	39.0738	10.7076	35.2501	0.8555	0.9150	0.9107	0.9109	0.2414	0.5933
	ONE (Adapter)	38.9000	11.5449	35.2323	0.8395	0.9090	0.9078	0.9081	0.2342	0.5669
	ONE (Prompt)	30.6709	7.2285	27.5339	0.7646	0.8554	0.8623	0.8628	0.1267	0.4590
CL	TST (w/o pool)	29.9746	7.1159	27.2446	0.9088	0.9427	0.8760	0.8778	0.1959	0.4836
	TST (w/o similarity)	38.3660	11.6289	34.7497	0.8898	0.9335	0.9098	0.9100	**0.2471**	0.5893
	TST (w/o comparison)	34.8660	9.6079	31.4729	0.9084	0.9421	0.8931	0.8923	0.2180	0.5493
	TST	**38.7758**	**11.3652**	**34.9935**	**0.9161**	**0.9453**	**0.9104**	**0.9103**	0.2425	**0.6169**

Table 3: Ablation experiment results - averages over 5 random sequences (the standard deviation is reported in Appendix B). We bold the best performance within CL baselines.

| Scenario | Data | SUM | | | ASC | | CCD | | DRG | NER |
	Model	R1	R2	RL	MF1	Acc	MF1	Acc	BLEU	F1
CL	TST (w/o pool)	8.9037	4.7496	5.7680	-0.0055	-0.0008	0.0413	0.0400	0.0494	0.1603
	TST (w/o similarity)	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
	TST (w/o comparison)	2.7010	1.4196	1.9688	-0.0079	-0.0039	0.0202	0.0214	0.0299	0.0850
	TST	0.3456	0.3051	0.2469	-0.0097	-0.0026	0.0075	0.0078	0.0133	-0.0062

Table 4: Forgetting rate for ablation experiment results.

Effectiveness of task similarity detection. We are interested in how good the similarity detection of TST is. Comparing the forgetting rate in Table 2, we can see that TST has only a very slight forgetting compared to baselines, indicating the effectiveness of its similarity detection. CAT, CTR and L2P all have much more forgetting than TST except on the CCD data, indicating they have poorer similarity detection. To provide more evidences, we show the task similarity detection results for TST in Appendix C. For *NER*, we see that tasks "conll2003", "wikigold" and "btc" use the same mask (indicating they are similar). This makes sense as they all share the same named entity classes while the other tasks have different named entities. In contrast, CAT, which is the only other baseline that does task-level similarity detection, finds all NER tasks dissimilar. In *SUM*, TST finds "icsi" and "ami" to be similar (sharing a mask). This is also reasonable because both tasks are summarization on meetings while the others are conversations of diverse forms. Similarly, we can see TST finds "Yelp" and "Amazon" to be similar in *CCD* because they are all sentiment classification tasks. CAT finds no similarity in both CCD and SUM tasks and produces worse results. Regarding *ASC* and *DRG*, it is hard to say which system is better at detecting task similarity as ASC tasks are all somehow similar and all tasks of DRG are dissimilar, but we see from the results in Table 1 that TST is better.

Ablation study. We want to know whether (1) the proposed mask pool, (2) the similarity detection and (3) the importance comparison are helpful. To answer (1), we conduct the ablation experiment **TST (w/o pool)**, where we use only one single mask/sub-network in the pool for all tasks that it continuously learns. To answer (2), we conduct the experiment **TST (w/o similarity)**, where we remove the similarity detection in TST and use different masks in the pool for different tasks (thus no CF or KT). To answer (3), we conduct experiment **TST (w/o comparison)**, where we remove the importance comparison in TST and simply use the mask with the highest importance based on the current task data as the mask for learning the current task.

Tables 3 and 4 show the ablation results and the corresponding forgetting rates. We can see that the full TST gives the best average result, indicating that every component helps. Additional observations are: (1) TST's gain is partially from the mask pool as TST (w/o pool) is poorer on average, particularly for those datasets having little shared knowledge; (2) Similarity detection helps as TST (w/o similarity) gives worse performance. (3) Our importance comparison is effective. We see that TST (w/o comparison) is poorer, indicating the importance comparison learning in TST helps mitigate CF.

5 CONCLUSION

This paper studied task continual learning (Task-CL) on a wide range of NLP problems using pre-trained BART model as backbone to achieve both CF prevention and knowledge transfer (KT). The key novelty of the proposed technique TST is the novel task similarity detection method based on mask importance. The importance is computed to find a similar task so that effective KT and CF prevention can be achieved. CF is prevented by using a different mask while KT is achieved by sharing the same mask. Experimental results showed that TST markedly improves the performance of both the new task and the old tasks via KT and is also effective at overcoming CF.

REFERENCES

Dominic Balasuriya, Nicky Ringland, Joel Nothman, Tara Murphy, and James R. Curran. Named entity recognition in wikipedia. In Iryna Gurevych and Torsten Zesch (eds.), *Proceedings of the 1st 2009 Workshop on The People's Web Meets NLP: Collaboratively Constructed Semantic Resources@IJCNLP 2009, Suntec, Singapore, August 7, 2009*, pp. 10–18. Association for Computational Linguistics, 2009.

Tom B. Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, Sandhini Agarwal, Ariel Herbert-Voss, Gretchen Krueger, Tom Henighan, Rewon Child, Aditya Ramesh, Daniel M. Ziegler, Jeffrey Wu, Clemens Winter, Christopher Hesse, Mark Chen, Eric Sigler, Mateusz Litwin, Scott Gray, Benjamin Chess, Jack Clark, Christopher Berner, Sam McCandlish, Alec Radford, Ilya Sutskever, and Dario Amodei. Language models are few-shot learners. In Hugo Larochelle, Marc'Aurelio Ranzato, Raia Hadsell, Maria-Florina Balcan, and Hsuan-Tien Lin (eds.), *Advances in Neural Information Processing Systems 33: Annual Conference on Neural Information Processing Systems 2020, NeurIPS 2020, December 6-12, 2020, virtual*, 2020. URL https://proceedings.neurips.cc/paper/2020/hash/1457c0d6bfcb4967418bfb8ac142f64a-Abstract.html.

Arslan Chaudhry, Marc'Aurelio Ranzato, Marcus Rohrbach, and Mohamed Elhoseiny. Efficient lifelong learning with A-GEM. In *ICLR*, 2019.

Tianlong Chen, Jonathan Frankle, Shiyu Chang, Sijia Liu, Yang Zhang, Zhangyang Wang, and Michael Carbin. The lottery ticket hypothesis for pre-trained bert networks. *Advances in neural information processing systems*, 33:15834–15846, 2020.

Cyprien de Masson d'Autume, Sebastian Ruder, Lingpeng Kong, and Dani Yogatama. Episodic memory in lifelong language learning. In Hanna M. Wallach, Hugo Larochelle, Alina Beygelzimer, Florence d'Alché-Buc, Emily B. Fox, and Roman Garnett (eds.), *Advances in Neural Information Processing Systems 32: Annual Conference on Neural Information Processing Systems 2019, NeurIPS 2019, December 8-14, 2019, Vancouver, BC, Canada*, 2019.

Leon Derczynski, Kalina Bontcheva, and Ian Roberts. Broad twitter corpus: A diverse named entity recognition resource. In Nicoletta Calzolari, Yuji Matsumoto, and Rashmi Prasad (eds.), *COLING 2016, 26th International Conference on Computational Linguistics, Proceedings of the Conference: Technical Papers, December 11-16, 2016, Osaka, Japan*, pp. 1169–1179. ACL, 2016.

Alexander R. Fabbri, Faiaz Rahman, Imad Rizvi, Borui Wang, Haoran Li, Yashar Mehdad, and Dragomir R. Radev. Convosumm: Conversation summarization benchmark and improved abstractive summarization with argument mining. In Chengqing Zong, Fei Xia, Wenjie Li, and Roberto Navigli (eds.), *Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing, ACL/IJCNLP 2021, (Volume 1: Long Papers), Virtual Event, August 1-6, 2021*, pp. 6866–6880. Association for Computational Linguistics, 2021.

Angela Fan, Edouard Grave, and Armand Joulin. Reducing transformer depth on demand with structured dropout. In *International Conference on Learning Representations*, 2020. URL https://openreview.net/forum?id=SylO2yStDr.

Chrisantha Fernando, Dylan Banarse, Charles Blundell, Yori Zwols, David Ha, Andrei A. Rusu, Alexander Pritzel, and Daan Wierstra. Pathnet: Evolution channels gradient descent in super neural networks. *CoRR*, 2017.

Yang Gao, Nicolo Colombo, and Wei Wang. Adapting by pruning: A case study on bert. *arXiv preprint arXiv:2105.03343*, 2021.

Yiwen Guo, Anbang Yao, and Yurong Chen. Dynamic network surgery for efficient dnns. *NIPS*, 29, 2016.

Song Han, Jeff Pool, John Tran, and William Dally. Learning both weights and connections for efficient neural network. *Advances in neural information processing systems*, 28, 2015.

Xu He and Herbert Jaeger. Overcoming catastrophic interference using conceptor-aided backpropagation. In *ICLR*, 2018.

Neil Houlsby, Andrei Giurgiu, Stanislaw Jastrzebski, Bruna Morrone, Quentin de Laroussilhe, Andrea Gesmundo, Mona Attariyan, and Sylvain Gelly. Parameter-efficient transfer learning for NLP. In Kamalika Chaudhuri and Ruslan Salakhutdinov (eds.), *ICML*, 2019.

Yufan Huang, Yanzhe Zhang, Jiaao Chen, Xuezhi Wang, and Diyi Yang. Continual learning for text classification with information disentanglement based regularization. *arXiv preprint arXiv:2104.05489*, 2021.

Nitin Kamra, Umang Gupta, and Yan Liu. Deep generative dual memory network for continual learning. *CoRR*, 2017.

Zixuan Ke, Bing Liu, and Xingchang Huang. Continual learning of a mixed sequence of similar and dissimilar tasks. In *NeurIPS*, 2020.

Zixuan Ke, Bing Liu, Nianzu Ma, Hu Xu, and Lei Shu. Achieving forgetting prevention and knowledge transfer in continual learning. *Advances in Neural Information Processing Systems*, 34, 2021.

James Kirkpatrick, Razvan Pascanu, Neil C. Rabinowitz, Joel Veness, Guillaume Desjardins, Andrei A. Rusu, Kieran Milan, John Quan, Tiago Ramalho, Agnieszka Grabska-Barwinska, Demis Hassabis, Claudia Clopath, Dharshan Kumaran, and Raia Hadsell. Overcoming catastrophic forgetting in neural networks. *CoRR*, 2016.

Defence Science Technology Laboratory. Relationship and entity extraction evaluation dataset. 2017. URL https://github.com/dstl/re3d.

Cheng-I Jeff Lai, Yang Zhang, Alexander H Liu, Shiyu Chang, Yi-Lun Liao, Yung-Sung Chuang, Kaizhi Qian, Sameer Khurana, David Cox, and Jim Glass. Parp: Prune, adjust and re-prune for self-supervised speech recognition. *NeurIPS*, 34, 2021.

Sang-Woo Lee, Jin-Hwa Kim, Jaehyun Jun, Jung-Woo Ha, and Byoung-Tak Zhang. Overcoming catastrophic forgetting by incremental moment matching. In *NIPS*.

Brian Lester, Rami Al-Rfou, and Noah Constant. The power of scale for parameter-efficient prompt tuning. In Marie-Francine Moens, Xuanjing Huang, Lucia Specia, and Scott Wen-tau Yih (eds.), *EMNLP*, 2021.

Mike Lewis, Yinhan Liu, Naman Goyal, Marjan Ghazvininejad, Abdelrahman Mohamed, Omer Levy, Veselin Stoyanov, and Luke Zettlemoyer. BART: denoising sequence-to-sequence pre-training for natural language generation, translation, and comprehension. In Dan Jurafsky, Joyce Chai, Natalie Schluter, and Joel R. Tetreault (eds.), *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics, ACL 2020, Online, July 5-10, 2020*, pp. 7871–7880. Association for Computational Linguistics, 2020. doi: 10.18653/v1/2020.acl-main.703. URL https://doi.org/10.18653/v1/2020.acl-main.703.

Jiaoda Li, Ryan Cotterell, and Mrinmaya Sachan. Differentiable subset pruning of transformer heads. *Transactions of the Association for Computational Linguistics*, 9:1442–1459, 2021.

Zi Lin, Jeremiah Zhe Liu, Zi Yang, Nan Hua, and Dan Roth. Pruning redundant mappings in transformer models via spectral-normalized identity prior. *arXiv preprint arXiv:2010.01791*, 2020.

Yaoyao Liu, Yuting Su, An-An Liu, Bernt Schiele, and Qianru Sun. Mnemonics training: Multi-class incremental learning without forgetting. In *CVPR*, 2020.

David Lopez-Paz and Marc'Aurelio Ranzato. Gradient episodic memory for continual learning. In *NIPS*, 2017.

Andrea Madotto, Zhaojiang Lin, Zhenpeng Zhou, Seungwhan Moon, Paul Crook, Bing Liu, Zhou Yu, Eunjoon Cho, and Zhiguang Wang. Continual learning in task-oriented dialogue systems. *arXiv preprint arXiv:2012.15504*, 2020.

Arun Mallya and Svetlana Lazebnik. Packnet: Adding multiple tasks to a single network by iterative pruning. In *CVPR*, 2018.

JS McCarley, Rishav Chakravarti, and Avirup Sil. Structured pruning of a bert-based question answering model. *arXiv preprint arXiv:1910.06360*, 2019.

Michael McCloskey and Neal J Cohen. Catastrophic interference in connectionist networks: The sequential learning problem. In *Psychology of learning and motivation*. 1989.

Paul Michel, Omer Levy, and Graham Neubig. Are sixteen heads really better than one? *Advances in neural information processing systems*, 32, 2019.

Osman Ramadan, Paweł Budzianowski, and Milica Gasic. Large-scale multi-domain belief tracking with knowledge sharing. In *Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics*, volume 2, pp. 432–437, 2018.

Vivek Ramanujan, Mitchell Wortsman, Aniruddha Kembhavi, Ali Farhadi, and Mohammad Rastegari. What's hidden in a randomly weighted neural network? In *2020 IEEE/CVF Conference on Computer Vision and Pattern Recognition, CVPR 2020, Seattle, WA, USA, June 13-19, 2020*, pp. 11890–11899. Computer Vision Foundation / IEEE, 2020.

Sylvestre-Alvise Rebuffi, Alexander Kolesnikov, Georg Sperl, and Christoph H. Lampert. icarl: Incremental classifier and representation learning. In *CVPR*, 2017.

Mohammad Rostami, Soheil Kolouri, and Praveen K. Pilly. Complementary learning for overcoming catastrophic forgetting using experience replay. In *IJCAI*, 2019.

Andrei A. Rusu, Neil C. Rabinowitz, Guillaume Desjardins, Hubert Soyer, James Kirkpatrick, Koray Kavukcuoglu, Razvan Pascanu, and Raia Hadsell. Progressive neural networks. *CoRR*, 2016.

Sara Sabour, Nicholas Frosst, and Geoffrey E Hinton. Dynamic routing between capsules. In *NIPS*, 2017.

Hassan Sajjad, Fahim Dalvi, Nadir Durrani, and Preslav Nakov. On the effect of dropping layers of pre-trained transformer models. *arXiv preprint arXiv:2004.03844*, 2020.

Erik F. Tjong Kim Sang and Fien De Meulder. Introduction to the conll-2003 shared task: Language-independent named entity recognition. In Walter Daelemans and Miles Osborne (eds.), *Proceedings of the Seventh Conference on Natural Language Learning, CoNLL 2003, Held in cooperation with HLT-NAACL 2003, Edmonton, Canada, May 31 - June 1, 2003*, pp. 142–147. ACL, 2003.

Ari Seff, Alex Beatson, Daniel Suo, and Han Liu. Continual learning in generative adversarial nets. *CoRR*, abs/1705.08395, 2017.

Joan Serrà, Didac Suris, Marius Miron, and Alexandros Karatzoglou. Overcoming catastrophic forgetting with hard attention to the task. In *ICML*, 2018.

Hanul Shin, Jung Kwon Lee, Jaehong Kim, and Jiwon Kim. Continual learning with deep generative replay. In *NIPS*, 2017.

Fan-Keng Sun, Cheng-Hao Ho, and Hung-Yi Lee. Lamol: Language modeling is all you need for lifelong language learning. In *ICLR*, 2020. URL https://openreview.net/forum?id=Skgxcn4YDS.

Elena Voita, David Talbot, Fedor Moiseev, Rico Sennrich, and Ivan Titov. Analyzing multi-head self-attention: Specialized heads do the heavy lifting, the rest can be pruned. *arXiv preprint arXiv:1905.09418*, 2019.

Zifeng Wang, Zizhao Zhang, Chen-Yu Lee, Han Zhang, Ruoxi Sun, Xiaoqi Ren, Guolong Su, Vincent Perot, Jennifer Dy, and Tomas Pfister. Learning to prompt for continual learning. In *CVPR*, 2022.

Zirui Wang, Sanket Vaibhav Mehta, Barnabás Póczos, and Jaime Carbonell. Efficient meta lifelong-learning with limited memory. In *EMNLP*, 2020.

Mitchell Wortsman, Vivek Ramanujan, Rosanne Liu, Aniruddha Kembhavi, Mohammad Rastegari, Jason Yosinski, and Ali Farhadi. Supermasks in superposition. In H. Larochelle, M. Ranzato, R. Hadsell, M. F. Balcan, and H. Lin (eds.), *NeurIPS*, 2020.

Hu Xu, Bing Liu, Lei Shu, and Philip S. Yu. BERT post-training for review reading comprehension and aspect-based sentiment analysis. In Jill Burstein, Christy Doran, and Thamar Solorio (eds.), *NAACL-HLT*, 2019.

Amir Zeldes. The GUM corpus: creating multilayer resources in the classroom. *Lang. Resour. Evaluation*, 51(3):581–612, 2017. doi: 10.1007/s10579-016-9343-x. URL `https://doi. org/10.1007/s10579-016-9343-x`.

Guanxiong Zeng, Yang Chen, Bo Cui, and Shan Yu. Continuous learning of context-dependent processing in neural networks. *Nature Machine Intelligence*, 2019.

Friedemann Zenke, Ben Poole, and Surya Ganguli. Continual learning through synaptic intelligence. In *International Conference on Machine Learning*, pp. 3987–3995. PMLR, 2017.

Qi Zhu, Bing Li, Fei Mi, Xiaoyan Zhu, and Minlie Huang. Continual prompt tuning for dialog state tracking. *arXiv preprint arXiv:2203.06654*, 2022.

A   ADDITIONAL DETAILS ABOUT THE DATASETS

Recall that TST uses five datasets. Here we give their detailed statistics.

(1) **ASC.** ASC is more than a traditional classification problem because of the additional input of the aspect and the fact that in the same sentence different aspects can have different opinions. Here we show more detailed on these datasets in Table 5.

(2) **CCD, SUM, DRG and NER.** We give their detailed statistic in Table 6

Tasks/Domains	#Training	#Validating	#Testing
Speaker	233 S./352 A./287 P./65 N./0 Ne.	30 S./44 A./35 P./9 N./0 Ne.	38 S./44 A./40 P./4 N./0 Ne.
Router	200 S./245 A./142 P./103 N./0 Ne.	24 S./31 A./19 P./12 N./0 Ne.	22 S./31 A./24 P./7 N./0 Ne.
Computer	187 S./283 A./218 P./65 N./0 Ne.	25 S./35 A./23 P./12 N./0 Ne.	29 S./36 A./29 P./7 N./0 Ne.
Nokia6610	209 S./271 A./198 P./73 N./0 Ne.	29 S./34 A./30 P./4 N./0 Ne.	28 S./34 A./25 P./9 N./0 Ne.
Nikon4300	131 S./162 A./135 P./27 N./0 Ne.	15 S./20 A./18 P./2 N./0 Ne.	15 S./21 A./19 P./2 N./0 Ne.
Creative	582 S./677 A./422 P./255 N./0 Ne.	68 S./85 A./42 P./43 N./0 Ne.	70 S./85 A./52 P./33 N./0 Ne.
CanonG3	190 S./228 A./180 P./48 N./0 Ne.	25 S./29 A./21 P./8 N./0 Ne.	24 S./29 A./24 P./5 N./0 Ne.
ApexAD	281 S./343 A./146 P./197 N./0 Ne.	35 S./43 A./16 P./27 N./0 Ne.	28 S./43 A./31 P./12 N./0 Ne.
CanonD500	103 S./118 A./96 P./22 N./0 Ne.	11 S./15 A./14 P./1 N./0 Ne.	13 S./15 A./11 P./4 N./0 Ne.
Canon100	137 S./175 A./123 P./52 N./0 Ne.	19 S./22 A./20 P./2 N./0 Ne.	16 S./22 A./21 P./1 N./0 Ne.
Diaper	166 S./191 A./143 P./48 N./0 Ne.	22 S./24 A./18 P./6 N./0 Ne.	24 S./24 A./22 P./2 N./0 Ne.
Hitachi	152 S./212 A./153 P./59 N./0 Ne.	23 S./26 A./19 P./7 N./0 Ne.	23 S./27 A./14 P./13 N./0 Ne.
Ipod	124 S./153 A./101 P./52 N./0 Ne.	18 S./19 A./14 P./5 N./0 Ne.	19 S./20 A./15 P./5 N./0 Ne.
Linksys	152 S./176 A./128 P./48 N./0 Ne.	19 S./22 A./13 P./9 N./0 Ne.	20 S./23 A./16 P./7 N./0 Ne.
MicroMP3	384 S./484 A./340 P./144 N./0 Ne.	42 S./61 A./48 P./13 N./0 Ne.	51 S./61 A./39 P./22 N./0 Ne.
Nokia6600	298 S./362 A./244 P./118 N./0 Ne.	26 S./45 A./32 P./13 N./0 Ne.	39 S./46 A./30 P./16 N./0 Ne.
Norton	168 S./194 A./54 P./140 N./0 Ne.	17 S./24 A./15 P./9 N./0 Ne.	24 S./25 A./5 P./20 N./0 Ne.
Restaurant	1893 S./3452 A./2094 P./779 N./579 Ne.	84 S./150 A./70 P./26 N./54 Ne.	600 S./1120 A./728 P./196 N./196 Ne.
Laptop	1360 S./2163 A./930 P./800 N./433 Ne.	98 S./150 A./57 P./66 N./27 Ne.	411 S./638 A./341 P./128 N./169 Ne.

Table 5: Statistics of the ASC tasks. **S.**: number of sentences; **A**: number of aspects; **P., N., and Ne.**: number aspects with positive, negative and neutral opinions, respectively. Note that the "Restaurant" and "Laptop" have 3 classes of opinion polarities (positive, negative and neutral) while the others have only 2 classes (positive and negative).

Dataset	Tasks/Domains	#Training	#Validating	#Testing	#Classes
CCD	Yahoo	4500	500	4840	10
	AGnews	1785	199	1756	2
	Amazon	898	100	998	2
	Dbpedia	6237	693	6748	14
	Yelp	900	100	984	4
SUM	icsi	43	10	6	—
	ami	97	20	20	—
	reddit	201	50	250	—
	stack	205	50	250	—
	nyt	200	50	250	—
	emails	215	50	250	—
DRG	taxi	406	71	56	—
	hotel	3366	143	177	—
	attraction	298	27	28	—
	train	1954	196	262	—
	restaurant	569	63	59	—
NER	conll2003	200	3250	3453	9
	wikigold	200	170	170	9
	btc	200	934	934	9
	re3d	200	77	200	21
	gum	200	250	1000	23

Table 6: Statistics of the CCD, SUM, DRE and NER datasets. Number of classes is not applicable to SUM and DRG because they are generation datasets.

B   STANDARD DEVIATIONS

Table 7 reports the standard deviations of the corresponding results in Table 1 (in the main paper) of TST and the considered baselines over 5 runs with random sequences. We only report the CL

| Scenario | Data | SUM | | | ASC | | CCD | | DRG | NER |
	Model	R1	R2	RL	MF1	Acc	MF1	Acc	BLEU	F1
	NCL	±0.6028	±0.5458	±0.6623	±0.0040	±0.0027	±0.0233	±0.0230	±0.0060	±0.0767
	EWC	±1.3205	±0.5331	±1.1258	±0.0093	±0.0063	±0.0227	±0.0216	±0.0217	±0.0707
	HAT	±1.3035	±0.4912	±1.1464	±0.0130	±0.0042	±0.0028	±0.0028	±0.0094	±0.0063
CL	LAMOL	±1.2519	±0.4218	±0.5231	±0.0085	±0.0039	±0.0317	±0.0258	±0.0068	—
	CAT	±1.0424	±0.4027	±0.9029	±0.0096	±0.0021	±0.0019	±0.0021	±0.0051	±0.0106
	CTR	±1.1595	±0.5189	±0.9646	±0.0080	±0.0030	±0.0009	±0.0010	±0.0127	±0.0049
	L2P	±2.1496	±0.4747	±2.0267	±0.0650	±0.0361	±0.0181	±0.0176	±0.0216	±0.0022
	TST	±0.5287	±0.3585	±0.5175	±0.0027	±0.0032	±0.0049	±0.0048	±0.0079	±0.0031

Table 7: Standard deviations of the corresponding metrics of the proposed DGA model and the baselines on the five different datasets.

| Scenario | Data | SUM | | | ASC | | CCD | | DRG | NER |
	Model	R1	R2	RL	MF1	Acc	MF1	Acc	BLEU	F1
	TST (w/o pool)	±0.8603	±0.3504	±0.5482	±0.0049	±0.0034	±0.0300	±0.0287	±0.0103	±0.0437
CL	TST (w/o comparison)	±1.0655	±0.5163	±0.9594	±0.0073	±0.0028	±0.0098	±0.0089	±0.0057	±0.0374
	TST	±0.5287	±0.3585	±0.5175	±0.0027	±0.0032	±0.0049	±0.0048	±0.0079	±0.0031

Table 8: Standard deviations of the corresponding metrics of the proposed TST model and the six ablation experiments.

baselines since they are related to the task order. We can see the results of TST is stable. SupSup trains different mask/sub-networks for different tasks, so it is not related to the task order and not reported in the table.

Table 8 reports the standard deviations of the corresponding results in Table 3 (in the main paper) of TST and the considered baselines over 5 runs with random sequences. We can see the results of TST and its variants are stable. TST (w/o similarity) trains different mask/sub-network for different tasks, so it is not related to task order and not reported in the table.

C TASK SIMILARITY DETECTION RESULTS

In Sec. 4, we discussed the effectiveness of task similarity comparison and compare the similarity detection results of TST and CAT. Figure 3 show the task similarity results for TST. Figure 2 shows the task similarity results on the ASC data for CAT. CAT did not find any similar tasks for the other datasets. The analysis is already in Sec. 4.

Figure 2: Similarity detection results for ASC of CAT. The y-axis gives the sequence of tasks that are learned, and the x-axis lists the same set of task names. The yellow cells indicate that the corresponding tasks are detected by CAT as similar (one task can be similar to multiple tasks but only the previously learned tasks are considered for the current task) while the purple cells indicate the tasks are dissimilar or unknown (because they have not been learned). For example row 3 means when we are learning task "DiaperChamp", CAT finds it to be dissimilar to any of learned tasks ("CanonG3" and "Computer"); Row 4 means when we are learning task "Router", CAT finds it to be similar to task "DiaperChamp".

Figure 3: Similarity detection results of TST (after the continual training of all tasks). X-axis shows mask IDs and y-axis shows the task names. The yellow cells indicate that the masks are used by some tasks while the purple cells indicate the masks are not used by their corresponding tasks. If multiple tasks use the same mask, they are regarded as similar by our system TST. Note that not all masks are used because different tasks may share the same mask.