APPLICATION OF POISSON LEARNING FOR THE CLASSIFICATION OF SOLUTIONS OF DYNAMICAL SYSTEMS

ABSTRACT

In this article, we consider the application of the Poisson learning method to solve the problem of classifying solutions of dynamical systems based on two-dimensional data. In work a modification of Poisson learning is proposed. Furthermore, to find the minimum loss function, the Nesterov algorithm is employed, which demonstrates better results compared to gradient descent. With this approach and modification, the task of classifying the periodic solutions of the dynamical system is solved with sufficient accuracy even in real-time mode, taking into account accumulation errors and time constraints.

1 INTRODUCTION

Graph-based semi-supervised learning (GSSL) is recognized as one of the most effective approaches in semi-supervised learning. The integration of mathematical methods in GSSL—including graph theory, optimization techniques, and numerical methods for solving differential and algebraic equations—enables a precise mathematical formulation of the problem and a rigorous justification of algorithmic solutions. Additionally, the physical interpretation of label propagation in GSSL plays a crucial role, drawing parallels with gas diffusion, Bernoulli processes, harmonic fields and waves, heat conduction, and other physical phenomena. The most widely known GSSL methods utilize energy functions and the graph Laplacian. These methods include Label Propagation, Label Spreading, p-Laplace Propagation, Deformable Laplacian, and Poisson Learning, among others. The key advantage of these methods lies in their ability to spread labels across the graph using a minimal amount of labeled data while maintaining high accuracy through iterative computation. The application of the normalized Laplacian allows these methods to effectively capture both local and global data structures. Currently, numerous approaches exist for implementing semi-supervised learning with the Laplacian, as discussed in several reviews (7), (11), (9), (10), (12), (16) and others.

Among the most well-established semi-supervised learning methods that leverage the Laplacian are extbfLabel Propagation, Label Spreading, and Poisson Learning. Each of these methods has its own strengths and limitations. The first two approaches exhibit slow convergence on large datasets and suffer from the issue of forgetting initial labels over iterations. Meanwhile, Poisson Learning does not fully account for the local structure of the data. In recent research, a novel method based on the Laplacian— Poisson Label Propagation (Poisson Learning) —has been introduced. This approach addresses some of the limitations of Laplace-based methods, particularly their inefficiency when dealing with a small amount of labeled data. However, in other aspects, it remains similar to Label Propagation. In our study, we employed Poisson Learning to investigate its effectiveness in label propagation.

In previous research, a graph-analytical method using Poincaré sections and its numerical implementation was employed for this task to construct a projection of the trajectory structure of the phase space of a dynamical system on two-dimensional manifolds. This two-dimensional data structure consists of different classes of periodic solutions (closed curves). The trajectory is constructed sequentially in real time and consists of a set of points from the numerical solution of a system of differential equations using the Runge-Kutta method. However, this process is time-limited due to the accumulation error, which is the main challenge for fully automating the classification of solutions. As a result, within a fixed time period, trajectory data flows are obtained on the two-dimensional Poincaré sections, which exhibit different properties and must be classified into distinct classes.

Graph-based semi-supervised learning methods are a modern tool for solving various classification problems, whether for two classes or more. This machine learning technique is used when fully supervised methods cannot be applied and the structure of the data space can be represented as a graph, which is well-suited to our case.

In this article, we consider the application of GSSL method to solve the problem of classifying solutions of dynamical systems based on two-dimensional data. To improve the data classification problem, this work proposes the use of a graph-based semi-supervised learning method based on nonlinear Poisson equations, known as Poisson Learning via new modification this method - Nesterov optimization.

2 COMPUTER ANALYSIS RELATED RESEARCH

Currently, a fairly not more large number of works are devoted to the study of the application of different machine learning methods for solving problems of locating periodic orbits of dynamical system. We will consider some of these works in more detail [5-8].

In work [5] the detection of periodic orbits bears significance for the study of nonlinear mappings, since they can reveal crucial information on their dynamics. Recently, population–based stochastic optimization algorithms were introduced to address problems where traditional gradient–based approaches failed. The efficiency of these approaches in a applications, triggered further research towards the development of more efficient variants. This work presents the principal concepts of applying concurrent stochastic population–based approaches for the detection of periodic orbits, and also reports new results attained by the appli cation of Memetic Algorithms on well–known chaotic maps for periodic orbits with high period.

In [6] authors are proposed a new approach for the identification of the reso nances appearing in symplectic maps. In the proposed methodology, they make use of Evolutionary Algorithms which are population based search strategies used for global optimization. Authors have applied the proposed methodology to the 2-dimensional (2D) Henon map and obtained promising results which can be generalized to symplectic maps of higher (2m) dimensions. As is well-known, such maps are representative of Hamiltonian systems and occur in many physical applications.

In [7] authors presents an algorithm for automatic detection of round shapes on complex and noisy images. Algorithm based on a hybrid technology consisting of simulated annealing and differential evolu tion. New fuzzy target function was obtained on the boundary map of the input Images. Minimizing this function with the hybrid differential evolution firing algorithm results in automatic detection of circles in the image. Simulation of the results ends with several synthetic as well as natural images with variable complexity, which confirms the effectiveness of the proposed technique in terms of its ultimate accuracy, speed and reliability. In (2) non-autonomous systems are studied by examining their Poincaré maps. Poincaré maps are used to identify periodic and subharmonic solutions and to study systems whose solutions exhibit chaotic behavior.

3 GRAPH-BASED SEMI-SUPERVISED POISSON LEARNING FOR TASKS CLASSIFICATION

3.1 PROBLEM STATEMENT

We consider the problem of classifying datasets from two classes represented on a on the trajectory flow are obtained on the two-dimensional Poincaré sections, which is discrete two-dimensional datasets. This datasets can has several classes. We will used a graph-based semi-supervised Poisson learning method for task classification this datasets. We used this method because we have small start label data in beginning.

So, we consider GSSL and first step is building a graph on the datasets. For the set of vertices $X = \{x_1, x_2, \ldots, x_n\}$ of some undirected graph G and the first m vertices (initial ones) of the set X receive the corresponding labels $\{y_1, y_2, \ldots, y_m\}$. The number of labeled data is less than the total, i.e., $m < n$. The task of graph-based semi-supervised learning using a graph is to spread the label values from the initial vertices to all others, that is, to find the values labels for $\{x_{m+1}, x_{m+2}, \ldots, x_n\}$.

General steps GSSL method will be consist is

Here is a rephrased version of your text:

1. Constructing a Weighted Graph. To construct a weighted graph, common weight calculation methods include geometric distance, Gaussian distance, and KNN distance. The choice of the weight function depends on the data distribution. For datasets with overlapping classes, KNN-based weights are preferable (11).

2. Initializing Labels. The initial label assignment involves selecting a subset of labeled data points from each class. It is recommended to maintain an equal number of labeled samples across all classes to ensure balanced initialization.

3. Defining the Penalty Function and Incorporating Regularization. The penalty function is formulated using the Dirichlet energy function on the graph, supplemented with additional terms that enforce data regularization or boundary constraints. Regularization terms such as L2 or L1 can be incorporated to improve stability.

4. Minimizing the Penalty Function and Label Propagation. When the complete energy function is used on the graph, minimizing the penalty function corresponds to solving the Poisson equation. If an incomplete energy function is used, the problem reduces to solving the Laplace equation. The numerical solution of these equations forms the basis of the label propagation algorithm. In the proposed approach, we utilize the Nesterov method for optimization.

3.2 GRAPH CONSTRUUCTION AND POISSON LEARNING

Let there be given an undirected weighted graph $G = G(X, V, W)$, where n number of vertices. $X = \{x_1, x_2, ..., x_n\}$ - the set of vertices of the graph, V - the set of edges, $W = (w_{ij})_{i,j=1}^{n}$ - is the weight matrix of the graph G.

The weight of the graph edges can be calculated using the following formulas (1):

$$w_{ij} = \psi\left(\frac{|x_i - x_j|}{\varepsilon_k(x_i)}\right) \text{ - KNN weight,}$$

$$w_{ij} = \exp\left(\frac{-|x_i - x_j|^2}{2\sigma^2}\right) \text{ - Gaussian weight.}$$

$$(1)$$

Where ψ - some function, ε - neighborhood, σ is a parameter that controls the variance of neighbors.

The degree of the node x_i is determined by the formula $d_i = \sum_{j=1}^{n} w_{ij}$.

According to Poisson learning **(11)**, label propagation occurs by solving the Poisson equation, which has the form (2):

$$L(u_i) = \sum_{j=1}^{n} w_{i,j}[u(x_i) - u(x_j)] = \sum_{j=1}^{m}(y_j - \bar{y})\delta_{ij}, \quad 1 \le i \le m$$

$$L(u_i) = 0, \quad m+1 \le i \le n$$

$$(2)$$

where L - is the non-normalized Laplace operator, x_i - are the vertices of the undirected weighted graph, $y_i = y(x_i)$ - are the initial labels of the graph vertices, $u_i = u(x_i)$ - is the function of graph vertex labels G, w_{ij} - edge weight (x_i, x_j), n - is the total number of graph vertices, the first m of which are considered labeled. $\bar{y} = \frac{1}{m}\sum_{j=1}^{m} y_j$. $\delta_{i,j}$ - is the Kronecker symbol. $\sum_{i=1}^{n} d_i u(x_i) = 0$.

In (11) an iterative process for solving this system based on the solution of the diffusion equation was proposed - Poisson Learning (Poisson Label Propagation) method. We note some advantages of f Poisson Label Propagation over the classical Label Propagation (Laplace Label Propagation).

First of all (11), it means higher speed and shorter execution time due to the use of exact differential methods rather than stochastic methods (Random Walk, Diffuse, Broun Move).

Secondly, it is overcoming degeneracy at "zero" - that is, when the number of given labeled vertices is very small in relation to all vertices - or the ratio of labeled vertices to all vertices converges to zero.

Third (11), it is overcoming the problem of "forgetting" for a large amount of data. That is, in Laplace learning, with a small number of initial labeled vertices and a large number of unlabeled vertices, it is possible to re-label their initial values.

Fourth, there is still the problem of the speed of algorithm convergence for big data. There are many optimization algorithms to improve the solution convergence problem. One of the best optimization methods is the Nesterov method,

In addition to the general problems, the Poisson label propagation method has other drawbacks that arise in the case of class intersection. To solve the problem of semi-supervised graph-based learning for the case of class intersection, various regularization additives are used. **(14),**

Thus, in this paper, we will consider a semi-supervised learning method using the Poisson equation for more efficient application to samples difficult classes.

3.3 Poisson Learning via Nesterov optimization

Let's consider the problem of semi-supervised learning using Poisson equations more thoroughly. Poisson learning also has a variational interpretation, which reduces semi-supervised learning to minimizing the Dirichlet energy. Dirichlet energy is often used as a penalty function. The Dirichlet energy formula can be represented as (3)

$$E\left(u\right) = \sum_{i,j=1}^{n} w_{ij} \left|u\left(x_i\right) - u\left(x_j\right)\right|^2 - \sum_{j=1}^{m} \left(y_j - \bar{y}\right) u\left(x_j\right) \tag{3}$$

In this work, a modification of Poisson learning is proposed. Furthermore, to find the minimum, the Nesterov algorithm is employed, which demonstrates better results compared to gradient descent.

For the Nesterov approach, the optimization step looks like this

$$g_{\{k\}}\left(x_i\right) = \frac{1}{d_i} \left(\sum_{j=1}^{m} \left(y_j - \bar{y}\right) \delta_{ij} - \sum_{j=1}^{n} w_{ij} \left(u_{\{k\}}\left(x_i\right) - u_{\{k\}}\left(x_j\right)\right) \right)$$
$$,$$
$$v_{\{k\}} = \gamma v_{\{k-1\}} - \alpha g_{\{k\}},$$
$$u_{\{k+1\}}\left(x_i\right) = u_{\{k+1\}}\left(x_i\right) + v_{\{k\}}. \tag{4}$$

Where $g_{\{k\}}$ - is the gradient at any time step k, α - hyperparametr.

The classical Poisson learning has iterative solution (2) by gradient descent. and the label selection rule can be written as (5):

$$u_l\left(x_i\right) = argmax_{j \in 1,2} s_j u_j\left(x\right) \tag{5}$$

where $s_j = \left(\frac{b_j}{\bar{y}}\right)$, b_j - is the share of data belonging to the class $j \in 1, 2$.

Let's consider a graph-based semi-supervised learning method based on Poisson learning with an additional regularizer $L2$ and Nesterov optimizer. This method will consist of the following steps.

Input : $W, \ F = [y_1, y_2, \ldots, y_m], \ T$

1. **Compute Degree Matrix** : $D = \mathrm{diag} \ (W\mathbf{1})$

2. **Compute Laplacian** : $L = D - W$

3. **Compute Average Label Vector** : $c = \frac{1}{m} \ F\mathbf{1}$

4. **Construct Matrix** : $B = [F - c, \ Z \ (2, n - m)]$

5. **Initialize** : $U = Z \ (n, 2)$

6. **For** $i = 1 \ to \ T$:

   Update : $U_j^k \ using \ the \ update \ formula \ (\mathbf{4}) - (\mathbf{6})$

7. **Label Assignment** : $l_k = argmax_{1 \leq j \leq 2} U_j^k$

3.4 COMPARISON AND ANALYSES

We will compare with existing methods and their modifications: Label Propagation, Label Spreading, Poisson GD, Poisson Adam, Poisson Nesterov on classical model "Two Moons" with 10000 datasets and $\{1,2,3,4,5,6,7,8,9,10\}$ numbered label per class.

Figure 1: Comparison with other methods. Label Propagation, Label Spreading, Poisson GD, Poisson Adam, and Poisson Nesterov.

The picture illustrates how the accuracy of five semi-supervised learning methods (Label Propagation, Label Spreading, Poisson GD, Poisson Adam, and Poisson Nesterov) changes depending on the number of labeled instances per class (shown on the X-axis). The Y-axis represents the final accuracy in percentage.

Overall trend: as the number of labels per class increases, all methods improve in accuracy. Highest accuracy is achieved by Poisson Nesterov (brown curve): starting at about 80% with just one label per class, it reaches around 92% at ten labels. Second place goes to Poisson GD (red curve), which rises to about 90% at ten labels. Poisson Adam (purple curve) comes in third, achieving around 80% accuracy by ten labels. Label Propagation (blue curve) and Label Spreading (orange curve) yield lower results compared to the Poisson-based methods. By ten labels, Label Propagation approaches about 70%, while Label Spreading reaches around 60–65%. In summary, as the number of labeled samples increases, all algorithms become more accurate. However, the Poisson Learning–based methods significantly outperform Label Propagation and Label Spreading, especially with a sufficient number of labels.

With this approach and modification, the task of classifying the periodic solutions of the dynamical system is solved with sufficient accuracy even in real-time mode, taking into account accumulation errors and time constraints.

4 Application of Poisson Learning for the Classification of Solutions of Dynamical Systems

4.1 General conception of classification of regularity solutions

The existing methods of KAM theory for studying dynamical systems provide a clear characterization of a system and predict its behavior under given initial conditions, whether regular, quasi-regular, or chaotic. However, performing a comprehensive analytical study of dynamical systems is challenging in practice due to their high dimensional and numerous parameters. Consequently, the solutions obtained are often highly localized and approximate. When numerical and computational methods are employed, errors and cumulative numerical inaccuracies arise, making the investigation of global regular cases particularly difficult.

A useful approach for numerical studies of phase space, which consists of a set of non-intersecting phase trajectories, is through Poincaré sections. These sections, constructed in phase space, reduce the dimensional of the system by one. Dynamical systems of third and fourth order are of particular interest, as their Poincaré sections produce graphical representations either on a plane or in three-dimensional space. When phase flow points form a curve, the system exhibits regular behavior, either periodic or multi-periodic, as observed in Hamiltonian systems.

A major research focus is the reconstruction and analysis of global Poincaré sections, which provide insights into all possible motions of the system. Although Poincaré sections are approximated using numerical integration over a fixed time interval, they still offer valuable insights into the overall behavior of Hamiltonian systems. The resulting phase portraits of two- and three-dimensional Poincaré sections can be analyzed using statistical or deterministic pattern recognition techniques .

In modern studies, the significance of new results in dynamical systems often relies on computational analysis and advanced numerical techniques. New and particular interest approach are machine learning methods - Label Propagation for ask classification solve of dynamical system. It represents a new technique for studying dynamical systems and holds great promise for the automatic detection of regular and chaotic behaviors in such systems with spatial program.

4.2 Problem Statement for Hamiltonian System

Let a dynamical system of Hamiltonian type of even order be given, for example two. Assume that the system possesses an energy integral, i.e., the Hamiltonian is defined as $H(q,p), (q,p) \in \Omega \subset \mathbb{R}^{2n}$, and the system is described by Hamilton's equations:

$$\dot{q} = \frac{\partial H(q,p)}{\partial p}, \quad \dot{p} = -\frac{\partial H(q,p)}{\partial q}.$$

Assume that the system admits a global or local Poincaré section S. Choose a smooth section S in the phase space defined by $g(q,p) = 0, \quad \nabla g(q,p) \neq 0$.

For each initial condition $(q(0), p(0))$, consider the phase trajectory $\gamma(t) = (q(t), p(t))$ and record its intersections with S. As a result, we obtain a set of points $\mathcal{X} = \{x_i\}_{i=1}^{N} \subset S \subset \mathbb{R}^2$.

Assume that the trajectories are divided into K classes corresponding to different dynamical regimes. For a subset of indices $L \subset \{1, 2, \ldots, N\}$, labels are provided: $y_i \in \{1, 2, \ldots, K\}, \quad i \in L$. It is assumed that if the points x_i and x_j (corresponding to close initial conditions) are nearby, then their trajectories belong to the same class.

The set of points forms a trajectory structure of the phase space, which in the case of numerical integration is discrete and can be divided into classes using machine learning methods.

The goal article is to construct a classifier $f \colon S \to \{1, 2, \ldots, K\}$, which assigns to each unlabeled point x_i, for $i \in U = \{1, \ldots, N\} \setminus L$, a label $\hat{y}_i = f(x_i)$. To this end, we employ graph-based Semi-Supervised Learning method based on a graph model.

Thus, using the Hamiltonian equations, the construction of a global (or local) Poincaré section, and a graph-based model, we obtain a rigorous mathematical formulation of the semi-supervised classification problem for the trajectory structure of the phase space using the Label Propagation method.

4.3 Review of Relevant Literature of Poincaré sections

Let's consider the works devoted to the construction of the analysis of Poincaré sections for various physical problems.

Zhang et al. (**?**) explore the stabilization of tearing modes in plasmas using modulated electron cyclotron current drive. Their study provides insights into the control of plasma instabilities in fusion devices and demonstrates the impact of current modulation on stability.

Lerma-Hernández et al. (20) present an analytical description of the survival probability of coherent states within regular regimes. This work contributes to the understanding of dynamical evolution in quantum systems by characterizing long-term behavior under different regimes.

Liu et al. (21) propose a method for discriminating tokamak sawtooth crash models using localized density and temperature measurements. Their findings enhance the capability to differentiate between competing theoretical models based on experimental diagnostics.

Kovaleva et al. (22) analyze the forced pendulum within the framework of engineering mechanics. Their study highlights the complex behavior of forced oscillatory systems, emphasizing deterministic chaos and stability conditions.

Caracciolo et al. (23) investigate the three-dimensional orbital architecture of exoplanetary systems using KAM stability analysis. Their research contributes to celestial mechanics by assessing long-term stability criteria for exoplanets.

The conducted analysis of the considered and other works shows that at present there are no known works devoted to the application of machine learning methods for classifying solutions of dynamic systems on Poincaré sections in the plane and space. This direction of research, as well as the obtained results, is new.

4.4 Example of Mechanical system

The problem of the motion of a rigid body with a fixed point is considered in the classical framework, addressing the direct problems of mechanics. Given the static, kinematic, and dynamic (structural) parameters of a rigid body with a fixed point and the initial conditions of motion, it is necessary to determine its trajectory in space at any given moment, classify the type of motion, and establish the nature of the body's dynamics

A mathematical model describing the motion of a free rigid body in a mobile reference frame is given by a system of six ordinary differential Euler equations:

$$J\dot{\omega} = J\omega \times \omega + r \times \nu, \quad \dot{\nu} = \nu \times \omega, \tag{6}$$

where $J = \text{Diag}(A, B, C)$ represents the inertia tensor, $\omega = (p, q, r)$ is the angular velocity of the body in the mobile frame, $\nu = (\nu_1, \nu_2, \nu_3)$ is the unit vertical vector, and $r = (r_1, r_2, r_3)$ is the vector from the fixed point to the center of mass of the body.

Equation (6) determines the phase space R^{12} as $R^6(\omega, \nu) \times R^6(J, r)$, defining the family of possible (both regular and chaotic) trajectories of the dynamical system. The initial conditions are given by $\omega_0 = \omega(0)$ and $\nu_0 = \nu(0)$.

In the regular case, the dynamical system exhibits "well-behaved" trajectories that remain stable under small perturbations of initial conditions, allowing long-term predictability. In contrast, chaotic motion is characterized by an extreme sensitivity to initial conditions, leading to exponentially unstable trajectories. The chaotic case limits predictability to a finite time interval, known as the time horizon.

The aim of previously article is to develop an interactive computational system to solve system (6), classify its behavior system. If system (6) can be integrated explicitly, it is possible to distinguish between regular and chaotic cases.

4.4.1 INTEGRABILITY AND NUMERICAL SOLUTION

It is known in previously, that the solution of system (6) can be reduced to quadratures if four integrals are found. However, for arbitrary values of the system parameters, only three first integrals exist:

$$H(\omega,\nu) = \frac{1}{2}J\omega \cdot \omega - r \times \nu = h, \quad G(\omega,\nu) = J\omega \cdot \nu = g, \quad I(\nu,\nu) = \nu \cdot \nu = 1. \quad (7)$$

A fourth integral exists only in three well-known cases: Euler-Poinsot, Lagrange-Poisson, and Kowalewski, as well as in some special cases. These cases are characterized by specific parameter sets, allowing the reduction of system (6) to a system of algebraic equations. In integrable cases, the phase space trajectories are deterministic and exhibit stable motion. For non-integrable cases, the system's trajectory cannot be expressed analytically, necessitating numerical integration using the fifth-order Runge-Kutta method. The nature of the motion is determined by analyzing phase-space trajectories. For a fixed point in $R^6(J,r)$, the first integrals (7) define a compact three-dimensional invariant manifold $Q_{h,g}^3$ in $R^6(\omega,\nu)$, which governs the system's phase flow. The spatial organization of $Q_{h,g}^3$ within $R^3(\omega)$ and $R^3(\nu)$ provides insight into the evolution of physical quantities described by equation (6).

4.4.2 QUALITATIVE ANALYSIS AND COMPUTATIONAL APPROACH

The qualitative analysis of phase space structures relies on Poincaré sections and the theory of invariant curves. The onset of chaotic behavior is identified when the Poincaré section appears as a scattered cloud of points, forming a two-dimensional region. In contrast, regular motion corresponds to phase trajectories confined to smooth curves.

To study the topology of $Q_{h,g}^3$, integrable cases are analyzed using global sections $P^2 \subset Q_{h,g}^3$. For non-integrable cases, these sections are represented on the Poisson sphere S^2 with $\|\nu\| = 1$. The global section P^2 forms a compact two-dimensional manifold within $Q_{h,g}^3$, with phase trajectories either entirely filling $Q_{h,g}^3$ or intersecting P^2.

A computational program was developed for the intelligent analysis of regular and chaotic dynamics in mechanical systems, demonstrating the feasibility of this approach. An example of recognizing regular and chaotic motion using a three-dimensional Poincaré section is illustrated in Figure. This Poincaré section was computed via the Runge-Kutta 4-5 method for system (6) and reconstructed on the Poisson sphere using equation (7).

4.4.3 RESULT OF CLASSIFICATION

So, in the integrable cases Poincare section will be of a plane (surface area), which shows a certain type of closed curves: circles, ellipses and set of circle. These cases correspond to the regular (quasi-periodic) solution of a nonlinear dynamical system. We use Poisson Learning for classification this cases. With help computer program we labeled start points from this classes. (Fig.2 - Fig.5.)

5 CONCLUSION

In this paper we have consider the problem of classification periodic and multi-periodic orbits of dynamical systems using graph-based semi-supervised Poisson Learning method. The detection of periodic orbits of dynamical systems has carried out by means of an analysis of the Poincare' sections of phase space on the plane or 2d - datasets.

In work a modification of Poisson learning is proposed. Furthermore, to find the minimum loss function, the Nesterov algorithm is employed, which demonstrates better results compared to gradient descent. With this approach and modification, the task of classifying the periodic solutions of the dynamical system is solved with sufficient accuracy even in real-time mode, taking into account accumulation errors and time constraints.

Figure 2: Classification of regular orbits.

Figure 3: Classification of multi - regular orbits in case 1.

Figure 4: Classification of multi - regular orbits in case 2.

The proposed approach for investigation dynamic systems expands the possibilities of analytical and numerical use of KAM theory and is the next step in building a computer system for conducting a complete automatic investigation of dynamic systems.

Figure 5: Classification of resonance orbits.

REFERENCES

[1] Xiaojin Zhu. Semi-Supervised Learning with Graphs. PhD thesis, Carnegie Mellon University, 2005. CMU-LTI-05-192

[2] Kondratiev Alexander Sergeyevich, Lyaptsev Alexander Viktorovich, Sections of Poincaré in Describing the Behavior of Nonlinear Systems // KIO. 2012. No. 1.

[3] Petalas Y., Parsopoulos K., Vrahatis M. (2008). Stochastic optimization for de tecting periodic orbits of nonlinear mappings. Nonlinear Phenomena in Complex Systems. 11. 285-291.

[4] Petalas Y., Antonopoulos Ch., Bountis T., Vrahatis M., (2019). Detecting Reso nances using Evolutionary Algorithms. doi:10.1201/9780429070655-106.

[5] Das S. Automatic circle detection on images with annealed differential evolution / S. Das, A. Biswas, A. Abraham // Norwegian University of Science and Technology- 2012.- P. 1-6.

[6] Neimark Yu.I., Kotelnikov I.V., Teklina I.G. Investigation of the structure of the phase space of a dynamical system as a pattern recognition problem // conf. Mmro 12. M. Makspress 2005. P. 177-180.

[7] X. Zhu, "Semi-Supervised Learning Literature Survey," Computer Sciences TR 1530, University of Wisconsin – Madison, 2005.

[8] J. E. Van Engelen and H. H. Hoos, "A survey on semi-supervised learning," Mach. Learn., pp. 373–440, 2020, doi: 10.1007/s10994-019-05855-6.

[9] Y. Song, J. Zhang, and C. Zhang, "A survey of large-scale graph-based semi-supervised classification algorithms," International Journal of Cognitive Computing in Engineering, pp. 188-198, 2022, doi: 10.1016/j.ijcce.2022.10.002.

[10] Z. Song, X. Yang, Z. Xu, and I. King, "Graph-Based Semi-Supervised Learning: A Comprehensive Review," IEEE Transactions on Neural Networks and Learning Systems, 2022.

[11] J. Calder, B. Cook, M. Thorpe, and D. Slepcev, "Poisson Learning: Graph Based Semi-Supervised Learning At Very Low Label Rates," in Proceedings of the 37th International Conference on Machine Learning, pp. 1306-1316, 2020.

[12] M. A. Aromal and A. Rasool, "Semi Supervised Learning Using Graph Data Structure – A Review," in 2021 Third International Conference on Intelligent Communication Technologies and Virtual Mobile Networks (ICICV), pp. 894-899, 2021.

[13] K. Avrachenkov and M. Dreveton, "Chapter 5. Graph-based semi-supervised learning," Inria Sophia-Antipolis, 2023, doi: 10.1561/9781638280514.ch5.

[14] S. Abhishake and Sivananthan, "Multi-penalty regularization in learning theory," Journal of Complexity, vol. 141-165, 2016, doi: 10.1016/j.jco.2016.05.003.

[15] J. Calder, B. Cook, M. Thorpe, and D. Slepcev, "Poisson learning: Graph-based semi-supervised learning at very low label rates," ICML, Proceedings of Machine Learning Research, pp. 1306-1316, 2020.

[16] Y. Chong, Y. Ding, Q. Yan, and S. Pan, "Graph-based semi-supervised learning: A review," Neurocomputing, vol. 216-230, 2020, doi: 10.1016/j.neucom.2019.12.130.

[17] C. Garcia-Cardona, E. Merkurjev, A. Bertozzi, A. Flenner, and A. Percus, "Multiclass Data Segmentation Using Diffuse Interface Methods on Graphs," IEEE Transactions on Pattern Analysis and Machine Intelligence, 2013, doi: 10.1109/TPAMI.2014.2300478.

[18] O. Chapelle, B. Scholkopf, and A. Zien, "Semi-Supervised Learning," IEEE Transactions on Neural Networks, vol. 20, no. 5, pp. 542–542, 2009, doi: 10.1109/TNN.2009.2015974.

[19] R. K. Ando and T. Zhang, "Learning on graph with Laplacian regularization," in Proceedings of the 19th International Conference on Neural Information Processing Systems (NIPS'06), pp. 25-32, 2006. Available: https://dl.acm.org/doi/10.5555/2976456.2976460.

[20] Lerma-Hernández, S., Chávez-Carlos, J., Bastarrachea-Magnani, M., Santos, L., Hirsch, J. (2018). Analytical description of the survival probability of coherent states in regular regimes. *Journal of Physics A: Mathematical and Theoretical*, 51. https://doi.org/10.1088/1751-8121/aae2c3.

[21] Liu, D., Fox, W., Bose, S., Ji, H., Jardin, S. C., Ferraro, N. (2024). On discriminating tokamak sawtooth crash models via localized density and temperature measurements. *Physics of Plasmas*, 31. https://doi.org/10.1063/5.0186504.

[22] Kovaleva, A., Smirnov, V., Starosvetsky, Y. (2018). Forced Pendulum. *Foundations in Engineering Mechanics*. https://doi.org/10.1007/978-981-10-4666-7_12.

[23] Caracciolo, C., Locatelli, U., Sansottera, M., Volpi, M. (2024). 3D Orbital Architecture of Exoplanetary Systems: KAM-Stability Analysis. *Regular and Chaotic Dynamics*, 29, 565-582. https://doi.org/10.1134/S1560354724040038.