Sorries Are Not the Hard Part:
An Expert-Review Case Study of a Semi-Autonomous Formalization

Vasily Ilin [* 1] **Brian Nugent** [* 2]

Abstract

Large language models can often close proof gaps in interactive theorem provers, but a verified theorem is not the same thing as a reusable library contribution. We study this distinction through a detailed case study: a semi-autonomous formalization of Grothendieck's vanishing theorem. The initial version compiles with no sorries, but an expert review found serious problems in definitions, theorem generality, file organization, and the API. We then ran a review-driven refactor and compression process and obtained a second expert review. The before-and-after comparison shows a sharp split: agents adapted well to local, mechanically checkable feedback, but remained weak at choosing definitions and designing APIs. We argue that autoformalization should be evaluated not only by closed sorries, but by whether the resulting formalization survives expert review.

1. Intro

The default public story for semi-autonomous formalization is proof completion: given an informal or formal statement, can an agent produce code accepted by a proof assistant? This is the right first question, but it is not the last. Modern mathematics is highly interconnected, and a formal library that supports it must compose: definitions must combine, theorem statements must have the right generality, namespaces must support search, and APIs must let future users reason about properties rather than unfold implementations.

This paper evaluates the quality of LLM-produced Lean code and asks what the current barriers are between it and a reusable library contribution. Our case study is a Lean formalization of Grothendieck's vanishing theorem ([Hartshorne](), [1977](), Ch. III, Thm. 2.7): if X is a Noetherian topological space and n is above the topological Krull dimension of X, then the n-th sheaf cohomology of any sheaf of abelian groups on X vanishes. The authors wrote the Lean statement by hand, supplied Claude Code with a PDF excerpt of Hartshorne's proof, and instructed the agent to follow that proof. The statement uses only existing mathlib definitions:

```
theorem GrothendieckVanishing
    (X : TopCat) [NoetherianSpace X]
    (n : Nat) (h : n > topologicalKrullDim X)
    (F : Sheaf AddCommGrpCat X) :
    Subsingleton (Sheaf.H F n)
```

That the statement uses only existing definitions matters: it prevents the agent from making custom definitions to render the theorem trivially true.

Proof sketch. The formal proof follows Hartshorne's route by induction on `topologicalKrullDim X`. First it reduces to the irreducible case using a closed-immersion short exact sequence and the fact that Noetherian spaces have finitely many irreducible components. For an irreducible space of dimension zero, every open is simple enough that any sheaf is flasque, and higher cohomology of any flasque sheaf vanishes. In the positive-dimensional irreducible case, the proof chooses a proper irreducible closed $Z \subset X$, uses strict dimension drop on Z, and combines the induction hypothesis with closed-immersion cohomology, extension by zero, and a finite-generation reduction through filtered colimits. These reductions need supporting definitions and API not currently in mathlib — for the closed-immersion short exact sequence, flasque vanishing, extension by zero, finite-generation via filtered colimits, topological Krull dimension, and sheaf cohomology — which serve as our tests for the agent's ability to define new objects and build around them.

Before and After. We treat the project as a before-and-after experiment. State A is the first verified version, inspected by one of the authors, a Lean/mathlib expert. State B is the version after an automated response to that review and a later mathlib-style cleanup, inspected by the same expert. The review exposes what proof-completion metrics

---
[*]Equal contribution [1]University of Washington, Seattle, WA, USA [2]University of Utah, Salt Lake City, UT, USA. Correspondence to: Vasily Ilin <vasilin97@gmail.com>.

3rd AI for Math Workshop at the 43^{rd} International Conference on Machine Learning, Seoul, South Korea, 2026. Copyright 2026 by the author(s).

miss: LLMs are much better at closing local goals than at deciding what objects should exist.

The contributions are:

- a case study of semi-autonomous formalization of a graduate-level algebraic geometry theorem in Lean;

- a qualitative before-and-after analysis of expert review feedback on definitions, theorem statements, proofs, and file/API structure.

Why this theorem is a useful stress test. Grothendieck vanishing is not a contest-style problem reducible to a single tactic script. The theorem is short only because it sits on a tower of categorical and topological infrastructure: the agent had to work simultaneously with presheaves, sheaves, stalks, exact sequences, filtered colimits, Krull dimension, and the derived-category definition of cohomology. The central claim is deliberately modest: we do not claim one formalization predicts all future work, only that kernel acceptance is an incomplete evaluation target, and that this case shows why.

2. Related Work

Formal libraries as shared interfaces. The case study builds on Lean (de Moura et al., 2015; de Moura & Ullrich, 2021) and mathlib, a single shared library supporting modern mathematics at scale (The mathlib Community, 2020). Evaluating a contribution to such a library is closer to code review than to grading a fixed benchmark theorem.

LLMs for proof generation. Autoformalization and neural theorem proving have largely been framed as translation (Wu et al., 2022), retrieval, and proof-search problems: LeanDojo (Yang et al., 2023) and Baldur (First et al., 2023) target retrieval-augmented proving and whole-proof repair, APRIL (Wang et al., 2026) learns proof repair and iterative refinement from compiler feedback, and recent systems— Seed-Prover (Chen et al., 2025), Aristotle (Achim et al., 2025), Numina-Lean-Agent (Liu et al., 2026), and QED-Nano (LM-Provers et al., 2026)—scale proof search through formal feedback, agentic tool use, and distillation. A few efforts push past binary correctness: Petrov et al. (2026) score whether a proof is clear, concise, and transferable, Xie et al. (2026) test whether models can judge mathlib pull-request merge-readiness, and Klingner et al. (2026) evaluate many LLMs for formalization in several settings. In all of these the unit of evaluation is the attempted theorem; ours is the library delta that survives after it closes — the duplicated definition or over-specific lemma a theorem benchmark has no reason to penalize.

Research-scale semi-autonomous formalization. Several recent projects move beyond contest problems: rapid large-scale topology (Urban, 2026), parallel Diophantine formalization in Isabelle (Bayer et al., 2025), a Lean/PhysLean formalization that uncovered a literature error (Tooby-Smith, 2026), autonomous number-theory and algebra formalizations (Chen et al., 2026b;a), Archon's previously open commutative-algebra conjecture in roughly 19,000 lines (Ju et al., 2026), LeanMarathon's multi-agent construct–audit–prove–repair harness over four Erdős problems (Zhang et al., 2026), and AutoformBot's thousands of agents formalizing 26 textbooks into over 45,000 declarations (Rammal et al., 2026). Closest to our setting, the Vlasov-Maxwell-Landau case study (Ilin, 2026) also emphasizes full-process logs, agent failure modes, and human review of key statements. These reports show AI can produce substantial verified artifacts quickly and that process logs expose failures a final proof hides.

What the prior work leaves open. What none of this isolates is the gap between a verified artifact and a reusable one. Proof-generation evaluations have an unambiguous terminal condition — the artifact checks or it does not — but for library construction the statement and its intermediate abstractions are themselves outputs, and a proof can pass the kernel while forcing future users through awkward coercions or duplicated definitions. Large-scale reports include rich process data, but their notion of quality is still dominated by completion. We instead make the expert review the object of study, letting us ask which complaints an automated loop fixes and which persist because they require judgment about future reuse rather than proof search.

3. Timeline

Reconstructing the project. Figure 1 and Table 1 reconstruct the project from its commit history, structured loop logs, telemetry summaries, and two expert reviews of the same development.[1] The mathematical statement and proof outline were supplied by humans.

The proving phase. The proving phase was fast because the route was fixed in advance. The sorry curve in Figure 1 is nonetheless jagged, because the agent scaffolded intermediate claims, discharged some, and repeatedly changed the proof decomposition. The clearest side quest is the heartbeat episode (Mar. 28 – Apr. 1). Mathlib's `synthInstance`

---

[1]The two expert reviews and the structured process logs analyzed in this paper are released as a public dataset: https://huggingface.co/datasets/uw-math-ai/grothendieck-vanishing-logs. The Lean source is available at https://github.com/Vilin97/Clawristotle/tree/main/grothendieck-vanishing.

Figure 1. Project timeline reconstructed from the commit log. The blue curve is raw Lean lines of code and the red curve is the sorry count. Background colors mark the process phases: green = proving, yellow = expert-review window, blue = review-driven refactor, purple = compression and final mathlib-style polish. The proving phase produces the first sorry-free version by April 4; LOC then keeps moving well after the sorry count reaches zero, as the project is rewritten in response to the expert review.

budget for `HasDerivedCategory` kept colliding with proofs mentioning `Ext` or `Sheaf.H`, and the agent's first instinct was to raise `set_option maxHeartbeats`, oscillating budgets between 200K and 12.8M across days without producing a stable project. The episode only ended after one author told the agent to "keep optimizing until the whole project compiles with default heartbeats". Stripping the overrides regressed the sorry count from 3 to 24; recovery came from caching instances via `inferInstanceAs` and splitting large proofs into named sub-lemmas. The durable rule that came out of this is: never raise `maxHeartbeats` above 200000. It is the first appearance of a pattern that recurs throughout the project: a proof too expensive to check is usually a proof that should be decomposed.

After the proof closed. As seen in Figure 1 and Table 1, the project did not end when the sorry count reached zero. Instead, one of the authors performed a comprehensive review of the initial formalization (one week), which was converted into a checklist, and then the agent (Claude and Codex) iterated until the checklist was finished (two weeks). Three additional views of the same project (Figures 2 to 4) record commit counts by loop mode, token usage, and tool-use mix; we refer to them where relevant below. We refer to the initial formalization as state A, and the formalization that followed the first review as state B.

4. Analysis

What state A got right. The initial state had the proof in the right mathematical shape. The overall structure of the proof was exactly as expected and followed the proof outline described above. While the goal of this article is to provide analysis of the quality of LLM-produced Lean code, we still need to note that it is remarkable that it is able to produce a proof this sophisticated with no human guidance other than the theorem statement and a standard textbook proof – this was not possible one year ago.

Now that we have a formalized proof, the next question is: what can be done with the 5,000 lines of code that were produced? Can the definitions and lemmas proved along the way to this theorem be repurposed and built off of? These questions are the focus of our analysis.

Lean code, in the context of theorem proving, has three main components: definitions, theorem statements, and proofs. We report on how the agent did in both state A and state B for each of these.

Definitions were the weakest point. Of the three main components to Lean code, definitions are by far the most important to get right and are where the agent struggled the most.

Bad definitions create future transport costs. If a construction is placed at the wrong level of generality, later users must compare it to the version they actually need and then transport every relevant theorem across that comparison. This transport can often be harder than simply redoing ev-

Table 1. Project phases reconstructed from commits, loop logs, and reviews.

Phase	Duration	What happened	Main difficulty
Formalization	Mar. 27–Apr. 4; nine active days	Claude Code followed the supplied Hartshorne proof plan, with Aristotle used for bounded lemmas. This produced state A, the first sorry-free version.	The agent could close local goals, but the emerging API was ad hoc. A heartbeat detour also stopped the project from compiling cleanly until large proofs were decomposed.
Expert review	Apr. 8–15; one week	The same expert read the first verified tree as library code and wrote a structured audit with large cross-file changes and per-file comments.	The review judged the code after kernel success, so it found design failures that no proof-completion metric could see.
Review response	Apr. 17–May 1; about two weeks	The main refactor loop ran Apr. 19–27.	Local checklist items were tractable; open-ended requests such as building a usable `Sheaf.H` API were much harder.
Compression and polish	Apr. 27–May 1	The compression loop ran Apr. 27–28, followed by a mathlib-style cleanup pass for names, docstrings, lint, and stale comments.	The LOC gate found real redundancy, but short code was only a proxy for library quality.

Table 2. Qualitative before-and-after summary from the expert reviews. The table separates review items that have a local syntactic target from items that require global API judgment.

Review theme	State A criticism	State B outcome
File structure	File names were confusing and unorganized.	Fixed. File names make sense and docstrings became readable.
Definitions	Dozens of specific and often unnecessary definitions.	Still the weakest category, did not noticeably improve after the review.
Theorem statements	Most intermediate results were not general enough to be reusable. Agent proved exactly what it needed and nothing more.	All specific changes requested in the review were done but the agent failed to identify further changes on its own.
API design	Proofs worked by repeatedly unfolding definitions rather than building an interface.	Partially fixed. Downstream files are now cleaner but the API itself is noisy and bloated.
Proof style	Proofs have long walls of `have` statements and frequent misuse of definitional equality.	Better but uneven. Some files became maintainable. The filtered-colimit files are still quite bad.

erything from scratch. When that is the case, it begs the question of whether there is any value in a formalization if it cannot be built upon effectively in the future. A proof can be ugly and still mostly function while a bad definition can create serious problems down the line.

The finitely generated subsheaf construction is a representative example. The agent defined finitely generated subsheaves of sheaves of abelian groups on a topological space. That was enough for the Grothendieck-vanishing proof, but the construction is not inherently about abelian groups or even topological spaces. In the future, one may want finitely generated subsheaves for sheaves of rings, or on sheaves over a site. A human library designer would first design the general construction and then provide convenient specializations. The agent created exactly what the current proof needed instead.

The same pattern appears in smaller definitions. Some declarations merely name a bijection that is needed once in a proof; others wrap a standard library construction under a name that mentions the current application rather than the mathematical object. These choices are cheap in the moment because they give the agent a handle to continue the proof. They are expensive later because they create public surface area whose intended use is unclear. In state A, there was a definition that roughly stated "n is less than the Krull dimension of X". This is mathematically identical to just writing `n < topologicalKrullDim X`. Not only do useless definitions like this make code more confusing, but they also hinder the ability of tactics like `simp`. These tactics use the syntax of the goal to decide on their next step so a useless definition like this will cause it to fail where it otherwise would have succeeded.

In total the agent made 62 of its own definitions and there was exactly one that was done the correct way, namely `TopCat.closedIncl`. This is a construction that exists in mathlib for open sets but was missing for closed sets. The agent was able to build a useful API, likely copying the one from open sets in mathlib. This is the kind of definition a library can keep, the object is mathematically natural, the name describes the object correctly, and the

Figure 2. Daily commit counts classified by loop mode (commit-message tag). Phase shading matches Figure 1. Interactive commits dominate the proving phase (the formalization was not fully automated); the April 8–17 gap is the expert-review window; the refactor loop (green) drives the April 17–26 activity; the compression loop (orange) and a final mathlib-style polish (red) close out the project.

Figure 3. Cumulative Claude token usage across 31,529 turns in 270 sessions. Output (blue), fresh input (purple), and cache-creation (orange) are on the left axis (millions); cache reads (red) on the right axis (billions). Cache reads exceed output by roughly two orders of magnitude: formalization is context-dominated because each step reloads Lean files, diagnostics, and nearby library code. At the posted Opus API rates ($75/M output, $18.75/M cache write, $1.50/M cache read, $15/M fresh input), the captured Claude usage corresponds to a total of roughly $13K, dominated by cache reads (about $10K). The authors used the $200 subscription.

adjacent API lets later proofs use it without needing to unfold its definition. The remaining 61 definitions were all done poorly and are not very useful for future formalizations. We give more specific examples of the problems with its definitions in a section below.

The agent did not improve its ability to make good definitions between state A and state B. Definitions remain the largest hurdle between the agent and writing usable, extensible code.

The API improved but not by much. After one decides on the right definition for an object, the next step is to build an API for interacting with it. A good test of the agent's ability to do this came with cohomology. The version of

mathlib that the agent had access to possessed a definition of sheaf cohomology (`Sheaf.H`) but there had yet to be an API built for it. The first review complained that the agent did not build an API for cohomology at all and instead just repeatedly unfolded the definition. A specific change requested in the first review was for the agent to build an API for `Sheaf.H` and to not unfold its definition in downstream files. In state B, the agent did create a dedicated cohomology API file, and this did substantially improve the rest of the proof. While in state A, many files were littered with specific and ad hoc proofs about cohomology, in state B they were contained to one file and the proofs in later files became much cleaner. Unfortunately, the API itself was built very poorly. Whenever a later proof needed a fact about `Sheaf.H`, the agent simply added a new lemma

Figure 4. Tool calls across the project (19,393 total). Left: top 20 tools by call count, dominated by shell/file operations (`Bash`, `Read`, `Edit`, `Grep`) and Lean LSP queries. Right: daily tool calls grouped by category, phase shading as in Figure 1. Proof construction leans on Lean LSP diagnostics, goal queries, and library search; the review response is dominated by repository edits, shell checks, and grep-style audits — visibly different workflows on the same Lean tree.

to the file. Most of these lemmas were highly specific to whatever proof the agent was writing at the time. In the end, the file totaled almost 800 lines of code with 24 lemmas in the documentation header. A human designing this would instead try and distill out the most important properties to design a small principled interface. This not only results in fewer lines of code, but more importantly, is much easier for future users to build off of.

The reviewer also requested the agent build an API for `topologicalKrullDim`. This was also defined in mathlib but did not have an API for it yet. This definition is much simpler than that of cohomology and the agent did a much better job with it. It is still not at the level of mathlib quality but it is much closer than the majority of machine-generated code. This is a good sign that the agent is capable of good design given sufficiently specific prompting.

Theorem statements improved more reliably. The response was much better at fixing local problems. The review had a number of specific requests for generalizations of theorems. In particular, state A had a number of theorems that had the hypothesis "let S be a short exact sequence coming from an injective presentation" while the statements were all true under the simpler hypothesis "let S be a short exact sequence". The agent had no problem making these changes.

In state A, there were a number of cases where the agent tried to prove "$x = y$", then realized it would be easier to just prove "if $x = 0$ then $y = 0$" since that turned out to be all it needed for the rest of the proof. This method of taking the path of least resistance makes sense when generating sorry-free code is the only goal but does not lead to useful, reusable code. This was pointed out in the review and it was fixed in state B. Even in cases where this change required a large refactor, the agent was able to fix them.

The review also prompted the agent to try and identify where these kinds of generalizations would make its code more useful and cleaner. Aside from a few artificial changes, the agent was not able to identify and correct any of these generality mistakes without them being requested. Much like with the definitions problems, the agent struggles to make decisions that have a global effect on the project and is much better suited for dealing with local problems.

Lean code of the type produced in this project, with an excess of specific lemmas and definitions, can still be useful to a search-heavy repository of generated results. In such a repository, an agent can sift through excess statements and find a useful fact. It is not useful to a human curated library like mathlib, where users need a smaller and more intentional theorem surface.

Proofs improved, but unevenly. The proof terms in state B are better than in state A. There are fewer walls of intermediate `have` statements, less definitional-equality abuse, more named intermediate lemmas replacing long unreadable proofs, and less direct unfolding of definitions. In general, the proofs that only used objects defined in mathlib were

much cleaner, as the agent was able to rely on the good API built in mathlib. The proofs that used definitions made by the agent were extremely bad in state A and were noticeably better in state B after the APIs for Krull dimension and cohomology were built. Some of the more technical proofs remained bad, for example, the filtered-colimit files remained hard to read because they contain a dozen hyper-specific definitions that are only useful in this one proof.

In some ways, the proof terms themselves are the least important part, as they are erased at runtime. There are performance and maintainability concerns however. Long tactic blocks can create performance failures, and fragile definitional-equality arguments are sensitive to breaks from changes upstream. The project history shows a recurring pattern: when a proof became too expensive to check, progress improved only after the goal was decomposed into named sublemmas rather than pushed through a larger heartbeat allowance. That lesson is not specific to this theorem. It is the software-engineering version of a mathematical norm: if a proof has a meaningful intermediate claim, name it and make later maintenance depend on that claim.

More definitions as examples. As mentioned above, definitions are the most important thing to get right and are where the agent struggled the most. We will give some specific examples of the kinds of mistakes the agent made that it was unable to correct even after being prompted.

The worst offender is the definition `sheafH_filtered_colimit_h1_sectionsFunctor`. This definition is equivalent to `sheafSections`, a definition available in mathlib, and has nothing to do with sheafH, filtered colimits, or H1. The naming is likely because of the particular use case the agent had for this definition. Creating superfluous definitions like this is not just unnecessary, it can be actively harmful to future development. For example, if an instance is put onto this definition, say an instance of it being an additive functor, then even if `sheafH_filtered_colimit_h1_sectionsFunctor` is shown to be equal to `sheafSections` (which it is), the instances will likely not be definitionally equal. This leads to some of the most confusing errors in Lean, where you can rewrite `sheafH_filtered_colimit_h1_sectionsFunctor` into `sheafSections` but since the instances don't agree definitionally, everything will break.

Some other bad examples came from equivalences the agent defined. The definitions `extClass_postcompAddEquiv_of_subsingleton_middle`, `sheafH_extClassAddEquiv_of_subsingleton_middle`, and `sheafH_succ_iso_of_subsingleton_middle` are all roughly "in this hyper-specific case, this function is bijective, so here it is as an `Equiv`". The correct thing to do here is just prove the function is bijective and use that. Anytime an

equiv is needed, `Equiv.ofBijective` can be inlined. The problem with making them definitions is that this essentially creates a barrier between the user and the actual function they should be working with, with no real upside.

`sheafH0EquivSections` and `sheafH0NatIsoSections` are essentially the same definition under different names, it should be clear why this is a bad thing.

In some cases, the agent made a choice that clearly went against previous design decisions. Sheaf cohomology is defined as a type, as opposed to a term of `AddCommGrpCat`. Both choices have their benefits, but choosing to go with the former was a deliberate design decision informed by considering all future applications. The agent chose to define `sheafH_succ_map` as a morphism between the `AddCommGrpCat` versions of cohomology. This is not a bad definition in principle but it clearly goes against a previous design decision and working with both adds work that is not needed.

Some definitions, like `familyMap` and `familyImage` are just silly. The definition of `familyMap f` is just `Sigma.desc f` so this definition saves exactly one character of typing and does nothing else. Similarly, `TopologicalSpace.IrreducibleCloseds.height` is just defined to be `Order.height`. This one has some use, as it allows the dot notation when working with irreducible closeds. However, because it chose to make it a `def` instead of an `abbrev`, all of the theorems in mathlib proven about `Order.height` will not be usable with it unless it is explicitly unfolded, which is exactly what the agent does when it uses it.

Why feedback adaptation is uneven. The successful review items had crisp completion predicates: no remaining uses of an old name, a file renamed, a theorem statement generalized, a wrapper deleted, or a stronger isomorphism available at a call site. The failed items required counterfactual judgment. A good definition is good because future developments can use it without transport pain. A good API is good because it contains the right small set of lemmas, including lemmas whose need has not yet appeared. The agent optimized for the next compiling proof, but was unable to make good long-term decisions.

Prompts had to forbid escape hatches. A recurring failure mode during long autonomous runs was loop drift toward declaring a task "blocked" or pinning a failure on infrastructure ("genuine mathlib gap"). The drift was fast and consistent enough that the project's slash-command prompts explicitly forbade both phrases — "You are NOT allowed to say that you are blocked. You MUST close the sorrys yourself!" and "A no-op cycle is never acceptable."

When an agent has a verbal escape hatch, it will reach for it before it reaches for a decomposition; the gate partially removes the escape hatch.

Human feedback as a specification. The review supplied the quality specification the automated loop otherwise lacked. "Build a useful cohomology API" reads like a programming task but is really a design task, and a loop can satisfy every local complaint while still producing an interface that is too broad, too specific, or too hard to navigate. The division of labor follows: expert reviewers should spend their scarce attention on definitions, theorem surfaces, and global organization, and hand agents the narrow refactors that carry an explicit completion predicate.

Gates are only as good as their target. The two loops shared the worker/evaluator structure but had different reward signals. The compression loop reduced normalized LOC under a compilation gate: a clean mechanical signal, which made the loop a reliable optimizer but only loosely aligned with review intent. The refactor loop had to operationalize natural-language review items, and its evaluator could report progress as strong, partial, or absent without ever being sure a broad review item was truly satisfied. The lesson is that a mechanical gate is powerful when it matches the quality target and dangerous when it is only a proxy. Compilation gates are correctness gates; LOC and dead-code gates are maintenance proxies; review-item checklists are alignment proxies. None of them measures whether the public definitions are the ones a future formalizer would choose — exactly the gap between state A and the first review.

External proving as a bounded tool. Aristotle submissions are local assistance, not an autonomous strategy engine. Successful calls closed bounded lemmas; disproven calls were informative because they falsified incorrect lemmas. But the hard project decisions — which intermediate statements should exist, which definitions should be public — were never theorem-prover queries.

5. Conclusion

Without a sophisticated harness, LLMs are very capable of closing proofs and local changes, but cannot yet make the global design decisions that a reusable formalization requires. Choosing good definitions and building a good API remain the biggest barriers. We suggest a practical evaluation standard for AI-for-math systems: after the proof checks, ask an expert to review the public definitions, theorem statements, namespaces, and API surface, then measure how well the system responds.

Code and Data Availability

The Lean 4 formalization is available at `https://github.com/Vilin97/Clawristotle/tree/main/grothendieck-vanishing`. The two expert reviews and the structured process logs analyzed in this paper—per-turn token usage, the refactor and compression loop histories, per-commit LOC and sorry counts, the agent tool-use timeline, Aristotle proving jobs, the human prompts, and the loop prompts—are released as a public dataset at `https://huggingface.co/datasets/uw-math-ai/grothendieck-vanishing-logs`.

Acknowledgements

This work used computational resources from the Hyak high-performance computing cluster at the University of Washington. The AI subscription was funded by the UW Math AI Lab. We thank the mathlib community, whose library and conventions defined the standard of quality against which this formalization was reviewed.

References

Achim, T., Best, A., Der, K., Fédérico, M., Gukov, S., Halpern-Leistner, D., Henningsgard, K., Kudryashov, Y., Meiburg, A., Michelsen, M., Patterson, R., Rodriguez, E., Scharff, L., Shanker, V., Sicca, V., Sowrirajan, H., Swope, A., Tamas, M., Tenev, V., Thomm, J., Williams, H., and Wu, L. Aristotle: IMO-level automated theorem proving, 2025. URL https://arxiv.org/abs/2510.01346.

Bayer, J., David, M., Hassler, M., Matiyasevich, Y., and Schleicher, D. Diophantine equations over $\mathbb{Z}$: Universal bounds and parallel formalization, 2025. URL https://arxiv.org/abs/2506.20909.

Chen, E., Cummins, C., Eltschig, B., Grubisic, D., Haller, L., Hong, L., Kurghinyan, A., Lau, K., Leather, H., Lee, S., Markosyan, A., Ono, K., Patel, M., Pendharkar, G., Rathi, V., Schneidman, A., Seeker, V., Sengupta, S., Sinha, I., Xin, J., and Zhang, J. Almost all primes are partially regular, 2026a. URL https://arxiv.org/abs/2602.05090.

Chen, E., Cummins, C., GSM, Grubisic, D., Haller, L., Hong, L., Kurghinyan, A., Lau, K., Leather, H., Lee, S., Markosyan, A., Ono, K., Patel, M., Pendharkar, G., Rathi, V., Schneidman, A., Seeker, V., Sengupta, S., Sinha, I., Xin, J., and Zhang, J. Fel's conjecture on syzygies of numerical semigroups, 2026b. URL https://arxiv.org/abs/2602.03716.

Chen, L., Gu, J., Huang, L., Huang, W., Jiang, Z., Jie, A., Jin, X., Jin, X., Li, C., Ma, K., Ren, C., Shen, J., Shi, W., Sun, T., Sun, H., Wang, J., Wang, S., Wang, Z., Wei, C., Wei, S., Wu, Y., Wu, Y., Xia, Y., Xin, H., and Yang, F. Seed-prover: Deep and broad reasoning for automated theorem proving, 2025. URL https://arxiv.org/abs/2507.23726.

de Moura, L. and Ullrich, S. The lean 4 theorem prover and programming language. In *Automated Deduction – CADE 28*. Springer, 2021. doi: 10.1007/978-3-030-79876-5_37. URL https://doi.org/10.1007/978-3-030-79876-5_37.

de Moura, L., Kong, S., Avigad, J., van Doorn, F., and von Raumer, J. The lean theorem prover (system description). In *Automated Deduction – CADE-25*, pp. 378–388. Springer, 2015. doi: 10.1007/978-3-319-21401-6_26. URL https://doi.org/10.1007/978-3-319-21401-6_26.

First, E., Rabe, M. N., Ringer, T., and Brun, Y. Baldur: Whole-proof generation and repair with large language models. In *Proceedings of the 31st ACM Joint European Software Engineering Conference and Symposium on the Foundations of Software Engineering*. ACM, 2023. doi: 10.1145/3611643.3616243.

Hartshorne, R. *Algebraic Geometry*, volume 52 of *Graduate Texts in Mathematics*. Springer, 1977. doi: 10.1007/978-1-4757-3849-0. URL https://link.springer.com/book/10.1007/978-1-4757-3849-0.

Ilin, V. Semi-autonomous formalization of the Vlasov-Maxwell-Landau equilibrium, 2026. URL https://arxiv.org/abs/2603.15929.

Ju, H., Gao, G., Jiang, J., Wu, B., Sun, Z., Chen, L., Wang, Y., Wang, Y., Wang, Z., He, W., Wu, P., Xiao, L., Liu, R., Dai, B., and Dong, B. Automated conjecture resolution with formal verification, 2026. URL https://arxiv.org/abs/2604.03789.

Klingner, T., Bladek, D., Crawford, E., Chen, B., Fu, A., Nair, K., Alper, J., Inchiostro, G., and Ilin, V. Evaluation of LLMs for mathematical formalization in Lean, 2026. URL https://arxiv.org/abs/2606.05632.

Liu, J., Zhou, Z., Zhu, Z., Dos Santos, M., He, W., Liu, J., Wang, R., Xie, Y., Zhao, J., Wang, Q., Zhi, L., Li, J., and Li, W. Numina-lean-agent: An open and general agentic reasoning system for formal mathematics, 2026. URL https://arxiv.org/abs/2601.14027.

LM-Provers, Qu, Y., Setlur, A., Dekoninck, J., Beeching, E., Li, J., Wu, I., Tunstall, L., and Kumar, A. QED-Nano: Teaching a tiny model to prove hard theorems, 2026. URL https://arxiv.org/abs/2604.04898.

Petrov, I., Dekoninck, J., Dimitrov, D. I., and Vechev, M. Not all proofs are equal: Evaluating LLM proof quality beyond correctness, 2026. URL https://arxiv.org/abs/2605.10379.

Rammal, A., Patel, N., Gloeckle, F., Hayat, A., Kempe, J., Munos, R., Arnal, C., and Cabannes, V. Formalizing mathematics at scale, 2026. URL https://arxiv.org/abs/2605.29955.

The mathlib Community. The lean mathematical library. In *Proceedings of the 9th ACM SIGPLAN International Conference on Certified Programs and Proofs*, pp. 367–381, 2020. doi: 10.1145/3372885.3373824.

Tooby-Smith, J. Formalizing the stability of the two Higgs doublet model potential into Lean: Identifying an error in the literature, 2026. URL https://arxiv.org/abs/2603.08139.

Urban, J. 130k lines of formal topology in two weeks: Simple and cheap autoformalization for everyone?, 2026. URL https://arxiv.org/abs/2601.03298.

Wang, E., Chess, S., Lee, D., Ge, S., Mallavarapu, A., Alper, J., and Ilin, V. Learning to repair Lean proofs from compiler feedback, 2026. URL https://arxiv.org/abs/2602.02990.

Wu, Y., Jiang, A. Q., Li, W., Rabe, M. N., Staats, C., Jamnik, M., and Szegedy, C. Autoformalization with large language models. In *Advances in Neural Information Processing Systems*, 2022.

Xie, Z., Liu, X., and Zhang, S. MathlibPR: Pull request merge-readiness benchmark for formal mathematical libraries, 2026. URL https://arxiv.org/abs/2605.07147.

Yang, K., Swope, A., Gu, A., Chalamala, R., Song, P., Yu, S., Godil, S., Prenger, R., and Anandkumar, A. LeanDojo: Theorem proving with retrieval-augmented language models. In *Advances in Neural Information Processing Systems*, 2023. URL https://arxiv.org/abs/2306.15626.

Zhang, Y., Sun, Y., Suzuki, T., Lee, J. D., and Liu, F. LeanMarathon: Toward reliable AI co-mathematicians through long-horizon Lean autoformalization, 2026. URL https://arxiv.org/abs/2606.05400.

A. Additional Figures

This appendix collects additional diagnostic material that helps audit the case study.

Loop effectiveness. The loop-effectiveness plot gives a per-cycle view of the refactor and compression loops. Refactor cycles are scored by progress and task-completion status, compression cycles by LOC delta, which is why the two loops should not be compared as if they shared an objective: one was interpreting a natural-language code review, the other optimizing a mechanical signal. The plot also shows why the paper does not treat cycle count as evidence of quality by itself — some stretches are productive, others are repeated low-value attempts.

Figure 5. Per-cycle refactor and compression outcomes summarizing loop behavior across the project.

Import graph. The import graph records the final organization of the Lean development. Many review complaints were about where concepts lived rather than about isolated proof terms, so the organization is itself a result. The intended reading is bottom-up: dimension, zero-outside, flasque, closed-immersion, filtered-colimit, and generated-subsheaf infrastructure feed the irreducible step and then the main theorem. A future user navigates this artifact through imports and namespaces before reading any proof, which is why file naming carried weight in the review.

Figure 6. Import graph for the Grothendieck-vanishing Lean files.