Unsupervised Disentanglement with Tensor Product Representations on the Torus

Abstract

The current methods for learning representations with auto-encoders almost exclusively employ vectors as the latent representations. In this work, we propose to employ a tensor product structure for this purpose. This way, the obtained representations are naturally disentangled. In contrast to the conventional variations methods, which are targeted toward normally distributed features, the latent space in our representation is distributed uniformly over a set of unit circles. We argue that the torus structure of the latent space captures the generative factors effectively. We employ recent tools for measuring unsupervised disentanglement, and in an extensive set of experiments demonstrate the advantage of our method in terms of disentanglement, completeness, and informativeness. The code for our proposed method is available as a supplementary material.

1 Introduction

Unsupervised learning methods of disentangled representations attempt to recover the explanatory factors z of variation in the data. The recovered representation, c, is expected to be: (i) *disentangled*, i.e., each element in c should vary one of the generative factors in z (ii) *complete* in the sense that all generative factors z can be controlled by the latent representation c, and (iii) *informative*, that is the ability to relate via a low capacity model (e.g., a linear model) the generative factors z and the latent representation c.

It has been shown that solving this task without further assumptions is impossible, since there is an infinite number of bijective functions f that map between c and $z = f(c)$ (Locatello et al., 2019) with all corresponding generative models having the same marginal distributions of the observations. In this work, we propose to use representations that are a tensor product of elements, which take values on unit circles S^1, claiming that this structure is suitable for the effective recovery of the underlying modes of variation.

This claim follows from entropy considerations. One wishes to have a representation that has a low *entropy of entanglement*. The entropy of entanglement is measured by evaluating the number of non-zero eigenvalues of the Schmidt decomposition of the representation. If a representation can be described by only one term, which is an outer product of the orthogonal basis functions, it has the lowest possible entanglement entropy, zero. If a representation requires the use of more than one term in the decomposition, it is entangled and its entanglement entropy can be quantified, e.g. by the Von Neumann entropy constructed from non-zero eigenvalues.

The tensor product of n unit circles, S^1, takes the shape of an n-torus $T^n = (S^1)^n$, and has a low entanglement property. This representation has the advantage that it can capture the periodicity structure of the generative factors, where each circle controls a different aspect of the original distribution. Unlike other generative models, which rely on the Gaussian distribution as a prior, T^n is a compact manifold, and therefore any function that acts on it, such as a decoder, has to interpolate only, but not extrapolate when generating new instances.

In this work, we present the T^D-VAE, a Variational Auto Encoder whose latent space resides on the T^D torus manifold. In an extensive set of experiments with four different datasets, we compare the torus latent representations with others proposed in the literature. We show a clear advantage of the torus representation in terms of various measures of disentanglement, completeness, informativeness and propose a new metric, the DC-score, which assesses the combined disentanglement and com-

pleteness performance. We present a detailed quantitative and qualitative analysis that supports our method.

2 RELATED WORK

Generative models aim to create new instances that are indistinguishable from a given distribution. Auto encoders (Kramer, 1991) achieve this by constructing the identity function using a composition of two components, an encoder and a decoder. The encoder is tasked with compressing the input into a latent representation with a dimension smaller than the input's, whereas the decoder is responsible for reconstructing the original input from the latent space.

Such auto encoders usually overfit to their training data and are very limited when tasked with generating new samples. Instead of mapping each input instance to a constant vector, Variational Auto Encoders (Kingma & Welling, 2013) (VAE) map each instance to a pre-defined distribution, by minimizing both the encoder-decoder reconstruction loss and a KL-divergence term that depends on the prior distribution. VAE's are capable of generating new instances by sampling a latent vector from the predefined distribution; however, the interpretation of latent space components is typically obscure and the mapping between them and the dataset properties may be complex.

In order to increase the latent space interoperability, various modifications of the original VAE were introduced. These variants try to achieve a factorization of the latent space components with each component corresponding to a specific simple characteristic of the dataset. In β-VAE (Higgins et al., 2016), the weight of the KL-divergence term is increased w.r.t. the reconstruction term, which results in better factorization of the latent space. However, this introduces a new hyper-parameter and departs from the theoretical derivation of the ELBO term. For example, large β parameters may prevent the conditional distribution from modeling the data faithfully. DIP-VAE (Kumar et al., 2017) introduces a regularizer that constrains the covariance matrix of the posterior distribution. This term is added to the original VAE loss function, along with two hyper-parameters, and helps achieve better factorization. Factor-VAE (Kim & Mnih, 2018) adds a Total Correlation (TC) approximation penalty over the produced latent codes and introduces an additional hyper-parameter.

2.1 DISENTANGLEMENT METRICS

In order to evaluate the expressiveness of different generative models, a plethora of disentanglement definitions and metrics were suggested in the literature (Do & Tran, 2019; Eastwood & Williams, 2018), see Locatello et al. (2019) for a comprehensive review. In this work, we adopt the definitions and metrics introduced in Eastwood & Williams (2018) which provides a successful set of disentanglement metrics.

The authors of Eastwood & Williams (2018) introduce three metrics, *Disentanglement*, *Completeness* and *Informativeness* (DCI), to quantify the disentanglement properties of the latent space and its ability to characterize the generative factors of a dataset. Given a dataset that was generated using a set of K generative factors, $\vec{z} \in \mathbb{R}^K$, and that it is required to learn latent codes, $\vec{c} \in \mathbb{R}^D$ of D-dimensional representation. Ideally, in an interpretable representation, each generative factor z_i would correspond to only one latent code c_a. It is also beneficial if the mapping is linear, as the correlation between generative factors and codes can then be easily assessed. Generating new instances that are indistinguishable from the original dataset distribution requires that the latent codes cover the whole range of the generative factors. Furthermore, such a representation provides the ability to modify a specific property of a generated instance by directly tuning the corresponding latent code.

The DCI metrics aim to quantify the relationship between codes and generating factors by having a single number that characterizes the relative importance of each code,[1] c_a, in predicting a factor, z_i, which in turn defines an importance matrix R_{ai}. To construct the importance matrix, K regressors are trained to find a mapping between z_i and $\vec{c}$, $\hat{z}_i = f_i(\vec{c})$. In this work, we follow Eastwood & Williams (2018) and infer the importance matrix using a lasso linear regressor's weights, W_{ia}, by $R_{ia} = |W_{ia}|$.

---

[1]throughout the paper we use $a, b, c, \ldots$ and $i, j, k, \ldots$ letters for indices of the codes $\vec{c}$ and the factors $\vec{z}$ components respectively.

Once the importance matrix R_{ai} is obtained, the DCI metrics can be defined explicitly. The **disentanglement** is given by

$$\mathcal{D} = \frac{\text{rank}(R)}{K} \sum_{a=1}^{D} \rho_a \mathcal{D}_a \,, \tag{1}$$

where

$$\mathcal{D}_a = 1 - H_K(P_a) = 1 + \sum_{k=1}^{K} P_{ak} \log_K P_{ak}, \quad P_{aj} = \frac{R_{aj}}{\sum_{k=1}^{K} R_{ak}}, \quad \rho_a = \frac{\sum_j R_{aj}}{\sum_{bk} R_{bk}} \,. \tag{2}$$

High disentanglement means that each entry of the latent vector $\vec{c}$ corresponds to only one element in $\vec{z}$ (in a linear sense), that is, each code element, c_a, affects one generating factor. The disentanglement metric defined above differs from Eastwood & Williams (2018) by a correction factor $\frac{\text{rank}(R)}{K}$. When the rank of R is equal to the generative factor's dimension, this correction equals 1, and does not affect the metric. However, it does make a difference when the number of codes is smaller than what is needed to account for all generating factors. Typically, one assumes that there are at least as many expressive codes as the number of factors. When this is not the case, it means that even if we have disentanglement among the expressive codes, their number is not sufficient, and our correction accounts for this. Note that the correction has no influence if there are irrelevant code elements in addition to a sufficient number of expressive ones. The ρ factors handle cases where some of the code dependence on the factors is very weak (namely irrelevant codes), while other codes depend mainly on one factor and hence should not be of equal importance.

The **completeness** is defined by

$$\mathcal{C} = \frac{1}{K} \sum_{j=1}^{K} \mathcal{C}_j \,, \quad \mathcal{C}_j = 1 - H_D(\tilde{P}_j) = 1 + \sum_{a=1}^{D} \tilde{P}_{aj} \log_D \tilde{P}_{aj} \,, \quad \tilde{P}_{aj} = \frac{R_{aj}}{\sum_{b=1}^{D} R_{bj}} \,. \tag{3}$$

In contrast to the disentanglement metric, which considers a weighted mean over the generative factors, motivated by the fact that irrelevant units in $\vec{c}$ should be ignored, here all codes are treated equally. A situation in which each factor z_i is explained by only one element of the code c_a results in high completeness.

The **informativeness** is the MSE between the ground-truth factors, z, and the predicted values, $f_j(\vec{c})$,

$$\mathcal{I} = \frac{1}{K} \sum_{j=1}^{K} \mathbb{E}_{\text{dataset}} \left[|z_j - f_j(\vec{c})|^2 \right] \,. \tag{4}$$

Disentanglement and completeness values range between zero and one, where one is the best value, while the best value for informativeness is zero.

Disentanglement and completeness alone do not provide sufficient information on whether a representation factorizes properly. For example, consider the case of a representation where only one generative factor is described by all the codes. While this representation is completely disentangled, it is not complete, and is therefore meaningless. In order to have a meaningful representation, both disentanglement and completeness need to be high. Thus, we introduce a new score, called the DC-score, which accounts for both disentanglement and completeness. We define the DC-score as the geometric mean of the two metrics, DC-score $= \sqrt{\mathcal{D}\mathcal{C}}$. This way, only cases where both scores are high will result in a high DC-score. Furthermore, the score will favor cases where both disentanglement and completeness are comparable rather than having different values while having the same arithmetic mean.

3 METHOD

Assume a pre-determined set of vectors sampled from an unknown distribution χ, each vector containing K independent factors, $\vec{z} \in \mathbb{R}^K$. The training dataset contains samples $x_I = F(\vec{z}_I)$, $I = 1, \ldots, N$ that are generated using a generative function F. In unsupervised disentanglement, the learner has no access to $\vec{z}$ nor to F, and receives only the set of samples, $\{x_I\}_{I=1}^N$.

The learner has to recover a set of representation vectors $\vec{c}_I$ that are linked to $\vec{z}_I$ in a way that is bijective and disentangled, see Section 2.1. Furthermore, in order to generate new samples, it is also necessary to be able to sample new representation vectors $\vec{c}_{\text{new}}$, and to obtain a generative function G such that the new generated samples are from the same distribution of $F(\vec{z})$, where $\vec{z} \sim \chi$.

In this work, we view the latent representation vector $\vec{c}$ as the angles associated with a list of D two-dimensional unit vectors $m_a \in \mathbb{R}^2$, $1 \le a \le D$, i.e., $\forall a$, $\|m_a\| = 1$. Using the two-dimensional vectors we define

$$v_{prod} \equiv \text{vec}\left(v_{prod}^{\alpha_1\ldots\alpha_D}\right), \quad v_{prod}^{\alpha_1\ldots\alpha_D} = m_1^{\alpha_1} \otimes \cdots \otimes m_n^{\alpha_D}, \quad v_{orient} \equiv \left(m_1^0, \ldots, m_D^0\right), \quad (5)$$

where $\otimes$ is the outer product operator, $\alpha_a \in \{0, 1\}$ and vec is the vectorization operation (equivalent to flattening the tensor). Next, define the operator V, that given $m_1, \ldots, m_D$, concatenates v_{prod} together with v_{orient}, $V(m_1, \ldots, m_D) = [v_{prod}; v_{orient}]$. The vector $v = V(m_1, \ldots, m_D)$ resides in a vector subspace of $\mathbb{R}^{2^D+D}$, defined by only a set of D parameters. The additional D elements of v_{orient} are required to ensure that the mapping V is bijective. For example, this can be seen by examining the case of $D = 2$: let $m_1 \equiv (\cos\theta_1, \sin\theta_1)$, $m_2 \equiv (\cos\theta_2, \sin\theta_2)$, $m_1' \equiv -m_1$ and $m_2' \equiv -m_2$. Then $m_1 \otimes m_2 = m_1' \otimes m_2'$.

A natural way of acquiring a random point on the circle, S^1, is by sampling two independent Gaussians, $\hat{m}_a^{\alpha_k} \sim \mathcal{N}(\mu_a^{\alpha_k}, \sigma_a^{\alpha_k})$. Each tuple of these vectors is then normalized to have a unit norm,

$$m_a^{\alpha_k} = \frac{\hat{m}_a^{\alpha_k}}{\sqrt{\left(\hat{m}_a^0\right)^2 + \left(\hat{m}_a^1\right)^2}}. \quad (6)$$

Assume that the elements, $\hat{m}_a^{\alpha_k}$, follow the normal distribution with a zero mean and a standard deviation of 1, $\hat{m}_a^{\alpha_k} \sim \mathcal{N}(0, \sigma)$, then the vectors m_a follow the uniform distribution on S^1.

For the purpose of obtaining the distribution parameters of $\hat{m}_a^{\alpha_k}$, the encoder e is applied on an instance, x,

$$e(x) = \left[\begin{array}{ccccc} \mu_1^0 & \sigma_1^0 & & \mu_D^0 & \sigma_D^0 \\ \mu_1^1 & \sigma_1^1 & \cdots & \mu_D^1 & \sigma_D^1 \end{array}\right]. \quad (7)$$

The reparametization trick (Kingma & Welling, 2013) is then used to obtain a set of normally distributed vectors. Denote by S the sampling operator, we sample the coding vector as

$$\vec{M}_I \equiv \left\{\left(\begin{array}{c} m_1^0 \\ m_1^1 \end{array}\right), \ldots, \left(\begin{array}{c} m_D^0 \\ m_D^1 \end{array}\right)\right\} = S(e(x_I)), \quad (8)$$

where each index (a, α_a) of m, $a = 1 \ldots D$, $\alpha = 0, 1$ is sampled from $\mathcal{N}(\mu_a^\alpha, \sigma_a^\alpha)$.

The decoder G then acts on $V(m_1, \ldots, m_D)$ to generate a new instance, $\tilde{x}$. The requirement that the generated instance is indistinguishable from the original distribution $F(\chi)$ translates to minimizing the ELBO loss function. First, it maximizes the log-likelihood probability of $\tilde{x}$ to be similar to the training sample it reconstructs by having an l2 loss term. Second, to encourage a uniform distribution on the torus, it contains a KL-divergence term with respect to $\mathcal{N}(0, \sigma)$. The overall expression for the loss function used during the optimization of the networks e and G is

$$\mathcal{L} = \sum_I \left[\left|G\left(V\left(\vec{M}_I\right)\right) - x_I\right|^2 - \beta D_{KL}\left(p(\hat{m}) \| \mathcal{N}(0, 1)\right)\right], \quad (9)$$

where β is a hyperparameter introduced in β-VAE (Higgins et al., 2016).

As the latent representation resides on the torus, sub-vectors $2D$ components of m_a may be described by D angles, $\theta_a \in [0, 2\pi]$ (the angles θ_a are identified with the codes c_a). In order to generate new instances, identify, $m_a^0 = \cos\theta_a$, $m_a^1 = \sin\theta_a$. and apply the decoder $G(V(m))$ to these elements.

The torus topology, T^D, is both compact and periodic. Since it is compact, for every sampled θ_a, there is a nearby θ_a' from the training set, thus, the network G can be viewed as an interpolator. This is in contrast to vectors sampled over $\mathbb{R}^D$, in which G has to extrapolate. Furthermore, being periodic, this topology is able to exploit a periodic structure in the generative factors. Consider a common generative factor associated with rotations. A rotation cannot be represented by a single non-compact variable; therefore encoding a rotation in a latent space requires the entanglement of two components. However, on the torus, only one compact dimension can be used to identify this generative factor.

Figure 1: An example of how a tensor product of two circles, $T^2 = S^1 \times S^1$, is converted to a flattened latent representation that can be fed into the decoder. Each point on the torus can be described by two angles. Each angle represents an m_a tuple. The tensor product of the m_a tuples is concatenated with their respective $\alpha = 0$ component to produce the input to the decoder.

Figure 2: Heatmap of the generative factors vs. the codes for the teapots dataset with our architecture with six circles. The factors are ordered by azimuth and elevation angles, followed by RGB values. The disentanglement, completeness and DC-scores are 0.67, 0.59 and 0.64, respectively. One can clearly see the high disentanglement property where each code mostly controls only one factor and high completeness where most factors are controlled by one code (e.g. θ_0 controlling z_3).

4 EXPERIMENTS

We compare our method to the leading VAE architectures from the current literature. The baseline methods are (i) β-VAE (Higgins et al., 2016), (ii) DIP-VAE-II (Kumar et al., 2017), and (iii) Factor-VAE (Kim & Mnih, 2018). The code for all methods was taken from the Pytorch-VAE repository (Subramanian, 2020) (Apache License 2.0). The network architectures for both the encoder, decoder and the Factor-VAE's discriminator (which we do not use) follow those in Eastwood & Williams (2018), see Table 1. Each horizontal line in Table 1 denotes a skip-connection.

All methods were trained using ADAM (Kingma & Ba, 2014) with a learning rate of 0.0001 and a batch size of 144. The hyperparameters used for DIP-VAE were $\lambda_{\text{diag}} = 10$ and $\lambda_{\text{off-diag}} = 1.0$. All methods were trained for a maximum number of 50 epochs, and the metrics were evaluated using the model that performs best on the validation set with respect to MSE. Furthermore, each baseline method was evaluated using two latent representations sizes, $D = 10, 128$ for all datasets. For our method, T^8-VAE, we use 8 circles, $\left(S^1\right)^8$. This results in $V \in \mathbb{R}^{136}$, leaving the number of parameters in the decoder comparable to the other baseline methods. Each experiment was evaluated with five different seeds and the mean value is reported.

In order to compute the DCI metrics, we used a linear lasso regressor based on the implementation of Eastwood & Williams (2018) (MIT License) and Zaidi et al. (2020) (Apache License 2.0). For each generative factor, a lasso regressor fits between the normalized codes obtained by the encoder, e, to a normalized factor, namely $f_i(\vec{c})$ for each z_i. For each factor, the α parameter for the regressor using 10-fold cross-validation from the set $\left\{10^{-6}, 10^{-5}, 10^{-4}, 10^{-3}, 10^{-2}, 0.1, 0.2, 0.4, 0.8, 1\right\}$, picking the one with the minimal the MSE error. The weights of the lasso regressor are then used to construct the $W \in \mathbb{R}^{K \times D}$ matrix from which the metrics are computed as explained in section 2.1.

(a)

(b)

Figure 3: The latent representation of the T^8-VAE. Each S^1 circle corresponds to a different factor of the dataset that is varied as the angle changes. (a) The 5 most expressive circles on the Teapot dataset. (b) The 6 most expressive circles on the 2dshapes dataset.

The Fréchet Inception Distance (Heusel et al., 2017) (FID) is used to assess the quality of image generation. Specifically, we use the implementation of Seitzer (2020) (Apache License 2.0) and report the FID at the final average pooling features of the Inception3 NN (Szegedy et al., 2016).

The teapots dataset (Moreno et al., 2016) contains $200,000$ 64×64 images of camera-centered teapots rendered using a set of 5 generative factors, azimuth that is sampled from $\sim U[0, 2\pi)$, elevation that is sampled from $\sim U\left[0, \frac{\pi}{2}\right)$ and three RGB channels, each sampled from $U[0, 1]$. All VAEs are trained over a subset of $160,000$ (the generative factors are unknown to all architectures), whereas the disentanglement metrics are evaluated on the remaining $40,000$ images.

The Cars3D dataset (Reed et al., 2015) contains 183 CAD models of different cars projected into 64×64 image with four elevations and 24 azimuths. These three generative factors are split between a training set of 14054 images and a validation set of 3514 images.

The 2dshapes Dataset, introduced here and released to the public (MIT License), contains $200,000$ 64×64 images of four possible shapes, triangles, squares, pentagons and hexagons. All shapes in the dataset are centered in the image and have a white background. The factors controlling the images are the following: specific shape drawn from a discrete uniform distribution, a scale value between $s \sim U[20, 40]$, rotation angle $\theta \sim U[0, 2\pi]$, and color RGB values $r \sim U[0, 1]$, $g \sim U[0, 1]$, $b \sim U[0, 1]$ all sampled uniformly. Since the shapes are symmetric, different angles could correspond to the same image. The training set contains a subset of $160,000$ instances, whereas the disentanglement metrics are evaluated on the remaining $40,000$ validation instances.

The 3dshapes dataset (Burgess & Kim, 2018) contains $480,000$ 64×64 images of four possible objects, a cylinder, a tube, a sphere and a box rendered with 8 linearly spaced scale values, 10 hues linearly spaced, floor wall and object hue values and fifteen different orientations, which amounts to six generative factors.

The dSprites Dataset (Matthey et al., 2017) contains $737,280$ 64×64 binary images of three shapes, a square, an ellipse and a heart with six different, equally spaced scale values, 40 different orientations, and 32×32 possible positions in the plane, amounting to five generative factors. $589,824$ instances were used for training and evaluation was performed on the remaining $147,456$ validation instances.

Results   Across all the datasets (Tables 2–6), our T^8-VAE architecture obtains the highest DC-score, which combines the disentanglement and completeness scores, compared with the baselines. In all of these cases the generated images are meaningful, as can be seen from the relatively low FID scores. Furthermore, for teapots (Table 2), 2dshapes (Table 3) and dSprites (Table 6), we also achieve the best reconstruction MSE and FID scores. In the 3dshapes dataset (Table 4) we get the best MSE score and comparable FID scores to β-VAE, which gets the highest score.

For the Cars3D dataset (Table 5) the results are quite different, even though our DC-score is highest. The best performing method in terms of the MSE and FID scores is DIP-VAE-II 128, which is not among the best performing methods for the other datasets. One plausible reason is that this dataset,

Table 1: Architectures for the encoder e, the decoder G and the discriminator used for Factor-VAE. These architectures follow the ones in Eastwood & Williams (2018).

Encoder	Decoder	Discriminator
3×3 64 conv	FC $d \to 8192$	FC $d \to 1000$
BN, ReLU, 3×3 64 conv
BN, ReLU, 3×3 128 conv	BN, ReLU, 3×3 512 conv
BN, ReLU, 3×3 512 conv	BN, LeakyReLU 0.2
FC $1000 \to 1000$
BN, ReLU, 3×3 128 conv
BN, ReLU, 3×3 256 conv	BN, ReLU, 3×3 256 conv
BN, ReLU, 3×3 256 conv	BN, LeakyReLU 0.2
FC $1000 \to 1000$
BN, ReLU, 3×3 256 conv
BN, ReLU, 3×3 512 conv	BN, ReLU, 3×3 128 conv
BN, ReLU, 3×3 128 conv	BN, LeakyReLU 0.2
FC $1000 \to 2$
BN, ReLU, 3×3 512 conv
BN, ReLU, 3×3 512 conv	BN, ReLU, 3×3 64 conv
BN, ReLU, 3×3 64 conv	
FC $8192 \to d$	BN, ReLU, 3×3 3 conv, tanh	

Table 2: Results on Teapots dataset.

	DC-Score	$\mathcal{D}$	$\mathcal{C}$	$\mathcal{I}$	MSE	FID
β-VAE 10	0.1796	0.1902	0.1702	0.0263	0.0178	154.9922
β-VAE 128	0.1286	0.1715	0.0964	**0.0123**	0.0187	159.7412
DIP-VAE-II 10	0.1226	0.2480	0.0676	0.0534	0.0186	151.7267
DIP-VAE-II 128	0.0966	0.1592	0.0593	0.0180	0.0063	62.8249
Factor-VAE 10	0.2526	0.2183	0.3119	0.0601	0.0167	110.7673
Factor-VAE 128	0.3891	0.3564	0.4761	0.0586	0.0061	70.9153
T^8-VAE	**0.6230**	**0.6558**	**0.5919**	0.0332	**0.0012**	**15.7170**

although having only three generative factors, hides a much richer high-dimensional distribution. The factors controlling the car model (183 in total) implicitly contain many characteristics of a car, which requires a high dimensional latent space. Nonetheless, our method achieves the second best FID score for this dataset.

Dependence on β and on D   In order to examine the sensitivity of our method to different tori dimensions, as well as the influence of the β parameter on KL-divergence, we examined the DC-score and reconstruction error on the Teapot dataset, using four topologies, T^4, T^5, T^6 and T^8, and using five different β coefficients, $0, 1, 3, 6, 9$ (0 corresponds to no KL-divergence). As can be seen in Fig. 4, removing the KL-divergence completely, leads to a decrease in the reconstruction error; however, the DC-score also decreases. The T^4-VAE exhibits the worst reconstruction error - not surprisingly, as it can only encode four generative factors, whereas there are five generative factors in the dataset. Both the T^5-VAE, T^6-VAE and T^8-VAE have the capacity of encoding all generative factors, however, the encoder of the T^8-VAE should ignore three of the circles whereas the encoders of the T^5-VAE and T^6-VAE should ignore at most one circle. Thus, when increasing β, the induced angles on T^8 tend to a more uniform distribution, which entangles between themselves. This does not happen in T^5-VAE and T^6-VAE, since there is at most one extra component that can be entangled.

Heatmap analysis Disentanglement results can be qualitatively evaluated through a visual inspection of the 2d heatmaps of the generative factors z_i vs. the codes c_a (the angles θ_a in our case). In Figure 2 we show an example of the heatmap results for using our method with $D = 6$, namely using a T^6-VAE. The disentanglement and completeness properties are clearly seen in the z_1, z_2, z_3, z_4 dependence on $\theta_5, \theta_2, \theta_0, \theta_1$ respectively, while we see worse completeness for the z_0 factor. Such images help us better understand cases where one of the scores is high and the other is low, or whether a specific regressor is suited for capturing the functional dependence.

5   DISCUSSION

We proposed and analyzed a low entangled latent representation of the generating factors of a distribution. The latent space has the topology of a torus which is a direct product of circles. Each

Figure 4: The performance dependence on the latent torus and β parameter of the KL-divergence term with five generating factors.(a) The accumulated DC-score. (b) The reconstruction error. (c) The FID score. We see a clear advantage for a latent space of at least the same dimension as the number of generating factors.

Table 3: Results on 2dshapes dataset.

	DC-Score	$\mathcal{D}$	$\mathcal{C}$	$\mathcal{I}$	MSE	FID
β-VAE 10	0.2898	0.2913	0.2883	0.0335	0.0145	143.7522
β-VAE 128	0.1733	0.2748	0.1093	**0.0216**	0.0165	178.0128
DIP-VAE-II 10	0.1701	0.2525	0.1342	0.0650	0.0224	221.5138
DIP-VAE-II 128	0.1125	0.2354	0.0543	0.0378	0.0131	78.1923
Factor-VAE 10	0.1875	0.2104	0.1676	0.0660	0.0214	122.2750
Factor-VAE 128	0.5165	0.3935	**0.6847**	0.0844	0.0062	86.3864
T^8-VAE	**0.7021**	**0.7274**	0.6777	0.0321	**0.0009**	**17.3992**

Table 4: Results on 3dshapes.

	DC-Score	$\mathcal{D}$	$\mathcal{C}$	$\mathcal{I}$	MSE	FID
β-VAE 10	0.5121	0.5319	0.4934	0.0420	0.0020	**18.3127**
β-VAE 128	0.1219	0.1739	0.0854	**0.0070**	0.0023	20.0576
DIP-VAE-II 10	0.0838	0.2211	0.0329	0.0867	0.0046	186.8153
DIP-VAE-II 128	0.1052	0.1799	0.0617	0.0185	0.0115	267.8511
Factor-VAE 10	0.1759	0.2195	0.1418	0.0738	0.3748	139.5286
Factor-VAE 128	0.1884	0.2166	0.1641	0.0236	0.0024	62.3407
T^8-VAE	**0.7112**	**0.8301**	**0.6140**	0.0731	**0.0009**	22.2525

Table 5: Results on Cars3D.

	DC-Score	$\mathcal{D}$	$\mathcal{C}$	$\mathcal{I}$	MSE	FID
β-VAE 10	0.1962	0.2917	0.1321	0.0897	0.1152	393.0866
β-VAE 128	0.1447	0.2469	0.0848	0.0709	0.1153	384.6031
DIP-VAE-II 10	0.2090	0.3979	0.1106	0.0789	0.0629	259.0138
DIP-VAE-II 128	0.1226	0.2261	0.0665	**0.0492**	**0.0206**	**191.8091**
Factor-VAE 10	0.2551	0.3800	0.1729	0.0961	0.0817	274.6059
Factor-VAE 128	0.3630	**0.6047**	0.2351	0.0892	0.0738	315.6645
T^8-VAE	**0.4623**	0.5984	**0.3571**	0.0783	0.0465	242.2127

Table 6: Results on dSprites.

	DC-Score	$\mathcal{D}$	$\mathcal{C}$	$\mathcal{I}$	MSE	FID
β-VAE 10	0.2047	0.2600	0.1613	0.0843	0.0116	77.3847
β-VAE 128	0.1160	0.1837	0.0733	**0.0548**	0.0125	77.4040
DIP-VAE-II 10	0.1886	0.2673	0.1335	0.0897	0.0209	134.6068
DIP-VAE-II 128	0.1065	0.2237	0.0509	0.0645	0.0218	168.3634
Factor-VAE 10	0.3020	0.2619	**0.3908**	0.0932	0.1529	153.1589
Factor-VAE 128	0.1654	0.2373	0.1154	0.0571	0.0419	101.6020
T^8-VAE	**0.3396**	**0.3681**	0.3161	0.0767	**0.0066**	**65.7015**

circle controls one generative factor, and moving along the circle changes the corresponding aspect of the distribution. Our latent space construction resembles the phase space structure of a classical, integrable physical system, whose dynamics can be described using action-angle canonical variables as motion on a phase space torus. The dimension of the torus is the number of the system's degrees of freedom, and each point on it specifies the location in space and the velocity of the system at a given instant in time. The coordinates of the point on each circle correspond to a particular periodic cycle to which the whole motion has been decomposed. Analogously, the coordinates on each circle of a point in the latent space torus specify one of the basic properties of an element of the dataset to which the description of that element has been decomposed. The possible intriguing relationship between the integrable structure of dynamical systems and its decomposition into its basic harmonic motions and the decomposition of the dataset into its basic constituents can be valuable in relating dynamical systems to the process of learning.

The task of unsupervised disentanglement learning is complicated by the fact that given any disentanglement representation there is an infinite family of entangled representations that have the same marginal distribution (Locatello et al., 2019). Therefore, an inductive bias is needed for the task. Our solution in this work is based on the concept of entanglement entropy in quantum physics. There are non-generic states in the Hilbert space that have low entanglement, and a special class of them are the product states, whose entanglement entropies are identically zero. We employed these states for our disentanglement representation. It is indeed easy to see that these provide a special representation, since any random unitary (or orthogonal) matrix acting on them will make our representation entangled and hence destroy the disentanglement properties of our solution. Thus, in a sense, our inductive bias is the use of the special non-generic states (of measure zero) in the Hilbert space for our representation.

We introduced a DC-score to jointly quantify the disentanglement and completeness of the torus latent representation and calculated it, as well as various other measures in a large set of numerical experiments. For the comparison we used five different types of datasets. We varied the dimension of the latent space torus and showed a clear advantage of the torus latent description compared to others when the torus dimension is equal or greater than the number of generating factors. In order to properly assess the cases where the number of expressive codes is lower than the number of generative factors, we introduced a correction to the disentanglement score, and hence to our DC-score.

One limitation of our proposed low entangled representation is in scaling to datasets containing a large number of generative factors. The dimensionality of v increases exponentially with the dimension of the torus latent representation and is, therefore, limited in describing these situations. This can perhaps be remedied by a different choice of embedding, e.g. working with a direct sum of tensor products, which increases polynomially. Another limitation of the model may be in its ability to effectively describe a property of the dataset that is not naturally encoded in a circle, but is, rather, non-compact in nature.

While our torus latent representation performs better compared to other approaches, one may still wonder why it did not achieve the perfect DC-score 1. This can be explained by the fact that the generation of the datasets assumes a certain number of generating factors, while in fact there could be more, some indirectly combined. For example, in a case where multiple underlying factors are combined into one explanatory factor, the disentanglement may overshoot, thereby reducing the obtained score.

REPRODUCIBILITY STATEMENT

All the code for reproducing all experiments presented in this work is available in the supplement.

REFERENCES

Chris Burgess and Hyunjik Kim. 3d shapes dataset. https://github.com/deepmind/3dshapes-dataset/, 2018.

Kien Do and Truyen Tran. Theory and evaluation metrics for learning disentangled representations. *arXiv preprint arXiv:1908.09961*, 2019.

Cian Eastwood and Christopher KI Williams. A framework for the quantitative evaluation of disentangled representations. In *International Conference on Learning Representations*, 2018.

Martin Heusel, Hubert Ramsauer, Thomas Unterthiner, Bernhard Nessler, and Sepp Hochreiter. Gans trained by a two time-scale update rule converge to a local nash equilibrium. *arXiv preprint arXiv:1706.08500*, 2017.

Irina Higgins, Loic Matthey, Arka Pal, Christopher Burgess, Xavier Glorot, Matthew Botvinick, Shakir Mohamed, and Alexander Lerchner. beta-vae: Learning basic visual concepts with a constrained variational framework. In *ICLR*, 2016.

Hyunjik Kim and Andriy Mnih. Disentangling by factorising. In *International Conference on Machine Learning*, pp. 2649–2658. PMLR, 2018.

Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014.

Diederik P Kingma and Max Welling. Auto-encoding variational bayes. *arXiv preprint arXiv:1312.6114*, 2013.

Mark A Kramer. Nonlinear principal component analysis using autoassociative neural networks. *AIChE journal*, 37(2):233–243, 1991.

Abhishek Kumar, Prasanna Sattigeri, and Avinash Balakrishnan. Variational inference of disentangled latent concepts from unlabeled observations. *arXiv preprint arXiv:1711.00848*, 2017.

Francesco Locatello, Stefan Bauer, Mario Lucic, Gunnar Raetsch, Sylvain Gelly, Bernhard Schölkopf, and Olivier Bachem. Challenging common assumptions in the unsupervised learning of disentangled representations. In Kamalika Chaudhuri and Ruslan Salakhutdinov (eds.), *Proceedings of the 36th International Conference on Machine Learning*, volume 97 of *Proceedings of Machine Learning Research*, pp. 4114–4124. PMLR, 09–15 Jun 2019. URL http://proceedings.mlr.press/v97/locatello19a.html.

Loic Matthey, Irina Higgins, Demis Hassabis, and Alexander Lerchner. dsprites: Disentanglement testing sprites dataset. https://github.com/deepmind/dsprites-dataset/, 2017.

Pol Moreno, Christopher KI Williams, Charlie Nash, and Pushmeet Kohli. Overcoming occlusion with inverse graphics. In *European Conference on Computer Vision*, pp. 170–185. Springer, 2016.

Scott E Reed, Yi Zhang, Yuting Zhang, and Honglak Lee. Deep visual analogy-making. *Advances in neural information processing systems*, 28:1252–1260, 2015.

Maximilian Seitzer. pytorch-fid: FID Score for PyTorch. https://github.com/mseitzer/pytorch-fid, August 2020. Version 0.1.1.

A.K Subramanian. Pytorch-vae. https://github.com/AntixK/PyTorch-VAE, 2020.

Christian Szegedy, Vincent Vanhoucke, Sergey Ioffe, Jon Shlens, and Zbigniew Wojna. Rethinking the inception architecture for computer vision. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 2818–2826, 2016.

Julian Zaidi, Jonathan Boilard, Ghyslain Gagnon, and Marc-André Carbonneau. Measuring disentanglement: A review of metrics. *arXiv preprint arXiv:2012.09276*, 2020.