SURREAL-GAN: SEMI-SUPERVISED REPRESENTATION LEARNING VIA GAN FOR UNCOVERING HETEROGENEOUS DISEASE-RELATED IMAGING PATTERNS

ABSTRACT

A plethora of machine learning methods have been applied to imaging data, enabling the construction of clinically relevant imaging signatures of neurological and neuropsychiatric diseases. Oftentimes, such methods don't explicitly model the heterogeneity of disease effects, or approach it via nonlinear models that are not interpretable. Moreover, unsupervised methods may parse heterogeneity that is driven by nuisance confounding factors that affect brain structure or function, rather than heterogeneity relevant to a pathology of interest. On the other hand, semi-supervised clustering methods seek to derive a dichotomous subtype membership, ignoring the truth that disease heterogeneity spatially and temporally extends along a continuum. To address the aforementioned limitations, herein, we propose a novel method, termed Surreal-GAN (**S**emi-**SU**pe**R**vised **R**epr**E**sent**A**tion **L**earning via GAN). Using cross-sectional imaging data, Surreal-GAN dissects underlying disease-related heterogeneity under the principle of semi-supervised clustering (cluster mappings from normal control to patient), proposes a continuously dimensional representation, and infers the disease severity of patients at individual level along each dimension. The model first learns a transformation function from normal control (CN) domain to the patient (PT) domain with latent variables controlling transformation directions. An inverse mapping function together with regularization on function continuity, pattern orthogonality and monotonicity was also imposed to make sure that the transformation function captures necessarily meaningful imaging patterns with clinical significance. We first validated the model through extensive semi-synthetic experiments, and then demonstrate its potential in capturing biologically plausible imaging patterns in Alzheimer's disease (AD).

1 INTRODUCTION

Neuroimaging, conventional machine learning, and deep learning have offered unprecedented opportunities to understand the underlying mechanism of brain disorders over the past decades (Davatzikos (2018)), and pave the road towards individualized precision medicine (Bzdok & Meyer-Lindenberg (2018)). A large body of case-control studies leverage mass univariate group comparisons to derive structural or functional neuroimaging signatures (Habeck et al. (2008), Hampel et al. (2008), Ewers et al. (2011)). However, these studies suffer from under-powered statistical inferences since the heterogeneous nature of neurological diseases usually violate the assumption that each group population are pathologically homogeneous.

A developing body of methodologies aim to disentangle this heterogeneity with various machine learning methods. Zhang et al. (2016) used the Bayesian Latent Dirichlet Allocation (LDA) model to identify latent atrophy patterns from voxel-wise gray matter (GM) density maps. However, due to the nature of the LDA model, the density maps need to be first discretized, and the model hypothesized to exclusively capture brain atrophy while ignoring the potential regional enlargement. Young et al. (2018) proposed another method, Sustain, to uncover temporal and phenotypic heterogeneity by inferring both subtypes and stages. However, the model only handles around 10-20 large brain regions without more detailed information. Notably, both methods applied directly in the PT domain, confront main limitations in avoiding potential disease-unrelated brain variations. In con-

trast, semi-supervised clustering methods (Varol et al. (2016), Dong et al. (2015), Wen et al. (2020), Yang et al. (2021)) were proposed to cluster patients via the patterns or transformations between the reference group (CN) and the target patient group (PT). A recent proposed deep learning-based semi-supervised clustering method, termed Smile-GAN (Yang et al. (2021)), achieved better clustering performance by learning multiple mappings from CN to PT with an inverse clustering function for both regularization and clustering. Albeit these methods demonstrated potential in clinical applications, they have a major limitation. In particular, these methods model disease heterogeneity as a dichotomous process and derive a discrete output, i.e., subtype, ignoring the fact that brain disorders progress along a continuum. Moreover, variations among subtypes were contributed by both spatial and temporal differences in disease patterns, thus confounding further clinical analysis.(Fig. 1a)

To address the aforementioned limitations, we propose a novel method, Surreal-GAN (Semi-Supervised Representation Learning via GAN), for deriving heterogeneity-refined imaging signatures. Surreal-GAN is a significant extension of Smile-GAN under the same principle of semi-supervised learning by transforming data from CN domain X to PT domain Y. Herein, the key extension is to represent complex disease-related heterogeneity with low dimensional representations with each dimension indicating the severity of one relatively homogeneous imaging patterns (Fig. 1b). We refer to these low dimensional representations as R-indices ($\mathbf{r}_i$, where i represent the i_{th} dimension) of disease pattern. The first novelty of the method is modelling disease as a continuous process and learning infinite transformation directions from CN to PT, with each direction capturing a specific combination of patterns and severity. The idea is realized by learning one transformation function which takes both normal data and a continuous latent variable as inputs and output synthesized-PT data whose distribution is indistinguishable from that of real PT data. The second novelty here is controlling the monotonicity (from light to severe with increasing index value) of disease patterns through one monotonicity loss and double sampling procedure. The third novelty is boosting the separation of captured disease patterns through one orthogonality regularization. The fourth novelty is introducing a inverse mapping function consisting of a decomposition part and a reconstruction part which further ensure that patterns synthesized through transformation are exactly captured for inferring representations of disease patterns, the R-indices. Besides the above mentioned regularization, function continuity, transformation sparsity and inverse consistency further guide the model to capture meaningful imaging patterns.

To support our claims, we first validated Surreal-GAN on semi-synthetic data with known ground truth of disease patterns and severity. We compared performance of Surreal-GAN to NMF (Lee & Seung (1999)), Factor Analysis and LDA (Blei et al. (2001)) models, and subsequently studied the robustness of model under various conditions. Finally, we applied the model to one real dataset for Alzheimer's disease (AD), and demonstrated significant correlations between the proposed imaging signatures and clincial variables.

2 METHODS

The schematic diagram of Surreal-GAN is shown in Fig. 1d. The model is applied on regional volume data (volumes of different graymatter (GM) and whitematter (WM) regions) derived from structural MRI. The essential idea is to learn one transformation function $f : \mathbb{X} * \mathbb{Z} \rightarrow \mathbb{Y}$ which transforms CN data $\mathbf{x}$ to different synthesized PT data $\mathbf{y}' = f(\mathbf{x}, \mathbf{z})$, with latent variable $\mathbf{z}$ specifying distinct combinations of patterns and severity. Here, the Latent (LAT) domain, $\mathbb{Z} = \{\mathbf{z} : 0 \leq \mathbf{z}_i \leq 1 \ \forall 1 \leq i \leq M\}$, is a class of vectors with dimension M (predefined number of patterns). We denote four different data distributions as $\mathbf{x} \sim p_{cn}(\mathbf{x})$, $\mathbf{y} \sim p_{pt}(\mathbf{y})$, $\mathbf{y}' \sim p_{syn}(\mathbf{y}')$ and $\mathbf{z} \sim p_{lat}(\mathbf{z})$, respectively, where $\mathbf{z} \sim p_{lat}(\mathbf{z})$ is sampled from a multivariate uniform distribution $U[0, 1]^M$. In addition to the transformation function, an adversarial discriminator D is introduced to distinguish between real PT data $\mathbf{y}$ and synthesized PT data $\mathbf{y}'$, thereby ensuring that the synthesized PT data are indistinguishable from real PT data (i.e. minimizing the distance between real PT data distribution and synthesized PT data distribution).

A continuous latent variable does not necessarily lead to desired properties of CN to PT transformation (e.g. separation/monotonicity of captured patterns). That is, there are a number of functions potentially achieving equality in distributions, thus making it hard to guarantee that the transformation function learned by the model is closely related to the underlying pathology progression process. Moreover, during the actual training procedure, the transformation function backboned by the neural network tends to ignore the latent variable $\mathbf{z}$. Even when the Latent variable $\mathbf{z}$ is emphasized through regularization, different components of $\mathbf{z}$ variable do not naturally lead to separate disease

Figure 1: Model Ideas and Schematic Diagram. (a) Results from Semi-supervised clustering for AD disease: model clusters PT into discrete subtypes based on both spatial and temporal variations: P1 and P4 show mild and severe stages and are mixture of two patterns; (b) Expected improvements from Surreal-GAN: two patterns are captured by two indices with values indicating severity; (c) General architecture of networks; (d) Schematic diagram of Surreal-GAN.

patterns and are not positively correlated with pattern severity. Therefore, with the assumption that there is one true underlying function for real PT data $\mathbf{y} = h(\mathbf{x}, \mathbf{z})$, Surreal-GAN aims to boost the transformation function f to approximate the true underlying function h, while having the latent variable, $\mathbf{z}$, contributing to recognizable imaging patterns rather than being random "activators" of the GAN. For this purpose, we constrain the function class of f via different types of regularization as follows: 1) encourage sparse transformations; 2) enforce Lipschitz continuity of functions; 3) introduce one inverse function $g : \mathbb{Y} \rightarrow \mathbb{Z}$ serving to decompose and reconstruct; 4) boost orthogonality among synthesized/captured patterns; 5) enforce monotonicity of synthesized patterns and their positive correlations with components of $\mathbf{z}$. The training procedure of Surreal-GAN is thus a adversarial learning process constrained by these regularization.

2.1 ADVERSARIAL LOSS

The adversarial loss (Goodfellow et al. (2014)) is used for iterative training of discriminator D and the mapping function f, which can be written as:

$$L_{\text{GAN}}(D, f) = \mathbb{E}_{y \sim p_{pt}(\mathbf{y})}[\log(D(\mathbf{y}))] + \mathbb{E}_{\mathbf{x} \sim p_{cn}(\mathbf{x}), \mathbf{z} \sim P_{lat}(\mathbf{z})}[\log(1 - D(f(\mathbf{x}, \mathbf{z})))] \quad (1)$$

$$= \mathbb{E}_{\mathbf{y} \sim p_{pt}(\mathbf{y})}[\log(D(\mathbf{y}))] + \mathbb{E}_{\mathbf{y}' \sim p_{syn}(\mathbf{y}')}[\log(1 - D(\mathbf{y}'))] \quad (2)$$

The transformation function f attempts to transform CN data to synthesized PT data so that they follow similar distributions as real PT data. The discriminator, providing a probability that $\mathbf{y}$ comes from the real data rather than transformation function, tries to identify the synthesized PT data and distinguish it from real PT data. Therefore, the discriminator D attempts to maximize the adversarial loss function while the mapping f attempts to minimize against it. The training process can be

denoted as:

$$\min_f \max_D L_{\text{GAN}}(D, f) = \mathbb{E}_{\mathbf{y} \sim p_{pt}(\mathbf{y})}[\log(D(\mathbf{y}))] + \mathbb{E}_{\mathbf{y}' \sim p_{syn}(\mathbf{y}')}[\log(1 - D(\mathbf{y}'))] \tag{3}$$

2.2 REGULARIZATION

2.2.1 SPARSE TRANSFORMATION

We assumed that disease process will not change brain anatomy dramatically and primarily only affect certain regions throughout most of disease stages, which means that the true underlying transformation only moderately changes some regions while keeping the rest mildly affected with most of $\mathbf{z}$ variable values. Therefore, to encourage sparsity and control the distance of transformations, we defined one change loss to be the l_1 distance between the synthesized PT data and the original CN data:

$$L_{\text{change}}(f) = \mathbb{E}_{\mathbf{x} \sim p_{cn}(\mathbf{x}), \mathbf{z} \sim p_{lat}(\mathbf{z})}[||f(\mathbf{x}, \mathbf{z}) - \mathbf{x}||_1] \tag{4}$$

2.2.2 LIPSCHITIZ CONTINUITY AND INVERSE MAPPING

First, by enforcing the transformation function f to be K-Lipschitz continuous, we can derive that, for fixed latent variable $\mathbf{z} = \boldsymbol{a}$ and $\forall \boldsymbol{x}_1, \boldsymbol{x}_2 \in \mathbb{X}$, $||f(\boldsymbol{x}_1, \boldsymbol{a}) - f(\boldsymbol{x}_2, \boldsymbol{a})||_2 \leq K_1 ||\boldsymbol{x}_1 - \boldsymbol{x}_2||_2$. Thus, by controlling the constant K_1, we constrained the transformation function to preserve the original distances among CN data instead of scattering them into the PT domain if a same combination of disease patterns is imposed to them.

Second, to prevent latent variable $\mathbf{z}$ from being ignored, we introduced an inverse mapping function from PT domain to Latent domain, $g : \mathbb{Y} \to \mathbb{Z}$. With function g being K-Lipschitz continuous and $d(\cdot, \cdot)$ being any distance metric satisfying triangular inequality, we can derive that, $\forall \boldsymbol{z}_1, \boldsymbol{z}_2 \sim p_{lat}(\mathbf{z}), \boldsymbol{z}_1 \neq \boldsymbol{z}_2$, and $\bar{\boldsymbol{x}} \sim p_{cn}(\mathbf{x})$

$$d(f(\bar{\boldsymbol{x}}, \boldsymbol{z}_1), f(\bar{\boldsymbol{x}}, \boldsymbol{z}_2)) \geq \frac{1}{K_2} d(g(f(\bar{\boldsymbol{x}}, \boldsymbol{z}_1)), g(f(\bar{\boldsymbol{x}}, \boldsymbol{z}_2))) \tag{5}$$

$$\geq \frac{1}{K_2}(d(\boldsymbol{z}_1, \boldsymbol{z}_2) - d(g(f(\bar{\boldsymbol{x}}, \boldsymbol{z}_1)), \boldsymbol{z}_1) - d(g(f(\bar{\boldsymbol{x}}, \boldsymbol{z}_2)), \boldsymbol{z}_2)) \tag{6}$$

$$= \frac{d(\boldsymbol{z}_1, \boldsymbol{z}_2)}{K_2} - \frac{1}{K_2}(d(g(f(\bar{\boldsymbol{x}}, \boldsymbol{z}_1)), \boldsymbol{z}_1) + d(g(f(\bar{\boldsymbol{x}}, \boldsymbol{z}_2)), \boldsymbol{z}_2)) \tag{7}$$

Therefore, $d(f(\bar{\boldsymbol{x}}, \boldsymbol{z}_1), f(\bar{\boldsymbol{x}}, \boldsymbol{z}_2))$ is lower bounded by $(\frac{d(\boldsymbol{z}_1, \boldsymbol{z}_2)}{K_2} - \frac{1}{K_2}(d(g(f(\bar{\boldsymbol{x}}, \boldsymbol{z}_1)), \boldsymbol{z}_1) + d(g(f(\bar{\boldsymbol{x}}, \boldsymbol{z}_2)), \boldsymbol{z}_2)))$. By minimizing the distance between sampled latent variable $\mathbf{z}$ and reconstructed latent variable $g(f(\mathbf{x}, \mathbf{z}))$, we can control differences between synthesized patterns to be positively related to the distances between latent variables, and thus to be non-trivial (i.e., same CN data is transformed to significantly different PT data with different $\mathbf{z}$ variables). Therefore, we define a reconstruction loss as the l_2 distance between $g(f(\mathbf{x}, \mathbf{z}))$ and $\mathbf{z}$:

$$L_{\text{recons}}(f, g) = \mathbb{E}_{\mathbf{x} \sim p_{cn}(\mathbf{x}), \mathbf{z} \sim p_{lat}(\mathbf{z})}[||g(f(\mathbf{x}, \mathbf{z})) - \mathbf{z}||_2] \tag{8}$$

2.2.3 PATTERN DECOMPOSITION

Nevertheless, a simple function g directly reconstructing sampled $\mathbf{z}$ from synthesized PT $\mathbf{y}'$ do not reconstruct each component $\mathbf{z}_i$ completely based on changes led by $\mathbf{z}_i$ in transformation. We are more interested in pattern representations of real PT data than generating synthesized PT, and inverse function g will be used for inferring R-indices as introduced in section 2.4. Thus, it is very important for the inverse function to accurately capture patterns synthesized by intensively regularized transformation function f. For this purpose, we further separated the function $g : \mathbb{Y} \to \mathbb{Z}$ into $g_1 : \mathbb{Y} \to \mathbb{R}^{M*S}$ (where M is number of patterns and S is number of features) and $g_2 : \mathbb{R}^S \to \mathbb{R}$. Decomposer g_1 serves to reconstruct changes synthesized by each component z_i in transformation process: $\mathbf{q}_i = f(\mathbf{x}, \mathbf{z}_i) - \mathbf{x}$. Let $\hat{\mathbf{q}}_{f(x,z)} = [\mathbf{q}_1^T, \cdots, \mathbf{q}_M^T]^T$ be concatenation of all synthesized changes $\mathbf{q}_i$, we defined the decomposition loss as:

$$L_{\text{decom}}(f, g_1) = \mathbb{E}_{\mathbf{x} \sim p_{cn}(\mathbf{x}), \mathbf{z} \sim p_{lat}(\mathbf{z})}[||g_1(f(\mathbf{x}, \mathbf{z})) - \hat{\mathbf{q}}_{f(\mathbf{x}, \mathbf{z})}||_2] \tag{9}$$

g_2 serves to further reconstruct each component of sampled $\mathbf{z}$ variable from $g_1(f(\mathbf{x}, \mathbf{z}))$ independently, so that $g(\mathbf{x}) = \hat{\boldsymbol{l}}_{g_2(g_1(f(\mathbf{x}, \mathbf{z})))} = [g_2(g_1(f(\mathbf{x}, \mathbf{z}))_{0:S}), \cdots, g_2(g_1(f(\mathbf{x}, \mathbf{z}))_{S*(M-1):S*M})]^T$ and the reconstruction loss can be rewritten as

$$L_{\text{recons}}(f, g) = L_{\text{recons}}(f, g_1, g_2) = \mathbb{E}_{\mathbf{x} \sim p_{cn}(\mathbf{x}), \mathbf{z} \sim p_{lat}(\mathbf{z})}[||\hat{\boldsymbol{l}}_{g_2(g_1(f(\mathbf{x}, \mathbf{z})))} - \mathbf{z}||_2] \qquad (10)$$

Function g here can be also considered as the approximation of expectation of posterior distribution. In this sense, minimization of l_2 distances can also be interpreted as maximization of mutual information between latent variable $\mathbf{z}$ and synthesized PT data $\mathbf{y}' = f(\mathbf{x}, \mathbf{z})$ as explained in Remark1 in Appendix (Chen et al. (2016)). From this perspective, the transformation function is forced to best utilize information from latent variable $\mathbf{z}$, while also keeping mutual information between synthesized PT data $\mathbf{y}'$ and original CN data $\mathbf{x}$ by controlling transformation distances.

2.2.4 ORTHOGONALITY OF PATTERNS

Inclusion of latent variable $\mathbf{z}$ in the transformation function does not guarantee that different components of the latent variable, $\mathbf{z}_i$, contributes to relatively different patterns in synthesized PT data. Instead, during training procedure, different components, $\mathbf{z}_i$, are more likely to synthesize patterns in same regions and lead to accumulated severity. Therefore, we define another orthogonal loss to encourage separation among patterns synthesized by different components. For any sampled latent variable $\mathbf{z}$ with dimension M, we decompose it into sum of M vectors $\mathbf{z} = \sum_{i=1}^{M} \mathbf{a}^i$, where $\mathbf{a}^i$ is a vector with i_{th} component $\mathbf{a}_i^i = \mathbf{z}_i$ and $\mathbf{a}_j^i = 0$, $\forall i \neq j$. With changes led by each component, $\mathbf{q}_i$ defined in section 2.2.3, we constructed a matrix $\mathbf{A}_{f(\mathbf{x}, \mathbf{z})}$ with the i_{th} column $\mathbf{A}_{f(\mathbf{x}, \mathbf{z})_{:,i}} = |\mathbf{q}_i|$. To encourage separation of changes led by different components, we boosted the matrix $\mathbf{A}_{f(\mathbf{x}, \mathbf{z})}$ to be relatively orthogonal by minimizing the following orthogonality loss:

$$L_{\text{ortho}}(f) = \mathbb{E}_{\mathbf{x} \sim p_{cn}(\mathbf{x}), \mathbf{z} \sim p_{lat}(\mathbf{z})}[||\mathbf{A}_{f(\mathbf{x}, \mathbf{z})}^T \mathbf{A}_{f(\mathbf{x}, \mathbf{z})} - \boldsymbol{I}||_F] \qquad (11)$$

2.2.5 MONOTONICITY AND POSITIVE CORRELATION

Besides separation of synthesized patterns, a positive correlation between values of each component $\mathbf{z}_i$ (from 0 to 1) and severity of synthesized patterns can not be acquired spontaneously either. Regarding severity of the disease pattern, we assumed that, as a pattern is becoming more severe, absolute values of changes in regional volumes can only increase monotonically or remain constant. In another word, there is no oscillation in regional volumes as disease pattern is becoming more severe, while more regions can be included gradually with absolute changes switched from 0 to a positive value. To satisfy this requirement, we sampled another latent variable $\mathbf{z}' \sim p_{sev}(\mathbf{z}'|\mathbf{z})$, conditioned on previous sampled $\mathbf{z}$ variable, such that $\mathbf{z}_i' \geq \mathbf{z}_i$, $\forall 1 \leq i \leq M$. With these double sampled latent variables, we defined the monotonicity loss to be:

$$L_{\text{mono}}(f) = \mathbb{E}_{\mathbf{x} \sim p_{cn}(\mathbf{x}), \mathbf{z} \sim p_{lat}(\mathbf{z}), \mathbf{z}' \sim p_{sev}(\mathbf{z}'|\mathbf{z})}[|| \max(|f(\mathbf{x}, \mathbf{z}) - \mathbf{x}| - |f(\mathbf{x}, \mathbf{z}') - \mathbf{x}|, \mathbf{0})||_2] \quad (12)$$

Minimization of this monotonicity loss penalize the case that volume changes induced by $\mathbf{z}$ is larger than that induced by $\mathbf{z}'$, while the other direction is permitted. To further ensure a positive correlation (small $\mathbf{z}$ lead to mild patterns; large $\mathbf{z}$ lead to severe patterns), we introduced a cn loss, which serves to more strictly constrain the distance between synthesized PT data $\mathbf{y}'$ and CN data $\mathbf{x}$, when latent variable $\mathbf{z}$ is close to $\mathbf{0}$ vector. By letting $p_{cn}(\mathbf{z}) = U(0, 0.05)^M$ to be a multivariate uniform distribution, the cn loss is defined as:

$$L_{\text{cn}}(f) = \mathbb{E}_{\mathbf{x} \sim p_{cn}(\mathbf{x}), \mathbf{z}^{cn} \sim p_{cn}(\mathbf{z})}[||f(\mathbf{x}, \mathbf{z}^{cn}) - \mathbf{x}||_1] \qquad (13)$$

2.3 FULL OBJECTIVE

With the adversarial loss and all other loss functions defined for regularization, we can write the full objective as:

$$L(D, f, g_1, g_2) = L_{\text{GAN}}(D, f) + \gamma L_{\text{change}}(f) + \kappa L_{\text{decom}}(f, g_1) + \zeta L_{\text{recon}}(f, g_1, g_2) \qquad (14)$$
$$+ \lambda L_{\text{ortho}}(f) + \mu L_{\text{mono}}(f) + \eta L_{\text{cn}}(f) \qquad (15)$$

with $\gamma, \kappa, \zeta, \lambda, \mu$ and η be parameters controlling the relative importance of different loss functions. Through training process, we want to derive parametrized functions f, g_1 and g_2 satisfying:

$$f, g_1, g_2 = \arg \min_{f,g} \max_D L(D, f, g_1, g_2) \qquad (16)$$

2.4 Representation-Indices Inference

With the assumption that $p_{syn}(f(\mathbf{x}, \mathbf{z})) \approx p_{pt}(\mathbf{y})$ and f satisfying all constraints, we consider learned transformation function f to be a good approximation of the true underlying function h, such that $f(\mathbf{x}, \mathbf{z}) \approx h(\mathbf{x}, \sigma(\mathbf{z}))$, where $\sigma \in \Omega$ and Ω is a class of permutation functions which change orders of elements in vector $\mathbf{z}$. Since the order of indices in derived representation is not important and we can always reorder them to find the best matching, we simply rewrite it as $f(\mathbf{x}, \mathbf{z}) \approx h(\mathbf{x}, \mathbf{z})$ without loss of generality. For any real PT data, $\bar{\mathbf{y}} = h(\bar{\mathbf{x}}, \mathbf{r}) \sim p_{pt}(\mathbf{y})$, we can derive that the ground truth R-indices $\mathbf{r} \approx g(f(\bar{\mathbf{x}}, \mathbf{r})) \approx g(h(\bar{\mathbf{x}}, \mathbf{r})) \approx g(\bar{\mathbf{y}})$. Therefore, reconstruction function g can be directly applied to infer R-indices of disease patterns, $\mathbf{r}$, of any unseen PT data.

3 Implementation Details

3.1 Model Architecture

The general architecture of networks can be understood from Fig. 1c. The transformation function f utilizes a encoding-decoding structure. Latent variable $\mathbf{z}$ and CN data $\mathbf{x}$ are first mapped to two vectors with dimension 34 and the dot product of them are then decoded to construct the synthesized PT data with dimension 139. The inverse function g first decodes real/synthesized PT data $\mathbf{y}/\mathbf{y}'$ to larger vector with dimension 139*M and then maps them into a vector with dimension M. The discriminator D utilizes the encoding structure which maps y/y' to a vector with dimension 2. More details of model architectures can be found in Appendix Table 3 and 4.

3.2 Lipschitz Continuity

In implementation, we performed weight clipping to ensure Lipschitz continuity of transformation function f and inverse function g (Arjovsky et al. (2017)). With Θ_f and Θ_g denoting the weight spaces of function f and g, the compactness of them imply the Lispchitz continuity of two functions, with Lipschitz constants K_1 and K_2 only depends on Θ_f and Θ_g. The compactness of Θ_f and Θ_g was guaranteed by clapping weight spaces into two closed box, $\Theta_f = [-c_f, c_f]^d$ and $\Theta_g = [-c_g, c_g]^d$. In implementation, both c_f and c_g were set to be 0.5 and these bounds can be further relaxed. Weight clipping was claimed not to be the most satisfactory method to ensure Lipschitz continuity because of difficulty in choosing the appropriate clipping bounds. However, in our case, we performed weight clipping for function f and g rather than discriminator D for a different purpose and weight clipping contributed to good performances for deriving representations.

3.3 Training Details

Regarding optimization procedure, ADAM optimizer (Kingma & Ba (2014)) was used with a learning rate $4 * 10^{-5}$ for Discriminator and $2 * 10^{-4}$ for mapping function f and clustering function g. β_1 and β_2 are set to be 0.5 and 0.999 respectively. For hyper-parameters, we set $\gamma = 6$, $\kappa = 80$, $\zeta = 80$, $\mu = 500$, $\eta = 6$. Parameter λ determines the relative importance of orthogonality loss and thus controls the degree of overlapping among synthesized patterns. Without prior knowledge on overlapping degree of underlying disease patterns, we set λ to different values in the following experiments and used the agreement among multiple repetitively trained models to determine the optimal one. Moreover, for all experiments, the batch size was set to be 1/8 of the PT data sample sizes. The model was trained for at least 100000 epochs and saved until the reconstruction loss is smaller than 0.003 and the monotonicity loss is smaller than $6 * 10^{-4}$. Detailed training procedure is revealed by Appendix Algorithm1.

4 Experiments

4.1 Data Preprocessing

For semi-synthetic and real data experiments, we used T1-weighted (T1w) MR imaging (MRI) and cognition from an international multicentric consortium for cognitive impairment and dementia (anonymous for review process). All baseline MRIs were corrected for intensity inhomogeneities

(Sled et al. (1998)). Then, 139 regions of interest (ROIs) of brain volumes were extracted using a multi-atlas label fusion method (Doshi et al. (2015)). The ROIs were then harmonized (Pomponio et al. (2020)) to remove site effect and utilized as input features for Surreal-GAN.

4.2 SEMI-SYNTHETIC EXPERIMENTS

Semi-synthetic data construction To set the ground truth of disease patterns and severity a prior, we generated semi-synthetic data by imposing simulated disease-related patterns to real CN data, thereby retaining the variation from the real CN data. Specifically, we split 1392 cognitively normal (age < 70 years) into one real CN group (RCN) with 492 subjects and one Pseudo-PT group with 900 subjects. For the i_{th} Pseudo-PT subject, we sampled a three dimensional vector as pattern severity from a multivariate uniform distribution, $s_i \sim U[0, 1]^3$. Three types of atrophy patterns were introduced to 900 Pseudo-PT subjects. Different regions were included in different patterns as shown in Appendix Table 5. Five different datasets were constructed for testing the robustness of model under different conditions: (1) **Basic dataset**: For the i_{th} Pseudo-PT subject and the j_{th} ROI included in pattern k, we decreased the volume v_{ij} depending on sampled severity: $v_{ij} = v_{ij} - v_{ij} * s_{ik} * N(1, 0.05) * 0.3$. Each pattern consists of changes in 14 ROIs and has four of them shared with other patterns; (2) **Large overlapping dataset**: Same as the Basic dataset, except that each pattern shares 8 ROIs with others; (3) **Scarce regions dataset**: Each patterns consists of changes in only 4 ROIs with other parts the same as the Basic dataset; (4)**Within-pattern noise dataset**: Regional changes incorporated in the same pattern have larger within-pattern variances with $v_{ij} = v_{ij} - v_{ij} * s_{ik} * N(1, \mathbf{0.2}) * 0.3$; (5) **Mild atrophy dataset**: Compared to the basic case, smaller changes were imposed by letting $v_{ij} = v_{ij} - v_{ij} * s_{ik} * N(1, 0.05) * \mathbf{0.2}$.

Evaluation and Agreement Metric In our experiments, Concordance Index (C-index) was used as the evaluation metric. Specifically, for each pattern, we calculated a c-index between the inferred R-index and the ground truth. The average of M derived C-indices, refereed as pattern-c-index, was used for model evaluations. Moreover, to quantify the pair-wise agreement between two trained models, we proposed another Pattern-agr-index which equals pattern-c-index between R-indices derived by two different models.

Experiment Procedure We first validated the relationship between model agreements and their accuracy. On each dataset, we ran the model 10 times with parameter $\lambda = 0.1, 0.2, 0.4, 0.6, 0.8$ respectively. With each λ, the average pair-wise pattern-agr-index among 10 models was compared with their average pattern-c-indices. Further, the parameter value leading to the best agreement was considered as the best choice, and results from 10 corresponding models were reported as model performances for each task. Lastly, we compared our model with three other models, Factor Analysis (FA), Non-negative Matrix Factorization (NMF) and Latent Dirichlet Allocation (LDA) in all five tasks. Z-scores of ROIs with respect to the CN group were directly used as input features of FA model. However, for NMF and LDA model, we need to borrow a prior knowledge that atrophy (volume decreasing) is more common in dementia-related brain diseases, and thus, reversed the sign of z-scores, kept positive z-scores, and set negative values to 0. For LDA model, we further discretized the value by first multiplying z-scores by 10 and then mapping them to the closest integer as described in Zhang et al. (2016).

4.3 REAL DATA EXPERIMENTS

Data Selection We applied Surreal-GAN to a Alzheimer's Disease dataset. For AD, we defined the CN group (N=850) to be subjects whose Mini-mental state examination (MMSE) scores were above 29, and the PT group (N=2204) as subjects that were diagnosed as mild cognitive impairment (MCI) or AD at baseline.

Experiments Procedure We estimated covariates effects (age&gender) in the CN group using a linear regression model. Then, all CN and PT subjects were residualized to rule out the covariate effects. The adjusted features were then standardized with respect to CN group. Without ground truth, we selected both the optimal number of patterns, M, and λ parameter by measuring agreement among repetitively trained models. For each combination of $M = 2, 3, 4$ and $\lambda = 0.1, 0.2, 0.4, 0.6, 0.8$, we ran the model 10 times respectively. The M and λ values leading to the highest agreement was considered optimal. Among the 10 corresponding models, the one having the highest mean pair-wise agreements with the other models was used to derive R-indices for all PT subjects. To visualize patterns corresponding to the i_{th} dimension of R-indices, $\mathbf{r}_i$, we grouped subjects into three different subgroups: $\mathbf{r}_i < 0.4$, $0.4 < \mathbf{r}_i < 0.7$ and $\mathbf{r}_i > 0.7$, with

Figure 2: Results on Semi-synthetic data. (a) Representation accuracies on different tasks (measured by Pattern-c-index); (b) Agreements among repetitively trained models on different tasks.

Table 1: Model Comparison Results

	Surreal-GAN	NMF	LDA	FA
Basic Case	0.838 ± 0.011	0.680 ± 0.000	0.605 ± 0.001	0.631 ± 0.000
Large Overlapping	0.837 ± 0.008	0.692 ± 0.000	0.591 ± 0.000	0.612 ± 0.000
Scarce Regions	0.783 ± 0.007	0.625 ± 0.000	0.582 ± 0.001	0.526 ± 0.000
Within Pattern Noise	0.818 ± 0.013	0.675 ± 0.000	0.626 ± 0.000	0.619 ± 0.000
Mild Changes	0.762 ± 0.023	0.611 ± 0.000	0.574 ± 0.004	0.526 ± 0.000

$\mathbf{r}_j < 0.4$ for all $j \neq i$. Voxel-wise group comparisons were performed between each subgroup and the CN group via AFNI-3dttest (R.W. (1996)) and GM-tissue map (Davatzikos et al. (2002)) which encodes, for each tissue type, the volumetric changes observed during the registration. Pattern representations, R-indices, of PT subjects were further compared with other clinical variables to test their significance. Details of clinical variables and statistical tests can be found in Appendix section A.5.

5 RESULTS

5.1 RESULTS ON SEMI-SYNTHETIC DATA

We first validated that agreements among multiple trained models (Fig. 2b) are good indicators of model accuracy (Fig. 2a) for parameter selections. Besides, from Fig. 2a, we proved the model's ability in capturing ground truth of patterns and severity under different cases including pattern overlapping and large within-pattern noise. However, the model experienced declining performances when scarce disease-related regions were included in each pattern and showed even worse performances when very mild atrophies are led by disease process. This is expected since, for the mild atrophy data set, the simulated atrophy rate is 0-20% of the regional volume which is even smaller than the standard deviation of most of regional volumes among the normal population. Finally, Surreal-GAN significantly outperformed all three other methods on five data sets we constructed (Table 1).

5.2 RESULTS ON REAL DATA

On the AD dataset, models show highest agreement when the number of patterns $M = 2$. From voxel-based comparison results (Fig. 3), we can clearly visualize two patterns related to AD. Each dimension of R-indices, $\mathbf{r}_i$, shows a clear positive correlation with the corresponding pattern severity. Pattern1, correlated with $\mathbf{r}_1$, shows diffuse cortical atrophies (e.g., bilateral insula, orbitofrontal and frontal poles), while pattern2 reveals focal atrophy in medial temporal lobes.

Figure 3: Voxel-wise statistical comparison results between selected subgroups and CN. (FDR method with p-value threshold of 0.05 was used for multiple comparison). In each direction guided by arrows, we increased values of one R-index and keep the other relatively fixed. Therefore, we chose out groups of subjects who have much stronger expression of one pattern for visualization.

Table 2: Correlation between pattern severity and clinical variables for AD disease

	r_1	r_2
White matter lesion volumes	0.415 (**p<0.001**)	0.184 (**p<0.001**)
DSST	-0.055 (p=0.603)	-0.212 (**p=0.042**)
Apoe-E4 Alleles Carrier	0.003 (p=0.965)	0.212 (**p<0.001**)
Hypertension	0.181 (**p<0.001**)	-0.006 (p=0.890)
CSF-Abeta	-0.238 (**p<0.001**)	-0.302 (**p<0.001**)
CSF-Tau	0.111 (**p=0.002**)	0.270 (**p<0.001**)
CSF-PTau	0.059 (p=0.103)	0.152 (**p<0.001**)
ADNI-EF	-0.409 (**p<0.001**)	-0.240 (**p<0.001**)
ADNI-MEM	-0.453 (**p<0.001**)	-0.466 (**p<0.001**)
ADNI-LAN	-0.422 (**p<0.001**)	-0.281 (**p<0.001**)

Continuity and monotonicity of inferred R-indices further enable us to easily test correlation among them and other clinical variables (Table 2). Both r_1 and r_2 are highly correlated with CSF-Abeta value and memory dysfunction measured by ADNI-MEM . However, r_1 shows stronger correlations with white matter lesion volumes, presence of hypertension, executive function and language functioning, while r_2 is more correlated with CSF-Tau, CSF-pTau and presence of APOE-E4 alleles.

6 CONCLUSION

In this study, we have proposed a novel method, Surreal-GAN, for learning representations of underlying disease-related imaging patterns. This model has overcome limitations in previous published semi-supervised clustering methods and shown great performance on semi-synthetic data sets. On AD dataset, the model identified two clinically informative patterns, further proving its huge potential in uncovering disease heterogeneity from MRI data.

REFERENCES

Martin Arjovsky, Soumith Chintala, and Léon Bottou. Wasserstein gan, 2017.

David Blei, Andrew Ng, and Michael Jordan. Latent dirichlet allocation. volume 3, pp. 601–608, 01 2001.

Danilo Bzdok and Andreas Meyer-Lindenberg. Machine learning for precision psychiatry: Opportunities and challenges. *Biological Psychiatry: Cognitive Neuroscience and Neuroimaging*, 3, 02 2018. doi: 10.1016/j.bpsc.2017.11.007.

Xi Chen, Yan Duan, Rein Houthooft, John Schulman, Ilya Sutskever, and Pieter Abbeel. Infogan: Interpretable representation learning by information maximizing generative adversarial nets. *Advances in Neural Information Processing Systems*, 29, 06 2016.

Christos Davatzikos. Machine learning in neuroimaging: Progress and challenges. *NeuroImage*, 197, 10 2018. doi: 10.1016/j.neuroimage.2018.10.003.

Christos Davatzikos, Ahmet Genc, Dongrong Xu, and Susan Resnick. Voxel-based morphometry using the ravens maps: Methods and validation using simulated longitudinal atrophy. *NeuroImage*, 14:1361–1369, 01 2002. doi: 10.1006/nimg.2001.0937.

Aoyan Dong, Nicolas Honnorat, Bilwaj Gaonkar, and Christos Davatzikos. Chimera: Clustering of heterogeneous disease effects via distribution matching of imaging patterns. *IEEE transactions on medical imaging*, 35, 10 2015. doi: 10.1109/TMI.2015.2487423.

Jimit Doshi, Guray Erus, Yangming Ou, Susan Resnick, Ruben Gur, Raquel Gur, Theodore Satterthwaite, Susan Furth, and Christos Davatzikos. Muse: Multi-atlas region segmentation utilizing ensembles of registration algorithms and parameters, and locally optimal atlas selection. *NeuroImage*, 127, 12 2015. doi: 10.1016/j.neuroimage.2015.11.073.

Michael Ewers, Reisa Sperling, William Klunk, Michael Weiner, and Harald Hampel. Neuroimaging markers for the prediction and early diagnosis of alzheimer's disease dementia. *Trends in neurosciences*, 34:430–42, 06 2011. doi: 10.1016/j.tins.2011.05.005.

Ian Goodfellow, Jean Pouget-Abadie, Mehdi Mirza, Bing Xu, David Warde-Farley, Sherjil Ozair, Aaron Courville, and Y. Bengio. Generative adversarial networks. *Advances in Neural Information Processing Systems*, 3, 06 2014.

Christian Habeck, Norman Foster, Robert Perneczky, Alexander Kurz, Panagiotis Alexopoulos, Robert Koeppe, Alexander Drzezga, and Yaakov Stern. Multivariate and univariate neuroimaging biomarkers of alzheimer's disease. *NeuroImage*, 40:1503–15, 06 2008. doi: 10.1016/j.neuroimage.2008.01.056.

Harald Hampel, Katharina Bürger, Stefan Teipel, Arun Bokde, Henrik Zetterberg, and Kaj Blennow. Core candidate neurochemical and imaging biomarkers of alzheimer's disease. *Alzheimer's & dementia : the journal of the Alzheimer's Association*, 4:38–48, 01 2008. doi: 10.1016/j.jalz.2007.08.006.

Diederik Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *International Conference on Learning Representations*, 12 2014.

Daniel Lee and H. Seung. Learning the parts of objects by non-negative matrix factorization. *Nature*, 401:788–91, 11 1999. doi: 10.1038/44565.

Raymond Pomponio, Guray Erus, Mohamad Habes, Jimit Doshi, Dhivya Srinivasan, Elizabeth Mamourian, Vishnu Bashyam, Ilya M. Nasrallah, Theodore D. Satterthwaite, Yong Fan, Lenore J. Launer, Colin L. Masters, Paul Maruff, Chuanjun Zhuo, Henry Völzke, Sterling C. Johnson, Jurgen Fripp, Nikolaos Koutsouleris, Daniel H. Wolf, Raquel Gur, Ruben Gur, John Morris, Marilyn S. Albert, Hans J. Grabe, Susan M. Resnick, R. Nick Bryan, David A. Wolk, Russell T. Shinohara, Haochang Shou, and Christos Davatzikos. Harmonization of large mri datasets for the analysis of brain imaging patterns throughout the lifespan. *NeuroImage*, 208:116450, 2020. ISSN 1053-8119. doi: https://doi.org/10.1016/j.neuroimage.2019.116450. URL `http://www.sciencedirect.com/science/article/pii/S1053811919310419`.

Cox R.W. Afni: software for analysis and visualization of functional magnetic resonance neuroimages. *Comput Biomed Res*, 29:162–173, 06 1996. doi: 10.1006/cbmr.1996.0014.

J Sled, Alex Zijdenbos, and Alan Evans. Sled jg, zijdenbos ap, evans aca non-parametric method for automatic correction of intensity nonuniformity in mri data. ieee trans med imaging 17:87-97. *IEEE transactions on medical imaging*, 17:87–97, 03 1998. doi: 10.1109/42.668698.

Erdem Varol, Aristeidis Sotiras, and Christos Davatzikos. Hydra: Revealing heterogeneity of imaging and genetic patterns through a multiple max-margin discriminative analysis framework. *NeuroImage*, 145, 02 2016. doi: 10.1016/j.neuroimage.2016.02.041.

Junhao Wen, Erdem Varol, Ganesh Chand, Aristeidis Sotiras, and Christos Davatzikos. Magic: Multi-scale heterogeneity analysis and clustering for brain diseases. 09 2020. ISBN 978-3-030-59727-6. doi: 10.1007/978-3-030-59728-3_66.

Zhijian Yang, Ilya M. Nasrallah, Haochang Shou, Junhao Wen, Jimit Doshi, Mohamad Habes, Guray Erus, Ahmed Abdulkadir, Susan M. Resnick, David Wolk, and Christos Davatzikos. Disentangling brain heterogeneity via semi-supervised deep-learning and mri: dimensional representations of alzheimer's disease, 2021.

Alexandra Young, Razvan Marinescu, Neil Oxtoby, Martina Bocchetta, Keir Yong, Nicholas Firth, David Cash, David Thomas, Katrina Moore, Manuel Jorge Cardoso, John Swieten, Barbara Borroni, Daniela Galimberti, Mario Masellis, Maria Tartaglia, James Rowe, Caroline Graff, Fabrizio Tagliavini, Giovanni Frisoni, and Daniel Alexander. Uncovering the heterogeneity and temporal complexity of neurodegenerative diseases with subtype and stage inference. *Nature Communications*, 9, 10 2018. doi: 10.1038/s41467-018-05892-0.

Xiuming Zhang, Elizabeth Mormino, Nanbo Sun, Reisa Sperling, Mert Sabuncu, and B.T. Thomas Yeo. Bayesian model reveals latent atrophy factors with dissociable cognitive trajectories in alzheimer's disease. *Proceedings of the National Academy of Sciences*, 113:E6535–E6544, 10 2016. doi: 10.1073/pnas.1611073113.

A APPENDIX

A.1 REMARK1

By minimizing the reconstruction loss L_{recons} defined in section 2.2.2 and 2.2.3, we are maximizing a lower bound of the mutual information between latent variable $\mathbf{z}$ and synthesized PT data $\mathbf{y}' = f(\mathbf{x}, \mathbf{z})$. Considering $Q(\mathbf{z}|\mathbf{y}')$ to be an approximation of distribution $P(\mathbf{z}|f(\mathbf{x}, \mathbf{z}))$ and assuming that it follows a Gaussian distribution $N(g(\mathbf{y}'), \Sigma)$, mutual information denoted by I and entropy denoted by H, we can derive that:

$$I(\mathbf{z}, f(\mathbf{x}, \mathbf{z})) = H(\mathbf{z}) - H(\mathbf{z}|f(\mathbf{x}, \mathbf{z})) \tag{17}$$

$$= \mathbb{E}_{\mathbf{y}' \sim p_{syn}(\mathbf{y}')}[\mathbb{E}_{\mathbf{z}' \sim p(\mathbf{z}|\mathbf{y}')}[\log P(\mathbf{z}'|\mathbf{y}')]] + H(z) \tag{18}$$

$$= \mathbb{E}_{\mathbf{y}' \sim p_{syn}(\mathbf{y}')}[D_{\text{KL}}(P(\cdot|\mathbf{y}')||Q(\cdot|\mathbf{y}')) + \mathbb{E}_{\mathbf{z}' \sim p(\mathbf{z}|\mathbf{y}')}[\log Q(\mathbf{z}'|\mathbf{y}')]] + H(\mathbf{z}) \tag{19}$$

$$\geq \mathbb{E}_{\mathbf{y}' \sim p_{syn}(\mathbf{y}')}[\mathbb{E}_{\mathbf{z}' \sim p(\mathbf{z}|\mathbf{y}')}[\log Q(\mathbf{z}'|\mathbf{y}')]] \tag{20}$$

$$= \mathbb{E}_{\mathbf{z} \sim p_{lat}(z), \mathbf{y}' \sim p_{syn}(f(\mathbf{x}, \mathbf{z}))}[\log Q(\mathbf{z}|\mathbf{y}')] \tag{21}$$

$$= \mathbb{E}_{\mathbf{z} \sim p_{lat}(z), \mathbf{x} \sim p_{cn}(\mathbf{x})}[[\log Q(\mathbf{z}|f(\mathbf{x}, \mathbf{z}))]] \tag{22}$$

$$\approx \frac{1}{nm} \sum_{i=1}^{n} \sum_{j=1}^{m} \left(-\frac{\ln |\Sigma|}{2} - \frac{1}{2}(\mathbf{z}_i - f(\mathbf{x}_j, \mathbf{z}_i))^T \Sigma^{-1}(\mathbf{z}_i - f(\mathbf{x}_j, \mathbf{z}_i)) + \text{constant}\right) \tag{23}$$

(21) and (22) follows the Lemma 5.1 in Info-GAN (Chen et al. (2016)) and law of the unconscious statistician (Lotus) Theorem respectively. Therefore, we derive that the mutual information between the latent variable $\mathbf{z}$ and synthesized PT data $\mathbf{y}'$ is bounded below by $\frac{1}{nm} \sum_{i=1}^{n} \sum_{j=1}^{m} (-\frac{\ln |\Sigma|}{2} - \frac{1}{2}(\mathbf{z}_i - f(\mathbf{x}_j, \mathbf{z}_i))^T \Sigma^{-1}(\mathbf{z}_i - f(\mathbf{x}_j, \mathbf{z}_i)) + \text{constant})$. With a further assumption that Σ is an identity matrix, maximization of this lower bound is equivalent to minimizing the reconstruction loss L_{recons}.

A.2 NETWORK ARCHITECTURE

Table 3 and Table 4 display network architectures of transformation function f, discriminator D and reconstruction function g (consisting of g_1 and g_2).

Table 3: Architecture of mapping function f

	Layer	Input Size	Bias Term	leaky relu α	Output Size
Encoder from $\mathbf{x}$	Linear1+Leaky-Relu	139*1	No	0.2	69*1
	Linear2+Leaky-Relu	69*1	No	0.2	34*1
Decoder from $\mathbf{z}$	Linear1+Sigmoid	M*1	Yes	NA	34*1
Decoder to $\mathbf{y}'$	Linear1+Leaky-Relu	34*1	No	0.2	69*1
	Linear2+Leaky-Relu	69*1	No	0.2	139*1

Table 4: Architecture of discriminator D, Decomposer g_1 and Reconstruction g_2

	Layer	Input Size	Bias Term	leaky relu α	Output Size
Discriminator	Linear1+Leaky-Relu	139*1	Yes	0.2	69*1
	Linear2+Leaky-Relu	69*1	Yes	0.2	34*1
	Linear3+Softmax	34*1	Yes	NA	2*1
g_1	Leaky-Relu+Linear1	139*1	Yes	0.2	(139*M)*1
g_2	Linear1+Leaky-Relu	139*1	Yes	0.2	69*1
	Linear2+Leaky-Relu	69*1	Yes	0.2	34*1
	Linear3+Softmax	34*1	Yes	NA	M*1

A.3 Algorithm

Detailed training procedure of Surreal-GAN is disclosed by Algorithm 1.

Algorithm 1: Surreal-GAN training procedure. l_c represents cross entropy loss and e_i represents a one hot vector with 1 at i_{th} component. $\hat{q}_{f(x,z)}$, $\hat{l}_{g_2(g_1(f(x,z)))}$ and $A_{f(x,z)}$ are defined in section 2.2.3 and 2.2.4.

while *not meeting stopping criteria or reaching max_epoch* **do**
> **for** *all batches* $\{x_i\}_{i=1}^m, \{y_i\}_{i=1}^m$ **do**
>> sample m latent vectors $\{z_i\}_{i=1}^m$ from multivariate uniform distribution with
>> $z_i \sim U[0,1]^M$
>>
>> **Update weights of discriminator D:** Use ADAM to update θ_D with gradient:
>> $\nabla_{\theta_D} \frac{1}{m} \sum_{i=i}^m [(l_c(D(y_i), e_1) + l_c(D(f(x_i, z_i)), e_0)))]$
>>
>> sample m latent vectors $\{z_i'\}_{i=1}^m$ conditioned on previously sampled $\{z_i\}_{i=1}^m$, with each
>> $z_{i_j}' \sim U(z_{i_j}, 1]^M$
>> sample another m latent vectors $\{z_i^{cn}\}_{i=1}^m$ with each $z_i^{cn} \sim U(0, 0.05)^M$
>>
>> **Update weights of mapping function f:** Use ADAM to update θ_f with gradient:
>> $\nabla_{\theta_f} \frac{1}{m} \sum_{i=i}^m [l_c(D(f(x_i, z_i)), e_1))) + \gamma(||f(x_i, z_i) - x_i||_1) + \kappa||g_1(f(x_i, z_i)) - \hat{q}_{f(x_i,z_i)}||_2 + \zeta||\hat{l}_{g_2(g_1(f(x_i,z_i)))} - z_i||_2 + \lambda||A_{f(x_i,z_i)}^T A_{f(x_i,z_i)} - I||_F + \mu|| \max(|f(x_i, z_i) - x_i| - |f(x_i, z_i') - x_i|, 0)||_2 + \eta||f(x_i, z_i^{cn}) - x_i||_1]$
>>
>> **Update weights of function g_1:** Use ADAM to update θ_{g_1} with gradient:
>> $\nabla_{\theta_{g_1}} \frac{1}{m} \sum_{i=i}^m [||g_1(f(x_i, z_i)) - \hat{q}_{f(x_i,z_i)}||_2]$
>>
>> **Update weights of function g_2:** Use ADAM to update θ_{g_2} with gradient:
>> $\nabla_{\theta_{g_2}} \frac{1}{m} \sum_{i=i}^m [||l_{g_2(g_1(f(x_i,z_i)))} - z_i||_2$
> **end**
end

A.4 Regions with simulated atrophy in semi-synthetic datasets

Regions of interest (ROI) included in three patterns (P1-P3) in different semi-synthetic datasets are revealed by Table 5. Small overlapping case indicates the distribution of ROIs in three different dataset as described in section 4.2: (1) Basic dataset; (4)Within-pattern noise dataset and (5)Mild atrophy dataset. Each ROI is a combination of left and right parts of the region, so each check sign represents inclusion of 2 out of 139 regions.

A.5 Associations with Clinical Variables

Each dimension of R-indices, r_i, is compared with different clinical variables for AD disease. For each clinical variable, we only selected out samples who have it available for statistical analyses. ADNI composite scores, including ADNI-EF, ADNI-MEM and ADNI-LAN, measure subjects' functions in executive functions, memory and language respectively. They are only available among subjects from Alzheimer's Disease Neuroimaging Initiative (ADNI) study. Digit Symbol Substitution Test (DSST) measures a range of cognition operations including motor speed, attention, and visuoperceptual. For all mentioned clinical scores, a higher value indicates a better performance. CSF-Abeta, CSF-Tau and CSF-PTau are three very important hallmarks of AD disease corresponding to amyloid and tau hypotheses. Since measures of these three values have great variance among different studies, only ADNI samples with CSF measures were included for analysis. For dichotomous variables (Apoe-E4 Alleles Carrier & Hypertension), point biserial correlation with corresponding p value was derived between the variable and each pattern dimension, r_i. Pearson correlations were derived for other continuous variables.

Table 5: ROIs included in synthetic patterns (OP:opercular part; TP: triangular part)

ROI	Small overlapping			Large overlapping			Scarce Region		
	P1	P2	P3	P1	P2	P3	P1	P2	P3
Amygdala	✓			✓	✓		✓		
Hippocampus	✓	✓		✓	✓		✓		
Angular gyrus			✓			✓			✓
entorhinal area	✓			✓					
frontal operculum		✓			✓				
inferior temporal gyrus	✓			✓					
lateral orbital gyrus			✓			✓			
medial frontal cortex		✓	✓		✓	✓			
middle frontal gyrus		✓			✓	✓		✓	
middle occipital gyrus			✓			✓			
OP of the inferior frontal gyrus		✓			✓			✓	
parahippocampal gyrus	✓			✓					
posterior insula		✓			✓				
parietal operculum	✓		✓	✓		✓			
supramarginal gyrus			✓			✓			
superior parietal lobule			✓	✓		✓			✓
temporal pole	✓			✓					
TP of the inferior frontal gyrus		✓			✓				