LEARNING INSTANCE-SOLUTION OPERATOR FOR OPTIMAL CONTROL

ABSTRACT

Optimal control problems (OCPs) aim at finding a control function for a dynamical system such that a cost functional is optimized. These problems are central to physical system research in both academia and industry. In this paper, we propose a novel instance-solution operator learning perspective, which solves OCPs in a one-shot manner with no dependence on the explicit expression of dynamics or iterative optimization processes. The design is in principle endowed with substantial speedup in running time, and the model reusability is guaranteed by high-quality in- and out-of-distribution generalization. We theoretically validate the perspective by presenting the approximation bounds for the instance-solution operator learning. Extensive experiments on 6 physical systems verify the effectiveness and efficiency of our approach. The source code will be made publicly available.

1 INTRODUCTION

The explosion of data for embedding the physical world is reshaping the ways we understand, model, and control dynamical systems. Though control theory has been classically rooted in a model-based design and solving paradigm, the demands of model reusability, and the opacity of complex dynamical systems call for a rapprochement of modern control theory, machine learning, and optimization. Recent years have witnessed emerging trends of control theories with successful applications to engineering and scientific research, such as robotics (Krimsky & Collins, 2020), aerospace technology (He et al., 2019), economics and management (Lapin et al., 2019), and biology (Sweilam & Al-Mekhlafi, 2022) among others.

We consider the well-established formulation of optimal control (Kirk, 2004) with finite time horizon $T = [t_0, t_f]$ in Lebesgue measurable function space $L^2(\Xi; \Phi)$ with domain Ξ and range Φ. Denote the d_x-dim state function as $X \subset L^2(T; \mathbb{R}^{d_x})$ and the d_u-dim control function as $U \subset L^2(T; \mathbb{R}^{d_u})$, altogether constituting the domain of the cost functional $F \subset L^2(X \times U; \mathbb{R})$. The state function $\boldsymbol{x} \in X$ and control function $\boldsymbol{u} \in U$ are governed by a differential equation. The optimal control problem (OCP) is targeted at finding a control function that minimizes the cost functional $f \in F$ (Lions, 1992; Kirk, 2004; Vinter & Vinter, 2010; Lewis et al., 2012):

$$\min_{\boldsymbol{u} \in U} \quad f(\boldsymbol{x}, \boldsymbol{u}) = \int_{t_0}^{t_f} p(\boldsymbol{x}(t), \boldsymbol{u}(t)) \, \mathrm{d}t + h(\boldsymbol{x}(t_f)) \tag{1a}$$

$$\text{s.t.} \quad \dot{\boldsymbol{x}}(t) = \boldsymbol{d}(\boldsymbol{x}(t), \boldsymbol{u}(t)), \tag{1b}$$

$$\boldsymbol{x}(t_0) = \boldsymbol{x}_0, \tag{1c}$$

where $\boldsymbol{d}$ is the dynamics of differential equations; p evaluates the cost alongside the dynamics and h evaluates the cost at the termination state $\boldsymbol{x}(t_f)$; and $\boldsymbol{x}_0$ is the initial state. We restrict our discussion to differential equation-governed optimal control problems, leaving the control problems in stochastic networks (Dai & Gluzman, 2022), inventory management (Abdolazimi et al., 2021), etc. out of our scope. The analytic solution of Eq. 1 is usually unavailable, especially for complex dynamical systems. Thus, there has been a wealth of research on accurate, efficient, and scalable numerical OCP solvers (Rao, 2009) and neural network based solvers (Kiumarsi et al., 2017) in recent years. However, both classic and modern numerical OCP solvers are facing challenges, especially emerging in the big data era, which we briefly discuss as follows.

Table 1: Comparison of modern optimal control approaches. OptCtrlOP naturally covers all the merits in the sense of performing a single-phase direct-mapping paradigm that does not rely on known system dynamics, and supports arbitrary input-domain queries.

Methods	Phase	Continuity	Dynamics	Reusability	Paradigm
Direct (Böhme & Frank, 2017a)	Single	Discrete	Required	No	Iterative
Two-Phase (Hwang et al., 2022)	Two	Discrete	Dispensable[1]	Partial[2]	Iterative
PDP (Jin et al., 2020)	Single	Discrete	Required	No	Iterative
DP (Tassa et al., 2014)	Single	Discrete	Required	No	Iterative
OptCtrlOP (ours)	Single	Continuous	Dispensable	Yes	One-pass

[1] if phase-1 uses PINN loss (Wang et al., 2021a): required.   [2] only phase-1 is reusable.

1) Opacity of Dynamical Systems. Existing works (Böhme & Frank, 2017a; Effati & Pakdaman, 2013; Jin et al., 2020) assume the dynamical systems a priori and exploit their explicit forms to ease the optimization. However, the real-world dynamical systems can be unknown to researchers. It raises serious challenges in data collection and system inference (Schmidt et al., 2021; Ghosh et al., 2021), where special care is required for error reduction.

2) Model Reusability. Since solving an individual instance of Eq. 1 is time-consuming, a reusable computational model that can be well adapted to systems of similar forms is preferred for practical usage. This point traces to the research on the sensitivity analysis of optimal control problems (Oniki, 1973) but is absent in recent works.

3) Running Paradigm. As of typical paradigms adopted in optimization, numerical optimal control solvers traditionally use iterative methods before picking the control solution, and thus introducing a multiplicative term regarding the iteration in the running time complexity. This sheds light on the high computational cost of solving a single optimal control problem.

4) Control Solution Continuity. Control functions are defined on a continuous domain (typically time), although being intractable for numerical solvers. Hence resorting to discretization in the input domain gives rise to the trade-off in the precision of the control solution and the computational cost, as well as the truncation errors. While the discrete solution can give point-wise queries, learning a control function for arbitrary time queries is much more valued.

5) Running Phase. A two-phase model (Chen et al., 2018; Wang et al., 2021a; Hwang et al., 2022) can (partially) overcome the above issues at the cost of introducing an auxiliary dynamics inference phase. However, the two-phase paradigm increases computational cost and manifests inconsistency between the two phases. A motivating example in Fig. 1 shows the two-phase paradigm leads to crucial failures. When the domain of phase-2 optimization goes outside the training distribution in phase-1, this method might collapse.

Figure 1: Phase-2 cost curves of two failed instances of two-phase control on Pendulum system. The control function gradually moves outside the training data distribution of phase-1. As a result, the control function converges w.r.t. the cost predicted by the surrogate model (blue), but diverges w.r.t. true cost (red).

We compare the mainstream methods regarding the above aspects in Table 1. With a striking difference from the extant literature, we propose a novel instance-solution operator perspective for learning to solve OCPs, thereby tackling all the issues above. **We list the main contributions as follows.**

1. The proposed operator perspective solves OCPs by learning direct mappings from OCPs to their solutions. The design in principle holds the following merits. The system dynamics is implicitly learned during the training process, it relies on neither any explicit form of the system nor the optimization process at test time. The operator can be reused and generalized to similarly-formed OCPs without retraining. The single-phase direct mapping paradigm avoids iterative processes in optimization and contributes to a substantial speedup.

2. We theoretically validate the instance-solution mapping perspective by leveraging Pontryagin's Maximum Principle, thereby converting Eq. 1 to a boundary value problem. We instantiate a neural

solver, termed as OptCtrlOP (Optimal Control OPerator), and give theoretical bounds on its approximation error.

3. Experiments on real physical systems show that OptCtrlOP is versatile for various forms of OCPs. It achieves 100x speedup against MLP baseline, and 10Kx speedup over classical direct method solvers. It also generalizes well on both in- and out-of-distribution OCP instances.

2 BACKGROUND AND RELATED WORK

In this section, we will provide a concise introduction to two related research topics, namely Differential Equation (DE) neural solvers and OCP solvers.

2.1 DIFFERENTIAL EQUATION NEURAL SOLVERS

A variety of networks have been developed to solve DE, including Physics-informed neural networks (PINNs) (Raissi et al., 2019), neural operators (Lu et al., 2021), hybrid models (Mathiesen et al., 2022; Lienen & Günnemann, 2021), and frequency domain models (Li et al., 2020; Poli et al., 2022). We will briefly introduce the first two models for their close relevance to our work.

PINNs parameterize the DE solution as a neural network, and learn the parameters by minimizing the sum of the residual loss and boundary condition loss (Yu et al., 2018; Raissi et al., 2019; Sirignano & Spiliopoulos, 2018). PINNs are similar to those numerical methods e.g. the finite element method in that they replace the linear span of a finite set of local basis functions with neural networks. PINNs usually have simple architectures (e.g. MLP), although they have produced remarkable results across a wide range of areas in computational science and engineering (Raissi et al., 2020; Zhu et al., 2019). However, these models are limited to learning the solution of one specific DE instance, but not the operator. In other words, if the coefficients of the DE instance slightly change, then a new neural network needs to be trained accordingly, which is time-consuming. Another major drawback of PINNs, as pointed out by Wang et al. (2021b), is that the magnitude of two loss terms is inherently imbalanced, leading to heavily biased predictions even for simple linear equations.

Neural operators regards DE as an operator that maps the input to the solution. Learning operators using neural networks is initially introduced in the seminal work (Chen & Chen, 1995). It proposes the universal approximation theorem for operator learning, i.e. a network with a single hidden layer can approximate any nonlinear continuous operator. Lu et al. (2021) follows this theorem by designing a deep learning architecture named *DeepONet*, which consists of two networks: a branch net for input functions and a trunk net for the querying locations in the output space. In this paper, we choose this architecture as our OCP operator learner, and our analysis of optimal control error bound is partly inspired by Lanthaler et al. (2022), providing error estimation of DeepONet. Note that DeepONet is designed to solve DE operators, and is not ready to handle optimization tasks such as OC. Neural operators with other architectures will be discussed in Appendix B.

2.2 OPTIMAL CONTROL SOLVERS

Most OCPs can not be solved analytically, and numerical methods are developed, which can be mainly categorized into three groups: direct methods, indirect methods, and dynamic programming. Our work bears a resemblance to indirect methods as will be discussed in detail. Due to space limits, we leave the dynamic programming to Appendix B.

Direct methods (Böhme & Frank, 2017a) reformulate OCP as finite-dimensional nonlinear programming (NLP) (Bazaraa et al., 2013), and solve the problem by NLP algorithms, e.g. sequential quadratic programming (Boggs & Tolle, 1995) and interior-point method (Mehrotra, 1992). The reformulation essentially constructs surrogate models, where the state and control function (infinite dimension) is replaced by polynomial or piece-wise constant functions. The dynamics constraint is discretized into equality constraints. The direct methods optimize on the surrogate models, thus the solution is not guaranteed to be optimal for the origin problem. Likewise, typical direct neural solvers (Chen et al., 2018; Wang et al., 2021a; Hwang et al., 2022), termed as Two-Phase models, consist of two phases: 1) approximating the dynamics by a neural network (surrogate model); 2) solving the NLP via gradient descent, by differentiating through the network. The advantage of Two-Phase models against traditional direct methods is the computational efficiency, especially in

high-dimensional cases. However, the two-phase method is sensitive to data distribution shift, as shown in Fig. 1.

Indirect methods (Böhme & Frank, 2017b) are based on Pontryagin's Maximum Principle (PMP) (Pontryagin, 1987). By PMP, indirect methods convert OCP (Eq. 1) into a boundary-value problem (BVP) (Lasota, 1968), which is then solved by numerical methods such as shooting method (Bock & Plitt, 1984), collocation method (Xiu & Hesthaven, 2005), adjoint-based gradient descend (Effati & Pakdaman, 2013; Jin et al., 2020). These numerical methods are sensitive to the initial guesses of the solution. Some existing indirect methods based neural solvers approximate the finite-dimensional mapping from state $\boldsymbol{x}^*(t) \in \mathbb{R}^{d_x}$ to control $\boldsymbol{u}^*(t) \in \mathbb{R}^{d_u}$ (Cheng et al., 2020), or to co-state $\boldsymbol{\lambda}^*(t) \in \mathbb{R}^{d_x}$ (Xie et al., 2018). The full trajectory of the control function is obtained by repeatedly applying the mapping and getting feedback from the system, and such sequential nature is the efficiency bottleneck. Another work (D'ambrosio et al., 2021) proposes to solve the BVP via a PINN, thus its trained network works only for one specific OCP instance. Distinctive from all these models, OptCtrlOP solves BVP by learning an infinite-dimensional operator that maps cost functional $f \in F$ to control function $\boldsymbol{u}^* \in U$. The trained model is available for parallel queries on different OCP instances, with high efficiency and accuracy.

3 METHODOLOGY

In this section, we present the instance-solution operator perspective for solving OCPs. Inspired by Pontryagin's Maximum Principle, OCPs (Eq. 1) can be converted to a boundary value problem (BVP), the solution of which is a typical function operator. The operator can further be approximated accurately by neural networks with theoretical guarantees. Hence, we propose OptCtrlOP, an end-to-end OCP neural solver that learns the underlying infinite-dimensional operator $\mathcal{G}$ governed by BVP. The input of operator $\mathcal{G}$ is the cost functional f, and the output is the optimal control function $\boldsymbol{u}^*$, i.e. $\mathcal{G} : F \to U$. OptCtrlOP learns such an operator from paired data by minimizing the error between predicted and optimal control, without explicit knowledge of the dynamics. Our theoretical analysis guarantees that for an arbitrary small approximation error tolerance, there exists an instance of OptCtrlOP that satisfies the tolerance with bounded size and depth.

3.1 INSTANCE-SOLUTION OPERATOR PERSPECTIVE OF OCP

This section presents the theoretical pre-condition of our model, a novel perspective that converts OCPs into an operator that maps problem instances (defined by cost functionals and dynamics) into their solutions. The conversion consists of two steps: 1) convert OCP into BVP by PMP, and 2) define the operator based on BVP, as explained below. Here we assume the dynamics are deterministic DE, and the derivation of stochastic DE (SDE) (Carius et al., 2022; Kishida & Ogura, 2022) is similar but based on Hamilton-Jacobi-Bellman (HJB) equation (Yong & Zhou, 1999), which is left for future work.

We elaborate how PMP converts OCP into BVP, following the derivation of the first-order necessary optimality conditions in the calculus of variations. To begin with, define the Hamiltonian $\mathcal{H}$ of Eq. 1 as:

$$\mathcal{H}(\boldsymbol{x}, \boldsymbol{u}, \boldsymbol{\lambda}) := p(\boldsymbol{x}, \boldsymbol{u}) + \boldsymbol{\lambda}^\top \boldsymbol{d}(\boldsymbol{x}, \boldsymbol{u}). \tag{2}$$

Then suppose $\boldsymbol{u}^* \in U$ is the optimal control function, and $\boldsymbol{x}^* \in X$ is the optimal state trajectory. The PMP asserts that there exists a co-state (adjoint) function $\boldsymbol{\lambda}^* : T \to \mathbb{R}^{d_x}$ such that the following BVP is satisfied (Pontryagin, 1987):

$$\text{dynamics:} \qquad \dot{\boldsymbol{x}}^* = \frac{\partial}{\partial \boldsymbol{\lambda}} \mathcal{H}(\boldsymbol{x}^*, \boldsymbol{u}^*, \boldsymbol{\lambda}^*), \tag{3a}$$

$$\text{co-state:} \qquad \dot{\boldsymbol{\lambda}}^* = -\frac{\partial}{\partial \boldsymbol{x}} \mathcal{H}(\boldsymbol{x}^*, \boldsymbol{u}^*, \boldsymbol{\lambda}^*), \tag{3b}$$

$$\text{optimal control:} \qquad \boldsymbol{0} = \frac{\partial}{\partial \boldsymbol{u}} \mathcal{H}(\boldsymbol{x}^*, \boldsymbol{u}^*, \boldsymbol{\lambda}^*), \tag{3c}$$

$$\text{boundary conditions:} \qquad \boldsymbol{\lambda}^*(t_f) = \frac{\partial}{\partial \boldsymbol{x}} h(\boldsymbol{x}^*(t_f)), \quad \boldsymbol{x}^*(t_0) = \boldsymbol{x}_{init}. \tag{3d}$$

A BVP is composed of a set of DEs along with boundary conditions. The BVP defines an implicit mapping from cost functional and dynamics, both of which can be represented by functions, to the optimal control function, with state and co-state being intermediate variables.

Based on BVP, one can define an operator according to concrete problem settings or protocols. In this paper, we follow a commonly used neural OCP solver protocol such that: the initial state $\boldsymbol{x}_{init}$ and the dynamics $\boldsymbol{d} : X \times U \to \mathbb{R}$ are unknown but constant (Hwang et al., 2022). Consequently, the state $\boldsymbol{x}$ is uniquely determined by control $\boldsymbol{u}$, thus the cost functional $f : X \times U \to \mathbb{R}$ can be rewritten interchangeably as $f_{\boldsymbol{d}} : U \to \mathbb{R}$. Under the protocol, the operator is defined as $\mathcal{G} : F \to U$, a mapping from cost functional to optimal control.

In this way, we have converted the OCPs into an operator, which directly maps OCP instances to their solutions. Theoretically, the operator is able to solve all OCPs of the same type (e.g. governed by the same dynamics $\boldsymbol{d}$), thus highly reusable and efficient. Since in practice such a non-linear operator can hardly have a closed-form expression, we propose the following neural model that learns the operator in a data-driven approach.

3.2 ARCHITECTURE OF THE PROPOSED NEURAL MODEL

From the operator perspective discussed above, constructing an OCP solver is equivalent to an operator learning problem. Inspired by DeepONet (Lu et al., 2021), we propose Operator Learning based Control Network (OptCtrlOP) as an instance to solve the OCP by learning the non-linear operator $\mathcal{G}$ directly, and theoretically show the error bounds estimation. Specifically, we decompose OptCtrlOP into three components, as proposed in (Lanthaler et al., 2022):

1. **Encoder.** We define the following mapping as the encoder: $\mathcal{E} : F \to \mathbb{R}^m$, which converts the infinite-dimensional cost functional f into a finite-dimensional vector $\boldsymbol{e}$ that can be processed by neural networks. For demonstration, we now let the encoder be an ad-hoc function that returns the target state $\boldsymbol{x}_{goal}$. Such a simplified encoder is still effective, since the form of the cost functional is assumed fixed, and the only parameter is the target state (Eq. 12, following Jin et al. (2020)). Otherwise, the encoder can be implemented by functional approximations, e.g. point-wise evaluation, basis expansion, or neural network. For example, in the Heating system (Appendix D.5) the encoder output is the coefficients of a trigonometric polynomial.

2. **Approximator.** The encoded vector $\boldsymbol{e}$ is mapped to another finite dimensional vector $\boldsymbol{a}$ by the approximator mapping defined as: $\mathcal{A} : \mathbb{R}^m \to \mathbb{R}^p$.

The approximator is implemented by a neural network termed as *branch net* $\boldsymbol{\beta}$, which is a ReLU activated multi-layer perceptron (MLP)(Goodfellow et al., 2016):

$$\boldsymbol{\beta}(\boldsymbol{e}) = g_{d_{\boldsymbol{\beta}}} \circ \sigma \circ g_{d_{\boldsymbol{\beta}}-1} \circ \ldots \sigma \circ g_1(\boldsymbol{e}),$$
$$g_i(\boldsymbol{h}) = \boldsymbol{W}_i \boldsymbol{h} + \boldsymbol{c}_i, \quad 1 \le i \le d_{\boldsymbol{\beta}},$$
$$\sigma(\boldsymbol{h}) = \max\{0, \boldsymbol{h}\},$$

where $d_{\boldsymbol{\beta}}$ is the network depth, and $\{\boldsymbol{W}_i, \boldsymbol{c}_i\}_{1 \le i \le d_{\boldsymbol{\beta}}}$ are trainable parameters. The output vector $\boldsymbol{a} = \boldsymbol{\beta}(\boldsymbol{e})$ will serve as the coefficient vector of basis functions produced by the following reconstructor.

3. **Reconstructor.** It reconstructs the control function $\boldsymbol{u}$ by the mapping: $\mathcal{R} : \mathbb{R}^p \to U$.

The reconstructor firstly constructs $p + 1$ basis functions via another MLP named *trunk net*, $\boldsymbol{\tau} : T \to \mathbb{R}^{p+1}$, a parametric mapping from time to basis function values. Note that the original DeepONet trunk net output is p-dimensional, we add an additional bias function dimension as suggested by (Lanthaler et al., 2022). Then, the control function $\boldsymbol{u} = \mathcal{R}(\boldsymbol{a})$ is reconstructed by an affine combination of basis functions, where the coefficient $\boldsymbol{a}$ is produced by the approximator:

$$\mathcal{R}(\boldsymbol{a}) := \tau_0 + \boldsymbol{a}^\top \boldsymbol{\tau}_{1:p}. \tag{4}$$

Combining three components together, OptCtrlOP maps the cost functional to a control function, $\mathcal{N} : F \to U$, and can be viewed as a composition of the above three mappings:

$$\mathcal{N} := \mathcal{R} \circ \mathcal{A} \circ \mathcal{E}. \tag{5}$$

The forward step of OptCtrlOP $\mathcal{N}$ is also described in Alg. 1 in Appendix A.

3.3 APPROXIMATION ERROR ESTIMATION

We give the estimation for the approximation error of the proposed model. The theoretic result guarantees that there exists a neural network instance of OptCtrlOP architecture (Eq. 5) approximating the operator $\mathcal{G}$ to arbitrary error tolerance. Furthermore, the size and depth of such a network are upper-bounded. The technical line of our analysis is partly inspired by (Lanthaler et al., 2022) which provides error estimation for DeepONets (Lu et al., 2021).

The error of interest in OCP is the distance between the cost of the solution and the optimal cost. Let μ be the probability measure of cost functional, with $\mu \in \mathcal{P}_2(F)$, where $\mathcal{P}_2(F)$ is the set of probability measures with finite second moments. Furthermore, We assume the control dimension $d_u = 1$, and $f_{\boldsymbol{d}} > 0$ in the following theoretical analyses, w.l.o.g. Then the **approximation error** of OptCtrlOP can be defined as:

$$\widehat{\mathscr{E}} := \int_F \left| \frac{f_{\boldsymbol{d}} \circ \mathcal{N}(f) - f_{\boldsymbol{d}} \circ \mathcal{G}(f)}{f_{\boldsymbol{d}} \circ \mathcal{G}(f)} \right| \mathrm{d}\mu(f). \tag{6}$$

Following the decomposition described in Sec. 3.2, the approximation error of OptCtrlOP can also be decomposed into three parts: 1) encoder error, 2) approximator error, and 3) reconstructor error.

The error of our simplified encoder is zero, since there exists a one-to-one mapping between the target state (encoder output) and the cost functional (encoder input). In other words, for a given OptCtrlOP encoder $\mathcal{E}$, there exists an inverse mapping $\mathcal{E}^{-1}$, such that $\mathcal{E}^{-1} \circ \mathcal{E} = \mathrm{Id}$. If the encoder is implemented by functional approximations, e.g. point-wise evaluation (Lu et al., 2021; Lanthaler et al., 2022), then the encoder error should be considered.

For a reconstructor $\mathcal{R}$, the reconstructor error $\widehat{\mathscr{E}}_{\mathcal{R}}$ is estimated by the mismatch between $\mathcal{R}$ and its approximate inverse mapping, projector $\mathcal{P}$, weighted by push-forward measure $\mathcal{G}_{\#}\mu$:

$$\widehat{\mathscr{E}}_{\mathcal{R}} := \left(\int_U \|\mathcal{R} \circ \mathcal{P}(u) - u\|_U \mathrm{d}\left(\mathcal{G}_{\#}\mu\right)(u) \right)^{\frac{1}{2}}$$

$$\mathcal{P} := \operatorname*{argmin}_{\mathcal{P}} \widehat{\mathscr{E}}_{\mathcal{R}}, \quad \text{s.t.} \quad \mathcal{P} \circ \mathcal{R} = \mathrm{Id}. \tag{7}$$

Given the encoder and reconstructor, the error $\widehat{\mathscr{E}}_{\mathcal{A}}$ induced by approximator $\mathcal{A}$ is defined as the distance between the approximator output and the optimal coefficient vector, weighted on push-forward measure $\mathcal{E}_{\#}\mu$:

$$\widehat{\mathscr{E}}_{\mathcal{A}} := \left(\int_{\mathbb{R}^m} \|\mathcal{A}(\boldsymbol{v}) - \mathcal{P} \circ \mathcal{G} \circ \mathcal{E}^{-1}(\boldsymbol{v})\|^2_{\ell^2(\mathbb{R}^p)} \mathrm{d}\left(\mathcal{E}_{\#}\mu\right)(\boldsymbol{v}) \right)^{\frac{1}{2}}. \tag{8}$$

With the definitions above, we can estimate the approximation error of our OptCtrlOP by the error of each of its components, as stated in the following theorem (see detailed proof in Appendix C.1):

Theorem 1 (**Decomposition of OptCtrlOP Approximation Error**). *Suppose the cost functional $f_{\boldsymbol{d}}$ is Lipschitz continuous. Define constant $C = \sup_{f \in F} \frac{\mathrm{Lip}(f_{\boldsymbol{d}})}{f_{\boldsymbol{d}} \circ \mathcal{G}(f)}$. The approximation error $\widehat{\mathscr{E}}$ (Eq. 6) of a OptCtrlOP $\mathcal{N} = \mathcal{R} \circ \mathcal{A} \circ \mathcal{E}$ is upper-bounded by*

$$\widehat{\mathscr{E}} \leq C\left(\mathrm{Lip}(\mathcal{R})\widehat{\mathscr{E}}_{\mathcal{A}} + \widehat{\mathscr{E}}_{\mathcal{R}} \right). \tag{9}$$

The estimation of reconstructor error $\widehat{\mathscr{E}}_{\mathcal{R}}$ is analyzed in the previous work (Lanthaler et al., 2022), which gives a detailed discussion of the error estimation of DeepONet, and the reconstructor error component is the same as that of OptCtrlOP. We cite the result to establish the following theorem:

Theorem 2 (**Reconstructor Error** (Lanthaler et al., 2022)). *If $\mathcal{G}$ defines a Lipschitz mapping $\mathcal{G} : F \to H^s(T)$,for some $s > 0, M > 0$, with $\int_F \|\mathcal{G}(f)\|^2_{H^s} \mathrm{d}\mu(f) \leq M < \infty$, then there exists a constant $C = C(s, M) > 0$, such that for any $p \in \mathbb{N}$, there exists a trunk net $\boldsymbol{\tau} : T \to \mathbb{R}^{p+1}$ (with bias term $\tau_0 \equiv 0$) and the associated reconstruction $\mathcal{R} : \mathbb{R}^p \to U$ satisfy:*

$$\mathrm{size}(\boldsymbol{\tau}) \leq Cp\left(1 + \log(p)^2\right), \qquad \mathrm{depth}(\boldsymbol{\tau}) \leq C\left(1 + \log(p)^2\right), \qquad \widehat{\mathscr{E}}_{\mathcal{R}} \leq Cp^{-s}. \tag{10}$$

Furthermore, the reconstruction $\mathcal{R}$ and the optimal projection $\mathcal{P}$ satisfy $\mathrm{Lip}(\mathcal{R}), \mathrm{Lip}(\mathcal{P}) \leq 2$.

Table 2: Typical control systems used in literature and our experiments and their dimensions.

System	Description	Dynamics	$\boldsymbol{u}$ #	$\boldsymbol{x}$ #
Pendulum	single pendulum	ODE	1	2
RobotArm	two-link robotic arm	ODE	1	4
CartPole	one pendulum with cart	ODE	1	4
Quadrotor	helicopter with 4 rotors	ODE	4	9
Rocket	6-DoF rocket	ODE	3	9
Heating	source heating on 2D plane	PDE	1	1

Note that $\mathrm{size}(\cdot)$ is defined as the number of trainable parameters of a neural network, and $\mathrm{depth}(\cdot)$ denotes the number of hidden layers. H^s is a Sobolev space with s degrees of regularity and L^2 norm. Next, the error bound of the approximator will be presented. Recall that the approximator is an MLP, whose error estimation is well studied in deep learning theory. One of the existing works (Gühring et al., 2020) derives the estimation based on the Sobolev regularity of the mapping. We extend their result to form the following theorem (proof given in Appendix C.2):

Theorem 3 (**Approximator Error**). *Given operator $\mathcal{G} : F \to U$, encoder $F \to \mathbb{R}^m$, and reconstructor $\mathcal{R} : \mathbb{R}^p \to U$, let $\mathcal{P}$ denote the corresponding projector. If for some $s \in \mathbb{N}_{\geq 2}, M > 0$, the following bound is satisfied: $\left\| \mathcal{P} \circ \mathcal{G} \circ \mathcal{E}^{-1} \right\|_{H^s(\mathcal{E}_{\#}\mu)} \leq M < \infty$, then there exists a constant $C = C(m, s, M) > 0$, such that for any $\varepsilon \in (0, \frac{1}{2})$, there exists an approximator $\mathcal{A} : \mathbb{R}^m \to \mathbb{R}^p$:*

$$\mathrm{size}(\mathcal{A}) \leq Cp^2 \varepsilon^{-m/s} \log\left(\varepsilon^{-1}\right), \qquad \mathrm{depth}(\mathcal{A}) \leq C \log\left(\varepsilon^{-1}\right), \qquad \widehat{\mathscr{E}}_{\mathcal{A}} \leq \sqrt{p}\varepsilon. \quad (11)$$

In summary, we prove that the approximation error is bounded by the sum of the reconstructor and approximator errors. Those errors can hold under arbitrary small tolerance, by OptCtrlOP with bounded size and depth. The theorems hold as long as some integratable and continuous conditions are satisfied, which is trivial in real-world OCPs.

4 EXPERIMENTS

4.1 CONTROL SYSTEMS AND DATA GENERATION

We evaluate OptCtrlOP on six representative optimal control systems by following the same protocol of Jin et al. (2020); Hwang et al. (2022), as summarized in Table 2. We postpone the rest systems to Appendix D, and only describe the details of the Pendulum control here:

$$\min_{u} \quad \int_0^{tf} \boldsymbol{c}_{\boldsymbol{x}}^\top (\boldsymbol{x}(t) - \boldsymbol{x}_{goal})^2 + c_u u^2(t) \, \mathrm{d}t \tag{12}$$

$$\text{s.t.} \quad \dot{\boldsymbol{x}}(t) = \begin{bmatrix} x_2(t) \\ [u(t) - m \cdot g \cdot l \sin x_1(t) - b \cdot x_2(t)]/I \end{bmatrix}$$

$$\boldsymbol{x}(0) = \boldsymbol{x}_{init}$$

where state $\boldsymbol{x} = [x_1, x_2]^\top$, denoting the angle and angular velocity of pendulum respectively, and control u is the external torque. The initial condition $\boldsymbol{x}_{init} = [0, 0]^\top$, i.e. the pendulum starts from the lowest position with zero velocity. The cost functional consists of two parts: state mismatching penalty and control function regularization, and $\boldsymbol{c}_{\boldsymbol{x}} = [10, 1]^\top, c_u = 0.1$ are balancing coefficients. Other constants are: $m = 1, g = 10, l = 1, I = 1/3$. For all the ODE-constrained OCP, we set the time horizon $T = [0, \text{tf}], \text{tf} \sim \mathcal{U}(1, 1.01)$.

With the settings above given, the solution of OCP only depends on the target state $\boldsymbol{x}_{goal}$. Therefore, we generate datasets (for model training/validation) and benchmarks (for model testing) by sampling target states from a pre-defined distribution. To fully evaluate the generalization ability, we define both in-distribution (ID) and out-of-distribution (OOD) (Shen et al., 2021). Specifically, we design two random variables, $\mathbf{x}_{goal}^{in} := \boldsymbol{x}_{goal}^{base} + \boldsymbol{\epsilon}_{in}$, and $\mathbf{x}_{goal}^{out} := \boldsymbol{x}_{goal}^{base} + \boldsymbol{\epsilon}_{out}$, where $\boldsymbol{x}_{goal}^{base}$ is a baseline goal state, and $\boldsymbol{\epsilon}_{in,out}$ are different noise applied to ID and OOD. In Pendulum problems for example, we set $\boldsymbol{x}_{goal}^{base} = [\pi, 0]^\top$, and uniform noise $\boldsymbol{\epsilon}_{in} \sim \mathcal{U}(0.1, 1.1)$, and $\boldsymbol{\epsilon}_{out} \sim \mathcal{U}(-0.1, 0.1)$.

(a) Running Time (s/problem)   (b) ID MAPE   (c) OOD MAPE

Figure 2: The running time and mean absolute percentage error (MAPE) on in-distribution (ID) and out-of-distribution (OOD) benchmark problem sets.

The training data are sampled from ID, while validation data and benchmark sets are both sampled from ID and OOD separately. The data generation process are summarized in Alg. 2 in Appendix. For a given distribution, we sample a target state $\boldsymbol{x}_{goal}$, construct the corresponding cost functional f and OCP. Then we solve the resulting OCP by the DM solver, and get the optimal control u^*. After that we sample 10 time indices $\{t_i\}_{1 \le i \le 10}$, creating 10 triplets $\{(f, t_i, u^*(t_i))\}_{1 \le i \le 10}$ and adding them to dataset. Repeat the process, until the size of the dataset meets the requirement. The benchmark set is generated in the same way, but we store (f, J_{opt}) pair (J_{opt} denotes the optimal cost) for each problem instead.

4.2 IMPLEMENTATION AND BASELINES

We fix the width of OptCtrlOP to 40, and tune the depth such that its size increases linearly with the dimension of state, as shown in Table 3 in Appendix E. For all systems, the learning rate starts from 0.01, decaying every 1,000 epochs at a rate of 0.9. The batch size is 10,000, and the optimizer is Adam (Kingma & Ba, 2014). The loss is the mean squared error defined below, with a dataset D of N samples: $\mathcal{L} = \frac{1}{N} \sum_{i,j \in D} \left\| \mathcal{N}(\boldsymbol{x}_{goal,j})(t_i) - \boldsymbol{u}_j^*(t_i) \right\|^2$. Other details of implementation is recorded in Appendix E. For comparison, we choose the following baselines:

1) **Direct Method (DM):** a classical direct OCP solver, with time horizon T discretized uniformly into 100 intervals. The dynamics are discretized by Euler method. The reformulated NLP is solved by Interior Point OPTimizer (IPOPT) (Biegler & Zavala, 2009).

2) **Pontryagin Differentiable Programming (PDP)** (Jin et al., 2020): an adjoint-based indirect method, differentiating through Pontryagin's Maximum Principle, and optimized by gradient descent. To limit the running time, we set the maximal number of iterations to 2,500.

3) **Multi-layer Perceptron (MLP):** a fully connected counterpart of OptCtrlOP, with the same input/output and train/test set. For fairness, hyper-parameters are the same or as close as to that of OptCtrlOP. We adjust the width of MLP layer to reach almost same number of trainable parameters as OptCtrlOP.

4.3 RESULTS AND DISCUSSION

We present the numerical results on the six systems to evaluate the efficiency and accuracy of OptCtrlOP. The metrics of interest are 1) running time of solving problems; 2) quality of solution, measured by mean absolute percentage error (MAPE) between the true optimal cost and the predicted cost, which is defined as the mean of $|(J_{opt} - J_{sol})/J_{opt}|$, where J_{opt} is the optimal cost generated by DM (regarded as ground truth), and J_{sol} is the cost of the solution produced by the model. The MAPE is calculated on ID/OOD benchmarks respectively, and the running time is averaged for 2,000 random problems. The results of ODE constrained OCP are given in Fig. 2, and the results of PDE constrained OCP are summarized in 5 in Appendix.

Firstly, the comparison of running time is shown in Fig. 2a, which shows that the neural operator solver is much faster than the classic solver. For example, OptCtrlOP achieves over 10^5 times speedup against the DM solver. The acceleration can be reasoned from two aspects: 1) the neural operator solvers produce the output by a single forward propagation, while the classic methods need to iterate between forward and backward pass multiple times; 2) the neural solver calculation is

(a) Loss (b) MAPE

Figure 3: (a) Pendulum Loss curve. (b) Pendulum cost MAPE (mean absolute percentage error) curve. Both curves are visualized after exponential moving average with weight=0.5.

Figure 4: Pendulum state trajectories of instances from ID (left two) and OOD (right two).

highly paralleled. Another observation is that OptCtrlOP is 100 times faster than MLP, although both of them are neural operator models. The difference is rooted in OptCtrlOP architecture, where two inputs (cost functional and time index) are processed by branch net and trunk net separately. Consequently, OptCtrlOP runs $\mathcal{O}(M + N)$ network forward passes, if the benchmark set consists of N problems, and the time horizon is discretized into M indices. In comparison, MLP entangles two inputs together, requiring $\mathcal{O}(MN)$ forward passes. The difference is also given in Alg. 3-4 in Appendix.

Next, the accuracy on in- and out-of-distribution benchmark set is compared in Fig. 2b-2c. Compared with MLP, OptCtrlOP achieves about 20% less MAPE for ID, and about 50% less MAPE for OOD, on average for all benchmarks. It outperforms PDP in more than half of the benchmarks. These results show the accuracy of OptCtrlOP among different tasks and distributions. For MLP there is a significant performance gap between ID and OOD. Such gap, incurred by distribution shift, is the common vulnerability of data-driven models. However, the experimental result shows OptCtrlOP is relatively robust to the distribution shift. The ID/OOD performance gap of OptCtrlOP is close to PDP (not data-driven), and much smaller than that of MLP. The OOD generalization ability of OptCtrlOP results from its architecture, where branch net and trunk net (coefficients and basis functions) are explicitly disentangled. Such a structure inherits the inductive bias from numerical basis expansion methods (e.g. Kafash et al. (2014)), thus robust to distribution shift.

As a concrete example, we investigate the learning process of the Pendulum system. From Fig. 3, one can observe that MLP performance on ID is slightly better than that of OptCtrlOP, but OptCtrlOP significantly outperforms MLP on OOD. The state trajectories of four randomly sampled OCP instances in Fig. 4 also support this observation. For ID instances, the trajectories of MLP and OptCtrlOP are almost overlapping, and both of them are close to DM trajectories (regarded as optimal). For OOD instances, MLP trajectories deviate from optimal ones, while OptCtrlOP results are still nearly optimal. The curves and trajectories of other systems are given in Appendix F.

5 CONCLUSION

We propose a novel instance-solution operator perspective of OCPs, where the operator directly maps cost functionals to optimal control functions. Based on this perspective, we present a neural operator OptCtrlOP, with a theoretic guarantee on its approximation capability. Extensive experiments on various OCP system benchmarks show the outstanding generalization ability and efficiency of OptCtrlOP, on both ID and OOD settings. We envision the proposed model will be beneficial in solving numerous high-dimensional problems in the learning and control fields.

REFERENCES

Omid Abdolazimi, Davood Shishebori, Fariba Goodarzian, Peiman Ghasemi, and Andrea Appolloni. Designing a new mathematical model based on abc analysis for inventory control problem: A real case study. *RAIRO-operations research*, 55(4):2309–2335, 2021.

Asma Al-Tamimi, Frank L Lewis, and Murad Abu-Khalaf. Discrete-time nonlinear hjb solution using approximate dynamic programming: Convergence proof. *IEEE Transactions on Systems, Man, and Cybernetics, Part B (Cybernetics)*, 38(4):943–949, 2008.

Anima Anandkumar, Kamyar Azizzadenesheli, Kaushik Bhattacharya, Nikola Kovachki, Zongyi Li, Burigede Liu, and Andrew Stuart. Neural operator: Graph kernel network for partial differential equations. In *ICLR 2020 Workshop on Integration of Deep Neural Models and Differential Equations*, 2020.

Joel A E Andersson, Joris Gillis, Greg Horn, James B Rawlings, and Moritz Diehl. CasADi – A software framework for nonlinear optimization and optimal control. *Mathematical Programming Computation*, 11(1):1–36, 2019. doi: 10.1007/s12532-018-0139-4.

Mokhtar S Bazaraa, Hanif D Sherali, and Chitharanjan M Shetty. *Nonlinear programming: theory and algorithms*. John Wiley & Sons, 2013.

Richard Bellman and Robert Kalaba. Dynamic programming and adaptive processes: mathematical foundation. *IRE transactions on automatic control*, (1):5–10, 1960.

Lorenz T Biegler and Victor M Zavala. Large-scale nonlinear programming using ipopt: An integrating framework for enterprise-wide dynamic optimization. *Computers & Chemical Engineering*, 33(3):575–582, 2009.

Hans Georg Bock and Karl-Josef Plitt. A multiple shooting algorithm for direct solution of optimal control problems. *IFAC Proceedings Volumes*, 17(2):1603–1608, 1984.

Paul T Boggs and Jon W Tolle. Sequential quadratic programming. *Acta numerica*, 4:1–51, 1995.

Thomas J. Böhme and Benjamin Frank. *Direct Methods for Optimal Control*, pp. 233–273. Springer International Publishing, Cham, 2017a. ISBN 978-3-319-51317-1. doi: 10.1007/978-3-319-51317-1_8. URL https://doi.org/10.1007/978-3-319-51317-1_8.

Thomas J. Böhme and Benjamin Frank. *Indirect Methods for Optimal Control*, pp. 215–231. Springer International Publishing, Cham, 2017b. ISBN 978-3-319-51317-1. doi: 10.1007/978-3-319-51317-1_7. URL https://doi.org/10.1007/978-3-319-51317-1_7.

Greg Brockman, Vicki Cheung, Ludwig Pettersson, Jonas Schneider, John Schulman, Jie Tang, and Wojciech Zaremba. Openai gym, 2016.

Jan Carius, René Ranftl, Farbod Farshidian, and Marco Hutter. Constrained stochastic optimal control with learned importance sampling: A path integral approach. *The International Journal of Robotics Research*, 41(2):189–209, 2022.

Tianping Chen and Hong Chen. Universal approximation to nonlinear operators by neural networks with arbitrary activation functions and its application to dynamical systems. *IEEE Transactions on Neural Networks*, 6(4):911–917, 1995.

Yize Chen, Yuanyuan Shi, and Baosen Zhang. Optimal control via neural networks: A convex approach. *arXiv preprint arXiv:1805.11835*, 2018.

Lin Cheng, Zhenbo Wang, Yu Song, and Fanghua Jiang. Real-time optimal control for irregular asteroid landings using deep neural networks. *Acta Astronautica*, 170:66–79, 2020.

Jim G Dai and Mark Gluzman. Queueing network controls via deep reinforcement learning. *Stochastic Systems*, 12(1):30–67, 2022.

Andrea D'ambrosio, Enrico Schiassi, Fabio Curti, and Roberto Furfaro. Pontryagin neural networks with functional interpolation for optimal intercept problems. *Mathematics*, 9(9):996, 2021.

Sohrab Effati and Morteza Pakdaman. Optimal control problem via neural networks. *Neural Computing and Applications*, 23(7):2093–2100, 2013.

Wendell H Fleming and Raymond W Rishel. *Deterministic and stochastic optimal control*, volume 1. Springer Science & Business Media, 2012.

Sanmitra Ghosh, Paul Birrell, and Daniela De Angelis. Variational inference for nonlinear ordinary differential equations. In *International Conference on Artificial Intelligence and Statistics*, pp. 2719–2727. PMLR, 2021.

Ian Goodfellow, Yoshua Bengio, and Aaron Courville. *Deep learning*. MIT press, 2016.

Ingo Gühring, Gitta Kutyniok, and Philipp Petersen. Error bounds for approximations with deep relu neural networks in w s, p norms. *Analysis and Applications*, 18(05):803–859, 2020.

Xiaoxiao Guo, Wei Li, and Francesco Iorio. Convolutional neural networks for steady flow approximation. In *Proceedings of the 22nd ACM SIGKDD international conference on knowledge discovery and data mining*, pp. 481–490, 2016.

Xiaolong He, Jichao Li, Charles A Mader, Anil Yildirim, and Joaquim RRA Martins. Robust aerodynamic shape optimization—from a circle to an airfoil. *Aerospace Science and Technology*, 87: 48–61, 2019.

Lukas Hewing, Kim P Wabersich, Marcel Menner, and Melanie N Zeilinger. Learning-based model predictive control: Toward safe learning in control. *Annual Review of Control, Robotics, and Autonomous Systems*, 3:269–296, 2020.

Rakhoon Hwang, Jae Yong Lee, Jin Young Shin, and Hyung Ju Hwang. Solving pde-constrained control problems using operator learning. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 36, pp. 4504–4512, 2022.

Yan-Bin Jia. Quaternions. *Com S*, 477:577, 2019.

Wanxin Jin, Zhaoran Wang, Zhuoran Yang, and Shaoshuai Mou. Pontryagin differentiable programming: An end-to-end learning and control framework. *Advances in Neural Information Processing Systems*, 33:7979–7992, 2020.

B Kafash, A Delavarkhalafi, and SM Karbassi. A numerical approach for solving optimal control problems using the boubaker polynomials expansion scheme. *J. Interpolat. Approx. Sci. Comput*, 3:1–18, 2014.

Yuehaw Khoo, Jianfeng Lu, and Lexing Ying. Solving parametric pde problems with artificial neural networks. *European Journal of Applied Mathematics*, 32(3):421–435, 2021.

Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014.

Thomas N Kipf and Max Welling. Semi-supervised classification with graph convolutional networks. *arXiv preprint arXiv:1609.02907*, 2016.

Donald E Kirk. *Optimal control theory: an introduction*. Courier Corporation, 2004.

Masako Kishida and Masaki Ogura. Temporal deep unfolding for constrained nonlinear stochastic optimal control. *IET Control Theory & Applications*, 16(2):139–150, 2022.

Bahare Kiumarsi, Kyriakos G Vamvoudakis, Hamidreza Modares, and Frank L Lewis. Optimal and autonomous control using reinforcement learning: A survey. *IEEE transactions on neural networks and learning systems*, 29(6):2042–2062, 2017.

Erez Krimsky and Steven H Collins. Optimal control of an energy-recycling actuator for mobile robotics applications. In *2020 IEEE International Conference on Robotics and Automation (ICRA)*, pp. 3559–3565. IEEE, 2020.

Samuel Lanthaler, Siddhartha Mishra, and George E Karniadakis. Error estimates for deeponets: A deep learning framework in infinite dimensions. *Transactions of Mathematics and Its Applications*, 6(1):tnac001, 2022.

Alexander Lapin, Shuhua Zhang, and Sergey Lapin. Numerical solution of a parabolic optimal control problem arising in economics and management. *Applied Mathematics and Computation*, 361:715–729, 2019.

A Lasota. A discrete boundary value problem. In *Annales Polonici Mathematici*, volume 20, pp. 183–190. Institute of Mathematics Polish Academy of Sciences, 1968.

Frank L Lewis, Draguna Vrabie, and Vassilis L Syrmos. *Optimal control*. John Wiley & Sons, 2012.

Weiwei Li and Emanuel Todorov. Iterative linear quadratic regulator design for nonlinear biological movement systems. In *ICINCO (1)*, pp. 222–229. Citeseer, 2004.

Zongyi Li, Nikola Borislavov Kovachki, Kamyar Azizzadenesheli, Kaushik Bhattacharya, Andrew Stuart, Anima Anandkumar, et al. Fourier neural operator for parametric partial differential equations. In *International Conference on Learning Representations*, 2020.

Marten Lienen and Stephan Günnemann. Learning the dynamics of physical systems from sparse observations with finite element networks. In *International Conference on Learning Representations*, 2021.

PL Lions. Optimal control. In *ICIAM 91: Proceedings of the Second International Conference on Industrial and Applied Mathematics*, volume 61, pp. 182. SIAM, 1992.

Lu Lu, Pengzhan Jin, Guofei Pang, Zhongqiang Zhang, and George Em Karniadakis. Learning nonlinear operators via deeponet based on the universal approximation theorem of operators. *Nature Machine Intelligence*, 3(3):218–229, 2021.

Frederik Baymler Mathiesen, Bin Yang, and Jilin Hu. Hyperverlet: A symplectic hypersolver for hamiltonian systems. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 36, pp. 4575–4582, 2022.

Sanjay Mehrotra. On the implementation of a primal-dual interior point method. *SIAM Journal on optimization*, 2(4):575–601, 1992.

Julian Nubert, Johannes Köhler, Vincent Berenz, Frank Allgöwer, and Sebastian Trimpe. Safe and fast tracking on a robot manipulator: Robust mpc and neural network control. *IEEE Robotics and Automation Letters*, 5(2):3050–3057, 2020.

Hajime Oniki. Comparative dynamics (sensitivity analysis) in optimal control theory. *Journal of Economic Theory*, 6(3):265–283, 1973.

Adam Paszke, Sam Gross, Francisco Massa, Adam Lerer, James Bradbury, Gregory Chanan, Trevor Killeen, Zeming Lin, Natalia Gimelshein, Luca Antiga, et al. Pytorch: An imperative style, high-performance deep learning library. In *Advances in neural information processing systems*, 2019.

Michael Poli, Stefano Massaroli, Federico Berto, Jinkyoo Park, Tri Dao, Christopher Re, and Stefano Ermon. Transform once: Efficient operator learning in frequency domain. In *ICML 2022 2nd AI for Science Workshop*, 2022.

Lev Semenovich Pontryagin. *Mathematical theory of optimal processes*. CRC press, 1987.

Antonin Raffin. Rl baselines3 zoo. https://github.com/DLR-RM/rl-baselines3-zoo, 2020.

Antonin Raffin, Ashley Hill, Adam Gleave, Anssi Kanervisto, Maximilian Ernestus, and Noah Dormann. Stable-baselines3: Reliable reinforcement learning implementations. *Journal of Machine Learning Research*, 22(268):1–8, 2021. URL http://jmlr.org/papers/v22/20-1364.html.

Maziar Raissi, Paris Perdikaris, and George E Karniadakis. Physics-informed neural networks: A deep learning framework for solving forward and inverse problems involving nonlinear partial differential equations. *Journal of Computational physics*, 378:686–707, 2019.

Maziar Raissi, Alireza Yazdani, and George Em Karniadakis. Hidden fluid mechanics: Learning velocity and pressure fields from flow visualizations. *Science*, 367(6481):1026–1030, 2020.

Anil V Rao. A survey of numerical methods for optimal control. *Advances in the Astronautical Sciences*, 135(1):497–528, 2009.

Jonathan Schmidt, Nicholas Krämer, and Philipp Hennig. A probabilistic state space model for joint inference from differential equations and data. *Advances in Neural Information Processing Systems*, 34:12374–12385, 2021.

John Schulman, Filip Wolski, Prafulla Dhariwal, Alec Radford, and Oleg Klimov. Proximal policy optimization algorithms. *arXiv preprint arXiv:1707.06347*, 2017.

Zheyan Shen, Jiashuo Liu, Yue He, Xingxuan Zhang, Renzhe Xu, Han Yu, and Peng Cui. Towards out-of-distribution generalization: A survey. *arXiv preprint arXiv:2108.13624*, 2021.

Justin Sirignano and Konstantinos Spiliopoulos. Dgm: A deep learning algorithm for solving partial differential equations. *Journal of computational physics*, 375:1339–1364, 2018.

Mark W Spong, Seth Hutchinson, and Mathukumalli Vidyasagar. *Robot modeling and control*. John Wiley & Sons, 2020.

NH Sweilam and SM Al-Mekhlafi. A survey on numerical studies for fractional biological models and their optimal control. In *Fractional Order Systems*, pp. 1–34. Elsevier, 2022.

Yuval Tassa, Nicolas Mansard, and Emo Todorov. Control-limited differential dynamic programming. In *2014 IEEE International Conference on Robotics and Automation (ICRA)*, pp. 1168–1175. IEEE, 2014.

Russ Tedrake. *Underactuated Robotics*. 2022. URL http://underactuated.mit.edu.

Fredi Tröltzsch. *Optimal control of partial differential equations: theory, methods, and applications*, volume 112. American Mathematical Soc., 2010.

Clifford A Truesdell. *A First Course in Rational Continuum Mechanics V1*. Academic Press, 1992.

George E Uhlenbeck and Leonard S Ornstein. On the theory of the brownian motion. *Physical review*, 36(5):823, 1930.

Richard B Vinter and RB Vinter. *Optimal control*. Springer, 2010.

Sifan Wang, Mohamed Aziz Bhouri, and Paris Perdikaris. Fast pde-constrained optimization via self-supervised operator learning. *arXiv preprint arXiv:2110.13297*, 2021a.

Sifan Wang, Yujun Teng, and Paris Perdikaris. Understanding and mitigating gradient flow pathologies in physics-informed neural networks. *SIAM Journal on Scientific Computing*, 43(5):A3055–A3081, 2021b.

Shaobo Xie, Xiaosong Hu, Shanwei Qi, and Kun Lang. An artificial neural network-enhanced energy management strategy for plug-in hybrid electric vehicles. *Energy*, 163:837–848, 2018.

Dongbin Xiu and Jan S Hesthaven. High-order collocation methods for differential equations with random inputs. *SIAM Journal on Scientific Computing*, 27(3):1118–1139, 2005.

Jiongmin Yong and Xun Yu Zhou. *Stochastic controls: Hamiltonian systems and HJB equations*, volume 43. Springer Science & Business Media, 1999.

Bing Yu et al. The deep ritz method: a deep learning-based numerical algorithm for solving variational problems. *Communications in Mathematics and Statistics*, 6(1):1–12, 2018.

Yinhao Zhu and Nicholas Zabaras. Bayesian deep convolutional encoder–decoder networks for surrogate modeling and uncertainty quantification. *Journal of Computational Physics*, 366:415–447, 2018.

Yinhao Zhu, Nicholas Zabaras, Phaedon-Stelios Koutsourelakis, and Paris Perdikaris. Physics-constrained deep learning for high-dimensional surrogate modeling and uncertainty quantification without labeled data. *Journal of Computational Physics*, 394:56–81, 2019.

A   ALGORITHMS

Algorithm 1: OptCtrlOP forward step (single sample version)

Input: cost functional f, and time index t_i
Output: estimated control $\hat{\boldsymbol{u}}(t_i) = \mathcal{N}(f)(t_i)$

1   $\boldsymbol{e} \leftarrow \mathcal{E}(f)$; // Encoder
2   $\boldsymbol{a} \leftarrow \mathcal{A}(\boldsymbol{e})$; // Approximator
3   $\boldsymbol{r} \leftarrow \boldsymbol{\tau}(t_i)$; // trunk net (Reconstructor step 1)
4   $\hat{\boldsymbol{u}}(t_i) \leftarrow \boldsymbol{r}_0 + \boldsymbol{a}^\top \boldsymbol{r}_{1:p}$; // affine combination (Reconstructor step 2)
5   **return** $\hat{\boldsymbol{u}}(t_i)$

Algorithm 2: Data generation

Input: Distribution of target state $\mathbf{x}_{goal}$
Output: Dataset

1   $N \leftarrow$ Number of samples per trajectory;
2   Dataset $\leftarrow$ empty set;
3   **while** *not Dataset is full* **do**
4   sample $\boldsymbol{x}_{goal}$ from $\mathbf{x}_{goal}$;
5   construct cost functional f (e.g. Eq. 12) with $\boldsymbol{x}_{goal}$;
6   construct OCP (Eq. 1) with cost functional f;
7      $\boldsymbol{u}^* \leftarrow$ OC_Solver(OCP); // Any solver is applicable. We choose DM.
8   sample $\{t_i\}_{1 \leq i \leq N}$ from time horizon T of OCP;
9   add triplets $\{(f, t_i, \boldsymbol{u}^*(t_i))\}_{1 \leq i \leq N}$ to Dataset;
10   **return** *Dataset*

Algorithm 3: OptCtrlOP inference on benchmark set

Input: Benchmark set of cost functionals $F = \{f_j\}_{j \leq N}$, time indices $\boldsymbol{t} = \{t_i\}_{i \leq M}$
Output: estimated controls $\hat{\boldsymbol{U}} = \{\hat{\boldsymbol{u}}_j(t_i)\}_{i \leq M, j \leq N}$

1   $\boldsymbol{E} \leftarrow \mathcal{E}(F)$; // Encoder
2   $\boldsymbol{A} \leftarrow \mathcal{A}(\boldsymbol{E})$; // Approximator, $\mathcal{O}(N)$
3   $\boldsymbol{R} \leftarrow \boldsymbol{\tau}(\boldsymbol{t})$; // trunk net (Reconstructor step 1), $\mathcal{O}(M)$
4   **for** $j \leftarrow 1$ **to** N **do**
5      $\hat{\boldsymbol{u}}_j(\boldsymbol{t}) \leftarrow \boldsymbol{R}_0 + \boldsymbol{A}_j^\top \boldsymbol{R}_{1:p}$; // affine combination (Reconstructor step 2)
6   **return** $\hat{\boldsymbol{U}}$

B   MORE ON RELATED WORKS

B.1   DE NEURAL SOLVERS

Neural Operators (continued) In addition to the DeepONet mentioned in the main text, there exist many neural operators with other architectures. For example, another type of neural operator is to parameterize the operator as a convolutional neural network (CNN) between the finite-dimensional data meshes (Guo et al., 2016; Zhu & Zabaras, 2018; Khoo et al., 2021). The major weakness of these models is that it is impossible to query solutions at off-grid points. Moreover, graph neural networks (GNNs) (Kipf & Welling, 2016) are also applied in operator learning (Anandkumar et al., 2020). The key idea is to construct the spacial mesh as a graph, where the nodes are discretized spatial locations, and the edges link neighboring locations. Compared with CNN-based models, the graph operator model is less sensitive to resolution, and is capable of inferencing at off-grid points by adding new nodes to the graph. However, its computational cost is still high, growing quadratically with the number of nodes.

Algorithm 4: MLP inference on benchmark set

Input: Benchmark set of cost functionals $F = \{f_j\}_{j \leq N}$, time indices $\boldsymbol{t} = \{t_i\}_{i \leq M}$

Output: estimated controls $\hat{\boldsymbol{U}} = \{\hat{\boldsymbol{u}}_j(t_i)\}_{i \leq M, j \leq N}$

1 **for** $i \leftarrow 1$ **to** M **do**
2   **for** $j \leftarrow 1$ **to** N **do**
3          $\boldsymbol{e}_j \leftarrow \mathcal{E}(f_j)$; // Encoder
4          $\hat{\boldsymbol{u}}_j(t_i) \leftarrow \text{MLP}(\boldsymbol{e}_j, t_i)$; // repeat $\mathcal{O}(MN)$ times

5 **return** $\hat{U}$

B.2 OCP SOLVERS

Dynamic programming (DP) is an alternative, based on Bellman's principle of optimality (Bellman & Kalaba, 1960). It offers a rule to divide a high-dimensional optimization problem with a long time horizon into smaller, easier-to-solve auxiliary optimization problems. Typical methods falling in this category are: Hamilton-Jacobi-Bellman (HJB) equation (Al-Tamimi et al., 2008), differential dynamical programming (DDP) (Tassa et al., 2014), which assumes quadratic dynamics and value function, and iterative linear quadratic regulator (iLQR) (Li & Todorov, 2004), which assumes linear dynamics and quadratic value function. Similar to dynamic programming, model predictive control (MPC) synthesizes the approximate control function via the repeated solution of finite overlapping horizons (Hewing et al., 2020). The main drawback of DP is the *curse of dimensionality* on the number and complexity of the auxiliary problem. MPC alleviates this problem at the expense of optimality. Yet fast implementation of MPC is still under exploration and remains open (Nubert et al., 2020).

C PROOFS

C.1 PROOF OF THEOREM 1

Proof. Firstly, extract the constant, and decompose the error by triangle inequality (subscript of norm omitted):

$$
\begin{aligned}
\widehat{\mathscr{E}} &= \left| \frac{f_{\boldsymbol{d}} \circ \mathcal{G} - f_{\boldsymbol{d}} \circ \mathcal{N}}{f_{\boldsymbol{d}} \circ \mathcal{G}} \right| \\
&\leq \sup_{f \in F} \left(\frac{\text{Lip}(f_{\boldsymbol{d}})}{f_{\boldsymbol{d}} \circ \mathcal{G}} \right) \|\mathcal{G} - \mathcal{N}\| = C \|\mathcal{G} - \mathcal{N}\| \\
\|\mathcal{G} - \mathcal{N}\| &= \|\mathcal{G} - \mathcal{R} \circ \mathcal{A} \circ \mathcal{E}\| \\
&= \|\mathcal{G} - \mathcal{R} \circ \mathcal{P} \circ \mathcal{G} + \mathcal{R} \circ \mathcal{P} \circ \mathcal{G} - \mathcal{R} \circ \mathcal{A} \circ \mathcal{E}\| \\
&\leq \|\mathcal{G} - \mathcal{R} \circ \mathcal{P} \circ \mathcal{G}\| + \|\mathcal{R} \circ \mathcal{P} \circ \mathcal{G} - \mathcal{R} \circ \mathcal{A} \circ \mathcal{E}\|
\end{aligned}
$$

The first term is exactly the reconstructor error $\widehat{\mathscr{E}}_{\mathcal{R}}$, by definition of push-forward:

$$
\|\mathcal{G} - \mathcal{R} \circ \mathcal{P} \circ \mathcal{G}\|_{L^2(\mu)} = \|\text{Id} - \mathcal{R} \circ \mathcal{P}\|_{L^2(\mathcal{G}_\# \mu)} = \widehat{\mathscr{E}}_{\mathcal{R}}
$$

And the second term is related to the approximator error $\widehat{\mathscr{E}}_{\mathcal{A}}$:

$$
\begin{aligned}
\|\mathcal{R} \circ \mathcal{P} \circ \mathcal{G} - \mathcal{R} \circ \mathcal{A} \circ \mathcal{E}\|_{L^2(\mu)} &= \|\mathcal{R} \circ \mathcal{P} \circ \mathcal{G} \circ \mathcal{E}^{-1} \circ \mathcal{E} - \mathcal{R} \circ \mathcal{A} \circ \mathcal{E}\|_{L^2(\mu)} \\
&\leq \text{Lip}(\mathcal{R}) \|\mathcal{P} \circ \mathcal{G} \circ \mathcal{E}^{-1} \circ \mathcal{E} - \mathcal{A} \circ \mathcal{E}\|_{L^2(\mu)} \\
&= \text{Lip}(\mathcal{R}) \|\mathcal{P} \circ \mathcal{G} \circ \mathcal{E}^{-1} \circ \mathcal{E} - \mathcal{A} \circ \mathcal{E}\|_{L^2(\mathcal{E}_\# \mu)} \\
&= \text{Lip}(\mathcal{R}) \widehat{\mathscr{E}}_{\mathcal{A}}
\end{aligned}
$$

$\square$

C.2 PROOF OF THEOREM 3

Proof. Our estimation of approximator error is based on the approximation rates of deep ReLU neural networks derived in Gühring et al. (2020)(notation modified for consistency):

Theorem 4. *Let $m \in \mathbb{N}, s \in \mathbb{N}_{\geq 2}, 1 \leq q \leq \infty, M > 0$, and $0 \leq n \leq 1$, then there exists a constant $C = C(m, s, q, M, n)$, with the following properties: For any function f with d-dimensional input and one-dimensional output in subsets of the Sobolev space $W^{s,q}$:*

$$\|f\|_{W^{s,q}} \leq M,$$

and for any $\epsilon \in (0, 1/2)$, there exists a ReLU MLP $\mathcal{N}$ such that:

$$\|\mathcal{N} - f\|_{W^{n,q}} \leq \epsilon,$$

and:

$$
\begin{aligned}
\text{size}(\mathcal{N}) &\leq C\epsilon^{-m/(s-n)} \log\left(\epsilon^{-s/(s-n)}\right), \\
\text{depth}(\mathcal{N}) &\leq C \log\left(\epsilon^{-s/(s-n)}\right).
\end{aligned}
$$

Such error bounds can not be directly applied to the approximator $\mathcal{A}$ in our framework, since $\mathcal{A}$ is implemented by a single branch net β with p-dimensional output. It is different with stacking p independent one-dimensional output networks $\{\mathcal{N}_j\}_{1 \leq j \leq p}$ and concatenating the outputs. The key difference lies in the parameter sharing of hidden layers. To fill the gap, we design a special structure of the branch net β without parameter sharing, as explained below.

Given p independent one-dimensional output networks $\{\mathcal{N}_j : \mathbb{R}^m \to \mathbb{R}^1\}_{1 \leq j \leq p}$, denote the weight matrix of the i-th layer of the $\mathcal{N}_j$ as $\boldsymbol{W}_{i,j}$. The weight matrix of i-th layer of the branch net, $\boldsymbol{W}_i^\beta$, can be constructed as:

$$
\boldsymbol{W}_1^\beta = \begin{bmatrix} \boldsymbol{W}_{1,1} \\ \boldsymbol{W}_{1,2} \\ \vdots \\ \boldsymbol{W}_{1,p} \end{bmatrix}, \qquad \boldsymbol{W}_{i \geq 2}^\beta = \begin{bmatrix} \boldsymbol{W}_{i,1} & 0 & \cdots & 0 \\ 0 & \boldsymbol{W}_{i,2} & \cdots & 0 \\ \vdots & \vdots & \ddots & \vdots \\ 0 & 0 & \cdots & \boldsymbol{W}_{i,p} \end{bmatrix}.
$$

The weight of first layer $\boldsymbol{W}_1^\beta$ is a vertical concatenation of $\{\boldsymbol{W}_{1,j}\}_{1 \leq j \leq p}$. And the weight $\boldsymbol{W}_i^\beta$ of any remaining layer $i \geq 2$ is a block diagonal matrix, with the main-diagonal blocks being $\{\boldsymbol{W}_{i,j}\}_{1 \leq j \leq p}$. It is easy to verify that such approximator is computationally equivalent to stacking of p independent one-dimensional output networks $\text{stack}(\{\mathcal{N}_j\}_{1 \leq j \leq p})$.

Let $q = 2$, $n = 0$, and $f = \mathcal{P} \circ \mathcal{G} \circ \mathcal{E}^{-1}$, then by Theorem 4 the approximator error is bounded by:

$$
\begin{aligned}
\widehat{\mathscr{E}}_\mathcal{A} &= \left\|\beta - \mathcal{P} \circ \mathcal{G} \circ \mathcal{E}^{-1}\right\| \\
&= \left(\sum_j \left\|\mathcal{N}_j - \mathcal{P} \circ \mathcal{G} \circ \mathcal{E}_j^{-1}\right\|^2\right)^{1/2} \\
&\leq (p\varepsilon^2)^{1/2} = \sqrt{p}\varepsilon.
\end{aligned}
$$

And the depth and size of β can be calculated by comparing with any $\mathcal{N}_j$:

$$\text{depth}(\mathcal{A}) = \text{depth}(\mathcal{N}_j) \leq C \log\left(\varepsilon^{-1}\right),$$

$$
\begin{aligned}
\text{size}(\mathcal{A}) &= \text{size}(\boldsymbol{W}_1^\mathcal{A}) + \sum_{i=2}^p \text{size}(\boldsymbol{W}_i^\mathcal{A}) \\
&= p\,\text{size}(\boldsymbol{W}^{1,j}) + \sum_{i=2}^p p^2\,\text{size}(\boldsymbol{W}_{i,j}) \\
&\leq \sum_{i=1}^p p^2\,\text{size}(\boldsymbol{W}_{i,j}) \\
&= p^2\,\text{size}(\mathcal{N}_j) \\
&\leq Cp^2\varepsilon^{-m/s} \log\left(\varepsilon^{-1}\right).
\end{aligned}
$$

$\square$

D DYNAMIC SYSTEMS

D.1 ROBOT ARM

$$\boldsymbol{M}(\boldsymbol{x}) = \begin{bmatrix} m_1 r_1^2 + I_1 + m_2(l_1^2 + r_2^2 + 2l_1 r_2 \cos(x_2)) & m_2(r_2^2 + l_1 r_2 \cos(x_2)) + I_2 \\ m_2(r_2^2 + l_1 r_2 \cos(x_2)) + I_2 & m_2 r_2^2 + I_2 \end{bmatrix},$$

$$\boldsymbol{C}(\boldsymbol{x}) = \begin{bmatrix} -m_2 l_1 r_2 \sin(x_2) x_4 & -m_2 l_1 r_2 \sin(x_2)(x_3 + x_4)) \\ m_2 l_1 r_2 \sin(x_2) x_3 & 0 \end{bmatrix},$$

$$\boldsymbol{g}(\boldsymbol{x}) = \begin{bmatrix} m_1 r_1 g \cos(x_1) + m_2 g(r_2 \cos(x_1 + x_2) + l_1 \cos(x_1)) \\ m_2 g r_2 \cos(x_1 + x_2) \end{bmatrix},$$

$$\begin{bmatrix} \dot{x}_1 \\ \dot{x}_2 \end{bmatrix} = \begin{bmatrix} x_3 \\ x_4 \end{bmatrix},$$

$$\begin{bmatrix} 0 \\ u \end{bmatrix} = \boldsymbol{M}(\boldsymbol{x}) \begin{bmatrix} \dot{x}_3 \\ \dot{x}_4 \end{bmatrix} + \boldsymbol{C}(\boldsymbol{x}) \begin{bmatrix} x_3 \\ x_4 \end{bmatrix} + \boldsymbol{g}(\boldsymbol{x}).$$

The RobotArm (also named Acrobot) is a planar two-link robotic arm in the vertical plane, with an actuator at the elbow. The state is $\boldsymbol{x} = [x_1, x_2, x_3 x_4]^\top$, where x_1 is the shoulder joint angle, and x_2 is the elbow (relative) joint angle, x_3, x_4 denotes their angular velocity respectively. The control u is the torque at the elbow. Note that the last equation is the manipulator equation, where $\boldsymbol{M}$ is the inertia matrix, $\boldsymbol{C}$ captures Coriolis forces, and $\boldsymbol{g}$ is the gravity vector. The details of the derivation can be found in (Spong et al., 2020, Sec. 6.4).

The initial condition $\boldsymbol{x}_{init} = [\pi/4, \pi/2, 0, 0]^\top$, and the target state baseline $\boldsymbol{x}_{goal} = [\pi/2, 0, 0, 0]^\top$. The cost functional coefficients are $\boldsymbol{c_x} = [0.1, 0.1, 0.1, 0.1]^\top, c_u = 0.1$. Other constants are: mass of two links $m_{1,2} = 1$, gravitational acceleration $g = 0$, links length $l_{1,2} = 1$, distance from joint to the center of mass $r_{1,2} = 0.5$, moment of inertia $I_{1,2} = 1/3$.

D.2 CART-POLE

$$\dot{x}_1 = x_3,$$
$$\dot{x}_2 = x_4,$$
$$\dot{x}_3 = \frac{1}{m_c + m_p \sin^2(x_2)} \left[u + m_p \sin(x_2) \left(l x_4^2 + g \cos(x_2) \right) \right],$$
$$\dot{x}_4 = \frac{1}{l \left(m_c + m_p \sin^2(x_2) \right)} [-u \cos(x_2) - m_p l x_4^2 \cos(x_2) \sin(x_2) - (m_c + m_p) g \sin(x_2)].$$

In the CartPole system, an unactuated joint connects a pole(pendulum) to a cart that moves along a frictionless track. The pendulum is initially positioned upright on the cart, and the goal is to balance the pendulum by applying horizontal forces to the cart. The state is $\boldsymbol{x} = [x_1, x_2, x_3 x_4]^\top$, where x_1 is the horizontal position of the cart, x_2 is the counter-clockwise angle of the pendulum, x_3 velocity and angular velocity of cart and pendulum respectively. We refer the reader to of (Tedrake, 2022, Sec. 3.2) for derivation of above equations.

The initial condition $\boldsymbol{x}_{init} = [0, 0, 0, 0]^\top$, and the target state baseline $\boldsymbol{x}_{goal} = [0, \pi, 0, 0]^\top$. The cost functional coefficients are $\boldsymbol{c_x} = [0.1, 0.6, 0.1, 0.1]^\top, c_u = 0.3$. Other constants are: mass of cart and pole $m_{c,p} = 0.1$, gravitational acceleration $g = 10$, pole length $l = 1$.

D.3 QUADROTOR

$$\dot{\boldsymbol{p}} = \boldsymbol{v},$$

$$m\dot{\boldsymbol{v}} = \begin{bmatrix} 0 \\ 0 \\ mg \end{bmatrix} + \boldsymbol{R}^\top(\boldsymbol{q}) \begin{bmatrix} 0 \\ 0 \\ \boldsymbol{1}^\top \boldsymbol{u} \end{bmatrix},$$

$$\dot{\boldsymbol{q}} = \frac{1}{2} \boldsymbol{\Omega}(\boldsymbol{\omega}) \boldsymbol{q},$$

$$J\dot{\boldsymbol{\omega}} = \boldsymbol{T}\boldsymbol{u} - \boldsymbol{\omega} \times \boldsymbol{J}\boldsymbol{\omega}.$$

This system describes the dynamics of a helicopter with four rotors. The state $\boldsymbol{x} = [\boldsymbol{p}^\top, \boldsymbol{v}^\top, \boldsymbol{\omega}^\top]^\top \in \mathbb{R}^9$ consists of parts: position $\boldsymbol{p}$, velocity $\boldsymbol{v}$, and angular velocity $\boldsymbol{\omega}$. The control $\boldsymbol{u} \in \mathbb{R}^4$ is the thrusts of the four rotating propellers of the quadrotor. $\boldsymbol{q} \in \mathbb{R}^4$ is the unit quaternion (Jia, 2019) representing the attitude(spacial rotation) of quadrotor w.r.t. the inertial frame. $\boldsymbol{J}$ is the moment of inertia in quadrotor's frame, and $\boldsymbol{T}\boldsymbol{u}$ is the torque applied to the quadrotor. Our setting is similar to (Jin et al., 2020, Appx. E.1), but we exclude the quaternion from the state.

The derivation is straightforward. The first two equations are Newton's laws of motion, the third equation is time-derivative of quaternion (Jia, 2019, Appx. B), and the last equation is Euler's rotation equation (Truesdell, 1992, Sec. I.10). And the coefficient matrices and operators used in the equations are defined as follows:

$$\boldsymbol{\Omega}\left(\boldsymbol{\omega}\right) = \begin{bmatrix} 0 & -\omega_1 & -\omega_2 & -\omega_3 \\ \omega_1 & 0 & \omega_3 & -\omega_2 \\ \omega_2 & -\omega_3 & 0 & \omega_1 \\ \omega_3 & \omega_2 & -\omega_1 & 0 \end{bmatrix},$$

$$\boldsymbol{R}(\boldsymbol{q}) = \begin{bmatrix} 1 - 2\left(q_3^2 + q_4^2\right) & 2\left(q_2 q_3 - q_4 q_1\right) & 2\left(q_2 q_4 + q_3 q_1\right) \\ 2\left(q_2 q_3 + q_4 q_1\right) & 1 - 2\left(q_2^2 + q_4^2\right) & 2\left(q_3 q_4 - q_2 q_1\right) \\ 2\left(q_2 q_4 - q_3 q_1\right) & 2\left(q_3 q_4 + q_2 q_1\right) & 1 - 2\left(q_2^2 + q_3^2\right) \end{bmatrix},$$

$$\boldsymbol{T} = \begin{bmatrix} 0 & -l/2 & 0 & l/2 \\ -l/2 & 0 & l/2 & 0 \\ c & -c & c & -c \end{bmatrix},$$

We set the initial state $\boldsymbol{x}_{init} = [-8, -6, 9, \boldsymbol{0}]^\top$, the initial quaternion $\boldsymbol{q}_{init} = \boldsymbol{0}$, and the target state baseline $\boldsymbol{x}_{goal} = \boldsymbol{0}$. Cost functional coefficients $c_{\boldsymbol{x}} = 1$, $c_u = 0.1$. Other constants are configured as: mass $m = 1$, wing length $l = 0.4$, moment of inertia $\boldsymbol{J} = \boldsymbol{1}$, z-axis torque constant $c = 0.01$.

D.4 ROCKET

$$\dot{\boldsymbol{p}} = \boldsymbol{v},$$

$$m\dot{\boldsymbol{v}} = \begin{bmatrix} mg \\ 0 \\ 0 \end{bmatrix} + \boldsymbol{R}^\top(\boldsymbol{q})\boldsymbol{u},$$

$$\dot{\boldsymbol{q}} = \frac{1}{2}\boldsymbol{\Omega}(\boldsymbol{\omega})\boldsymbol{q},$$

$$\boldsymbol{J}\dot{\boldsymbol{\omega}} = \boldsymbol{T}\boldsymbol{u} - \boldsymbol{\omega} \times \boldsymbol{J}\boldsymbol{\omega}.$$

The rocket system models a 6-DoF rocket in 3D space. The formulation is very close to Quadrotor mentioned above. The state $\boldsymbol{x} = [\boldsymbol{p}^\top, \boldsymbol{v}^\top, \boldsymbol{\omega}^\top]^\top \in \mathbb{R}^9$ is same as that of Quadrotor, but the control $\boldsymbol{u} \in \mathbb{R}^3$ is slightly different. Here $\boldsymbol{u}$ denotes the total thrust in 3 dimensions. Accordingly, the torque $\boldsymbol{T}\boldsymbol{u}$ is changed to:

$$\boldsymbol{T}\boldsymbol{u} = \begin{bmatrix} -l/2 \\ 0 \\ 0 \end{bmatrix} \times \boldsymbol{u}$$

We set the initial state $\boldsymbol{x}_{init} = [10, -8, 5, -1, \boldsymbol{0}]^\top$, the initial quatenion $\boldsymbol{q}_{init} = [\cos(0.75), 0, 0, \sin(0.75)]^\top$, and the target state baseline $\boldsymbol{x}_{goal} = \boldsymbol{0}$. The cost functional coefficients $c_{\boldsymbol{x}} = 1$, $c_u = 0.4$. Other constants are configured as: mass $m = 1$, rocket length $l = 1$, the moment of inertia $\boldsymbol{J} = \text{diag}([0.5, 1, 1])$

D.5 HEATING

$$-\Delta x = u \quad \text{in } \Omega$$
$$x = 0 \quad \text{on } \partial\Omega$$

Table 3: Hyper-parameter settings of the proposed OptCtrlOP for different systems.

System	Depth	#Params	#Train Data	#Epochs
Pendulum	2	3521	1×10^4	1×10^4
RobotArm	2	3601	1×10^4	1×10^4
CartPole	3	6881	3×10^4	2×10^3
Quadrotor	3	17284	1×10^5	5×10^2
Rocket	3	13883	1×10^5	5×10^2
Heating	2	3601	1×10^4	1×10^4

The heating system mimics a 2D plane Ω, whose temperature x is controlled by a heating source u, such as a plane heated by electromagnetic induction or microwaves (Tröltzsch, 2010, Chap. 1.2.1). The dynamics is a Poisson equation with zero boundary, where $\Delta = \nabla \cdot \nabla = \nabla^2$ is the Laplace operator. The objective is thus a double integral over Ω:

$$\min_u \int_\Omega c_x (x(\boldsymbol{s}) - x_{goal}(\boldsymbol{s}))^2 + c_u u^2(\boldsymbol{s}) \, \mathrm{d}\boldsymbol{s} \, .$$

The target state here is a function, not a vector. To simplify the problem, we let $x_{goal}(\boldsymbol{s}) = a \sin(\pi s_1) \sin(\pi s_2) + b \sin(\pi s_1) + c \sin(\pi s_2)$, with $[a, b, c]^\top$ being the parameters. Let the baseline parameters to be $[a, b, c]^\top = \mathbf{1}$, and the in and out of distribution problem are generated by adding noise $\boldsymbol{\epsilon}_{in}$ and $\boldsymbol{\epsilon}_{out}$ to the baseline. The cost functional coefficients are $c_x = 1, c_u = 10^{-4}$. During testing, the time horizon $T = [0, 1]^2$ is evenly divided into $11 = 121$ grid points.

D.6 STOCHASTIC PENDULUM

$$\mathrm{d}x_1(t) = x_2(t) \, \mathrm{d}t \, ,$$

$$\mathrm{d}x_2(t) = \frac{1}{I} [u(\boldsymbol{o}(t)) - mgl \sin x_1(t)] \, \mathrm{d}t + \sigma \mathrm{d}B(t),$$

$$\boldsymbol{o}(t) = \begin{bmatrix} \sin x_1(t) \\ \cos x_1(t) \\ x_2(t) \end{bmatrix} .$$

This system is similar to simple Pendulum system introduced in the main text, but with Brownian motion $B(t)$ (Uhlenbeck & Ornstein, 1930) involved in the dynamics, resulting a stochastic OCP (Fleming & Rishel, 2012). The state function is now a random process, thus the cost functional is defined as expectation:

$$\min_u \quad E \int_0^{tf} \boldsymbol{c}_{\boldsymbol{x}}^\top (\boldsymbol{x}(t) - \boldsymbol{x}_{goal})^2 + c_u u^2(\boldsymbol{o}(t)) \, \mathrm{d}t \, .$$

The state is defined by angle x_1 and angular velocity x_2, and control u is the torque applied to pendulum. We follow the convention of Gym environment Brockman et al. (2016) by adding $\boldsymbol{o}$, the observation of state $\boldsymbol{x}$. And further constrain the scale of state and control as $|u| \leq 2, |x_2| \leq 8$. The initial state is $\boldsymbol{x}_{init} = \mathbf{0}$, and the target state baseline is $\boldsymbol{x}_{goal} = [\pi, 0]^\top$. Cost functional coefficients $\boldsymbol{c}_{\boldsymbol{x}} = \mathbf{1}, c_u = 0.001$. Other constants are: mass $m = 1$, length $l = 1$, gravitational acceleration $g = 10$, scale of noise $\sigma = 0.01$.

E DETAILS ON EXPERIMENTS

For all the systems, we have 2,000 samples in each ID/OOD validation set, and 100 problems in each ID/OOD benchmark set. The size of the training set varies among systems, and is roughly proportional to the number of trainable parameters, as displayed in Table 3.

PDP, DM and control systems are implemented in CasADi (Andersson et al., 2019), which are adapted from the code repository[1]. OptCtrlOP and MLP are implemented in PyTorch (Paszke et al., 2019).

---

[1] https://github.com/wanxinjin/Pontryagin-Differentiable-Programming/tree/master

Table 4: Results of closed-loop control on StochasticPendulum environment. The ground truth result is generated by PPO.

	Time(s/problem)	In Dist. MAPE	Out of Dist. MAPE
PPO	$3.81 \times 10^1 (\pm 1.86 \times 10^{-1})$		
MLP	$2.10 \times 10^{-4} (\pm 1.87 \times 10^{-6})$	$9.13 \times 10^{-2} (\pm 4.59 \times 10^{-2})$	$4.69 \times 10^{-2} (\pm 1.07 \times 10^{-2})$
OptCtrlOP	$3.33 \times 10^{-4} (\pm 4.08 \times 10^{-6})$	$9.19 \times 10^{-2} (\pm 4.59 \times 10^{-2})$	$3.04 \times 10^{-2} (\pm 1.09 \times 10^{-2})$

Table 5: Results of PDE-constrained control on Heating environment.

	Time(s/problem)	In Dist. MAPE	Out of Dist. MAPE
DM	$5.87 \times 10^{-2} (\pm 7.58 \times 10^{-5})$		
MLP	$2.05 \times 10^{-5} (\pm 1.48 \times 10^{-7})$	$1.26 \times 10^0 (\pm 2.28 \times 10^0)$	$1.69 \times 10^3 (\pm 1.91 \times 10^3)$
OptCtrlOP	$2.14 \times 10^{-7} (\pm 5.60 \times 10^{-9})$	$4.85 \times 10^{-2} (\pm 2.29 \times 10^{-2})$	$1.50 \times 10^2 (\pm 1.66 \times 10^2)$

For stochastic OCP (i.e. Stochastic Pendulum), we choose a reinforcement learning algorithm named Proximal Policy Optimization(PPO) (Schulman et al., 2017) as the ground truth OCP solver. The PPO implementation is credit to open-source package *Stable Baselines* (Raffin et al., 2021), with hyper-parameter settings cited from Raffin (2020).

For fairness, all training/testing cases are executed on an Intel i9-10920X CPU, without GPU.

F   MORE EXPERIMENT RESULTS

Figure 5: The loss curves of 4 systems on the training set, in- and out-of-distribution testing sets. All curves are visualized after exponential moving average with weight=0.5

Figure 6: The cost MAPE (mean absolute percentage error) curves of 4 systems on the in- and out-of-distribution testing sets. All curves are visualized after exponential moving average with weight=0.5

Figure 7: The state trajectories of four systems on four randomly sampled OCPs. The left two columns are in distribution problems, and the right two columns are out of distribution problems. The three dimensions consists of time t and the first two dimension of state x_1, x_2.

Figure 8: The MAPE (mean absolute percentage error) w.r.t. the number of training samples curves of 5 systems on the in- and out-of-distribution testing sets.