3D Cross Pseudo Supervision (3D-CPS): A semi-supervised nnU-Net architecture for abdominal organ segmentation

Yongzhi Huang[1,2,#,], Hanwen Zhang[1,2,#,],
Yan Yan[1,2,], Haseeb Hassan[1,2,], and Bingding Huang[1,2,*,]

[1] College of Big Data and Internet, Shenzhen Technology University, Shenzhen, 518188, China
{2060411015,2110416013,2070416009}@stumail.sztu.edu.cn
{haseeb,huangbingding}@sztu.edu.cn
[2] College of Applied Sciences, Shenzhen University, Shenzhen, 518060, China

\# These two authors contributed equally to this work.
Corresponding author: Bingding Huang(huangbingding@sztu.edu.cn).

Abstract. Large curated datasets are necessary, but annotating medical images is a time-consuming, laborious, and expensive process. Therefore, recent supervised methods are focusing on utilizing a large amount of unlabeled data. However, to do so, is a challenging task. To address this problem, we propose a new 3D Cross Pseudo Supervision (3D-CPS) method, a semi-supervised network architecture based on nnU-Net with the Cross Pseudo Supervision method. We design a new nnU-Net based preprocessing method and adopt the forced spacing settings strategy in the inference stage to speed up the inference time. In addition, we set the semi-supervised loss weights to expand linearity with each epoch to prevent the model from low-quality pseudo-labels in the early training process. Our proposed method achieves an average dice similarity coefficient (DSC) of 0.881 and an average normalized surface distance (NSD) of 0.913 on the 2022-MICCAI-FLARE validation set (20 cases).

Keywords: Abdominal organ segmentation · Semi-supervised learning · 3D Cross Pseudo Supervision.

1 Introduction

With the advancement of medical technology, more and more medical imaging devices are being used in clinical diagnosis [1]. Nowadays, the analysis of medical images by physicians to diagnose any possible disease has become the basis of clinical diagnosis [2]. Therefore, image segmentation is the first step in the process of many clinical diagnoses and plays a key role in the quantitative analysis of medical images [3]. With the rapid development of deep learning in recent years, various U-Net-based network models have achieved excellent results in different medical image segmentation competitions [4]. Among them, the nnU-Net

performs significantly well with its excellent adaption to different datasets and achieves excellent segmentation results under fully supervised medical datasets using a plain U-Net network [5]. However, manual annotation for segmentation is time-consuming and needs expert experience, especially in medical images. Thus, recent trends have focused on automatically using a large amount of unlabeled medical images. For instance, a semi-supervised approach has been introduced to construct a teacher-student model with dropout or uncertainty to generate stable segmentations automatically over the unlabeled images [6,7]. Likewise, Li et al. and Luo et al. proposed a model for different tasks, and then this model can be trained with consistency losses on unlabeled data [8,9].Above all, these inspired semi-supervised-based approaches still have the following challenges.

1. Data preprocessing pipelines and algorithms that rely on labeled data can not be applied directly to unlabeled data.
2. Semi-supervised strategies for processing data are often used only in binary tasks, while multi-class 3D medical tasks will take more time and memory consumption in the data processing.
3. To deal with the imbalance problem in the number of labeled data and unlabeled data, an appropriate training strategy is required to learn from different losses.

To address the above challenges, we design a semi-supervised method based on nnU-Net by improving the Cross Pseudo-label algorithm. The proposed method applies the preprocessing of nnU-Net to unlabeled data and further adapts the Cross Pseudo-label algorithm(CPS) [10] to 3D CT images. The proposed method is validated on Fast and Low-resource semi-supervised Abdominal Organ Segmentation in CT (2022-MICCAI-FLARE) grand challenge. The main contributions of our work are summarized as follows.

1. Modifying the nnU-Net architecture for semi-supervised tasks.
2. Adopting a semi-supervised strategy called Cross Pseudo Supervision for 3D medical images.
3. Proposing the forced spacing settings strategy for nnU-Net inference to reduce resources consumption and speed up the inference time.

2 Method

2.1 Preprocessing

Training In the training stage, we use the same preprocessing pipeline generated from the heuristic rules as in the nnU-Net on labeled data, including intensity transformation, spatial transformation, and data augmentation. The only difference is that when analyzing the distribution of CT intensity, nnU-Net analyzes the intensity of the foreground so that the label is required. However, we obtain the intensity distribution of unlabeled data by unifying a statistical method for calculating the intensity of the whole image by collecting global pixels information instead of foreground pixels.

Inference For the inference, we adopt the enforced spacing settings strategy for nnU-Net inference to reduce resource consumption and speed up the inference time. The relevant detail will be discussed in section 2.2.

2.2 Proposed method

Semi-supervised learning on nnU-Net architecture Our proposed framework is shown in Fig. 1, which is derived from the nnU-Net. For segmentation tasks on a specific dataset, the pipeline of the nnU-Net framework mainly includes the following steps:

1. Collect and analyze the data information, and generate rule-based parameters using its heuristic rules.
2. Train the network based on fixed parameters and rule-based parameters.
3. Perform ensemble selection and post-processing methods based on empirical parameters.

Our proposed framework keeps the pipeline of the nnU-Net but modifies some of their components such as for data fingerprint collection, we replaced the distribution of foreground pixels with global pixels to analyze the intensity distribution of unlabeled data, as mentioned in section 2.1. Secondly, we doubled the U-Net network architecture and optimizer generated from the heuristic rules of the nnU-Net. The sibling networks have the same architecture but with different initialization. Correspondingly, the two sibling networks have their optimizer to update the weights. Then, the proposed semi-supervised method trains the network in the training stage which will be discussed in detail in next section. Since the model ensembling module is of no use for comparing the plain 2D

Fig. 1. The 3D CPS framework: a semi-supervised learning framework based on nnU-Net architecture. The proposed framework entirely follows nnU-Net and we modified their respective blocks including intensity distribution analysis, network architecture, optimizer, training policy, and inference preprocessing in the framework which are marked as red.

and 3D U-Net architectures with or without the CPS, so it is removed from the proposed framework. Additionally, in the inference stage, the forced spacing settings is used before preprocessing to improve the segmentation efficiency.

Proposed semi-supervised method The proposed semi-supervised method is mainly derived from CPS. Though the CPS is a 2D semi-supervised semantic segmentation method, this method can be adopted for 3D CT images. A semi-supervised semantic segmentation task aims to learn a segmentation network by exploring labeled and unlabeled data. For instance, given a set D_l of labeled images and a set D_u of unlabeled images. The proposed method consists of two parallel segmentation networks T_1 and T_2, and both have the same network architecture but were initialized with different weights θ_1 and θ_2. The inputs X can be either a 2D patch with the shape of [C, H, W] or a 3D patch with the shape of [C, S, H, W].

The semi-supervised training strategy is shown in Fig. 2, where the input X is preprocessed with the same pipeline as the nnU-Net. Then, the default data augmentation in nnU-Net is applied for the input X. $T_1(X)$ and $T_2(X)$ represent the predicted one-hot confidence map from the two parallel T_1 and T_2 networks, respectively. $Y_1(X)$ and $Y_2(X)$ represent the predicted one-hot label map generated from $T_1(X)$ and $T_2(X)$, respectively.

Fig. 2. Modified semi-supervised architecture from cross pseudo supervision(CPS). Labeled data (X_1, Y_1) and unlabeled data X_2 are sampled randomly as input for both networks $T_1(\cdot)$ and $T_2(\cdot)$. For any input X, the output is a pair of branches i.e., $T_1(X)$ and $T_2(X)$. Labeled data and unlabeled data are calculated based on cross pseudo supervision loss. Moreover, the labeled data also requires calculation of supervision loss.

Furthermore, our training objective contains two losses: supervision loss L_{sup} and cross pseudo supervision loss L_{cps}. The supervision loss L_{sup} can only be calculated for the labeled data and is given as follows.

$$L_{sup}^l = l_{sup}(T_1(x), Y) + l_{sup}(T_2(x), Y) \qquad (1)$$

where Y is the ground truth and l_{sup} is dice and cross-entropy loss configured by default in nnU-Net, which is proved to be robust in medical image segmentation tasks [11].

The cross pseudo supervision loss L_{cps} is defined as $L_{cps} = L_{cps}^l + L_{cps}^u$, which is combined with the CPS loss on labeled dataset L_{cps}^l and on unlabeled dataset L_{cps}^u. The two parallel networks view the output of the other one as own pseudo-labels and the L_{cps} can be calculated as L_{sup}. The cross pseudo supervision loss on the unlabeled data is written as:

$$L_{cps}^u = l_{cps}(T_1(x), Y_2) + l_{cps}(T_2(x), Y_1) \qquad (2)$$

where l_{cps} is dice and cross-entropy loss like l_{sup} in our experiments. Given Eq. 2, the definition of CPS loss on labeled data is same with the loss on unlabeled data. The overall training objective is given as:

$$L = L_{sup} + \lambda L_{cps} \qquad (3)$$

where λ is a hyper-parameter that needs to be set in advance, which determines the weight of cross supervision loss. We set the λ to increase linearity with epoch from 0 to 0.5, and keep that fixed after the specific epoch instead of the fixed value as in CPS.

Network architecture Our network is a U-Net [12] like Encoder-Decoder architecture, and its backbone is based on residual blocks [13]. Considering that the input data can have different dimensions, we use two different networks(generated from heuristic rules of nnU-Net), 2D and 3D, and their detailed structures are provided in Fig. 3 and Fig. 4, respectively.

The 2D CPS U-Net can only take one slice as input. During the training and inference stage, each slice needs to be resized to 512× 512. The network is an 8-layers U-Net, and the encoding process downsamples images to 4× 4. The implementation of residual blocks is given as follows: conv-instnorm-ReLU, and each encoder contains two residual blocks, where the first residual block performs the downsampling task (except encoder1). The decoder has a similar structure to the encoder, except that it adds a transposed convolution at the end for upsampling.

Regarding 3D CPS U-Net, 3D data can be used as input (i.e., a sliding window). During our training and inference stage, each input needs to be resized to 112×160×128 (S×H×W). The 3D network is a 6-layers U-Net, and the encoding process downsamples images to 7×5×4. The residual blocks' structure is similar to 2D CPS U-Net, except that 3D convolutions replace the 2D convolutions.

Fig. 3. A 2D U-Net like Encoder-Decoder architecture generated by heuristic rules of nnU-Net. The network further entails residual encoder blocks (containing conv-instnorm-ReLU), residual decoder blocks (containing conv-instnorm-ReLU and transpose convolution), and output blocks. The output blocks generate segmentations at different resolutions.

Fig. 4. A 3D U-Net like Encoder-Decoder architecture generated by heuristic rules of nnU-Net. The 3D network further entails residual encoder blocks (including conv-instnorm-ReLU), residual decoder blocks (containing conv-instnorm-ReLU and transpose convolution), and output blocks. Same as in the 2D network, the output blocks generate segmentations at different resolutions.

Inference speed and resources consumption trade-offs Generally, the performance of the segmentation network is contrary to inference speed and resource consumption. Most methods improve performance at the expense of inference speed or more resource consumption, such as Test Time Augmentation(TTA) inference or sliding window inference. Therefore, we propose a method for the inference stage by enforcing spacing parameters (settings) to reduce the patch size (especially for dense CT images like Case0050 in the validation set). So, by modifying its spacing parameters before preprocessing, the input patch size is constrained to an optimal value for the inference stage.

The enforced spacing settings is an empirical parameter that needs to be set manually. For this purpose, we consider the number of slices (S) of CT images for spacing settings, where s_x,s_y and s_z represent spacing on the x, y, and z axes, respectively. In our experiments, default settings for s_x,s_y and s_z are 0.75, 0.75, 0.5. So, if S is less than 150, only the spacing of s_x and s_y are modified, and s_z will be set as the original spacing. If S is between 150 and 600, the spacing will be modified as the default spacing, and if S is greater than 600, s_x and s_y will be modified as default settings, and s_z will be set to $max(0.8, 600/S) * s_z$.

2.3   Post-processing

Suppose the enforced spacing settings is used in the preprocessing stage. In that case, the spacing of the segmentation output needs to be modified back to its original spacing in the post-processing stage. The remaining post-processing method is consistent with that of the nnU-Net.

3   Experiments

3.1   Dataset and evaluation measures

The FLARE 2022 dataset is curated from more than 20 medical groups under the license permission including MSD [14], KiTS [15,16], AbdomenCT-1K [17], and TCIA [18]. The training set includes 50 labeled CT scans with pancreas disease and 2000 unlabelled CT scans with liver, kidney, spleen, or pancreas diseases. The validation set includes 50 CT scans with liver, kidney, spleen, or pancreas diseases. The testing set includes 200 CT scans where 100 cases have liver, kidney, spleen, or pancreas diseases and the other 100 cases have uterine corpus endometrial, urothelial bladder, stomach, sarcomas, or ovarian diseases. All the CT scans only have image information and the center information is not available. The evaluation measures are Dice Similarity Coefficient (DSC) and Normalized Surface Dice (NSD), and three running efficiency measures: running time, area under GPU memory-time curve, and area under CPU utilization-time curve. All measures are used to compute the ranking score. Moreover, the GPU memory consumption has a 2 GB performance. For the FLARE2022 challenge, we use 50 labeled CT scans and the first 1000 unlabeled CT scans.

3.2   Environments and requirements

The configured environments and requirements are provided in Table 1.

Table 1. Development environments and requirements.

Windows/Ubuntu version	Ubuntu 20.04.1 LTS
CPU	AMD EPYC 7742 64-Core Processor
RAM	1.8TB
GPU (number and type)	8 NVIDIA A100 (40G)
CUDA version	11.4
Programming language	Python 3.9
Deep learning framework	Pytorch (1.10), nnU-Net

3.3   Training and inference protocols

The protocols are basically calculated by the heuristic rules of nnU-Net, while data-independent parameters are consistent with nnU-Net. The training and inference protocols of our experiments are provided in Table 2.

Table 2. Training and Inference protocols.

Mode	2D+CPS	3D+CPS
Network initialization	"he" normal initialization	"he" normal initialization
Batch size	12 in D_l and 12 in D_u	2 in D_l and 2 in D_u
Patch size	512×512	112×160×128
Total epochs	1000	1000
Optimizer	SGD	SGD
Weight decay	3e-5	3e-5
Initial learning rate (lr)	0.01	0.01
Lr scheduler	ReduceLROnPlateau	ReduceLROnPlateau
Training time	47 hours	97 hours
Loss function	Dice and Cross-Entropy	Dice and Cross-Entropy
Number of model parameters	41.29M[3]	30.79M
Number of flops	65.55G[4]	585.43G

4   Results and discussions

4.1   Quantitative results on validation set

For ablation study to analyze the effect of unlabeled data and semi-supervised learning, we use 2D and 3D supervised training strategies (previously deployed by nnU-Net) as the baseline in our experiments. Furthermore, our experiments

adopt the same preprocessing method and training protocol. In a semi-supervised scheme, we employ two parallel models with the same structure but different initialization weights, while in a supervised scheme, only a single model is required. Note that the loss function for the semi-supervised scheme is based on Eq. 3, while the experiments in a supervised scheme are performed without L_{cps}.

The quantitative results are provided in Table 3, showing the DSC for 13 organs and mean DSC (mDSC) for all classes. The baseline method refers to fully supervised learning on nnU-Net, while Baseline + CPS are the results of 3D-CPS. Table 3 shows baseline+CPS slightly outperforming baseline for both 2D and 3D networks, by +0.0223 and +0.0167 mDSC respectively.

Table 3. Quantitative results on 50 cases of validation set.

Method	Baseline2D	Baseline2D+CPS	Baseline3D	Baseline3D+CPS
Liver	0.9623	0.9733	0.9717	0.9745
RK	0.7699	0.8042	0.8863	0.8851
Spleen	0.8936	0.9202	0.9311	0.9559
Pancreas	0.7646	0.7865	0.8619	0.8769
Aorta	0.9392	0.9630	0.9584	0.9617
IVC	0.8230	0.8545	0.8851	0.8992
RAG	0.7124	0.7362	0.8196	0.8354
LAG	0.6479	0.7196	0.8060	0.8236
Gallbladder	0.6137	0.6993	0.7228	0.8067
Esophagus	0.8357	0.8461	0.8637	0.8644
Stomach	0.8377	0.7414	0.8800	0.9059
Duodenum	0.6119	0.6363	0.7586	0.7753
LK	0.7880	0.8091	0.8699	0.8672
mDSC	0.7846	0.8069	0.8627	0.8794

4.2 Qualitative results

The qualitative analysis of 20 cases of the validation set released officially is shown in Table 4 and Table 5, including both the score of DSC and NSD. Exemplary segmentation results generated by nnU-Net(baseline) and 3D-CPS (baseline+CPS) are shown in Fig. 5, where case2 and case42 are challenging and case21 and case28 are easy cases. In easy cases, both 2D and 3D networks performed marginally better and improved overall performance. In the challenging cases, the performance of 3D CPS seems to be struggling. Although the overall performance of baseline+CPS is better than the baseline in 20 released cases, the DSC score of baseline+CPS has dropped in these cases(2D model of case2 and 3D model of case42).

Table 4. Quantitative analysis of 2D model on 20 cases of validation set.

Metrics	Baseline(DSC)	Baseline+CPS(DSC)	Baseline(NSD)	Baseline+CPS(NSD)
Liver	0.9725	0.9769	0.9487	0.9587
RK	0.7595	0.7946	0.7225	0.7690
Spleen	0.9374	0.9413	0.9151	0.9355
Pancreas	0.8043	0.8052	0.8858	0.8944
Aorta	0.9661	0.9717	0.9832	0.9881
IVC	0.8403	0.8575	0.8280	0.8615
RAG	0.7768	0.7625	0.8782	0.8596
LAG	0.6867	0.7817	0.7958	0.8839
Gallbladder	0.5034	0.6345	0.4929	0.6328
Esophagus	0.7690	0.8231	0.8322	0.8980
Stomach	0.8575	0.7217	0.8668	0.7736
Duodenum	0.6817	0.6580	0.8329	0.8212
LK	0.8210	0.8495	0.7749	0.8545
mean	0.7982	0.8137	0.8274	0.8562

Table 5. Quantitative analysis of 3D model on 20 cases of validation set.

Metrics	Baseline(DSC)	Baseline+CPS(DSC)	Baseline(NSD)	Baseline+CPS(NSD)
Liver	0.9790	0.9754	0.9736	0.9707
RK	0.8063	0.8483	0.7927	0.8479
Spleen	0.9436	0.9581	0.9386	0.9434
Pancreas	0.8737	0.8862	0.9538	0.9589
Aorta	0.9713	0.9730	0.9864	0.9899
IVC	0.8897	0.8958	0.8926	0.8937
RAG	0.8596	0.8651	0.9568	0.9527
LAG	0.8386	0.8521	0.9228	0.9301
Gallbladder	0.6626	0.7998	0.6553	0.7946
Esophagus	0.8752	0.8861	0.9411	0.9438
Stomach	0.8891	0.8869	0.9082	0.9182
Duodenum	0.7682	0.7727	0.8930	0.8733
LK	0.8651	0.8537	0.8453	0.8490
mean	0.8632	0.8810	0.8969	0.9128

4.3   Segmentation efficiency results

To improve the performance of inference speed and resource consumption, additionally, an enforced spacing settings strategy is adopted for the inference, ensuring that segmentation quality will not drop dramatically. Specific parameters of inference in our experiments are set as follows: the TTA inference is disabled, whereas the step size of the sliding window is set to 0.7, and the inference mode is set to "fastest mode" as in nnU-Net.

Fig. 5. Qualitative results on challenging (case 0002 and 0042) and easy (case 0021 and 0028) cases. Mean DSC scores(%) are attached to the top left. The first column is the ground truth released by the official. The second and fourth columns are the segmentation mask generated from the 2D model and 3D model in nnU-Net, respectively, and the third and fifth columns are generated from 3D-CPS (baseline+CPS).

5   Conclusion

Our anticipated model aims to take part in FLARE 2022 competition. For this purpose, a co-training-based semi-supervised method is developed. The proposed method incorporated a semi-supervised architecture based on Cross Pseudo Supervision (CPS) and nnU-Net, extending to 2D and 3D medical images for annotation purposes. Moreover, introducing an enforced spacing settings in the inference stage leads to a faster inference time (however, it slightly affects the final segmentation outcomes). The proposed method yields better quantitative results with marginally better qualitative predictions.

Acknowledgements We would like to thank the School-Enterprise Graduate Student Cooperation Fund of Shenzhen Technology University. The authors of this paper declare that the segmentation method they implemented for participation in the FLARE 2022 challenge has not used any pre-trained models nor additional datasets other than those provided by the organizers.

References

1. Xiangbin Liu, Liping Song, Shuai Liu, and Yudong Zhang. A review of deep-learning-based medical image segmentation methods. *Sustainability*, 13(3):1224, 2021. 1

2. Dinggang Shen, Guorong Wu, and Heung-Il Suk. Deep learning in medical image analysis. *Annual review of biomedical engineering*, 19:221, 2017. 1

3. Miguel Monteiro, Virginia FJ Newcombe, Francois Mathieu, Krishma Adatia, Konstantinos Kamnitsas, Enzo Ferrante, Tilak Das, Daniel Whitehouse, Daniel Rueckert, David K Menon, et al. Multiclass semantic segmentation and quantification of traumatic brain injury lesions on head ct using deep learning: an algorithm development and multicentre validation study. *The Lancet Digital Health*, 2(6):e314–e322, 2020. 1

4. Getao Du, Xu Cao, Jimin Liang, Xueli Chen, and Yonghua Zhan. Medical image segmentation based on u-net: A review. *Journal of Imaging Science and Technology*, 64:1–12, 2020. 1

5. Fabian Isensee, Jens Petersen, Andre Klein, David Zimmerer, Paul F Jaeger, Simon Kohl, Jakob Wasserthal, Gregor Koehler, Tobias Norajitra, Sebastian Wirkert, et al. nnu-net: Self-adapting framework for u-net-based medical image segmentation. *arXiv preprint arXiv:1809.10486*, 2018. 2

6. Xiaomeng Li, Lequan Yu, Hao Chen, Chi-Wing Fu, Lei Xing, and Pheng-Ann Heng. Transformation-consistent self-ensembling model for semisupervised medical image segmentation. *IEEE Transactions on Neural Networks and Learning Systems*, 32(2):523–534, 2020. 2

7. Lequan Yu, Shujun Wang, Xiaomeng Li, Chi-Wing Fu, and Pheng-Ann Heng. Uncertainty-aware self-ensembling model for semi-supervised 3d left atrium segmentation. In *International Conference on Medical Image Computing and Computer-Assisted Intervention*, pages 605–613. Springer, 2019. 2

8. Shuailin Li, Chuyu Zhang, and Xuming He. Shape-aware semi-supervised 3d semantic segmentation for medical images. In *International Conference on Medical Image Computing and Computer-Assisted Intervention*, pages 552–561. Springer, 2020. 2

9. Xiangde Luo, Jieneng Chen, Tao Song, and Guotai Wang. Semi-supervised medical image segmentation through dual-task consistency. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 35, pages 8801–8809, 2021. 2

10. Xiaokang Chen, Yuhui Yuan, Gang Zeng, and Jingdong Wang. Semi-supervised semantic segmentation with cross pseudo supervision. pages 2613–2622. ISBN: 9781665445092 _eprint: 2106.01226. 2

11. Jun Ma, Jianan Chen, Matthew Ng, Rui Huang, Yu Li, Chen Li, Xiaoping Yang, and Anne L. Martel. Loss odyssey in medical image segmentation. *Medical Image Analysis*, 71:102035, 2021. 5

12. Olaf Ronneberger, Philipp Fischer, and Thomas Brox. U-net: Convolutional networks for biomedical image segmentation. Number: arXiv:1505.04597. 5

13. Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. 2016-Decem:770–778. ISBN: 9781467388504 _eprint: 1512.03385. 5

14. Amber L Simpson, Michela Antonelli, Spyridon Bakas, Michel Bilello, Keyvan Farahani, Bram Van Ginneken, Annette Kopp-Schneider, Bennett A Landman, Geert Litjens, Bjoern Menze, et al. A large annotated medical image dataset for the development and evaluation of segmentation algorithms. *arXiv preprint arXiv:1902.09063*, 2019. 7

15. Nicholas Heller, Fabian Isensee, Klaus H Maier-Hein, Xiaoshuai Hou, Chunmei Xie, Fengyi Li, Yang Nan, Guangrui Mu, Zhiyong Lin, Miofei Han, et al. The state of the art in kidney and kidney tumor segmentation in contrast-enhanced ct imaging: Results of the kits19 challenge. *Medical Image Analysis*, 67:101821, 2021. 7

16. Nicholas Heller, Sean McSweeney, Matthew Thomas Peterson, Sarah Peterson, Jack Rickman, Bethany Stai, Resha Tejpaul, Makinna Oestreich, Paul Blake, Joel Rosenberg, et al. An international challenge to use artificial intelligence to define the state-of-the-art in kidney and kidney tumor segmentation in ct imaging. *American Society of Clinical Oncology*, 38(6):626–626, 2020. 7

17. Jun Ma, Yao Zhang, Song Gu, Cheng Zhu, Cheng Ge, Yichi Zhang, Xingle An, Congcong Wang, Qiyuan Wang, Xin Liu, Shucheng Cao, Qi Zhang, Shangqing Liu, Yunpeng Wang, Yuhui Li, Jian He, and Xiaoping Yang. Abdomenct-1k: Is abdominal organ segmentation a solved problem? *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 2021. 7

18. Kenneth Clark, Bruce Vendt, Kirk Smith, John Freymann, Justin Kirby, Paul Koppel, Stephen Moore, Stanley Phillips, David Maffitt, Michael Pringle, et al. The cancer imaging archive (tcia): maintaining and operating a public information repository. *Journal of Digital Imaging*, 26(6):1045–1057, 2013. 7