A query engine for L1-L2 parallel dependency treebanks

Affiliation / Address line 1
Affiliation / Address line 2
Affiliation / Address line 3
email@domain

Anonymouser Author
Affiliation / Address line 1
Affiliation / Address line 2
Affiliation / Address line 3
email@domain

Anonymousest Author
Affiliation / Address line 1
Affiliation / Address line 2
Affiliation / Address line 3
email@domain

Abstract

L1-L2 parallel dependency treebanks, aimed at achieving interoperability between learner corpora, consist of learner sentences paired with correction hypotheses. Rather than explicitly labelled for errors, sentences are morphosyntactically annotated following the Universal Dependencies standard, which enables error retrieval via tree queries. Work in this sense has, however, been limited. Addressing the limitations of the existing tools, we present a query engine for L1-L2 treebanks and evaluate it on a manually validated and an automatically parsed corpus.

1 Introduction

L1-L2 parallel dependency treebanks are learner corpora where sentences produced by learners of a second language (L2) are paired with correction hypotheses, assumed to be native-like and therefore referred to as *L1 sentences*. Both the original sentences and the corresponding corrections are annotated following the cross-lingual Universal Dependencies (UD) standard (Nivre et al., 2020). The idea is that such morphosyntactical information makes explicit error labelling unnecessary, making it possible for errors to be retrieved by means of tree queries instead. This format was in fact proposed by Lee et al. (2017b) as a way to address the interoperability issues arising from the coexistence of the different markup styles and error taxonomies normally employed for the annotation of learner corpora, which tend not only to be language-specific, but also to vary widely between different projects. An additional advantage of using UD is the availability of several increasingly fast and reliable parsers (Straka, 2018; Qi et al., 2020) that, while not very robust to learner errors yet (Huang et al., 2018), can already be used to automate a significant part of the annotation process.

While handcrafted L1-L2 UD treebanks exist for English (Berzak et al., 2016), Chinese (Lee et al., 2017a) and Italian (Di Nuovo et al., 2022), work on error retrieval tools has been limited. An online query engine exists for the first one of these corpora, the ESL (English as a Second Language) treebank.[1] This tool, however, on top of not being easily applicable to other corpora of the same kind, has several limitations, the most important of which being its reliance on a pre-existing error taxonomy. This is in contrast with Lee et al. (2017b)'s idea (note, however, that Berzak et al.'s treebank actually predates Lee et al.'s paper). Closer in spirit to such proposal, Choshen et al. (2020) have developed a method to automatically derive dynamic syntactical error taxonomies from L1-L2 treebanks, but do not provide a way to search them for specific error patterns.

In this paper, we present a language- and error taxonomy-agnostic query engine for L1-L2 parallel dependency treebanks. The tool allows searching for morphosyntactical errors by describing them in a pre-existing pattern matching language for UD trees, which we extend to facilitate comparing L2 sentences to their corrections, resulting in what we call *L1-L2 patterns*. Our main contribution is a sentence retrieval algorithm that matches the L1 and L2 portions of a query pattern on the corresponding treebanks in parallel, ensuring that correspondences are found between segments that align with each other. Addressing another limitation of the existing tools, we also make it possible to extract the specific portions of the L1-L2 sentence matching the pattern. The engine is part of L2-UD, a larger toolkit for L1-L2 treebanks currently under development, available for download at `URL/hidden/for.review`.

---

[1] The query engine's homepage, `esltreebank.org`, is no longer reachable, but its user interface can be inspected through the Internet Archive: `web.archive.org/web/20220120204838/http://esltreebank.org/`.

Figure 1: UD trees for the Italian sentence *Sono andat{o→a*} da entrambi* ("I have been to both"), discrepancies highlighted in bold. In the L2 sentence, displayed on the right, the gender of the participle *andato*, referring to the implicit subject of the sentence, is incorrect, but without further context we have no way to infer the author's gender. As a consequence, the error can only be described in terms of its correction. Example adapted from the VALICO-UD treebank.

2 Related work

As mentioned in the introduction, learner corpora exist in a variety of formats. Lee et al. (2017b)'s proposal to use L1-L2 parallel dependency treebanks is not the only one aiming at overcoming the interoperability issues that follow. Bryant et al. (2017), for instance, introduce ERRANT, an ERRor ANnotation Toolkit operating in the framework of a taxonomy that exclusively relies on dataset-agnostic information such as the POS (Part Of Speech) and morphological features of the tokens involved. In a sense, this can be seen as an attempt to solve the problem by developing a "universal" error taxonomy. The annotation schemes currently in use, however, differ significantly not only in their underlying assumptions, which are often language-specific, but also in their granularity level, both of which vary according to the intended use of the specific corpus.

Lee et al.'s idea, while only concerned with morphosyntactical errors, is more radical, as UD-annotated parallel treebanks have the potential to remove the need for any explicit error pre-categorization and instead allow to infer error taxonomies automatically and dynamically. Choshen et al.'s work on syntactical error classification, showing promising results even on automatically parsed L1-L2 treebanks, goes in this direction.

When it comes to the complementary problem of retrieving example sentences for a specific pattern of error from an L1-L2 treebank, the only tool is, to the best of our knowledge, the above mentioned ESL treebank query engine. From the perspective of the tree queries envisioned by Lee et al. (2017b), however, it presents several limitations. First and foremost, searching for errors is primarily done by selecting an error label from a pre-defined set. A simple query language is also available, but it only allows searching for sequences of word forms, POS tags and dependency labels. In other words, UD sentences are treated as lists of tokens rather than trees, which can be limiting since syntactical relations between words are often more relevant than their linear order. Furthermore, there is no connection between the L1 and L2 treebanks the corpus consists in, other than that they are aligned at the sentence level. Error patterns are only matched against L2 sentences, making it impossible to search for errors whose description requires a comparison with the correction (cf. Figure 1 for an example) or locate the relevant portions of their L1 counterparts. A final, related limitation is that the tool always returns complete L2 sentences, optionally paired with their corrections, while it is sometimes useful to isolate the portions of the sentences matching the query.

3 Design and implementation

Addressing these limitations, we aim for a query engine with the following characteristics:

1. there is no underlying error taxonomy: errors are described in a pattern matching language which allows treating UD sentences both as sequences of tokens and as tree structures;
2. queries consist in an L1 pattern, that has to be matched by a correction hypothesis, and an L2 pattern to be matched in the corresponding learner sentence. This also allows formulating queries by comparing learner sentences with their corrections;
3. it is possible to retrieve full sentence pairs as well as the specific portions of the sentences matching the query.

3.1 Query language

Central for our engine is the query language. We start with an overview of the pattern matching language our system employs. After that, we present the extensions through which we adapt it to querying L1-L2 treebanks.

3.1.1 UD patterns

To describe the morphosyntactical structures of interest, we use the Haskell-embedded pattern

Figure 2: UD trees for the L1-L2 Swedish sentence *Därför {vill jag → jag vill*} inte flytta* ("Therefore I don't want to move"), discrepancies highlighted in bold. The L2 sentence, on the right, violates V2 word order. Example adapted from the DaLAJ corpus.

matching language available as part of the GF-UD toolset for dependency trees and interlingual syntax (Kolachina and Ranta, 2016; Ranta and Kolachina, 2017).[2] The language provides three types of core patterns:

- *single-token patterns*, e.g. `POS "VERB"`, matching all (sub)trees rooted in a verb. With a similar syntax, it is possible to pattern match based on the token's `XPOS`, `DEPREL`, `FEATS`, `FORM` or `LEMMA`, all of which correspond to homonymous CoNNL-U fields;[3]
- *tree patterns*, in the form `TREE p [ps]`, where `p` is a pattern to be matched by the root node and `[ps]` an ordered list of patterns denoting its dependents. For instance, the pattern `TREE (POS "VERB") [DEPREL "nsubj", DEPREL "obj"]` matches all subtrees rooted in a verb having exactly two subtrees: a nominal subject `nsubj` and a direct object `obj`, in this order;
- *sequence patterns*, matching subtrees where a certain sequence of patterns occurs with no intervening words. For instance, in Subject-Verb-Object (SVO) languages we might want to write `SEQUENCE [POS "VERB", DEPREL "nsubj", DEPREL "obj"]`.

More liberal versions of some of these patterns, using the original pattern name followed by an underscore, also exists. Namely, `DEPREL_ d` ignores relation subtypes, `FEATS_ fs` matches all tokens whose morphological features include (rather than conicide with) `fs`, `TREE_ p [ps]` allows other dependents to appear before, between and/or after the explicitly listed ones and `SEQUENCE_ ps` does not require the listed patterns to occur contiguously. In addition, the language allows to combine

patterns with the logical operators `AND`, `OR` and `NOT` and provides a `TRUE` pattern that matches any subtree.

As a slightly more complex example, consider

```
TREE_
  (POS "VERB")
[DEPREL_ "nsubj",
 OR [DEPREL "obj", DEPREL "obl"]]
```

The above pattern matches any subtree rooted in a verb which has at least two dependents: a nominal subject (ignoring subtyping) and a direct object `obj` or oblique `obl` (not subtyped).

3.1.2 L1-L2 patterns

In some cases, errors can be described by a single UD pattern to be looked for in the L2 treebank. Often, however, it is more convenient and concise (if not even necessary, as illustrated in Figure 1) to describe errors by comparing an L2 sentence to its correction. For this reason, queries in our system are pairs of UD patterns.[4]

As an example of the usefulness of L1-L2 patterns, consider the sentence displayed in Figure 2: in the L2 text displayed on the right, the learner is using Swedish's default SVO order, with the pronoun *jag* preceding the auxiliary verb *vill*. The sentence, however, starts with the adverb *därför*. Being Swedish a language with verb-second (V2) word order, the correction, displayed on the left, moves the auxiliary in the second position, right after the adverb itself. A way to find L2 sentences presenting the same problem is to use a single sequence pattern, for instance:

```
SEQUENCE [
  POS "ADV",
  OR [POS "VERB", POS "AUX"],
  DEPREL_ "nsubj"]
```

This would match sentences like the one above, but not all cases in which V2 order is violated: rather than with an adverb, the sentence might for example start with a prepositional phrase (cf. *På*

---

[2]For an exhaustive description of the pattern matching language, see the relevant GF-UD documentation: `github.com/GrammaticalFramework/gf-ud/blob/master/doc/patterns.md`.

[3]For a short description of the CoNNL-U format and a complete list of the abbreviations used in this text, see Appendix A.

[4]L2-only patterns are of course also allowed and are expanded to ⟨TRUE, p⟩ pairs, where p is the L2 pattern.

grund av detta vill jag inte flytta, with the similar meaning of "Because of this I don't want to move"). Rather than enumerating all possible patterns of V2 order violation, it can be more convenient to express the error in terms of its correction, for instance with the following pair of patterns, which disregards the opening phrase:

```
L1 : SEQUENCE [
        OR [POS "VERB", POS "AUX"],
        DEPREL "nsubj"]
L2 : SEQUENCE [
        DEPREL "nsubj",
        OR [POS "VERB", POS "AUX"]]
```

To avoid repetition, rather than writing two separate patterns, we enclose the discrepant portion in curly brackets and divide the L1 and L2 segments with an arrow:

```
SEQUENCE [
   {OR [POS "VERB", POS "AUX"],
   DEPREL "nsubj" →
   DEPREL "nsubj",
   OR [POS "VERB", POS "AUX"]}]
```

This is our first extension to the pattern matching language described in Section 3.1.1.

We also extend the language with variables. Consider gender agreement. In a dependency tree, most errors of this kind can be identified by checking whether the gender of certain dependents matches the gender of the token they are referred to. In Italian, for instance, adjectives normally agree with the nouns they modify. This is not the case in the sentences like *Indossava una maglietta nero* ("(S)he was wearing a black t-shirt"), where the adjective is incorrectly inflected for gender and matches the pattern

```
TREE_
   (FEATS_  "Gender=Fem")
   [AND [DEPREL "amod",
         FEATS_ "Gender=Masc"]]
```

With the syntax presented until now, however, looking for all noun-adjective gender agreement errors requires a separate query for each possible combination of genders.[5] With variables, syntactically characterized by capital letters preceded by a $ sign, we can instead simply write

```
TREE_
   (FEATS_  "Gender=$A")
   [AND [DEPREL "amod",
         FEATS_ "Gender=$B"]]
```

where $A is assumed to be different from $B. Variables are currently supported for morphological

---

[5]Two in Italian, whose only genders are masculine and feminine, but already six for languages with neuter!

features, Universal POS tags and dependency relations.

3.2 Sentence retrieval algorithm

Alongside the pattern matching language, GF-UD provides a function that, given a pattern and a UD tree, recursively checks if the former matches the latter itself or any of its subtrees. One might be prone to think that performing an L1-L2 query can simply consist in applying this function to all trees in the treebank, looking for L1 sentences matching the L1 portion of the pattern and L2 sentences matching its L2 portion. Doing that, however, generally leads to a significant amount of false positives. Consider, for instance, the following query, intended for searching number agreement errors between a head and its direct dependents:

```
TREE_
   (FEATS_  "Number=$A")
   [FEATS_ "Number={$A → $B}"]
```

Following this naïve approach, the sentence in Figure 1 would match the pattern even if it does not contain a number agreement error. This happens because the L1 sentence matches the L1 pattern at *sono andato* ("(I) have been", two singular verb forms), while the L2 sentence matches the L2 pattern at *andata da entrambi* ("been to both"), where the head *andata* is again a singular but the dependent *entrambi* is a pronoun in its masculine plural form. In this case, in fact, both the original sentence and its correction match both portions of the pattern.

A key observation here is that *sono andato* and *andata da entrambi* do not semantically correspond to each other: to solve the problem, we need to further align our L1-L2 treebank, recursively putting L1 subtrees in correspondence with their L2 counterparts. To do that, we use the CONCEPT-ALIGNMENT Haskell library (Masciolini and Ranta, 2021). While originally designed for extracting translation equivalents from multilingual parallel treebanks, its *alignment criteria*, i.e. the set of rules to decide whether two subtrees correspond to each other, are configurable and easily adaptable to the L1-L2 domain. Actually, accuracy on L1-L2 corpora tends to be better than it is for multilingual treebanks. Learner sentences and their corrections, in fact, usually share the vast majority of the lemmas, something that can be taken into account when defining custom alignment criteria.

As a first step, then, we extract phrase- and word alignments, in the form of pairs of L1-L2 UD trees, for each L1-L2 sentence pair. After that, to decide whether a sentence pair matches a given L1-L2 pattern, we apply a nonrecursive version of GF-UD's pattern matching function to check if there is a pair of aligned subtrees whose L1 (resp. L2) component matches the L1 (resp. L2) portion of the pattern. Matching nonrecursively, only on complete UD trees (although extracted from full sentences), is crucial here, as it is, in most cases, what prevents L1-L2 patterns from being matched in structurally similar but semantically unrelated subtrees of the L1-L2 sentence pair.

The careful reader, however, will have noticed that this does not solve the issue for the specific example mentioned, where the subtrees matching the L1-L2 pattern, *sono andata* and *andata da entrambi*, share the same head *andata*. The false positive is due to the fact that its dependents, *sono* and *da entrambi*, do not correspond to each other. For TREE and TREE_ patterns, then, we recursively perform the additional check that all dependents involved in the match are aligned with each other. A similar mechanism is in place for SEQUENCE and SEQUENCE_ patterns, to avoid matching subsequences that, while part of the same subtree, are semantically unrelated to each other.

3.3 Subsentence extraction

By default, the output of the program is the list of IDs of the sentences matching the given query. Nontheless, extracting relevant subsentences can be useful both for futher processing of the error-correction pair and to more easily visualize discrepancies in the context in which they occur.

The fact that the algorithm we just presented applies patterns on sub-sentence alignments makes it straightforward to locate the specific L1 and L2 subtrees where the match is found. Doing so, however, looses its usefulness when the root (or the head of a large subtree) is involved in the error, as the resulting subtrees are too big. For this reason, we prune the extracted subtrees by only keeping the portions explicitly described by the pattern: individual heads for single-token queries, heads and their dependents that match a pattern in `ts` for TREE_ `ts` patterns and, for sequence patterns, rather than the whole subtree including the given sequence, only subtrees matching one of patterns explicitly listed in it. Implementation-wise, this is done by converting the query's UD patterns into *replacement patterns* in GF-UD's tree manipulation language.[6]

The engine has options to extract such pairs of matching subsentences and write them to CoNNL-U files or to output a markdown report where they are highlighted in bold in the sentences where they occur. Reports obtained with this method can be found in Appendix C.

4 Evaluation

Aiming at assessing the performance of the query engine, we tested it on two L1-L2 error-tagged corpora in two different languages, one that comes with manually validated UD annotations and one that was only parsed automatically. In both cases, we randomly selected 100 sentences to be used during development and set the rest aside for testing. Carrying out a systematic evaluation was not possible: more often than not, an error tag maps not to a single L1-L2 query, but to a potentially rather large set of queries whose exhaustiveness is hard to verify. We therefore decided to compute the sentence-level precision and recall obtained upon running, for each corpus, a single-token, a tree and a sequence example query, all chosen to be descriptive of an error typical of the language at hand. To automate part of the evaluation, we tried to make it so that the single-token queries correspond exactly to an error label of the dataset at hand. For tree and sequence queries, this was more difficult, so we aimed at describing, through our queries, a subset of the errors described by a certain error label. By comparing the results obtained on the two corpora, and in particular through manual error analysis, we also aim at getting insights about the ways in which automatic annotation affects the performance of the engine, even though we cannot quantify its impact.

4.1 Experiments on manually validated data

4.1.1 Data

Our first treebank of choice is the 398-sentence manually validated subset of the VALICO-UD corpus (Di Nuovo et al., 2022), consisting of texts written by Italian L2 learners with various L1 backgrounds. While this is much smaller than

---

[6]The pattern replacement language is, in many ways, analogous to the pattern replacement language and exhaustively documented alongside it: `github.com/GrammaticalFramework/gf-ud/blob/master/doc/patterns.md`

the above mentioned ESL treebank, we preferred it due to its full UD annotation (ESL sentences, on the contrary, are not annotated for lemmas and POS tags).

Error tagging is XML-like and based on Nicholls (2003), where each label consists of a two-letter code, with the first character representing the general class of error (inflection, omission etc.), and the second generally specifying the POS tag of the word(s) involved. In some cases, VALICO-UD labels also present a third letter, usually denoting an incorrect inflectional feature.[7] In the error tag IDG, for instance, the three letters stand for "Inflection", "Determiner" and "Gender" and are meant to enclose determiners incorrectly inflected for gender.

4.1.2 Queries

Gender being a notorious source of confusion for learners of Italian, we chose the set of two L1-L2 patterns equivalent to IDG as our first test query:

```
V₁: AND [
        POS "DET",
        FEATS_ "Gender={$A → $B}"]
```

Our second, more complex query is in turn

```
V₂: TREE
        (POS "NOUN")
        [ {DEPREL "det", → }
          DEPREL "det:poss" ]
```

which denotes a subclass of the MD (Missing Determiner) VALICO category describing the common error pattern for which the definite article that should precede a possessive modifying a noun is omitted (consider, for instance, the nominal phrase $\{il \to \_ *\}$ *suo naso* - "his nose").

Word order is relatively free in Italian, and finding recurrent patterns in such a small corpus is not easy. Instead, we use a sequence pattern to find particular occurrences of RD (Replacement of Determiner) errors:[8]

```
V₃: SEQUENCE [
        LEMMA "non",
        LEMMA "ci",
        LEMMA "essere",
        LEMMA {"nessun*" —> "un*"}]
```

---

[7]An exhaustive description of the error annotation guidelines is given at `https://raw.githubusercontent.com/ElisaDiNuovo/VALICO-UD_guidelines/main/Error_Annotation_Guidelines_v.1.1.pdf`

[8]Even though UD patterns do not support general regular expressions, an asterisk at the beginning or end of a string can be used as a wildcard.

	Precision	Recall
V_1	43% (40%)	100%
V_1'	100% (90%)	100% (64%)
V_2	100%	40%
V_3	-	0%
V_3'	100%	100%

Table 1: Precision and recall of the example queries run on the VALICO-UD corpus. Values in parentheses do not take correctness, consistency and completeness issues in the manual annotation of the sentences.

This pattern matches phrases that translate to "there is/are no x". In Italian, this is usually expressed with a double negation: not only is there an initial negation, *non*, but the determiner introducing x (*nessuno* or *nessuna*, depending on x's gender) also has negative polarity. However, since this is not the case in most other languages, it is common for L2 speakers to simply use the indefinite article (*un/un'/uno/una*).

4.1.3 Results

As displayed in Table 1, recall is perfect for the first query. The low precision should not mislead: one of the false positives is due to an inconsistency in the error annotation,[9] and 8 of the remaining 20 false positives are due to cascading errors: it is often the case, in fact, that the gender of the noun the determiner is referred to is incorrect itself and the incorrect inflection of the determiner introducing it is only a consequence of that. In this case, the incorrect noun is marked with the RN (Replace Noun) label in case of a lexical error (cf. *la panca → il banco**, "the bench → the desk") or with the ING (Incorrect Noun Gender) label if the noun is incorrectly inflected (cf. *gli uccelli → le uccelle**", "the birds"), while the determiner gets the IDGcascade tag. To avoid matching cascading errors, we can turn V_1 into a TREE query and check whether the determiner's gender agrees with the noun's:

```
V₁': TREE_
        (AND [POS "NOUN",
              FEATS_ "Gender=$A"])
        [AND [POS "DET",
              FEATS_ "Gender={$A → $B}"]]
```

---

[9]The sentence in question is *Ho voltato la pagina e ho iniziato a leggere {un → un'*} altro titolo.* ("I turned the page and started reading another title."). This is an interesting case: the UD annotation correctly states that the indefinite article *un* is masculine while its L2 counterpart *un'* (mind the apostrophe) is feminine, but the manually assigned error tag, rather than the expected IDG, is SEU, which indicates, also correctly, a spelling error involving an unnecessary apostrophe.

As the table shows, precision significantly increases after this change. While recall appears to decline, all of the false negatives can be traced back to errors, inconsistencies or incompletenesses in either UD annotation or error tagging (see Appendix B for a complete list of issues found in the VALICO-UD corpus).

When it comes to V_2, there are no false positives and 3 false negatives due to alignment errors. In every cases, the sentence at hand presents several errors, so that the L1 and L2 trees differ significantly, increasing the difficulty of the alignment task.

V_3, on the other hand, only has one expected hit, the sentence *-Non c'è {nessun bacio → una baciata*} per me,- ha pensato tristemente.* (-There's no kiss for me,- (s)he thought sadly."), but no matches. Again, the problem is an alignment error, since the expected sentence id is indeed returned if we use a similar L2-only query:

```
V'₃: SEQUENCE [
        LEMMA "non",
        LEMMA "ci",
        LEMMA "essere",
        LEMMA "un*"]
```

4.2 Experiments on parsed data

4.2.1 Data

To evaluate the tool on automatically annotated data, we used a 2087-sentence subset of a not-yet-released version of the DaLAJ corpus (Volodina et al., 2021).[10] Such corpus is composed of L1-L2 sentence pairs automatically derived from the error-annotated learner corpus of anonymized L2 Swedish essays SweLL (Volodina et al., 2019). More specifically, SweLL essays are processed so that the L2 component of each sentence pair in the DaLAJ corpus contains exactly one morphological or syntactical error. Arguably, this makes automatically parsing the L2 sentences and aligning them to their L1 counterparts significantly easier than it would be if multiple, possibly cascading and/or overlapping errors coexisted. Evaluating the tool on the SweLL corpus itself would however have been impossible since the original versions of the essays are not sentence-aligned.

In terms of error-annotation, since DaLAJ entries only contain one error each, sentence pairs are simply assigned a SweLL error label. SweLL's

---

[10]The initial version of the corpus presented in the paper is exclusively composed of sentences presenting lexical errors; while the updated one also covers morphosyntactical errors

error taxonomy, thorughly described by Rudebeck and Sundberg (2021), is a two-level classification: error labels are composed of a capital letter, indicating the error's macro-category (Ortography, Lexical level, Morphological level, Syntactical level or Punctuation), followed by a secondary label giving additional information about the type of error and/or the POS involved. The M-Case label, for instance, indicates the presence of a morphological error that has to do with the case inflection of a noun or pronoun.

DaLAJ sentences were parsed with UDPipe 1 (Straka et al., 2016) using the `swedish-talbanken-2.5` model. UDPipe 1 was chosen due to its speed and ease of use, even though a more recent version of the same or another UD parser might achieve better results. The resulting dataset is available at `URL/hidden/for.review`.

4.2.2 Queries

We mentioned the M-Case label, used to mark wrongly inflected nouns and pronouns. Such label can be mapped to a rather straightforward single-token query:

```
D₁: FEATS_ "Case={$A → $B}"
```

In Swedish, nouns have a definite and an indefinite form. The correct usage of these two forms is typically difficult to aquire for L2 learners. As an example of tree query, we therefore use

```
D₂: TREE_
      (FEATS_ "Definite={Def → Ind}")
      [AND [DEPREL_ "det",
            FEATS_ "Definite=Def"]]
```

This denotes sentences where a nominal (typically a noun) is in its indefinite form despite being introduced by a definite determiner (typically an article). In terms of SweLL error labels, these cases are a fraction of those marked as M-Def, which is used to indicate a wide variety of errors concerning definiteness (adjective-noun agreement, missing determiners etc.).

Finally, along the lines of the sequence patterns discussed in Section 3.1.2, we use

```
D₃: SEQUENCE [
      DEPREL_ "advmod",
       {OR [POS "VERB", POS "AUX"],
        DEPREL_ "nsubj" →
        DEPREL_ "nsubj",
        OR [POS "VERB", POS "AUX"]}]
```

	Precision	Recall
D_1	77% (76%)	58%
D_2	75%	90%
D_3	89%	62%

Table 2: Precision and recall of the three example queries run on the DaLAJ corpus. Values in parentheses do not take error annotation issues into account.

to look for sentences where the V2 order is violated following an adverb or an adverbial clause.[11] With this pattern, we cover some of the errors labelled as S-FinV, i.e. those involving the misplacement of a finite verb.

4.2.3 Results

As Table 2 suggests, precision is reasonably good even on our automatically annotated data, while recall fluctuates significantly depending on the query.

When it comes to the first query, false negatives are in the almost totality of the cases due to the fact that the parser, as it is to be expected, assigns tokens different dependency labels based on their case (typically, subjects incorrectly inflected in their accusative form are labelled as direct objects and objects in the nominative form become obliques). The vast majority of the false positives is also due not to the query engine itself, but to incorrect alignments deriving from parse errors. In 11 out of 13 such cases, false positives are sentences containing a syntax error, which seems to confirm the intuition that incorrect syntax causes the parser to annotate the sentences incorrectly. In only one case a false positive is due to an incorrectly assigned error label. More interesting are the cases in which tokens are correctly aligned, but the correction of a syntax error consists in a rephrasing that happens to also alter the case of one of the words involved, such as in the L2 phrase *Rollerna för barn* (literally "The roles for the children"), corrected as *Barnens roller* ("The children's roles"), transforming the nominative *barn* into a genitive *barnens*.

The tree query, more specific, has only 10 expected matches, allowing for a through error analysis. The only false negative seems to be due to an alignment error whose cause is hard to pinpoint. Of three false positives, one derives from incorrect morphological annotation, one from a rephrasing that creates problems at the alignment stage and

---

[11]Note that, for simplicity, we are only looking for sequences where the verb is contiguous to the subject.

one results from the presence, in the L2 sentence *De ligger på första plats i den ligan!* ("They are in first place in that league!"), of the English word "league", annotated (arguably correctly) as an indefinite but translated, in the correction, to the definite *ligan*.

The relatively low recall for D_3 is easily explained by the fact that, as we already discussed, sentences containing syntactical errors are especially challenging for the parser.

5 Conclusions and future work

We presented a query engine for L1-L2 parallel UD treebanks, the first in a larger collection of tools for L2 UD treebanks. The tool, which does not rely on an underlying error taxonomy, allows to search for error-correction pairs via L1-L2 patterns, i.e. pairs of morphosyntactical structures expressed in a pattern matching language for dependency trees, which we extended simplifying its use on parallel treebanks. Our novel retrieval algorithm allows searching for full sentences as well as extracting their specific query-matching portions.

Our first evaluation of the tool gives promising results, but also shows that the alignment component is often the bottleneck, which encourages us to investigate alignment techniques specifically meant for L1-L2 corpora, such as Felice et al. (2016)'s. The fact that, for automatically annotated data, many alignment issues derive from parse errors also seems to confirm the scarce robustness of standard tools to learner errors, pointing to a need to train *ad hoc* models or explore new, more specific approaches. In future versions of the tool, we aim at optimizing variables and generalizing them to all UD fields rather than only those with a finite number of possible values, so to increase the query language's expressive power. Furthermore, while the tool is designed with L1-L2 treebanks in mind, nothing prevents us from testing it on multilingual parallel UD treebanks, for example to find instances of known translation divergences.

As for the future of L2-UD, our efforts in the near future will be focused on extracting L1-L2 patterns from L1-L2 treebanks. Eventually, we hope it will also be possible to integrate the two and enable performing queries by typing an example L2 sentence-correction pair: the tool will extract the error pattern it contains and search the treebank for similarly incorrect sentences.

References

Yevgeni Berzak, Jessica Kenney, Carolyn Spadine, Jing Xian Wang, Lucia Lam, Keiko Sophie Mori, Sebastian Garza, and Boris Katz. 2016. Universal Dependencies for learner English. *arXiv preprint arXiv:1605.04278*.

Christopher Bryant, Mariano Felice, and Edward Briscoe. 2017. Automatic annotation and evaluation of error types for grammatical error correction. In *Proceedings of the 55th Annual Meeting of the Association for Computational Linguistics*. Association for Computational Linguistics.

Leshem Choshen, Dmitry Nikolaev, Yevgeni Berzak, and Omri Abend. 2020. Classifying syntactic errors in learner language. *arXiv preprint arXiv:2010.11032*.

Elisa Di Nuovo, Manuela Sanguinetti, Alessandro Mazzei, Elisa Corino, and Cristina Bosco. 2022. VALICO-UD: Treebanking an italian learner corpus in universal dependencies. *IJCoL. Italian Journal of Computational Linguistics*, 8(8-1).

Mariano Felice, Christopher Bryant, and Ted Briscoe. 2016. Automatic extraction of learner errors in esl sentences using linguistically enhanced alignments. In *Proceedings of COLING 2016, the 26th International Conference on Computational Linguistics: Technical Papers*, pages 825–835.

Yan Huang, Akira Murakami, Theodora Alexopoulou, and Anna Korhonen. 2018. Dependency parsing of learner English. *International Journal of Corpus Linguistics*, 23(1):28–54.

Prasanth Kolachina and Aarnte Ranta. 2016. From abstract syntax to Universal Dependencies. In *Linguistic Issues in Language Technology, Volume 13, 2016*.

John SY Lee, Herman Leung, and Keying Li. 2017a. Towards Universal Dependencies for learner Chinese. In *Proceedings of the NoDaLiDa 2017 Workshop on Universal Dependencies (UDW 2017)*, pages 67–71.

John SY Lee, Keying Li, and Herman Leung. 2017b. L1-L2 parallel dependency treebank as learner corpus. In *Proceedings of the 15th International Conference on Parsing Technologies*, pages 44–49.

Arianna Masciolini and Aarne Ranta. 2021. Grammar-based concept alignment for domain-specific Machine Translation. In *Proceedings of the Seventh International Workshop on Controlled Natural Language (CNL 2020/21)*.

Diane Nicholls. 2003. The Cambridge Learner Corpus: Error coding and analysis for lexicography and elt. In *Proceedings of the Corpus Linguistics 2003 conference*, volume 16, pages 572–581. Cambridge University Press Cambridge.

Joakim Nivre, Marie-Catherine de Marneffe, Filip Ginter, Jan Hajič, Christopher D Manning, Sampo Pyysalo, Sebastian Schuster, Francis Tyers, and Daniel Zeman. 2020. Universal Dependencies v2: An evergrowing multilingual treebank collection. *arXiv preprint arXiv:2004.10643*.

Peng Qi, Yuhao Zhang, Yuhui Zhang, Jason Bolton, and Christopher D Manning. 2020. Stanza: A Python natural language processing toolkit for many human languages. *arXiv preprint arXiv:2003.07082*.

Aarne Ranta and Prasanth Kolachina. 2017. From Universal Dependencies to abstract syntax. In *Proceedings of the NoDaLiDa 2017 Workshop on Universal Dependencies (UDW 2017)*, pages 107–116.

Lisa Rudebeck and Gunlög Sundberg. 2021. SweLL correction annotation guidelines.

Milan Straka. 2018. UDPipe 2.0 prototype at CoNLL 2018 UD shared task. In *Proceedings of the CoNLL 2018 Shared Task: Multilingual Parsing from Raw Text to Universal Dependencies*, pages 197–207.

Milan Straka, Jan Hajic, and Jana Straková. 2016. UDPipe: trainable pipeline for processing CoNLL-U files performing tokenization, morphological analysis, pos tagging and parsing. In *Proceedings of the Tenth International Conference on Language Resources and Evaluation (LREC'16)*, pages 4290–4297.

Elena Volodina, Lena Granstedt, Arild Matsson, Beáta Megyesi, Ildikó Pilán, Julia Prentice, Dan Rosén, Lisa Rudebeck, Carl-Johan Schenström, Gunlög Sundberg, et al. 2019. The SweLL language learner corpus: From design to annotation. *Northern European Journal of Language Technology*, 6:67–104.

Elena Volodina, Yousuf Ali Mohammed, and Julia Klezl. 2021. DaLAJ-a dataset for linguistic acceptability judgments for Swedish: Format, baseline, sharing. *arXiv preprint arXiv:2105.06681*.

Appendix A Abbreviations

A.1 UD standard

A.2 CoNNL-U fields

- `DEPREL`: dependency label;
- `FEATS`: list of morphological features;
- `FORM`: word form or punctuation symbol;
- `LEMMA`: lemma/stem of the word form;
- `POS`: Universal POS tag;
- `XPOS`: language-specific POS tag.

For an exhaustive description of the CoNNL-U format, see `universaldependencies.org/format.html`.

A.2.1 Universal POS tags

- `ADP`: adposition (pre- or postposition);
- `ADV`: adverb;
- `AUX`: auxiliary;
- `DET`: determiner;
- `PRON`: pronoun;
- `VERB`: non-auxiliary verb.

For a comprehensive list of UD POS tags, see `universaldependencies.org/u/pos`.

A.2.2 Universal dependency relations

- `advmod`: adverbial modifier of a predicate or modifier word;
- `amod`: adjectival modifier of a nominal;
- `aux`: auxiliary;
- `case`: case-marking element treated as a separate word;
- `det`: determiner. Subtypes: `poss` (possessive);
- `nsubj`: nominal subject;
- `obj`: direct object;
- `obl`: oblique nominal, i.e. non-core verb argument or adjunct;
- `root`: root of the sentence, usually its main (non-auxiliary) verb.

For a comprehensive list of UD relations, see `universaldependencies.org/u/dep`.

A.3 VALICO error labels

- IDG: Determiner incorrectly Inflected for Gender. The IDGcascade label is used in cases where the incorrect inflection depends on another error, typically ING or RN;
- ING: Noun incorrectly Inflected for Gender;
- RD: Determiner Replacement (wrong choice of determiner);
- RN: Noun Replacement (lexical error involving a noun);
- SEU: Spelling error - Unnecessary apostrophE.

A.4 SweLL error labels

- M-Case: noun or pronoun incorrectly inflected for case;
- M-Def: definiteness-related error, namely either:
  - noun, pronoun, adjective or participle incorrectly inflected for definiteness;
  - incorrect, missing or redundant article;
- S-FinV: incorrect placement of a finite verb.

Appendix B Annotation inconsistencies

B.1 VALICO-UD corpus

- sentence `34-12_en-3`: *{un → un'*}* correctly labelled as SEU but not as IDG
- sentence `19-06_en-3` *un* in *{un uomo → un'uoma*}* labelled as IDG rather than IDG-cascade
- sentence `18-10_en-1` *la* in *{sul braccio → sul+la braccia*}* labelled as IDG rather than IDGcascade
- sentence `18-05_en-1` token *sedile* lacking gender annotation in both the L1 and the L2 files
- sentece `17-07_en-2` token *amante* lacking gender annotation in both the L1 and the L2 files
- sentece `3-13_fr-3` *le* in *{gli uccelli → le uccele*}* labelled as IDG rather than IDGcascade

B.2 DaLAJ corpus

- sentence `1811` labelled as S-Clause rather than M-Case.

Appendix C   Example program output: markdown reports

C.1 `TREE_ (AND [POS "NOUN", FEATS_ "Gender=$A"]) [AND [POS "DET", FEATS_ "Gender=$A → $B"]]` (V_1')

Sentence 30-09_de-2:

L1 sentece	L2 sentece
Poi , lei si è arrabbiata e mi ha detto che questo uomo con i grandi muscoli che si è sdraiato a terra era il suo fidanzato e **il suo** grande **amore** .	Poi , lei si è arrabbiata e mi ha detto che questo uomo con i grandi muscoli che si è sdraiato sulla terra era il suo fidanzato e **la sua** grande **amore** .

Sentence 3-11_fr-3:

L1 sentece	L2 sentece
La donna ringraziava il suo salvatore con un abbraccio e chiudeva **gli occhi** .	La dona ringraziava suo salvatore con un braccio e chiusa **le occhi** .

Sentence 10-07_es-1:

L1 sentece	L2 sentece
Gli ho gridato **alcune parolacce** .	L' ho gridato **alquini parolace** .

Sentence 4-04_fr-2:

L1 sentece	L2 sentece
Un **altro uomo** si trovava lì , seduto su una panchina del di il parco , leggendo un giornale con i suoi occhiali .	Un **altra uomo** , si trova li , seduto sul su il un panchino del di il parco , leggendo un giornale con i suoi occhiali .

Sentence 34-12_en-3:

L1 sentece	L2 sentece
Ho voltato la pagina e ho iniziato a leggere **un** altro **titolo** .	Ho voltato la pagina e ho iniziato a leggere **un'** altro **titolo** .

Sentence 19-01_en-3:

L1 sentece	L2 sentece
Ieri al a il parco , **un uomo** brutto è arrivato e ha detto delle parole cattive a una donna .	Ieri al a il parco , **un' uomo** brutto è arrivata e ha detto le parole cattive a una donna .

Sentence 27-02_de-3:

L1 sentece	L2 sentece
Subito guarda come un altro uomo con grande forza fisica e con malumore porta sulle **sue spalle** una ragazza che grida .	Subito guarda come un altro uomo con grande forza fisica e con malumore porta una ragazza sulle **sui spalle** che grida .

Sentence 3-12_fr-3:

L1 sentece	L2 sentece
Era **un** vero **momento** di benessere .	Era **una** vero **momento** di benessere .

Sentence 27-08_de-3:

L1 sentece	L2 sentece
« Il **mio amore** non dipende dal suo comportamento . »	« Il **mia amore** non dipende dal suo comportamento . »

Sentence 32-06_de-2:

L1 sentece	L2 sentece
Un uomo molto forte , intelligente , sportivo e carino mi ha salvato da **questa** ignorante **persona** , Marco .	Un' uomo molto forte , intelligente , sportivo e carino mi ha salvato di **questo** ignorante **persona** Marco .
Un uomo molto forte , intelligente , sportivo e carino mi ha salvato da questa ignorante persona , Marco .	**Un' uomo** molto forte , intelligente , sportivo e carino mi ha salvato di questo ignorante persona Marco .

C.2 SEQUENCE [DEPREL_ "advmod", OR [POS "VERB", POS "AUX"], DEPREL_ "nsubj" -> DEPREL_ "nsubj", OR [POS "VERB", POS "AUX"]] (D_3)

Sentence 1958:

L1 sentece	L2 sentece
Därför tycker jag om havet .	**Därför jag tycker** om havet .

Sentence 1943:

L1 sentece	L2 sentece
Tyvärr har någonting hänt som gör att jag inte kan gå på kursen och jag önskar att få pengarna tillbaka .	**Tyvärr någonting har hänt** som gör att jag inte kan gå på kursen och jag önskar att få pengarna tillbaka .

Sentence 1950:

L1 sentece	L2 sentece
Därför vill jag inte **flytta** .	**Därför jag vill** inte **flytta** .

Sentence 1965:

L1 sentece	L2 sentece
Där bodde jag i Göteborg med min mamma och hennes hundar i hennes hus .	**Där jag bodde** i Göteborg med min mamma och hennes hundar i hennes hus .

Sentence 1936:

L1 sentece	L2 sentece
Ibland **kan vi titta** och lyssna på hur det funkar .	Ibland **vi kan titta** och lyssna på hur det funkar .

Sentence 1139:

L1 sentece	L2 sentece
Därför har **man kommit** med förslaget att ha en kurs angående arbetslivet i gymnasiet .	**Därför man kommit** med förslaget att ha en kurs angående arbetslivet i gymnasiet .

Sentence 1942:

L1 sentece	L2 sentece
Lyckligtvis kan du spela piano , och **där** kan **du lära** känna nya vänner .	Lyckligtvis kan du spela piano , och **där du** kan **lära** känna nya vänner .

Sentence 1976:

L1 sentece	L2 sentece
Ibland brukar man säga att kärleken har ingen gräns och det är sant .	**Ibland man brukar** säga att kärleken har ingen gräns och det är sant .

Sentence 1939:

L1 sentece	L2 sentece
Men nu **är jag** inte **intresserad** av den längre .	Men nu **jag är** inte **intresserad** av den längre .