Discrete Time Series Clustering and Delineation: A Tree-Based Approach to Linear Temporal Logic Discovery

ICAPS XAIP 2022 Submission

Abstract

Inferring temporal logic specifications from plan traces can offer significant insight into several aspects of planning such as goal recognition, policy summarization, and system dynamic modelling. Prior work in this area has predominantly focused on the identification of specifications that satisfy all plan traces within a set, however more recently, contrastive approaches concerning the delineation of two sets have also been established. While these approaches are effective in their defined scope, they assume the existence of only one or two behavioural clusters. In this paper, we re-imagine contrastive specification learning by proposing a novel tree generation technique which allows k clusters to be discovered. By embracing a Monte Carlo node-splitting approach, our algorithm seeks balance to contrastively divide any given set of plan traces into two sets with an accompanying temporal logic specification satisfying one of the sets. Recursing this procedure, we demonstrate the effectiveness of our approach to cluster and delineate plan traces, allowing temporal logic specifications to evoke insight at each level of the resulting tree.

Introduction

Time series data represents a significant opportunity for institutions and individuals to learn from the past and present to improve the future. The prevalence of unstructured data within real-world settings, however, represents an active challenge for existing analytical techniques. This impediment is especially relevant within research areas such as goal recognition, policy summarization, and system dynamic modelling, where the shared objective is to derive meaning from observed behavior. To establish meaningful insights from unstructured time-series data, partitions and patterns must be identified to effectively differentiate observations based on temporal attributes. Currently, however, there are no existing techniques that allow multiple sets of time-series traces to be automatically clustered and differentiated. To address this challenge, we propose a novel approach to provide structure to unstructured time series data. By leveraging linear temporal logic, our proposed method successfully clusters an unspecified quantity of plan traces using unsupervised techniques and contrastively explains

how these clusters are characterized. Given these developments, our novel framework represents a vital first step in providing researchers a new and more powerful approach to time-series data analysis.

Prior works in the area of plan explanations have focused on effectively summarizing a single set of traces with the goal of making sense of the output of planners. This has typically been done by determining temporal specifications that are satisfied by all traces in a given set (Yang et al. 2006; Lemieux, Park, and Beschastnikh 2015). The problem with summarization-based methods like these, however, is that temporal specifications are not designed to be relevant or interesting, merely accurate. To address this, more recent research has shifted focus towards contrastive explanations, where the research task is to automatically identify specifications that differentiate two sets of traces (Kim et al. 2019). While contrastive explanations arguably offer greater insight than summarization-based approaches because they allow trade-offs within plan rationale to be understood, the conditions required for these techniques to be applicable are quite niche. Most importantly, traditional contrastive explanation research condenses the assertion of contrast to exactly two sets of traces; in practical applications, natural decomposition likely exists between more than two clusters of traces. To accommodate this, we reimagine contrastive explanations to account for multiple sets of traces. Given the significant research interest that has been demonstrated in these similar areas in recent years, this topic is demonstrated to be both important and relevant. The main contribution of this paper includes an extension of contrastive explanations to differentiate multiple sets of traces. As a further contribution, this paper's proposed methodology allows contrastive sets to be automatically identified through a novel unsupervised clustering process.

Our methodology approaches contrastive explanations as an unsupervised learning task, where the objective is to automatically identify k sets of traces guided by temporal logic specifications. We begin by formulating this as a subproblem, where the challenge becomes identifying an efficient and accurate technique to split a single set of plan traces into two balanced sets of near-equal size via temporal logic specifications. To achieve information gain when splitting a given set of plan traces, the identified temporal logic specification must entail the first subset of traces, but

Template	n_T	Formula	Meaning
$\varphi global$	1	$\mathbf{G}p_i$	p_i is true throughout the entire trace.
$\varphi eventually$	1	$\mathbf{F}p_i$	p_i eventually occurs (may later become false).
$\varphi atmostonce$	1	$\mathbf{G}(p_i \rightarrow (p_i\mathbf{W}\mathbf{G}\neg p_i))$	Only one contiguous interval exists where p_i is true.
$\varphi stability$	1	$\mathbf{FG}p_i \wedge \mathbf{G}(p_i \rightarrow (p_i\mathbf{W}\mathbf{G}\neg p_i))$	p_i eventually occurs and stays true forever.
$\varphi until$	2	$p_i\mathbf{U}p_j$	p_i has to be true until p_j eventually becomes true.
$\varphi response$	2	$\mathbf{G}(p_i \rightarrow \mathbf{XF}p_j)$	If p_i occurs, p_j eventually follows.
$\varphi precedence$	2	$(p_j \wedge \neg p_i)\mathbf{R}(\neg p_i)$	If p_i occurs, p_j occurred in the past.

Table 1: The set of LTL templates embraced within BayesLTL (Kim et al. 2019), adopted within our approach. n_T corresponds to the number of free propositions for each template. When multiple propositions are used in a template, the condition is asserted for all propositions using conjunction.

not the second; the more equal these subsets are in size, the greater the information gain of the split. By proposing a solution to this sub-problem and recursing on that, we focus on discovering trees of LTL specifications that allow human users to understand plan traces with respect to the behaviour of acting agents.

Applying tree generation to six benchmark planning domains of three unique vocabulary sizes, we demonstrate the generality of our algorithm to adapt to diverse problem sets. Evaluating the size of the resulting LTL specifications from this assessment, we discover a tendency of robust fit, mitigating threats of underfitting/overfitting behavior. For a deeper analysis into the mechanics of our approach, we measure the relationship between node size and splitting execution time, discovering a near-linear positive correlation and justifying our sampling step. To further highlight the effectiveness of sampling, we derive probability distributions of information gain with respect to sample size, observing consistently high information gain densities for samples as small as 10% of the original set of traces. Finally, we investigate the benefit in time of additional search iterations, discovering a trend of diminishing marginal returns, which indicates a lack of necessity for excessive iterations.

Preliminaries

Linear temporal logic (LTL) is a modal logic which was first proposed by Pnueli in 1977 and has become widely adopted for applications such as automata-theoretical model checking (Vardi 1996; Rozier 2011; Latvala 2005), property expression in formal verification (Grosse and Drechsler 2003; Kupferman 2006), and as a specification language (Kim et al. 2019; Kasenberg and Scheutz 2017; Lemieux, Park, and Beschastnikh 2015). Due to its powerful ability to encode relationships between events in time, LTL represents an effective medium for describing system behaviour in relation to the past, present, and future. LTL's modalities referring to time enable formulae to express concepts such as possibility, necessity, and existence. The syntax of LTL consists of two fundamental operators, "next"(X) and "until"(U). The first fundamental operator, X, is designed to provide a constraint for the next period in time, where the

proposition $X\phi$ is defined to be true if in the next time period ϕ is true. The second fundamental operator, U, is designed to connect various fluents with each other, where the proposition $\phi\,U\psi$ is defined to be true if ϕ remains true in every state until ψ becomes true. Using these fundamental operators, additional operators can also be created.

When evaluating the size $|\varphi|$ of an LTL formula, we embrace Gaglione et al.'s definition, which counts the number of unique subformulas contained within an expression. For example, the size of $\varphi = (p\,UXq) \vee Xq$ is 5 because the unique subformulas in φ are p, q, Xq, $p\,UXq$, and $(p\,UXq) \vee Xq$ (Gaglione et al. 2021). Since we employ BayesLTL (Kim et al. 2019) as a subprocess within our algorithm, we embrace the same interpretable templates used by Kim et al. in our research. These templates were selected within BayesLTL due to their widespread use within software verification systems; these templates can be viewed in Table 1.

Problem Statement and Approach

Tree and Node Structure

Our proposed delineation tree consists of nodes and edges that resemble a binary tree data structure. The primary attribute that defines a given node is a set of internally stored traces. Non-terminal nodes also possess an LTL formula that is catered to their respective traces and designed for delineation. By using a given node's LTL specification, traces within that node can be constrastively evaluated based on entailment. This evaluation allows two new nodes to be created, whereby traces are allocated into two subsets based on whether the formula is satisfied by a given trace. These subsets of traces are initialized as new nodes, and this novel process is recursively implemented and repeated until a tree is fully created. Once the tree generation process is complete, the delineation of nodes can be analyzed as a collective or in subsets of any size. By evaluating the shortest path between any pair of nodes, the conjugation of LTL along the tree's branches allows nodes to be accurately differentiated and contrastively explained. See Figure 1 for a visual representation of this tree structure.

Figure 1: A visual representation of the binary tree structure used within our delineation process. Each node π represents a collection of traces sorted by entailment for each formula φ down the tree.

Node Splitting Criteria

As the primary engine of tree generation, our approach relies on a node splitting technique that is designed to efficiently discover contrastively differentiating LTL specifications. Representing the primary sub-problem of cluster identification and delineation, the challenge of this step is to automatically discover LTL specifications that maximize information gain. Formally, we define information gain of a specification φ, given node n, containing the set of traces π as:

$$1 - \frac{\left| \left| \{\pi : \pi \models \varphi, \pi \in \pi_n\} \right| - \left| \{\pi : \pi \not\models \varphi, \pi \in \pi_n\} \right| \right|}{|\pi_n|} \tag{1}$$

Specifications that demonstrate information gain of 1 are considered perfect, while specifications with information gain of 0 are ineffectual. By maximizing information gain, we maximize the balance of the resulting tree, leading to an optimally efficient and concise data structure.

To discover specifications that maximize information gain, our technique embraces the explanatory power of the BayesLTL framework (Kim et al. 2019). Given the effectiveness of BayesLTL to identify LTL specifications differentiating two groups of traces, the tool can be used as an instrument to assist in the discovery of relevant splits. BayesLTL, however, requires positive and negative labels for input traces. Therefore, given a single set of unlabelled traces, the problem becomes identifying the optimal allocation of traces into positive and negative subsets (π_+ and π_-), such that an LTL specification can be discovered that maintains balance post-evaluation of entailment. The quantity of ways in which these two equally sized subsets can be created intuitively leads to a combinatorial explosion. To combat the complexity associated with this immense search space, we employ both sampling and Monte Carlo search.

We first use random sampling without replacement to mitigate the complexity of each search step. This means that instead of evaluating BayesLTL (Kim et al. 2019) on positive and negative sets of size $\frac{1}{2}|\pi_n|$, we reduce the contrastive evaluation to input sets of size $\frac{p}{2}|\pi_n|$, where p represents the size of the sample proportion from the parent set. We demonstrate the representative abilities of varying sample proportions, and allow this value to be adjusted as a parameter. By reducing search step complexity through our use of sampling, search capacity is enhanced.

Algorithm 1: LTL Specification Search

Input: Parent set of traces π_n
Parameters: Iteration limit max_iter, Information gain threshold τ, Sample proportion p
Output: LTL specification φ_{best}

1: $\varphi_{best} \leftarrow None$
2: **for** $i = 0...max\_iter$ **do**
3:      $\pi_{sample} \leftarrow$ random sample set of size $p|\pi_n|$ from π_n
4:      $\pi_+, \pi_- \leftarrow$ random balanced split of π_{sample}
5:      **for** values of φ resulting from BayesLTL(π_+, π_-) **do**
6:          **if** $InfoGain(\varphi, \pi_n) \geq \tau$ **then**
7:              **return** φ
8:          **else if** $!\varphi_{best}$ **or** $InfoGain(\varphi, \pi_n) > InfoGain(\varphi_{best}, \pi_n)$ **then**
9:              $\varphi_{best} \leftarrow \varphi$
10:         **end if**
11:     **end for**
12: **end for**
13: **return** φ_{best}

We iterate search according to a Monte Carlo approach, which is procedurally shown in Algorithm 1. Our proposed approach begins by sampling a subset of traces from the parent set, as previously described. We then randomly split this subset into two equally sized new subsets, labelling one positive and the other negative. Applying BayesLTL (Kim et al. 2019) to these positive and negatively labelled sets of traces, we arrive at a list of contrastive explanations, which each individually attempt to best describe variation between the two groups. Using this list of discovered LTL specifications, we score each formula on the information gain it offers to the parent set of traces. If a given specification is found to provide information gain that is either perfect or is beyond a parameterized threshold, the specification is accepted and the

Figure 2: Example of a Generated Tree from Blocksworld Domain

An example tree generated from the blocksworld evaluation domain with a vocabulary size of 10. While the depth of this example tree continues beyond the levels that are presented within this visual representation, we display only four levels for compactness. The terminal nodes of this tree represent clusters of traces, and the LTL contrastive explanations along the tree's branches can simply be read off of the tree in conjunction to differentiate each node via its path to the root node.

splitting process is ceased for that node. Alternatively, the specification offering the highest information gain is compared with the previous best, and the better specification is retained. This entire process is repeated until a parameter representing the maximum permitted quantity of iterations is reached, and the best LTL formula is accepted. This information gain-maximizing formula is then stored in the parent node and used as a splitting mechanism to create child nodes.

Evaluations and Results

Evaluation Dataset Derivation

To establish an evaluation dataset of discrete time-series data, we embrace planning as an environment for testing. Six benchmark domains were selected from International Planning Competition (Fox and Long 2003), and used in conjunction with a diversity-bounded diverse planner (Katz and Sohrabi 2020). Representing assortment in testing, these selected domains include Blocksworld, Gripper, Rovers, Satellite, TPP, and ZenoTravel. Additionally, within each domain, three vocabulary sizes $|V|$ in $\{10, 15, 20\}$ were used. Given these 18 unique configurations, 100 diverse plans were generated for each configuration using a stability similarity threshold (Fox et al. 2006; Coman and Munoz-Avila 2011) of 0.25, enforcing every possible pair of two plans to have a maximum of 25% identical actions. By following this process, we arrived at 18 unique datasets to probe various aspects of our methodology in testing.

Similar to Kim et al.'s evaluation of BayesLTL (Kim et al. 2019), we also explored injection of LTL ground truth into problem/domain PDDL files via LtlFond2Fond (Camacho et al. 2017). However, this additional step was deemed unnecessary for our purposes, since preliminary results demonstrated an abundance of naturally balancing partitions existing between diverse plans generated using stability-similarity. Unlike BayesLTL where two sets of traces are contrasted, our approach contrasts multiple sets of traces, resulting in a greater quantity of available solutions. Since several accurate ground truths exist within our generated diverse plans, the expectation for any specific predetermined solution to be found is typically unreasonable.

Domain (100 Traces)	$\|V\|$	Average Depth (20 Trees)		Average Info Gain (20 Trees), ($\|\pi\| \geq 10$)	
		Med	Mean	Med	Mean
Blocks	10	6.299	6.308	0.505	0.501
	15	6.372	6.404	0.388	0.380
	20	6.219	6.202	0.128	0.135
Gripper	10	5.789	5.792	0.860	0.867
	15	5.995	6.009	0.729	0.726
	20	6.382	6.381	0.622	0.618
Rovers	10	5.836	5.821	0.788	0.783
	15	5.942	5.944	0.873	0.876
	20	5.783	5.776	0.879	0.880
Satellite	10	5.789	5.788	0.911	0.921
	15	5.810	5.811	0.844	0.847
	20	5.783	5.797	0.879	0.873
TPP	10	5.779	5.784	0.897	0.898
	15	5.789	5.787	0.891	0.893
	20	5.799	5.796	0.888	0.893
Zeno-Travel	10	5.779	5.781	0.898	0.899
	15	5.784	5.784	0.897	0.895
	20	5.779	5.779	0.899	0.895

Table 2: Performance results of 20 test cases for each of the listed domains and vocabulary sizes $|V|$. Trees were generated using a sample proportion of 40%, an information gain threshold of 80%, and a maximum of 10 iterations, isolating all unique traces as leaves. Each row reports the median and mean of average node depth and average information gain from the 20 samples of each respective domain/vocabulary configuration. For reference, a perfect tree initialized with 100 traces and possessing maximal information gain at every node, would have an average node depth of 5.759.

General Effectiveness of Tree Generation

Since our approach merely represents an introduction to the solution of this problem, functional testing is beyond the scope of this paper. We therefore leave functional testing to future work and instead focus our evaluation on the inner mechanics and properties of our proposed solution.

To evaluate the effectiveness and applicability of our delineation process, we analyze our approach's adaptability and scalability potential. To assess these attributes, we generated 20 trees for each domain/vocabulary size configuration in our evaluation dataset. An example of one of these trees can be viewed in Figure 2, where we display four lev-

els of a contrastive explanation tree derived from the blocks domain with a vocabulary size of 10. Post-generation, we then judged the strength of the discovered trees according to balance and information gain metrics. Balance, which represents the efficiency of our process to organize and differentiate traces, was calculated using average node depth. Since high quality specifications minimize the quantity of splits required to isolate traces, smaller values of average depth are desirable, as they are indicative of higher quality specifications. When analyzing average depth of trees, it is important to note they can both only be evaluated in contrast to trees with identical quantities of root traces, as is the case within our presented experiment. Alternatively, the balance can also be evaluated as a ratio of $\log_2(n)$, where n represents the total quantity of nodes in a tree, releasing the measurement from its context dependency, but the resulting value is less intuitive to comprehend. We calculated information gain according to Formula 1 for all nodes containing at least 10 traces in each tree, then averaged these values for each individual tree, presenting the median tree. The minimum node size of 10 traces was selected as a filter for our analysis of information gain as averages should not be overshadowed and overstated by including easier splits of less relevant nodes. By generating and evaluating several trees of diverse configurations, the resilience of our algorithm to identify high quality specifications was demonstrated.

Table 2 summarizes the characteristics of the resulting trees generated to evaluate the efficacy of our approach. From the recorded measurements, it is clear that our algorithm is capable of discovering and differentiating clusters existing within a variety of unique domains associated with diverse vocabulary sizes. In analyzing the median information gain of our evaluation trees, we observe little impediment associated with higher-complexity problems. This is also shown to translate successfully to median average depth, where measures appear similarly small across all domains and vocabulary sizes. These observations effectively demonstrate our algorithm's ability to cluster and delineate traces in an efficient manner.

Analysis of Discovered Specifications

It has been shown that our algorithm is capable of identifying high-information gain LTL specifications to establish minimal-depth trees; however a more extensive analysis of those specifications is necessary to rule out unintended behaviour. For instance, it would likely be problematic if only large specifications were identified because this would be indicative of overfitting, mitigating the usefulness of discovered formulae. To investigate the quality tendency of discovered specifications, we evaluate the size of the specifications within our sample trees; we measure size according to the number of unique subformulas within a given expression, as defined by Gaglione et al..

In Table 3 we present the resulting size measurements of specifications within our 20 evaluation trees for each domain/vocabulary configuration. These values positively demonstrate our algorithm's ability to identify low-complexity formulas corresponding with a robust fit for each configuration within our test data. To provide a clear under-

Domain (100 Traces)	$|V|$	Average LTL Size (20 Trees), $(|\pi| \geq 10)$			
		Min	Med	Max	σ
Blocks	10	6.905	7.841	8.857	0.626
	15	4.381	5.390	6.947	0.676
	20	3.600	4.667	5.733	0.562
Gripper	10	5.357	6.942	8.357	0.765
	15	6.933	8.036	9.063	0.742
	20	7.125	8.092	10.222	0.744
Rovers	10	5.824	7.129	10.467	1.081
	15	7.071	8.171	10.467	1.083
	20	5.400	8.157	10.800	1.231
Satellite	10	6.266	7.633	10.231	1.104
	15	4.643	6.829	8.692	0.712
	20	5.214	6.379	8.067	1.009
TPP	10	6.423	8.100	10.307	1.104
	15	4.643	7.031	11.214	1.601
	20	5.214	6.893	9.286	0.935
Zeno-Travel	10	5.857	9.033	11.400	1.407
	15	6.308	8.136	10.357	1.180
	20	4.923	7.833	9.786	1.085

Table 3: Analysis of LTL specification size $|\varphi|$ distribution within the test cases established in Table 2. LTL size is measured according to the quantity of unique subformulas, as defined by Gaglione et al.. Each row reports the minimum, median, maximum, and standard deviation of average $|\varphi|$ within the 20 sample trees of each respective domain/vocabulary configuration, where robust fit is apparent.

standing of the LTL specifications our process discovers, we present example formulas in Table 4 along with their respective sizes. Another insightful finding in these measurements is the tendency of LTL size to negatively correlate with vocabulary size in most domains. This trend is likely due to the idea that higher complexity domains possess greater quantities of natural ground truth to be found, which eases discovery.

Node Size Versus Splitting Time

Since our Monte Carlo node-splitting technique with randomized balanced subsets of traces represents the primary sub-process behind our delineation method, the execution time performance of this step, with respect to the quantity of analyzed traces, was of interest. We expected the execution time required to split a single node of traces to increase with the quantity of input traces; however, the rate of growth defining this relationship was unknown. To approximate this rate of growth, we conducted 10 splits for each size $|\varphi|$ in $\{10n : n \in Z^+, n < 11\}$ of randomly sampled subsets of traces, measuring execution time of each split. By plotting these data points for each domain, the relationship between node size and splitting time can be visualized and understood.

In Figure 3, we observe a near linear relationship between

Domain	LTL Specification (φ)	Size ($|\varphi|$)
Blocks	atmostonce: ((clear object i)), ((on object a object d)), ((on object j object b))	19
Gripper	eventual: ((carry object ball16 object right)), ((carry object ball19 object left)), ((carry object ball21 object right)), ((carry object ball4 object left))	9
Rovers	atmostonce: ((calibrated camera camera2 rover rover1)), ((calibrated camera camera5 rover rover3))	13
Satellite	sometime_before: ((have_image object star15 object spectrograph1), (pointing object satellite4 object phenomenon8))	5
TPP	eventual: ((loaded goods goods5 truck truck2 level level1))	2
Zeno-Travel	eventual: ((at object person3 object city4)), ((fuel-level object plane1 object fl1)), ((in object person8 object plane2))	7

Table 4: Examples of LTL specifications discovered within trees of our six evaluation domains, along with their respective measurements of size. See Table 1 for descriptions of templates. We measure LTL size according to the number of unique subformulas within a given expression, as defined by Gaglione et al..

Figure 3: The average execution time of splitting a node π of randomly sampled traces with respect to the quantity of traces $|\varphi|$ over 10 splits for each value of $|\varphi|$ in $\{10n : n \in Z^+, n < 11\}$. Since scales of execution time differ relative to each domain, normalization is conducted via $\frac{x_i - min(x)}{max(x) - min(x)}$ for plotting purposes.

node size and splitting time within all six of the explored domains. This relationship emphasizes the importance of our sampling step, since the time complexity of a single split appears to grow continuously large.

Probability Distribution of Information Gain with Respect to Sample Size

Given a randomly sampled subset of traces of a larger set, it is of interest to derive the probability distribution of information gain. Intuitively, larger sample sizes should have stronger representative abilities; however since runtime is dependent upon the size of the input set, accepting lesser probabilities may be of better utility. We estimated this distribution by running 100 splits of sample proportions in $\{0.02, 0.05, 0.1, 0.4, 0.7, 1\}$ for each domain and analyzing

the resulting information gain.

As seen in Figure 4, sampling was shown to be highly effective and proved capable of representing the population distributions. Within all six of the evaluated domains and across each of the tested sample proportions, significant density was observed in the upper range of the information gain spectrum. As would be expected, higher sample proportions tended to provide greater representative ability; however, the size of this effect was interestingly small-scale. Within some domains, such as Satellite and TPP, we observe sampling effectiveness with sampling sizes as small as 2%; within all domains, however, we observe effectiveness with samples as small as 10%. This tiny performance cost of using small sample sizes represents a strong opportunity for runtime savings within complex domains.

Specification Exploration Time Utility

When searching for an LTL specification to split a given set of traces, the quantity of exploration iterations permitted will impact the information gain of the resulting split. Since iterations represent opportunities for better specifications to be found, the quantity of iterations should negatively correlate with the resulting information gain. The rate at which information gain is improved per iteration is of interest because iterations come at a cost of execution time. To investigate this tradeoff, we conducted 20 splits for each iteration limit value in $\{5i : i \in Z^+, i < 11\}$ for each evaluation domain, recording execution times and discovered LTL. By analyzing the average information gain and average execution time of these splits with respect to the iteration limit used for each domain, the curve of this relationship can be approximated.

When increasing specification search iterations, we observe performance improvements through measurements of information gain across all six evaluation domains. However, with marginal increases, the size of observed information gain improvement tends to decrease. This trend of diminishing marginal benefit of search iterations persists across all experimented values of permitted iterations, while

Figure 4: Kernel density estimation (KDE) plots of information gain with respect to sample proportion used when approximating split. Each domain subplot shows the KDE's of 100 single-split iterations for each sample proportion in {0.02, 0.05, 0.1, 0.4, 0.7, 1}.

Figure 5: The average information gain and average execution time with respect to permitted maximum quantity of iterations over 20 sample splits for each test value and evaluation domain. Splits were conducted using a sample proportion of 10% with an information gain threshold of 100% to ensure maximal performance potential.

search time appears to increase near-linearly. This means that although the cost of search time increases at a constant rate, the marginal value received by incurring this cost decreases with higher values of the parameter. This curve of diminishing marginal value can be seen in Figure 5. This trend can likely be attributed to the idea that specifications satisfying the information gain threshold do not always exist, or, for a variety of reasons, may be less conducive to being found. Since our algorithm's precondition for early stopping is achieving a minimum score of information gain, if this milestone is impossible to reach, all iterations will still be conducted, even if a globally optimal specification has already been found.

Future Work

With complexity mitigation in mind, we investigated a process whereby splitting criteria could be intelligently identified via the analysis of previous splitting attempts. This experimental intelligent splitting algorithm can be viewed procedurally in Algorithm 2. In this revised procedure, when a discovered specification fails to meet the information gain threshold, we do not resample π_+ and π_- from π_{parent}. Instead, we reestablish π_+ and π_- as the subsets of traces that satisfy and dissatisfy φ, respectfully. We then rebalance π_+

Algorithm 2: Experimental Intelligent Splitting Algorithm

Input: Parent set of traces π_n
Parameters: Iteration limit max_iter, Information gain threshold τ, Sample proportion p
Output: LTL specification φ_{best}

1: $\varphi_{best} \leftarrow None$
2: $\pi_{sample} \leftarrow$ random sample set of size $p|\pi_n|$ from π_n
3: $\pi_+, \pi_- \leftarrow$ random balanced split of π_{sample}
4: **for** $(i = 0...max\_iter)$ **do**
5:    $\varphi \leftarrow$ LTL that maximizes $InfoGain(\varphi, \pi_n)$ from BayesLTL(π_+, π_-)
6:    **if** $InfoGain_{\varphi, \pi_n} \geq \tau$ **then**
7:      **return** φ
8:    **else if** $!\varphi_{best}$ **or** $InfoGain(\varphi, \pi_n) > InfoGain(\varphi_{best}, \pi_n)$ **then**
9:      $\varphi_{best} \leftarrow \varphi$
10: **end if**
11: **while** $(||\pi_+| - |\pi_-|| > 1)$ **do**
12:    **if** $|\pi_+| > |\pi_-|$ **then**
13:      Randomly select trace from π_+ and append to π_-
14:    **else**
15:      Randomly select trace from π_- and append to π_+
16:    **end if**
17:   **end while**
18: **end for**
19: **return** φ_{best}

and π_- by randomly drawing traces from the majority set and inserting them into the minority set. The hope of this revised strategy was that the sizes of these subsets would converge over multiple iterations, leading to the desired information gain specified by the threshold.

However, when testing this revised process to split nodes of traces, we observed identical formulas being discovered repeatedly until the maximum iterations were reached. We observed this same pattern across all six of our evaluation domains, indicating a lack of success for this specific procedure. With no variety in the formulas being discovered, our revised algorithm failed to learn, meaning the resulting information gain was equal to that of the first identified formula. While this observed failure to learn rejects the proposed method as a viable alternative, it is possible that the approach could be adapted and improved to make learning feasible. From our experiment, we can deduce that in order for an intelligent-splitting algorithm to be successful, it is likely that greater freedom from the initial random allocation of traces is necessary. This could perhaps take the form of randomized resets or other statistical methods to introduce variance; we identify this side of our research to be the area with the greatest potential for future work.

Related Work

As an alternative to traditional planning research, which seeks to investigate the process of identifying optimal plans from problems, the area of plan explanation seeks to iden-

tify and describe characteristics of problems from plans. Through the analysis of observed behaviour, the goal of plan explanation is to use abductive-reasoning to infer reasoning behind observed actions to better understand why certain events occur. To rationalize observed actions, plan explanation research focuses on automatically learning temporal properties that allow system behaviour to be modelled, understood, and predicted.

Plan explanations have been relevant in goal recognition settings, where they have been used as a means to infer latent goal states from incomplete observations (Ramírez and Geffner 2010; Sohrabi, Riabov, and Udrea 2016), and explicable planning research has embraced plan explanations to synthesize plans that are self-explanatory for a human's mental model (Zhang et al. 2017). Research focused on system diagnosis has also incorporated plan explanations to explain failures (Göbelbecker et al. 2010; McIlraith 1999). While each of these works focus on identifying accurate specifications to explain plans, they focus on describing a single set of traces. Our approach, on the other hand, is designed to contrast multiple sets of traces and characterize behavioural differences.

Prior works on contrastive explanations have elevated the plan explanation problem to describe temporal differences between two sets of plan traces. Approaches to contrastive explanations have adopted SAT-based methods (Neider and Gavran 2018; Camacho and McIlraith 2021; Gaglione et al. 2021), in addition to Bayesian inference, as in the BayesLTL framework (Kim et al. 2019). Our approach embraces the Bayesian inference strategy, using BayesLTL as a subprocess. However, instead of limiting the assertion of contrast to two sets of plan traces, we evaluate contrast amongst k-sets. Our approach also clusters input traces to establish suitable contrastive sets automatically, as opposed to prior works, which require contrastive sets to be predefined by the user.

Leveraging decision tree learning algorithms to infer temporal logic formulas is an area that has also been previously explored (Bombara et al. 2016; Brunello, Sciavicco, and Stan 2019; Gaglione et al. 2021). As the most relevant approach in this space, Gaglione et al. use decision tree learning in their Algorithm 2 to discover contrastive LTL specifications between two sets of plan traces. Similarly, our approach adopts a decision tree learning method for contrastive explanations; however, our tree's structure is also designed to hold sets of traces in nodes, rather than only representing formulas. Our use of decision tree learning is focused on the task of cluster discovery, conducted simultaneously with formula construction.

Concluding Remarks

The challenge of inferring temporal logic specifications to cluster and delineate plan traces is relevant to a wide array of planning applications. In this work, we reimagined the trace clustering and delineation challenge by proposing a novel tree generation technique which allows k clusters to be discovered and described. By embracing a Monte Carlo node-splitting approach, our algorithm seeks balance to contrastively divide any given set of plan traces into two sets

with an accompanying temporal logic specification satisfying one of the sets. Recursing this procedure, we demonstrate the effectiveness of our approach to cluster and delineate plan traces from our evaluation dataset of benchmark domains, allowing temporal logic specifications to evoke insight at each level of the resulting tree.

References

Bombara, G.; Vasile, C.-I.; Penedo, F.; Yasuoka, H.; and Belta, C. 2016. A Decision Tree Approach to Data Classification using Signal Temporal Logic. In *Proceedings of the 19th International Conference on Hybrid Systems: Computation and Control*, 1–10.

Brunello, A.; Sciavicco, G.; and Stan, E. 2019. *Interval Temporal Logic Decision Tree Learning*, 778–793. Logics in Artificial Intelligence. ISBN 978-3-030-19569-4.

Camacho, A.; and McIlraith, S. A. 2021. Learning Interpretable Models Expressed in Linear Temporal Logic. *Proceedings of the International Conference on Automated Planning and Scheduling*, 29(1): 621–630.

Camacho, A.; Triantafillou, E.; Muise, C.; Baier, J. A.; and McIlraith, S. A. 2017. Non-Deterministic Planning with Temporally Extended Goals: LTL over Finite and Infinite Traces. In *Proceedings of the Thirty-First AAAI Conference on Artificial Intelligence*, AAAI'17, 3716–3724. AAAI Press.

Coman, A.; and Munoz-Avila, H. 2011. Generating Diverse Plans Using Quantitative and Qualitative Plan Distance Metrics. In *AAAI Conference on Artificial Intelligence*, 946–951.

Fox, M.; Gerevini, A.; Long, D.; and Serina, I. 2006. Plan Stability: Replanning versus Plan Repair. In *Proceedings of the Sixteenth International Conference on International Conference on Automated Planning and Scheduling*, ICAPS'06, 212–221. AAAI Press. ISBN 9781577352709.

Fox, M.; and Long, D. 2003. The 3rd International Planning Competition: Results and Analysis. *ArXiv*, abs/1106.5998.

Gaglione, J.; Neider, D.; Roy, R.; Topcu, U.; and Xu, Z. 2021. Learning Linear Temporal Properties from Noisy Data: A MaxSAT-Based Approach. In *ATVA*, volume 12971 of *Lecture Notes in Computer Science*, 74–90. Springer.

Grosse, D.; and Drechsler, R. 2003. Formal verification of LTL formulas for SystemC designs. In *Proceedings of the 2003 International Symposium on Circuits and Systems, 2003. ISCAS '03.*, volume 5, V–V.

Göbelbecker, M.; Keller, T.; Eyerich, P.; Brenner, M.; and Nebel, B. 2010. Coming up With Good Excuses: What to do When no Plan Can be Found. In *Proceedings of the 20th International Conference on Automated Planning and Scheduling, ICAPS 2010*, 81–88.

Kasenberg, D.; and Scheutz, M. 2017. Interpretable apprenticeship learning with temporal logic specifications. *2017 IEEE 56th Annual Conference on Decision and Control (CDC)*, 4914–4921.

Katz, M.; and Sohrabi, S. 2020. Reshaping Diverse Planning. *Proceedings of the AAAI Conference on Artificial Intelligence*, 34(06): 9892–9899.

Kim, J.; Muise, C.; Shah, A.; Agarwal, S.; and Shah, J. 2019. Bayesian Inference of Linear Temporal Logic Specifications for Contrastive Explanations. In *Proceedings of the Twenty-Eighth International Joint Conference on Artificial Intelligence, IJCAI-19*, 5591–5598. International Joint Conferences on Artificial Intelligence Organization.

Kupferman, O. 2006. Sanity Checks in Formal Verification. In Baier, C.; and Hermanns, H., eds., *CONCUR 2006 – Concurrency Theory*, 37–51. Berlin, Heidelberg: Springer Berlin Heidelberg. ISBN 978-3-540-37377-3.

Latvala, T. 2005. *Automata-theoretic and bounded model checking for linear temporal logic*. Ph.D. thesis, Väitöskirja :, Espoo. Tiivistelmä ja 5 erip.

Lemieux, C.; Park, D.; and Beschastnikh, I. 2015. General LTL Specification Mining (T). In *2015 30th IEEE/ACM International Conference on Automated Software Engineering (ASE)*, 81–92.

McIlraith, S. 1999. Explanatory Diagnosis: Conjecturing Actions to Explain Observations. In Levesque, H.; and Pirri, F., eds., *Logical Foundations for Cognitive Agents: Papers in Honour of Ray Reiter*, 155–172. Springer-Verlag.

Neider, D.; and Gavran, I. 2018. Learning Linear Temporal Properties. *CoRR*, abs/1806.03953.

Pnueli, A. 1977. The temporal logic of programs. In *18th Annual Symposium on Foundations of Computer Science (sfcs 1977)*, 46–57.

Ramírez, M.; and Geffner, H. 2010. Probabilistic Plan Recognition Using Off-the-Shelf Classical Planners. In *Proceedings of the Twenty-Fourth AAAI Conference on Artificial Intelligence*, AAAI'10, 1121–1126. AAAI Press.

Rozier, K. Y. 2011. Survey: Linear Temporal Logic Symbolic Model Checking. *Comput. Sci. Rev.*, 5(2): 163–203.

Sohrabi, S.; Riabov, A. V.; and Udrea, O. 2016. Plan Recognition as Planning Revisited. In *Proceedings of the Twenty-Fifth International Joint Conference on Artificial Intelligence*, IJCAI'16, 3258–3264. AAAI Press. ISBN 9781577357704.

Vardi, M. Y. 1996. An Automata-Theoretic Approach to Linear Temporal Logic. In *Proceedings of the VIII Banff Higher Order Workshop Conference on Logics for Concurrency: Structure versus Automata: Structure versus Automata*, 238–266. Berlin, Heidelberg: Springer-Verlag. ISBN 3540609156.

Yang, J.; Evans, D.; Bhardwaj, D.; Bhat, T.; and Das, M. 2006. Perracotta: Mining Temporal API Rules from Imperfect Traces. In *Proceedings of the 28th International Conference on Software Engineering*, ICSE '06, 282–291. New York, NY, USA: Association for Computing Machinery. ISBN 1595933751.

Zhang, Y.; Sreedharan, S.; Kulkarni, A.; Chakraborti, T.; Zhuo, H.; and Kambhampati, S. 2017. Plan explicability and predictability for robot task planning. *2017 IEEE International Conference on Robotics and Automation (ICRA)*, 1313–1320.