# Domain adaptation using optimal transport for invariant learning using histopathology datasets

## Abstract

Histopathology is critical for the diagnosis of many diseases, including cancer. These protocols typically require pathologists to manually evaluate slides under a microscope, which is time-consuming and subjective, leading to interest in machine learning to automate analysis. However, computational techniques are limited by batch effects, where technical factors like differences in preparation protocol or scanners can alter the appearance of slides, causing models trained on one institution or patient to fail when generalizing to others. Here, we propose a domain adaptation method that improves the generalization of histopathological models to data from unseen institutions, without the need for labels or retraining in these new settings. Our approach introduces an optimal transport (OT) loss, that extends adversarial methods that penalize models if images from different institutions can be distinguished in their representation space. Unlike previous methods, which operate on single samples, our loss accounts for distributional differences between batches of images. We show that on the Camelyon17 dataset, while both methods can adapt to global differences in color distribution, only our OT loss can reliably classify a cancer phenotype unseen during training. Together, our results suggest that OT improves generalization on rare but critical phenotypes that may only make up a small fraction of the total tiles and variation in a slide.

**Keywords:** Domain adaptation, Batch effect, Optimal transport, Digital pathology, Deep learning.

## 1. Introduction

Histopathology is a crucial tool in the diagnosis of various diseases, including cancer. In this process, a tissue sample is taken from a patient, thinly sliced, fixed to a microscope slide, and stained to visualize cells and tissue. By examining samples under a microscope, pathologists diagnose disease by identifying changes in cells and tissue (such as abnormal mitosis in cancer)(Gurcan et al., 2009). However, manual qualitative evaluation is time-consuming and subjective, leading to the development of various machine learning methods, including image segmentation and inference of molecular features and therapy response (Echle et al., 2021; Van der Laak et al., 2021).

Although initial models have shown promise, few algorithms have demonstrated robust performance in widespread clinical implementation. One reason for this is that pathology machine learning models are challenged by batch effects (Howard et al., 2021). Different histopathology images may exhibit subtle differences stemming from variation in slide preparation, staining protocol, and data processing. While these effects are often systematic between institutions (e.g. institutions may use different scanners technologies to digitize

their images), even two slides for the same patient prepared at the same institution can still be impacted by slight variations in preparation protocol. While human pathologists can largely ignore these differences, machine learning models are severely impacted, so accuracy degrades as models are deployed in new hospitals (Shaban et al., 2019; Lafarge et al., 2019).

Making histopathology models robust to batch effects is an active area of research, with several general strategies proposed. In this manuscript, we focus on domain invariant representation learning. Compared to other strategies that may require targeted domain knowledge to design augmentations (Faryna et al., 2021; Pérez-Bueno et al., 2022; Ataky et al., 2020) or access to test images for alignment or retraining (Lafarge et al., 2019; Abbet et al., 2021; Saenko et al., 2010), domain invariant representation learning aims to learn a model that is intrinsically robust to batch effects, by ensuring only biological variation (and not batch effects) is present in the representation learned by a model. The simplest way to achieve this premise is through use of an adversary during training (Ganin et al., 2016), by penalizing a model if hospital institution can be classified from the model's representation of images (Lafarge et al., 2017, 2019), under the premise that that data across institutions should not be substantially different in biological content, and differences stem mostly from technical batch effects.

Most previous research in histopathology that utilizes this strategy relies on a loss function that penalizes the ability to classify institutions from individual images. While this approach is technically simple, these losses are prone to failure as the models focus on more frequent examples in the training dataset. We believe that these failures may have practical implications in histopathology, as differences in institutions or patients often appear locally in only a fraction of tiles from a whole slide image. For example, differences in fixation may cause changes in some tissues and not others (Chatterjee, 2014), and cancer tissue in patients may exhibit different phenotypes, even as their non-tumor tissue remains more comparable.

Inspired by theoretical advances suggesting that these failures can be mitigated by penalizing on batches of images instead, we propose a new optimal transport (OT) based loss. Our OT-based loss allows us to compare if the distributions of two sets of images are different, which we use to quantify and penalize representational differences in images between institutions. Consistent with our hypothesis that OT leads to more robust learning of batch effects, we demonstrate that our OT loss not only improves in performance on the Camelyon17 dataset over standard sample-based adversaries, but the improvement in performance is because our OT method correctly classifies a cancer phenotype in the test dataset unseen in the training dataset.

## 2. Background

### 2.1. Optimal Transport

Optimal Transport is a mathematical framework to compare, align, and transform probability distributions. It was originally formulated by Gaspard Monge (Monge, 1781) who was interested in finding optimal matchings between source and target locations across which materials or goods had to be transported. Recently a more general formulation has gained popularity in various fields including computer vision (Arjovsky et al., 2017), natural language processing (Alvarez-Melis and Jaakkola, 2018), and economics (Galichon, 2018).

In this work, we consider a classification setting where we are given labeled data $\{(x_i^s, y_i^s)\}$ from a source domain $(S)$, but only unlabeled data $\{x_j^t\}$ from the target domain $(T)$ is available. Here we assume the features of both datasets have the same dimensionality, e.g., $x_i^s, x_j^t \in \mathbb{R}^d$. The goal is then to leverage the data from the source domain to train a model that will ultimately be used in the target domain. In the machine learning literature, this is known as the *unsupervised* domain adaptation problem. Optimal transport can be used to define a distance between the source and target samples by treating them as discrete distributions supported on finitely many points. Formally, we define the distributions $\mu_s = \sum_{i=1}^{n_s} p_i^s \delta_{x_i^s}$ and $\mu_t = \sum_{i=1}^{n_t} p_i^t \delta_{x_i^t}$ where $\delta_{x_i}$ is the Dirac at $x_i$, and $p^s$ and $p^t$ are probability vectors associated with the samples. Given a cost function $c(\cdot, \cdot) : \mathbb{R}^d \times \mathbb{R}^d \to \mathbb{R}^+$, the Kantorovich (Kantorovitch, 1958) formulation of the discrete OT problem consists of finding a coupling matrix $\Gamma \in \mathbb{R}^{n_s \times n_t}$ minimizing:

$$\mathrm{OT}(\mu_s, \mu_t) = \min_{\Gamma \in \Pi(\mu_s, \mu_t)} \langle \Gamma, C \rangle, \tag{1}$$

where $\langle .,. \rangle$ is the inner product, $C_{ij} = c(x_i^s, x_j^t)$ is the cost associated with moving probability mass from $x_i^s$ to $x_j^t$ (typically taken to be the euclidean distance between these two points), and $\Pi$ is the probabilistic coupling between the distribution of $S$ and $T$ which is a set of doubly stochastic matrices defined as below:

$$\Pi(\mu_s, \mu_t) = \{\Gamma \in \mathbb{R}_+^{n_s \times n_t} \mid \Gamma 1 = \mu_s, \; \Gamma^T 1 = \mu_t\} \tag{2}$$

As Equation 1 is linear programming problem, the runtime complexity of solving it scales cubically with the number of samples (Peyré et al., 2019), which is typically prohibitive in applications. Moreover, in the presence of outliers, this formulation may lead to incorrect transportation of points and demonstrate some irregularities. To overcome the aforementioned challenges, (Cuturi, 2013) introduced a regularized version of Equation 1 by adding an entropy term as below:

$$\mathrm{OT}(\mu_s, \mu_t) = \min_{\Gamma \in \Pi(\mu_s, \mu_t)} \langle \Gamma, C \rangle + \epsilon H(\Gamma) \tag{3}$$

Where $H(\Gamma) = -\sum_{i,j} \Gamma(i,j) \log \Gamma(i,j)$ computes the entropy of $\Gamma$. Equation 3 can be solved using the Sinkhorn- Knopp algorithm(Cuturi, 2013).

## 2.2. Optimal transport to regularize model training

We consider a simple tumor/normal classification model $(C)$ for histopathology data, and seek a way to generalize our model without knowledge of the target data distribution. We first use a model $(\phi)$ to map the raw histology images to a feature space, then a fully connected network $(C)$ is used to map the feature space to the classifications. We use our unlabeled validation data to define a optimal transport distance between the training and validation data at the feature space level. This is minimized simultaneously with the training of the classification model, to limit over fitting and promote invariant learning. At test time, we deploy only the classification model, without any additional domain adaptation steps.

Our overall loss function is as below:

$$L_{total} = L_{\text{CE}} + \alpha * L_{\text{OT}}, \tag{4}$$

where $\alpha$ is a hyperparameter controlling the strength of cross-domain regularization, and will be further discussed in the results section. $L_{CE}$ is a cross-entropy loss, i.e.:

$$L_{\text{CE}} = -\sum(\log(C(\phi(X_S; \theta_\phi); \theta_C)) \tag{5}$$

$X_S$, $\theta_\phi$, and $\theta_C$ represent images from source domain, the weights of $\phi$, and the weights of $C$ respectively. $L_{OT}$ is defined as:

$$L_{\text{OT}} = \sum(\text{OT}(\phi(X_S, \theta_S), \phi(X_T, \theta_S))) \tag{6}$$

$X_T$ represents data from the target domain (validation).

Figure 1: **Method overview**. We integrated the OT loss during model training. The total objective function is the combination of CE loss and OT loss, regularized by the tuning parameter $\alpha$.

## 2.3. WILDS dataset

In this study, we used the Camelyon17-WILDS benchmark dataset, designed to support method development for addressing distribution shift (Koh et al., 2021). Camelyon17-WILDS is a tiled and sampled version of the Camelyon-17 dataset, which contains Hematoxylin and Eosin (H&E) stained images of breast lymph node resections from 5 institutions (Litjens et al., 2018). A representative example is shown in Figure 2. The Camelyon17-WILDS dataset includes sparsely sampled 96x96 patches from a whole-slide image of a lymph node; each patch has been annotated by experts as tumor or non-tumor. Sample patches are 96x96 pixels, and the entire dataset has previously been partitioned into a training, validation and test set; there are a total of 302,436 patches from 30 WSI and 3 institutions in the training set, 34,904 patches from 10 WSI and 1 institution in the validation set, and 85,054 patches from 10 WSI and 1 institution in the test set.

Figure 2: **Representative examples of image patches within the Camelyon17-WILDS dataset illustrating distribution shift.** A. Representative example of patch distribution across a WSI, showing that patches are sampled randomly throughout the tissue sample. B. Representative sample patches from each institution used in the training (1, 2, 3), validation (4) and test (5) sets, showing visual diversity in the images by institution.

## 2.4. Computational Implementation

The full code for our implementation can be found here: https://github.com/kiakh93/OT-regularized-UDA

For all experiments, we use ResNet-50 architecture initialized randomly. In addition, we substitute Batch Normalization layers with Instance normalization layers. We used a learning rate of $10^{-3}$, $L_2$ regularization with $10^{-3}$, and SGD optimizer with momentum of 0.9. All models were trained for 5 epochs with early stopping using 96 x 96 patches with batch size of 128. We report the results that are aggregated over 4 experiments with random initialization.

## 3. Methodology and Results

In principle, our OT loss can be used to adapt models to unseen datasets at test time, since it does not rely on labels for the test dataset (only the training dataset). In practice, this would require re-training a model for each new institution and potentially each new patient, which is computationally expensive and time-consuming. To overcome this limitation, we instead decided to test if our OT loss would lead to a model capable of generalizing on unseen test domains *without retraining*. We demonstrate on the Camelyon17-WILDS dataset (Figure 2), which seeks to classify tissue crops as normal or tumor under domain shift (i.e. both the validation and test dataset are unseen institutions). In our set-up (summarized in Figure 1, we minimize the OT loss between the training and validation dataset during training, but then we test generalization on the test data without re-training, under the hypothesis that learning to minimize between two domains (the training and validation dataset) would lead to invariant features that would generalize to future, unseen domains (the test dataset).

We trained a ResNet50 model (He et al., 2016) to classify images in the training dataset using a cross entropy loss. During training, we also encoded validation images, and calculated the OT distance between features at the final layer of the ResNet50 encoder immedi-

Table 1: **Model performance using various $\alpha$, representing the OT contribution to the overall loss function**. We report standard deviation in the parenthesis

| $\alpha$ | 0.00001 | 0.0001 | 0.001 | 0.01 | 0.1 | 1 |
|---|---|---|---|---|---|---|
| **Accuracy of validation** | 0.882 (0.011) | 0.882 (0.002) | 0.871 (0.004) | 0.882 (0.007) | **0.891 (0.005)** | 0.712 (0.165) |
| **Accuracy of test** | 0.799 (0.029) | **0.857 (0.011)** | 0.811 (0.019) | 0.826 (0.012) | 0.850 (0.019) | 0.733 (0.150) |

Table 2: **Model performance compared to DANN method**. We report standard deviation in the parenthesis

| | OT-regularized | DANN |
|---|---|---|
| **Accuracy of validation** | 0.891 (0.005) | 0.873 (0.014) |
| **Accuracy of test** | 0.850 (0.019) | 0.796 (0.052) |

ately before the classification layer between validation batches and training batches. The overall loss of the classification model is a combination of the cross entropy loss and the OT loss, regularized by the tuning parameter $\alpha$. To tune 1, we selected the parameter achieving the highest accuracy for the validation dataset, $\alpha = 0.1$ (Table 1). Additional experiments on how parameterization impacts model training can be found in Appendix A.

As a baseline, we compared our method against the domain adaptive neural network (DANN) method. Both methods penalize models if different domains can be distinguished in the representation of a model, but while our method calculates a loss on batches of images, the DANN method penalizes individual images if an adversary can discriminate domain. To maximize comparability, we trained a DANN model using the same architecture and data splits as our OT method. We observed that our OT method outperforms DANN on both the validation and test dataset, and with a greater margin on the test dataset (Table 2). Finally, as a more trivial baseline, we compared if using the OT distance to align validation and test features with training features after training (i.e. with a frozen ResNet50) would be effective (Appendix B). This strategy leads to much inferior performance than either our OT method and DANN, suggesting that incorporating OT during training is critical to model generalization, rather the strength of OT in correction alone.

To understand why our OT method outperforms DANN, we performed a qualitative evaluation of the training, validation, and test datasets using features extracted by a frozen ImageNet-trained encoder with tSNE (Figure 3). Unlike features learned by either our OT or the DANN method, ImageNet features are not trained on or exposed to any images in Camelyon17, allowing for an unbiased exploration of the perceptual similarity of tiles in these datasets. We observed that while tumor and normal tiles form distinct clusters in the training dataset (clusters 1 and 4 in Figure 3), tumor and normal tiles now form a continuous single cluster in the test dataset (3/4/5 in Figure 3), with tumor and normal tiles overlapping in the ImageNet feature space. Qualitative evaluation of samples from

these clusters indicates that while nuclei in tumor tiles are more spread out and sparse in tissue (samples for Cluster 4 in Figure 3) compared to normal tiles (samples for Cluster 1), and this difference is also seen in most tiles in the test dataset (samples for Cluster 5 and 2), some tumor tiles exhibit cancer cell nuclei growing in dense, clustered clumps (samples for Cluster 3). We observe that DANN systematically fails in classifying this clumped cancer nuclei phenotype (Figure 3C), while our method succeeds. In addition, we provide t-SNE projection of OT-regularized and DANN in Appendix C

Figure 3: **The t-SNE projection of feature embeddings from a ResNet-50 model trained on ImageNet**. (A) represents the distribution of each domain. (B) highlights the distribution of normal/tumor patches. (C) compares the performance of DANN and OT. (D) demonstrate examples from the distributions that have been highlighted in (B).

Finally, while our previous results show that our proposed OT loss leads to significant improvements in generalization in adversarial methods, correcting batch effects in histopathology is a well-studied topic, and numerous other approaches have been proposed. We next took a more systematic comparison of the performance of our method against other algorithms previously reported on the WILDS-Camelyon17 dataset: empirical risk minimization (ERM), which minimizes the average training loss and does not include any domain adaptation, CORAL(Gulrajani and Lopez-Paz, 2021), originally designed for unsupervised domain adaptation; IRM(Arjovsky et al., 2019), for domain generalization; and Group DRO(Sagawa et al., 2019), for subpopulation shifts. These baselines indicate that domain adaptation is not trivial on histopathology images, with all methods worsening performance on the test dataset relative to the ERM baseline. Compared to these methods, our method performs significantly better than ERM.

More recent approaches in correcting batch effects have investigated the use of synthetic images (MBDG (Robey et al., 2021)), improved architectures like vision transformers (SGD

Table 3: **Model performance compared to benchmark algorithms.**. We report standard deviation in the parenthesis

| Methods | ERM | CAROL | IRM | Group DRO | MBDG | SGD (Freeze-Embed) | OT-regularized |
|---------|-----|-------|-----|-----------|------|--------------------|----------------|
| **Accuracy of** | 0.849 | 0.862 | 0.862 | 0.855 | 0.881 | 0.952 | 0.891 |
| **validation** | (0.031) | (0.014) | (0.014) | (0.022) | (0.018) | (0.003) | (0.005) |
| **Accuracy of** | 0.703 | 0.595 | 0.642 | 0.684 | 0.933 | 0.965 | 0.850 |
| **test** | (0.064) | (0.077) | (0.081) | (0.073) | (0.010) | (0.004) | (0.019) |

(Freeze Embed) (Kumar et al., 2022))), and adaptive data augmentation (Appendix D). Compared to these approaches, our OT method underperforms, but we highlight opportunities for synergy between approaches in the next section.

## 4. Discussion

In this paper, we show that using optimal transport to quantify and penalize differences in domain during training leads to more invariant learning in histopathology, allowing models to be directly deployed on new institutions without retraining. Unlike standard adversarial approaches, our method correctly classifies a clumped cancer nuclei phenotype in the Camelyon17 test dataset, unseen in the training dataset. We hypothesize that this is because our OT loss is more robust to local domain shifts that may only occur in a small fraction of tiles, consistent with previous findings that show that OT losses are not as susceptible to overfitting to the mode of the data distribution as standard adversarial losses. As seen in the Camelyon17 dataset, this is especially important in histopathology, where methods may show systematic failures on sparsely represented, but highly critical tiles (e.g. unseen cancer phenotypes).

While our OT loss does not out-perform the top proposed batch effect correction methods on Camelyon17, the top current methods take different approaches than our method, indicating opportunities for synergy. Stain augmentation methods are effective in histopathology, and minimize differences in intensity and color of stains between institutions and samples (see Appendix D). However, these methods fail to account for differences in morphology stemming from e.g. differences in cancer phenotypes between patients, which we showed our method is robust to. Other works, which have proposed more advanced architectures and synthetic data, would similarly synergize with our method. We anticipate in future work, combining these methods would lead to better overall performance.

In conclusion, we have demonstrated that using OT to constrain model training can lead to invariant learning, improving model performance in unseen domains. Future work may explore how this method performs in cases of subpopulation shift (ie under-represented populations) and with other non-histological data types.

## References

Christian Abbet, Linda Studer, Andreas Fischer, Heather Dawson, Inti Zlobec, Behzad Bozorgtabar, and Jean-Philippe Thiran. Self-rule to adapt: Learning generalized features

from sparsely-labeled data using unsupervised domain adaptation for colorectal cancer tissue phenotyping. In *Medical Imaging with Deep Learning*, 2021.

David Alvarez-Melis and Tommi S Jaakkola. Gromov-wasserstein alignment of word embedding spaces. *arXiv preprint arXiv:1809.00013*, 2018.

Martin Arjovsky, Soumith Chintala, and Léon Bottou. Wasserstein generative adversarial networks. In *International conference on machine learning*, pages 214–223. PMLR, 2017.

Martin Arjovsky, Léon Bottou, Ishaan Gulrajani, and David Lopez-Paz. Invariant risk minimization. *arXiv preprint arXiv:1907.02893*, 2019.

Steve Tsham Mpinda Ataky, Jonathan De Matos, Alceu de S Britto, Luiz ES Oliveira, and Alessandro L Koerich. Data augmentation for histopathological images based on gaussian-laplacian pyramid blending. In *2020 International Joint Conference on Neural Networks (IJCNN)*, pages 1–8. IEEE, 2020.

Shailja Chatterjee. Artefacts in histopathology. *Journal of oral and maxillofacial pathology: JOMFP*, 18(Suppl 1):S111, 2014.

Marco Cuturi. Sinkhorn distances: Lightspeed computation of optimal transport. *Advances in neural information processing systems*, 26, 2013.

Amelie Echle, Niklas Timon Rindtorff, Titus Josef Brinker, Tom Luedde, Alexander Thomas Pearson, and Jakob Nikolas Kather. Deep learning in cancer pathology: a new generation of clinical biomarkers. *British journal of cancer*, 124(4):686–696, 2021.

Khrystyna Faryna, Jeroen van der Laak, and Geert Litjens. Tailoring automated data augmentation to h&e-stained histopathology. In *Medical Imaging with Deep Learning*, 2021.

Alfred Galichon. *Optimal transport methods in economics*. Princeton University Press, 2018.

Yaroslav Ganin, Evgeniya Ustinova, Hana Ajakan, Pascal Germain, Hugo Larochelle, François Laviolette, Mario Marchand, and Victor Lempitsky. Domain-adversarial training of neural networks. *The journal of machine learning research*, 17(1):2096–2030, 2016.

Ishaan Gulrajani and David Lopez-Paz. In search of lost domain generalization. In *International Conference on Learning Representations*, 2021. URL https://openreview.net/forum?id=lQdXeXDoWtI.

Metin N Gurcan, Laura E Boucheron, Ali Can, Anant Madabhushi, Nasir M Rajpoot, and Bulent Yener. Histopathological image analysis: A review. *IEEE reviews in biomedical engineering*, 2:147–171, 2009.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 770–778, 2016.

Frederick M Howard, James Dolezal, Sara Kochanny, Jefree Schulte, Heather Chen, Lara Heij, Dezheng Huo, Rita Nanda, Olufunmilayo I Olopade, Jakob N Kather, et al. The impact of site-specific digital histology signatures on deep learning model accuracy and bias. *Nature communications*, 12(1):1–13, 2021.

Leonid Kantorovitch. On the translocation of masses. *Management science*, 5(1):1–4, 1958.

Pang Wei Koh, Shiori Sagawa, Henrik Marklund, Sang Michael Xie, Marvin Zhang, Akshay Balsubramani, Weihua Hu, Michihiro Yasunaga, Richard Lanas Phillips, Irena Gao, et al. Wilds: A benchmark of in-the-wild distribution shifts. In *International Conference on Machine Learning*, pages 5637–5664. PMLR, 2021.

Ananya Kumar, Ruoqi Shen, Sébastien Bubeck, and Suriya Gunasekar. How to fine-tune vision models with sgd. *arXiv preprint arXiv:2211.09359*, 2022.

Maxime W Lafarge, Josien PW Pluim, Koen AJ Eppenhof, Pim Moeskops, and Mitko Veta. Domain-adversarial neural networks to address the appearance variability of histopathology images. In *Deep learning in medical image analysis and multimodal learning for clinical decision support*, pages 83–91. Springer, 2017.

Maxime W Lafarge, Josien PW Pluim, Koen AJ Eppenhof, and Mitko Veta. Learning domain-invariant representations of histological images. *Frontiers in medicine*, 6:162, 2019.

Geert Litjens, Peter Bandi, Babak Ehteshami Bejnordi, Oscar Geessink, Maschenka Balkenhol, Peter Bult, Altuna Halilovic, Meyke Hermsen, Rob van de Loo, Rob Vogels, et al. 1399 h&e-stained sentinel lymph node sections of breast cancer patients: the camelyon dataset. *GigaScience*, 7(6):giy065, 2018.

Gaspard Monge. Mémoire sur la théorie des déblais et des remblais. *Mem. Math. Phys. Acad. Royale Sci.*, pages 666–704, 1781.

Fernando Pérez-Bueno, Juan G Serra, Miguel Vega, Javier Mateos, Rafael Molina, and Aggelos K Katsaggelos. Bayesian k-svd for h and e blind color deconvolution. applications to stain normalization, data augmentation and cancer classification. *Computerized Medical Imaging and Graphics*, 97:102048, 2022.

Gabriel Peyré, Marco Cuturi, et al. Computational optimal transport: With applications to data science. *Foundations and Trends® in Machine Learning*, 11(5-6):355–607, 2019.

Alexander Robey, George J Pappas, and Hamed Hassani. Model-based domain generalization. *Advances in Neural Information Processing Systems*, 34:20210–20229, 2021.

Kate Saenko, Brian Kulis, Mario Fritz, and Trevor Darrell. Adapting visual category models to new domains. In *European conference on computer vision*, pages 213–226. Springer, 2010.

Shiori Sagawa, Pang Wei Koh, Tatsunori B Hashimoto, and Percy Liang. Distributionally robust neural networks for group shifts: On the importance of regularization for worst-case generalization. *arXiv preprint arXiv:1911.08731*, 2019.

M. Tarek Shaban, Christoph Baur, Nassir Navab, and Shadi Albarqouni. Staingan: Stain style transfer for digital histological images. In *2019 IEEE 16th International Symposium on Biomedical Imaging (ISBI 2019)*, pages 953–956, 2019. doi: 10.1109/ISBI.2019. 8759152.

Jeroen Van der Laak, Geert Litjens, and Francesco Ciompi. Deep learning in histopathology: the path to the clinic. *Nature medicine*, 27(5):775–784, 2021.

## Appendix A. Analysis of convergence

Figure 4: From left to right, plots show CE loss, OT loss, and model performance of the validation set respectively during training. Each row represents different values of $\alpha$.

To optimize the regularization tuning parameter $\alpha$, where $\alpha$ represents the regularized contribution of the OT loss to the overall loss function, we varied $\alpha$ and reported the model performance on the test set, aggregated over 4 experiments initialized with different random number seeds. Our results are summarized in Table 1. When $\alpha$ is very small, the OT loss contribution is minimal and the model does not generalize well, leading to worse model performance. However, at very large $\alpha$, the model struggles to converge, leading to lower classifier accuracy and increased standard deviation of the model performance.

## Appendix B. Aligning target and source distributions after training

One of the approaches that we have investigated was to apply OT to the feature map after training. The idea was to train a model with only cross-entropy loss on source data. Then, forwarding the target data to the feature extractor, aligning the target feature representation with source, and classifying them. To solve this OT problem, we have used Sinkhorn algorithm with the regularization value of 2. As can be seen in Figure 5, the t-SNE projection of features demonstrate a good alignment of target data after OT. However, this does not guarantee that the classification will be good, as the validation and test accuracy only slightly improve, with values of 0.855 and 0.711, respectively. This is only slightly better than the ERM approach. Therefore, having a cross-entropy and OT loss function at the time of will ensure the discrimination power, which will enhance the performance.

Figure 5: The t-SNE projection of feature embeddings from a random sample of 1000 image patches of target, source, and OT-adapted domains.

## Appendix C. Analysis of feature embeddings

Figure 6: **The t-SNE projection of feature embeddings for EMR, DANN, and OT models.** We demonstrate OT's feature map projection for ($\alpha = 0.1$). First row highlights each train, validation, and test dataset. Second row represents true positive (TP), false positive (FP), true negative (TN), and false negative (FN).

In Figure 6, we visualize the alignment of feature embeddings between training, validation, and test domains using the baseline ERM method, DANN, and our OT-regularized method. Visually, we observe better alignment between the training, validation and test domains using both DANN and OT. However, OT better separates normal and tumor patches. We also observe visually that using OT loss, incorrect predictions (FP and FN) cluster away from the correct predictions, clearly indicating gaps in the training data diversity.

## Appendix D. Stain augmentation

In this section, we analyze the effect of stain augmentation on model generalization. In Table 4, We compare our OT-regularized approach with ERM w/ data aug developed by WILDS and H&E-tailored RandAugment (Faryna et al., 2021). Our findings demonstrate that H&E-tailored RandAugment approach outperform OT-regularized using camelyon17-WILDS dataset. In addition, we integrated OT-regularized approach with H&E-tailored RandAugment and we did not observe any improvement.

Table 4: **Comparison of stain augmentation appraoches with OT-regularized.**

| Methods | ERM w/ data aug | H&E-tailored RandAugment | OT-regularized | H&E-tailored RandAugment w/ OT-regularized |
|---|---|---|---|---|
| **Accuracy of validation** | 0.906 (0.012) | 0.914 (0.006) | 0.891 (0.005) | 0.912 (0.005) |
| **Accuracy of test** | 0.820 (0.074) | 0.922 (0.022) | 0.850 (0.019) | 0.924 (0.006) |