Music Playlist Title Generation Using Artist Information

Abstract

Automatically generating or captioning music playlist titles given a set of tracks is of significant interest in music streaming services as customized playlists are widely used in personalized music recommendation, and well-composed text titles attract users and help their music discovery. We present an encoder-decoder model that generates a playlist title from a sequence of music tracks. While previous work takes track IDs as tokenized input for playlist title generation, we use artist IDs corresponding to the tracks to mitigate the issue from the long-tail distribution of tracks included in the playlist dataset. Also, we introduce a chronological data split method to deal with newly-released tracks in real-world scenarios. Comparing the track IDs and artist IDs as input sequences, we show that the artist-based approach significantly enhances the performance in terms of word overlap, semantic relevance, and diversity.

1 Introduction

With the popularization of music streaming services, music playlists have become essential resources in helping music discovery from huge collections of music (Dias, Gonçalves, and Fonseca 2017). Because of the expected difficulty of browsing a large number of music playlists, a music playlist title that depicts the content information is often provided to attract users and help their discovery. For example, a title could be used to describe genre (e.g., *Send this playlist to your friend who doesn't know what indie rock is*), situation (e.g., *Best Jogging Music for Motivation*), originality (e.g., *Playlist that Will Make You Feel Like an Arabian Princess*), and so on. Making an informative and attractive title, however, does not come easily to everybody; we have seen a lot of titles that do not contain musically meaningful information (e.g., *my favorites*) or simply consist of a few related words (e.g., *"meditation, zen, yoga, sleep, study, focus"*). Thus, if a descriptive playlist title could be generated automatically, it would help make the playlist more inviting and discoverable.

Several approaches to automatically create a playlist's title or description have been proposed. They are mainly based on a neural machine translation model, which encodes a whole sequence of musical information into fixed-length latent vectors and then decodes them into text (Bahdanau, Cho, and Bengio 2014; Vaswani et al. 2017). Specifically,

they used an RNN-based sequence-to-sequence model that learns from audio and supplementary text data (e.g., genre) (Choi et al. 2016) or a transformer-based model that takes a series of track IDs (unique IDs given to each track) (Doh, Lee, and Nam 2021) to generate a title for a music playlist. From the previous work, we observe two major issues. One is that a significant amount of the data is rarely-seen, making it difficult to capture the semantics for the model. As a result, the model has a tendency to repetitively produce musically meaningless titles such as "*My Favorite Songs*". Another issue is that it does not reflect real-world settings in which the model makes inferences from playlists containing new releases. An ideal music playlist title generation system should generalize well across different types of music playlists; its performance should not deviate when inferring from playlists with infrequently appearing tracks or new releases.

To address these limitations, we introduce a music playlist title generation model that takes artist IDs instead of track IDs as input (Section 2). Because tracks by the same artist all use the same input embedding vector, the model is capable of capturing the semantics of songs regardless of the frequency of appearances in playlists. To better represent real-world settings, we propose chronological data split method to simulate the case of inferring from tracks that are newly released (Section 3). Furthermore, We perform a systematic evaluation regarding word overlap, semantic relevance, and diversity (Section 4). Finally, Sections 5 and 6 show that the artist ID embedding approach improves the ability to deal with unpopular tracks or artists without compromising the ability to handle popular tracks or artists.

2 Music Playlist Title Generation

Encoder-Decoder Model

Similar to the previous work (Doh, Lee, and Nam 2021), our music playlist title generation model is based on an encoder-decoder framework: an encoder network for obtaining the semantics of music tracks and an decoder for generating a sequence of natural language. We use the Transformer architecture (Vaswani et al. 2017), which has two or three sub-layers: multi-head attention sub-layers, fully-connected sub-layers, and the masked multi-head attention layer in the case of the decoder. As illustrated Figure 1, the architecture

Word Sequence in a Title

Figure 1: Model Architecture.

Dataset	Statistic	Original	Doh et al	Proposed
	# of Playlist	148,826	51,404	78,064
	# of Unique Track	649,902	429,266	512,258
	# of Unique Artist	115,457	77,145	90,987
Melon	# of Unique Title	115,318	59,209	74,325
	# of Unique Word	88,524	49,978	61,066
	Avg. Char Length	2.8	3.56	3.05
	Avg. Title Length	3.6	4.68	5.09
	Avg. Track Length	39.7	46.17	45.35
	# of Playlist	1,000,000	50,083	34,729
	# of Unique Track	2,262,292	402,523	309,741
	# of Unique Artist	286,787	69,641	55,046
MPD	# of Unique Title	17,381	1,859	1,490
	# of Unique Word	11,146	1,886	1,632
	Avg. Char Length	5.2	4.2	4.15
	Avg. Title Length	1.4	3.4	3.44
	Avg. Track Length	66.3	66.3	63.98

Table 1: Dataset Statistics.

Dataset	Entity	Proportion of <UNK>token
Melon	Track ID	14.70%
	Artist ID	2.85%
MPD	Track ID	9.74%
	Artist ID	2.17%

Table 2: Proportion of *<UNK>* tokens in validation and test sets

takes unique token IDs from a sequence of music tracks. In the proposed systems, a music track sequence is a collection of track or artist information x, with each track or artist represented as a unique token $(x_1, ..., x_n)$. The tokenized IDs are initialized by d_{model} dimension random vectors and processed by the encoder network $f \colon \mathcal{X} \mapsto \mathcal{Z}$. The vectors are transformed into a sequence of latent representations $z = (z_1, ..., z_n)$, which is fed to the decoder $g \colon \mathcal{Z} \mapsto \mathcal{Y}$, and it generates an output sequence $\hat{y} = (\hat{y}_1, .., \hat{y}_m)$ where $\hat{y}$ refers to a generated music playlist title and each element in $(\hat{y}_1, .., \hat{y}_m)$ refers to each token in the title. We used the soft-max cross-entropy loss for comparing the ground truth with the prediction.

Music Track Representations

We use music track sequences as input for the encoders. Each element of the track sequence was represented with metadata such as a track ID and an artist ID. Tracks provides more specific information than artists. Such high specificity may capture the detail of music semantics, but it often causes the issue that the system cannot extract meaningful semantics if the track was infrequently seen in the training phase. For example, in the playlist datasets in our experiment, more than 17% of tracks do not appear more than two times in the training phase. On the other hand, only less than 5.0% artist IDs appear at most two times. Therefore, using artist IDs may allow the system to extract the semantics from the information obtained from prior songs by the same artists.

3   Dataset and Experiment

We used two different datasets: the Melon Playlist Dataset (Melon) (Ferraro et al. 2021) and the Spotify Million Playlist Dataset (MPD) (Chen et al. 2018). The dominant languages used are Korean and English, respectively. Originally cre-

ated for the automatic playlist continuation (APC) tasks, the datasets contain playlist titles, music track sequences, and music metadata (track, artist name) along with the last modification date. Using both datasets, the previous work (Doh, Lee, and Nam 2021) suggested a random data split scheme and a noise-cleaning strategy for generating playlist titles. However, this approach has two limitations – First, validating and testing on randomly divided data does not imitate the circumstance of making inferences from newly released tracks and artists. Second, the filtering strategy considered the structural quality of titles only, while overlooking the semantic quality. This would reduce the usability of the system in practice. To address the problem, we propose a new data split and noise-filtering strategy.

Chronological Data Split

In the real world, the model makes predictions on playlists with new releases as a large number of music tracks are uploaded to music streaming platforms every day. Validating and testing on randomly split sets does not represent this reality. To overcome this limitation, we performed train, validation, and test on data that was chronologically divided, as shown in figure 2 and replaced a new release with a special token, *<UNK>*. For the Melon Playlist Dataset, we used playlists made in 2020 as validation and test sets. Any playlist created before that was used as train data. For the Million Playlist Dataset, playlists made in the last quarter of 2017 were used as validation and test sets. Those created be-

(a) Melon Playlist   (b) Million Playlist

Figure 2: Chronologically split data. Train data is colored blue and validation/test data is colored red. The horizontal axes are split by year and quarter.

fore that were used as train data. The approximated ratio of train sets to validation/test sets is 83:17 and 82:18, respectively. As Table 2 shows, the proportion of $<UNK>$ token is significantly higher when using track IDs as input than artist IDs, which implies that the model is more likely to handle unseen data when taking track IDs as input.

Filtering Out Noisy Data

As the previous study (Doh, Lee, and Nam 2021) suggested, some playlists in datasets come with undesirable titles or a very small number of tracks (including playlists with no tracks). Therefore, they only used playlists that meet the following criteria. i) The title should have at least three tokens after white space tokenization. ii) The average character length of tokens should be at least three. iii) The playlist should contain at least ten tracks. We modified the criteria by mitigating the second and third one and adding one newly defined one. A new criterion was introduced to avoid generating titles without musically meaningful information, such as *"good music to listen to"* or *"best music ever"*. Therefore, we only used playlists that contain at least one word from a pre-defined music tags list. We obtained the music tags list in the following steps.

Korean: The music tags list in Korean is based on the 30,652 unique tags provided by the Melon Playlist Dataset. We only considered tags that appeared at least fifty times in the entire dataset. Tags that are musically meaningless, such as *"recommendation"* and *"compilation"* were excluded. The total number of tags in Korean is 731.

English: The Million Playlist Dataset does not provide music tags. We obtained the tag list in English from two publicly available music tag datasets for music auto-tagging research (The MTG-Jamendo Dataset (Bogdanov et al. 2019) and the Million Song Dataset (Bertin-Mahieux et al. 2011)). Since they do not contain a large number of genres that have recently gained popularity (e.g., *"trap"*), we gained additional tags from frequently appearing words on YouTube Music. Again, we removed tags that are not suitable for music playlist descriptions. There are a total of 1,013 tags in English.

To summarize, we filtered out playlists that did not meet the following criteria. i) The title should have at least three tokens after white space tokenization. ii) The average character length of tokens should be at least two. iii) The playlists should contain at least two tracks. iv) The title should contain at least one musically meaningful word. As a result of our modification of criteria, we were able to collect titles with meaningful information as all of the titles include at least one musically relevant term without reducing the average title length (see Table 1).

Training Details

The model was optimized with the Adam optimizer with a 0.005 learning rate and 0.0001 learning rate decay (Kingma and Ba 2014) with one GPU (GeForce GTX 1080). The rate was scheduled with the cosine annealing scheduler with a minimum learning rate of 0.000001 (Loshchilov and Hutter 2017). We used a batch size of 64 and performed validation at the end of every epoch. Following previous research, we randomly shuffled the position of the input sequence because the order of tracks or artists in a music playlist does not provide crucial information when generating a title in most circumstances.

4 Evaluation Metrics

For our evaluation, we use text generation evaluation metrics (Celikyilmaz, Clark, and Gao 2020) and grouped them into three categories: (i) n-gram based overlap metrics (ii) BERT-based neural metrics (iii) n-gram based diversity metrics. Using these metrics, we assess the overall performance. In addition, we measure the robustness which we define as the degree to which the model's performance changes when dealing with data that appears infrequently versus frequently.

n-gram Overlap Metrics

Counting the number of overlapping n-gram between a reference $y = (y_1, ..., y_l)$ and a candidate $\hat{y} = (\hat{y}_1, ..., \hat{y}_m)$ is one of the most common ways to evaluate models for text generation . This paper uses three popular n-gram overlap metrics to evaluate the model performance — BLEU, ROUGE, and METEOR.

Bilingual Evaluation Understudy (BLEU) was proposed to assess machine translation performance, and this includes modified n-gram precision (Papineni et al. 2002). The computation of the modified precision score for one reference sentence and one candidate sentence is done by counting the number of n-gram matches and dividing it by the number of candidate n-grams. In this paper, we calculated BLEU for two different values of n ($n = 1, 2$).

Recall-Oriented Understudy for Gisting Evaluation (ROUGE) was proposed for text summarization evaluation and has also been used for evaluating short text generation (Lin 2004). Whereas BLEU focuses on precision, ROUGE uses both recall and precision. In this paper, we use the f1-score of ROUGE-N, one of the variants of ROUGE, for

Dataset	Input	Loss	n-gram Overlap Metrics					BERT-Based Metrics	
		NLL	BLEU-1	BLEU-2	ROUGE-1	ROUGE-2	METEOR	BERT Score	SenBERT
Melon	Track ID	6.40	0.048	0.01	0.061	0.01	0.041	0.417	0.775
	Artist ID	6.23	0.056	0.01	0.074	0.01	0.049	0.430	0.778
MPD	Track ID	1.35	0.232	0.180	0.237	0.174	0.212	0.889	0.408
	Artist ID	1.17	0.288	0.229	0.293	0.223	0.265	0.897	0.460

Table 3: Comparison between the track ID embedding model and the artist ID embedding model. The results indicate word overlap and BERT-based metric improved when using the artist ID embedding.

(a) Melon Playlist   (b) Million Playlist

Figure 3: Distribution of average track frequency (F_t) and average artist frequency (F_a). We removed items above the 99th percentile to eliminate statistical outliers.

evaluating our model. It is obtained by calculating the harmonic mean of prediction (the number of n-gram matches devided by the number of candidate n-grams) and recall (the number of n-gram matches devided by the number of reference n-grams). The values of n used in this paper are 1 and 2.

Metric for Evaluation of Translation with Explicit ORdering (METEOR) was proposed to address some limitations of BLEU for machine translation evaluation (Banerjee and Lavie 2005). In a similar fashion to ROUGE, this metric considers both recall and precision. It could be obtained by calculating the harmonic mean of the unigram precision score and the unigram recall score with weighting recall nine times more than precision. The final score combines this with the chunk penalty. The penalty increases if the number of chunks (consecutive unigrams) increases. When there is no bi-gram match, the maximum number of penalty (0.5) is given.

BERT-Based Neural Metrics

Instead of counting the number of exact matches, BERT-based metrics use the pre-trained contextual embeddings generated by the model to capture the semantic similarity between a reference sentence $y = (y_1, ..., y_l)$ and a candidate sentence $\hat{y} = (\hat{y}_1, ..., \hat{y}_m)$.

BERT Score is obtained by computing the cosine similarity between each token in a reference sentence and in

a candidate sentence and using greedy matching to maximize the score (Zhang et al. 2019). In this paper, we used the pretrained KcBert-Base model (Lee 2020) for evaluating the Melon Playlist Dataset and the pretrained RoBERTa-large model (Zhuang et al. 2021) for evaluating the Million Playlist Dataset to get the contextual embeddings. **Sentence BERT (SentBERT)** was proposed for semantic textual similarity evaluation tasks (Reimers and Gurevych 2019). The SentBERT uses a siamese pre-trained BERT network to derive semantically meaningful sentence embeddings. Each embedding is calculated by taking the mean of all vector representations of each token and computing the cosine similarity between them. In this paper, we adopted the embeddings of KLEU RoberTa small (Park et al. 2021) for evaluating the Melon Playlist Dataset and the all-MiniLM-L6-v2 (Wang et al. 2020) for evaluating the Million Playlist Dataset.

n-gram-Based Diversity Metrics

A successful music playlist title generation model should avoid generating repetitive titles and instead produce diverse outputs. Researchers suggested n-gram-based diversity metrics show a high correlation with lexical diversity (Tevet and Berant 2021). One of the n-gram based metrics used for diversity evaluation is *distinct-n*, the number of distinct n-grams divided by the total number of n grams (Li et al. 2016). In this paper, we evaluated lexical variations using *distinct-n* with three values of n ($n = 1, 2, 3$).

(a) Melon Playlist   (b) Million Playlist

Figure 4: Distribution of BERT Score of the highest 25% F_t group and the lowest 25% F_t group. The score of the lowest 25% group is improved without imparing the performance of the highest 25% group when the artist ID embedding is used.

(a) Melon Playlist   (b) Million Playlist

Figure 5: Distribution of BERT Score of the highest 25% F_a group and the lowest 25% F_a group. The score of the lowest 25% group is improved without imparing the performance of the highest 25% group when the artist ID embedding is used.

5 Results and Discussion

Word Overlap and Semantic Relevance

Table 3 compares all n-gram overlap performance (BLEU, ROUGE, and METEOR) of different input models (Track ID, Artist ID). The artist ID embedding model shows a clear performance improvement over the track ID embedding model. In the case of the Melon Playlist Dataset, the change in BLEU-2 was not noticeable because of the grammatical characteristics of Korean (that post-positional particles immediately follow a noun or pronoun without white space). We observed a similar trend on the Negative Log-likelihood (NLL) Loss and the BERT-based neural metrics (BERT Score and Sentence BERT). This indicates that utilizing artist IDs lessens the problem of dealing with infrequently appearing tracks, enabling the system to extract more musically meaningful information.

Diversity

Figure 6 shows an increase in *distinct-n* when using artist ID embedding regardless of the value of n. Despite the better specificity of track IDs, the artist ID embedding model produces more lexically diverse outputs. This indicates that the low $<UNK>$ token ratio in artist ID (Table 2) contribute to diversity performance as well as relevant performance.

(a) Melon Playlist   (b) Million Playlist

Figure 6: *distinct-n* ($n = 1, 2, 3$) indicates that the artist ID embedding generated more lexically diverse titles.

Robustness

We evaluated the robustness to infrequent appearances of tracks in the playlist datasets. We defined the frequency of appearance from two perspectives: average track frequency and average artist frequency. Based on these points of view, we equally divided the entire playlist into four groups and compared the model performance on the top 25% and bottom 25%. In this paper, we denote them as F_t and F_a, respectively. The average track frequency F_t and the average artist frequency F_a are calculated in the following way. When a playlist consists of tracks $(t_1, ..., t_m)$ and artists $(a_1, ..., a_n)$, the average track frequency F_t is obtained by taking the mean of track frequency $(f_1, ..., f_m)$.

PID	143802	75870
F_t	355.39	0.75
Ground Truth	카페를 가득채우는 감성노래
(An atmosphere of touching music permeates a cafe.)	나른한 오후에 어울리는 잔잔한 연주
(Calming melodies in the afternoon when feeling drowsy)
Track ID Embedding	따뜻한 커피한잔과 함께 듣는 발라드
(Ballad music and a cup of coffee in hand))	영화 속 ost 모음
(Movie soundtracks compilation)
Artist ID Embedding	센치한 밤에 듣는 감성 노래
(A sentimental night with touching music)	잔잔한 피아노 선율로 듣는 클래식
(Piano melodies in classical music that are soothing)

Table 4: Inference examples from the highest 25% Avergage Track Frequency (F_t) group (**Left**) and the lowest 25% Avergage Track Frequency (F_t) group (**Right**).

PID	117646	116152
F_a	3161.39	540.40
Ground Truth	달빛아래 들려오는 감미로운 보이스
(A sweet voice in the moonlight)	한국 힙합 흐름 따라가기
(Catching up with the flow of the Korean hip-hop scene)
Track ID Embedding	따뜻한 커피한잔과 함께 듣는 발라드
(Ballad music and a cup of coffee in hand)	영화 속 bgm rock 영화 속 bgm 모음
(BGM Rock Music in the Movie, Compilation of Movie BGMs)
Artist ID Embedding	조용한 밤에 듣는 감성 노래
(Touching songs you might wanna listen to on a calm night)	한국 힙합의 시작에서 정착까지
(Korean hip-hop: From its inception until its maturation)

Table 5: Inference examples from the highest 25% Avergage Artist Frequency (F_a) group (**Left**) and the lowest 25% Avergage Artist Frequency(F_a) group (**Right**).

Similarly, we can calculate the average artist frequency score F_a by averaging the frequency of each artist in the train sets $(\hat{f}_1, ..., \hat{f}_n)$ (The numbers of m and n could be different because there could be multiple artists on a single track).

$$F_t = \frac{1}{m}\Sigma_{x=1}^{m}f_x \qquad (1)$$

$$F_a = \frac{1}{n}\Sigma_{x=1}^{n}\hat{f}_x \qquad (2)$$

As shown in figure 3, there were a much greater number of playlists with low F_t than those with low F_a. In this figure, we added the red lines to visualize the values that divide the data into four parts.

The artist ID embedding model shows remarkably better performance on the lowest F_t score group (those from 0% to 25%) than the track ID embedding in terms of semantic relevance, as shown in figure 4. The improvement is made without impairing the performance on the highest F_t score group (those from 75% to 100%). In fact, the performance on the highest F_t group (those with the highest 25% average track frequency) improves when using artist ID embedding in the case of the Million Playlist Dataset. As a consequence of this, the performance gap between the subgroups is mitigated. We also observed the artist ID embedding improve the performance on the lowest F_a score group (from 0% to 25%) and alleviate the performance gap, as shown in Table 5.

Qualitative Results

We provide four inference examples on the Melon Playlist Dataset in Table 4 and 5, each from the group with highest 25% F_t, lowest 25% F_t, highest 25% F_a, and lowest 25% F_a. Regardless of the inputs, the model successfully generated a phrase-like title describing the mood (e.g., *touching*) or location (e.g., *cafe*) of the playlists for the highest 25% F_t and highest 25% F_a group. The model trained with artist ID embedding generated informative titles that represents the mood (*soothing*), originality (*Korean*) and genre (*hip-hop*) of the playlists from the lowest 25% F_t and lowest 25% F_a group. However, when trained with track IDs, the model could not generate a title with the correct information for the playlist from the lowest 25% F_t and lowest 25% F_a group (PID : 75870). Whereas the ground truth defines each playlists as *calming melodies* and *Korean hip-hop*, the model predicts them as *movie soundtracks* and *rock music in the movie*, respectively.

6   Conclusions

In this paper, we proposed a model for music playlist title generation model using a series of artist IDs as input. Throughout our assessment, we showed that the artist ID embedding can improve the performance in terms of word overlap, semantic similarity, and diversity. We also proved that the artist ID embedding improves the model robustness because rarely or never-before-seen data are less likely to be handled by the model. Our findings were supported by two datasets with different languages. For future work, we plan to experiment with different inputs, such as genre labels, audio, or a mixture of track and artist IDs.

References

Bahdanau, D.; Cho, K.; and Bengio, Y. 2014. Neural machine translation by jointly learning to align and translate. In *Proceedings of the International Conference on Learning Representations (ICLR)*.

Banerjee, S.; and Lavie, A. 2005. METEOR: An Automatic Metric for MT Evaluation with Improved Correlation with Human Judgments. In *Proceedings of the ACL Workshop on Intrinsic and Extrinsic Evaluation Measures for Machine Translation and/or Summarization*.

Bertin-Mahieux, T.; Ellis, D.; Whitman, B.; and Lamere, P. 2011. The Million Song Dataset. In *Proceedings of the 12th International Conference on Music Information Retrieval (ISMIR)*, 591–596.

Bogdanov, D.; Won, M.; Tovstogan, P.; Porter, A.; and Serra, X. 2019. The MTG-Jamendo Dataset for Automatic Music Tagging. In *Machine Learning for Music Discovery Workshop, International Conference on Machine Learning (ICML)*. Long Beach, CA, United States.

Celikyilmaz, A.; Clark, E.; and Gao, J. 2020. Evaluation of text generation: A survey. *arXiv preprint arXiv:2006.14799*.

Chen, C.-W.; Lamere, P.; Schedl, M.; and Zamani, H. 2018. Recsys challenge 2018: Automatic music playlist continuation. In *Proceedings of the 12th ACM Conference on Recommender Systems*, 527–528.

Choi, K.; Fazekas, G.; McFee, B.; Cho, K.; and Sandler, M. 2016. Towards music captioning: Generating music playlist descriptions. *Late Breaking Demo in the 22st International Society for Music Information Retrieval Conference (ISMIR)*.

Dias, R.; Gonçalves, D.; and Fonseca, M. J. 2017. From manual to assisted playlist creation: a survey. In *Multimedia Tools and Applications*.

Doh, S.; Lee, J.; and Nam, J. 2021. Music Playlist Title Generation: A Machine-Translation Approach. *Proceedings of the 2nd Workshop on NLP for Music and Spoken Audio, 22th International Society for Music Information Retrieval Conference (ISMIR)*.

Ferraro, A.; Kim, Y.; Lee, S.; Kim, B.; Jo, N.; Lim, S.; Lim, S.; Jang, J.; Kim, S.; Serra, X.; et al. 2021. Melon playlist dataset: A public dataset for audio-based playlist generation and music tagging. In *Proceedings of the International Conference on Acoustics, Speech and Signal Processing (ICASSP)*.

Kingma, D. P.; and Ba, J. 2014. Adam: A method for stochastic optimization. In *Proceedings of the International Conference on Learning Representations (ICLR)*.

Lee, J. 2020. KcBERT: Korean Comments BERT. In *Proceedings of the 32nd Annual Conference on Human and Cognitive Language Technology*, 437–440.

Li, J.; Galley, M.; Brockett, C.; Gao, J.; and Dolan, W. B. 2016. A Diversity-Promoting Objective Function for Neural Conversation Models. In *Proceedings of the 2016 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, 110–119.

Lin, C.-Y. 2004. Rouge: A package for automatic evaluation of summaries. In *Text summarization branches out*, 74–81.

Loshchilov, I.; and Hutter, F. 2017. SGDR: Stochastic Gradient Descent with Warm Restarts. In *International Conference on Learning Representations (ICLR)*.

Papineni, K.; Roukos, S.; Ward, T.; and Zhu, W.-J. 2002. Bleu: a method for automatic evaluation of machine translation. In *Proceedings of the 40th annual meeting of the Association for Computational Linguistics*, 311–318.

Park, S.; Moon, J.; Kim, S.; Cho, W. I.; Han, J.; Park, J.; Song, C.; Kim, J.; Song, Y.; Oh, T.; Lee, J.; Oh, J.; Lyu, S.; Jeong, Y.; Lee, I.; Seo, S.; Lee, D.; Kim, H.; Lee, M.; Jang, S.; Do, S.; Kim, S.; Lim, K.; Lee, J.; Park, K.; Shin, J.; Kim, S.; Park, L.; Oh, A.; Ha, J.; and Cho, K. 2021. KLUE: Korean Language Understanding Evaluation. arXiv:2105.09680.

Reimers, N.; and Gurevych, I. 2019. Sentence-BERT: Sentence Embeddings using Siamese BERT-Networks. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, 3982–3992.

Tevet, G.; and Berant, J. 2021. Evaluating the Evaluation of Diversity in Natural Language Generation. In *Proceedings of the 16th Conference of the European Chapter of the Association for Computational Linguistics: Main Volume*, 326–346.

Vaswani, A.; Shazeer, N.; Parmar, N.; Uszkoreit, J.; Jones, L.; Gomez, A. N.; Kaiser, Ł.; and Polosukhin, I. 2017. Attention is all you need. In *Proceedings of the Advances in neural information processing systems (NeurIPS)*.

Wang, W.; Wei, F.; Dong, L.; Bao, H.; Yang, N.; and Zhou, M. 2020. Minilm: Deep self-attention distillation for task-agnostic compression of pre-trained transformers. *Advances in Neural Information Processing Systems*, 33: 5776–5788.

Zhang, T.; Kishore, V.; Wu, F.; Weinberger, K. Q.; and Artzi, Y. 2019. BERTScore: Evaluating Text Generation with BERT. In *International Conference on Learning Representations (ICLR)*.

Zhuang, L.; Wayne, L.; Ya, S.; and Jun, Z. 2021. A Robustly Optimized BERT Pre-training Approach with Post-training. In *Proceedings of the 20th Chinese National Conference on Computational Linguistics*, 1218–1227.