Dynamic Inverse Reinforcement Learning for Characterizing Animal Behavior

Abstract

Building computational models of decision-making is a core objective in both
neuroscience and psychology. While many models have been developed for char-
acterizing behavior in binary decision-making and bandit tasks, limited work has
focused on animal decision-making in more complex tasks, such as navigation
through a maze. Inverse reinforcement learning (IRL) is a promising direction
for understanding such behavior as it aims to infer the unknown reward function
of an agent from its trajectories. However, IRL has yet to be widely applied in
neuroscience. One potential reason for this is that existing IRL frameworks assume
that an agent's reward function is fixed over time. In this work we introduce
'DIRL', a novel IRL framework that allows for time-varying intrinsic rewards. Our
method decomposes the unknown reward function into a linear combination of
reward maps ("goal maps"), which can be weighted differently at each moment
in time. We develop an inference method that allows us to recover these rewards,
and demonstrate the application of our method in simulation, as well as on the
trajectories of mice exploring a labyrinth. Our method returns interpretable reward
functions for two separate cohorts of mice, and provides a novel characterization
of exploratory behavior. Overall, we anticipate our framework having broad ap-
plicability in neuroscience, and in facilitating the design of biologically-inspired
reward functions for training artificial agents to perform analogous tasks.

1 Introduction

Characterizing the decision-making behavior of humans and animals is a central goal in neuroscience
and psychology [1, 2]. Decision-making tasks such as Two-Alternative Forced Choice (2AFC) and
bandit problems have been widely studied [3–7], and previous work has developed a variety of models
for choice behavior in these tasks [1, 7–9]. The classic psychometric curve represents one such model
[10], and more recent work has focused on models based on reinforcement learning [1, 8, 11, 12].
Such models allow us to understand and compare the decision-making strategies used by humans
and animals, and can also provide a low-dimensional description of behavior that can be regressed
against neural data [1, 13].

Although a large literature has focused on models of decision-making in simple 2AFC and bandit tasks,
comparatively few papers have sought to model behavior in larger, complex natural environments.
[14–16]. In a recent study, Rosenberg et al. [15] introduced a novel experimental paradigm involving
water-restricted mice navigating a 127-node labyrinth equipped with a water port at one terminal node
(Fig. 1). At each node, the mouse could make up to 4 distinct decisions ('stay', 'go left', 'go right', or

Figure 1: Example mouse trajectories in the labyrinth task of Rosenberg et al. [15]. Water-restricted and unrestricted mice moved freely through a 127 node maze environment for 7 hours. Over the course of the night, each mouse completed over 100 such trajectories, which began at the home port. For the water-restricted mice, a water port existed at the terminal node in the environment that is shaded grey (next to the water drop image).

'reverse'). Navigation through a maze is a perfect example of complex yet natural decision-making behavior. Although reinforcement learning may seem like the natural framework for modeling such goal-driven behavior, the rewards experienced by these mice are not obvious to the experimenter. Indeed, as noted in Rosenberg et al. [15], the observed trajectories indicate that mice are not only motivated by the extrinsic water reward, but also by intrinsic rewards such as their curiosity to explore the environment.

Inverse reinforcement learning (IRL) [17–19] addresses the problem of inferring the unknown reward function of an agent. Given access to the agent's trajectories as it interacts with the environment, IRL identifies the states and actions that the agent finds rewarding. While IRL has found many successes in robotics [20, 21] and healthcare contexts [22], most existing methods are not well suited to neuroscience. This is because IRL methods typically assume that the unknown reward function is fixed over the course of the agent's trajectory. Yet in many real-world decision-making tasks, rewards can change over time. For example: the goals of a mouse, and consequently its intrinsic rewards, can change with time depending on factors such as fatigue, satiation and curiosity. This motivated us to develop an IRL method for characterizing animal decision-making in complex environments such as the labyrinth, in which rewards may vary over time.

Here we propose dynamic inverse reinforcement learning (DIRL), an IRL method that allows for time-varying reward functions. DIRL decomposes the animal's reward function into a linear combination of a small number of "goal maps". A goal map constitutes the reward associated with each state in the environment and represents one of the potentially many goals of the animal. For example, a satiation goal map could have the water port as highly rewarding, and the other nodes in the maze as unrewarding. Time-varying weights then modulate the extent to which each goal map is active at any timestep. We introduce a method for inferring both the goal maps and the time-varying weights from trajectory data, and demonstrate the application of our framework in simulation (gridworld and labyrinth environments), as well as on real mouse decision-making data from Rosenberg et al. [15]. Our method recovers interpretable reward functions for both cohorts of mice studied there, and reveals an 'explore' goal map for one of the cohorts. While exploration remains poorly understood in neuroscience [23], our method offers a powerful framework for characterizing exploratory, as well as exploitative behavior from an animal's trajectories alone.

2   Related Work

The neuroscientific literature describing models of decision-making is vast, including both normative [1, 8] and descriptive models [9, 10, 24–27]. While some of this work considers models of decision-making that vary over time, most such models have focused on 2AFC or bandit tasks, and do not scale easily to complex decision-making tasks such as navigation. To the best of our knowledge, IRL has found relatively few applications in neuroscience. One exception is [28] which performed inverse optimal control to infer the cost function associated with sensorimotor behavior. Their targeted application—modeling the cost function optimized by a human performing a reaching task—is very different to ours, which results in different assumptions in their work. Another exception is [29] which described an IRL framework for identifying the thermotactic strategies used by C. elegans. Relative to the work we present here, [29] doesn't allow for time-varying rewards, and is also restricted to the

Figure 2: DIRL model schematic. So as to infer a mouse's time-varying intrinsic reward function from its trajectory data, we decompose the reward function into a linear combination of a small number of goal maps, where the weights placed on each map vary over time. A goal map is a map of the environment, showing states that are simultaneously rewarding.

case of a linearly-solvable MDP. Finally, while not the main focus of their paper, Reddy [16] used the static IRL framework of Ziebart et al. [19] to infer the rewards optimized by mice navigating in the Rosenberg et al. [15] task.

The literature on IRL [17–19, 30–32] is extensive, but most studies have assumed that the true underlying reward function is fixed over time. While Babes-Vroman et al. [33] and Choi and Kim [34] allowed trajectories from multiple agents with distinct intentions, neither allowed for a single agent's trajectory to be associated with a time-varying reward function. Surana and Srivastava [35] developed a Bayesian non-parametric method that assumed that an agent's trajectory could be partitioned into distinct behavioral states, and that each discrete state has its own associated reward function. Here, we instead focus on settings where rewards can continuously vary over time.

3 DIRL: Dynamic Inverse Reinforcement Learning

3.1 The Inverse Reinforcement Learning Problem

Let us consider a Markov Decision Process (MDP), $\mathcal{M} = \{\mathcal{S}, \mathcal{A}, \mathcal{T}, \gamma\}$, where $\mathcal{S}$ is the state space, $\mathcal{A}$ is the action space, $\mathcal{T} : \mathcal{S} \times \mathcal{S} \times \mathcal{A} \to [0, 1]$ represents the probability of transitioning between states when a certain action is taken and $\gamma \in [0, 1]$ is the discount factor. Inverse reinforcement learning [17–19, 30, 33, 34] aims to infer the unknown reward function, $r : \mathcal{S} \times \mathcal{A}$, when given access to $\{\mathcal{S}, \mathcal{A}, \mathcal{T}, \gamma\}$ and N trajectories of experts navigating in this environment, $\mathcal{D} = \{\zeta_1, \zeta_2, ..., \zeta_N\}$. Each trajectory is a sequence of state-action pairs, $\zeta_i = \{(s_1, a_1), (s_2, a_2), ...\}$. Typically, IRL frameworks assume that the reward function does not vary across experts or over the course of an expert's trajectory. As discussed earlier, this is a severe limitation when applying IRL in neuroscientific settings, where the subjective value of the rewards an animal receives may vary as a function of time, satiety, thirst, fatigue, curiosity etc. In the following, we introduce an extension of IRL that allows for reward functions that vary across time.

3.2 DIRL Generative Model: Goal Maps and Time-Varying Weights

Considering the MDP defined above, our objective is to infer an agent's time-varying reward function, $r_t(s, a)$ from a set of observed trajectories $\mathcal{D} = \{\zeta_i\}_{i=1}^N$. Following previous work [17–19, 30, 33, 34], we assume that the reward function depends only on the state s, thereby simplifying it to $r_t(s)$. However, inferring the reward for every state at every timepoint still requires learning $|\mathcal{S}| \times T$ parameters. We therefore make two assumptions to reduce the number of parameters and make inference tractable: (1) we model the reward function as low rank, parameterized by a small number of "goal maps" modulated by a set of time-varying weights; and (2) we impose a prior encouraging these weights to vary slowly in time.

In our approach, the time-varying reward function has the following low-rank representation:

$$r_t(s) = \sum_{k=1}^{K} \alpha_{k,t} u_{k,s},\tag{1}$$

where $\mathbf{u}_k \in \mathbb{R}^{\mathcal{S}}$ represents the k'th "goal map", and $\alpha_{k,t} \in \mathbb{R}$ is the weight on this goal map at timestep t. Each goal map specifies a reward level for each state in the environment, while weight $\alpha_{k,t}$ specifies the contribution of goal map k to the animal's reward function at t.

To impose smoothness over time, we place a Gaussian random walk prior over weight trajectories:

$$\alpha_{k,t} = \alpha_{k,t-1} + \epsilon_k; \qquad \epsilon_k \sim \mathcal{N}(0, \sigma_k^2),\tag{2}$$

where σ_k^2 is a hyperparameter controlling the variance of the weight changes. This prior reflects our belief that the factors influencing an animal's subjective experience of reward (e.g., thirst, hunger, fatigue) vary slowly relative to the timescale of individual decisions. The low-rank assumption reduces the number of parameters specifying the reward function from $(|\mathcal{S}| \times T)$ to $(|\mathcal{S}| + T)K$, a massive reduction provided $K \ll \min(|\mathcal{S}|, T)$. The smoothness assumption allows us to further reduce the effective number of parameters, as the weight trajectories $\alpha_{k,t}$ become more correlated with decreasing variance σ_k^2 [36].

Figure 2 illustrates the resulting generative model using a simplified 3×3 gridworld. In this example, there are multiple goal maps, one with reward located at the water port, a second with reward located at the home state, and a third with reward distributed broadly across states, which is associated with exploratory behavior. Each map has a time-varying weight that determines its contribution to the animal's total reward function. In this example, the "home" goal map dominates the reward function at the beginning of time, while the "water" goal map dominates at the very end as the animal becomes increasingly thirsty.

To model decision-making behavior, we assume that animals seek to maximize their expected future reward and entropy in each state under a maximum entropy policy [37, 38], given by:

$$\pi_t(s, a) = \frac{e^{Q^t(s,a)}}{\sum_{a' \in \mathcal{A}} e^{Q^t(s,a')}} \qquad \forall\, s \in \mathcal{S}, a \in \mathcal{A}, t \in \{1, ...T\},\tag{3}$$

where $Q^t(s, a)$ is the soft Q-function for state s and action a at time t:

$$Q^t(s, a) = r_t(s) + \gamma \sum_{s'} P(s' \mid s, a) \log\left(\sum_{a'} Q^t(s, a')\right),\tag{4}$$

which arises from the reward function by performing soft value iteration [30]. This is a common choice of policy in IRL frameworks [30, 38], as it is easily differentiable (unlike maximizing or "greedy" policies), and it has been widely applied to data from both humans and animals [13, 25]. Note that our formulation does not require a temperature parameter, as this is incorporated into the time-varying weights; more (less) deterministic policies can be achieved with larger (smaller) weights.

3.3 DIRL inference procedure

During inference, our objective is to learn the time-varying weights $\{\boldsymbol{\alpha}_k\}_{k=1}^{K}$, as well as the goal maps $\{\mathbf{u}_k\}_{k=1}^{K}$ from the trajectories of an agent (animal). To do so, we alternately optimize the goal maps and time-varying weights to maximize the log-posterior of the observed trajectories in $\mathcal{D}$ under our model. Let $\mathbf{u} \in \mathbb{R}^{\mathcal{S}K}$ be a long vector with the goal maps $\{\mathbf{u}_k\}_{k=1}^{K}$ stacked vertically, and similarly let $\boldsymbol{\alpha} \in \mathbb{R}^{TK}$ contain the time-varying weights $\{\boldsymbol{\alpha}_k\}_{k=1}^{K}$ stacked vertically. We, first, initialize the parameters randomly, such that the elements of the goal maps are chosen from $U(0, 1)$ and the time-varying weights are Gaussian distributed. We then perform coordinate ascent to iteratively update the time-varying weights and the goal maps while holding the other set of parameters constant.

Concretely, we obtain the goal map updates $\mathbf{u}$ by maximizing the following objective using gradient ascent:

$$\mathbf{u}^* = \arg\max_{\mathbf{u}} \sum_{i=1}^{N} \sum_{(s_t,a_t)\sim\zeta_i} \log \pi_t(s_t, a_t) - \lambda||\mathbf{u}||^2 \tag{5}$$

where π_t is the policy given by Eq. 3 and $\lambda||\mathbf{u}||^2$ represents an L2 regularizer.

We then update the time-varying weights $\boldsymbol{\alpha}$ by first updating the reward function and policy (Eq. 3) with the new goal maps, $r_t(s) = \sum_k \alpha_{t,k} u_{k,s}^*$. We then use gradient ascent to perform the optimization:

$$\boldsymbol{\alpha}^* = \arg\max_{\boldsymbol{\alpha}} \left(\sum_{i=1}^{N} \sum_{(s_t,a_t)\sim\zeta_i} \log \pi_t(s_t, a_t) - \tfrac{1}{2}\log|C| - \tfrac{1}{2}\boldsymbol{\alpha}^\top C^{-1}\boldsymbol{\alpha} \right). \tag{6}$$

The last two terms in this objective correspond to the negative log of the Gaussian prior on $\boldsymbol{\alpha}$ (Eq. 2), where $C = D^\top \Sigma^{-1} D$ is the prior covariance, with D a block diagonal matrix of K identical $T \times T$ first-order difference matrices (with 1s on the diagonal and -1s on the sub-diagonal), and Σ is a diagonal matrix with noise-variances σ_k^2 along the diagonal.

We iteratively update the goal maps and time-varying weights using Eq. 5 and Eq. 6 until convergence. (See Alg. 1 for pseudo-code). We consider the number of goal maps K, the discount factor γ, the strength of the goal map prior λ, as well as the noise variances associated with the time-varying weights, $\{\sigma_k\}_{k=1}^{K}$, to be hyperparameters. To restrict the number of hyperparameters, we set $\sigma_k = \sigma \ \forall k$. We then swept across a broad range of values for all hyperparameters (see SM for the full list of values considered) and selected the values that optimized the log-likelihood of a set of held-out trajectories.

Algorithm 1: DIRL Inference Procedure

Input 1: MDP state and action spaces, transition matrix: $(\mathcal{S}, \mathcal{A}, \mathcal{T})$;
Input 2: N trajectories, $\mathcal{D} \equiv \{\zeta_i\}_{i=1}^{N}$;
Input 3: Hyperparameters: no. of goal maps K, noise variances $\{\sigma_k\}$, discount factor γ, strength of goal map prior, λ ;
Output: Parameters governing the rewards $\{\mathbf{u}_k, \boldsymbol{\alpha}_k\}_{k=1}^{K}$, where $\mathbf{u}_k \in \mathbb{R}^{\mathcal{S}}, \boldsymbol{\alpha}_k \in \mathbb{R}^T$;

Let $\mathbf{u} = [\mathbf{u}_1, ...\mathbf{u}_k], \boldsymbol{\alpha} = [\boldsymbol{\alpha}_1, ...\boldsymbol{\alpha}_k]$;
Initialize $\mathbf{u}^0, \boldsymbol{\alpha}^0$;
for $iter = 1...N_{iter}$ **do**

    Calculate rewards $r_t(s) = \sum_k \alpha_{k,t}^{\text{iter}} u_{k,s}^{\text{iter}} \ \forall s \in \mathcal{S}, t \in \{1...T\}$;

    Get policy using soft value iteration : $\pi_t(s, a) = \dfrac{e^{Q^t(s,a)}}{\sum_{a'} e^{Q^t(s,a')}} \ \forall(s, a, t)$;

    Update $\mathbf{u}^{\text{iter}+1}$ by maximizing the log-posterior of trajectories (Eq. 5).;
    Update rewards $r_t(s) = \sum_k \alpha_{k,t}^{\text{iter}} u_{k,s}^{\text{iter}+1}$ and learn new policy $\pi_t(s, a)$;
    Update $\boldsymbol{\alpha}^{\text{iter}+1}$ by maximizing the log-posterior, with noise variances $\{\sigma_k\}$ (Eq. 6).;
end
Output $\mathbf{u}^{N_{\text{iter}}}, \boldsymbol{\alpha}^{N_{\text{iter}}}$, ;

---

4 Results

4.1 Application to a simulated gridworld environment

We first demonstrate our method on simulated trajectories in a 5×5 gridworld environment, with 5 actions per state (up, down, left, right, stay). We generated two goal maps for this environment: a "home" map and a "water" map, which were rewarding only at the home state and the water state, respectively (Fig 3B). Corresponding to these goal maps, we also generated time-varying weights (Fig. 3C, solid lines) for 50 timesteps with the random-walk prior of Eq. 2 (for $\sigma_k = 2^{-3.5}$; this was

Figure 3: Simulations on a 5×5 gridworld. **(A)** Example expert trajectories when the time-varying reward function is obtained using the generative goal maps shown in B and the time-varying weights shown in C. **(B)** Generative goal maps: the first map has a high reward at the "home state" (upper left), the other has a high reward at the the "water state" (bottom center). **(C)** Time varying weights for the home and water goal maps: solid lines show the generative parameters, while dotted lines show the recovered parameters along with a 95% confidence interval. Error bars are computed via the inverse Hessian of the log-posterior of Eq. 6 at the MAP estimate of the weights. **(D)** Recovered goal maps. **(E)** Rewards for the home and water states are shown in red and blue respectively. The average reward for the remaining states is shown in green. Solid lines show the generative rewards, while the dotted lines show the inferred rewards. **(F)** Held-out test set performance as a function of the number of goal maps. Higher values are better; units are bits per decision.

168 chosen to provide adequate variation in the reward function during the time period considered). The
169 weight for the water map started high but decreased over time, thus making the water state the most
170 rewarding for the first ∼25 timesteps (Fig. 3E, blue solid line). In contrast, the weight on the home
171 map started small but increased so that the home state became the most rewarding state at the end of
172 the 50 timesteps (Fig. 3E, red solid line). All of the other states in the environment had a constant
173 reward of 0. In order to generate trajectories corresponding to this reward function (Fig. 3E), we used
174 soft value iteration to learn the corresponding optimal time-varying policy (Eq. 3). We then executed
175 this policy in order to obtain 200 trajectories (a similar number to the number of trajectories we have
176 for the real dataset discussed later), two examples of which are shown in Fig. 3A.

177 Next, we applied our IRL inference method so as to learn the goal maps and time-varying weights
178 from 80% of the generated trajectories. Fig. 3F shows the log-likelihood of the remaining 20% of
179 trajectories as a function of the number of goal maps. The held-out test log-likelihood is equally
180 high for 2 and 3 maps, so we focus on the 2-map solution in order to be able to compare with the
181 generative parameters. It is important to note that we can only recover rewards at each timestep up to
182 an additive constant, as the policy remains unchanged upon the addition of a constant to the rewards.
183 Further, scaling of the goal maps accompanied by an inverse scaling of the time-varying weights also
184 leaves the recovered rewards unchanged. Thus, to compare to the generative parameters, we perform
185 a post hoc processing method to the recovered parameters to handle all such invariances (details in
186 SM). Figures 3C and D show that our method allows us to accurately recover the generative goal
187 maps and time-varying weights from the simulated trajectories. Finally, combining the goal maps
188 and time-varying weights, we are able to accurately match the generative time-varying rewards for
189 different states in the gridworld (Fig. 3E). We also simulated trajectories in a 127-node labyrinth
190 environment (akin to [15], Fig 1), and confirmed that we were able to recover goal maps and time-
191 varying weights (see SM for details). We focus on the gridworld simulations here to demonstrate the
192 versatility of our approach across environments.

4.2 Application of DIRL to real mouse trajectories

Next, we applied our framework to the trajectories of real mice navigating (in the dark) in a 127-node labyrinth environment [15]. In this task, two cohorts of 10 mice moved freely through the labyrinth over the course of 7 hours. The first cohort was water-restricted and the mice were provided with a water port at one of the terminal nodes (shown in gray in Fig. 1). The second cohort was not water-restricted and did not have access to the water port. We show an example trajectory for an animal in each cohort in Fig. 1. Over the course of the night, each animal completed over a hundred such trajectories, with some animals completing many more.

Figure 4: Inferred time-varying rewards for water-restricted mice. **(A)** Inferred goal maps for the water-restricted mice: a "water" map and a "home" map. Dots indicate each of the 127 nodes in the labyrinth environment. **(B)** Recovered time-varying weights for the same animals. Each timestep corresponds to 1 second. **(C)** Model comparison: comparison of DIRL on held-out trajectories to a random policy, as well as the Maximum Entropy IRL framework of [19] and the Deep Maximum Entropy IRL framework of [30]. Higher test log-likelihood is better; test log-likelihood has units of bits/decision. **(D)** Inferred time-varying rewards for the home state, the water state, and the average reward for the remaining states.

4.2.1 Inferring interpretable reward functions from water-restricted mice

We began our investigation by applying our method to a subset of trajectories for the water-restricted animals. Here, we anticipated being able to identify the water port as highly rewarding (in contrast to the water-unrestricted animals). Due to the high variability in trajectories across animals and over the course of the 7 hours, and to be able to obtain trajectories corresponding to similar goal maps and with a similar time course, we used an unsupervised clustering algorithm (based on dbscan [39] and using the Levenshtein distance metric; full details are in the SM) to identify similar trajectories. This procedure had the advantageous side effect of excluding the first 25 or so trajectories for each animal: our focus is not on characterizing learning. Overall, we obtained 200 trajectories for this cohort. Each timestep in a trajectory was recorded at a one second interval.

We then fit the goal maps and time-varying weights to 160 of these trajectories, and held out the remaining 20% of trajectories as a validation set. We found that validation log-likelihood began to level off at two maps (Fig. 4C), so we focus on the 2 map solution here. The 3 map solution is shown in the SM (where the recovered water goal map is simply repeated) Overall, we found that we were, indeed, able to recover a "water" goal map (Fig 4A), with a large reward at the water state and small rewards elsewhere, as well as a "home" goal map with a large reward at the home state.

The recovered time-varying varying weights (Fig 4B) for the water map were high at the beginning – the mouse likely entered the labyrinth due to being thirsty – and later on, as satiation and fatigue set in, tailed off. In contrast, the weights corresponding to the home map started low, but increased over time. The final reward function (Fig 4D) reflects the same dynamics: the water state was highly rewarding for the mouse at the start of its trajectory, while the home state became the more rewarding state after ∼6 seconds. The other states in the labyrinth offered only a small intrinsic reward for the mouse throughout the course of its trajectory.

4.2.2 'Exploratory' maps inferred from water-unrestricted mice

We then moved on to examining the trajectories of the water-unrestricted cohort. Relative to the water-restricted mice, the goal maps for these mice are not obvious – there are no extrinsic reward locations for this cohort in the labyrinth. We began by applying the same clustering algorithm as for the water-restricted animals (discussed in the SM) and identified 155 trajectories for our analysis.

We fit the time-varying weights and goal maps to 80% of these trajectories, and held out the remaining 20% as a validation set. As we show in Fig. 5C, the validation log-likelihood is best for the 2 map solution. While we recover (Fig 5A) a "home" map once again, a new map – that was not present for the water-restricted animals – also appears. This map is rewarding at many states throughout the maze, but is very unrewarding at the home port. Hence, when this map dominates the reward function, the mouse wants to leave the home state and venture into the maze. For these reasons, we refer to this map as the "explore" map. The time-varying weights (Fig 5B) for the home map increase with time; this captures the tendency of these animals to go back to the home state towards the end of the trajectory. The weights corresponding to the explore map are high at the beginning of the trajectory, capturing the exploratory behavior of these animals when they enter the labyrinth. Finally, the inferred rewards (Fig 5D) capture the same behavior: the intrinsic reward associated with the home state increases with time, while the reward for the other states starts high and decreases.

Figure 5: Inferred time-varying rewards for water-unrestricted mice. **(A)** Inferred goal maps for this cohort: an "explore" map and a "home" map are returned. Dots indicate each of the 127 nodes in the labyrinth environment. **(B)** Recovered time-varying weights for the same animals. **(C)** Model comparison: comparison of DIRL on held-out trajectories to a random policy, as well as the Maximum Entropy IRL framework of [19] and the Deep Maximum Entropy IRL framework of [30]. Higher test log-likelihood is better; test log-likelihood has units of bits/decision. **(D)** Inferred time-varying rewards for the home state, the water port, and the average reward for the remaining states. Here the average reward line is on top of the line corresponding to the water port.

4.2.3 DIRL outperforms existing IRL approaches

Finally, we compare the performance of our method with two popular IRL frameworks: the maximum entropy IRL framework of Ziebart et al. [19] and the deep maximum entropy IRL framework of Wulfmeier et al. [30]. In comparison to DIRL, these methods learn a static reward function. We use an open-source implementation of these frameworks [40] and infer the reward functions for each of these methods for the two cohorts of mice studied above. Using the retrieved reward functions, we then obtain the corresponding optimal policy and use it to compute the log-likelihood of the validation set of trajectories. In Figures 4C and 5C, we demonstrate that our method dramatically outperforms these existing methods at explaining the held-out trajectories of both water-restricted and unrestricted mouse cohorts. In the SM, we also show that the trajectories generated by DIRL very well resemble the behavior of mice in the labyrinth, as compared to those generated from [19] and [30].

5 Discussion

In this work, we develop DIRL, a novel inverse reinforcement learning framework for characterizing the behavior of animals during complex decision-making tasks. Our framework infers the intrinsic, time-varying reward functions of animals from their trajectories alone. We validated our framework on simulated data in a gridworld environment, and applied it to two cohorts of 10 mice navigating in a labyrinth [15]. Our method provided distinct and interpretable reward functions for both cohorts: the water-restricted mice assigned a high reward to the water state upon entering the labyrinth, while the water-unrestricted mice assigned a high reward to many states, as they were motivated to explore. As time passed and the mice became fatigued, the reward for the home state increased for animals in both cohorts. Our method also dramatically outperfomed existing IRL approaches according to the log-likelihood of held-out trajectories, indicating a clear need for tailored IRL approaches for neuroscientific applications. Finally, our method is computationally efficient and infers the time-varying reward function from $\sim$4000 decisions in the 127-node labyrinth environment in 20 minutes on a laptop.

One exciting finding of our work is the discovery of an "explore" goal map for the water-unrestricted mouse cohort. In general, exploration in animals is not well understood [23], yet our method offers an unsupervised approach for characterizing exploration from behavior alone. Future work could build upon the framework we present here in order to provide normative explanations for the nature of the explore map. Finally, relative to animals, it is often challenging to get artificial agents to explore in sparse reward environments [41]. With access to the internal reward function that motivates mice, we hope that our framework may be useful for inspiring better reward functions for training artificial agents to navigate in analogous environments (such as in [42] where artificial agents navigated in an analogous depth 6 binary tree environment).

We will now briefly discuss some limitations of our work. Firstly, our framework requires over a hundred trajectories to infer an animal's time-varying reward function. While it may be possible to reduce this number (with, for example, a careful choice of prior), it is easy to conceive of failure modes where a single decision reveals nothing about the active goal map. In practice, having access to multiple trajectories (or several decisions) can significantly reduce the uncertainty in the recovered time-varying weights and goal maps. Next, our approach may not scale well to high-dimensional state spaces, as we currently learn a separate reward for each state in each goal map. We don't anticipate this being a problem in the neuroscientific applications that we discuss in this work (where the state-space is 127 dimensional) but a straightforward extension of our framework could involve learning a state embedding (via a deep network), and then learning the time-varying rewards in this embedding space. Finally, our inferred rewards rely on the animal's policy being the Boltzmann policy of Eq. 3. However, assuming this form for the policy is not atypical in applications of reinforcement learning to human or animal decision-making data [13, 25]. Overall, we believe that the advantages of using our method far outweigh its limitations, and that we present a new, flexible framework for characterizing animal behavior in complex environments.

References

[1] Yael Niv. Reinforcement learning in the brain. *Journal of Mathematical Psychology*, 53 (3):139–154, June 2009. ISSN 0022-2496. doi: 10.1016/j.jmp.2008.12.005. URL `https://www.sciencedirect.com/science/article/pii/S0022249608001181`.

[2] Robert C Wilson and Anne GE Collins. Ten simple rules for the computational modeling of behavioral data. *eLife*, 8:e49547, November 2019. ISSN 2050-084X. doi: 10.7554/eLife.49547. URL `https://doi.org/10.7554/eLife.49547`. Publisher: eLife Sciences Publications, Ltd.

[3] K. H. Britten, M. N. Shadlen, W. T. Newsome, and J. A. Movshon. Responses of neurons in macaque MT to stochastic motion signals. *Visual Neuroscience*, 10(6):1157–1169, December 1993. ISSN 0952-5238. doi: 10.1017/s0952523800010269.

[4] Jerome R. Busemeyer and Julie C. Stout. A contribution of cognitive decision models to clinical assessment: decomposing performance on the Bechara gambling task. *Psychological assessment*, 14(3):253, 2002. Publisher: American Psychological Association.

[5] Eldad Yechiam, Jerome R. Busemeyer, Julie C. Stout, and Antoine Bechara. Using cognitive models to map relations between neuropsychological disorders and human decision-making deficits. *Psychological science*, 16(12):973–978, 2005. Publisher: SAGE Publications Sage CA: Los Angeles, CA.

[6] Joshua I. Gold and Michael N. Shadlen. The neural basis of decision making. *Annual Review of Neuroscience*, 30:535–574, 2007. ISSN 0147-006X. doi: 10.1146/annurev.neuro.29.051605.113038.

[7] Matteo Carandini and Anne K. Churchland. Probing perceptual decisions in rodents. *Nature Neuroscience*, 16(7):824–831, July 2013. ISSN 1546-1726. doi: 10.1038/nn.3410. URL `https://www.nature.com/articles/nn.3410`. Number: 7 Publisher: Nature Publishing Group.

[8] Peter Dayan and Nathaniel D. Daw. Decision theory, reinforcement learning, and the brain. *Cognitive, Affective, & Behavioral Neuroscience*, 8(4):429–453, December 2008. ISSN 1531-135X. doi: 10.3758/CABN.8.4.429. URL `https://doi.org/10.3758/CABN.8.4.429`.

[9] Laura Busse, Asli Ayaz, Neel T. Dhruv, Steffen Katzner, Aman B. Saleem, Marieke L. Schölvinck, Andrew D. Zaharia, and Matteo Carandini. The detection of visual contrast in the behaving mouse. *The Journal of Neuroscience: The Official Journal of the Society for Neuroscience*, 31(31):11351–11361, August 2011. ISSN 1529-2401. doi: 10.1523/JNEUROSCI.6689-10.2011.

[10] Felix A. Wichmann and N. Jeremy Hill. The psychometric function: I. Fitting, sampling, and goodness of fit. *Perception & Psychophysics*, 63(8):1293–1313, November 2001. ISSN 1532-5962. doi: 10.3758/BF03194544. URL `https://doi.org/10.3758/BF03194544`.

[11] Nathaniel D. Daw. Trial-by-trial data analysis using computational models. *Decision making, affect, and learning: Attention and performance XXIII*, 23(1), 2011. Publisher: Oxford University Press Oxford.

[12] Armin Lak, Emily Hueske, Junya Hirokawa, Paul Masset, Torben Ott, Anne E Urai, Tobias H Donner, Matteo Carandini, Susumu Tonegawa, Naoshige Uchida, and Adam Kepecs. Reinforcement biases subsequent perceptual decisions when confidence is low, a widespread behavioral phenomenon. *eLife*, 9:e49834, April 2020. ISSN 2050-084X. doi: 10.7554/eLife.49834. URL `https://doi.org/10.7554/eLife.49834`. Publisher: eLife Sciences Publications, Ltd.

[13] Charles Findling, Vasilisa Skvortsova, Rémi Dromnelle, Stefano Palminteri, and Valentin Wyart. Computational noise in reward-guided learning drives behavioral variability in volatile environments. *Nature neuroscience*, 22(12):2066–2077, 2019. Publisher: Nature Publishing Group.

[14] Dean Mobbs, Pete C. Trimmer, Daniel T. Blumstein, and Peter Dayan. Foraging for foundations in decision neuroscience: insights from ethology. *Nature Reviews Neuroscience*, 19(7):419–427, July 2018. ISSN 1471-0048. doi: 10.1038/s41583-018-0010-7. URL `https://www.nature.com/articles/s41583-018-0010-7`. Number: 7 Publisher: Nature Publishing Group.

[15] Matthew Rosenberg, Tony Zhang, Pietro Perona, and Markus Meister. Mice in a labyrinth show rapid learning, sudden insight, and efficient exploration. *eLife*, 10:e66175, July 2021. ISSN 2050-084X. doi: 10.7554/eLife.66175. URL `https://doi.org/10.7554/eLife.66175`. Publisher: eLife Sciences Publications, Ltd.

[16] Gautam Reddy. Reinforcement waves as a mechanism for discontinuous learning. Technical report, bioRxiv, May 2022. URL `https://www.biorxiv.org/content/10.1101/2022.05.06.490910v1`. Section: New Results Type: article.

[17] Andrew Y. Ng and Stuart J. Russell. Algorithms for inverse reinforcement learning. In *Icml*, volume 1, page 2, 2000.

[18] Pieter Abbeel and Andrew Y. Ng. Apprenticeship learning via inverse reinforcement learning. In *Proceedings of the twenty-first international conference on Machine learning*, page 1, 2004.

[19] Brian D. Ziebart, Andrew Maas, J. Andrew Bagnell, and Anind K. Dey. Maximum entropy inverse reinforcement learning. In *Proc. AAAI*, pages 1433–1438, 2008.

[20] Pieter Abbeel, Adam Coates, Morgan Quigley, and Andrew Ng. An Application of Reinforcement Learning to Aerobatic Helicopter Flight. In *Advances in Neural Information Processing Systems*, volume 19. MIT Press, 2006. URL `https://proceedings.neurips.cc/paper/2006/hash/98c39996bf1543e974747a2549b3107c-Abstract.html`.

[21] Adam Coates, Pieter Abbeel, and Andrew Y. Ng. Learning for control from multiple demonstrations. In *Proceedings of the 25th international conference on Machine learning - ICML '08*, pages 144–151, Helsinki, Finland, 2008. ACM Press. ISBN 978-1-60558-205-4. doi: 10.1145/1390156.1390175. URL `http://portal.acm.org/citation.cfm?doid=1390156.1390175`.

[22] Alex J. Chan and Mihaela van der Schaar. Scalable bayesian inverse reinforcement learning. *arXiv preprint arXiv:2102.06483*, 2021.

[23] Robert N Hughes. Intrinsic exploration in animals: motives and measurement. *Behavioural Processes*, 41(3):213–226, December 1997. ISSN 0376-6357. doi: 10.1016/S0376-6357(97)00055-7. URL `https://www.sciencedirect.com/science/article/pii/S0376635797000557`.

[24] Florian Kattner, Aaron Cochrane, and C. Shawn Green. Trial-dependent psychometric functions accounting for perceptual learning in 2-AFC discrimination tasks. *Journal of Vision*, 17(11):3, September 2017. ISSN 1534-7362. doi: 10.1167/17.11.3.

[25] Amir Dezfouli, Kristi Griffiths, Fabio Ramos, Peter Dayan, and Bernard W. Balleine. Models that learn how humans learn: The case of decision-making and its disorders. *PLOS Computational Biology*, 15(6):e1006903, June 2019. ISSN 1553-7358. doi: 10.1371/journal.pcbi.1006903. URL `https://journals.plos.org/ploscompbiol/article?id=10.1371/journal.pcbi.1006903`. Publisher: Public Library of Science.

[26] Nicholas A. Roy, Ji Hyun Bak, Athena Akrami, Carlos D. Brody, and Jonathan W. Pillow. Extracting the dynamics of behavior in sensory decision-making experiments. *Neuron*, 109 (4):597–610.e6, February 2021. ISSN 0896-6273. doi: 10.1016/j.neuron.2020.12.004. URL https://www.sciencedirect.com/science/article/pii/S0896627320309636.

[27] Zoe C. Ashwood, Nicholas A. Roy, Iris R. Stone, Anne E. Urai, Anne K. Churchland, Alexandre Pouget, and Jonathan W. Pillow. Mice alternate between discrete strategies during perceptual decision-making. *Nature Neuroscience*, 25(2):201–212, February 2022. ISSN 1546-1726. doi: 10.1038/s41593-021-01007-z. URL https://www.nature.com/articles/s41593-021-01007-z. Number: 2 Publisher: Nature Publishing Group.

[28] Matthias Schultheis, Dominik Straub, and Constantin A. Rothkopf. Inverse Optimal Control Adapted to the Noise Characteristics of the Human Sensorimotor System. October 2021. doi: 10.48550/arXiv.2110.11130. URL https://arxiv.org/abs/2110.11130v1.

[29] Shoichiro Yamaguchi, Honda Naoki, Muneki Ikeda, Yuki Tsukada, Shunji Nakano, Ikue Mori, and Shin Ishii. Identification of animal behavioral strategies by inverse reinforcement learning. *PLOS Computational Biology*, 14(5):e1006122, May 2018. ISSN 1553-7358. doi: 10.1371/journal.pcbi.1006122. URL https://journals.plos.org/ploscompbiol/article?id=10.1371/journal.pcbi.1006122. Publisher: Public Library of Science.

[30] Markus Wulfmeier, Peter Ondruska, and Ingmar Posner. Maximum entropy deep inverse reinforcement learning. *arXiv preprint arXiv:1507.04888*, 2015.

[31] Chelsea Finn, Sergey Levine, and Pieter Abbeel. Guided cost learning: Deep inverse optimal control via policy optimization. In *International conference on machine learning*, pages 49–58. PMLR, 2016.

[32] Yunzhu Li, Jiaming Song, and Stefano Ermon. Infogail: Interpretable imitation learning from visual demonstrations. *arXiv preprint arXiv:1703.08840*, 2017.

[33] Monica Babes-Vroman, Vukosi Marivate, Kaushik Subramanian, and Michael L. Littman. Apprenticeship learning about multiple intentions. In *ICML*, 2011.

[34] Jaedeug Choi and Kee-Eung Kim. Nonparametric bayesian inverse reinforcement learning for multiple reward functions. In *NIPS*, 2012.

[35] Amit Surana and Kunal Srivastava. Bayesian nonparametric inverse reinforcement learning for switched markov decision processes. In *2014 13th International Conference on Machine Learning and Applications*, pages 47–54, 2014. doi: 10.1109/ICMLA.2014.105.

[36] James S. Hodges and Daniel J. Sargent. Counting degrees of freedom in hierarchical and other richly-parameterised models. *Biometrika*, 88(2):367–379, 06 2001. ISSN 0006-3444. doi: 10.1093/biomet/88.2.367. URL https://doi.org/10.1093/biomet/88.2.367.

[37] Tuomas Haarnoja, Haoran Tang, Pieter Abbeel, and Sergey Levine. Reinforcement learning with deep energy-based policies. 2017.

[38] Divyansh Garg, Shuvam Chakraborty, Chris Cundy, Jiaming Song, and Stefano Ermon. IQ-Learn: Inverse soft-Q Learning for Imitation. *arXiv:2106.12142 [cs]*, December 2021. URL http://arxiv.org/abs/2106.12142. arXiv: 2106.12142.

[39] Martin Ester, Hans-Peter Kriegel, and Xiaowei Xu. A Density-Based Algorithm for Discovering Clusters in Large Spatial Databases with Noise. page 6, 1996.

[40] Yiren Lu. IRL-Imitation, 2017. URL https://github.com/yrlu/irl-imitation.

[41] Deepak Pathak, Pulkit Agrawal, Alexei A. Efros, and Trevor Darrell. Curiosity-driven exploration by self-supervised prediction. In Doina Precup and Yee Whye Teh, editors, *Proceedings of the 34th International Conference on Machine Learning*, volume 70 of *Proceedings of Machine Learning Research*, pages 2778–2787. PMLR, 06–11 Aug 2017. URL `https://proceedings.mlr.press/v70/pathak17a.html`.

[42] Runzhe Yang, Xingyuan Sun, and Karthik Narasimhan. A Generalized Algorithm for Multi-Objective Reinforcement Learning and Policy Adaptation. *arXiv:1908.08342 [cs]*, November 2019. URL `http://arxiv.org/abs/1908.08342`. arXiv: 1908.08342.