ONLINE CONTINUAL LEARNING ON CLASS INCREMENTAL BLURRY TASK CONFIGURATION WITH ANYTIME INFERENCE

ABSTRACT

Despite rapid advances in continual learning, a large body of research is devoted to improving performance in the existing setups. While a handful of work do propose new continual learning setups, they still lack practicality in certain aspects. For better practicality, we first propose a novel continual learning setup that is online, task-free, class-incremental, of blurry task boundaries and subject to inference queries at any moment. We additionally propose a new metric to better measure the performance of the continual learning methods subject to inference queries at any moment. To address the challenging setup and evaluation protocol, we propose an effective method that employs a new memory management scheme and novel learning techniques. Our empirical validation demonstrates that the proposed method outperforms prior arts by large margins.

1 INTRODUCTION

Continual learning (CL) is a learning scenario where a model learns from a continuous and online stream of data and is regarded as a more realistic and practical learning setup than offline learning on a fixed dataset (He et al., 2020). However, many CL methods still focus on the offline setup (Kirkpatrick et al., 2017; Rebuffi et al., 2017; Saha et al., 2021) instead of the more realistic online setup. These methods assume access to a large storage, storing the entire data of the current task and iterating on it multiple times. On the other hand, we are interested extensively in the more realistic online setup where only a small memory is allowed as storage. Meanwhile, even for the online CL methods, we argue they have room for more practical and realistic improvements concerning multiple crucial aspects. The aspects include the class distributions such as the disjoint (Rebuffi et al., 2017) or the blurry (Aljundi et al., 2019c) splits and the evaluation metric that focuses only on the task accuracy such as average task accuracy (A_{avg}).

The two main assumptions on the class distributions in existing CL setups, *i.e.* , the disjoint and blurry splits, are less realistic for the following reasons. The disjoint split assumes no classes overlap over different tasks; already observed classes will never appear again. This assumption is not plausible because already observed classes can still appear later on in real-world scenarios (see Fig. 2 of (Bang et al., 2021)). On the other hand, in the blurry split (Aljundi et al., 2019c) no new classes appear after the first task even though the split assumes overlapping classes over tasks. This is also not plausible as observing new classes is common in real-world scenarios.

The typical evaluation metric such as A_{avg} in which the accuracy is measured only at the task transition is also less realistic. It implicitly assumes that no inference queries occur in the middle of a task. However, in real-world scenarios, inference queries can occur *at any-time*. Moreover, there is no explicit task transition boundary in most real-world scenarios. Thus, it is desirable for CL models to provide good inference results at any time. To accurately evaluate whether a CL model is effective at such 'any-time' inference, we need a new metric for CL models.

In order to address the issues of the current CL setups, we propose a new CL setup that is more realistic and practical by considering the following criteria: First, the class distribution is comprised of the advantages from both blurry and disjoint. That is, we assume that the model continuously encounters new classes as tasks continue, *i.e.* , class-incremental and that classes overlap across tasks, *i.e.* , blurry task boundaries, while not suffering from the restrictions of blurry and disjoint.

Second, the model is evaluated throughout training and inference such that it can be evaluated for any-time inference. We call this new continual learning setup **'i-Blurry'**.

For the i-Blurry setup, we first propose a plausible baseline that employs experience replay (ER) with reservoir sampling and a learning rate scheduling tuned for the online and task-free CL setting. While existing online CL methods are applicable to the i-Blurry setup, they perform only marginally better than our baseline or often worse.

To better handle the i-Blurry setup, we propose a novel continual learning method, which improves the baseline in three aspects. We design a new memory management scheme to discard samples using a per-sample importance score that reflects how useful a sample is for training. We then propose to draw training samples only from the memory instead of drawing them from both memory and the online stream as is done in ER. Finally, we propose a new learning rate scheduling to adaptively decide whether to increase or decrease the learning rate based on the loss trajectory, *i.e.* a data-driven manner. To evaluate the algorithms in the new setup, we evaluate methods by conventional metrics, and further define a new metric called 'area under the curve of accuracy' (A_{AUC}) which measures the model's accuracy throughout training.

We summarize our contributions as follows:

- Proposing a new CL setup called i-Blurry, which addresses a more realistic setting that is online, task-free, class-incremental, of blurry task boundaries, and subject to any-time inference.
- Proposing a novel online and task-free CL method by a new memory management, memory usage, and learning rate scheduling strategy.
- Outperforming existing CL models by large margins on multiple datasets and settings.
- Proposing a new metric to better measure a CL model's capability for the desirable any-time inference.

2   RELATED WORK

Continual learning setups. There are many CL setups that have been proposed to reflect the real-world scenario of training a learning model from a stream of data (Prabhu et al., 2020). We categorize them in the following aspects for brevity.

First, we categorize them into (1) task-incremental (*task-IL*) and (2) class-incremental learning (*class-IL*), depending on whether the task-ID is given at test time. Task-IL, also called multi-head setup, assumes that task-ID is given at test time (Lopez-Paz & Ranzato, 2017; Aljundi et al., 2018; Chaudhry et al., 2019). In contrast, in class-IL, or single-head setup, task-ID is not given at test time and has to be inferred (Rebuffi et al., 2017; Wu et al., 2019; Aljundi et al., 2019a). Class-IL is more challenging than task-IL, but is also more realistic since task-ID will not likely be given in the real-world scenario (Prabhu et al., 2020). Most CL works assume that task ID is provided at training time, allowing CL methods to utilize the task ID to save model parameters at task boundaries (Kirkpatrick et al., 2017; Chaudhry et al., 2018) for later use. However, this assumption is impractical (Lee et al., 2019) since real-world data usually do not have clear task boundaries. To address this issue,, a task-free setup (Aljundi et al., 2019b), where task-ID at training is not available, has been proposed. We focus extensively on the task-free setup as it is challenging and being actively investigated recently (Kim et al., 2020; Lee et al., 2019; Aljundi et al., 2019c).

We now categorize CL setups into *disjoint* and *blurry* setup by how the data split is configured. In the disjoint task setup, each task consists of a set of classes disjoint from all other tasks. But the disjoint setup is less realistic as the classes in the real-world can appear at any time not only in a disjoint manner. Recently, to make the setup more realistic, a blurry task setup has been proposed and investigated (Aljundi et al., 2019c; Prabhu et al., 2020; Bang et al., 2021), where $100 - M\%$ of the sampels are from the dominant class of the task and $M\%$ of the samples are from all classes, where M is the blurry level (Aljundi et al., 2019c). However, the blurry setup assumes *no class is added* in new tasks, *i.e.* , not class-incremental, which makes the setup still not quite realistic.

Finally, depending on how many samples are streamed at a time, we categorize CL setups into *online* (Rolnick et al., 2018; Aljundi et al., 2019a; Chaudhry et al., 2019) and *offline* (Wu et al., 2019; Rebuffi et al., 2017; Chaudhry et al., 2018; Castro et al., 2018). In the offline setup, all data from the current task can be used an unlimited number of times. This is impractical since it requires additional memory of size equal to the current task's data. For the online setup, there are many

notions of 'online' that differs in each literature. Prabhu et al. (2020); Bang et al. (2021) refer online to a setup using each streamed sample *only once* to train a model while Aljundi et al. (2019c;a) refer online to a setup where only one or a few samples are streamed at a time. We follow the latter as the former allows storing the whole task's data, which is similar to offline and more unrealistic than using the sample more than a few times.

Incorporating the pros and cons of existing setups, we propose a novel CL setup that is online, task-free, class-incremental, of blurry task boundaries, and subject to any-time inference as the most realistic setup for continual learning.

Continual learning methods. Given neural networks would suffer from catastrophic forgetting (McCloskey & Neal, 1989; Ratcliff, 1990), the online nature of streaming data in continual learning generally aggravates the issue. To alleviate the forgetting, there are various proposals to store the previous task information; (1) regularization, (2) replay, and (3) parameter isolation.

(1) Regularization methods (Kirkpatrick et al., 2017; Zenke et al., 2017; Lee et al., 2017b; Ebrahimi et al., 2020) store previous task information in the form of model priors and use it for regularizing the neural network currently being trained. (2) Replay methods store a subset of the samples from the previous tasks in an *episodic memory* (Rebuffi et al., 2017; Castro et al., 2018; Chaudhry et al., 2019; Wu et al., 2019) or keep a generative model that is trained to generate previous task samples (Shin et al., 2017; Wu et al., 2018; Hu et al., 2019; Cong et al., 2020). The sampled or generated examplars are replayed on future tasks and used for distillation, constrained training, or joint training. (3) Parameter isolation methods augment the networks (Rusu et al., 2016; Lee et al., 2017a; Aljundi et al., 2017) or decompose the network into subnetworks for each task (Mallya & Lazebnik, 2018; Cheung et al., 2019; Yoon et al., 2020).

Since (1), (2), and (3) all utilize different ways of storing information that incurs parameter storage costs, episodic memory requirement and increase in network size respectively, a fair comparison among the methods is not straighforward. We mostly compare our method with episodic memory-based methods (Wu et al., 2019; Aljundi et al., 2019a; Bang et al., 2021), as they perform the best in various CL setups but also with methods that use both regularization and episodic memory (Chaudhry et al., 2018; Wu et al., 2019).

Online continual learning. Despite being more realistic (Losing et al., 2018; He et al., 2020), online CL setups have not been popular (Prabhu et al., 2020) due to the difficulty and subtle differences in the setups in the published literature. ER (Rolnick et al., 2018) is a simple yet strong episodic memory-based online CL method. It employs reservoir sampling for memory management and jointly trains a model with half of the batch sampled from memory. Many online CL methods are based on ER (Aljundi et al., 2019c;a). GSS (Aljundi et al., 2019c) selects samples using a score based on cosine similarity of gradients. MIR (Aljundi et al., 2019a) retrieves maximally interfering samples from memory to use for training.

Different from ER, A-GEM (Chaudhry et al., 2019) uses the memory to enforce constraints on the loss trajectory of the stored samples. GDumb (Prabhu et al., 2020) only updates the memory during training phase and trains from scratch at the test time only using the memory.

Unlike these methods, recently proposed RM (Bang et al., 2021) uses an uncertainty-based memory sampling and two-stage training scheme where the model is trained for one epoch on the streamed samples and trains extensively only using the memory at the end of each task, effectively delaying most of the learning to the end of the tasks. Note that the uncertainty-based memory sampling cannot be implemented in the online CL setup and the two-stage training performs particularly worse in our i-Blurry setup. Our method outperforms all other online CL method introduced in this section while strictly adhering to the online and task-free restrictions.

3 PROPOSED CONTINUAL LEARNING SETUP: I-BLURRY

For a more realistic and practical CL setup, considering real-world scenarios, we strictly adhere to the online and task-free CL setup (Lee et al., 2019; Losing et al., 2018). Specifically, we propose a novel CL setup (named as **i-Blurry**), with two characteristics: 1) class distribution being class incremental and having blurry task boundaries and 2) allowing for any-time inference.

Figure 1: i-Blurry-N-M split. $N\%$ of classes are partitioned into the disjoint set and the rest into the Blurry$M$ set where M denotes the blurry level (Aljundi et al., 2019c). To form the i-Blurry-N-M task splits, we draw training samples from a uniform distribution from the 'disjoint' or the 'Blurry$M$' set (Aljundi et al., 2019c). The 'blurry' classes always appear over the tasks while disjoint classes gradually appears.

(a) Rainbow Memory (RM) (Bang et al., 2021)   (b) CLIB

Figure 2: Comparison of A_{AUC} with A_{avg}. (a) online version of RM (Bang et al., 2021) (b) proposed CLIB. The two-stage method delays most of the training to the end of the task. The accuracy-to-{# of samples} plot shows that our method is more effective at any time inference than the two-stage method. The difference in A_{avg} for the two methods is much smaller than that of in A_{AUC}, implying that A_{AUC} captures the effectiveness at any-time inference better.

i-Blurry-N-M Split. We partition the classes into groups where $N\%$ of the classes are for disjoint and the rest of $100-N\%$ of the classes are used for Blurry$M$ sampling (Aljundi et al., 2019c), where M is the blurry level. Once we determine the partition, we draw samples from the partitioned groups. We call the resulting sequence of tasks as **i-Blurry-N-M** split. The i-Blurry-N-M splits feature both class-incremental and blurry task boundaries. Note that the i-Blurry-N-M splits generalize previous CL setups. For instance, $N = 100$ is the disjoint split as there are no blurry classes. $N = 0$ is the Blurry$M$ split (Aljundi et al., 2019c) as there are no disjoint classes. $M = 0$ is the disjoint split as the blurry level is $M = 0$ (Bang et al., 2021). We use multiple i-Blurry-N-M splits for reliable empirical validations and share the splits for reproducible research. Fig. 1 illustrates the i-Blurry-N-M split.

A New Metric: Area Under the Curve of Accuracy (A_{AUC}). Average accuracy (*i.e.*, $A_{avg} = \frac{1}{T}\sum_{i=1}^{T} A_i$ where A_i is the accuracy at the end of the i[th] task) is one of the widely used measures in continual learning. But A_{avg} only tells us how good a CL model is at the few discrete moments of task transitions ($5 - 10$ times for most CL setups) when the model could be queried at any time. Thus, a CL method could be poor at any-time inference but the A_{avg} may be insufficient to deduce that conclusion due to its temporal sparsity of measurement. For example, Fig. 2 compares the online version of RM (Bang et al., 2021), which conducts most of the training by iterating over the memory at the end of a task, with our method. RM is shown as it is a very recent method that performs well on A_{avg} but particularly poor at any-time inference. Only evaluating with A_{avg} might give the false sense that the difference between the two methods is not severe. However, the accuracy-to-{# of samples} curve reveals that our method shows much more consistently high accuracy during training, implying that our method is more suitable for any-time inference than RM. To alleviate the limitations of A_{avg}, we shorten the accuracy measuring frequency to after every Δn samples are observed instead of at discrete task transitions. The new metric is equivalent to the area under the curve (AUC) of the accuracy-to-{# of samples} curve for CL methods when $\Delta n = 1$ We

Figure 3: Overview of the proposed CLIB. We compute sample-wise importance during training to manage our memory. Note that we only draw training samples from the memory whereas ER based methods draw them from both the memory and the online stream.

call it area under the curve of accuracy (A_{AUC}):

$$A_{\text{AUC}} = \sum_{i=1}^{k} f(i \cdot \Delta n) \cdot \Delta n, \qquad (1)$$

where the step size Δn is the number of samples observed between inference queries and $f(\cdot)$ is the curve in the accuracy-to-{# of samples} plot. High A_{AUC} corresponds to a CL method that consistently maintains high accuracy throughout training.

The large difference in A_{AUC} between the two methods in Fig. 4 implies that delaying strategies like the two-stage training scheme are not effective for any-time inference, a conclusion which is harder to deduce with just A_{avg}.

4 METHOD

4.1 A BASELINE FOR I-BLURRY SETUP

To address the realistic i-Blurry setup, we first establish a baseline by considering a memory management policy and a learning rate scheduling scheme for the challenging online and task-free i-Blurry setup. For the memory management policy, we use reservoir sampling (Vitter, 1985) as it is widely used in the online and task-free setups with good performance. Note that in online CL, memory management policies that use the entire task's samples at once, such as herding selection (Rebuffi et al., 2017), mnemonics (Liu et al., 2020), and rainbow memory (Bang et al., 2021) are inapplicable. For the memory usage, we use the experience replay (ER) method of drawing half of the training batch from the stream and the other half from the memory, following a large number of online CL methods based on ER with good performance (Mai et al., 2021).

For the LR scheduling, other CL methods use either (1) use exponential decay (Rebuffi et al., 2017; Kirkpatrick et al., 2017; Mirzadeh et al., 2020) or (2) constant LR. We do not use (1) as it is hyperparameter sensitive; the decay rate that works for CIFAR10 decayed the LR too quickly for larger datasets such as CIFAR100. If the LR is decayed too fast, the LR becomes too small to learn about new classes that are introduced in the future. Thus, we use an exponential LR schedule but reset the LR when a new class is encountered. Comparing with the constant LR, we obtain slightly better performance for EWC++ and our baseline on CIFAR10, as shown in Table 8. Thus, we denote this LR schedule as the exponential with reset and use it in our baseline.

Note that the above baseline still has room to improve. The reservoir sampling does not consider whether one sample could be more useful for training than the others. ER uses samples from the stream directly, which can skew the training of CL models to recently observed samples. While the exponential with reset does increase the LR periodically, the sudden changes may disrupt the CL model. Thus, we discuss how we can improve the baseline in the following sections. The final method with all the improvements is illustrated in Fig. 3.

4.2 SAMPLE-WISE IMPORTANCE BASED MEMORY MANAGEMENT

In reservoir sampling, the samples are removed from the memory at random. Arguing that considering all samples equal in the removal process would lead to training efficacy decreases, we propose a new sampling strategy that removes samples from the memory based on sample-wise importance as following Theorem 1.

Theorem 1. *Let $\mathcal{C} = \mathcal{M} \cup \{(x_{new}, y_{new})\}$, $\mathcal{M}$ be a memory from the previous time step, (x_{new}, y_{new}) be the newly encountered sample, $l(\cdot)$ be the loss and θ be the model parameters. Assuming that the model trained with the optimal memory, $\mathcal{M}^*$ will induce maximal loss decrease on $\mathcal{C}$, the optimal memory is given by $\mathcal{M}^* = \mathcal{C} \setminus \{(\bar{x}, \bar{y})\}$ with*

$$(\bar{x}, \bar{y}) = \underset{(x_i, y_i) \in \mathcal{C}}{\arg\min} \, \mathbb{E}_\theta \left[\sum_{(x,y) \in \mathcal{C}} l(x, y; \theta) - l(x, y; \theta - \nabla_\theta l(x_i, y_i; \theta)) \right]. \tag{2}$$

Proof. Please see Sec. A.1 for the proof. □

We solve Eq. 2 by keeping track of the sample-wise importance $\mathcal{H}_i$

$$\mathcal{H}_i = \mathbb{E}_\theta \left[\sum_{(x,y) \in \mathcal{C}} l(x, y; \theta) - l(x, y; \theta - \nabla_\theta l(x_i, y_i; \theta)) \right]. \tag{3}$$

Intuitively, $\mathcal{H}$ is the expected loss decrease when the associated sample is used for training. We update $\mathcal{H}$ associated with the samples used for training after every training iteration.

For computational efficiency, we use empirical estimates instead of precise computation of the expectation. The empirical estimates are calculated by the discounted sum of the differences between the actual loss decrease and the predicted loss decrease (see Alg. 1). The memory is updated whenever a new sample is encountered, and the full process is given in Alg. 2. The memory management strategy significantly outperforms reservoir sampling, especially with memory only training.

4.3 Memory Only Training

ER uses joint training where half of the training batch is obtained from the online stream and the other half from memory. However, we argue that using the streamed samples directly will cause the model to be easily affected by them, which skews the training to favor the recent samples more. Thus, we propose to use samples only from the memory for training, without using the streamed samples. The memory works as a distribution stabilizer for streamed samples through the memory update process (see Sec. 4.2), and samples are used for training only with the memory. We observe that the memory only training improves the performance despite its simple nature. Note that this is different from Prabhu et al. (2020) as we train with the memory during the online stream but Prabhu et al. (2020) does not.

4.4 Adaptive Learning Rate Scheduling

The exponential with reset scheduler resets the LR to the initial value when a new class is encountered. As the reset occurs regardless of the current LR value, it could result in a large change in LR value. We argue that such abrupt changes may harm the knowledge learned from previous samples.

Instead, we propose a new data-driven LR scheduling scheme that adaptively increases or decreases the LR based on how good the LR is for optimizing over the memory. Specifically, it decides which of the increasing or decreasing direction for the LR is better in a data-driven manner. The loss decrease is measured for a high and low value of LR and the direction in which the loss decreased more is chosen using a Student's t-test. The LR is altered in the chosen direction by a small amount. We depict this scheme in Alg. 3 in Sec. A.3.

With all the proposed components, we call our method **Continual Learning for i-Blurry** or (**CLIB**).

5 Experiments

Experimental Setup. We use the CIFAR10, CIFAR100, and TinyImageNet datasets for empirical validations. We use the i-Blurry setup with $N = 50$ and $M = 10$ (i-Blurry-50-10) for our experiments unless otherwise stated. All results are averaged over 3 independent runs. For metrics, we use the average accuracy (A_{avg}) and the proposed A_{AUC} (see Sec. 3). Additional discussion with other metrics such as the forgetting measure (F_5) can be found in Sec. A.8.

Methods	CIFAR10		CIFAR100		TinyImageNet	
	A_{AUC}	A_{avg}	A_{AUC}	A_{avg}	A_{AUC}	A_{avg}
EWC++ (Kirkpatrick et al., 2017)	57.06±1.63	59.96±3.18	35.26±1.82	39.35±1.50	20.63±1.02	22.89±1.11
BiC (Wu et al., 2019)	52.35±1.85	54.94±1.81	26.26±0.92	29.90±1.03	16.68±1.95	20.19±1.35
ER-MIR (Aljundi et al., 2019a)	57.65±2.49	61.15±3.74	34.49±2.29	37.95±2.05	21.07±0.89	22.89±0.71
GDumb (Prabhu et al., 2020)	53.20±1.93	55.27±2.69	32.84±0.45	34.03±0.89	18.17±0.19	18.69±0.45
RM† (Bang et al., 2021)	22.77±1.55	60.73±1.03	8.62±0.64	32.09±0.99	3.67±0.03	11.35±0.12
Baseline-ER (Sec. 4.1)	56.96±1.97	60.22±3.04	34.26±1.66	38.99±1.31	21.37±1.01	23.65±1.22
CLIB (Ours)	**70.32±1.22**	**74.00±0.72**	**46.73±1.13**	**49.53±1.18**	**23.78±0.66**	**24.79±0.21**

Table 1: Comparison of various online CL methods on the i-Blurry setup for CIFAR10, CIFAR100, and TinyImageNet are shown. CLIB outperforms all other CL methods by large margins on both the A_{AUC} and the A_{avg}.

Figure 4: Accuracy-to-{number of samples} for various CL methods on CIFAR10, CIFAR100, and TinyImageNet. Our CLIB is consistent at maintaining high accuracy throughout inference while other CL methods are not as consistent.

Implementation Details. For all methods, we fix the batch size and the number of updates per streamed samples observed when possible. For CIFAR10, we use a batch size of 16 and 1 updates per streamed sample. When using ER, this translates to 8 updates using the same streamed batch, since each batch contains 8 streamed samples. For CIFAR100, we use a batch size of 16 and 3 updates per streamed sample. For TinyImageNet, we use a batch size of 32 and 3 updates per streamed sample.

We use ResNet-18 as the model for CIFAR10 and ResNet-34 for CIFAR100 and TinyImageNet. For all methods, we apply AutoAugment (Cubuk et al., 2019) and CutMix (Yun et al., 2019) as data augmentation, following RM (Bang et al., 2021). For memory size, we use 500, 2000, 4000 for CIFAR10, CIFAR100, TinyImageNet, respectively. Additional analysis on the sample memory size can be found in Sec. A.5. Adam optimizer with initial LR of 0.0003 is used. Exponential with reset LR schedule is applied for all methods except ours and GDumb, with $\gamma = 0.9999$ for CIFAR datasets and $\gamma = 0.99995$ for TinyImageNet. Ours use adaptive LR with $\gamma = 0.95, m = 10$ for all datasets, GDumb (Prabhu et al., 2020) and RM (Bang et al., 2021) follow original settings in their respective paper. All code and i-Blurry-N-M splits (see Supp.) will be publicly released.

Baselines. We compare our method with both online CL methods and ones that can be extended to the online setting; EWC++ (Chaudhry et al., 2018), BiC (Wu et al., 2019), GDumb (Prabhu et al., 2020), A-GEM (Chaudhry et al., 2019), MIR (Aljundi et al., 2019a) and RM (Bang et al., 2021). $\cdot^\dagger$ indicates that the two-stage training scheme (Bang et al., 2021) is used. For details of the online versions of these methods, see Sec. A.4. Note that A-GEM performs particularly worse (also observed in (Prabhu et al., 2020; Mai et al., 2021)) as A-GEM was designed for the task-incremental setup and our setting is task-free. We discuss the comparisons to A-GEM in Sec. A.6.

5.1 RESULTS ON THE I-BLURRY SETUP

In all our experiments, we denote the best result for each of the metrics in **bold**.

We first compare various online CL methods in the i-Blurry setup on CIFAR10, CIFAR100, and TinyImageNet in Table 1. On CIFAR10, proposed CLIB outperforms all other CL methods by large margins; at least +12.55% in A_{AUC} and +13.31% in A_{avg}. On CIFAR100, CLIB also outperforms all other methods by large margins; at least +12.29% in A_{AUC} and +9.51% in A_{avg}. On TinyIm-

Varying N	$N = 0$ (Blurry)		$N = 50$ (i-Blurry)		$N = 100$ (Disjoint)	
	A_{AUC}	A_{avg}	A_{AUC}	A_{avg}	A_{AUC}	A_{avg}
EWC++	52.32±0.76	56.41±1.18	57.06±1.63	59.96±3.18	77.57±2.18	78.34±2.33
BiC	45.73±0.86	49.08±1.40	52.35±1.85	54.94±1.81	76.47±0.87	**78.84±2.06**
ER-MIR	51.79±1.25	56.84±0.34	57.65±2.49	61.15±3.74	76.56±1.78	78.36±2.25
GDumb	45.86±0.80	46.37±2.09	53.20±1.93	55.27±2.69	65.27±1.54	66.74±2.39
RM†	20.81±2.85	50.61±2.21	22.77±1.55	60.73±1.03	34.06±4.80	64.01±5.33
Baseline-ER	52.55±0.71	56.84±1.38	56.96±1.97	60.22±3.04	77.65±2.17	78.43±2.29
CLIB (Ours)	**68.64±0.66**	**72.99±0.68**	**70.32±1.22**	**74.00±0.72**	**78.37±2.09**	78.00±1.48

Varying M	$M = 10$		$M = 30$		$M = 50$	
	A_{AUC}	A_{avg}	A_{AUC}	A_{avg}	A_{AUC}	A_{avg}
EWC++	57.06±1.63	59.96±3.18	65.90±2.57	69.83±3.07	68.44±0.65	73.71±1.31
BiC	52.35±1.85	54.94±1.81	59.31±2.91	63.89±4.06	61.55±1.02	67.81±1.07
ER-MIR	57.65±2.49	61.15±3.74	66.58±1.78	71.22±2.93	68.18±0.44	73.35±0.04
GDumb	53.20±1.93	55.27±2.69	54.73±1.54	54.63±2.39	53.86±0.59	52.82±1.24
RM†	22.77±1.55	60.73±1.03	26.50±2.43	61.36±3.12	27.83±2.65	58.43±3.13
Baseline-ER	56.96±1.97	60.22±3.04	65.94±2.53	70.74±2.70	68.78±0.64	73.92±1.36
CLIB (Ours)	**70.32±1.22**	**74.00±0.72**	**74.84±1.93**	**77.84±1.40**	**74.94±1.22**	**78.19±1.87**

Table 2: Analysis on various values of N (top) and M (bottom) in the i-Blurry-N-M setup using CIFAR10 dataset. For varying N, we use $M = 10$. For varying M, we use $N = 50$. Note that $N = 0$ corresponds to the blurry split and $N = 100$ corresponds to the disjoint split. For $N = 100$, CLIB outperforms or performs on par with other CL methods. For $N = 0$, the gap between CLIB and other methods widens. For $N = 50$, CLIB again outperforms all comparisons by large margins. For varying M, CLIB outperforms all comparisons excepting only the A_{avg} when $M = 0$.

ageNet, all methods score very low; the i-Blurry setup for TinyImageNet is challenging as it has 200 classes instead of 100 of CIFAR100 but has the same number of samples per class and the total training duration and task length is doubled from CIFAR10 and CIFAR100 which makes continually learning more difficult. Nonetheless, CLIB outperforms other CL methods by at least +2.91% in A_{AUC} and +2.17% in A_{avg}. Since, CLIB uses memory only training scheme, the distribution of the training samples are stabilized through the memory (see Sec. 4.3) which is helpful in the i-Blurry setup where the model encounters samples from more varied classes.

Note that Rainbow Memory (RM) (Bang et al., 2021) exhibits a very different trend than other compared methods. On TinyImageNet, it performs poorly. We conjecture that the delayed learning from the two-stage training is particularly detrimental in larger datasets with longer training duration and tasks such as TinyImageNet. On CIFAR10 and CIFAR100, RM performs reasonably well in A_{avg} but poorly in A_{AUC}. This verifies that its two-stage training method delays most of the learning to the end of each task, resulting in a poor any-time inference performance measured by A_{AUC}. Note that A_{avg} fails to capture this; on CIFAR10, the difference in A_{avg} for CLIB and RM is +13.27% which is similar to other methods but the difference for A_{AUC} is +47.55% which is noticeably larger than other methods. Similar trends can be found on CIFAR100 as well.

We also show the accuracy-to-{# of samples} curve for the CL methods on CIFAR10, CIFAR100, and TinyImageNet for comprehensive analysis throughout training in Fig 4. Interestingly, RM shows a surged accuracy only at the task transitions due to the two-stage training method it uses and the accuracy is overall low. Additionally, GDumb show a decreasing trend in accuracy as tasks progress as opposed to other methods. It is because the 'Dumb Learner' trains from scratch at every inference query leading to accuracy degradation. In contrast, CLIB not only outperforms other methods but also shows the most consistent accuracy at all times.

5.2 ANALYSIS ON DISJOINT CLASS PERCENTAGES (N) AND BLURRY LEVELS (M).

We further investigate the effect of different N and M values in the i-Blurry-N-M splits with various CL methods and summarize the results for varying values of the disjoint class percentages such as $N = 0, 50, 100$ in Table 2 (top). For $N = 0$, CLIB outperforms other methods by at least +16.59%

Methods	CIFAR10		CIFAR100	
	A_{AUC}	A_{avg}	A_{AUC}	A_{avg}
CLIB	**70.32±1.22**	**74.00±0.72**	**46.73±1.13**	**49.53±1.18**
w/o Sample Importance Mem. (Sec.4.2)	53.75±2.11	56.31±2.56	36.59±1.22	38.59±1.21
w/o Memory-only training (Sec.4.3)	67.06±1.51	71.65±1.87	44.63±0.22	48.66±0.39
w/o Adaptive LR scheduling (Sec.4.4)	69.70±1.34	73.06±1.35	45.01±0.22	48.66±0.39

Table 3: Ablations for proposed components of our method using CIFAR10 and CIFAR100 dataset. All proposed components improve the performance, with sample-wise importance based memory management providing the biggest gains. While adaptive LR scheduling provides small gains in CIFAR10, the gains increase in the more challenging CIFAR100.

in A_{AUC} and $+16.36\%$ in A_{avg}. For $N = 100$, the performance is similar for the majority of the methods, with CLIB being the best in A_{AUC}. For $N = 50$, CLIB outperforms all comparisons by at least $+12.55\%$ in A_{AUC} and $+13.31\%$ in A_{avg}. Even though CLIB was designed with the i-Blurry setup in mind, it also outperforms other CL methods in conventional setups such as the $N = 100$ (disjoint) or the $N = 0$ (blurry) setups. It implies that CLIB is generally applicable to online CL setups and not restricted to just the i-Blurry setup. Meanwhile, except GDumb, all methods show similar performance on the $N = 100$ (disjoint) setup. The results imply that the i-Blurry setup differentiates CL methods better than the more traditionally used disjoint setup.

Following Bang et al. (2021), we additionally summarize the results for varying values of the blurry level such as $M = 10, 30, 50$ in Table 2 (bottom). We observe that CLIB again outperforms or performs on par with other CL methods on various blurry levels.

5.3 ABLATION STUDIES

We investigate the benefit of each proposed component by ablation studies in Table 3. We use both CIFAR10 and CIFAR100.

Sample-wise Importance Based Memory Management. We replace the 'sample-wise importance memory management' module with the reservoir sampling. As shown in the table, the removal of our memory management strategy degrades the performance in both A_{AUC} and A_{avg} on both CIFAR10 and CIFAR100. As explained in Sec. 4.2, reservoir sampling removes samples at random, hence samples are discarded without considering if some samples are more important than others. Thus, using sample-wise importance to select which sample to discard greatly contributes to performance.

Memory Only Training. We replace the memory usage strategy from our memory only training with ER. Training with ER means that samples from both the online stream and the memory are used. Without the proposed memory only training scheme, the performance degrades across the board by fair margins. As the streamed samples are being used directly without the sample memory acting as a distribution regularizer (see Sec. 4.3), the CL model is more influenced by the recently observed samples, skewing the training and resulting in worse performance.

Adaptive Learning Rate Scheduling. We change the LR scheduling from adaptive LR to exponential with reset. Although performance drop is small on CIFAR10 but gets bigger in the more challenging CIFAR100. CIFAR100 induces more training iterations which makes the ablated model suffer more from a lack of good adaptive LR scheduling.

6 CONCLUSION

We question the practicality of existing continual learning setups for real-world application and propose a novel CL setup named i-Blurry. It is online, task-free, class-incremental, has blurry task boundaries, and is subject to any-time inference. To address this realistic CL setup, we propose a method which uses per-sample memory management, memory only training, and adaptive LR scheduling, named Continual Learning for i-Blurry (CLIB). Additionally, we propose a new metric to better evaluate the effectiveness of any-time inference. Our proposed CLIB consistently outperforms existing CL methods in multiple datasets and setting combinations by large margins.

ETHICS STATEMENT

All continual learning (CL) methods including the proposed one would adapt and extend the already trained AI model to recognize better with the streamed data. The CL methods will expedite the deployment of AI systems to help humans by its versatility of adapting to a new environment out of the factory or research labs. As all CL methods, however, would suffer from adversarial streamed data as well as data bias, which may cause ethnic, gender or biased gender issues, the proposed CLIB would not be an exception. Although the proposed CLIB has *no intention* to allow such problematic cases, the method may be exposed to such threats. Relentless efforts should be made to develop mechanisms to prevent such usage cases in order to make the continuously updating machine learning models safer and enjoyable to be used by humans.

REPRODUCIBILITY STATEMENT

We take the reproducibility of the research very seriously and solemnly promise to release all codes, containers (*e.g.*, Docker) that includes running environments and learned models of pretraining and downstream tasks in a public repository.

REFERENCES

R. Aljundi, P. Chakravarty, and T Tuytelaars. Expert Gate: Lifelong Learning with a Network of Experts. In *CVPR*, 2017.

Rahaf Aljundi, Francesca Babiloni, Mohamed Elhoseiny, Marcus Rohrbach, and Tinne Tuytelaars. Memory aware synapses: Learning what (not) to forget. In *ECCV*, 2018.

Rahaf Aljundi, Eugene Belilovsky, Tinne Tuytelaars, Laurent Charlin, Massimo Caccia, Min Lin, and Lucas Page-Caccia. Online continual learning with maximal interfered retrieval. *Advances in Neural Information Processing Systems*, 32:11849–11860, 2019a.

Rahaf Aljundi, Klaas Kelchtermans, and Tinne Tuytelaars. Task-free continual learning. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 11254–11263, 2019b.

Rahaf Aljundi, Min Lin, Baptiste Goujaud, and Yoshua Bengio. Gradient based sample selection for online continual learning. In *NeurIPS*, pp. 11816–11825, 2019c.

Jihwan Bang, Heesu Kim, YoungJoon Yoo, Jung-Woo Ha, and Jonghyun Choi. Rainbow memory: Continual learning with a memory of diverse samples. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 8218–8227, 2021.

Francisco M. Castro, Manuel J. Marin-Jimenez, Nicolas Guil, Cordelia Schmid, and Karteek Alahari. End-to-end incremental learning. In *ECCV*, 2018.

Arslan Chaudhry, Puneet K. Dokania, Thalaiyasingam Ajanthan, and Philip H. S. Torr. Riemannian walk for incremental learning: Understanding forgetting and intransigence. In *ECCV*, 2018.

Arslan Chaudhry, Marc'Aurelio Ranzato, Marcus Rohrbach, and Mohamed Elhoseiny. Efficient lifelong learning with A-GEM. In *ICLR*, 2019.

B. Cheung, A. Terekhov, Y. Chen, P. Agrawal, and B. Olshausen. Superposition of Many Models into One. In *NeurIPS*, 2019.

Yulai Cong, Miaoyun Zhao, J. Li, Sijia Wang, and L. Carin. GAN memory with no forgetting. In *NeurIPS*, 2020.

Ekin D. Cubuk, Barret Zoph, Dandelion Mane, Vijay Vasudevan, and Quoc V. Le. AutoAugment: Learning augmentation strategies from data. In *CVPR*, June 2019.

S. Ebrahimi, M. Elhoseiny, T. Darrell, and M. Rohrbach. Uncertainty-Guided Continual Learning with Bayesian Neural Networks. In *ICLR*, 2020.

J. He, R. Mao, Z. Shao, and F. Zhu. Incremental Learning In Online Scenario. In *CVPR*, 2020.

Wenpeng Hu, Zhou Lin, Bing Liu, Chongyang Tao, Zhengwei Tao, Jinwen Ma, Dongyan Zhao, and Rui Yan. Overcoming catastrophic forgetting via model adaptation. In *ICLR*, 2019.

C. Kim, J. Jeong, and G. Kim. Imbalanced Continual Learning with Partitioning Reservoir Sampling. In *ECCV*, 2020.

James Kirkpatrick, Razvan Pascanu, Neil Rabinowitz, Joel Veness, Guillaume Desjardins, Andrei A Rusu, Kieran Milan, John Quan, Tiago Ramalho, Agnieszka Grabska-Barwinska, et al. Overcoming catastrophic forgetting in neural networks. *Proceedings of the national academy of sciences*, 114(13):3521–3526, 2017.

Jeongtae Lee, Jaehong Yoon, Eunho Yang, and Sung Ju Hwang. Lifelong learning with dynamically expandable networks. *ICLR*, 2017a.

Sang-Woo Lee, Jin-Hwa Kim, JungWoo Ha, and Byoung-Tak Zhang. Overcoming catastrophic forgetting by incremental moment matching. In *NeurIPS*, 2017b.

Soochan Lee, Junsoo Ha, Dongsu Zhang, and Gunhee Kim. A neural dirichlet process mixture model for task-free continual learning. In *International Conference on Learning Representations*, 2019.

Yaoyao Liu, Yuting Su, An-An Liu, Bernt Schiele, and Qianru Sun. Mnemonics training: Multi-class incremental learning without forgetting. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 12245–12254, 2020.

David Lopez-Paz and Marc'Aurelio Ranzato. Gradient episodic memory for continual learning. In *NIPS*, 2017.

Viktor Losing, Barbara Hammer, and Heiko Wersing. Incremental on-line learning: A review and comparison of state of the art algorithms. *Neurocomputing*, 275:1261 – 1274, 2018. ISSN 0925-2312.

Zheda Mai, Ruiwen Li, Jihwan Jeong, David Quispe, Hyunwoo Kim, and Scott Sanner. Online continual learning in image classification: An empirical survey. *arXiv preprint arXiv:2101.10423*, 2021.

A. Mallya and S. Lazebnik. PackNet: Adding Multiple Tasks to a Single Network by Iterative Pruning. In *CVPR*, 2018.

M. McCloskey and Neal. Catastrophic interference in connectionist networks: The sequential learning problem. *Psychology of Learning and Motivation*, 24:109–165, 1989.

Seyed Iman Mirzadeh, Mehrdad Farajtabar, Razvan Pascanu, and Hassan Ghasemzadeh. Understanding the role of training regimes in continual learning. In *Advances in Neural Information Processing Systems 33: Annual Conference on Neural Information Processing Systems 2020*, 2020.

Ameya Prabhu, P. Torr, and Puneet K. Dokania. GDumb: A simple approach that questions our progress in continual learning. In *ECCV*, 2020.

R. Ratcliff. Connectionist models of recognition memory: Constraints imposed by learning and forgetting functions. *Psychological Review*, 97(2):285–308, 1990.

Sylvestre-Alvise Rebuffi, Alexander Kolesnikov, Georg Sperl, and Christoph H. Lampert. iCaRL: Incremental classifier and representation learning. In *CVPR*, 2017.

David Rolnick, Arun Ahuja, Jonathan Schwarz, Timothy P Lillicrap, and Greg Wayne. Experience replay for continual learning. *arXiv preprint arXiv:1811.11682*, 2018.

Andrei A. Rusu, Neil C. Rabinowitz, Guillaume Desjardins, Hubert Soyer, James Kirkpatrick, Koray Kavukcuoglu, Razvan Pascanu, and Raia Hadsell. Progressive neural networks. *arXiv*, abs/1606.04671, 2016.

Gobinda Saha, Isha Garg, and Kaushik Roy. Gradient projection memory for continual learning. In *International Conference on Learning Representations*, 2021.

Hanul Shin, Jung Kwon Lee, Jaehong Kim, and Jiwon Kim. Continual learning with deep generative replay. In *NeurIPS*, 2017.

Jeffrey S Vitter. Random sampling with a reservoir. *ACM Transactions on Mathematical Software (TOMS)*, 11(1):37–57, 1985.

Chenshen Wu, Luis Herranz, Xialei Liu, Yaxing Wang, Joost van de Weijer, and Bogdan Raducanu. Memory Replay GANs: learning to generate images from new categories without forgetting. In *NeurIPS*, 2018.

Yue Wu, Yan-Jia Chen, Lijuan Wang, Yuancheng Ye, Zicheng Liu, Yandong Guo, and Yun Fu. Large scale incremental learning. In *CVPR*, 2019.

Jaehong Yoon, Saehoon Kim, Eunho Yang, and Sung Ju Hwang. Scalable and order-robust continual learning with additive parameter decomposition. In *ICLR*, 2020.

Sangdoo Yun, Dongyoon Han, Seong Joon Oh, Sanghyuk Chun, Junsuk Choe, and Youngjoon Yoo. Cutmix: Regularization strategy to train strong classifiers with localizable features. In *ICCV*, pp. 6023–6032, 2019.

Friedemann Zenke, Ben Poole, and Surya Ganguli. Continual learning through synaptic intelligence. In *ICML*, 2017.

A   APPENDIX

A.1   PROOF OF THEOREM 1

We give the proof of Theorem 1 below. Our assumption is that when selecting memory $\mathcal{M}$ from a set of candidates $\mathcal{C}$, we should select M so that optimizing on M maximizes the loss decrease on C. In equations, optimal memory $\mathcal{M}^*$ is

$$\mathcal{M}^* = \underset{\mathcal{M} \subset \mathcal{C}, |\mathcal{M}| \leq m}{\arg\max} \sum_{(x',y') \in \mathcal{M}} \sum_{(x,y) \in \mathcal{C}} \mathbb{E}_\theta \left[l(x,y;\theta) - l(x,y;\theta - \nabla_\theta l(x',y';\theta)) \right] \tag{4}$$

$$= \underset{\mathcal{M} \subset \mathcal{C}, |\mathcal{M}| \leq m}{\arg\max} \left[\sum_{(x',y') \in \mathcal{C}} \sum_{(x,y) \in \mathcal{C}} \mathbb{E}_\theta \left[l(x,y;\theta) - l(x,y;\theta - \nabla_\theta l(x',y';\theta)) \right] \right.$$

$$\left. - \sum_{(x',y') \in \mathcal{C} \setminus \mathcal{M}} \sum_{(x,y) \in \mathcal{C}} \mathbb{E}_\theta \left[l(x,y;\theta) - l(x,y;\theta - \nabla_\theta l(x',y';\theta)) \right] \right] \tag{5}$$

$$= \underset{\mathcal{M} \subset \mathcal{C}, |\mathcal{M}| \leq m}{\arg\min} \sum_{(x',y') \in \mathcal{C} \setminus \mathcal{M}} \sum_{(x,y) \in \mathcal{C}} \mathbb{E}_\theta \left[l(x,y;\theta) - l(x,y;\theta - \nabla_\theta l(x',y';\theta)) \right], \tag{6}$$

where θ is the model parameter, l is the loss function, and m is the memory size. Since we perform memory update after every streamed sample, the problem reduces to selecting one sample $(\bar{x}, \bar{y})$ to remove when the memory is full. Thus, $\mathcal{C} \setminus \mathcal{M} = \{(\bar{x}, \bar{y})\}$. The optimal removed sample $(\bar{x}^*, \bar{y}^*)$ would be

$$(\bar{x}^*, \bar{y}^*) = \underset{(\bar{x},\bar{y}) \in \mathcal{C}}{\arg\min} \mathbb{E}_\theta \left[\sum_{(x,y) \in \mathcal{C}} l(x,y;\theta) - l(x,y;\theta - \nabla_\theta l(\bar{x},\bar{y};\theta)) \right]. \tag{7}$$

A.2   DETAILS ON SAMPLE-WISE IMPORTANCE BASED MEMORY MANAGEMENT

We describe the details of our sample-wise importance based memory management here. We update $\mathcal{H}$, the estimate of sample-wise importance for episodic memory, after every model update. The details are in Alg. 1. With the sample-wise importance scores, we update the memory everytime a new sample is encountered. The details are in Alg. 2.

Algorithm 1 Update Sample-wise Importance

1: **Input** model f_θ, memory $\mathcal{M}$, sample-wise importance $\mathcal{H}$, previous loss l_{prev}, indices used for training $\mathcal{I}$, update coefficient λ
2: $l_{\text{cur}} = \frac{1}{|\mathcal{M}|} \sum_{(x,y) \in \mathcal{M}} l(x,y;\theta)$ ▷ Obtain memory loss
3: $\Delta l = l_{\text{prev}} - l_{\text{cur}}$ ▷ Obtain memory loss decrease
4: $\Delta l_{\text{pred}} = \frac{1}{|\mathcal{I}|} \sum_{i \in \mathcal{I}} \mathcal{H}_i$ ▷ Memory loss decrease prediction using current $\mathcal{H}$
5: **for** $i \in \mathcal{I}$ **do**
6:     **Update** $\mathcal{H}_i \leftarrow \mathcal{H}_i + \lambda(\Delta l - \Delta l_{\text{pred}})$ ▷ Update $\mathcal{H}$ for samples used for training
7: **end for**
8: **Update** $l_{\text{prev}} \leftarrow l_{\text{cur}}$
9: **Output** $\mathcal{H}, l_{\text{prev}}$

A.3   ADAPTIVE LEARNING RATE SCHEDULER

We describe the adaptive LR schedule from 4.4 in Alg. A.3. We fix the significance level to the commonly used $\alpha = 0.05$. Our adaptive LR scheduling decreases or increases the LR based on its current value. Thus, the rate in which the LR can change is bounded and sudden changes in LR do not happen.

Algorithm 2 Sample-wise Importance Based Memory Update

1: **Input** model f_θ, memory $\mathcal{M}$, memory size m, sample $(\hat{x}, \hat{y})$, per-sample criterion $\mathcal{H}$, previous loss l_{prev}
2: **if** $|\mathcal{M}| < m$ **then**   ▷ If the memory is not full
3:      **Update** $\mathcal{M} \leftarrow \mathcal{M} \cup \{(\hat{x}, \hat{y})\}$ ▷ Append the sample to the memory
4:      $\hat{i} = |\mathcal{M}|$
5: **else**   ▷ If the memory is already full
6:      $y_{\text{max}} = \arg\max_y |\{(x_i, y_i)|(x_i, y_i) \in \mathcal{M} \cup \{(\hat{x}, \hat{y})\}, y_i = y\}|$ ▷ Find the most frequent label
7:      $\mathcal{I}_{y_{\text{max}}} = \{i|(x_i, y_i) \in \mathcal{M}, y_i = y_{\text{max}}\}$
8:      $\hat{i} = \arg\min_{i \in \mathcal{I}_{y_{\text{max}}}} \mathcal{H}_i$ ▷ Find the sample with the lowest importance
9:      **Update** $l_{\text{prev}} \leftarrow \frac{m}{m-1} l_{\text{prev}} - \frac{1}{m-1} l(x_{\hat{i}}, y_{\hat{i}}; \theta)$
10:      **Update** $\mathcal{M}_{\hat{i}} \leftarrow (\hat{x}, \hat{y})$ ▷ Replace that sample with the new sample
11: **end if**
12: **Update** $l_{\text{prev}} \leftarrow \frac{|\mathcal{M}|-1}{|\mathcal{M}|} l_{\text{prev}} + \frac{1}{|\mathcal{M}|} l(\theta, \hat{x}, \hat{y})$
13: $\mathcal{I}_{\hat{y}} = \{i|(x_i, y_i) \in \mathcal{M}, y_i = \hat{y}, i \neq \hat{i}\}$
14: **Update** $\mathcal{H}_{\hat{i}} \leftarrow \frac{1}{|\mathcal{I}_{\hat{y}}|} \sum_{i \in \mathcal{I}_{\hat{y}}} \mathcal{H}_i$ ▷ Initialize the importance for the new sample
15: **Output** $\mathcal{M}, \mathcal{H}, l_{\text{prev}}$

Algorithm 3 Adaptive Learning Rate Scheduler

1: **Input** current LR η, current base LR $\bar{\eta}$, loss before applying current LR l_{before}, current loss l_{cur}, LR performance history $\mathcal{H}^{(\text{high})}$ and $\mathcal{H}^{(\text{low})}$, LR step $\gamma < 1$, history length m, significance level α
2: $l_{\text{diff}} = l_{\text{before}} - l_{\text{cur}}$ ▷ Obtain loss decrease
3: **Update** $l_{\text{before}} \leftarrow l_{\text{cur}}$
4: **if** $\eta > \bar{\eta}$ **then**   ▷ If LR is higher than base LR
5:      **Update** $\mathcal{H}^{(\text{high})} \leftarrow \mathcal{H}^{(\text{high})} \cup \{l_{\text{diff}}\}$ ▷ Append loss decrease in high LR history
6:      **if** $|\mathcal{H}^{(\text{high})}| > m$ **then**
7:          **Update** $\mathcal{H}^{(\text{high})} \leftarrow \mathcal{H}^{(\text{high})} \setminus \{\mathcal{H}_1^{(\text{high})}\}$
8:      **end if**
9: **else**   ▷ If LR is lower than base LR
10:      **Update** $\mathcal{H}^{(\text{low})} \leftarrow \mathcal{H}^{(\text{low})} \cup \{l_{\text{diff}}\}$ ▷ Append loss decrease in low LR history
11:      **if** $|\mathcal{H}^{(\text{low})}| > m$ **then**
12:          **Update** $\mathcal{H}^{(\text{low})} \leftarrow \mathcal{H}^{(\text{low})} \setminus \{\mathcal{H}_1^{(\text{low})}\}$
13:      **end if**
14: **end if**
15: **if** $|\mathcal{H}^{(\text{high})}| = m$ **and** $|\mathcal{H}^{(\text{low})}| = m$ **then**   ▷ If both histories are full
16:      $p = \text{OneSidedStudentsTTest}\left(\mathcal{H}^{(\text{low})}, \mathcal{H}^{(\text{high})}\right)$
         ▷ Perform one-sided Student's t-test with alternative hypothesis $\mu_{\text{low}} > \mu_{\text{high}}$
17:      **if** $p < \alpha$ **then**   ▷ If pvalue is significantly low
18:          **Update** $\bar{\eta} \leftarrow \gamma^2 \cdot \bar{\eta}$ ▷ Decrease base LR
19:          **Update** $\mathcal{H}^{(\text{low})}, \mathcal{H}^{(\text{high})} = \emptyset, \emptyset$ ▷ Reset histories
20:      **else if** $p > 1 - \alpha$ **then**   ▷ If pvalue is significantly high
21:          **Update** $\bar{\eta} \leftarrow \frac{1}{\gamma^2} \cdot \bar{\eta}$ ▷ Increase base LR
22:          **Update** $\mathcal{H}^{(\text{low})}, \mathcal{H}^{(\text{high})} = \emptyset, \emptyset$
23:      **end if**
24: **end if**
25: **if** $\eta > \bar{\eta}$ **then**   ▷ Alternately apply high and low LR (note that $\gamma < 1$)
26:      **Update** $\eta = \gamma \cdot \bar{\eta}$
27: **else**
28:      **Update** $\eta = \frac{1}{\gamma} \cdot \bar{\eta}$
29: **end if**
30: **Output** $\eta, \bar{\eta}, l_{\text{before}}, \mathcal{H}^{(\text{low})}, \mathcal{H}^{(\text{high})}$

Methods	K=200		K=500		K=1000	
	A_{AUC}	A_{avg}	A_{AUC}	A_{avg}	A_{AUC}	A_{avg}
EWC++	51.29±1.05	53.84±2.34	57.06±1.63	59.96±3.18	60.26±1.17	65.25±1.77
BiC	49.65±1.78	51.58±1.11	52.35±1.85	54.94±1.81	54.78±1.99	58.04±1.94
ER-MIR	50.79±1.55	54.08±2.11	57.65±2.49	61.15±3.74	60.86±2.37	66.10±0.93
GDumb	42.54±2.01	43.99±2.28	53.20±1.93	55.27±2.69	66.55±1.10	69.21±1.29
RM†	21.59±0.85	47.53±0.93	22.77±1.55	60.73±1.03	25.82±2.19	71.15±2.92
Baseline-ER	51.41±1.07	53.70±2.40	56.96±1.97	60.22±3.04	60.55±1.21	65.47±1.76
CLIB (Ours)	**64.27±1.67**	**66.17±1.58**	**70.32±1.22**	**74.00±0.72**	**73.20±1.16**	**77.88±1.87**

Table 4: Analysis on various sample memory sizes (K) using CIFAR10. The i-Blurry-50-10 splits are used. The results are averaged over 3 runs. CLIB outperforms all other CL methods by large margins for all the memory sizes. CLIB uses the given memory budget most effectively, showing the superiority of our per-sample memory management method.

A.4   Details on the Online Versions of Compared CL Methods

We implemented online versions of RM (Bang et al., 2021), EWC++ (Chaudhry et al., 2018), BiC (Wu et al., 2019), GDumb (Prabhu et al., 2020), A-GEM (Chaudhry et al., 2019), GSS (Aljundi et al., 2019c) and MIR (Aljundi et al., 2019a) by incorporating ER and exponential decay with reset to the methods whenever possible. There is no specified memory management strategy for EWC++, and BiC uses herding selection from iCaRL(Rebuffi et al., 2017). However, herding selection is not possible in online since it requires whole task data for calculating class mean, so we attach reservoir memory to both methods instead. EWC++ does not require any other modification.

Additional modification should be applied to bias correction stage of BiC. BiC originally performs bias correction at end of each task, but since evaluation is also performed at the middle of task in our setup, we modified the method to perform bias correction whenever the model receives inference query.

In RM, their memory management strategy based on uncertainty is not applicable in an online setup, since it requires uncertainty rankings of the whole task samples. Thus, we replace their sampling strategy with balanced random sampling, while keeping their two-stage training scheme. Methods that were converted from offline to online, namely EWC++, BiC, and RM, may have suffered some performance drop due to deviation from their original methods.

A.5   Analysis on Sample Memory Size

We conduct analysis over various sample memory sizes (K) and summarize results in Table 4. We observe that CLIB outperforms other CL methods in both A_{AUC} and A_{avg} no matter the memory size. It is interesting to note that CLIB with a memory size of $K = 200$ outperforms other CL methods with a memory size of $K = 1000$ in the A_{AUC} and performs on par in A_{avg}. Thus, CLIB is the only method using memory only training scheme but is the least sensitive to memory size. It implies that our memory management policy is the most effective, which shows the superiority of our per-sample memory management method.

A.6   Additional Comparisons with A-GEM

We present additional comparisons to A-GEM. Note that as A-GEM was designed for the task-incremental setting, it performs very poorly in our i-Blurry setup which is task-free. Notably, it achieves only 4.62 A_{AUC} and 6.94 A_{avg} on CIFAR100, but other works (Prabhu et al., 2020; Mai et al., 2021) have also reported very poor performance for A-GEM in their studies as well.

A.7   Comparisons to Other Memory Management CL Methods

We present additional comparison to CL methods that use a different memory management strategy in Table 6. GSS (Aljundi et al., 2019c) is added as an additional comparison while Baseline-ER is used to represent the reservoir sampling. CLIB outperforms both methods by large margins in both

Methods	CIFAR10		CIFAR100	
	A_{AUC}	A_{avg}	A_{AUC}	A_{avg}
EWC++	57.06±1.63	59.96±3.18	35.26±1.82	39.35±1.50
BiC	52.35±1.85	54.94±1.81	26.26±0.92	29.90±1.03
ER-MIR	57.65±2.49	61.15±3.74	34.49±2.29	37.95±2.05
A-GEM	39.29±2.88	44.85±4.70	4.62±0.23	6.94±0.51
GDumb	53.20±1.93	55.27±2.69	32.84±0.45	34.03±0.89
RM†	22.77±1.55	60.73±1.03	8.62±0.64	32.09±0.99
Baseline-ER	56.96±1.97	60.22±3.04	34.26±1.66	38.99±1.31
CLIB (Ours)	**70.32±1.22**	**74.00±0.72**	**46.73±1.13**	**49.53±1.18**

Table 5: Additional comparisons to A-GEM with various online CL methods on the i-Blurry setup for CIFAR10 and CIFAR100 are shown. The i-Blurry-50-10 splits are used for all the datasets and the results are averaged over 3 runs. A-GEM performs very poorly, especially on CIFAR100 as it was designed for the task-incremental setting whereas i-Blurry setup is task-free. CLIB outperforms all other CL methods by large margins on both the A_{AUC} and the A_{avg}.

Methods	Mem. Management	CIFAR10		CIFAR100	
		A_{AUC}	A_{avg}	A_{AUC}	A_{avg}
GSS	GSS-Greedy	55.51±3.33	59.27±4.36	30.09±1.38	35.06±1.43
Baseline-ER	Reservoir	56.96±1.97	60.22±3.04	34.26±1.66	38.99±1.31
CLIB (Ours)	Sample-wise Importance	**70.32±1.22**	**74.00±0.72**	**46.73±1.13**	**49.53±1.18**

Table 6: Comparisons to other CL methods with different memory management strategies in the i-Blurry setup for CIFAR10 and CIFAR100 are shown. The i-Blurry-50-10 splits are used for all the datasets and the results are averaged over 3 runs. CLIB outperforms all other CL methods by large margins on both the A_{AUC} and the A_{avg} implying that the sample-wise importance memory management method is effective.

A_{AUC} and A_{avg}, implying that the sample-wise importance memory management method is better than reservoir or GSS-greedy.

A.8 ADDITIONAL RESULTS WITH THE F_5 MEASURE

We report the result of the forgetting measure (Chaudhry et al., 2018) here. Note that while forgetting is a useful metric for analyzing stability-plasticity of the method, lower forgetting does not necessarily mean that a CL method is better. For example, if a method do not train with the new task at all, its forgetting will be 0.

Also, we do not propose a new forgetting measure for anytime inference. It is because forgetting is measured with the best accuracy of each class, and best accuracy usually occur at the end of each task. Thus, measuring the best accuracy among all inferences would not be much different from best accuracy among the inferences at the end of each task.

Note that the F_5 values are roughly similar across all methods excepting BiC. BiC show a particularly lower forgetting, since they use distillation to prevent forgetting in a hard way. However, in an online setting where multiple epoch training over the whole task is not possible, it hinders the model from learning new knowledge which is why BiC's A_{AUC} and A_{avg} are generally low.

Methods	CIFAR10			CIFAR100			TinyImageNet		
	A_{AUC}	A_{avg}	F_5	A_{AUC}	A_{avg}	F_5	A_{AUC}	A_{avg}	F_5
EWC++	57.06±1.63	59.96±3.18	18.51±3.69	35.26±1.82	39.35±1.50	10.79±2.75	20.63±1.02	22.89±1.11	14.33±1.31
BiC	52.35±1.85	54.94±1.81	**8.92±5.40**	26.26±0.92	29.90±1.03	**-0.97±0.51**	16.68±1.95	20.19±1.35	**5.99±1.60**
ER-MIR	57.65±2.49	61.15±3.74	20.38±2.81	34.49±2.29	37.95±2.05	10.88±2.53	21.07±0.89	22.89±0.71	15.30±2.15
GDumb	53.20±1.93	55.27±2.69	18.50±1.96	32.84±0.45	34.03±0.89	8.78±0.51	18.17±0.19	18.69±0.45	8.61±1.81
RM†	22.77±1.55	60.73±1.03	5.60±0.85	8.62±0.64	32.09±0.99	7.22±0.64	3.67±0.03	11.35±0.12	-0.77±0.26
Baseline-ER	56.96±1.97	60.22±3.04	17.90±4.85	34.26±1.66	38.99±1.31	9.22±2.61	21.37±1.01	23.65±1.22	14.13±1.64
CLIB (Ours)	**70.32±1.22**	**74.00±0.72**	17.20±1.72	**46.73±1.13**	**49.53±1.18**	12.93±1.93	**23.78±0.66**	**24.79±0.21**	13.17±1.47

Table 7: Additional comparisons including the F_5 measure of various online CL methods on the i-Blurry setup for CIFAR10, CIFAR100, and TinyImageNet are shown. The i-Blurry-50-10 splits are used for all the datasets and the results are averaged over 3 runs. Ours outperforms all other CL methods by large margins on both the A_{AUC} and the A_{avg}. The F_5 value is roughly the same for all methods except BiC. The best result for each of the metrics is shown in **bold**.

A.9 Performance of Exponential with Reset LR Schedule

We show brief results for the LR schedule used in our baseline in Table 8. We compare the constant LR with the exponential with reset used in our baseline. The exponential with reset is better than the constant LR, which is why we used it in our baseline.

Methods	LR Schedule	A_{AUC}	A_{avg}
Baseline-ER	Constant	56.73±1.73	58.18±3.41
	Exp w/ Reset	56.96±1.97	60.22±3.04
EWC++	Constant	56.54±1.57	57.92±3.26
	Exp w/ Reset	57.06±1.63	59.96±3.18

Table 8: Comparison between exponential with reset schedule and constant LR on CIFAR10 are shown. It shows that our baseline LR schedule, exponential with reset, is reasonable. It shows better performance than constant LR, especially in A_{avg} metric.