ZERO PIXEL DIRECTIONAL BOUNDARY BY VECTOR TRANSFORM

ABSTRACT

Boundaries or contours are among the primary visual cues used by human and computer vision systems. One of the key problems in boundary detection is the loss formulation, which typically leads to class imbalance and, as a consequence, to thick boundaries which require non-differential post-processing steps to be thinned. In this paper, we re-interpret boundaries as 1-D surfaces and formulate a one-to-one vector transform function that allows for training of boundary prediction completely avoiding the class imbalance issue. Specifically, we define the boundary representation at any point as the unit vector pointing to the closest boundary surface. Our problem formulation leads to the estimation of direction as well as richer contextual information of the boundary, and, if desired, the availability of zero-pixel thin boundaries also at training time. Our method uses no hyper-parameter in the training loss and a fixed stable hyper-parameter at inference. We provide theoretical justification/discussions of the vector transform representation. We evaluate the proposed loss method using a standard architecture and show the excellent performance over other losses and representations on several datasets.

1 INTRODUCTION

Boundaries are considered to be one of the important interpretable visual cues that can describe both the low-level image characteristics as well as high-level semantics of the image. Human vision uses occluding contours and boundaries to interpret unseen or seen objects and classes. Because boundaries are an important visual cue for image understanding, they are also exploited as priors in several vision tasks (Zhu et al., 2020; Kim et al., 2021; Hatamizadeh et al., 2019; Revaud et al., 2015; Cashman & Fitzgibbon, 2012). Some key works on contours (Cootes et al., 2001; Matthews & Baker, 2004; Kass et al., 1988) have greatly impacted early research in computer vision. Although the advent of deep learning and end-to-end learning has somewhat shifted the focus away from interpretable visual cues, boundary discovery still remains an important task in computer vision.

Supervised deep learning has greatly transformed problems such as object detection and segmentation (Redmon et al., 2016; Chen et al., 2017; Cheng et al., 2020) by redefining the problem (Kirillov et al., 2019), using high-quality datasets (Cordts et al., 2016; Neuhold et al., 2017) and better network architectures (Cheng et al., 2020; 2021; Wang et al., 2021b). Boundary detection, however, has seen a rather modest share of such progress. Part of the reason is the excellent computational efficiency and decent performance of the old Canny edge detector (Canny, 1986). However, modern deeply learned methods (Xie & Tu, 2015; Liu et al., 2017; Maninis et al., 2017) provide better accuracy and the possibility to learn only the high-level boundaries, which may be preferred in some applications. Regardless of the approach, a particularly elusive goal in boundary detection has been the so-called crisp boundaries (Isola et al., 2014; Wang et al., 2018; Deng et al., 2018). The formulation of boundary detection as a binary segmentation task naturally introduces class imbalance, which makes detecting pixel thin sharp boundaries extremely difficult. Arguably a majority of recent methods in boundary detection are proposed in order to tackle the aforementioned issue. Many methods address the lack of 'crispiness' by fusing high-resolution features with the middle- and high-level features (Xie & Tu, 2015; Liu et al., 2017). Such a strategy has been successful in other dense prediction tasks (Ronneberger et al., 2015) as well. Others propose different loss functions (Kokkinos, 2016; Deng et al., 2018; Kervadec et al., 2019) to address class imbalance.

Despite the improvements, we identify two issues regarding crisp boundary detection. The first is that the evaluation protocol (Martin et al., 2004) does not necessarily encourage crisp detection, as the quantification is done after Non-Maximal Suppression (NMS). Such an evaluation may be misleading when the network outputs need to be used at training time for other high-level tasks, e.g., segmentation (Kim et al., 2021). The second is that the current losses (Kokkinos, 2016; Xie & Tu, 2015; Ma et al., 2021) push for edges as crisp as the ground-truth rather than as crisp as possible. The second point is particularly harmful since many boundary detection datasets (Arbelaez et al., 2010; Silberman et al., 2012) contain ambiguous boundaries or inconsistently thick boundaries.

In this paper, we take a different perspective on boundary detection. Boundaries are formed where visual features change, popularly referred to as the differential representation (Boykov et al., 2006; Kervadec et al., 2019). Such an assumption treats the boundaries as a set of 1-D surfaces embedded in a continuous 2D space, implying they do not have any thickness. Many previous energy-minimization based approaches (Chan & Zhu, 2005; Chan & Vese, 2001; Paragios et al., 2002; Boykov et al., 2006; Ma & Manjunath, 2000) and a few current methods (Kervadec et al., 2019) tackle boundaries in a similar way. Level-set methods (Chan & Zhu, 2005; Boykov et al., 2006; Ma & Manjunath, 2000) consider boundaries as the level-set of a continuous function of the image. Specifically, (Ma & Manjunath, 2000) defines the energy function related to the distance and direction of the boundary at each pixel and extracts the directional normals at the boundary using such energy. Inspired by such works and also recent works on 3D implicit functions (Tancik et al., 2020; Sitzmann et al., 2020; Mildenhall et al., 2020), we represent boundaries via a field of unit vectors defined at each pixel and pointing towards the closest boundary surface. We thus formulate boundary detection as a dense prediction task without class imbalance, as opposed to detecting sparse pixels. In distance transforms, vector fields are considered in complete euclidean transforms (Osher & Sethian, 1988), equal to the normalized Jacobian of the signed distance field. The vector field we use is in fact the normalized Jacobian of the positive distance field. In contrast to distance fields, it provides high sensitivity at the boundaries and does not ignore topological changes from small boundaries. In our work, we prove the equivalence of the vector field to the surface contour representation. We demonstrate that the standard binary or surface representation can be extracted from the level set of the normal field's divergence, providing sharp boundaries. We refer to such a zero-thickness boundary as the zero-pixel boundary. Our method is virtually hyper-parameter free at training and test time, and can provide zero-pixel thick boundaries at training time.

In order to evaluate the boundaries using the surface interpretation, we also advocate the use of surface distances including the average symmetric surface distance (assd) metric that is less prone to class imbalance and variable boundary thickness in the ground-truth (Kervadec et al., 2019). Such metrics are very popular in biomedical image segmentation (Yeghiazaryan & Voiculescu, 2018). We show significant improvements in all metrics using our boundary representation when compared to the various combinations of Dice (Dice, 1945) and cross-entropy losses in several large datasets.

2 RELATED WORK

There is a rich history of boundary detection in computer vision. Previous work on boundaries showed a diversity of definitions and approaches. We differentiate them based on two different interpretations of boundaries: i.e., *i)* a boundary is a separation between two or more image regions with different visual features and *ii)* a boundary is a thin group of pixels belonging to a specific class. It should be noted that most modern methods fall under the second category.

Perhaps the most notable representatives of the first strand are the energy-based segmentation methods (Chan & Vese, 2001; Comaniciu & Meer, 2002; Boykov et al., 2006; Grady, 2006; Ma & Manjunath, 2000). These methods relied on hand-crafted features and various optimization strategies to compute the low-level boundaries. In particular, Ma & Manjunath (2000) compute the normal vectors of the low-level boundaries from an energy function, without looking into an equivalent learnable representation. Graph-based segmentation methods (Shi & Malik, 2000; Felzenszwalb & Huttenlocher, 2004; Cheng et al., 2016) construct a graph from the image and cut the graph to obtain non-overlapping regions whose boundaries are viewed as image boundaries. A few deep learning methods followed a similar approach (Wang et al., 2021a; Kervadec et al., 2019). The advantage of such methods is that they provide boundaries as region separators and hence no post-processing for thinning is required. Nonetheless, such definitions are hard to adapt to generic boundaries and a compact multi-boundary representation is currently lacking in category *i)* methods.

A large corpus of work utilizes pixel-wise image features to decide whether pixels belong to a 'boundary' class. They form our category *ii)* methods. Early methods utilize various filter operators to detect discontinuities in image intensities or colors (Canny, 1986; Sobel, 1972). Learning based methods substantially boost the edge detection performance by classifying handcrafted features (Konishi et al., 2003; Martin et al., 2004; Arbelaez et al., 2010; Dollár & Zitnick, 2013; Hallman & Fowlkes, 2015). Modern deep neural network (DNN) methods have further improved this field by learning powerful feature representations, particularly high-level semantic information (Shen et al., 2015; Bertasius et al., 2015; Xie & Tu, 2015; Liu et al., 2017; Wang et al., 2018; Deng et al., 2018; He et al., 2019). Yang et al. (2016) leveraged the powerful deep features to detect only object boundaries. Others try to simultaneously detect edges and predict the semantic class of each edge point, so-called semantic edge detection (Hariharan et al., 2011; Yu et al., 2017; Liu et al., 2018; Yu et al., 2018). A contribution that is particularly relevant to our work is (Maninis et al., 2017), where the authors show that predicting boundaries with orientations instead of only a binary representation improves tasks such as image segmentation and superpixel extraction. Specifically, they use a sparse representation of oriented contours. Our method also falls in this category, as we develop a representation that includes directional boundaries as well as outside/inside regions.

On the other hand, classifying pixels as boundary class introduces class imbalance during training. A common strategy is to use a weighted cross-entropy loss to account for the large number of non-boundary pixels, giving that class a small weight and the boundary class a large weight (Xie & Tu, 2015; Liu et al., 2017; He et al., 2019). Yet, despite an improvement over regular cross-entropy, this leads to thick boundaries because networks tend to predict non-boundary pixels as boundary pixels. To thin the boundaries, Non-Maximal Suppression (NMS) is usually adopted. Such methods may be harmful when directly integrated with higher-level tasks such as segmentation (Kim et al., 2021). The Dice loss (Dice, 1945) is thus applied to generate crisp boundaries before NMS (Deng et al., 2018), but it still produces several pixel thick boundaries. In practice, we also found that the Dice loss usually leads to accuracy degradation. Moreover, the right approach still depends on the downstream tasks (Zhu et al., 2020; Kim et al., 2021; Hatamizadeh et al., 2019) and in either case a careful selection of training as well as testing hyper-parameters is required. We provide an alternative approach, motivated by the class imbalance and ambiguous definition of boundaries.

3   BOUNDARY TRANSFORM AND REPRESENTATION

In this section, we first discuss the surface representation of boundaries as a normal field transform and construct the corresponding detection method. Our boundary representation is inspired by recent work on implicit neural 3D surface representations (Park et al., 2019; Mescheder et al., 2019), energy-based methods on edge detection (Ma & Manjunath, 2000; Boykov et al., 2006) and distance transforms (Osher & Sethian, 1988). In 3D surface representations, a Signed Distance Function (SDF) (Osher & Sethian, 1988) or occupancy map (Mescheder et al., 2019) is used as representation. We instead propose a unit vector field from every point to the closest boundary. This choice is motivated by the high sensitivity and richer boundary context provided by the unit vector field, as shown in our experimental results in § 5. Fig. 1 shows our vector field representation of the ground-truth, with predictions using a standard quiver plot on a sub-sampled set of points.

We assume a continuous boundary image domain $\Omega \subset \mathbb{R}^2$ with the set of boundary points $\{x'\} = \Pi \subset \Omega$. Each point is denoted as a 2-vector $x = (x, y) \in \mathbb{R}^2$. In order to encode boundary properties on the whole image, we compute a signed x and y distance field separately and finally encode only the direction. The result is a unit vector field that represents the boundary. We can express our boundary representation by the following transform for any point $x \in \Omega$:

$$
\begin{aligned}
f_x(x) &= \inf_{x' \in \Pi} d_x(x, x'), \\
f_y(x) &= \inf_{x' \in \Pi} d_y(x, x'), \\
v(x) &= \frac{f(x)}{\|f(x)\|_2}, \quad \text{if } \|f(x)\|_2 \neq 0, \text{ otherwise } n, \\
n &= \lim_{d_x \to 0^+} \frac{f(x)}{\|f(x)\|_2}.
\end{aligned}
\tag{1}
$$

| (a) Image crop | (b) Traditional | (c) Vector transform | (d) Zoomed in |

Figure 1: **Boundary representations**. We contrast the conventional binary boundary representation with our representation. From left to right, we show (a) top-left crop of an image in a test set, (b) the standard binary representation of ground-truth boundary, (c) the vector transform plot of the prediction *(in red)* overlaid on the ground-truth representation *(in green)* and the conventional binary representation for clarity. Finally (d) shows the zoomed in view of (c) on the yellow rectangle.

Equation (1) defines the transform as a function $v(x)$ going from the boundary Π to a field representation. Here, d_x and d_y are operators that give the signed x and y difference, respectively. Similarly, f_x and f_y are the x and y components of the field f. Note that we choose the field vector arbitrarily among the two possible values at the boundary using the positive d_x distance.

We note the following properties of the vector field v.

Property 3.1 *The vector field $v(x)$ is equal to the unit normal field at the boundary.*

Proof This is a well known result by Osher & Fedkiw (2003) (see equation (2.4) in the text) and can be proved easily. The fact that we forcefully choose one normal over its negative directional normal at the boundary points does not affect the result.

Property 3.2 *Given a vector field representation $v(x)$ of a boundary, one can obtain the binary boundary representation by considering the following transform:*

$$g(x) = \operatorname{div} v(x). \tag{2}$$

The original boundary set Π can then be found by taking the zero level set of $g(x) + 2$, i.e.,

$$\Pi = L_0(g + 2). \tag{3}$$

Proof In the infinitesimal neighborhood of the boundary points, using property 3.1, the vector field is normal to the boundary, provided that good approximate normals can be obtained from equation (1). As the neighborhood size approaches zero, the tangential vector components approach zero around a point for a continuous boundary. Thus, around such an infinitesimal neighborhood, the normal fields pointing in opposite direction will invert perfectly in the normal direction creating a divergence flow of -2. Hence, the boundary is given by the level-set of -2 of the divergence. Strictly speaking the result holds only for piece-wise smooth surfaces (Osher & Fedkiw, 2003), with lower than -2 divergence at the discontinuities. In fact, this result is another interpretation of the Fast Marching Method presented in (Osher & Fedkiw, 2003).

Property 3.3 *The relation is one-to-one between the binary boundary representation and the proposed vector field representation in a continuous domain.*

Proof This property is the result of equation (1), for the forward transform and equation (3) for the inverse transform, providing a one-to-one relation.

Additionally, the vector field transform as defined in equation (1) has to correct for two different kinds of indeterminate states. The first is on the boundary, that is solved by using the right hand limit so that one of the two opposite directions is chosen consistently. The second is when the infimum operation in equation (1) produces two or more closest points resulting in an ambiguity. This is easily corrected by choosing any one of the points for the infimum value. The vector fields

around such points flip directions creating a positive divergence as shown in Fig. 2. More discussions are provided in §5 about the latter, which are in fact helpful for deciding superpixel centers.

The above properties are important in order to establish the validity of the proposed boundary representation and also to go from one representation to another for evaluation and visualization.

Vector field and the Distance Field. In essence, the normalized vector field proposed in equation (1) is just another representation of the distance transform. Let $\phi(\mathsf{x}) \in \mathbb{R}^+$ define the distance transform, then the vector field $\mathsf{v}(\mathsf{x})$ in equation (1) can be obtained by the following partial derivatives (Osher & Sethian, 1988; Osher & Fedkiw, 2003):

$$\mathsf{f}(\mathsf{x}) = \nabla \phi(\mathsf{x}). \tag{4}$$

One can optimize a given network by minimizing the loss on the distance transform or SDF (Dapogny & Frey, 2012; Caliva et al., 2019; Park et al., 2019) instead of using the loss on the normalized vector field. Compared to the binary mask, SDF has an added advantage that it is sensitive to small topological changes. However, when the distance field is close to 0, i.e., around the borders, any loss on the distance transform or SDF loses importance and at the same time lacks the contextual information of the vector field. Therefore, the representation is not suitable to learn sharp boundaries. The reader can observe such a behavior in the qualitative and quantitative experimental results in §5. On the other hand, a normalized vector field such as the one in equation (1) is sensitive to the topology similar to a distance field while also being sensitive at the boundaries, as shown in Fig. 1.

4 BOUNDARY DETECTION WITH THE VECTOR FIELD

In this section we provide the details for the construction of the boundary detection method using the representation proposed in §3.

4.1 NETWORK ARCHITECTURE

Most convolutional architectures (Liu et al., 2017; Xie & Tu, 2015) for boundary detection take advantage of both the low-level high resolution features and the deep high-level features, using several fusion strategies. We choose a similar network architecture HR-Net (Wang et al., 2020) which was proposed for segmentation and object detection tasks in high resolution images. We further enrich the high resolution representation provided by HR-Net with an additional skip connection at $\times 2$ downsampling level from the encoder to the decoder. This helps retrieve very high resolution details that are necessary in the boundary prediction task. The output of the HR-Net is first bilinearly upsampled and fused with the skip connection. Inspired by Deng et al. (2018), the high resolution skip connection goes through a ResNeXT module (Xie et al., 2017) before being fused with the decoder signal with a pixel-wise fully connected layer. Finally, the output goes through a convolutional layer and is further upsampled to formulate a prediction at the same resolution as the input. This architecture allows us to test our method as well as traditional, pixel-wise classification methods, without giving an unfair advantage to one over the other. Fig. 2 shows the simple setup of our complete pipeline with training and inference.

The output of our network is a two channel image which contains, respectively, the x-component $\hat{\mathsf{v}}_x$ and the y-component $\hat{\mathsf{v}}_y$ of the field prediction corresponding to equation (1). We denote the transform of equation (1) as Vector Transform (VT), upon which we build our method. Although it is possible to use a single angle prediction and representation as in $\theta \in [-\pi, \pi]$, we choose the x and y component representation because it avoids discontinuities in its value as the vector changes. To constrain the network to output predictions in the $[-1, 1]$ range typical of the sine and cosine functions, a hyperbolic tangent activation ($\tanh$) is applied to the output of the network.

Training loss. To train the x and y components of VT prediction, the mean-squared error (MSE) loss is used, which can be formulated as

$$\ell_{VT} = \left\| \mathsf{v}_x^{gt} - \hat{\mathsf{v}}_x \right\|_2 + \left\| \mathsf{v}_y^{gt} - \hat{\mathsf{v}}_y \right\|_2. \tag{5}$$

Unlike many other methods, there exists no hyper-parameters on the loss formulation as there is no reason to give the two components different weights.

Figure 2: **Training and Inference overview**. The predicted field $\hat{v}(x)$ is convolved with pre-selected filters to obtain the divergence at pixel boundaries for inference. For visualization, we show the divergence and the predicted boundary in pixel locations.

4.2 INFERENCE

At inference time, we predict the boundary VT densely on the image. It is entirely possible that for some downstream tasks, such a prediction may already provide the required endpoint. However, to obtain the surface representation of the boundary, we need to use the properties listed in §3. In particular, property 3.2 provides a differential means to obtain a zero-thickness boundary on a continuous domain. In the discrete space, the same principle can be used to derive the boundary as the inter-pixel points, which we refer to as the zero-pixel boundary. At this stage, at least two different approaches can be used to obtain the inter-pixel separation. One can be formulated by using 2×1 or 2×2 kernels to extract the divergence, which provides the necessary derivatives at the pixel boundaries. We describe in detail a second and simpler which uses a support image $\tilde{I}$ of twice the resolution, in which boundaries can be represented as a single pixel detection. The support image is obtained dilating the original image I to generate a new one that is twice the original dimension as below:

$$\begin{cases} \tilde{I}(x,y) = I\left(\frac{x}{2}, \frac{y}{2}\right) & \text{if } (x \bmod 2 = 0 \text{ and } y \bmod 2 = 0), \\ \tilde{I}(x,y) = 0 & \text{otherwise.} \end{cases} \tag{6}$$

Equation (6) is a simple copy and concatenate operation. On the support image, the divergence of the vector transform $\hat{v}(x)$ is computed using the Sobel filter as a derivative approximation:

$$\nabla \cdot \hat{v}(x) = \frac{\partial \hat{v}(x,y)}{\partial x} + \frac{\partial \hat{v}(x,y)}{\partial y}. \tag{7}$$

The image with boundaries I_b can then be obtained inverting the divergence of the support image in equation (7), subtracting 1 from it and applying ReLU activation (Nair & Hinton, 2010), like

$$I_b = \text{ReLU}\left(-(\nabla \cdot \hat{v}(x) + 1)\right). \tag{8}$$

The resulting image will have non-zero values only on the predicted boundary surface, with boundary pixels having values around 1. In practice we obtain small deviations of about 0.1 around the expected value of 1 due to imperfections in the field predictions. In the support image structure, it can be observed that only pixels not belonging to the original image can be classified as boundaries as they are the only ones for which the divergence can have a value different from zero.

In order to evaluate such a zero-pixel boundary with traditional metrics, and visualize, boundary pixels need to be represented on the original image. We do so, by copying the values of boundary pixels in the support image to the corresponding neighboring pixels belonging to the original image and averaging the values if necessary; all the other values are set to zero. This leads to two pixel boundaries with the added property of being differentiable, which may be particularly useful when integrating the boundary detection task in a larger DNN.

When evaluating the method with the surface distance metrics - which are discussed in §4.3 - the resulting image is thresholded to obtain a binary boundary image. More specifically, all the positive pixels are considered to belong to a boundary and this remains fixed throughout the experiments.

An important aspect of VT is that it provides directional information on each pixel, including those pixels which are associated to the boundaries. Directional boundaries have been previously explored

with applications and advantages (Maninis et al., 2017). We provide two key examples. In the first application, we detect boundary pixels which are proposal candidates for straight lines in a differentiable way. In the second, we detect superpixels by grouping pixels inside a convex boundary. These related tasks are discussed more in depth with some qualitative results in the appendices.

4.3 Metrics

The standard measures for boundary evaluation (Martin et al., 2004) are fixed contour threshold (ODS) and per-image best threshold (OIS). With these approaches it is possible to compute the recall (R), the precision (P) and the F score. These are the metrics traditionally applied using the approach proposed by Martin et al. (2004) to determine the true positives and false negatives. It proceeds by creating a one-to-one correspondence between the ground-truth boundary pixels and the predicted boundary pixels. In this context, each pixel without a correspondence within a fixed threshold distance is considered either a false positive or a false negative. This approach, however, suffers from a few drawbacks:

- It is extremely sensitive in differences of thickness between the prediction and the ground-truth. If the predicted boundary has different thickness compared to the ground truth, it is not able to satisfy the one-to-one correspondence and gives a large number of false positives or false negatives without regard for the actual boundary quality.
- ODS and OIS optimize the threshold hyper-parameter on the test set. This is not a standard practice in any learning-based task and often leads to an overestimation of the quality of the detected boundaries. A more rigorous approach would be optimizing the threshold on a validation set and keeping it fixed at test time to compute P, R and F score.
- As it is based on pixel correspondences, it cannot be directly applied to zero pixel thin boundaries.

To overcome these drawbacks and have a metric that can be applied to the zero pixel surfaces as well, we propose to use the average surface distances (asd), more favored in the medical imaging community (Yeghiazaryan & Voiculescu, 2018). For every boundary pixel or segment in the prediction, it is the distance to the closest ground truth boundary surface point - either a pixel or a segment. The same can be done starting from the ground truth pixels or segments. The distance from the prediction to the ground truth boundary (asd_P) is representative for the quality of the prediction - a precision-like term - while the distance from the ground truth to the prediction (asd_R), like recall, shows how effectively all the boundaries are detected. The two scores can be averaged to obtain a single metric, the average symmetric surface distance ($assd$). Given the no one-to-one correspondences between pixels are computed, asd_P, asd_R and $assd$ are less sensitive to the boundary thickness and more influenced by the overall quality of the prediction, compared to the previously defined metrics.

5 Experiments

We compare the proposed method on Cityscapes (Cordts et al., 2016), Mapillary Vistas (Neuhold et al., 2017) and Synthia (Ros et al., 2016), three datasets providing high quality instance and semantic boundaries. Our method (VT) is compared to other deep-learning based boundary detection methods, which tackle the problem as binary segmentation. We compare VT against three different losses; the dice loss (DL) (Dice, 1945), a weighted combination of Dice loss and cross-entropy (DCL) (Deng et al., 2018) and the weighted cross-entropy (WCL) (Xie & Tu, 2015). As part of the ablation, we further compare our method against the Distance Transform (DT) representation of boundaries which predicts a field of distances to the closest boundary. This is trained with a simple L1 loss between the ground truth d_{gt} and the predicted distance $\hat{d}$. Each representation and training loss is computed using the same network architecture and optimization.

Evaluation Metrics. We evaluate each method based on the traditionally used R, P and F score in the ODS and OIS setups as well as on our asd_R, asd_P, and $assd$ scores. For the traditional metrics for BSDS500 dataset evaluation (Arbelaez et al., 2010), we use an error tolerance of 0.0025 of the diagonal length of the image. This is lower than what is commonly used on the BSDS500 dataset, to account for the larger image sizes. To compute the surface distance metrics (asd_R, asd_P, and

Method	asd_R	asd_P	$assd$	ODS			OIS		
				R	P	F	R	P	F
OP @t_0	5.37	3.29	4.33	0.814	0.878	0.845	0.819	0.874	0.846
TP	5.16	3.92	4.54	0.699	0.740	0.719	0.726	0.718	0.722
TP @t_0	5.16	3.92	4.54	0.877	0.500	0.637	/	/	/
TG	6.02	3.26	4.64	0.621	0.850	0.718	0.621	0.850	0.718
TG @t_0	6.02	3.26	4.64	0.464	0.917	0.616	/	/	/

Table 1: Comparison of the sensitivity to thickness in prediction and ground truth of the used metrics. OP is the original prediction, TP is the thickened version of the prediction and TG the thickened ground truth. In TP, we use the original ground truth and, in TG, the original prediction.

Method	asd_R	asd_P	$assd$	ODS			OIS		
				R	P	F	R	P	F
VT	5.37	**3.29**	**4.33**	**0.814**	**0.878**	**0.845**	**0.819**	**0.874**	**0.846**
DCL	**5.17**	4.24	4.71	0.711	0.811	0.758	0.722	0.806	0.762
DL	5.40	6.51	5.96	0.758	0.747	0.752	0.747	0.760	0.754
WCL	6.42	5.98	6.20	0.773	0.756	0.764	0.755	0.779	0.767
DT	7.76	3.50	5.63	0.651	0.683	0.667	0.642	0.696	0.668

Table 2: Evaluation results on the Cityscapes dataset. As no ground truth is given for the test set, the training set is divided in 2500 images for training and 475 for validation, and the original validation set is used for testing.

$assd$), each boundary representation is converted to a binary form with a thresholding operation. For the DL, DCL, WCL, and DT models, the threshold is fixed using a selected validation set for each dataset. For VT, instead, it is fixed for each test to the value of -1 of the divergence image, the same value added during inference before applying ReLU §4.2; points with lower divergence are classified as boundaries and the others as non-boundaries.

5.1 METRIC ANALYSIS

We first show an analysis to support the use of the surface distance metrics (Yeghiazaryan & Voiculescu, 2018), asd_R, asd_P, and $assd$ over R, P, and F score in ODS and OIS conditions. On the Cityscapes dataset, we test everything using the predictions of the VT method that outputs boundaries with constant, 2-pixel thickness. To show the sensitivity of the metrics to different thicknesses in the prediction and ground truth, we compare the original prediction (OP) with the scores achieved when *doubling* the thickness of the prediction (TP) or of the ground truth (TG). When computing the R, P, and F score, we use two experimental setups: i.e. *(i)* changing the used prediction threshold in an ODS and OIS fashion and *(ii)* and keeping it fixed to the same value t_0 used in OP. For the surface distance metrics, the threshold is always fixed as in every other experiment.

From the results in Table 1, it is clear that the R, P and F scores are strongly dependent on the relative thickness of ground truth and prediction with variations in the F score of over 27%, while the $assd$ is only affected by a 7% change. The small influence of thickness shows that the surface distance metrics are suited to evaluate predictions without the need to apply thinning as post-processing. Furthermore, the evaluation also shows that the metric does not provide an advantage to the proposed method for its thinner prediction.

5.2 REPRESENTATION PERFORMANCE COMPARISON

In this section, we show the performance of each representation and their corresponding losses on the three datasets considered. We do not apply non-maximum suppression so as to keep similar post-processing conditions throughout all methods and to evaluate the methods under the same conditions, so they could be integrated in other tasks §1. Our method consistently outperforms the other boundary representations in terms of $assd$, the metric less affected by the prediction thickness. Furthermore, it achieves competitive results for all other metrics, being the best performing method on Cityscapes and Mapillary Vistas in terms of F score. Throughout Table 2, 3, and 4, it is possible to see that VT is the most stable method on the F score, being able to predict uniformly thin results.

Figure 3: Qualitative comparison between methods on a Mapillary Vistas image from the test set. From left to right on the first row: the original image, the ground truth and the prediction using VT. On the second row: the prediction using WCL, DCL, DL, and DT.

Method	asd_R	asd_P	$assd$	ODS			OIS		
				R	P	F	R	P	F
VT	**1.73**	1.61	**1.67**	0.767	0.877	0.819	0.767	0.878	0.819
DCL	3.60	2.69	3.15	0.682	0.754	0.717	0.710	0.730	0.720
DL	3.02	**0.79**	1.91	0.810	0.905	0.855	0.816	0.898	0.855
WCL	1.76	1.81	1.79	**0.874**	**0.929**	**0.900**	**0.888**	**0.927**	**0.907**
DT	4.72	2.76	3.74	0.786	0.840	0.812	0.782	0.846	0.813

Table 3: Evaluation results on the Synthia dataset. Out of the 9000 images of this dataset, 6600 are used for training, 800 for validation and the remaining 1600 for testing.

Method	asd_R	asd_P	$assd$	ODS			OIS		
				R	P	F	R	P	F
VT	3.99	**3.20**	**3.60**	0.761	**0.857**	**0.806**	0.778	**0.842**	**0.809**
DCL	4.64	4.06	4.35	0.670	0.807	0.750	0.724	0.784	0.753
DL	5.16	3.28	4.22	0.735	0.787	0.760	0.733	0.792	0.761
WCL	**2.86**	5.67	4.27	0.759	0.730	0.744	0.767	0.763	0.765
DT	9.42	4.83	7.13	**0.856**	0.271	0.412	**0.856**	0.271	0.412

Table 4: Evaluation results on the Mapillary Vistas dataset. As no ground truth is given for the test set, the training set is divided in 17000 images for training and 1000 for validation, and the original 2000 images validation set is used for testing.

From the qualitative comparison between predictions in Fig. 3, it is evident that the Vector Transform is the only method able to predict crisp boundaries without requiring any non-maximum suppression. The DT transform in particular tends to predict thick boundaries as it predicts quite large regions with close to 0 *distances to the boundary* that cannot be thinned without post-processing. For more in-depth qualitative results and analysis, please refer to the Supplementary Material.

6 CONCLUSION

Despite being an old computer vision problem, boundary detection remains an active research field, both due to the many issues involved and its potential for other vision problems. In this paper, we propose the Vector Transform and theoretically demonstrate its equivalence with a surface representation of boundaries. The substantially different representation and corresponding approach of the Vector Transform automatically solve two of the biggest challenges: class imbalance in the prediction and the ability to output crisp boundaries. We show the high performance capabilities of the representation and a few related tasks that can be tackled from such an approach, with extensive evaluations. The formulation proposed in our work opens possibilities of new approaches on the use of boundaries and adds research questions on its applicability for several other related tasks.

REFERENCES

Pablo Arbelaez, Michael Maire, Charless Fowlkes, and Jitendra Malik. Contour detection and hierarchical image segmentation. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 33(5):898–916, 2010.

Pablo Arbeláez, Jordi Pont-Tuset, Jon Barron, Ferran Marques, and Jitendra Malik. Multiscale combinatorial grouping. In *2014 IEEE Conference on Computer Vision and Pattern Recognition*, pp. 328–335, 2014. doi: 10.1109/CVPR.2014.49.

Gedas Bertasius, Jianbo Shi, and Lorenzo Torresani. DeepEdge: A multi-scale bifurcated deep network for top-down contour detection. In *IEEE Conference on Computer Vision and Pattern Recognition*, pp. 4380–4389, 2015.

Yuri Boykov, Vladimir Kolmogorov, Daniel Cremers, and Andrew Delong. An integral solution to surface evolution PDEs via geo-cuts. In *European Conference on Computer Vision*, pp. 409–422, 2006.

Francesco Caliva, Claudia Iriondo, Alejandro Morales Martinez, Sharmila Majumdar, and Valentina Pedoia. Distance map loss penalty term for semantic segmentation. In *Medical Imaging with Deep Learning*, 2019.

John Canny. A computational approach to edge detection. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 8(6):679–698, 1986.

Thomas J Cashman and Andrew W Fitzgibbon. What shape are dolphins? building 3D morphable models from 2D images. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 35(1):232–244, 2012.

Tony Chan and Wei Zhu. Level set based shape prior segmentation. In *IEEE Conference on Computer Vision and Pattern Recognition*, pp. 1164–1170, 2005.

Tony F Chan and Luminita A Vese. Active contours without edges. *IEEE Transactions on Image Processing*, 10(2):266–277, 2001.

Liang-Chieh Chen, George Papandreou, Iasonas Kokkinos, Kevin Murphy, and Alan L Yuille. DeepLab: Semantic image segmentation with deep convolutional nets, atrous convolution, and fully connected CRFs. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 40(4):834–848, 2017.

Bowen Cheng, Maxwell D Collins, Yukun Zhu, Ting Liu, Thomas S Huang, Hartwig Adam, and Liang-Chieh Chen. Panoptic-DeepLab: A simple, strong, and fast baseline for bottom-up panoptic segmentation. In *IEEE Conference on Computer Vision and Pattern Recognition*, pp. 12475–12485, 2020.

Bowen Cheng, Alexander G Schwing, and Alexander Kirillov. Per-pixel classification is not all you need for semantic segmentation. *arXiv preprint arXiv:2107.06278*, 2021.

Ming-Ming Cheng, Yun Liu, Qibin Hou, Jiawang Bian, Philip Torr, Shi-Min Hu, and Zhuowen Tu. HFS: Hierarchical feature selection for efficient image segmentation. In *European Conference on Computer Vision*, pp. 867–882, 2016.

Dorin Comaniciu and Peter Meer. Mean shift: A robust approach toward feature space analysis. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 24(5):603–619, 2002.

Timothy F. Cootes, Gareth J. Edwards, and Christopher J. Taylor. Active appearance models. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 23(6):681–685, 2001.

Marius Cordts, Mohamed Omran, Sebastian Ramos, Timo Rehfeld, Markus Enzweiler, Rodrigo Benenson, Uwe Franke, Stefan Roth, and Bernt Schiele. The Cityscapes dataset for semantic urban scene understanding. In *IEEE Conference on Computer Vision and Pattern Recognition*, pp. 3213–3223, 2016.

Charles Dapogny and Pascal Frey. Computation of the signed distance function to a discrete contour on adapted triangulation. *Calcolo*, 49(3):193–219, 2012.

Ruoxi Deng, Chunhua Shen, Shengjun Liu, Huibing Wang, and Xinru Liu. Learning to predict crisp boundaries. In *European Conference on Computer Vision*, pp. 562–578, 2018.

Lee R Dice. Measures of the amount of ecologic association between species. *Ecology*, 26(3):297–302, 1945.

Piotr Dollár and C Lawrence Zitnick. Structured forests for fast edge detection. In *IEEE International Conference on Computer Vision*, pp. 1841–1848, 2013.

Martin Ester, Hans-Peter Kriegel, Jörg Sander, and Xiaowei Xu. A density-based algorithm for discovering clusters in large spatial databases with noise. In *Proceedings of the Second International Conference on Knowledge Discovery and Data Mining*, KDD'96, pp. 226–231. AAAI Press, 1996.

Pedro F Felzenszwalb and Daniel P Huttenlocher. Efficient graph-based image segmentation. *International Journal of Computer Vision*, 59(2):167–181, 2004.

Leo Grady. Random walks for image segmentation. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 28(11):1768–1783, 2006.

Sam Hallman and Charless C Fowlkes. Oriented edge forests for boundary detection. In *IEEE Conference on Computer Vision and Pattern Recognition*, pp. 1732–1740, 2015.

Bharath Hariharan, Pablo Arbeláez, Lubomir Bourdev, Subhransu Maji, and Jitendra Malik. Semantic contours from inverse detectors. In *International Conference on Computer Vision*, pp. 991–998, 2011.

Ali Hatamizadeh, Demetri Terzopoulos, and Andriy Myronenko. End-to-end boundary aware networks for medical image segmentation. In *International Workshop on Machine Learning in Medical Imaging*, pp. 187–194, 2019.

Jianzhong He, Shiliang Zhang, Ming Yang, Yanhu Shan, and Tiejun Huang. Bi-directional cascade network for perceptual edge detection. In *IEEE Conference on Computer Vision and Pattern Recognition*, pp. 3828–3837, 2019.

Phillip Isola, Daniel Zoran, Dilip Krishnan, and Edward H Adelson. Crisp boundary detection using pointwise mutual information. In *European Conference on Computer Vision*, pp. 799–814. Springer, 2014.

Michael Kass, Andrew Witkin, and Demetri Terzopoulos. Snakes: Active contour models. *International Journal of Computer Vision*, 1(4):321–331, 1988.

Hoel Kervadec, Jihene Bouchtiba, Christian Desrosiers, Eric Granger, Jose Dolz, and Ismail Ben Ayed. Boundary loss for highly unbalanced segmentation. In *International Conference on Medical Imaging with Deep Learning*, pp. 285–296, 2019.

Myungchul Kim, Sanghyun Woo, Dahun Kim, and In So Kweon. The devil is in the boundary: Exploiting boundary representation for basis-based instance segmentation. In *IEEE Winter Conference on Applications of Computer Vision*, pp. 929–938, 2021.

Alexander Kirillov, Kaiming He, Ross Girshick, Carsten Rother, and Piotr Dollár. Panoptic segmentation. In *IEEE Conference on Computer Vision and Pattern Recognition*, pp. 9404–9413, 2019.

Iasonas Kokkinos. Pushing the boundaries of boundary detection using deep learning. In *International Conference on Learning Representations*, 2016.

Scott Konishi, Alan L. Yuille, James M. Coughlan, and Song Chun Zhu. Statistical edge detection: Learning and evaluating edge cues. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 25(1):57–74, 2003.

Yun Liu, Ming-Ming Cheng, Xiaowei Hu, Kai Wang, and Xiang Bai. Richer convolutional features for edge detection. In *IEEE Conference on Computer Vision and Pattern Recognition*, pp. 3000–3009, 2017.

Yun Liu, Ming-Ming Cheng, Deng-Ping Fan, Le Zhang, JiaWang Bian, and Dacheng Tao. Semantic edge detection with diverse deep supervision. *arXiv preprint arXiv:1804.02864*, 2018.

Jun Ma, Jianan Chen, Matthew Ng, Rui Huang, Yu Li, Chen Li, Xiaoping Yang, and Anne L. Martel. Loss odyssey in medical image segmentation. *Medical Image Analysis*, 71:102035, 2021.

Wei-Ying Ma and Bangalore S Manjunath. Edgeflow: a technique for boundary detection and image segmentation. *IEEE transactions on image processing*, 9(8):1375–1388, 2000.

Kevis-Kokitsi Maninis, Jordi Pont-Tuset, Pablo Arbeláez, and Luc Van Gool. Convolutional oriented boundaries: From image segmentation to high-level tasks. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 40(4):819–833, 2017.

David R Martin, Charless C Fowlkes, and Jitendra Malik. Learning to detect natural image boundaries using local brightness, color, and texture cues. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 26(5):530–549, 2004.

Iain Matthews and Simon Baker. Active appearance models revisited. *International Journal of Computer Vision*, 60(2):135–164, 2004.

Lars Mescheder, Michael Oechsle, Michael Niemeyer, Sebastian Nowozin, and Andreas Geiger. Occupancy networks: Learning 3D reconstruction in function space. In *IEEE Conference on Computer Vision and Pattern Recognition*, pp. 4460–4470, 2019.

Ben Mildenhall, Pratul P Srinivasan, Matthew Tancik, Jonathan T Barron, Ravi Ramamoorthi, and Ren Ng. Nerf: Representing scenes as neural radiance fields for view synthesis. In *European Conference on Computer Vision*, pp. 405–421, 2020.

Vinod Nair and Geoffrey E Hinton. Rectified linear units improve restricted Boltzmann machines. In *International Conference on Machine Learning*, pp. 807–814, 2010.

Gerhard Neuhold, Tobias Ollmann, Samuel Rota Bulo, and Peter Kontschieder. The mapillary vistas dataset for semantic understanding of street scenes. In *IEEE International Conference on Computer Vision*, pp. 4990–4999, 2017.

Stanley Osher and Ronald P Fedkiw. *Level set methods and dynamic implicit surfaces*, volume 153. Springer, 2003.

Stanley Osher and James A Sethian. Fronts propagating with curvature-dependent speed: Algorithms based on hamilton-jacobi formulations. *Journal of Computational Physics*, 79(1):12–49, 1988.

Nikos Paragios, Mikael Rousson, and Visvanathan Ramesh. Matching distance functions: A shape-to-area variational approach for global-to-local registration. In *European Conference on Computer Vision*, pp. 775–789, 2002.

Jeong Joon Park, Peter Florence, Julian Straub, Richard Newcombe, and Steven Lovegrove. DeepSDF: Learning continuous signed distance functions for shape representation. In *IEEE Conference on Computer Vision and Pattern Recognition*, pp. 165–174, 2019.

Joseph Redmon, Santosh Divvala, Ross Girshick, and Ali Farhadi. You only look once: Unified, real-time object detection. In *IEEE Conference on Computer Vision and Pattern Recognition*, pp. 779–788, 2016.

Jerome Revaud, Philippe Weinzaepfel, Zaid Harchaoui, and Cordelia Schmid. EpicFlow: Edge-preserving interpolation of correspondences for optical flow. In *IEEE Conference on Computer Vision and Pattern Recognition*, pp. 1164–1172, 2015.

Olaf Ronneberger, Philipp Fischer, and Thomas Brox. U-Net: Convolutional networks for biomedical image segmentation. In *International Conference on Medical Image Computing and Computer-assisted Intervention*, pp. 234–241, 2015.

Germán Ros, Laura Sellart, Joanna Materzynska, David Vázquez, and Antonio M. López. The synthia dataset: A large collection of synthetic images for semantic segmentation of urban scenes. *2016 IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 3234–3243, 2016.

Wei Shen, Xinggang Wang, Yan Wang, Xiang Bai, and Zhijiang Zhang. DeepContour: A deep convolutional feature learned by positive-sharing loss for contour detection. In *IEEE Conference on Computer Vision and Pattern Recognition*, pp. 3982–3991, 2015.

Jianbo Shi and Jitendra Malik. Normalized cuts and image segmentation. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 22(8):888–905, 2000.

Nathan Silberman, Derek Hoiem, Pushmeet Kohli, and Rob Fergus. Indoor segmentation and support inference from RGBD images. In *European Conference on Computer Vision*, pp. 746–760, 2012.

Vincent Sitzmann, Julien Martel, Alexander Bergman, David Lindell, and Gordon Wetzstein. Implicit neural representations with periodic activation functions. *Advances in Neural Information Processing Systems*, pp. 7462–7473, 2020.

Irwin Sobel. Camera models and machine perception. Technical report, Computer Science Department, Technion, 1972.

Matthew Tancik, Pratul P Srinivasan, Ben Mildenhall, Sara Fridovich-Keil, Nithin Raghavan, Utkarsh Singhal, Ravi Ramamoorthi, Jonathan T Barron, and Ren Ng. Fourier features let networks learn high frequency functions in low dimensional domains. *arXiv preprint arXiv:2006.10739*, 2020.

Chi Wang, Yunke Zhang, Miaomiao Cui, Jinlin Liu, Peiran Ren, Yin Yang, Xuansong Xie, XianSheng Hua, Hujun Bao, and Weiwei Xu. Active boundary loss for semantic segmentation. *arXiv preprint arXiv:2102.02696*, 2021a.

Huiyu Wang, Yukun Zhu, Hartwig Adam, Alan Yuille, and Liang-Chieh Chen. Max-DeepLab: End-to-end panoptic segmentation with mask transformers. In *IEEE Conference on Computer Vision and Pattern Recognition*, pp. 5463–5474, 2021b.

Jingdong Wang, Ke Sun, Tianheng Cheng, Borui Jiang, Chaorui Deng, Yang Zhao, Dong Liu, Yadong Mu, Mingkui Tan, Xinggang Wang, et al. Deep high-resolution representation learning for visual recognition. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 43(10):3349–3364, 2020.

Yupei Wang, Xin Zhao, Yin Li, and Kaiqi Huang. Deep crisp boundaries: From boundaries to higher-level tasks. *IEEE Transactions on Image Processing*, 28(3):1285–1298, 2018.

Saining Xie and Zhuowen Tu. Holistically-nested edge detection. In *IEEE International Conference on Computer Vision*, pp. 1395–1403, 2015.

Saining Xie, Ross Girshick, Piotr Dollár, Zhuowen Tu, and Kaiming He. Aggregated residual transformations for deep neural networks. In *IEEE Conference on Computer Vision and Pattern Recognition*, pp. 1492–1500, 2017.

Jimei Yang, Brian Price, Scott Cohen, Honglak Lee, and Ming-Hsuan Yang. Object contour detection with a fully convolutional encoder-decoder network. In *IEEE Conference on Computer Vision and Pattern Recognition*, pp. 193–202, 2016.

Varduhi Yeghiazaryan and Irina D Voiculescu. Family of boundary overlap metrics for the evaluation of medical image segmentation. *Journal of Medical Imaging*, 5(1):015006, 2018.

Zhiding Yu, Chen Feng, Ming-Yu Liu, and Srikumar Ramalingam. CASENet: Deep category-aware semantic edge detection. In *IEEE Conference on Computer Vision and Pattern Recognition*, pp. 5964–5973, 2017.

Zhiding Yu, Weiyang Liu, Yang Zou, Chen Feng, Srikumar Ramalingam, BVK Kumar, and Jan Kautz. Simultaneous edge alignment and learning. In *European Conference on Computer Vision*, pp. 388–404, 2018.

Shengjie Zhu, Garrick Brazil, and Xiaoming Liu. The edge of depth: Explicit constraints between segmentation and depth. In *IEEE Conference on Computer Vision and Pattern Recognition*, pp. 13116–13125, 2020.

A VECTOR TRANSFORM IN PRACTICE

There are some aspects of Vector Transform which requires special attention in several non-ideal cases. The first is the case of ground truth generation in datasets that were not designed with the interpretation of boundaries as surfaces. The second is the case of theoretical and practical aspects related to discontinuities and discretization.

GROUND TRUTH GENERATION

We now explain how in practice, we extract the Vector Transform from the ground truth boundary images to train the proposed method. For non-boundary pixels, the solution of the Vector Transform is clearly defined as the direction towards the closest boundary. In practice, to mitigate for discretization-related errors, the closest boundary pixel is computed averaging the multiple closest ones. This has the same effect of interpolating a planar surface on the set of closest boundary pixels and computing the normal direction to that surface. In the extreme case in which there are multiple equally distant boundaries, only one is chosen randomly as the closest one and the direction is computed towards it.

For boundary pixels, there can be multiple scenarios to take into account depending on the dataset quality:

- If the boundary is taken from a segmentation image, it can be treated as a non boundary pixel with its direction computed toward the closest set of pixel outside its semantic class/instance object.

- If the boundary is a manually annotated single pixel boundary, it is possible to consistently pair it to one of the neighboring non-boundary pixels and use its same vector direction. Any neighboring non-boundary pixel can be taken as long as the selection process remains consistent for each case.

- In case of thick boundaries, it is possible to devise a technique to assign a direction to each of its pixels - such as the direction of the closest non-boundary pixel and similarly to the previous point in undecided cases. However, this is not a proper definition of a surface boundary and, in practice, it is not considered in any of the tested cases.

DISCONTINUITIES AND DISCRETIZATION

As explored in §3, the invertibility of the vector transform does not strictly satisfy at discontinuities. Around the infinitesimal neighborhood of the discontinuous boundary, the divergence is evaluated using an approximate normal. It can be observed that under a large number of circumstances, the transform can yield lower than -2 or -2 value in many discontinuities. However, the discretization and/or its combination with the discontinuities can impact the transform, where we may observe a higher than -2 divergence of the field. Fortunately, the representation provides a relatively large margin between the divergence of a non-boundary point from that of any other point. Such a margin provides the robustness required in order to predict correct boundaries even in crowded regions.

B QUALITATIVE RESULTS ANALYSIS

In this section we report more qualitative results to support the observations in Section 5. We show results obtained with every method on an image taken from each of the datasets. From the qualitative comparison of predictions in Figure 4, it is evident that Vector Transform is the only method able to always predict crisp boundaries without requiring any non-maximum suppression. This provides a significant advantage, particularly in crowded regions where traditional methods require NMS post-processing to be used for downstream tasks. Therefore, our method provides a strong advantage when used at training time as an aide for different tasks.

Figure 4: Qualitative comparison between methods.For each of the three examples, from left to right on the first row, there is the original image, the ground truth and the prediction using VT. On the second row, there is the prediction using WCL, DCL, and DT. From top to bottom, the first image is taken from Cityscapes test set, the second from Synthia and the third from Mapillary Vistas.

Figure 5: Qualitative results of the boundary direction estimation on three images of Mapillary Vistas test set. In the figures, the direction of the boundaries is plotted to the boundary pixels, which are thickened to ease visualization. Vertical lines correspond to colors in the range of green and blue that gradually turn into red and pink for horizontal lines.

C BSDS500 EVALUATION

We show here a comparison of the performance on the traditionally used BSDS500 dataset (Arbelaez et al., 2010). While having tremendous impact on the boundary detection task, the dataset also suffers from problems such as an unclear definition of a boundary - it can vary between different annotators - and a very limited dataset training size of just 200 images as well as relatively low image resolution. Every method is trained on the BSDS500 (Arbelaez et al., 2010) training set, using the network pretrained on Mapillary Vistas dataset, to try and finetune the weights for the different type of boundaries. The VT field is particularly sensitive to inconsistent annotations as they change the morphology of the whole field and errors are not limited to the isolated pixel.

We show the results achieved by our network with different representations using the BSDS500 (Arbelaez et al., 2010) evaluation code and the surface distance metrics. As a reference point we set the estimated human level at an F-score of 0.8. Despite being not the state of the art and far from human performance in the evaluation, the result shows that our representation is also able to predict low-level image contours without instances or classes. Every representation struggles to achieve high quality results, but the VT representation is still achieves the second best accuracy both in terms of $assd$ and F score. To show its full capabilities in such low-level contours, it will be necessary to have a larger dataset with a clear definition of boundary, which is not currently available up to our knowledge.

D BOUNDARY DIRECTION ESTIMATION

As our method outputs the VT for each pixel, when the boundaries are represented inside the image, it is natural to extract the boundary direction. Differently from other methods (Maninis et al., 2017), no additional module or post-processing is required to estimate the direction. Furthermore, our method is able to predict continuous angles without the necessity to select from a discrete set of values.

Method	asd_R	asd_P	$assd$	ODS			OIS		
				R	P	F	R	P	F
VT	5.06	6.59	5.83	**0.72**	0.638	0.676	**0.721**	0.637	0.676
DCL	6.44	6.14	6.29	0.598	0.559	0.578	0.597	0.560	0.578
DL	7.99	5.81	6.90	0.540	0.534	0.537	0.543	0.531	0.537
WCL	**4.04**	7.28	**5.66**	0.660	0.718	**0.688**	0.662	0.716	**0.688**
DT	6.44	**5.30**	5.87	0.395	**0.860**	0.541	0.395	**0.860**	0.541
Human	/	/	/	/	/	0.8	/	/	0.8

Table 5: Evaluation results on the BSDS500 (Arbelaez et al., 2010) test set.

Figure 6: Qualitative example of line detection using the VT field on three images of Mapillary Vistas test set. In the images, the straight lines in the boundaries are identified with the red colors. For visualization purposes, the boundaries have first been artificially thickened before detecting straight lines.

In Figure 5, we show a qualitative representation of our boundary direction estimation on three example images from Mapillary Vistas to have a visualization of the prediction quality. From a quantitative standpoint, the predicting VT field can achieve a mean squared error on the estimated angle θ of 7.2 degrees.

E STRAIGHT LINE PROPOSALS

Given that in our method each boundary pixel has a direction feature, it is natural to try and solve the task of straight line proposal generation for detection without any specific supervision. A straight line is considered a boundary for which the direction does not change in neighboring pixels. To detect such points, it is possible to apply a simple algorithm:

- First the VT field is converted using only the absolute value of the two channels. In this way, differences of vectors having same orientation but opposite direction on the two sides of a boundary are removed.

- Then the derivative of the two channels are approximated using a Sobel filter and their absolute values are summed in a pixelwise manner.

- In the obtained image, pixels with a high value indicate places where the orientation changes while the low values show constant orientation. Therefore, we define a threshold ($t = 0.05$) and consider part of a straight line the boundary pixels with a value below the threshold.

In Figure 6, we show some qualitative results obtained with the above method. It is possible to identify short straight lines detected in areas of the image without an apparent straight line. This is due to the small dimension (3×3) of the derivative kernel used to detect a straight line and could be solved by filtering the prediction. We show the result without postprocessing as a proof that our method can be applied no matter what type of line detection is needed, from small segments to long lines.

F SUPERPIXEL

The VT field can also be used to create superpixels without any specific supervision. More specifically, when they are trained on semantically meaningful boundaries, they can be used to extract objects or object parts. This can be done without obtaining the partial result of boundaries, using only the fields and applying region growing algorithm on it. Specifically, we use the following algorithm:

- First, divergence is computed on the VT field using a Sobel filter as done to obtain boundary pixels. The high divergence values are the source points in the field and are treated as

Figure 7: Examples of superpixels obtained on three images of Mapillary Vistas test set using four different methods. From top to bottom: the original images, the superpixels obtained using the VT field, COB (Maninis et al., 2017), MCG (Arbeláez et al., 2014), and SCG (Arbeláez et al., 2014), respectively.

centroids of the parts. In case there is a connected part with high divergence, it is considered to be a single centroid region.

- Each pixel is associated to a two dimensional point based on its coordinates on the image grid. The point is then moved (its coordinates are changed) following the opposite of the field direction, towards the center and away from the border. This continues until the algorithm converges or for a maximum number of steps. This results in each pixel being associated with a point that has been moved to a different position from the original.

- Based on the position of the obtained point, the pixels are then assigned to the closest part centroid. Thanks to the complex shapes that the centroid regions can assume, the resulting clusters can have high structural complexity and represent complete objects or large parts. In the special case of pixels with an associated point that falls outside of the image border, an assignment to a part centroid cannot be done. These pixels are then clustered using DBSCAN (Ester et al., 1996) algorithm using as features the position of the associated points.

The technique benefits from the possibility of being made highly parallel with the clustering algorithm that only needs to be applied on a limited number of well separated points. We show some results obtained by grouping pixels based on the predicted Vector Transform in Figure 7. We compare to some well-know superpixel methods, i.e., Convolutional Oriented Boundaries (COB) (Maninis et al., 2017), Multiscale Combinatorial Grouping (MCG) (Arbeláez et al., 2014), and Singlescale Combinatorial Grouping (SCG) (Arbeláez et al., 2014), whose results are generated by thresholding the occlusion boundaries (Ultrametric Contour Map, UCM (Arbelaez et al., 2010)) using the optimal threshold of each method. It is visible that the VT field can group an object with high complexity as a single superpixel, which can ease downstream tasks that benefit from such a characteristic. In contrast, previous methods tend to create a higher number of clusters whose boundaries are not always coincidental with the complete objects. This task further justifies our re-definition of boundary detection.