On the Provable Generalization of Recurrent Neural Networks

Abstract

Recurrent Neural Network (RNN) is a foundational structure in deep learning. Recently, some works study the training process of over-parameterized neural networks, and show that over-parameterized networks can learn functions in some notable concept classes with a provable generalization error bound. In this paper, we analyze the training and generalization for RNN with random initialization, and provide the following improvements over recent works:

(1) For a RNN with input sequence $x = (X_1, X_2, ..., X_L)$, previous works study to learn functions that are summation of $f(\beta_l^T X_l)$ and require normalized conditions that $||X_l|| \leq \epsilon$ with some very small ϵ depending on the complexity of f. In this paper, using detailed analysis about the neural tangent kernel matrix, we prove a generalization error bound to learn such functions without normalized conditions and show that some notable concept classes are learnable with the numbers of iterations and samples scaling almost-polynomially in the input length L.

(2) Moreover, we prove a novel result to learn N-variables functions of input sequence with the form $f(\beta^T[X_{l_1}, ..., X_{l_N}])$, which do not belong to the "additive" concept class, i,e., the summation of function $f(X_l)$. And we show that when either N or $l_0 = \max(l_1, .., l_N) - \min(l_1, .., l_N)$ is small, $f(\beta^T[X_{l_1}, ..., X_{l_N}])$ will be learnable with the number iterations and samples scaling almost-polynomially in the input length L.

1 Introduction

In Deep Learning, the recurrent neural network (RNN) is well-known as one of the most popular models to model sequential data and is widely used in practice for tasks in natural language processing (NLP). One of the characters of RNN is that it performs the same operation for all the input of the sequence.

Consider a input sequence $x = (X_1, X_2, ..., X_L)$. A RNN with the form

$$h_l(x) = \phi(\boldsymbol{W} h_{l-1} + \boldsymbol{A} X_l),\tag{1}$$

is trying to learn functions $f_l(X_1, X_2, ...X_l)$ as

$$\begin{aligned}
h_1(x) &= f_1(X_1) \\
h_2(x) &= f_2(X_1, X_2) \\
&\vdots \\
h_L(x) &= f_L(X_1, X_2, ...X_L)
\end{aligned}\tag{2}$$

Submitted to 35th Conference on Neural Information Processing Systems (NeurIPS 2021). Do not distribute.

Due to the complex nonlinearity, the loss is generally non-convex, and it is very difficult to give a theoretical guarantee. Recently, there are some works[Allen-Zhu et al., 2019b, Cao and Gu, 2019, Allen-Zhu et al., 2019a, Du et al., 2019, Arora et al., 2019, Allen-Zhu et al., 2019c] trying to give a theoretical explanation that why gradient descent can allow an overparametrized network to attain arbitrarily low training error and ample generalization. These papers show that, under some assumptions, we have:

- *Multi-layer feed-forward networks[Allen-Zhu et al., 2019b, Du et al., 2019] and recurrent neural networks[Allen-Zhu et al., 2019c] with large hidden size can attain zero training error, regardless of whether the data is properly labeled or randomly labeled.*

- *For multi-layer feed-forward networks, functions with the form $F^*(x) = \sum_{r=1}^{C} \phi_r(\beta_r^T X), X \in \mathbb{R}^d, \beta_r \in \mathbb{R}^d, ||\beta_r|| = 1$ are learnable i.e. fitting the training data with a provably small generalization error, if ϕ is analytic and the "complexity" is low enough[Allen-Zhu et al., 2019a, Arora et al., 2019, Cao and Gu, 2019].*

- *The "complexity" of function ϕ can be measured by a matrix derived from the NTK (Neural Tangent Kernel) of the network[Arora et al., 2019, Cao and Gu, 2019].*

- *For recurrent neural networks[Allen-Zhu and Li, 2019a], if the input sequence is normalized, i.e., $x = (X_1, X_2, ..., X_L), ||X_1|| = 1, ||X_l|| = \epsilon$ with ϵ very small, functions with the form $F^*(x) = \sum_{l=1}^{L} \sum_{r=1}^{C_l} \phi_{l,r}(\beta_{l,r}^T X_l)$ are learnable, where m is the size of matrix $\boldsymbol{W}$, and $\mathscr{C} = \sum_{i=0}^{\infty} a_i R^i$ is a series representing the complexity of learnable functions.*

These work show the provable learning ability of deep learning. But there are still some issues that were not addressed in these papers. For RNNs, the method in [Allen-Zhu and Li, 2019a] requires a normalized condition for $\boldsymbol{A}$ and X_l in (1) that $||\boldsymbol{A}X_l|| \leq \epsilon_x$ and shows that, for a function $F^*(x)$ with complexity $\mathscr{C}$, it is learnable with error $O(\epsilon_x^{1/3}\mathscr{C})$. Thus $||X_l||$ (or equally, $||\boldsymbol{A}||$) should be very small and the scale is dependent on the complexity of functions. The dependence of $||\boldsymbol{A}X_l||$ on $\mathscr{C}$ makes the results rely on the linear expansion of RNNs to the input X, rather than the RNN generally used.

On the other hand, the result in [Allen-Zhu and Li, 2019a] shows that RNNs can learn functions which are the summation of functions like $\psi(\beta_l^T X_l)$. One may ask, since $h_L(x)$ is a function of $\{X_1, X_2, ...X_L\}$, is it possible to go beyond and learn more complex functions?

In order to study these problems, we consider the binary classification problem: for every input x_i, the label ($+1$ or -1) of x_i can be expressed by the sign of a target function $F^*(x_i)$. We consider Elman recurrent neural networks with ReLU activation

$$
\begin{aligned}
& h_l(x) = \phi(\boldsymbol{W}h_{l-1} + \boldsymbol{A}X_l) \\
& f(\boldsymbol{W}, x) = \boldsymbol{B}^T h_L(x) \in \mathbb{R}. \\
& x = (X_1, X_2, ..., X_L), X_l \in \mathbb{R}^d, \boldsymbol{W} \in \mathbb{R}^{m \times m}, \\
& \boldsymbol{A} \in \mathbb{R}^{m \times d}, \boldsymbol{B} \in \mathbb{R}^m, \phi(x) = \max(x, 0)
\end{aligned}
\tag{3}
$$

to learn two types of target functions:

- Additive Concept Class:

$$
\begin{aligned}
& F^*(x) = \sum_{l=1}^{L} \sum_{r=1} \psi_{l,r}(\beta_{l,r}^T X_l/||X_l||), \\
& \psi_{l,r}(x) = \sum_{i=0}^{\infty} c_i x^i,
\end{aligned}
\tag{4}
$$

- N-variables Concept Class:

$$
\begin{aligned}
& F^*(x) = \sum_{r} \psi_r(\langle \beta_r, [X_{l_1}, ..., X_{l_N}] \rangle), \\
& \psi_r(x) = \sum_{i=0}^{\infty} c_i x^i.
\end{aligned}
\tag{5}
$$

For these two types of function, we study the following questions:

- Can RNN learn additive concept class functions (4) without the normalized condition with **reasonable complexity on the sequence size** L?
- Can RNN learn functions in N-variables Concept Class (5) which can not be written as the summation of $f(X_l)$ with **reasonable complexity on** N **and** L?

Our Result. We answer the two question and give a provable generalization error bound. Our results are stated as follows:

Theorem 1 *(Informal) For a function* $F^*(X_1, X_2, ..., X_L)$ *with the form as in (4) or (5), there is a power series named the complexity* $\mathscr{C}(F^*)$ *dependent on the Taylor expansion coefficient in (4) and (5). For (4),* $\mathscr{C}(F^*)$ *is almost-polynomial in* L. *For (5), when* N *or* $l_0 = \max(l_1, .., l_N) - \min(l_1, .., l_N)$ *is small,* $\mathscr{C}(F^*)$ *is almost-polynomial in* L. *Under this definition of complexity* $\mathscr{C}(F^*)$, F^* *is learnable using RNN with* m *hidden nodes and ReLU activation in (3) in* $\mathcal{O}(\mathscr{C}(F^*)^2)$ *steps with* $\mathcal{O}(\mathscr{C}(F^*)^2)$ *samples if* $m \geq poly(n, L, \mathscr{C}(F^*))$.

Contribution. We summarize the contributions as follows:

- *In this paper, we prove that RNN without normalized condition can efficiently learn some notable concept classes with* **both time and sample complexity scaling almost polynomially in the input length** L.
- *Our results go beyond the "additive" concept class. We prove a novel result that RNN can learn more complex function of the input such as N-variables concept class functions. And "long range correlation functions" with small* N *(e.g.* $N = 2$, $f(\beta^T[X_l, X_{l+l_0}])$ *) are learnable with* **complexity scaling almost polynomially in the input length** L **and correlation distance** l_0.
- *Technically, we study the "backward correlation" of RNN network. In RNN case, using a crucial observation on the degeneracy of deep network, we show that the* **"backward correlation"** $\frac{1}{m}\langle \mathbf{Back}_l(x_i), \mathbf{Back}_l(x_j)\rangle$ **will decay polynomially rather than exponentially in input length** L. *This shows the complexity of learning RNN with ReLU activation function is polynomial in the size of input sequence* L.

Notions. For two matrices $\boldsymbol{A}, \boldsymbol{B} \in \mathbb{R}^{m \times n}$, we define $\langle \boldsymbol{A}, \boldsymbol{B} \rangle = \mathrm{Tr}(A^T B)$. We define the asymptotic notations $\mathcal{O}(\cdot), \Omega(\cdot), poly(\cdot)$ as follows. a_n, b_n are two sequences. $a_n = \mathcal{O}(b_n)$ if $\limsup_{n\to\infty} |a_n/b_n| < \infty$, $a_n = \Omega(b_n)$ if $\liminf_{n\to\infty} |a_n/b_n| > 0$, $a_n = poly(b_n)$ if there is $k \in \mathbb{N}$ that $a_n = O((b_n)^k)$. $\widetilde{\mathcal{O}}(\cdot), \widetilde{\Omega}(\cdot), \widetilde{poly}(\cdot)$ are notions which hide the logarithmic factors in $\mathcal{O}(\cdot), \Omega(\cdot), poly(\cdot)$. $|| \cdot ||$ and $|| \cdot ||_2$ denote the 2-norm of matrices. $|| \cdot ||_1$ denote the 1-norm. $|| \cdot ||_F$ is the Frobenius-norm. $|| \cdot ||_0$ is the number of non-zero entries.

For elements $A_{i,j}, B_{i,j}$ of symmetric matrix $\boldsymbol{A}, \boldsymbol{B}$. We abuse the notion $A_{i,j} \succeq B_{i,j}$ to denote $\boldsymbol{A} \succeq \boldsymbol{B}$, i.e. $\boldsymbol{A} - \boldsymbol{B}$ is a positive semidefinite matrix.

2 Preliminaries

2.1 Function Complexity

For a analytic function $\psi(z)$, we can write it as $\psi(z) = c_0 + \sum_{i=1}^{\infty} c_i z^i$. We define the following notion to measure the complexity to learn such functions.

$$\mathscr{C}(\psi, R) = 1 + \sum_{i=1}^{\infty} i \cdot |c_i| R^i. \tag{6}$$

$$\mathscr{C}_N(\psi, R) = 1 + \sum_{i=1}^{\infty} L^N C_1^N \cdot \sqrt{C_{N,i}} \cdot (i/N)^N \cdot |c_i| R^i \tag{7}$$

where $C_1 > 100$ is an large absolute constant and $C_{N,i}$ is the largest combination number $\frac{i!}{n_1! n_2! ... n_N!}$ for $n_1, n_2 ... n_N > 0, n_1 + n_2 + ... n_N = i,$

Example 2.1 *[Arora et al., 2019] Consider $\psi(z) = arctan(z/2)$. Then*

$$\psi(z) = \sum_{i=1} \frac{(-1)^{i-1}2^{1-2i}}{2i-1} z^{2i-1} \tag{8}$$

In this case,

$$\mathscr{C}(\psi, 1) = 1 + \sum_{i=1}^{\infty} i \cdot |c_i| \le 1 + \sum_{i=1}^{\infty} 2^{1-2i} \le \mathcal{O}(1).$$

Example 2.2 *In the case $N = 2$, $C_{2,i} = i$, $(i/2)^2 \le i^2$. $\psi(z) = exp(z)$*

$$\mathscr{C}_2(\psi, 1) \le 1 + \sum_{i=1}^{\infty} L^2 C_1^2 \pi i^{2.5}/i! \le \mathcal{O}(1)$$

2.2 Concept Class

For the input sequence $\{X_l\}$, we assume $C_{min} \le ||X_l|| \le C_{max}$, for all $1 \le l \le L$ and $C_{max}/C_{min} \le \mathcal{O}(C_0)$. Under this condition, we consider two types of target functions with the following form:

Additive Concept Class.

$$F^*(x) = \sum_{l=1}^{L} \sum_{r=1}^{C_l} \psi_{l,r}(\beta_{l,r}^T X_l/||X_l||). \tag{9}$$

Here for all l, r, $\psi_{l,r}$ is analytic and $||\beta_{l,r}||_2 \le 1$.

We define

$$\mathscr{C}(F^*) = L^3 \sum_{l=1}^{L} \sum_{r=1}^{C_l} \mathscr{C}(\psi_{l,r}, C_0\sqrt{L}), \tag{10}$$

to be the complexity of the target function.

Remark 2.1 *If we consider function $\psi(\beta^T X_l)$ and $||X_l|| = 1$ for all l, the above complexity will become $\mathscr{C}(\psi, \mathcal{O}(\sqrt{L}))$. This is similar with that in [Allen-Zhu and Li, 2019a] but this complexity requirement is much weaker than that in [Allen-Zhu and Li, 2019a]. For example, the complexity of $arctan(z/2)$ in [Allen-Zhu and Li, 2019a] is not finite, as shown in [Arora et al., 2019].*

N-variables Concept Class.

$$F^*(x) = \sum_{r} \psi_r(\langle \beta_r, [X_{l_1}, ..., X_{l_N}] \rangle)/\sqrt{N} \max ||X_{l_n}||). \tag{11}$$

For all r, $\psi_{l,a,r}(x, y)$ is an analytic function $\psi_r(x) = c_0 + \sum_{i=1}^{\infty} c_i x^i$. $\beta_r \in \mathbb{R}^{dN}$, $||\beta_r||_2 \le 1$. Let $l_0 = \max(l_1, .., l_N) - \min(l_1, .., l_N)$. We define

$$\mathscr{C}(F^*) = \min(L^2 \mathscr{C}_N(\psi_r, C_0\sqrt{L}), L^3 \mathscr{C}(\psi_r, 2^{l_0} C_0\sqrt{L})). \tag{12}$$

Remark 2.2 *The complexity $\sum_r \mathscr{C}_N(\psi_r, C_0\sqrt{L})$ and $\sum_r \mathscr{C}(\psi_r, 2^{l_0} C_0\sqrt{L})$ are exponential in N and l_0 respectively. And $\mathscr{C}(F^*)$ is less or equal than both. Thus if either l_0 or N is small, $\mathscr{C}(F^*)$ will be polynomial in L. Especially when N is small(e.g. $N=2$), even if $l_0 = L - 1$, functions with the form $f(\beta^T[X_l, X_{l+l_0}])$ are still learnable with a low complexity.*

2.3 Results on Positive Definite Matrices and Functions

We say a function $\phi(\cdot, \cdot) : \mathbb{R}^d \times \mathbb{R}^d \to \mathbb{R}$ is positive definite if for all $n \in \mathbb{N}$, any $\{x_1, ..., x_n\} \subseteq \mathbb{R}^d, \{c_1, ..., c_n\} \subseteq \mathbb{R}$,

$$\sum_{i,j} c_i c_j \phi(x_i, x_j) \ge 0. \tag{13}$$

The following basic properties in chapter 3 of [BergJens et al., 1984] are very useful in our proof.

130 **Proposition 2.1** *If $\phi(\cdot, \cdot)$ is positive definite function, let matrix $M \in \mathbb{R}^{n \times n}$, $\{x_1, ..., x_n\} \subseteq \mathbb{R}^d$,*
131 *and $M_{i,j} = \phi(x_i, x_j)$. Then M is a semi-positive definite matrix.*

132 **Proposition 2.2** *If $\phi_1(\cdot, \cdot)$ and $\phi_1(\cdot, \cdot)$ are positive definite, $\phi(x_i, x_j) = \phi_1(x_i, x_j) \cdot \phi_2(x_i, x_j)$ is*
133 *also a positive definite function.*

134 **Proposition 2.3** *Let $\phi(\cdot, \cdot)$ be a positive definite function, and $\psi(x) = \sum_{i=0}^{\infty} c_i x^i$, $c_i \geq 0$. Then*
135 *$\psi(\phi(\cdot, \cdot))$ is also a positive definite function.*

136 For a positive definite matrix $M \in \mathbb{R}^{n \times n}$, there is a result in [Arora et al., 2019],

137 **Proposition 2.4** *(Section E of [Arora et al., 2019].) Let $X = (x_1, ...x_n) \in \mathbb{R}^{d \times n}$ and $K_p \in \mathbb{R}^{n \times n}$*
138 *is a matrix with $(K_p)_{i,j} = (x_i^T x_j)^p$. Suppose there is $\alpha > 0$, such that $M \succeq \alpha^2 K_p$. Let*
139 *$y = ((\beta^T x_1)^p, ..., (\beta^T x_n)^p) \in \mathbb{R}^n$. We have $\sqrt{y^T (M)^{-1} y} \leq ||\beta||_2^p / \alpha$.*

3   Main Results

141 Assume there is an unknown data set $\mathcal{D} = \{x, y\}$. The inputs have the form $x = (X_1, X_2, ...X_L) \in$
142 $(\mathbb{R}^d)^L$. $||X_l|| \leq \mathcal{O}(1)$ for all $1 \leq l \leq L$. For every input x_i, there is a label $y_i = \pm 1$.

143 The neural network with input x is

$$h_0(x) = \phi(M_0),$$
$$h_l(x) = \phi(W h_{l-1} + A X_l), \tag{14}$$
$$f(W, x) = B^T h_L(x).$$

144 Here $W \in \mathbb{R}^{m \times m}, A \in \mathbb{R}^{m \times d}, B, M_0 \in \mathbb{R}^m$. The entries of M_0, W and A are respectively
145 i.i.d. generated from $N(0, \frac{2}{m})$, $N(0, \frac{2}{m})$ and $N(0, \frac{2}{L^3 \cdot m})$. The entries of B are i.i.d. generated from
146 $N(0, \frac{1}{m})$.

147 The goal of learning RNN is to minimize the population loss:

$$L_{\mathcal{D}}(W) = \mathbb{E}_{(x,y) \sim \mathcal{D}} \ell(y \cdot f(W, x)), \tag{15}$$

148 by optimizing the empirical loss

$$L_S(W) = \frac{1}{n} \sum_{i=1}^{n} \ell(y_i \cdot f(W, x_i)), \tag{16}$$

149 using SGD. Here $\ell(x) = \log(1 + exp(-x))$ is the cross-entropy loss. Consider the SGD algorithm on this RNN. Let the complexity $\mathscr{C}^*$ of $F^*(\cdot)$ be defined in (10) and (12). The 0-1 error for $\mathcal{D}$ is

---

Algorithm 1: Training RNN with SGD

Input: Data set $\mathcal{D}$, learning rate η.
The entries of W^0, A are i.i.d. generated from $N(0, \frac{2}{m})$. The entries of B are i.i.d. generated from $N(0, \frac{1}{m})$.
for $t = 1, 2, 3...n$ **do**
  Randomly sample (x_t, y_t) from the data set $\mathcal{D}$.
  $W^t = W^{t-1} - \eta \nabla_{W^{t-1}} \ell(y_t \cdot f(W^{t-1}, x_t))$.
end

150
151 $L_{\mathcal{D}}^{0-1}(W) = \mathbb{E}_{(x,y) \sim \mathcal{D}} \mathbb{1}\{y \cdot f(W, x) < 0\}$. We have:

152 **Theorem 2** *Assume there is $\delta \in (0, e^{-1}]$. Supposing for $\mathcal{D} = \{x_i, y_i\}$, there is a function F^**
153 *belonging to the concept class (9) or (11) such that $y_i \cdot F^*(x_i) \geq 1$ for all i. Let W^k be the output of*
154 *Algorithm 1. There is a parameter $m^*(n, \delta, L, \mathscr{C}^*) = poly(n, \delta^{-1}, L, \mathscr{C}^*)$ such that, with probability*
155 *at least $1 - \delta$, if $m > m^*(n, \delta, L)$, there exits parameter $\eta = \mathcal{O}(1/m)$ that satisfies*

$$\frac{1}{n} \sum_{k=1}^{n} L_{\mathcal{D}}^{0-1}(W^k) \leq \widetilde{\mathcal{O}}[\frac{(\mathscr{C}^*)^2}{n}] + \mathcal{O}(\frac{\log(1/\delta)}{n}). \tag{17}$$

Remark 3.1 *This theorem induces that, to achieve **population** $0 - 1$ **error**(rather than empirical loss) being less than ϵ, it is enough to train the network using Algorithm 1 with $\widetilde{\Omega}((L \cdot \mathscr{C}^*)^2/\epsilon)$ steps. As defined in section 2.1 and 2.2, when N is small, for the two types of concept class, $(\mathscr{C}^*)^2$ is almost-polynomial in input length L. Thus they can be learned effectively.*

Remark 3.2 *This theorem can also be generalized to "sequence labeling" loss such as $\frac{1}{n}\sum_{i=1}^{n}\sum_{l=1}^{L}\ell(y_i \cdot f_l(\boldsymbol{W}, x_i))$ with $f_l(\boldsymbol{W}, x) = \boldsymbol{B}^T h_l(x)$. This is because the matrix*

$$H_{i,j}^l = \frac{1}{m}\langle \nabla f_l(\boldsymbol{W}, x_i), \nabla f_l(\boldsymbol{W}, x_j)\rangle$$

with different l are almost "orthogonal" by a similar argument to (26) in Theorem 6. Then RNN can learn a function $f_l = sign(F_l^*(x))$ with $F_l^*(x)$ belonging to functions in section 2.2. See Remark H.1 in the supplementary materials.

Remark 3.3 *Note that in this theorem, different from that in [Cao and Gu, 2019, Arora et al., 2019], we make no assumptions on the data distribution $\mathcal{D}$ and the results do not dependent on the minimum eigenvalue of kernel matrix. Therefore this is a PAC learning type of result as in [Allen-Zhu and Li, 2019a]. In [Cao and Gu, 2019, Arora et al., 2019], matrix perturbation is used and m should be larger than λ_0^{-1} with $\lambda_0 = \lambda_{min}(\boldsymbol{H})$. Using their methods, we can show there is a parameter $m^*(n, \delta, L, \lambda_0) = poly(n, \delta^{-1}, L, \lambda_0^{-1})$ such that if $m > m^*(n, \delta, L, \lambda_0)$,*

$$\frac{1}{n}\sum_{k=1}^{n} L_{\mathcal{D}}^{0-1}(\boldsymbol{W}^k) \leq \widetilde{\mathcal{O}}[\frac{(\mathscr{C}^*)^2}{n}] + \mathcal{O}(\frac{\log(1/\delta)}{n}).$$

However, when $d \to \infty$, λ_0 can be very large for some input distribution. But in fact the dependence of λ_0 in [Cao and Gu, 2019, Arora et al., 2019] is due to the matrix perturbation. If we consider approximating $F^*(x_i) + \epsilon$ with ϵ is nonzero but small rather than $F^*(x_i)$, the dependence of λ_0 will not be necessary. Instead, we require $m > m^*(\mathscr{C}^*) \geq poly(\mathscr{C}^*)$.

4 Sketch Proof of the Main Theorem

The first step to prove the main theorem 2 is the following generalization of Corollary 3.10 in [Cao and Gu, 2019].

Theorem 3 *Under the condition of Theorem 2, let n samples in the training set be $\{x_i, y_i\}_{i=1}^{n}$. $\widetilde{y} = [F^*(x_1), F^*(x_2), ...F^*(x_n)]^T$. Let $\boldsymbol{H}$ be a matrix with $H_{i,j} = \frac{1}{m}\langle \nabla_{\widetilde{W}} f(\widetilde{\boldsymbol{W}}, x_i), \nabla_{\widetilde{W}} f(\widetilde{\boldsymbol{W}}, x_j)\rangle$. The entries of $\widetilde{\boldsymbol{W}}$ are i.i.d. generated from $N(0, \frac{2}{m})$. If there is a matrix $\boldsymbol{H}^\infty \in \mathbb{R}^{n \times n}$ satisfying*

$$\boldsymbol{H} + \boldsymbol{\epsilon}^T\boldsymbol{\epsilon} \succeq \boldsymbol{H}^\infty \text{ with } ||\boldsymbol{\epsilon}||_F \leq 0.01/\mathcal{O}(\mathscr{C}^*), \tag{18}$$

and $\sqrt{\widetilde{y}^T(\boldsymbol{H}^\infty)^{-1}\widetilde{y}} \leq \mathcal{O}(\mathscr{C}^*)$, there exits $m^*(n, \delta^{-1}, L, \mathscr{C}^*) = poly(n, \delta^{-1}, L, \mathscr{C}^*)$ such that, with probability at least $1 - \delta$, if $m > m^*$,

$$\frac{1}{n}\sum_{k=1}^{n} L_{\mathcal{D}}^{0-1}(\boldsymbol{W}^k) \leq \widetilde{\mathcal{O}}[\frac{\widetilde{y}^T(\boldsymbol{H}^\infty)^{-1}\widetilde{y}}{n}] + \mathcal{O}(\frac{\log(1/\delta)}{n}). \tag{19}$$

Remark 4.1 *In order to show Theorem 2 using this theorem, we need to carefully pick out the exponential parts of L. Using the methods in [Allen-Zhu et al., 2019c] and [Cao and Gu, 2019], we can show that $m^*(L, n, \sqrt{\widetilde{y}^T(\boldsymbol{H}^\infty)^{-1}\widetilde{y}}) \geq poly(n, L, \sqrt{\widetilde{y}^T(\boldsymbol{H}^\infty)^{-1}\widetilde{y}})$ is enough. $\sqrt{\widetilde{y}^T(\boldsymbol{H}^\infty)^{-1}\widetilde{y}}$ is dealt with by calculating the forward and backward correlation in section 4.1.1 and 4.1.2.*

The proof of theorem 3 is in fact a combination of the results in [Cao and Gu, 2019] and [Allen-Zhu et al., 2019c]. The really matter thing is how large can $\sqrt{\widetilde{y}^T(\boldsymbol{H}^\infty)^{-1}\widetilde{y}}$ be. We can show that:

Theorem 4 *Under the condition of Theorem 3, with probability at least $1 - \delta$, there exits matrix $\boldsymbol{H}^\infty$ satisfying (18) and*

$$\sqrt{\widetilde{y}^T(\boldsymbol{H}^\infty)^{-1}\widetilde{y}} \leq \mathcal{O}(\mathscr{C}^*). \tag{20}$$

Theorem 2 is a direct corollary of the above two theorems.

4.1 Calculation on Kernel Matrix

The proof of (20) relies on a direct calculation to construct a kernel matrix $\boldsymbol{H}^\infty$. We consider two input x_i and x_j. Let $X_{i,l}$ and $X_{j,l}$ be the $l-th$ input of x_i and x_j. Let $D_l \in \mathbb{R}^{m \times m}$ and $D'_l \in \mathbb{R}^{m \times m}$ be diagonal matrices that,

$$(D_l)_{k,k} = \mathbb{1}\{\boldsymbol{W}h_{l-1}(x_i) + \boldsymbol{A}X_{i,l} > 0\}$$
$$(D'_l)_{k,k} = \mathbb{1}\{\boldsymbol{W}h_{l-1}(x_j) + \boldsymbol{A}X_{j,l} > 0\} \tag{21}$$

$$\text{Back}_l = BD_L W \cdots D_{l+1}W, \text{Back}'_l = BD'_L W \cdots D'_{l+1}W \tag{22}$$

Then

$$\frac{1}{m}\langle \nabla_{\widetilde{W}} f(\widetilde{\boldsymbol{W}}, x_i), \nabla_{\widetilde{W}} f(\widetilde{\boldsymbol{W}}, x_j)\rangle = \frac{1}{m}\sum_{l,l'}\langle \text{Back}_l(x_i) \cdot D_l, \text{Back}_{l'}(x_j) \cdot D'_{l'}\rangle \cdot \langle h_l(x_i), h_{l'}(x_j)\rangle$$

$$\tag{23}$$

Generally $H_{i,j} = \frac{1}{m}\langle \nabla_{\widetilde{W}} f(\widetilde{\boldsymbol{W}}, x_i), \nabla_{\widetilde{W}} f(\widetilde{\boldsymbol{W}}, x_j)\rangle$ is hard to deal with. However, in the $m \to \infty$ limit, we can use some techniques to do the calculation.

4.1.1 Forward Correlation

Theorem 5 *For fixed i, j, under the condition in Theorem 3, with probability at least $1 - exp(-\Omega(\log^2 m))$,*

$$|\langle h_l(x_i), h_l(x_j)\rangle - K^l_{i,j}| \leq \mathcal{O}(l^2 \cdot \log^2 m/m) \tag{24}$$

And let $Q_l = \sqrt{(1 + \frac{1}{L^3}\sum_{k=1}^l ||X_{i,k}||^2) \cdot (1 + \frac{1}{L^3}\sum_{k=1}^l ||X_{j,k}||^2)}$,

$$K^1_{i,j} = Q_1 \cdot \sum_{r=0}^\infty \mu_r^2[(1 + \frac{1}{L^3}X_{i,1}^T X_{j,1})/Q_1]^r$$

$$K^l_{i,j} = Q_l \cdot \sum_{r=0}^\infty \mu_r^2(\{\frac{1}{L^3}X_{i,l}^T X_{j,l} + K^{l-1}_{i,j}\}/Q_l)^r \tag{25}$$

In the above equations, $\mu_r = \frac{1}{\sqrt{2\pi}}\int_0^\infty \sqrt{2}xh_r(x)e^{-\frac{x^2}{2}}dx$, $h_r(x) = \frac{1}{\sqrt{r!}}(-1)^r e^{\frac{x^2}{2}}\frac{d^r}{dx^r}e^{-\frac{x^2}{2}}$.

4.1.2 Backward Correlation

Theorem 6 *For $l \neq l'$, with probability at least $1 - exp(-\Omega(\log^2 m))$,*

$$|\frac{1}{m}\langle Back_l(x_i) \cdot D_l, Back_{l'}(x_j) \cdot D'_{l'}\rangle| \leq \mathcal{O}(\frac{L^4 \log^4 m}{m^{1/4}}). \tag{26}$$

For $l = l'$, there is $F^l_{i,j}$ that, with probability at least $1 - exp(-\Omega(\log^2 m))$,

$$|\frac{1}{m}\langle Back_l(x_i) \cdot D_l, Back_l(x_j) \cdot D'_{l'}\rangle - F^l_{i,j}| \leq \mathcal{O}(\frac{L^4 \log^4 m}{m^{1/4}}). \tag{27}$$

where

$$\Sigma(x) = \frac{1}{2} + \frac{arcsin(x)}{\pi}, \tag{28}$$

$$F^l_{i,j} \succeq \frac{1}{K}\Sigma(\{\frac{1}{L^3}\langle X_{i,l}, X_{j,l}\rangle + K^{l-1}_{i,j}\}/Q_l). \tag{29}$$

and $0 < K \leq \mathcal{O}(1/L^4)$.

Remark 4.2 *We should note that this theorem is one of the key differences between this work and the methods in [Allen-Zhu and Li, 2019a]. In fact, we must show that there is a constant $K > 0$ such that $\frac{1}{m}\langle Back_l(x_i), Back_l(x_j)\rangle - K$ is still positive definite. However, is K large enough thus $1/K \geq poly(L)$ rather than $1/K \leq exp(-\Omega(L))$? This is not a trivial question. One can only get $K \geq \frac{1}{2^L}$ using naive estimation. In[Allen-Zhu and Li, 2019a], $||\boldsymbol{A}X_l|| \leq \epsilon_x$ is required to make*

208 *sure $Back'_l = Back_l(x_i) - Back_l(x_j)$ samll. However after k steps of training, we can show the*
209 *approximation error is roughly $\mathcal{O}(||Back'||\cdot||\boldsymbol{W}^k-\boldsymbol{W}^0||)$ and $||\boldsymbol{W}^k-\boldsymbol{W}^0||_F \sim \sqrt{\widetilde{y}^T(\boldsymbol{H}^\infty)^{-1}\widetilde{y}} \sim$*
210 *$\mathscr{C}(F^*)$. Thus the dependence of ϵ_x on $\mathscr{C}(F^*)$ is hard to be dealt with using this method. In this*
211 *paper, we do not need the normalized condition. Our methods rely on a crucial observation that the*
212 *function $\lim_{l\to\infty} h_l(x_i)^T h_l(x_j)/(||h_l(x_i)|| \cdot ||h_l(x_j)||)$ will degenerate to a constant function.*

4.1.3 Sketch Proof of Theorem 4

214 In order to estimate the complexity, we use the results in the last subsection and Proposition 2.4,2.2
215 and 2.3.

216 Proposition 2.4 shows that, in order to estimate $\sqrt{\widetilde{y}^T(\boldsymbol{H}^\infty)^{-1}\widetilde{y}}$, we need to show

$$\boldsymbol{H}^\infty \succeq \xi_p \cdot (\boldsymbol{X}_l^T \boldsymbol{X}_l)^{\circ p} \tag{30}$$

217 with $\xi_p > 0$ for all $p \in \mathbb{N}, 1 \leq l \leq L$. Here $\boldsymbol{X}_l \in \mathbb{R}^{n \times d} = [X_{1,l}, X_{2,l}...X_{n,l}]$ and

$$[(\boldsymbol{X}_l^T \boldsymbol{X}_l)^{\circ p}]_{i,j} = \{X_{i,l}^T X_{j,l}\}^p. \tag{31}$$

218 We will show that, there is a matrix H^∞. With probability at least $1 - \delta$, $H_{ij} = H_{ij}^\infty \pm \mathcal{O}(\frac{L^4 \log^4 m}{m^{1/4}})$
219 for all $i,j \in [n]$, and,

$$H_{i,j}^\infty \succeq \frac{1}{\mathcal{O}(L^4)} \cdot Q_l \Sigma(\{\frac{1}{L^3}\langle X_{i,l}, X_{j,l}\rangle + K_{i,j}^{l-1}\}/Q_l). \tag{32}$$

220 for all l. Based on (32), we have the following results:

221 For all $1 \leq l \leq L$ and all k

$$H_{i,j}^\infty \succeq \frac{1}{\mathcal{O}(L^4)}\Sigma(\{K_{i,j}^l + \frac{1}{L^3}X_{i,l}^T X_{j,l}\}/Q_l) \succeq \Omega(\frac{1}{L^6}) \cdot (\frac{1}{\mathcal{O}(L)})^k \cdot \frac{1}{k^2}(X_{i,l}^T X_{j,l})^k/(||X_{i,l}||\cdot||X_{j,l}||)^k. \tag{33}$$

222 This deduces the complexity for the Additive Concept Class in section 2.1,

$$\sqrt{\widetilde{y}^T(\boldsymbol{H}^\infty)^{-1}\widetilde{y}} \leq \mathcal{O}(\mathscr{C}^*). \tag{34}$$

223 As for N-Variables Concept Class,

$$\begin{aligned}
H_{i,j}^\infty \succeq &\frac{1}{C_1^N L^4 \cdot L^{2N} \cdot C_{N,p} \cdot (p/N)^N} \\
&\cdot (X_{i,r_1}^T X_{j,r_1} + X_{i,r_2}^T X_{j,r_2}... + X_{i,r_N}^T X_{j,r_N})^p/(N \cdot \max_n(||X_{i,r_n}||) \cdot \max_n(||X_{j,r_n}||))^p
\end{aligned} \tag{35}$$

224 with some large constant $C_1 > 0$. Meanwhile, for any $l \leq L, a < l$, let $Z_i^{l,a} = X_{i,l} + X_{i,l-1} + ... +$
225 $X_{i,l-a}$. We have:

$$H_{i,j}^\infty \succeq \Omega(\frac{1}{L^6}) \cdot (\frac{1}{\mathcal{O}(L)})^k \cdot \frac{1}{k^2}(Z_{i,l}^T Z_{j,l})^k/(||Z_{i,l}|| \cdot Z_{j,l}|| \cdot 2^a)^k \tag{36}$$

226 Then from definition of complexity in section 2.2 and Proposition 2.4, we can prove

$$\sqrt{\widetilde{y}^T(\boldsymbol{H}^\infty)^{-1}\widetilde{y}} \leq \mathcal{O}(\mathscr{C}^*). \tag{37}$$

227 Therefore (20) follows.

5 Related Work

229 **Overparameterized neural network.** In [Tian, 2017] and [Du et al., 2018], it is shown that, for a
230 single-hidden-node ReLU network, under mild assumptions, the loss function is one point convex
231 in a very large area. However, in [Safran and Shamir, 2018], the authors pointed out that such good
232 properties are rare for networks with multi-hidden nodes, and indicated that an over-parameterization

assumption is necessary. Similarly, [Hardt et al., 2016] showed that over-parameterization can help in the training process of a linear dynamic system i.e., linear RNN. A different way to show over-parameterization is important as in [Freeman and Bruna, 2016], this work proved that in the two-layer case if the number of the hidden nodes is large enough, the sub-level sets of the loss will be nearly connected. Their method can also be applied to deep networks with a skip connection in [Wang et al., 2020] to study the properties of loss surfaces.

Recent breakthroughs were made in understanding the neural tangent kernel(NTK)[Jacot et al., 2018] of the neural network near the area of the random initialization. In [Li and Liang, 2018], [Du et al., 2019], [Allen-Zhu et al., 2019b] and [Allen-Zhu et al., 2019c], it is shown that deep networks with a large hidden size can attain zero training error, under some assumptions of input non-degeneracy. This explains the empirical results[Zhang et al., 2017] that DNN can fit training data with even random labels.

There are also some provable convergence results with over-parameterization going beyond NTK. The loss surface of the two-layer over-parameterized network with quadratic activation function was studied in [Du and Lee, 2018] and [Mahdi et al., 2018]. They showed that all the bad local minima are eliminated by over-parameterization. For ReLU activation function, in [Allen-Zhu and Li, 2019b], it is shown that there exits some functions can not be learned by any kernel functions but learnable with less error by a network with a skip connection. [Li et al., 2020] provided a convergence result for learning a specific two-layer neural network which can not be learned by any kernel method, including Neural Tangent Kernel.

Generalization of Deep Learning. Classical VC theory cannot explain the generalization ability of deep learning because the VC-dimension of neural networks is at least linear in the number of parameters [Bartlett et al., 2019]. Recently, [Allen-Zhu et al., 2019a] showed that overparameterized neural networks can learn some notable concept classes of target functions with rich types. Moreover, their work goes beyond the NTK linearization and provides new results on the non-convex interactions of the three-layer network. Meanwhile, [Arora et al., 2019] provided a fine-grained analysis on the generalization error and showed the connections to the matrix of the neural tangent kernel. The results were generalized to the multi-layer case in [Cao and Gu, 2019]. Following the method in [Allen-Zhu et al., 2019a], [Allen-Zhu and Li, 2019a] generalized the generalization results to RNN network to learn functions like $F^*(x) = \sum_l \sum_r \psi_{l,r}(\beta_{l,r}^T X_l)$. Previous work [Zhang et al., 2018, Chen et al., 2020a] requires sample complexity exponentially grows in the input size L. In [Allen-Zhu and Li, 2019a], the complexity of sampling and learning are polynomial in the input size L. Yet this work requires a normalized condition $||X_l|| \leq \epsilon_x$. To learn a function $F^*(x)$ with complexity C', it is learnable with error $O(\epsilon)$. Thus $||X_l|| \leq \mathcal{O}(\frac{\epsilon^{1/3}}{L^4 C'^3})$ should be very small to learn very complex functions.

6 Conclusion and Future Work

In this paper, we studied the problem of what type of function can be learned by RNN. In this work, we showed that RNN can provably learn the two types of functions, the additive concept class and the N-variables concept class in *almost-polynomial in input length many iterations and samples* starting from random initialization. For the additive concept class, we proved the result without the normalized condition and showed the almost-polynomial complexity in input length L. For the N-variable concept class, we showed that RNN with ReLU activation function can provably learn functions like $\psi(\langle \beta, [X_{l_1}, ..., X_{l_N}] \rangle)$. The complexity of learning such functions grows exponentially with either N or $l_0 = \max(l_1, ...l_N) - \min(l_1, ...l_N)$, but when one of them is small, the complexity is almost-polynomial in the input length L.

One of the limitations is that this work relies on the NTK linearization of RNN. One probably direction is to consider the non-convex interactions in RNN and learn more complex functions using the method in[Allen-Zhu et al., 2019a]. Meanwhile, this work studied RNN with ReLU activation function. This did not consider the "gate" structure in RNN. We believe that a study on GRU, LSTM, and MGU may lead to learning more complex functions with long-term memory.

References

[Allen-Zhu and Li, 2019a] Allen-Zhu, Z. and Li, Y. (2019a). Can sgd learn recurrent neural networks with provable generalization? In *Advances in Neural Information Processing Systems*, volume 32. Curran Associates, Inc.

[Allen-Zhu and Li, 2019b] Allen-Zhu, Z. and Li, Y. (2019b). What can resnet learn efficiently, going beyond kernels? In *Advances in Neural Information Processing Systems*, volume 32. Curran Associates, Inc.

[Allen-Zhu et al., 2019a] Allen-Zhu, Z., Li, Y., and Liang, Y. (2019a). Learning and generalization in overparameterized neural networks, going beyond two layers. In *Advances in Neural Information Processing Systems*, volume 32. Curran Associates, Inc.

[Allen-Zhu et al., 2019b] Allen-Zhu, Z., Li, Y., and Song, Z. (2019b). A convergence theory for deep learning via over-parameterization. In Chaudhuri, K. and Salakhutdinov, R., editors, *Proceedings of the 36th International Conference on Machine Learning, ICML 2019, 9-15 June 2019, Long Beach, California, USA*, volume 97 of *Proceedings of Machine Learning Research*, pages 242–252. PMLR.

[Allen-Zhu et al., 2019c] Allen-Zhu, Z., Li, Y., and Song, Z. (2019c). On the convergence rate of training recurrent neural networks. In *Advances in Neural Information Processing Systems*, volume 32. Curran Associates, Inc.

[Arora et al., 2019] Arora, S., Du, S. S., Hu, W., Li, Z., and Wang, R. (2019). Fine-grained analysis of optimization and generalization for overparameterized two-layer neural networks. In Chaudhuri, K. and Salakhutdinov, R., editors, *Proceedings of the 36th International Conference on Machine Learning, ICML 2019, 9-15 June 2019, Long Beach, California, USA*, volume 97 of *Proceedings of Machine Learning Research*, pages 322–332. PMLR.

[Bartlett et al., 2019] Bartlett, P. L., Harvey, N., Liaw, C., and Mehrabian, A. (2019). Nearly-tight vc-dimension and pseudodimension bounds for piecewise linear neural networks. *J. Mach. Learn. Res.*, 20:63:1–63:17.

[BergJens et al., 1984] BergJens, C., Reus, P., and Ressel, C. (1984). *Harmonic Analysis on Semi-groups Theory of Positive Definite and Related Functions*. Springer Netherlands.

[Boucheron et al., 2013] Boucheron, S., Lugosi, G., and Massart, P. (2013). *Concentration inequalities : a non asymptotic theory of independence*. Oxford University Press.

[Cao and Gu, 2019] Cao, Y. and Gu, Q. (2019). Generalization bounds of stochastic gradient descent for wide and deep neural networks. In *Advances in Neural Information Processing Systems*, volume 32. Curran Associates, Inc.

[Chen et al., 2020a] Chen, M., Li, X., and Zhao, T. (2020a). On generalization bounds of a family of recurrent neural networks. In Chiappa, S. and Calandra, R., editors, *The 23rd International Conference on Artificial Intelligence and Statistics, AISTATS 2020, 26-28 August 2020, Online [Palermo, Sicily, Italy]*, volume 108 of *Proceedings of Machine Learning Research*, pages 1233–1243. PMLR.

[Chen et al., 2020b] Chen, Z., Cao, Y., Zou, D., and Gu, Q. (2020b). How much over-parameterization is sufficient to learn deep relu networks?

[Daniely et al., 2016] Daniely, A., Frostig, R., and Singer, Y. (2016). Toward deeper understanding of neural networks: The power of initialization and a dual view on expressivity. In Lee, D., Sugiyama, M., Luxburg, U., Guyon, I., and Garnett, R., editors, *Advances in Neural Information Processing Systems*, volume 29. Curran Associates, Inc.

[Du and Lee, 2018] Du, S. S. and Lee, J. D. (2018). On the power of over-parametrization in neural networks with quadratic activation. *International conference on machine learning*, pages 1328–1337.

[Du et al., 2018] Du, S. S., Lee, J. D., and Tian, Y. (2018). When is a convolutional filter easy to learn. *International conference on machine learning*.

[Du et al., 2019] Du, S. S., Zhai, X., Poczos, B., and Singh, A. (2019). Gradient descent provably optimizes over-parameterized neural networks. In *7th International Conference on Learning Representations, ICLR 2019, New Orleans, LA, USA, May 6-9, 2019*. OpenReview.net.

[Freeman and Bruna, 2016] Freeman, C. D. and Bruna, J. (2016). Topology and geometry of half-rectified network optimization. *International conference on machine learning*.

[Ge et al., 2017] Ge, R., Lee, J. D., and Ma, T. (2017). Learning one-hidden-layer neural networks with landscape design. *CoRR*, abs/1711.00501.

[Hardt et al., 2016] Hardt, M., Ma, T., and Recht, B. (2016). Gradient descent learns linear dynamical systems. *Journal of Machine Learning Research*, 19.

[Huang et al., 2020] Huang, K., Wang, Y., Tao, M., and Zhao, T. (2020). Why do deep residual networks generalize better than deep feedforward networks? - A neural tangent kernel perspective. In *Advances in Neural Information Processing Systems 33: Annual Conference on Neural Information Processing Systems 2020, NeurIPS 2020, December 6-12, 2020, virtual*.

[Jacot et al., 2018] Jacot, A., Gabriel, F., and Hongler, C. (2018). Neural tangent kernel: Convergence and generalization in neural networks. In Bengio, S., Wallach, H., Larochelle, H., Grauman, K., Cesa-Bianchi, N., and Garnett, R., editors, *Advances in Neural Information Processing Systems*, volume 31. Curran Associates, Inc.

[Ji and Telgarsky, 2020] Ji, Z. and Telgarsky, M. (2020). Polylogarithmic width suffices for gradient descent to achieve arbitrarily small test error with shallow relu networks.

[Li and Liang, 2018] Li, Y. and Liang, Y. (2018). Learning overparameterized neural networks via stochastic gradient descent on structured data. In Bengio, S., Wallach, H., Larochelle, H., Grauman, K., Cesa-Bianchi, N., and Garnett, R., editors, *Advances in Neural Information Processing Systems*, volume 31. Curran Associates, Inc.

[Li et al., 2020] Li, Y., Ma, T., and Zhang, H. R. (2020). Learning over-parametrized two-layer relu neural networks beyond ntk.

[Mahdi et al., 2018] Mahdi, S., Adel, J., and D., L. J. (2018). Theoretical insights into the optimization landscape of over-parameterized shallow neural networks. *IEEE Transactions on Information Theory*.

[Safran and Shamir, 2018] Safran, I. and Shamir, O. (2018). Spurious local minima are common in two-layer relu neural networks. *International conference on machine learning*, pages 4430–4438.

[Tian, 2017] Tian, Y. (2017). Symmetry-breaking convergence analysis of certain two-layered neural networks with relu nonlinearity. *International conference on learning representations*.

[Wang et al., 2020] Wang, L., Shen, B., Zhao, N., and Zhang, Z. (2020). Is the skip connection provable to reform the neural network loss landscape? In Bessiere, C., editor, *Proceedings of the Twenty-Ninth International Joint Conference on Artificial Intelligence, IJCAI-20*, pages 2792–2798. International Joint Conferences on Artificial Intelligence Organization. Main track.

[Zhang et al., 2017] Zhang, C., Bengio, S., Hardt, M., Recht, B., and Vinyals, O. (2017). Understanding deep learning requires rethinking generalization. In *5th International Conference on Learning Representations, ICLR 2017, Toulon, France, April 24-26, 2017, Conference Track Proceedings*. OpenReview.net.

[Zhang et al., 2018] Zhang, J., Lei, Q., and Dhillon, I. S. (2018). Stabilizing gradients for deep neural networks via efficient SVD parameterization. In Dy, J. G. and Krause, A., editors, *Proceedings of the 35th International Conference on Machine Learning, ICML 2018, Stockholmsmässan, Stockholm, Sweden, July 10-15, 2018*, volume 80 of *Proceedings of Machine Learning Research*, pages 5801–5809. PMLR.